

Open Source Used In talos_crawl-api-go main-git-d1ea1d4-78

Cisco Systems, Inc.
www.cisco.com

Cisco has more than 200 offices worldwide.
Addresses, phone numbers, and fax numbers
are listed on the Cisco website at
www.cisco.com/go/offices.

Text Part Number: 78EE117C99-2574420951

This document contains licenses and notices for open source software used in this product. With respect to the free/open source software listed in this document, if you have any questions or wish to receive a copy of any source code to which you may be entitled under the applicable free/open source license(s) (such as the GNU Lesser/General Public License), please submit this form.

In your requests please include the following reference number 78EE117C99-2574420951

Contents

1.1 lz4 1.9.3
1.1.1 Available under license
1.2 zlib 1.3.1
1.2.1 Available under license
1.3 golang 1.24.4
1.3.1 Available under license
1.4 zstd 1.3.1
1.4.1 Available under license
1.5 librdkafka 2.10.0-r0
1.5.1 Notifications
1.5.2 Available under license
1.6 openssl 3.0.15
1.6.1 Available under license
1.7 curl 8.14.1-r2
1.7.1 Available under license
1.8 github.com/aws/aws-sdk-go-v2/service/ssooidc 1.32.0
1.8.1 Available under license
1.9 github.com/golang-jwt/jwt/v5 5.3.0
1.9.1 Available under license
1.10 utmps-libs 0.1.2.3-r2
1.10.1 Available under license
1.11 aws-sdk-go-v2-service-internal-endpoint-discovery 1.11.2
1.11.1 Available under license
1.12 ncurses 6.5_p20241006-r3
1.12.1 Available under license
1.13 universal-translator 0.18.1

1.13.1 Available under license
1.14 x-sync 0.16.0
1.14.1 Available under license
1.15 goautoneg 0.0.0-20191010083416-a7dc8b61c822
1.15.1 Available under license
1.16 intern 1.0.0
1.16.1 Available under license
1.17 aws-sdk-go-v2-internal-configsources 1.4.2
1.17.1 Available under license
1.18 golang-lru 2.0.7
1.18.1 Available under license
1.19 alpine-keys 2.5-r0
1.19.1 Available under license
1.20 shadow 4.16.0-r1
1.20.1 Available under license
1.21 swaggo-swag 1.16.6
1.21.1 Available under license
1.22 github.com/swaggo/http-swagger 1.3.4
1.22.1 Available under license
1.23 confluentinc-confluent-kafka-go 2.11.0
1.23.1 Available under license
1.24 github.com/aws/aws-sdk-go-v2/internal/configsources 1.4.2
1.24.1 Available under license
1.25 aws-sdk-go-v2-aws-protocol-eventstream 1.7.0
1.25.1 Available under license
1.26 github.com/aws/aws-sdk-go-v2/service/internal/endpoint-discovery 1.11.2
1.26.1 Available under license
1.27 github.com/aws/smithy-go 1.22.5
1.27.1 Available under license
1.28 perks 1.0.1
1.28.1 Available under license
1.29 github.com/aws/aws-sdk-go-v2/service/internal/accept-encoding 1.13.0
1.29.1 Available under license
1.30 zgo.at/zcache/v2 2.2.0
1.30.1 Available under license
1.31 scanelf 1.3.8-r1
1.31.1 Available under license
1.32 github.com/aws/aws-sdk-go-v2/service/internal/presigned-url 1.13.2
1.32.1 Available under license

1.33 aws-sdk-go-v2-service-s3 1.86.0
1.33.1 Available under license
1.34 aws-sdk-go-v2-internal-endpoints 2.7.2
1.34.1 Available under license
1.35 aws-sdk-go-v2-service-dynamodbstreams 1.28.0
1.35.1 Available under license
1.36 utmps 0.1.2.3-r2
1.36.1 Available under license
1.37 go-playground-locales 0.14.1
1.37.1 Available under license
1.38 github.com/aws/aws-sdk-go-v2/service/internal/s3shared 1.19.2
1.38.1 Available under license
1.39 githubcomgoopenapispec 0.21.0
1.39.1 Available under license
1.40 jsonreference 0.21.0
1.40.1 Available under license
1.41 github.com/aws/aws-sdk-go-v2/config 1.30.3
1.41.1 Available under license
1.42 easyjson 0.9.0
1.42.1 Available under license
1.43 swaggo-http-swagger 1.3.4
1.43.1 Available under license
1.44 githubcomgoopenapiswag 0.23.1
1.44.1 Available under license
1.45 x-crypto 0.40.0
1.45.1 Available under license
1.46 libcap 2.71-r0
1.46.1 Available under license
1.47 logrus 1.9.3
1.47.1 Available under license
1.48 libssl3 3.3.4-r0
1.48.1 Available under license
1.49 protobuf 1.36.6
1.49.1 Available under license
1.50 pam 1.6.1-r1
1.50.1 Available under license
1.51 go-playground-universal-translator 0.18.1
1.51.1 Available under license
1.52 wojtekwanczyk-average 0.0.0-20240221125520-eb722bafaeb3

1.52.1 Available under license
1.53 apk-tools 2.14.6-r3
1.53.1 Available under license
1.54 github.com/aws/aws-sdk-go-v2/aws/protocol/eventstream 1.7.0
1.54.1 Available under license
1.55 asn1-ber 1.5.8-0.20250403174932-29230038a667
1.55.1 Available under license
1.56 aws-sdk-go-v2-service-internal-checksum 1.8.2
1.56.1 Available under license
1.57 github.com/aws/aws-sdk-go-v2/internal/v4a 1.4.2
1.57.1 Available under license
1.58 aws-sdk-go-v2-config 1.30.3
1.58.1 Available under license
1.59 locales 0.14.1
1.59.1 Available under license
1.60 protobuf-go 1.36.6
1.60.1 Available under license
1.61 readline 8.2.13-r0
1.61.1 Available under license
1.62 swag 0.23.1
1.62.1 Available under license
1.63 skalibs 2.14.3.0-r0
1.63.1 Available under license
1.64 github.com/aws/aws-sdk-go-v2/credentials 1.18.3
1.64.1 Available under license
1.65 stdlib go1.24.4
1.65.1 Available under license
1.66 github.com/aws/aws-sdk-go-v2/service/sts 1.36.0
1.66.1 Available under license
1.67 iputils-clockdiff 20240905-r0
1.67.1 Available under license
1.68 iputils-arping 20240905-r0
1.68.1 Available under license
1.69 kelseyhightower-envconfig 1.4.0
1.69.1 Available under license
1.70 aws-sdk-go-v2-feature-dynamodb-attributevalue 1.20.2
1.70.1 Available under license
1.71 libbsd 0.12.2-r0
1.71.1 Available under license

1.72 swaggo-files 1.0.1
1.72.1 Available under license
1.73 github.com/aws/aws-sdk-go-v2/service/s3 1.86.0
1.73.1 Available under license
1.74 google-uuid 1.6.0
1.74.1 Available under license
1.75 go-openapi-jsonpointer 0.21.1
1.75.1 Available under license
1.76 zgo.at-zcache 2.2.0
1.76.1 Available under license
1.77 github.com/aws/aws-sdk-go-v2/feature/s3/manager 1.18.3
1.77.1 Available under license
1.78 spec 0.21.0
1.78.1 Available under license
1.79 x-net 0.42.0
1.79.1 Available under license
1.80 github.com/aws/aws-sdk-go-v2/internal/ini 1.8.3
1.80.1 Available under license
1.81 go-urn 1.4.0
1.81.1 Available under license
1.82 githubcommailrueasyjson 0.9.0
1.82.1 Available under license
1.83 mod 0.26.0
1.83.1 Available under license
1.84 github.com/gabriel-vasile/mimetype 1.4.9
1.84.1 Available under license
1.85 busybox 1.37.0-r13
1.85.1 Available under license
1.86 musl 1.2.5-r9
1.86.1 Available under license
1.87 github.com/aws/aws-sdk-go-v2/internal/endpoints/v2 2.7.2
1.87.1 Available under license
1.88 depth 1.2.1
1.88.1 Available under license
1.89 github.com/hashicorp/golang-lru/v2 2.0.7
1.89.1 Available under license
1.90 aws-sdk-go-v2-service-internal-presigned-url 1.13.2
1.90.1 Available under license
1.91 pax-utils 1.3.8-r1

1.91.1 Available under license
1.92 githubcomgoopenapijsonreference 0.21.0
1.92.1 Available under license
1.93 aws-sdk-go-v2-feature-ec2-imds 1.18.2
1.93.1 Available under license
1.94 ldap 3.4.11
1.94.1 Available under license
1.95 aws-sdk-go-v2-service-sso 1.27.0
1.95.1 Available under license
1.96 aws-sdk-go-v2-internal-v4a 1.4.2
1.96.1 Available under license
1.97 x-tools 0.35.0
1.97.1 Available under license
1.98 swag 1.16.6
1.98.1 Available under license
1.99 github.com/aws/aws-sdk-go-v2/feature/dynamodb/attributevalue 1.20.2
1.99.1 Available under license
1.100 iputils-ping 20240905-r0
1.100.1 Available under license
1.101 x-mod 0.26.0
1.101.1 Available under license
1.102 tre 0.8.0-r2
1.102.1 Available under license
1.103 procfs 0.17.0
1.103.1 Available under license
1.104 github.com/swaggo/files 1.0.1
1.104.1 Available under license
1.105 yaml 3.0.1
1.105.1 Available under license
1.106 alpine-baselayout-data 3.6.8-r1
1.106.1 Available under license
1.107 github.com/aws/aws-sdk-go-v2/service/dynamodbstreams 1.28.0
1.107.1 Available under license
1.108 aws-sdk-go-v2-service-ssooidc 1.32.0
1.108.1 Available under license
1.109 libmd 1.1.0-r0
1.109.1 Available under license
1.110 github.com/aws/aws-sdk-go-v2/service/dynamodb 1.46.0
1.110.1 Available under license

1.111 go-yaml 3.0.1
1.111.1 Available under license
1.112 aws-sdk-go-v2-feature-s3-manager 1.18.3
1.112.1 Available under license
1.113 validator 10.27.0
1.113.1 Available under license
1.114 github.com/wojtekwanczyk/average 0.0.0-20240221125520-eb722bafaeb3
1.114.1 Available under license
1.115 prometheus-common 0.65.0
1.115.1 Available under license
1.116 go-ntlmssp 0.0.0-20221128193559-754e69321358
1.116.1 Available under license
1.117 x-text 0.27.0
1.117.1 Available under license
1.118 ssl-client 1.37.0-r13
1.118.1 Available under license
1.119 x-sys 0.34.0
1.119.1 Available under license
1.120 aws-sdk-go-v2 1.37.2
1.120.1 Available under license
1.121 iputils-tracepath 20240905-r0
1.121.1 Available under license
1.122 github.com/aws/aws-sdk-go-v2/feature/ec2/imds 1.18.2
1.122.1 Available under license
1.123 github.com/aws/aws-sdk-go-v2/service/internal/checksum 1.8.2
1.123.1 Available under license
1.124 openssl 3.3.4-r0
1.124.1 Available under license
1.125 alpine-release 3.21.4-r0
1.125.1 Available under license
1.126 smithy-go 1.22.5
1.126.1 Available under license
1.127 alpine-baselayout 3.6.8-r1
1.127.1 Available under license
1.128 mime-type 1.4.9
1.128.1 Available under license
1.129 libncursesw 6.5_p20241006-r3
1.129.1 Available under license
1.130 clientmodel 0.6.2

1.130.1 Available under license
1.131 musl-utils 1.2.5-r9
1.131.1 Available under license
1.132 ca-certificates 20250619-r0
1.132.1 Available under license
1.133 libcrypto3 3.3.4-r0
1.133.1 Notifications
1.133.2 Available under license
1.134 github.com/aws/aws-sdk-go-v2/service/sso 1.27.0
1.134.1 Available under license
1.135 skalibs-libs 2.14.3.0-r0
1.135.1 Available under license
1.136 busybox 1.37.0-r14
1.136.1 Available under license
1.137 github.com/go-asn1-ber/asn1-ber 1.5.8-0.20250403174932-29230038a667
1.137.1 Available under license
1.138 bash 5.2.37-r0
1.138.1 Available under license
1.139 common 0.65.0
1.139.1 Available under license
1.140 github.com/confluentinc/confluent-kafka-go/v2 2.11.0
1.140.1 Available under license
1.141 aws-sdk-go-v2-credentials 1.18.3
1.141.1 Available under license
1.142 github.com/go-ldap/ldap/v3 3.4.11
1.142.1 Available under license
1.143 aws-sdk-go-v2-service-sts 1.36.0
1.143.1 Available under license
1.144 github.com/google/uuid 1.6.0
1.144.1 Available under license
1.145 ca-certificates-bundle 20250619-r0
1.145.1 Available under license
1.146 alpine-base 3.21.4-r0
1.146.1 Available under license
1.147 githubcomgoopenapijsonpointer 0.21.1
1.147.1 Available under license
1.148 zlib 1.3.1-r2
1.148.1 Available under license
1.149 aws-sdk-go-v2-service-dynamodb 1.46.0

1.149.1 Available under license
1.150 aws-sdk-go-v2-service-internal-s3shared 1.19.2
1.150.1 Available under license
1.151 iputils 20240905-r0
1.151.1 Available under license
1.152 sirupsen-logrus 1.9.3
1.152.1 Available under license
1.153 cjson 1.7.19-r0
1.153.1 Notifications
1.153.2 Available under license
1.154 prometheus-client-model 0.6.2
1.154.1 Available under license
1.155 aws-sdk-go-v2-internal-ini 1.8.3
1.155.1 Available under license
1.156 xxhash 2.3.0
1.156.1 Available under license
1.157 golang-jwt 5.3.0
1.157.1 Available under license
1.158 prometheus-client 1.23.0
1.158.1 Available under license
1.159 aws-sdk-go-v2-service-internal-accept-encoding 1.13.0
1.159.1 Available under license

1.1 lz4 1.9.3

1.1.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by

the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed

under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this

License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for

making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot

distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of

this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this

is what you want to do, use the GNU Lesser General
Public License instead of this License.
Copyright (c) 2014, lpsantil
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
This repository uses 2 different licenses :
- all files in the `lib` directory use a BSD 2-Clause license
- all other files use a GPLv2 license, unless explicitly stated otherwise

Relevant license is reminded at the top of each source file,
and with presence of COPYING or LICENSE file in associated directories.

This model is selected to emphasize that
files in the `lib` directory are designed to be included into 3rd party applications,
while all other files, in `programs`, `tests` or `examples`,
receive more limited attention and support for such scenario.
LZ4 Library
Copyright (c) 2011-2016, Yann Collet
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this

list of conditions and the following disclaimer in the documentation and/or
other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Format: http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: liblz4
Upstream-Contact: Yann Collet <Cyan4973@github.com>
Source: https://github.com/lz4/lz4

Files: *
Copyright: (C) 2011-2020 Yann Collet
License: GPL-2+
The full text of license: https://github.com/lz4/lz4/blob/dev/lib/LICENSE

1.2 zlib 1.3.1

1.2.1 Available under license :

Copyright notice:

(C) 1995-2022 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
   claim that you wrote the original software. If you use this software
   in a product, an acknowledgment in the product documentation would be
   appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be
   misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu
/* zlib.h -- interface of the 'zlib' general purpose compression library
version 1.3.1, January 22nd, 2024

Copyright (C) 1995-2024 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
claim that you wrote the original software. If you use this software
in a product, an acknowledgment in the product documentation would be
appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be
misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu

The data format used by the zlib library is described by RFCs (Request for
Comments) 1950 to 1952 in the files http://tools.ietf.org/html/rfc1950
(zlib format), rfc1951 (deflate format) and rfc1952 (gzip format).
*/

Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization
obtaining a copy of the software and accompanying documentation covered by
this license (the "Software") to use, reproduce, display, distribute,
execute, and transmit the Software, and to prepare derivative works of the
Software, and to permit third-parties to whom the Software is furnished to
do so, all subject to the following:

The copyright notices in the Software and this entire statement, including
the above license grant, this restriction and the following disclaimer,
must be included in all copies of the Software, in whole or in part, and
all derivative works of the Software, unless such copies or derivative
works are solely in the form of machine-executable object code generated by
a source language processor.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT
SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE
FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER
DEALINGS IN THE SOFTWARE.
/* gzlib.c -- zlib functions common to reading and writing gzip files
* Copyright (C) 2004-2024 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/

1.3 golang 1.24.4

1.3.1 Available under license :

```
// Copyright 2024 The Go Authors. All rights reserved.
// Use of this source code is governed by a BSD-style
// license that can be found in the LICENSE file.

package copyright

import (
 "bytes"
 "internal/testenv"
 "io"
 "io/fs"
 "os"
 "path/filepath"
 "testing"
)

var copyright = []byte("Copyright")

var permitted = [][]byte{
 []byte("// Code generated by "),
 []byte("// Code generated from "),
 []byte("// Created by cgo -cdefs"),
 []byte("// DO NOT EDIT\n// generated by:"),
 []byte("// Empty assembly file"),
 []byte("// Generated using cgo"),
 []byte("// Original source:\n//\thttp://www.zorinaq.com/papers/md5-amd64.html"), // public domain crypto/md5
 []byte("// created by cgo -cdefs"),
 []byte("// go run mkasm.go"),
 []byte("// mkerrors"),
 []byte("// mksys"),
 []byte("// run\n// Code generated by"), // cmd/compile/internal/test/constFold_test.go
}
```

```
func TestCopyright(t *testing.T) {
 buf := make([]byte, 2048)
 filepath.WalkDir(filepath.Join(testenv.GOROOT(t), "src"), func(path string,
 d fs.DirEntry, err error) error {
  if d.IsDir() && (d.Name() == "testdata" || d.Name() == "vendor") {
   return filepath.SkipDir
  }
  switch filepath.Ext(d.Name()) {
  default:
   return nil
  case ".s", ".go":
   // check
  }

  f, err := os.Open(path)
  if err != nil {
   t.Error(err)
   return nil
  }
  defer f.Close()
  n, err := f.Read(buf)
  if err != nil && err != io.EOF {
   t.Error(err)
   return nil
  }
  b := buf[:n]
  if bytes.Contains(b, copyright) {
   return nil
  }
  for _, ok := range permitted {
   if bytes.HasPrefix(b, ok) {
    return nil
   }
  }
  t.Errorf("%s: missing copyright notice", path)
  return nil
 })
}
```

Copyright 2009 The Go Authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above

copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE
 FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
The Go source code and supporting files in this directory
are covered by the usual Go license (see ../../../../LICENSE).

When building with GOEXPERIMENT=boringcrypto, the following applies.

The goboringcrypto_linux_amd64.syso object file is built
from BoringSSL source code by build/build.sh and is covered
by the BoringSSL license reproduced below and also at
https://boringssl.googlesource.com/boringssl/+/fips-20220613/LICENSE.

BoringSSL is a fork of OpenSSL. As such, large parts of it fall under OpenSSL
licensing. Files that are completely new have a Google copyright and an ISC
license. This license is reproduced at the bottom of this file.

Contributors to BoringSSL are required to follow the CLA rules for Chromium:
https://cla.developers.google.com/clas

Some files from Intel are under yet another license, which is also included
underneath.

The OpenSSL toolkit stays under a dual license, i.e. both the conditions of the
OpenSSL License and the original SSLeay license apply to the toolkit.
 See below
for the actual license texts. Actually both licenses are BSD-style Open Source
licenses. In case of any license issues related to OpenSSL please contact
openssl-core@openssl.org.

The following are Google-internal bug numbers where explicit permission from
some authors is recorded for use of their work. (This is purely for our own

record keeping.)
27287199
27287880
27287883

OpenSSL License

/* ==
* Copyright (c) 1998-2011 The OpenSSL Project. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following
disclaimer in
*   the documentation and/or other materials provided with the
*   distribution.
*
* 3. All advertising materials mentioning features or use of this
*   software must display the following acknowledgment:
*   "This product includes software developed by the OpenSSL Project
*   for use in the OpenSSL Toolkit. (http://www.openssl.org/)"
*
* 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to
*   endorse or promote products derived from this software without
*   prior written permission. For written permission, please contact
*   openssl-core@openssl.org.
*
* 5. Products derived from this software may not be called "OpenSSL"
*   nor may "OpenSSL" appear in their names without prior written
*   permission of the OpenSSL Project.
*
* 6. Redistributions of any form whatsoever must retain the following
*   acknowledgment:
*   "This product includes software developed by the OpenSSL Project
*   for use in the OpenSSL Toolkit
(http://www.openssl.org/)"
*
* THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS'' AND ANY
* EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR

* ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
* LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
* STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
* OF THE POSSIBILITY OF SUCH DAMAGE.
* ==
*
* This product includes cryptographic software written by Eric Young
* (eay@cryptsoft.com). This product
 includes software written by Tim
* Hudson (tjh@cryptsoft.com).
*
*/

Original SSLeay License

/* Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)
* All rights reserved.
*
* This package is an SSL implementation written
* by Eric Young (eay@cryptsoft.com).
* The implementation was written so as to conform with Netscapes SSL.
*
* This library is free for commercial and non-commercial use as long as
* the following conditions are aheared to. The following conditions
* apply to all code found in this distribution, be it the RC4, RSA,
* lhash, DES, etc., code; not just the SSL code. The SSL documentation
* included with this distribution is covered by the same copyright terms
* except that the holder is Tim Hudson (tjh@cryptsoft.com).
*
* Copyright remains Eric Young's, and as such any Copyright notices in
* the code are not to be removed.
* If this package is used in a product, Eric Young should be given attribution
* as the author of
 the parts of the library used.
* This can be in the form of a textual message at program startup or
* in documentation (online or textual) provided with the package.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright

```
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software
*    must display the following acknowledgement:
*    "This product includes cryptographic software written by
*     Eric Young (eay@cryptsoft.com)"
*    The word 'cryptographic' can be left out if the rouines from the library
*    being used are
 not cryptographic related :-).
* 4. If you include any Windows specific code (or a derivative thereof) from
*    the apps directory (application code) you must include an acknowledgement:
*    "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"
*
* THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS" AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED.  IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
 POSSIBILITY OF
* SUCH DAMAGE.
*
* The licence and distribution terms for any publically available version or
* derivative of this code cannot be changed.  i.e. this code cannot simply be
* copied and put under another distribution licence
* [including the GNU Public Licence.]
*/
```

ISC license used for completely new code in BoringSSL:

```
/* Copyright (c) 2015, Google Inc.
*
* Permission to use, copy, modify, and/or distribute this software for any
* purpose with or without fee is hereby granted, provided that the above
* copyright notice and this permission notice appear in all copies.
*
* THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
* WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
* MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY
* SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
* WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION
* OF CONTRACT, NEGLIGENCE
```

OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN
* CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE. */

Some files from Intel carry the following license:

Copyright (c) 2012, Intel Corporation
#
All rights reserved.
#
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:
#
* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
#
* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the
distribution.
#
* Neither the name of the Intel Corporation nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.
#
#
THIS SOFTWARE IS PROVIDED BY INTEL CORPORATION
 ""AS IS"" AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTEL CORPORATION OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
People who have agreed to one of the CLAs and can contribute patches.
The AUTHORS file lists the copyright holders; this file
lists people. For example, Google employees are listed here
but not in AUTHORS, because Google holds the copyright.
#
https://developers.google.com/open-source/cla/individual
https://developers.google.com/open-source/cla/corporate
#
Names should be added to this file as:

Name <email address>
Raul Silvera <rsilvera@google.com>
Tipp Moseley <tipp@google.com>
Hyoun Kyu Cho <netforce@google.com>
Martin Spier <spiermar@gmail.com>
Taco de Wolff <tacodewolff@gmail.com>
Andrew Hunter <andrewhhunter@gmail.com>
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

                                 Apache License
                           Version 2.0, January 2004
                        http://www.apache.org/licenses/

   TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

   1. Definitions.

      "License" shall mean the terms and conditions for use, reproduction,
      and distribution as defined by Sections 1 through 9 of this document.

      "Licensor" shall mean the copyright owner or entity authorized by

the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but

excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the

appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Copyright (c) 2015 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright 2015 The Go Authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Copyright 2009-2017 Andrea Leofreddi <a.leofreddi@vleo.net>. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are
permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holder nor the names of its
   contributors may be used to endorse or promote products derived from
   this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY COPYRIGHT HOLDERS AND CONTRIBUTORS ``AS IS" AND ANY
EXPRESS
OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY
AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL COPYRIGHT HOLDERS OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED
AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN
IF
ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation are those of the
authors and should not be interpreted as representing official policies, either expressed
or implied, of Andrea Leofreddi.

1.4 zstd 1.3.1

1.4.1 Available under license :

BSD-style without advertising clause

1.5 librdkafka 2.10.0-r0

1.5.1 Notifications :

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/)
This product includes cryptographic software written by Eric Young (eay@cryptsoft.com).
This product includes software written by Tim Hudson (tjh@cryptsoft.com).

1.5.2 Available under license :

For the files wingetopt.c wingetopt.h downloaded from https://github.com/alex85k/wingetopt

/*
* Copyright (c) 2002 Todd C. Miller <Todd.Miller@courtesan.com>
*
* Permission to use, copy, modify, and distribute this software for any
* purpose with or without fee is hereby granted, provided that the above
* copyright notice and this permission notice appear in all copies.
*
* THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
* WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
* MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
* ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
* WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
* ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
* OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
*
* Sponsored in part by the Defense Advanced Research Projects
* Agency (DARPA) and Air Force Research Laboratory,
Air Force
* Materiel Command, USAF, under agreement number F39502-99-1-0512.
*/
/*-
* Copyright (c) 2000 The NetBSD Foundation, Inc.
* All rights reserved.
*
* This code is derived from software contributed to The NetBSD Foundation
* by Dieter Baron and Thomas Klausner.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright

* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
*
* THIS SOFTWARE IS PROVIDED BY THE NETBSD FOUNDATION, INC. AND CONTRIBUTORS
* ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE FOUNDATION OR CONTRIBUTORS
* BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
* POSSIBILITY OF SUCH DAMAGE.
*/
src/rdxxhash.[ch] src/lz4*.[ch]: git@github.com:lz4/lz4.git 5ff839680134437dbf4678f3d0c7b371d84f4964

LZ4 Library
Copyright (c) 2011-2020, Yann Collet
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this
list of conditions and the following disclaimer in the documentation and/or
other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
parts of src/rdfnv1a.c: http://www.isthe.com/chongo/src/fnv/hash_32a.c

Please do not copyright this code. This code is in the public domain.

LANDON CURT NOLL DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL LANDON CURT NOLL BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

By:
  chongo <Landon Curt Noll> /\oo/\
  http://www.isthe.com/chongo/

Share and Enjoy! :-)
regexp.c and regexp.h from https://github.com/ccxvii/minilibs sha 875c33568b5a4aa4fb3dd0c52ea98f7f0e5ca684

"
These libraries are in the public domain (or the equivalent where that is not possible). You can do anything you want with them. You have no legal obligation to do anything else, although I appreciate attribution.
"
FindZstd.cmake: git@github.com:facebook/folly.git 87f1a403b49552dae75ae94c8610dd5979913477

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership
of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including
but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object

form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate

as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a
readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications
and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for
reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed
to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if
You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS
For src/crc32c.c copied (with modifications) from
http://stackoverflow.com/a/17646775/1821055

/* crc32c.c -- compute CRC-32C using the Intel crc32 instruction
* Copyright (C) 2013 Mark Adler
* Version 1.1 1 Aug 2013 Mark Adler
*/

/*
This software is provided 'as-is', without any express or implied
warranty. In no event will the author be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
claim that you wrote the original software. If you use this software
in a product, an acknowledgment in the product documentation would be
appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be
misrepresented as being the original
software.
3. This notice may not be removed or altered from any source distribution.

Mark Adler
madler@alumni.caltech.edu
*/
For sys/queue.h:

* Copyright (c) 1991, 1993

* The Regents of the University of California. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 4. Neither the name of the University nor the names of its contributors
*   may be used to endorse or promote products derived from this software
*   without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES
 OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* @(#)queue.h 8.5 (Berkeley) 8/20/94
* $FreeBSD$
For cJSON.c and cJSON.h:

Copyright (c) 2009-2017 Dave Gamble and cJSON contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
LICENSE
---
librdkafka - Apache Kafka C driver library

Copyright (c) 2012-2022, Magnus Edenhill
2023, Confluent Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LICENSE.cjson

For cJSON.c and cJSON.h:

Copyright (c) 2009-2017 Dave Gamble and cJSON contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished
to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

LICENSE.crc32c

For src/crc32c.c copied (with modifications) from
http://stackoverflow.com/a/17646775/1821055

/* crc32c.c -- compute CRC-32C using the Intel crc32 instruction
* Copyright (C) 2013 Mark Adler
* Version 1.1 1 Aug 2013 Mark Adler
*/

/*
 This software is provided 'as-is',
 without any express or implied
 warranty. In no event will the author be held liable for any damages
 arising from the use of this software.

 Permission is granted to anyone to use this software for any purpose,
 including commercial applications, and to alter it and redistribute it
 freely, subject to the following restrictions:

 1. The origin of this software must not be misrepresented; you must not
    claim that you wrote the original software. If you use this software
    in a product, an acknowledgment in the product documentation would be
    appreciated but is not required.
 2. Altered source versions must be plainly marked as such, and must not be
    misrepresented as being the original software.
 3. This notice may not be removed or altered from any source distribution.

 Mark Adler
 madler@alumni.caltech.edu
*/

LICENSE.fnv1a

---

parts of src/rdfnv1a.c: http://www.isthe.com/chongo/src/fnv/hash_32a.c

Please
do not copyright this code. This code is in the public domain.

LANDON CURT NOLL DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL LANDON CURT NOLL BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

By:
chongo <Landon Curt Noll> /\oo/\
http://www.isthe.com/chongo/

Share and Enjoy! :-)

LICENSE.hdrhistogram

This license covers src/rdhdrhistogram.c which is a C port of
Coda Hale's Golang HdrHistogram https://github.com/codahale/hdrhistogram
at revision 3a0bb77429bd3a61596f5e8a3172445844342120

The MIT License
(MIT)

Copyright (c) 2014 Coda Hale

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE

LICENSE.lz4

---

src/rdxxhash.[ch] src/lz4*.[ch]: git@github.com:lz4/lz4.git 5ff839680134437dbf4678f3d0c7b371d84f4964

LZ4 Library
Copyright (c) 2011-2020, Yann Collet
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this
list of conditions and the following disclaimer in the documentation and/or
other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LICENSE.murmur2

---

parts of src/rdmurmur2.c: git@github.com:abrandoned/murmur2.git

MurMurHash2 Library
//---

// MurmurHash2 was written by Austin Appleby, and is placed in the public
// domain. The author hereby disclaims copyright to this source code.

Permission is hereby granted, free of charge, to any person

obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

LICENSE.nanopb

For
files in src/nanopb :
https://github.com/nanopb/nanopb/blob/8ef41e0ebd45daaf19459a011f67e66224b247cd/LICENSE.txt

Copyright (c) 2011 Petteri Aimonen <jpa at nanopb.mail.kapsi.fi>

This software is provided 'as-is', without any express or
implied warranty. In no event will the authors be held liable
for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any
purpose, including commercial applications, and to alter it and
redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you
must not claim that you wrote the original software. If you use
this software in a product, an acknowledgment in the product
documentation would be appreciated but is not required.

2. Altered source versions must be plainly marked as such, and
must not be misrepresented as being the original software.

3. This notice may
not be removed or altered from any source
distribution.

LICENSE.opentelemetry

For files in src/opentelemetry: https://github.com/open-telemetry/opentelemetry-proto/blob/81a296f9dba23e32d77f46d58c8ea4244a2157a6/LICENSE

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the

editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of

the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution
incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE
text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify

the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier

identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

LICENSE.pycrc

The following license applies to the files rdcrc32.c and rdcrc32.h which
have been generated by the pycrc tool.

==========

Copyright (c) 2006-2012, Thomas Pircher <tehpeh@gmx.net>

Permission is hereby granted,
free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

LICENSE.queue

For
sys/queue.h:

* Copyright (c) 1991, 1993
* The Regents of the University of California. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 4. Neither the name of the University nor the names of its contributors
* may be used to endorse or promote products derived from this software
* without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
* ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* @(#)queue.h 8.5 (Berkeley) 8/20/94
* $FreeBSD$

LICENSE.regexp

---

regexp.c and regexp.h from https://github.com/ccxvii/minilibs sha 875c33568b5a4aa4fb3dd0c52ea98f7f0e5ca684

"
These libraries are in the public domain (or the equivalent where that is not
possible). You can do anything you want with them. You have no legal obligation to do anything else, although I appreciate attribution.

"

LICENSE.snappy

```
################################################################################
# LICENSE.snappy covers files: snappy.c, snappy.h, snappy_compat.h   #
# originally retrieved from http://github.com/andikleen/snappy-c     #
# git revision 8015f2d28739b9a6076ebaa6c53fe27bc238d219              #
################################################################################
```

The snappy-c code is under the same license as the original snappy source

Copyright 2011 Intel Corporation All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions
 in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Intel Corporation nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING
 NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LICENSE.tinycthread

From https://github.com/tinycthread/tinycthread/README.txt c57166cd510ffb5022dd5f127489b131b61441b9

License

Copyright (c) 2012 Marcus Geelnard
2013-2014 Evan Nemerson

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
claim that you wrote the original software. If you use this software
in a product, an acknowledgment in the product documentation would be
appreciated but is not required.

2. Altered source versions must be plainly marked as such, and must not be
misrepresented as being the original software.

3. This notice may not be removed or altered from any source
distribution.

LICENSE.wingetopt

For the files wingetopt.c wingetopt.h downloaded from https://github.com/alex85k/wingetopt

/*
* Copyright (c) 2002 Todd C. Miller <Todd.Miller@courtesan.com>
*
* Permission to use, copy, modify, and distribute this software for any
* purpose with or without fee is hereby granted, provided that the above
* copyright notice and this permission notice appear in all copies.
*
* THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
* WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
* MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
* ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR
ANY DAMAGES
* WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
* ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
* OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
*
* Sponsored in part by the Defense Advanced Research Projects

* Agency (DARPA) and Air Force Research Laboratory, Air Force
* Materiel Command, USAF, under agreement number F39502-99-1-0512.
*/
/*-
* Copyright (c) 2000 The NetBSD Foundation, Inc.
* All rights reserved.
*
* This code is derived from software contributed to The NetBSD Foundation
* by Dieter Baron and Thomas Klausner.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice,
 this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
* THIS SOFTWARE IS PROVIDED BY THE NETBSD FOUNDATION, INC. AND CONTRIBUTORS
* ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE FOUNDATION OR CONTRIBUTORS
* BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
* POSSIBILITY OF SUCH DAMAGE.
*/
##
LICENSE.snappy covers files: snappy.c, snappy.h, snappy_compat.h
originally retrieved from http://github.com/andikleen/snappy-c
git revision 8015f2d28739b9a6076ebaa6c53fe27bc238d219
##

The snappy-c code is under the same license as the original snappy source

Copyright 2011 Intel Corporation All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Intel
Corporation nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
librdkafka - Apache Kafka C driver library

Copyright (c) 2012-2022, Magnus Edenhill
2023, Confluent Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

Format: http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: librdkafka
Source: https://github.com/confluentinc/librdkafka

License: BSD-2-clause
 Redistribution and use in source and binary forms, with or without
 modification, are permitted provided that the following conditions are met:
 .
 1. Redistributions of source code must retain the above copyright notice,
    this list of conditions and the following disclaimer.
 2. Redistributions in binary form must reproduce the above copyright notice,
    this list of conditions and the following disclaimer in the documentation
    and/or other materials provided with the distribution.
 .
 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
 AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
 ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
 LIABLE FOR
 ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
 CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
 SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
 INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
 CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
 ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
 POSSIBILITY OF SUCH DAMAGE.

Files: *
Copyright: 2012-2022, Magnus Edenhill; 2023, Confluent Inc.
License: BSD-2-clause

Files: src/rdcrc32.c src/rdcrc32.h
Copyright: 2006-2012, Thomas Pircher <tehpeh@gmx.net>
License: MIT
 Permission is hereby granted, free of charge, to any person obtaining a copy
 of this software and associated documentation files (the "Software"), to deal
 in the Software without restriction, including without limitation the rights
 to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
 copies of the Software, and to
 permit persons to whom the Software is
 furnished to do so, subject to the following conditions:
 .
 The above copyright notice and this permission notice shall be included in
 all copies or substantial portions of the Software.
 .
 THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
 IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
 FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Files: src/snappy.c src/snappy.h src/snappy_compat.h
Copyright: 2005, Google Inc.
2011, Intel Corporation
License: BSD-3-clause
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
.
* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.
.
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Files: src/rdxxhash.h src/rdxxhash.c
Copyright: 2012-2014, Yann Collet
License: BSD-2-clause

Files: src/regexp.h src/regexp.c
Copyright: n/a
License: public-domain

License: public-domain
The files tagged with this license contain the following paragraphs:
.
These libraries are in the public domain (or the equivalent where that is not

possible). You can do anything you want with them. You have no legal
obligation to do anything else, although I appreciate attribution.

Files: debian/*
Copyright: 2013 Faidon Liambotis <paravoid@debian.org>
License: BSD-2-clause
BSD-style without advertising clause
Copyright (c) 2016-2019, Magnus Edenhill
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
For files in src/nanopb :
https://github.com/nanopb/nanopb/blob/8ef41e0ebd45daaf19459a011f67e66224b247cd/LICENSE.txt

Copyright (c) 2011 Petteri Aimonen <jpa at nanopb.mail.kapsi.fi>

This software is provided 'as-is', without any express or
implied warranty. In no event will the authors be held liable
for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any
purpose, including commercial applications, and to alter it and
redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you
must not claim that you wrote the original software. If you use
this software in a product, an acknowledgment in the product
documentation would be appreciated but is not required.

2. Altered source versions must be plainly marked as such, and
must not be misrepresented as being the original software.

3. This notice may not be removed or altered from any source

distribution.
parts of src/rdmurmur2.c: git@github.com:abrandoned/murmur2.git

MurMurHash2 Library
//---
// MurmurHash2 was written by Austin Appleby, and is placed in the public
// domain. The author hereby disclaims copyright to this source code.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
Format: http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: librdkafka
Source: https://github.com/confluentinc/librdkafka

License: BSD-2-clause
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
.
1. Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.
.
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"

AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Files: *
Copyright: 2012-2022, Magnus Edenhill; 2023 Confluent Inc.
License: BSD-2-clause

Files: src/rdcrc32.c src/rdcrc32.h
Copyright: 2006-2012, Thomas Pircher <tehpeh@gmx.net>
License: MIT
Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit
persons to whom the Software is
furnished to do so, subject to the following conditions:
.
The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.
.
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Files: src/snappy.c src/snappy.h src/snappy_compat.h
Copyright: 2005, Google Inc.
2011, Intel Corporation
License: BSD-3-clause
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:
.
* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.
.
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Files: debian/*
Copyright: 2013 Faidon Liambotis <paravoid@debian.org>
License: BSD-2-clause
This license covers src/rdhdrhistogram.c which is a C port of
Coda Hale's Golang HdrHistogram https://github.com/codahale/hdrhistogram
at revision 3a0bb77429bd3a61596f5e8a3172445844342120

The MIT License (MIT)

Copyright (c) 2014 Coda Hale

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE
From https://github.com/tinycthread/tinycthread/README.txt c57166cd510ffb5022dd5f127489b131b61441b9

License

Copyright (c) 2012 Marcus Geelnard
2013-2014 Evan Nemerson

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
claim that you wrote the original software. If you use this software
in a product, an acknowledgment in the product documentation would be
appreciated but is not required.

2. Altered source versions must be plainly marked as such, and must not be
misrepresented as being the original software.

3. This notice may not be removed or altered from
any source
distribution.
The following license applies to the files rdcrc32.c and rdcrc32.h which
have been generated by the pycrc tool.
==========

Copyright (c) 2006-2012, Thomas Pircher <tehpeh@gmx.net>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.6 openssl 3.0.15

1.6.1 Available under license :

This software is copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software; you can redistribute it and/or modify it under
the same terms as the Perl 5 programming language system itself.

Terms of the Perl programming language system itself

a) the GNU General Public License as published by the Free
Software Foundation; either version 1, or (at your option) any
later version, or
b) the "Artistic License"

--- The GNU General Public License, Version 1, February 1989 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

The GNU General Public License, Version 1, February 1989

GNU GENERAL PUBLIC LICENSE
Version 1, February 1989

Copyright (C) 1989 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The license agreements of most software companies try to keep users
at the mercy of those companies. By contrast, our General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. The
General Public License applies to the Free Software Foundation's

software and to any other program whose authors commit to using it.
You can use it for your programs, too.

When we speak of free software, we are referring to freedom, not price. Specifically, the General Public License is designed to make sure that you have the freedom to give away or sell copies of free software, that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of a such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must tell them their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

The precise terms and conditions
for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any work containing the Program or a portion of it, either verbatim or with modifications. Each licensee is addressed as "you".

1. You may copy and distribute verbatim copies of the Program's source

code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this General Public License and to the absence of any warranty; and give any other recipients of the
Program a copy of this General Public License
along with the Program. You may charge a fee for the physical act of transferring a copy.

2. You may modify your copy or copies of the Program or any portion of it, and copy and distribute such modifications under the terms of Paragraph 1 above, provided that you also do the following:

a) cause the modified files to carry prominent notices stating that you changed the files and the date of any change; and

b) cause the whole of any work that you distribute or publish, that in whole or in part contains the Program or any part thereof, either with or without modifications, to be licensed at no charge to all third parties under the terms of this General Public License (except that you may choose to grant warranty protection to some or all third parties, at your option).

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive
use
in the simplest and most usual way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this General Public License.

d) You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

Mere aggregation of another independent work with the Program (or its derivative) on a volume of a storage or distribution medium does not bring the other work under the scope of these terms.

3. You may copy and distribute the Program (or a portion or derivative of it, under Paragraph 2) in object code or executable form under the terms of Paragraphs 1 and 2 above provided that you also do one of the following:

a) accompany it with the complete corresponding
machine-readable
source code, which must be distributed under the terms of

Paragraphs 1 and 2 above; or,

b) accompany it with a written offer, valid for at least three
years, to give any third party free (except for a nominal charge
for the cost of distribution) a complete machine-readable copy of the
corresponding source code, to be distributed under the terms of
Paragraphs 1 and 2 above; or,

c) accompany it with the information you received as to where the
corresponding source code may be obtained. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or executable form alone.)

Source code for a work means the preferred form of the work for making
modifications to it. For an executable file, complete source code means
all the source code for all modules it contains; but, as a special
exception, it need not include source code for modules which are standard
libraries that
accompany the operating system on which the executable
file runs, or for standard header files or definitions files that
accompany that operating system.

4. You may not copy, modify, sublicense, distribute or transfer the
Program except as expressly provided under this General Public License.
Any attempt otherwise to copy, modify, sublicense, distribute or transfer
the Program is void, and will automatically terminate your rights to use
the Program under this License. However, parties who have received
copies, or rights to use copies, from you under this General Public
License will not have their licenses terminated so long as such parties
remain in full compliance.

5. By copying, distributing or modifying the Program (or any work based
on the Program) you indicate your acceptance of this license to do so,
and all its terms and conditions.

6. Each time you redistribute the Program (or any work based on the
Program), the recipient automatically receives a license from the
original
licensor to copy, distribute or modify the Program subject to these
terms and conditions. You may not impose any further restrictions on the
recipients' exercise of the rights granted herein.

7. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program

specifies a version number of the license which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the license, you may choose any version ever published by the Free Software Foundation.

8. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

9. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

10. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to humanity, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so,
attach the following notices to the program. It is safest to
attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the
"copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 1, or (at your option)
any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free
Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19xx name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the
appropriate parts of the General Public License. Of course, the
commands you use may be called something other than `show w' and `show
c'; they could even be mouse-clicks or menu items--whatever suits your
program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here a sample; alter
the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
program `Gnomovision' (a program to direct compilers to make passes

at assemblers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

That's all there is to it!

--- The Artistic License 1.0 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

The Artistic License 1.0

The Artistic License

Preamble

The intent of this document is to state the conditions under which a Package may be copied, such that the Copyright Holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

Definitions:

- "Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection
of files created through
textual modification.
- "Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder.
- "Copyright Holder" is whoever is named in the copyright or copyrights for the package.
- "You" is you, if you're thinking about copying or distributing this Package.
- "Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)
- "Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You may make and give away verbatim copies of

the source form of the
Standard Version of this Package without restriction, provided that you
duplicate all of the original copyright notices and associated disclaimers.

2. You may apply bug fixes, portability fixes and other modifications derived
from the Public Domain or from the Copyright Holder. A Package modified in such
a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that
you insert a prominent notice in each changed file stating how and when you
changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them
Freely Available, such as by posting said modifications to Usenet or an
equivalent medium, or placing the modifications on a major archive site
such as ftp.uu.net, or by allowing the Copyright Holder to include your
modifications in the Standard Version of the Package.

b) use the modified
Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with
standard executables, which must also be provided, and provide a separate
manual page for each non-standard executable that clearly documents how it
differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable
form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files,
together with instructions (in the manual page or equivalent) on where to
get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package
with your modifications.

c) accompany any non-standard executables with their corresponding Standard
Version executables, giving the non-standard executables non-standard
names,
and clearly documenting the differences in manual pages (or
equivalent), together with instructions on where to get the Standard
Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this

Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that you do not advertise this Package as a product of your own.

6. The scripts and library files supplied as input to or produced as output from the programs of this Package do not automatically fall under the copyright of this Package, but belong to whomever generated them, and may be sold commercially, and may be aggregated with this Package.

7. C or perl subroutines supplied by you and linked into this Package shall not
be considered part of this Package.

8. The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.

9. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

Apache License
Version 2.0, January 2004
https://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity

exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the

Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents

of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,

work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.7 curl 8.14.1-r2

1.7.1 Available under license :

Copyright (c) <year> <owner>.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
COPYRIGHT AND PERMISSION NOTICE

Copyright (C) Daniel Stenberg, <daniel@haxx.se>, and many

contributors, see the THANKS file.

All rights reserved.

Permission to use, copy, modify, and distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright
notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not
be used in advertising or otherwise to promote the sale, use or other dealings
in this
Software without prior written authorization of the copyright holder.
BSD-4-Clause (University of California-Specific)

Copyright [various years] The Regents of the University of California. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. All advertising materials mentioning features or use of this software must display the following acknowledgement: This product includes software developed by the University of California, Berkeley and its contributors.

4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific
prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN

CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
COPYRIGHT AND PERMISSION NOTICE

Copyright (c) 1996 - 2025, Daniel Stenberg, <daniel@haxx.se>, and many
contributors, see the THANKS file.

All rights reserved.

Permission to use, copy, modify, and distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright
notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not
be used in advertising or otherwise to promote the sale, use or other
 dealings
in this Software without prior written authorization of the copyright holder.

1.8 github.com/aws/aws-sdk-go-v2/service/ssooidc 1.32.0

1.8.1 Available under license :

GetLicense
 Initialize stack step
  spanInitializeStart

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

```
  InterceptTransmit
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
     - name: Run Scan code on pr ref
       run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
```

```
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
```

This member is required.
ClientToken *string

// Configuration for consumption of the license. Choose a provisional
// configuration for workloads running with continuous connectivity. Choose a
// borrow configuration for workloads with offline usage.
//
// This member is required.
ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

```
 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
```

```
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
```

UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step

ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint

```
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
```

```
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
```

```
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
```

```
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return
err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if
err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
 spanInitializeStart
 InterceptExecution
 RegisterServiceMetadata
 legacyEndpointContextSetter
 SetLogger
 OperationInputValidation
 spanInitializeEnd
 Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
 Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
 Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
```

```
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
```

```
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack,
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
```

OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
```

```
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
```

```
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
```

```
 return err
}
if err = addDisableHTTPSMiddleware(stack, options);
err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if
err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
```

```
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
```

```
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
```

```
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
```

```
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
```

```
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
```

```
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
```

```
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
```

```
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.

```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
```

```
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/DeregisterSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider
resource to deregister.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {},
```

```
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of name to filter by.</p>"
                 }
            },
            "Values": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
                }
            },
            "Operator": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
                "traits": {
                    "smithy.api#documentation": "<p>An operator for filtering results.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
```

```
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

        "traits": {
              "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
             }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
```

```
"com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/GetServiceSettings"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
```

```
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }
            },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                 "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
            "AmiId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
                }
            },
            "InstanceID": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
                }
            },
            "InstanceType": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>The instance type of the resource.</p>"
                }
            },
            "AccountID": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
        "Region": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
        },
        "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
        },
        "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
        },
        "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
        },
        "SubscriptionName": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
            }
        },
        "OsVersion": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
            }
        },
        "SubscriptionProviderCreateTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
        },
        "SubscriptionProviderUpdateTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
            }
        },
        "DualSubscription": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
            }
        },
        "RegisteredWithSubscriptionProvider": {
            "target": "smithy.api#String",
            "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
      "type": "structure",
```

```
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>An exception occurred with the service.</p>",
        "smithy.api#error": "server"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
      "type": "service",
      "version": "2018-05-10",
      "operations": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
         },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
        }
```

```
    ],
    "traits": {
      "aws.api#service": {
        "sdkId": "License Manager Linux Subscriptions",
         "arnNamespace": "license-manager-linux-subscriptions",
        "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
      },
      "aws.auth#sigv4": {
        "name": "license-manager-linux-subscriptions"
      },
      "aws.protocols#restJson1": {},
      "smithy.api#cors": {
        "additionalAllowedHeaders": [
          "*",
          "content-type",
          "x-amz-content-sha256",
          "x-amz-user-agent",
          "x-amzn-platform-id",
          "x-amzn-trace-id"
        ],
        "additionalExposedHeaders": [
          "x-amzn-errortype",
          "x-amzn-requestid",
          "x-amzn-trace-id"
        ]
      },
      "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
      "smithy.api#title": "AWS License Manager Linux Subscriptions",
      "smithy.rules#endpointRuleSet": {
        "version": "1.0",
        "parameters": {
          "Region": {
            "builtIn": "AWS::Region",
            "required": false,
            "documentation": "The AWS region used to dispatch the request.",
            "type": "String"
          },
          "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
             "type": "Boolean"
          },
          "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
```

```
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
          },
          "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }

      ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "rules": [
                  {
                    "conditions": [
                      {
```

```
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]

}
                    ],
                    "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                    "type": "error"
                  },
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": {
                        "ref": "Endpoint"
                      },
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],
                "type": "tree"

              }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "isSet",
                      "argv": [
                        {
                          "ref": "Region"
                        }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [
```

```
                {

            "fn": "aws.partition",
                    "argv": [
                      {
                        "ref": "Region"
                      }
                    ],
                    "assign": "PartitionResult"
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {

                       "ref": "UseFIPS"
                          },
                          true
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
                      }

],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              true,
                              {
                                "fn": "getAttr",
                                "argv": [
                                  {
                                    "ref": "PartitionResult"
```

```
                },
                                "supportsFIPS"
                            ]
                        }
                    ]
                },
                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [

                             {
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [],

        "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],

             "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
```

```
one or both",
                                        "type": "error"
                                    }
                                ],
                                "type": "tree"
                            },
                            {

                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "ref": "UseFIPS"
                                            },
                                            true
                                        ]
                                    }
                                ],
                                "rules": [
                                    {
                                        "conditions": [
                                            {

                            "fn": "booleanEquals",
                                                "argv": [
                                                    {
                                                        "fn": "getAttr",
                                                        "argv": [
                                                            {
                                                                "ref": "PartitionResult"
                                                            },
                                                            "supportsFIPS"
                                                        ]
                                                    },
                                                    true

                                                ]
                                            }
                                        ],
                                        "rules": [
                                            {
                                                "conditions": [],
                                                "rules": [
                                                    {
                                                        "conditions": [],
                                                        "endpoint": {
                                                            "url": "https://license-manager-linux-subscriptions-
```

```
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                                    "headers": {}
                                                },
                                                "type": "endpoint"
                                            }
                                        ],
                                        "type": "tree"
                                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS is enabled
but this partition does not support FIPS",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseDualStack"
                                    },
                                    true


                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            true,
                                            {
                                                "fn": "getAttr",
                                                "argv": [
                                                    {
```

```
                                        "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "rules": [

        {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"

                }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                            "properties": {},
                            "headers": {}
```

```
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
]
},
"smithy.rules#endpointTests": {
"testCases": [
{
"documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
"expect": {
"endpoint": {
"url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
},
"params": {
"Region": "us-east-1",
"UseFIPS": true,
"UseDualStack": true
}
},
{
"documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
"expect": {
"endpoint": {
"url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
}
},
"params": {
"Region": "us-east-1",
"UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {

      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
```

```
"documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                      }
                    },
                    "params": {
                      "Region": "cn-north-1",
                      "UseFIPS": true,
                      "UseDualStack": false
                    }
                  },
                  {
                    "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                      }
                     },
                    "params": {
                      "Region": "cn-north-1",
                      "UseFIPS": false,
                      "UseDualStack": true
                    }
                  },
                  {
                    "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
                      }
                    },
                    "params": {
                      "Region": "cn-north-1",
                      "UseFIPS": false,
                      "UseDualStack": false
                    }
                  },
                  {

 "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
                      }
                    },
                    "params": {
                      "Region": "us-gov-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }

        },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

        "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
```

```
{
  "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
  "expect": {
    "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": true,
    "UseDualStack": true
  }
},
{
  "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
  "expect": {
    "endpoint": {
      "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
     }
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": true,
    "UseDualStack": false
  }
},
{
  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
  "expect": {
    "error": "DualStack is enabled but this partition does not support DualStack"
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": false,
    "UseDualStack": true
  }
},
{

 "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
  "expect": {
    "endpoint": {
      "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
    }
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": false,
    "UseDualStack": false
  }
```

```
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {

      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
      },
```

```
                "params": {

 "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled LinuxSubscriptionsDiscovery"

       },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
        "type": "structure",
        "members": {
          "SourceRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "OrganizationIntegration": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
               "traits": {
                  "smithy.api#documentation":
"<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

  {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "Instances"
            }
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n          <li>\n
  <p>\n              <code>AccountID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
    <code>AmiID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>DualSubscription</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceType</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>ProductCode</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Region</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Status</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>UsageOperation</code>\n            </p>\n          </li>\n        </ul>\n        <p>For each filter, you can use
one of the following <code>Operator</code>
 values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
```

```
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
            "Instances": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
                }
            },
            "NextToken": {

     "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",

   "items": "Subscriptions"
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
         "type": "structure",
         "members": {
            "Filters": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n         <p>The valid names for this filter are:</p>\n         <ul>\n
<li>\n               <p>\n                  <code>Subscription</code>\n               </p>\n            </li>\n         </ul>\n
<p>The
 valid Operators for this filter are:</p>\n         <ul>\n            <li>\n               <p>\n
<code>contains</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>equals</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>Notequal</code>\n               </p>\n            </li>\n         </ul>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 16384
                  }
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "Subscriptions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
            "traits": {
              "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
             "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
```

```
        ],
        "traits": {
          "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListRegisteredSubscriptionProviders"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "RegisteredSubscriptionProviders"
          }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSources": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
          "traits": {
            "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
          }
        },
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }

  },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
          }
        }
      },
```

```
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
          "traits": {
            "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
          }
        },

        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
      },
      "errors": [
        {

      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
         }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
```

```
                "documentation": "Equal operator"
              },
              {
                "name": "NOT_EQUAL",
                "value": "NotEqual",
                "documentation": "Not equal operator"
              },
              {
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
```

```
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
```

```
            }
        },
        "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
                "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
        },
        "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
            }
        },
        "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
                "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
            }
        },
        "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
            }
        },
        "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed
third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and
license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider,
License Manager can get subscription data from the registered provider.</p>"
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
```

```
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
```

```
                "documentation": "Failed status"
              }
            ]
          }
        },

      "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            }
          }
        },
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
          },
          "smithy.api#uniqueItems": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
          "Name":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the subscription.</p>"
            }
          },
          "Type": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
```

```
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS.</p>"
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": "<p>The total amount of running instances using this subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
```

```
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "ACTIVE",
          "value": "ACTIVE",
          "documentation": "ACTIVE status"
        },
        {
          "name": "INVALID",
          "value": "INVALID",

"documentation": "INVALID status"
        },
        {
          "name": "PENDING",
          "value": "PENDING",
          "documentation": "PENDING status"
        }
      ]
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
    "type": "list",
    "member": {
      "target": "smithy.api#String"
    },
    "traits": {
      "smithy.api#length": {
        "min": 0,
        "max": 50
      },
      "smithy.api#sensitive": {}
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
     },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
 {
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        }
```

```
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

        },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                "smithy.api#required": {}
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                "smithy.api#required": {}
              }
            },
            "AllowUpdate": {
              "target":
```

```
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated data for Linux\n      subscriptions.</p>"
                }
            }
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
          "smithy.api#error": "client"
        }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {
```

```
// Unique, case-sensitive identifier that you provide to ensure the idempotency of
//
the request.
//
// This member is required.
ClientToken *string

// Digital signature method. The possible value is JSON Web Signature (JWS)
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string
```

```
// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
```

```
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
```

```
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
```

```
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
```

```
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata
```

```
 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
```

```
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
string) *awsmiddleware.RegisterServiceMetadata {
return &awsmiddleware.RegisterServiceMetadata{
```

```
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
```

```
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
```

```
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
```

```
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
```

```
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
```

InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,

DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP \n\t\t\taddresses, and the credential provider for user administration.</p>"
          }
        },
        "ActiveDirectoryType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
          "traits": {
            "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity
```

```
provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
            },
            "DomainIpv4List": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 2
                    }
                }
            },
            "DomainCredentialsProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
            },
            "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
        "type": "string",
        "traits": {
```

```
            "smithy.api#enum": [
               {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
               },
               {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
               }
            ]
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Arn": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
 {
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
```

```
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
            "type": "operation",
            "input": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
            },
            "output": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
            },
            "errors": [
                {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
                },
                {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
                },

               {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
                },
                {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
                },
                {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
                },
                {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
                },
                {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
                }
            ],
            "traits": {
                "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
                "smithy.api#http": {
                    "code": 200,
                    "method": "POST",
                    "uri": "/license-server/CreateLicenseServerEndpoint"
                },
                "smithy.api#idempotent": {}
            }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
            "type": "structure",
            "members": {
                "IdentityProviderArn": {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
              "smithy.api#required": {}
            }
          },
          "LicenseServerSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
             "traits": {
              "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
            }
          }
        },
        "traits": {
```

```
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

 }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/DeleteLicenseServerEndpoint"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
              "smithy.api#required": {}
            }
          },
           "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
            "traits": {
              "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
            }
          }
        },
```

```
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/DeregisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
```

```
{
        "type": "structure",
        "members": {
           "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                 "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
              }
           },
           "Product": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
              }
           },
           "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                 "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
              }
           }
        },
        "traits": {
           "smithy.api#input": {}
        }
     },
     "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
           "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                 "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                 "smithy.api#required": {}
              }
           }
        },
        "traits": {
           "smithy.api#output": {}

   }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
         },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/DisassociateUser"
        },
        "smithy.api#idempotent": {}
```

```
    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
      "type": "structure",
      "members": {
        "Username": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
          }
        },
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
          }
        },
        "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
          "traits": {
            "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
          }
        },
        "InstanceUserArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
          }
        },
        "Domain": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
      "type": "structure",
      "members": {
```

```
        "InstanceUserSummary":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
              "smithy.api#length": {
                "min": 1
              },

    "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Attribute": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
            }
          },
```

```
            "Value": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>Value of the filter.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
         "type": "union",
         "members": {
            "ActiveDirectoryIdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
         "type": "structure",
         "members": {
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
                "smithy.api#required": {}
            }
        },
        "Product": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
        },
        "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an identity provider.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
    "type": "list",
    "member": {

      "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
    "type": "structure",
```

```
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                    "smithy.api#required": {}
                }
            },
            "Products": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
                 "traits": {
                    "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                    "smithy.api#required": {}
                }
            },
            "LastStatusCheckDate": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The date of the last status check.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
```

```
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },

      "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                 }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
         "smithy.api#error": "server",
        "smithy.api#httpError": 500
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
      }
    },
```

```
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",

       "x-api-key",
            "authorization",
            "x-amz-date",
            "x-amz-security-token",
            "Access-Control-Allow-Headers",
            "Access-Control-Allow-Methods",
            "Access-Control-Allow-Origin"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
```

```
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region":
{
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
              "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
```

```
        }
      ],
      "rules": [
        {
          "conditions": [
            {
              "fn": "booleanEquals",
              "argv": [
                {
                  "ref": "UseFIPS"
                },
                true
              ]
            }
          ],
          "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
          "type": "error"
        },
        {
          "conditions": [
            {

              "fn": "booleanEquals",
              "argv": [
                {
                  "ref": "UseDualStack"
                },
                true
              ]
            }
          ],
          "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
          "type": "error"
        },
        {
          "conditions": [],
          "endpoint": {
            "url": {
              "ref": "Endpoint"
            },

"properties": {},
            "headers": {}
          },
          "type": "endpoint"
        }
      ],
      "type": "tree"
```

```
    },
    {
      "conditions": [
        {
          "fn": "isSet",
          "argv": [
            {
              "ref": "Region"
            }
          ]
        }
      ],
      "rules": [
        {
          "conditions": [
            {
              "fn": "aws.partition",

              "argv": [
                {
                  "ref": "Region"
                }
              ],
              "assign": "PartitionResult"
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
```

true

```
                    ]
                  },
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
```

```
                ],
                "rules": [
                  {
                    "conditions": [
                      {

 "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"
                              },
                              "supportsFIPS"
                            ]
                          }
                        ]
                      },

                    {
                        "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"
                              },
                              "supportsDualStack"
                            ]
                          }

                ]
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [],
                        "endpoint": {
                          "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                          "properties": {},
                          "headers": {}
                        },
                        "type": "endpoint"
```

```
                }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [

 {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [

    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true
                        ]
                    }
                ],
                "rules": [
```

```
                                    {
                                        "conditions": [],
                                        "endpoint": {

                "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS is enabled but this partition does not support FIPS",
                                "type": "error"

}
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]
                                }
                            ],
                            "rules": [
                                {

        "conditions": [
                                        {
                                            "fn": "booleanEquals",
                                            "argv": [
                                                true,
                                                {
                                                    "fn": "getAttr",
                                                    "argv": [
                                                        {
                                                            "ref": "PartitionResult"
                                                        },
```

```
                                    "supportsDualStack"
                                ]

        }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }

                    ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "endpoint": {
                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
    }
],
"type": "tree"
```

```
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
              }
            ]
          },
          "smithy.rules#endpointTests": {
            "testCases": [
              {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
                "expect":
{
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                  }
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                  }
                },
                "params": {
                  "Region": "us-east-1",

      "UseFIPS": true,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                  }
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
```

```
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS":
true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint":
```

```
{
                    "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": false,
                 "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint":
{
                    "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": true,
                "UseDualStack": false
```

```
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
         "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
```

```
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

        }
            },
            {
              "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
              },
              "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

          },
              "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
              },
              "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
```

```
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",

"UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
          "expect": {

         "endpoint": {
                "url": "https://example.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
```

```
        {
          "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }
          },
          "params": {
            "UseFIPS": false,
            "UseDualStack":
false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with fips enabled and dualstack disabled",
          "expect": {
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with fips disabled and dualstack enabled",
          "expect": {
            "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "Missing region",
          "expect": {
            "error": "Invalid Configuration: Missing Region"
          }
        }
      ],
      "version": "1.0"
```

```
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>"
              }
```

```
        },
        "ServerEndpoint": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
              "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network \n\t\t\taddress of the RDS license server endpoint.</p>"
          }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
          }
        },
        "LicenseServerEndpointId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
          }
        },
        "LicenseServerEndpointArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits":
 {
            "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
          }
        },
        "LicenseServerEndpointProvisioningStatus": {
          "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
          "traits": {
            "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
          }
        },
        "LicenseServers": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
          }
        },

       "CreationTime": {
          "target": "smithy.api#Timestamp",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
              "name": "PROVISIONED",
              "value": "PROVISIONED",
              "documentation": ""
            },
            {
              "name": "DELETING",
              "value": "DELETING",
              "documentation": ""
            },
            {
              "name": "DELETION_FAILED",
              "value": "DELETION_FAILED",
```

```
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
    "type": "string",
    "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
    }
},
 "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
    "type": "structure",
    "members": {
        "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>",
                "smithy.api#required": {}
            }
```

```
            },
            "ServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
```

```
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/ListIdentityProviders"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "IdentityProviderSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
         "type": "structure",
         "members": {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n        <li>\n        <p>Product</p>\n        </li>\n
        <li>\n        <p>DirectoryId</p>\n        </li>\n        </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
         "type": "structure",
         "members": {
```

```
        "IdentityProviderSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

        "traits": {
            "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
            "smithy.api#required": {}
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
      "type": "operation",
       "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
```

```
    {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n              <p>Status</p>\n          </li>\n
        <li>\n              <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/ListLicenseServerEndpoints"
          },

        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "LicenseServerEndpoints"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
             "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n              <p>IdentityProviderArn</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
             "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n
</li>\n          <li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
```

```
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
"com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
    }
      }
    },
    "traits": {
      "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
    "type": "structure",
    "members": {
      "Tags": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
        "traits": {
          "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
        }
      }
    },
    "traits": {
      "smithy.api#output": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
```

```
      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
```

```
user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a product for this user.</p>",
                    "smithy.api#required": {}
                }
            },
            "ProductUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {

            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
                }
            },
            "SubscriptionStartDate": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The start date of a subscription.</p>"
              }
            },
            "SubscriptionEndDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The end date of a subscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
user.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
          "type":
 "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
          "type": "structure",
          "members": {
            "RdsSalCredentialsProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
              "traits": {
                "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
          },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/RegisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
 {
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

       "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
```

```
            "Endpoint": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
         "type": "union",
         "members": {
            "RdsSalSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "RDS_SAL",
                  "value": "RDS_SAL",
                  "documentation": ""
               }
            ]
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
         "type": "structure",
         "members": {
            "message": {

   "target": "smithy.api#String"
            }
         },
         "traits": {
```

```
            "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
            "Subnets": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
                "traits": {
                    "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
                    "smithy.api#length": {
                        "min": 1
                    },
                    "smithy.api#required": {}
                }
            },
            "SecurityGroupId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

             "traits": {
                    "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/user/StartProductSubscription"
            }

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
```

```
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {

 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/StopProductSubscription"
        }
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
      "type": "structure",
      "members": {
        "Username": {
          "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
            }
          },
          "IdentityProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
```

```
            }

    }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
"<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
```

```
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
          "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
```

```
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
```

```
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
               }
            },
            "UpdateSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
               "traits": {
                  "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n            <li>\n               <p>Subnets which you want to add to provision VPC endpoints.</p>\n            </li>\n
      <li>\n               <p>Subnets which you want to remove the VPC endpoints from.</p>\n            </li>\n
<li>\n               <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n            </li>\n         </ul>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
         "type": "structure",
         "members": {
            "IdentityProviderSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
               "traits": {
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
         "type": "structure",
         "members": {
            "AddSubnets": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
                  "smithy.api#required": {}
```

```
            }
          },
          "RemoveSubnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
            "traits": {
              "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A parameter is not valid.</p>",
          "smithy.api#error": "client"
        }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)
```

```
// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
```

```
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
 nil {
  return err
 }
```

```
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
```

SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License

Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this
License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,

except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the

same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity

ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt

RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.9 github.com/golang-jwt/jwt/v5 5.3.0

1.9.1 Available under license :

Copyright (c) 2012 Dave Grijalva
Copyright (c) 2021 golang-jwt maintainers

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.10 utmps-libs 0.1.2.3-r2

1.10.1 Available under license :

Copyright (c) 2018-2024 Laurent Bercot <ska-skaware@skarnet.org>

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.11 aws-sdk-go-v2-service-internal-endpoint-discovery 1.11.2

1.11.1 Available under license :

GetLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd

```
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer

 // License name.
```

```
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
```

```
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
```

```
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
```

```
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
     - name: Run Scan code on pr ref
```

run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt

compare

- name: License test

run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi

CheckoutBorrowLicense

Initialize stack step

spanInitializeStart

InterceptExecution

RegisterServiceMetadata

legacyEndpointContextSetter

SetLogger

OperationInputValidation

spanInitializeEnd

Serialize stack step

spanBuildRequestStart

setOperationInput

ResolveEndpoint

InterceptBeforeSerialization

OperationSerializer

InterceptAfterSerialization

Build stack step

ClientRequestID

ComputeContentLength

SetCredentialSourceMiddleware

UserAgent

AddTimeOffsetMiddleware

RecursionDetection

spanBuildRequestEnd

Finalize stack step

spanRetryLoop

InterceptBeforeRetryLoop

Retry

InterceptAttempt

RetryMetricsHeader

ResolveAuthScheme

GetIdentity

ResolveEndpointV2

disableHTTPS

ComputePayloadHash

setLegacyContextSigningOptions

InterceptBeforeSigning

Signing

InterceptAfterSigning

Deserialize stack step

AddRawResponseToMetadata

ErrorCloseResponseBody

CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning

Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash

```
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
  - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
```

SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

```
package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32
```

```
 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
```

```
 return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
 return err
 }
 if err = addRetry(stack, options); err != nil {
 return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
 err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
```

```
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
 spanInitializeStart
 InterceptExecution
 RegisterServiceMetadata
 legacyEndpointContextSetter
 SetLogger
 OperationInputValidation
 spanInitializeEnd
 Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
 Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
 Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
```

```
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }
```

```
 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
```

```
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
```

```
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
```

```
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string
```

```
 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string
```

```
 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
AWS SDK for Go
Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.
{
  "smithy": "2.0",
  "shapes": {
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
        "type": "integer"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
        "type": "long"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
        "type": "operation",
        "input": {
           "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
        },
        "output": {
           "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
        },
        "errors": [
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
           },
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
           },

     {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
           },
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
           }
        ],
        "traits": {
           "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
```

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/DeregisterSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider
resource to deregister.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of name to filter by.</p>"
                 }
            },
            "Values": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
                }
            },
            "Operator": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
      "type":
 "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
      },
      "output": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
         },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/GetRegisteredSubscriptionProvider"
        },
```

```
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

          "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
```

```
last \n\t\t\tsuccessful subscription data request.</p>"
                }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"
```

```
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
      "type": "structure",
      "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
          "traits": {
            "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
          }
        },
        "StatusMessage": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
          "traits": {
            "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
          }
        },
        "HomeRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
          }
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
      "type": "structure",
      "members": {
        "AmiId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
          }
        },
        "InstanceID": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
          }
        },
        "InstanceType": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>The instance type of the resource.</p>"
          }
        },
        "AccountID": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of the instance.</p>"
          }
        },
        "Region": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
          }
        },
        "UsageOperation": {
          "target": "smithy.api#String",

   "traits": {
            "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User
```

```
Guide</i>.</p>"
                }
            },
            "ProductCode": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
                "traits": {
                    "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a
href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-
operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
                }
            },
            "LastUpdatedTime": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The time in which the last discovery updated the instance
details.</p>"
                }
            },
            "SubscriptionName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
                }
            },
            "OsVersion": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
                }
            },
            "SubscriptionProviderCreateTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
                }
            },
            "SubscriptionProviderUpdateTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
                }
            },
            "DualSubscription": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for \n\t\t\tthe same software on your instance.</p>"
                }
            },
            "RegisteredWithSubscriptionProvider": {
                "target": "smithy.api#String",
                "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta third-party Linux subscription provider that you've registered with License Manager.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
         },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
        }
    ],
    "traits": {
        "aws.api#service": {
            "sdkId": "License Manager Linux Subscriptions",
             "arnNamespace": "license-manager-linux-subscriptions",
            "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
            "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
            "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
```

```
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                 {
                   "fn": "isSet",
                   "argv": [
                      {
                         "ref": "Endpoint"
                      }
```

```
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }

    ],
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]

}
                            ],
                            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                            "type": "error"
                        },
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": {
                                    "ref": "Endpoint"
                                },
                                "properties": {},
                                "headers": {}
                            },
```

```
                "type": "endpoint"
            }
        ],
        "type": "tree"

    }
    ],
    "type": "tree"
},
{
    "conditions": [],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Region"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {

    "fn": "aws.partition",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ],
                            "assign": "PartitionResult"
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {

                                    "ref": "UseFIPS"
                                        },
                                        true
```

```
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }

    ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"

            },
                                "supportsFIPS"
                            ]
                          }
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [

                             {
                                  "ref": "PartitionResult"
                              },
                              "supportsDualStack"
                            ]
                          }
                        ]
                      }
```

```
                ],
                "rules": [
                  {
                    "conditions": [],

    "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }
                  ],

            "type": "tree"
                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {

        "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
```

```
                                    {

                            "fn": "booleanEquals",
                                        "argv": [
                                          {
                                            "fn": "getAttr",
                                            "argv": [
                                              {
                                                "ref": "PartitionResult"
                                              },
                                              "supportsFIPS"
                                            ]
                                          },
                                          true

                                      ]
                                        }
                                      ],
                                      "rules": [
                                        {
                                          "conditions": [],
                                          "rules": [
                                            {
                                              "conditions": [],
                                              "endpoint": {
                                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                                "headers": {}
                                              },
                                              "type": "endpoint"
                                            }
                                          ],
                                          "type": "tree"
                                        }
                                      ],
                                      "type": "tree"
                                    },
                                    {
                                      "conditions": [],
                                      "error": "FIPS is enabled
 but this partition does not support FIPS",
                                      "type": "error"
                                    }
                                  ],
                                  "type": "tree"
                                },
```

```
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseDualStack"
                        },
                        true

            ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            true,
                            {
                              "fn": "getAttr",
                              "argv": [
                                {

                                "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                              ]
                            }
                          ]
                        }
                      ],
                      "rules": [
                        {
                          "conditions": [],
                          "rules": [

    {
                                "conditions": [],
                                "endpoint": {
                                  "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                  "properties": {},
                                  "headers": {}
                                },
                                "type": "endpoint"
                              }
```

```
                                    ],
                                    "type": "tree"

                            }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
]
},
"smithy.rules#endpointTests": {
```

```
"testCases": [
  {
    "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
    },
    "params": {
      "Region": "us-east-1",
      "UseFIPS": true,
      "UseDualStack": true
    }
  },
  {
    "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
    },
    "params": {
      "Region": "us-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {

 "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
        }
    },
    "params": {
      "Region": "us-east-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {
    "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
        }
```

```
        },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
             },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
```

```
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }

     },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
        }
```

```
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {

    "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
```

```
enabled",
                "expect": {
                  "error": "DualStack is enabled but this partition does not support DualStack"
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
                  }
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS":
false,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                   }
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false
                }
              },
```

```
                {
                  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "error": "DualStack is enabled but this partition does not support DualStack"
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {

                 "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                    }
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }

        },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }
                  },
```

```
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
```

```
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

            },
            {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "OrganizationIntegration": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
          "traits": {
            "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n              <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceType</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>ProductCode</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Region</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Status</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>UsageOperation</code>\n              </p>\n            </li>\n          </ul>\n          <p>For each filter, you can use one of the following <code>Operator</code>
```

```
values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
          "type": "structure",
          "members": {
            "Instances": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
              }
            },
            "NextToken": {

           "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListLinuxSubscriptions"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",

  "items": "Subscriptions"
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
      "type": "structure",
      "members": {
        "Filters": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
```

```
match a certain subscription's name.</p>\n        <p>The valid names for this filter are:</p>\n        <ul>\n
<li>\n            <p>\n                <code>Subscription</code>\n            </p>\n        </li>\n        </ul>\n
<p>The
 valid Operators for this filter are:</p>\n        <ul>\n        <li>\n            <p>\n
<code>contains</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>equals</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n        </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
```

```
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
          },
          "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",
              "items": "RegisteredSubscriptionProviders"
            }
          }

        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSources": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
            }
        },
        "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                "smithy.api#range": {
                    "min": 1,
                    "max": 100
                }
            }

 },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
                "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
        },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
      },
      "errors": [
        {

     "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
        "smithy.api#http": {
          "method": "GET",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#readonly": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
                    "documentation": "Equal operator"
                },
                {
                    "name": "NOT_EQUAL",
                    "value": "NotEqual",
                    "documentation": "Not equal operator"
                },
                {
                    "name": "CONTAINS",
                    "value": "Contains",
                    "documentation": "Contains operator"
                }
            ],
            "smithy.api#length": {
                "min": 1,
                "max": 20
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled OrganizationIntegration"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
```

```
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
            }
          },
```

```
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"
```

```
}
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "InProgress",
          "value": "InProgress",
          "documentation": "InProgress status"
        },
        {
          "name": "Completed",
          "value": "Completed",
          "documentation": "Completed status"
        },
        {
          "name": "Successful",
          "value": "Successful",
          "documentation": "Successful status"
        },
        {
          "name": "Failed",
          "value": "Failed",
          "documentation": "Failed status"
        }
      ]
    }
  },

  "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
    "type": "list",
    "member": {
      "target": "smithy.api#String",
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        }
      }
    },
    "traits": {
      "smithy.api#length": {
        "min": 1,
        "max": 100
      },
      "smithy.api#uniqueItems": {}
    }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
      "type": "structure",
      "members": {
        "Name":
{
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the subscription.</p>"
          }
        },
        "Type": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
          }
        },
        "InstanceCount": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
```

```
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
                },
                {
                    "name": "INVALID",
                    "value": "INVALID",

   "documentation": "INVALID status"
                },
                {
                    "name": "PENDING",
                    "value": "PENDING",
                    "documentation": "PENDING status"
                }
            ]
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
      "type": "structure",
      "members":
{
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services resource to which to add the specified \n\t\t\tmetadata tags.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
```

```
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

          "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
          },
```

```
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
```

```
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
          }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
          "type": "structure",
          "members": {
              "message": {
                  "target": "smithy.api#String"
              }
          },
          "traits": {
              "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
              "smithy.api#error": "client"
          }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
```

```
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
```

```
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
```

```
//
// This member is required.
WorkspaceId *string

// A token from Grafana Labs that ties your Amazon Web Services account with a
// Grafana Labs account. For more information, see [Link your account with Grafana Labs].
//
// [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
GrafanaToken *string

noSmithyDocumentSerde
}

type AssociateLicenseOutput
struct {

// A structure containing data about the workspace.
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
```

```
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
```

```
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",

```
            "traits": {
                "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
        },
        "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
        },
        "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
                "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
      "type": "structure",
      "members": {
        "DomainName": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
          }
        },
        "DomainIpv4List": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
          "traits": {
            "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
            "smithy.api#length": {
              "min": 1,
              "max": 2
            }
          }
        },
        "DomainCredentialsProvider": {
          "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
              },
              "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>Contains network access and credential details that are needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
                }
              ]
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#Arn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
 {
            "type": "operation",
            "input": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n          <note>\n             <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n          </note>",
            "smithy.api#http":
 {
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
              "smithy.api#required": {}
            }
          },
           "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },

        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
```

```
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
              "traits": {
                "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
```

```
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}

      }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Directory": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
```

```
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary":
{
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
         "type": "structure",
         "members": {
            "Subnets": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                  "smithy.api#length": {
                     "min": 1
                  },
```

```
    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
              }
            },
            "FailureMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
          "type": "list",
          "member": {

            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
    "type": "structure",
    "members": {
        "Username": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

"IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
```

```
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
```

```
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
    "type": "structure",
    "members": {
        "message": {
            "target": "smithy.api#String"
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
         "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
         },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
```

```
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",

          "x-api-key",
            "authorization",
            "x-amz-date",
            "x-amz-security-token",
            "Access-Control-Allow-Headers",
            "Access-Control-Allow-Methods",
            "Access-Control-Allow-Origin"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region":
{
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
              "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
```

```
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
            "type": "Boolean"
          },
          "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
             ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [
                  {

                    "fn": "booleanEquals",
                    "argv": [
                      {
```

```
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "aws.partition",

                      "argv": [
                        {
                          "ref": "Region"
                        }
                      ],
                      "assign": "PartitionResult"
                    }
```

```
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },
```

true

```
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
```

"fn": "booleanEquals",

```
                            "argv": [
                              true,
                              {
                                "fn": "getAttr",
                                "argv": [
                                  {
                                    "ref": "PartitionResult"
                                  },
                                  "supportsFIPS"
                                ]
                              }
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              true,
```

```
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }

                            ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

    ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [

 {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
```

```
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "fn": "getAttr",
                                    "argv": [

{
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS is enabled but this partition does not support FIPS",
                    "type": "error"

}
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {

        "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]

          }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

            ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
```

```
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                            "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
{
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint":
{
                  "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
```

```
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
```

```
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

    },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",

  "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
```

```
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

     "endpoint": {
            "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
 false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
```

```
                },
                {
                  "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                  "expect": {
                    "error": "Invalid Configuration:
 Dualstack and custom endpoint are not supported"
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>"
              }
            },
            "ServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
              }
            },
            "LicenseServerEndpointId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits":
```

```
{
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
              }
            },
            "LicenseServerEndpointProvisioningStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
              "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
              }
            },
            "LicenseServers": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
              }
            },

           "CreationTime": {
              "target": "smithy.api#Timestamp",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
          "type": "string"
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

      "type": "string",
          "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
              "name": "PROVISIONED",
              "value": "PROVISIONED",
              "documentation": ""
            },
            {
              "name": "DELETING",
              "value": "DELETING",
              "documentation": ""
            },
            {
              "name": "DELETION_FAILED",
              "value": "DELETION_FAILED",
              "documentation": ""

           },
            {
              "name": "DELETED",
              "value": "DELETED",
              "documentation": ""
            }
         ]
      }
   },
   "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
         "smithy.api#enum": [
            {
              "name": "HEALTHY",
              "value": "HEALTHY",
              "documentation": ""
            },
            {
              "name": "UNHEALTHY",
              "value": "UNHEALTHY",
              "documentation": ""
            },
```

```
                {
                    "name": "NOT_APPLICABLE",
                    "value": "NOT_APPLICABLE",
                    "documentation": ""
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
        "type": "structure",
        "members": {
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
```

```
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n        <li>\n        <p>Product</p>\n        </li>\n
      <li>\n        <p>DirectoryId</p>\n        </li>\n      </ul>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

        "traits": {
            "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
 that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
            "smithy.api#required": {}
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
 empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
 next request to retrieve additional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
      "type": "operation",
```

```
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },

{
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
      }
    ],
    "traits": {
      "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
      "smithy.api#http": {
        "code": 200,
        "method": "POST",
        "uri": "/instance/ListInstances"
      },
      "smithy.api#paginated": {
        "inputToken": "NextToken",
        "outputToken": "NextToken",
        "pageSize": "MaxResults",
        "items": "InstanceSummaries"
      }
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
    "type": "structure",
    "members":
```

```
{
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
      <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
      "type": "structure",
      "members": {
        "InstanceSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
          }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
         },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/license-server/ListLicenseServerEndpoints"
        },

      "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "LicenseServerEndpoints"
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
      "type": "structure",
      "members": {
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n        <li>\n          <p>IdentityProviderArn</p>\n        </li>\n      </ul>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
      "type": "structure",
      "members": {
        "LicenseServerEndpoints": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " Lists the user-based subscription products available from an identity provider. ",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"

```
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
```

```
This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "ProductUserSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

           }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
```

```
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
    "type": "structure",
    "members": {
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
```

```
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {

            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
              }
            },
            "SubscriptionStartDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The start date of a subscription.</p>"
              }
            },
            "SubscriptionEndDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The end date of a subscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
          "type":
 "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
          "type": "structure",
          "members": {
```

```
            "RdsSalCredentialsProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
```

```
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
          "type": "structure",
          "members": {
            "IdentityProvider": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>",
                "smithy.api#required": {}
              }
            },
            "Settings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
              "traits":
 {
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
```

```
                    "min": 1
                }
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
    "type": "string",
    "traits": {
        "smithy.api#length": {

     "min": 5,
            "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
    "type": "structure",
    "members": {
        "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more servers.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
    "type": "union",
    "members": {
        "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
```

```
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {

  "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
            "smithy.api#length": {
              "min": 1
            },
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
            "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688
communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
            "smithy.api#required": {}
          }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StartProductSubscription"
            }

      }
       },
       "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
          "type": "structure",
          "members": {
             "Username": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                   "smithy.api#required": {}
                }
             },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                   "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                   "smithy.api#required": {}
                }
             },
             "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                   "smithy.api#required": {}
                }
             },
             "Domain": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
                }
             },
             "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                   "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
                }
```

```
 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "ProductUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }

    }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

 "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
 {
        "type": "structure",
        "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {
```

```
      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
```

```
            "type": "structure",
            "members": {
                "message": {
                    "target": "smithy.api#String"
                }
            },
            "traits": {
                "smithy.api#documentation": "<p>A parameter is not valid.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
```

```
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
```

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation

spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.12 ncurses 6.5_p20241006-r3

1.12.1 Available under license :

Upstream source https://invisible-island.net/ncurses/ncurses-examples.html

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 Thomas E. Dickey
Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 2003-2019,2020 by Thomas E. Dickey
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, distribute with modifications, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright
holders shall not be used in advertising or otherwise to promote the
sale, use or other dealings in this Software without prior written
authorization.

Files: install-sh
Copyright: 1994 X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining
a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN
AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNEC-
TION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not
be used in advertising or otherwise to promote the sale, use or other deal-
ings in this Software without prior written authorization from the X Consor-
tium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent
`make' implicit rules from creating a file called install from it
when there is no Makefile.

This script is compatible with the BSD install script, but was written
from scratch. It can only install one file at a time, a restriction
shared with many OS's install programs.

On Debian systems, the complete text of the GNU General
Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile: txtmode file-encoding=utf-8
Upstream source https://invisible-island.net/ncurses/ncurses.html
This package is used for testing builds of ncurses.

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 by Thomas E. Dickey
Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 1996-2020,2021 by Thomas E. Dickey
Licence: X11

Files: doc/html/NCURSES-Programming-HOWTO.html
Copyright: 2001 by Pradeep Padala
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files:
install-sh
Copyright: 1994 X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNEC-
TION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

Files: progs/tset.c ncurses/tinfo/read_termcap.c
Copyright: 1980,1991,1992,1993 The Regents of the University of California.
License: BSD

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list
of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

-- vile: txtmode file-encoding=utf-8
Copyright 2018-2020,2021 Thomas E. Dickey
Copyright 1998-2017,2018 Free Software Foundation, Inc.

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, distribute with modifications, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER
 IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright
holders shall not be used in advertising or otherwise to promote the
sale, use or other dealings in this Software without prior written
authorization.

-- vile:txtmode fc=72
-- $Id: COPYING,v 1.10 2021/01/01 09:54:30 tom Exp $
Upstream source https://invisible-island.net/ncurses/Ada95.html

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 by Thomas E. Dickey
Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 2010-2020,2021 by Thomas E. Dickey
Licence: X11

 Permission is hereby granted, free of charge, to any person obtaining a
 copy of this software and associated documentation files (the
 "Software"), to deal in the Software without restriction, including
 without limitation the rights to use, copy, modify, merge, publish,
 distribute, distribute with modifications, sublicense, and/or sell
 copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included

in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh
Copyright: 1994 X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except
as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent
`make' implicit rules from creating a file called install from it
when there is no Makefile.

This script is compatible with the BSD install script, but was written
from scratch. It can only install one file at a time, a restriction
shared with many OS's install programs.

On Debian systems, the complete text of the GNU General
Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile: txtmode file-encoding=utf-8
Upstream source https://invisible-island.net/ncurses/ncurses-examples.html

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 2017-2020,2021 Thomas E. Dickey
Copyright: 1998-2016,2017 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 2003-2020,2021 by Thomas E. Dickey
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, distribute with modifications, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright

holders shall not be used in advertising or otherwise to promote the
sale, use or other dealings in this Software without prior written
authorization.

Files: install-sh
Copyright: 1994 X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining
a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN
AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNEC-
TION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not
be used in advertising or otherwise to promote the sale, use or other deal-
ings in this Software without prior written authorization from the X Consor-
tium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent
`make' implicit rules from creating a file called install from it
when there is no Makefile.

This script is compatible with the BSD install script, but was written
from scratch. It can only install one file at a time, a restriction
shared with many OS's install programs.

On Debian systems, the complete text of the GNU General
Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile: txtmode file-encoding=utf-8

1.13 universal-translator 0.18.1

1.13.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Go Playground

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.14 x-sync 0.16.0

1.14.1 Available under license :

Copyright 2009 The Go Authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS

"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.15 goautoneg 0.0.0-20191010083416-a7dc8b61c822

1.15.1 Available under license :

Copyright (c) 2011, Open Knowledge Foundation Ltd.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of the Open Knowledge Foundation Ltd. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.16 intern 1.0.0

1.16.1 Available under license :

Copyright 2005-2012, The Dojo Foundation
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
  list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.
* Neither the name of the Dojo Foundation nor the names of its contributors
  may be used to endorse or promote products derived from this software
  without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN
 NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
New BSD License

20122013 Colin Snover http://zetafleet.com
2013 SitePen, Inc. http://sitepen.com
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
* Neither the name of The Intern nor the names of its contributors may

be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE LISTED COPYRIGHT HOLDERS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Released under [Dojo Foundation CLA](http://dojofoundation.org/about/cla).
BSD-3-Clause
MIT
UNRECOGNIZED LICENSE; MD5 sum: 5e4d59e3c157354fe02610ef281f37b6
License Disclaimer:

All contents of this directory are Copyright (c) the Dojo Foundation, with the
following exceptions:
---

dojo.css:
* parts Copyright (c) 2007, Yahoo! Inc. All rights reserved.
Distributed under the terms of the BSD License

The Program includes all or portions of the following software which was obtained under the terms and conditions of the BSD License.

http://developer.yahoo.com/yui/license.html

Copyright (c) 2007, Yahoo! Inc.
All rights reserved.
Redistribution and use of this software in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the
documentation
and/or other materials provided with the distribution.
* Neither the name of Yahoo! Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without
specific prior written permission of Yahoo! Inc.
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND

ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY,
OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.
UNICODE, INC. LICENSE AGREEMENT - DATA FILES AND SOFTWARE

Unicode Data Files include all data files under the directories http://www.unicode.org/Public/, http://www.unicode.org/reports/,
and http://www.unicode.org/cldr/data/ . Unicode Software includes any source code published in the Unicode Standard or under
the directories http://www.unicode.org/Public/, http://www.unicode.org/reports/, and http://www.unicode.org/cldr/data/.
NOTICE TO USER: Carefully read the following legal agreement. BY DOWNLOADING, INSTALLING, COPYING OR
OTHERWISE USING UNICODE INC.'S DATA FILES ("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"), YOU
UNEQUIVOCALLY ACCEPT, AND AGREE TO BE BOUND BY, ALL OF THE TERMS AND CONDITIONS OF THIS
AGREEMENT. IF YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE THE DATA FILES OR SOFTWARE.

COPYRIGHT AND PERMISSION NOTICE
Copyright 1991-2007 Unicode, Inc. All rights reserved. Distributed under the Terms of Use in http://www.unicode.org/copyright.html.

Permission
is hereby granted, free of charge, to any person obtaining a copy of the Unicode data files and any associated documentation (the "Data Files") or Unicode software and any associated documentation (the "Software") to deal in the Data
Files or Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell
copies of the Data Files or Software, and to permit persons to whom the Data Files or Software are furnished to do so, provided
that (a) the above copyright notice(s) and this permission notice appear with all copies of the Data Files or Software, (b) both the
above copyright notice(s) and this permission notice appear in associated documentation, and (c) there is clear notice in each modified Data File

or in the Software as well as in the documentation associated with the Data File(s) or Software that the data or software has been modified.
THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED,
INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE
AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS
INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES,
OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF
CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THE DATA FILES OR SOFTWARE.
Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other
dealings in these Data Files or Software without prior written authorization of the copyright holder.

1.17 aws-sdk-go-v2-internal-configsources 1.4.2

1.17.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection

```
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer
```

```
// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
```

```
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
```

```
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
```

```
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
```

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS

```
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
  - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
```

```
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string
```

```
 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
```

```
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
 err != nil {
  return err
 }
```

```
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
```

```
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
```

```
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
```

```
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
```

```
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string
```

```
// License entitlements.
//
// This member is required.
Entitlements []types.EntitlementData

// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string
```

```
 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
```

```
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
```

```
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
```

```
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
```

```
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/DeregisterSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                 "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider
resource to deregister.</p>",
                 "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
          "type": "structure",
          "members": {
            "Name": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of name to filter by.</p>"
               }
            },
            "Values": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
              }
            },
            "Operator": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/GetRegisteredSubscriptionProvider"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

          "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
              }
            },
            "SubscriptionProviderStatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
              }
            },
            "LastSuccessfulDataRetrievalTime": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
          "type": "operation",
          "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
```

```
            "uri": "/subscription/GetServiceSettings"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
          "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
          },
          "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
          },
          "AccountID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
          },
          "Region": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
          },
          "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
              "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For
more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-
```

subscriptions-usage-operation.html\">Usage\n operation values in the License Manager User Guide. "
}
},
"ProductCode": {
"target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
"traits": {
"smithy.api#documentation": " The product code for the instance. For more information, see Usage\n operation values in the License Manager User Guide . "
}
},
"LastUpdatedTime": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The time in which the last discovery updated the instance details. "
}
},
"SubscriptionName": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The name of the license subscription that the instance uses. "
}
},
"OsVersion": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The operating system software version that runs on your instance. "
}
},
"SubscriptionProviderCreateTime": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The timestamp when you registered
the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses. "
}
},
"SubscriptionProviderUpdateTime": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The timestamp from the last time that the instance synced with the registered \n\t\t\tthird-party Linux subscription provider. "
}
},
"DualSubscription": {
"target": "smithy.api#String",

```
            "traits": {
                "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for \n\t\t\tthe same software on your instance.</p>"
            }
        },
        "RegisteredWithSubscriptionProvider": {
            "target": "smithy.api#String",
            "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta third-party Linux subscription provider that you've registered with License Manager.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
        "smithy.api#error": "server"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
      "type": "service",
      "version": "2018-05-10",
      "operations": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
        },
```

```
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
     },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
    }
  ],
  "traits": {
    "aws.api#service": {
      "sdkId": "License Manager Linux Subscriptions",
       "arnNamespace": "license-manager-linux-subscriptions",
      "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
    },
    "aws.auth#sigv4": {
      "name": "license-manager-linux-subscriptions"
    },
    "aws.protocols#restJson1": {},
    "smithy.api#cors": {
      "additionalAllowedHeaders": [
        "*",
        "content-type",
        "x-amz-content-sha256",
        "x-amz-user-agent",
        "x-amzn-platform-id",
        "x-amzn-trace-id"
      ],
      "additionalExposedHeaders": [
```

```
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
```

```
                    }
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }

    ],
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]

}
                            ],
                            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                            "type": "error"
                        },
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": {
                                    "ref": "Endpoint"
                                },
                                "properties": {},
                                "headers": {}
```

```
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"

    }
    ],
    "type": "tree"
},
{
    "conditions": [],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Region"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {

    "fn": "aws.partition",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ],
                            "assign": "PartitionResult"
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {

                                "ref": "UseFIPS"
                                        },
```

```
                true
              ]
            },
            {
              "fn": "booleanEquals",
              "argv": [
                {
                  "ref": "UseDualStack"
                },
                true
              ]
            }

  ],
                "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    true,
                    {
                      "fn": "getAttr",
                      "argv": [
                        {
                          "ref": "PartitionResult"

        },
                            "supportsFIPS"
                        ]
                      }
                    ]
                  },
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [

                         {
                              "ref": "PartitionResult"
                            },
                            "supportsDualStack"
                        ]
                      }
                    ]
```

```
                }
            ],
            "rules": [
                {
                    "conditions": [],

    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-linux-subscriptions-fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],

                "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both",
            "type": "error"
        }
    ],
    "type": "tree"
},
{

    "conditions": [
        {
            "fn": "booleanEquals",
            "argv": [
                {
                    "ref": "UseFIPS"
                },
                true
            ]
        }
    ],
    "rules": [
        {
```

```
                "conditions": [
                    {

            "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true

                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS is enabled
 but this partition does not support FIPS",
                "type": "error"
            }
        ],
        "type": "tree"
```

```
                },
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseDualStack"
                        },
                        true

            ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            true,
                            {
                              "fn": "getAttr",
                              "argv": [
                                {

                                  "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                              ]
                            }
                          ]
                        }
                      ],
                      "rules": [
                        {
                          "conditions": [],
                          "rules": [

    {
                                "conditions": [],
                                "endpoint": {
                                  "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                  "properties": {},
                                  "headers": {}
                                },
                                "type": "endpoint"
```

```
                                        }
                                    ],
                                    "type": "tree"

                            }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
]
},
```

```
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
```

```
                }

        },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

 "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
             },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
```

```
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }

     },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
```

```
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

        "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
```

```
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
```

```
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
```

```
            },
            "params": {
              "UseFIPS": false,
              "UseDualStack": false,
              "Endpoint": "https://example.com"
            }
          },
          {

            "documentation": "For custom endpoint with fips enabled and dualstack disabled",
            "expect": {
              "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": true,
              "UseDualStack": false,
              "Endpoint": "https://example.com"
            }
          },
          {
            "documentation": "For custom endpoint with fips disabled and dualstack enabled",
            "expect": {
              "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
            },
            "params": {

"Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": true,
              "Endpoint": "https://example.com"
            }
          },
          {
            "documentation": "Missing region",
            "expect": {
              "error": "Invalid Configuration: Missing Region"
            }
          }
        ],
        "version": "1.0"
      }
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
```

```
                {
                    "name": "Enabled",
                    "value": "Enabled",
                    "documentation": "Enabled LinuxSubscriptionsDiscovery"

            },
                {
                    "name": "Disabled",
                    "value": "Disabled",
                    "documentation": "Disabled LinuxSubscriptionsDiscovery"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
        "type": "structure",
        "members": {
            "SourceRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "OrganizationIntegration": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
                "traits": {
                    "smithy.api#documentation":
"<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },

  {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptionInstances"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "Instances"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n    \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n              <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceType</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>ProductCode</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Region</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Status</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>UsageOperation</code>\n              </p>\n            </li>\n          </ul>\n          <p>For each filter, you can use
```

```
one of the following <code>Operator</code>
 values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n             <p>\n
<code>contains</code>\n             </p>\n          </li>\n          <li>\n             <p>\n
<code>equals</code>\n             </p>\n          </li>\n          <li>\n             <p>\n
<code>Notequal</code>\n             </p>\n          </li>\n        </ul>"
                }
             },
             "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                   "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
             },
             "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                   "smithy.api#length": {
                      "min": 1,
                      "max": 16384
                   }
                }
             }
          },
          "traits": {
             "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
       },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
          "type": "structure",
          "members": {
             "Instances": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
                "traits": {
                   "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
                }
             },
             "NextToken": {

           "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
             }
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
           {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptions"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",

   "items": "Subscriptions"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
```

<code>Subscription</code> with an optional operator to see subscriptions that match,\n partially match, or don't match a certain subscription's name. \n The valid names for this filter are: \n \n \n \n <code>Subscription</code>\n \n \n \n The valid Operators for this filter are: \n \n \n \n <code>contains</code>\n \n \n \n \n <code>equals</code>\n \n \n \n \n <code>Notequal</code>\n \n \n "
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": " The maximum items to return in a request. "
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response. ",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "Subscriptions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
            "traits": {
              "smithy.api#documentation": " An array that contains subscription objects. "
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects. "

```
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListRegisteredSubscriptionProviders"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "RegisteredSubscriptionProviders"
          }
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSources": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
            "traits": {
              "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }

  },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
          "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

           "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
```

```
    },
    "traits": {
      "smithy.api#output": {}
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
    },
    "errors": [
      {

 "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
      }
    ],
    "traits": {
      "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
      "smithy.api#http": {
        "method": "GET",
        "uri": "/tags/{resourceArn}"
      },
      "smithy.api#readonly": {}
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
    "type": "structure",
    "members": {
      "resourceArn": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
         "traits": {
           "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
           "smithy.api#httpLabel": {},
           "smithy.api#required": {}
         }
      }
    },
```

```
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
                    "documentation": "Equal operator"
                },
                {
                    "name": "NOT_EQUAL",
                    "value": "NotEqual",
                    "documentation": "Not equal operator"
                },
                {
                    "name": "CONTAINS",
                    "value": "Contains",
                    "documentation": "Contains operator"
                }
            ],
            "smithy.api#length": {
                "min": 1,
                "max": 20
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
```

```
            "smithy.api#enum": [
                {
                    "name": "Enabled",
                    "value": "Enabled",
                    "documentation": "Enabled OrganizationIntegration"
                },
                {
                    "name": "Disabled",
                    "value": "Disabled",
                    "documentation": "Disabled OrganizationIntegration"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/RegisterSubscriptionProvider"
```

```
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
            "smithy.api#required": {}
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
            "smithy.api#required": {}
          }
        },
        "Tags": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
          "traits": {
            "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
          }
        },
        "SubscriptionProviderArn": {
          "target": "smithy.api#String",
          "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
                "traits": {
                "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                 "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
```

```
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed
third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and
license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider,
License Manager can get subscription data from the registered provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"
```

```
}
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "InProgress",
          "value": "InProgress",
          "documentation": "InProgress status"
        },
        {
          "name": "Completed",
          "value": "Completed",
          "documentation": "Completed status"
        },
        {
          "name": "Successful",
          "value": "Successful",
          "documentation": "Successful status"
        },
        {
          "name": "Failed",
          "value": "Failed",
          "documentation": "Failed status"
        }
      ]
    }
  },

 "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
    "type": "list",
    "member": {
      "target": "smithy.api#String",
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        }
      }
    },
    "traits": {
      "smithy.api#length": {
        "min": 1,
        "max": 100
      },
      "smithy.api#uniqueItems": {}
```

```
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
            "Name":
{
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the subscription.</p>"
                }
            },
            "Type": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [

 {
            "name": "RedHat",
            "value": "RedHat",
            "documentation": "RedHat subscription provider namespace"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "ACTIVE",
            "value": "ACTIVE",
            "documentation": "ACTIVE status"
          },
          {
            "name": "INVALID",
            "value": "INVALID",

  "documentation": "INVALID status"
          },
          {
            "name": "PENDING",
            "value": "PENDING",
            "documentation": "PENDING status"
          }
        ]
      }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
      "type": "structure",
      "members":
{
        "resourceArn": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services resource to which to add the specified \n\t\t\tmetadata tags.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
             "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
```

```
            "tagKeys": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
               "traits": {

             "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                  "smithy.api#httpQuery": "tagKeys",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/UpdateServiceSettings"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n integration has been enabled, and which Regions data will be aggregated from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target": "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n integration has been enabled, and which Regions data will be aggregated
```

```
from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
          }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
          "type": "structure",
          "members": {
              "message": {
                  "target": "smithy.api#String"
              }
          },
          "traits": {
              "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
              "smithy.api#error": "client"
          }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
```

```
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
```

```
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
```

```
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType
```

```
 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
```

```
 return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
```

```
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
```

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",

```
            "traits": {
                "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
        },
        "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
        },
        "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
                "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
    "type": "structure",
    "members": {
      "DomainName": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
        }
      },
      "DomainIpv4List": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
        "traits": {
          "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
          "smithy.api#length": {
            "min": 1,
            "max": 2
          }
        }
      },
      "DomainCredentialsProvider": {
        "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
              },
              "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>Contains network access and credential details that are needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
                }
              ]
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#Arn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
 {
            "type": "operation",
            "input": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n          </note>",
            "smithy.api#http":
 {
              "code": 200,
              "method": "POST",
              "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
          "type": "structure",
          "members": {
            "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
              "smithy.api#required": {}
            }
          },
           "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },

        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
```

```
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
              "traits": {
                "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
```

```
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}

      }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Directory": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
```

```
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary":
{
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
         "type": "structure",
         "members": {
            "Subnets": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                  "smithy.api#length": {
                     "min": 1
                  },
```

```
    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
              }
            },
            "FailureMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
          "type": "list",
          "member": {

            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The date of the last status check.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },

    "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                    "smithy.api#required": {}
                }
```

```
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
```

```
    "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
    "type": "structure",
    "members": {
      "message": {
        "target": "smithy.api#String"
      }
    },
    "traits": {
      "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
       "smithy.api#error": "server",
      "smithy.api#httpError": 500
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
      "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
       },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
      },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
```

```
        "smithy.api#cors": {
            "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",

            "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
                "Region":
{
                    "builtIn": "AWS::Region",
                    "required": false,
                    "documentation": "The AWS region used to dispatch the request.",
                    "type": "String"
                },
                "UseDualStack": {
                    "builtIn": "AWS::UseDualStack",
                    "required": true,
                    "default": false,
                    "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                    "type": "Boolean"
                },
                "UseFIPS": {
                    "builtIn": "AWS::UseFIPS",
                    "required": true,
```

```
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
            "type": "Boolean"
          },
          "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
             ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [
                  {

                    "fn": "booleanEquals",
                    "argv": [
                      {
```

```
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "aws.partition",

                      "argv": [
                        {
                          "ref": "Region"
                        }
                      ],
                      "assign": "PartitionResult"
                    }
```

```
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseFIPS"
                                    },
```

true

```
                                ]
                            },
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseDualStack"
                                    },
                                    true
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
                                    {
```

"fn": "booleanEquals",

```
                                        "argv": [
                                            true,
                                            {
                                                "fn": "getAttr",
                                                "argv": [
                                                    {
                                                        "ref": "PartitionResult"
                                                    },
                                                    "supportsFIPS"
                                                ]
                                            }
                                        ]
                                    },
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            true,
```

```
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }

                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }

    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                    "type": "error"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [

 {
                            "ref": "UseFIPS"
                        },
                        true
                    ]
```

```
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "fn": "getAttr",
                                    "argv": [

        {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

    "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS is enabled but this partition does not support FIPS",
                    "type": "error"

}
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {

        "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]

          }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

            ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
```

```
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                            "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
{
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint":
{
                  "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
```

```
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
```

```
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

    },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",

  "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
```

```
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

     "endpoint": {
            "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
 false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
```

```
                },
                {
                  "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                  "expect": {
                    "error": "Invalid Configuration:
 Dualstack and custom endpoint are not supported"
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
 "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
 \n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
 \n\t\t\tlicense server.</p>"
              }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>"
              }
            },
            "ServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
              }
            },
            "LicenseServerEndpointId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits":
```

```
{
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
              }
            },
            "LicenseServerEndpointProvisioningStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
              "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
              }
            },
            "LicenseServers": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
              }
            },

           "CreationTime": {
              "target": "smithy.api#Timestamp",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
          "type": "string"
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

      "type": "string",
          "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
              "name": "PROVISIONED",
              "value": "PROVISIONED",
              "documentation": ""
            },
            {
              "name": "DELETING",
              "value": "DELETING",
              "documentation": ""
            },
            {
              "name": "DELETION_FAILED",
              "value": "DELETION_FAILED",
              "documentation": ""

           },
            {
              "name": "DELETED",
              "value": "DELETED",
              "documentation": ""
            }
          ]
       }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
       "type": "string",
       "traits": {
          "smithy.api#enum": [
            {
              "name": "HEALTHY",
              "value": "HEALTHY",
              "documentation": ""
            },
            {
              "name": "UNHEALTHY",
              "value": "UNHEALTHY",
              "documentation": ""
            },
```

```
                {
                    "name": "NOT_APPLICABLE",
                    "value": "NOT_APPLICABLE",
                    "documentation": ""
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
        "type": "structure",
        "members": {
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
```

```
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n        <li>\n        <p>Product</p>\n        </li>\n
        <li>\n        <p>DirectoryId</p>\n        </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                    "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
 that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                    "smithy.api#required": {}
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
 empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
 next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
```

```
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },

{
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
      }
    ],
    "traits": {
      "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
      "smithy.api#http": {
        "code": 200,
        "method": "POST",
        "uri": "/instance/ListInstances"
      },
      "smithy.api#paginated": {
        "inputToken": "NextToken",
        "outputToken": "NextToken",
        "pageSize": "MaxResults",
        "items": "InstanceSummaries"
      }
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
    "type": "structure",
    "members":
```

```
{
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
      <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
      "type": "structure",
      "members": {
        "InstanceSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
          }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/license-server/ListLicenseServerEndpoints"
        },

      "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "LicenseServerEndpoints"
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
      "type": "structure",
      "members": {
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n        <li>\n          <p>IdentityProviderArn</p>\n        </li>\n      </ul>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
      "type": "structure",
      "members": {
        "LicenseServerEndpoints": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
"operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " Lists the user-based subscription products available from an identity
provider. ",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"

```
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
```

```
This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "ProductUserSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

           }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
```

```
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
    "type": "structure",
    "members": {
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
```

```
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {

            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
               }
            },
            "SubscriptionStartDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The start date of a subscription.</p>"
               }
            },
            "SubscriptionEndDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The end date of a subscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
         "type":
 "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
         "type": "structure",
         "members": {
```

```
            "RdsSalCredentialsProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
```

```
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
          "type": "structure",
          "members": {
            "IdentityProvider": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>",
                "smithy.api#required": {}
              }
            },
            "Settings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
              "traits":
 {
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
```

```
                    "min": 1
                }
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
    "type": "string",
    "traits": {
        "smithy.api#length": {

     "min": 5,
            "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
    "type": "structure",
    "members": {
        "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more servers.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
    "type": "union",
    "members": {
        "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

    "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

           "traits": {
              "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688
communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
              "smithy.api#required": {}
            }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StartProductSubscription"
            }

      }
       },
       "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
          "type": "structure",
          "members": {
             "Username": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                   "smithy.api#required": {}
                }
             },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                   "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                   "smithy.api#required": {}
                }
             },
             "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                   "smithy.api#required": {}
                }
             },
             "Domain": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
                }
             },
             "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                   "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
                }
```

```
  }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

   },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StopProductSubscription"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
               }
            },
            "IdentityProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }

    }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

 "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
 {
        "type": "structure",
        "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {
```

```
      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
```

```
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
```

```
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
```

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation

spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.18 golang-lru 2.0.7

1.18.1 Available under license :

Copyright (c) 2014 HashiCorp, Inc.

Mozilla Public License, version 2.0

1. Definitions

1.1. "Contributor"

means each individual or legal entity that creates, contributes to the creation of, or owns Covered Software.

1.2. "Contributor Version"

means the combination of the Contributions of others (if any) used by a Contributor and that particular Contributor's Contribution.

1.3. "Contribution"

means Covered Software of a particular Contributor.

1.4. "Covered Software"

means Source Code Form to which the initial Contributor has attached the notice in Exhibit A, the Executable Form of such Source Code Form, and Modifications of such Source Code Form, in each case including portions thereof.

1.5. "Incompatible With Secondary Licenses"
means

a. that the initial Contributor has attached the notice described in Exhibit B to the Covered Software; or

b. that the Covered Software was made available under the terms of version 1.1 or earlier of the License, but not also under the terms of a Secondary License.

1.6. "Executable Form"

means any form of the work other than Source Code Form.

1.7. "Larger Work"

means a work that combines Covered Software with other material, in a separate file or files, that is not Covered Software.

1.8. "License"

means this document.

1.9. "Licensable"

means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently, any and all of the rights conveyed by this License.

1.10. "Modifications"

means any of the following:

a. any file in Source Code Form that results from an addition to, deletion from, or modification of the contents of Covered Software; or

b. any new file in Source Code Form that contains any Covered Software.

1.11. "Patent Claims" of a Contributor

means any patent claim(s), including without limitation, method, process, and apparatus claims, in any patent Licensable by such Contributor that would be infringed, but for the grant of the License, by the making, using, selling, offering for sale, having made, import, or transfer of either its Contributions or its Contributor Version.

1.12. "Secondary License"

means either the GNU General Public License, Version 2.0, the GNU Lesser General Public License, Version 2.1, the GNU Affero General Public License, Version 3.0, or any later versions of those licenses.

1.13. "Source Code Form"

means the form of the work preferred for making modifications.

1.14. "You" (or "Your")

means an individual or a legal entity exercising rights under this License. For legal entities, "You" includes any entity that controls, is controlled by, or is under common control with You. For purposes of this definition, "control" means (a) the power, direct or indirect, to cause the direction or

management of such entity, whether by contract or
otherwise, or (b) ownership of more than fifty percent (50%) of the
outstanding shares or beneficial ownership of such entity.

2. License Grants and Conditions

2.1. Grants

Each Contributor hereby grants You a world-wide, royalty-free,
non-exclusive license:

a. under intellectual property rights (other than patent or trademark)
Licensable by such Contributor to use, reproduce, make available,
modify, display, perform, distribute, and otherwise exploit its
Contributions, either on an unmodified basis, with Modifications, or
as part of a Larger Work; and

b. under Patent Claims of such Contributor to make, use, sell, offer for
sale, have made, import, and otherwise transfer either its
Contributions or its Contributor Version.

2.2. Effective Date

The licenses granted in Section 2.1 with respect to any Contribution
become effective for each Contribution
on the date the Contributor first
distributes such Contribution.

2.3. Limitations on Grant Scope

The licenses granted in this Section 2 are the only rights granted under
this License. No additional rights or licenses will be implied from the
distribution or licensing of Covered Software under this License.
Notwithstanding Section 2.1(b) above, no patent license is granted by a
Contributor:

a. for any code that a Contributor has removed from Covered Software; or

b. for infringements caused by: (i) Your and any other third party's
modifications of Covered Software, or (ii) the combination of its
Contributions with other software (except as part of its Contributor
Version); or

c. under Patent Claims infringed by Covered Software in the absence of
its Contributions.

This License does not grant any rights in the trademarks, service marks,

or logos of any Contributor (except as may be necessary to comply with the notice requirements in Section 3.4).

2.4. Subsequent Licenses

No Contributor makes additional grants as a result of Your choice to distribute the Covered Software under a subsequent version of this License (see Section 10.2) or under the terms of a Secondary License (if permitted under the terms of Section 3.3).

2.5. Representation

Each Contributor represents that the Contributor believes its Contributions are its original creation(s) or it has sufficient rights to grant the rights to its Contributions conveyed by this License.

2.6. Fair Use

This License is not intended to limit any rights You have under applicable copyright doctrines of fair use, fair dealing, or other equivalents.

2.7. Conditions

Sections 3.1, 3.2, 3.3, and 3.4 are conditions of the licenses granted in Section 2.1.

3. Responsibilities

3.1. Distribution of Source Form

All distribution of Covered Software in Source Code Form, including any Modifications that You create or to which You contribute, must be under the terms of this License. You must inform recipients that the Source Code Form of the Covered Software is governed by the terms of this License, and how they can obtain a copy of this License. You may not attempt to alter or restrict the recipients' rights in the Source Code Form.

3.2. Distribution of Executable Form

If You distribute Covered Software in Executable Form then:

a. such Covered Software must also be made available in Source Code Form, as described in Section 3.1, and You must inform recipients of the

Executable Form how they can obtain a copy of such Source Code Form by reasonable means in a timely manner, at a charge no more than the cost of distribution to the recipient; and

b. You may distribute such Executable Form under the terms of this License, or sublicense it under different terms, provided that the license for the Executable Form does not attempt to limit or alter the recipients' rights in the Source Code Form under this License.

3.3. Distribution of a Larger Work

You may create and distribute a Larger Work under terms of Your choice, provided that You also comply with the requirements of this License for the Covered Software. If the Larger Work is a combination of Covered Software with a work governed by one or more Secondary Licenses, and the Covered Software is not Incompatible With Secondary Licenses, this License permits You to additionally distribute such Covered Software under the terms of such Secondary License(s), so that the recipient of the Larger Work may, at their option, further distribute the Covered Software under the terms of either this License or such Secondary License(s).

3.4. Notices

You may not remove or alter the substance of any license notices (including copyright notices, patent notices, disclaimers of warranty, or limitations of liability) contained within the Source Code Form of the Covered Software, except that You may alter any license notices to the extent required to remedy known factual inaccuracies.

3.5. Application of Additional Terms

You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, You may do so only on Your own behalf, and not on behalf of any Contributor. You must make it absolutely clear that any such warranty, support, indemnity, or liability obligation is offered by You alone, and You hereby agree to indemnify every Contributor for any liability incurred by such Contributor as a result of warranty, support, indemnity or liability terms You offer. You may include additional disclaimers of warranty and limitations of liability specific to any jurisdiction.

4. Inability to Comply Due to Statute or Regulation

If it is impossible for You to comply with any of the terms of this License with respect to some or all of the Covered Software due to statute, judicial order, or regulation then You must: (a) comply with the terms of this License to the maximum extent possible; and (b) describe the limitations and the code they affect. Such description must be placed in a text file included with all distributions of the Covered Software under this License. Except to the extent prohibited by statute or regulation, such description must be sufficiently detailed for a recipient of ordinary skill to be able to understand it.

5. Termination

5.1. The rights granted under this License will terminate automatically if You fail to comply with any of its terms. However, if You become compliant, then the rights granted under this License from a particular Contributor are reinstated (a) provisionally, unless and until such Contributor explicitly and finally terminates Your grants, and (b) on an ongoing basis, if such Contributor fails to notify You of the non-compliance by some reasonable means prior to 60 days after You have come back into compliance. Moreover, Your grants from a particular Contributor are reinstated on an ongoing basis if such Contributor notifies You of the non-compliance by some reasonable means, this is the first time You have received notice of non-compliance with this License from such Contributor, and You become compliant prior to 30 days after Your receipt of the notice.

5.2. If You initiate litigation against any entity by asserting a patent infringement claim (excluding declaratory judgment actions, counter-claims, and cross-claims) alleging that a Contributor Version directly or indirectly infringes any patent, then the rights granted to You by any and all Contributors for the Covered Software under Section 2.1 of this License shall terminate.

5.3. In the event of termination under Sections 5.1 or 5.2 above, all end user license agreements (excluding distributors and resellers) which have been validly granted by You or Your distributors under this License prior to termination shall survive termination.

6. Disclaimer of Warranty

Covered Software is provided under this License on an "as is" basis, without warranty of any kind, either expressed, implied, or statutory, including, without limitation, warranties that the Covered Software is free of defects, merchantable, fit for a particular purpose or non-infringing. The entire risk as to the quality and performance of the Covered Software is with You. Should any Covered Software prove defective in any respect,

You (not any Contributor) assume the cost of any necessary servicing, repair, or correction. This disclaimer of warranty constitutes an essential part of this License. No use of any Covered Software is authorized under this License except under this disclaimer.

7. Limitation of Liability

Under no circumstances and under no legal theory, whether tort (including negligence), contract, or otherwise, shall any Contributor, or anyone who distributes Covered Software as permitted above, be liable to You for any direct, indirect, special, incidental, or consequential damages of any character including, without limitation, damages for lost profits, loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses, even if such party shall have been informed of the possibility of such damages. This limitation of liability shall not apply to liability for death or personal injury resulting from such party's negligence to the extent applicable law prohibits such limitation. Some jurisdictions do not allow the exclusion or limitation of incidental or consequential damages, so this exclusion and limitation may not apply to You.

8. Litigation

Any litigation relating to this License may be brought only in the courts of a jurisdiction where the defendant maintains its principal place of business and such litigation shall be governed by laws of that jurisdiction, without reference to its conflict-of-law provisions. Nothing in this Section shall prevent a party's ability to bring cross-claims or counter-claims.

9. Miscellaneous

This License represents the complete agreement concerning the subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. Any law or regulation which provides that the language of a contract shall be construed against the drafter shall not be used to construe this License against a Contributor.

10. Versions of the License

10.1. New Versions

Mozilla Foundation is the license steward.

Except as provided in Section
10.3, no one other than the license steward has the right to modify or publish new versions of this License. Each version will be given a distinguishing version number.

10.2. Effect of New Versions

You may distribute the Covered Software under the terms of the version of the License under which You originally received the Covered Software, or under the terms of any subsequent version published by the license steward.

10.3. Modified Versions

If you create software not governed by this License, and you want to create a new license for such software, you may create and use a modified version of this License if you rename the license and remove any references to the name of the license steward (except to note that such modified license differs from this License).

10.4. Distributing Source Code Form that is Incompatible With Secondary Licenses If You choose to distribute Source
Code Form that is
Incompatible With Secondary Licenses under the terms of this version of the License, the notice described in Exhibit B of this License must be attached.

Exhibit A - Source Code Form License Notice

This Source Code Form is subject to the
terms of the Mozilla Public License, v.
2.0. If a copy of the MPL was not
distributed with this file, You can
obtain one at
http://mozilla.org/MPL/2.0/.

If it is not possible or desirable to put the notice in a particular file, then You may include the notice in a location (such as a LICENSE file in a relevant directory) where a recipient would be likely to look for such a notice.

You may add additional accurate notices of copyright ownership.

Exhibit B - "Incompatible With Secondary Licenses" Notice

This Source Code Form is "Incompatible
With Secondary Licenses", as defined by
the Mozilla Public License, v. 2.0.

This license applies to simplelru/list.go

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED.
 IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
// Copyright (c) HashiCorp, Inc.
// SPDX-License-Identifier: MPL-2.0

1.19 alpine-keys 2.5-r0

1.19.1 Available under license :

MIT License

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED,

INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE
 OR OTHER DEALINGS IN THE SOFTWARE.
Maintainer: Natanael Copa <ncopa@alpinelinux.org>
pkgname=alpine-keys
pkgver=2.5
pkgrel=0
pkgdesc="Public keys for Alpine Linux packages"
url="https://alpinelinux.org"
we install arch specific keys to /etc so we cannot do arch=noarch
arch="all"
license="MIT"
replaces="alpine-base"

1.20 shadow 4.16.0-r1

1.20.1 Available under license :

SPDX-License-Identifier: BSD-3-Clause

All files under this project either

1. fall under the BSD 3 clause license (by default).

2. carry an SPDX header declaring what license applies.

or

3. list a full custom license

This software is originally

* Copyright (c) 1989 - 1994, Julianne Frances Haugh

* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. The name of the copyright holders or contributors may not be used to

```
*    endorse or promote products derived from this software without
*    specific
 prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
* ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
* LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED.  IN NO EVENT SHALL THE COPYRIGHT
* HOLDERS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
* LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
* THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
* (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
* OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
# Contributor: Patrycja Rosa <alpine@ptrcnull.me>
# Maintainer: Patrycja Rosa <alpine@ptrcnull.me>
pkgname=bsd-compat-headers
pkgver=0.7.2
pkgrel=6
pkgdesc="BSD compatibility headers (cdefs, queue, tree)"
url="https://gitlab.alpinelinux.org/alpine/aports"
arch="noarch"
license="BSD-2-Clause AND BSD-3-Clause"
source="
 cdefs.h
 queue.h
 tree.h
"
builddir="$srcdir"
options="!check" # just headers

package() {
 mkdir -p "$pkgdir"
 install -Dm644 -t "$pkgdir"/usr/include/sys \
  cdefs.h queue.h tree.h
}
sha512sums="
37c8fc73c7aea7b490f7850927e2bb91d12137c9e59e22c084146d515696dbc7973b5de92f4c987ba080dd2502ba8312
7006442c3f019b6447a620c0cae73178  cdefs.h
2f0d5e6e4dc3350285cf17009265dddcbe12431c111868eea39bc8cb038ab7c1f2acacbb21735c4e9d4a1fd106a8fc0f86
11ea33987d4faba37dde5ce6da0750  queue.h
d9ac210d81feb8ad2655bc80fb065d3fe20ae4417b32b4a1711e6738a4870140005c13373b5d1846ef3ce5ae6da45f2da
cef2092881eded0a2e94f6a07752ef3  tree.h
"
# Automatically generated by apkbuild-cpan, template 4
# Contributor: Valery Kartel <valery.kartel@gmail.com>
# Maintainer: Celeste <cielesti@protonmail.com>
```

```
maintainer="Celeste <cielesti@protonmail.com>"
pkgname=perl-bsd-resource
pkgver=1.2911
pkgrel=10
#_pkgreal is used by apkbuild-cpan to find modules at MetaCpan
_pkgreal=BSD-Resource
pkgdesc="Perl extension implements the BSD process resource limit functions"
url="https://metacpan.org/release/BSD-Resource/"
arch="all"
license="Artistic-2.0 OR LGPL-2.0"
depends="perl"
makedepends="perl-dev"
subpackages="$pkgname-doc"
source="https://cpan.metacpan.org/authors/id/J/JH/JHI/BSD-Resource-$pkgver.tar.gz"
builddir="$srcdir/$_pkgreal-$pkgver"

build() {
 export CFLAGS=$(perl -MConfig -E 'say $Config{ccflags}')
 PERL_MM_USE_DEFAULT=1 perl -I. Makefile.PL \
  INSTALLDIRS=vendor \
  NO_PACKLIST=1 \
  NO_PERLLOCAL=1
 make
}

check() {
 export CFLAGS=$(perl -MConfig -E 'say $Config{ccflags}')
 make test
}

package() {
 make DESTDIR="$pkgdir" install
}

sha512sums="
d0032d41c7c0468ed1c6d8f57b885f6cb97a5039d754c8cb60b2067daedaf53bd15fb6561a3d0f828df16dfa5417f663b
8065ba65f4fea16dc9262728b3b6b85
  BSD-Resource-1.2911.tar.gz
"
# Contributor: Fabian Affolter <fabian@affolter-engineering.ch>
# Maintainer: Fabian Affolter <fabian@affolter-engineering.ch>
pkgname=py3-flake8-copyright
_pkgname=flake8-copyright
pkgver=0.2.4
pkgrel=3
pkgdesc="Extension for flake8 which checks for copyrights"
options="!check" # No testsuite
url="https://github.com/savoirfairelinux/flake8-copyright"
```

```
arch="noarch"
license="MIT"
depends="py3-flake8 py3-setuptools"
makedepends="py3-gpep517 py3-wheel"
subpackages="$pkgname-pyc"
source="https://files.pythonhosted.org/packages/source/${_pkgname:0:1}/$_pkgname/$_pkgname-$pkgver.tar.gz"
builddir="$srcdir"/$_pkgname-$pkgver

replaces="py-flake8-copyright"                  # Backwards compatibility
provides="py-flake8-copyright=$pkgver-r$pkgrel" # Backwards compatibility

build() {
 gpep517 build-wheel \
  --wheel-dir .dist \
  --output-fd 3 3>&1 >&2
}

package() {
 gpep517 install-wheel --destdir "$pkgdir" \
  .dist/*.whl
}

sha512sums="
a6ab47e1bb715618f075c51f398e18180404871b3b0faf1c2d30701d5203db6bc23771bf22ffb5bafcd8ee856b9b64237
b316bd503ae7dceed6ca284ccd5a74d
  flake8-copyright-0.2.4.tar.gz
"
# Contributor: Dhruvin Gandhi <contact@dhru.vin>
# Maintainer: Patrycja Rosa <alpine@ptrcnull.me>
pkgname=py3-license-expression
_pkgname=license_expression
pkgver=30.4.0
pkgrel=0
pkgdesc="Library to parse, compare, simplify and normalize license expressions"
url="https://github.com/nexB/license-expression"
arch="noarch"
license="Apache-2.0"
depends="python3 py3-boolean.py"
makedepends="py3-setuptools py3-setuptools_scm py3-gpep517 py3-wheel"
checkdepends="py3-pytest py3-pytest-xdist"
subpackages="$pkgname-pyc"
source="https://files.pythonhosted.org/packages/source/l/$_pkgname/$_pkgname-$pkgver.tar.gz"
builddir="$srcdir/$_pkgname-$pkgver"

build() {
 gpep517 build-wheel \
  --wheel-dir .dist \
  --output-fd 3 3>&1 >&2
```

```
}

check() {
 python3 -m venv --clear --without-pip --system-site-packages .testenv
 .testenv/bin/python3 -m installer .dist/*.whl
 .testenv/bin/python3 -m pytest
}

package() {
 python3 -m installer -d "$pkgdir" \
  .dist/*.whl
}

sha512sums="
cc7cd6b5bd8ea4c99b66f074871ffd7cc78b3e8b1b0d3afd9b95efdb7147c8293db2fac977d684fc34d3d60bd79066a06
dc2bff0a38b130d9d83c63538502db1
  license_expression-30.4.0.tar.gz
"
# License

All new source code committed to the shadow project is assumed to be made
available under the [BSD-3-Clause](../../COPYING) license unless the submitter
specifies another license at that time. The shadow maintainers reserve the
right to refuse a submission if the license is deemed incompatible with the
goals of the project.

**Note**: old code may be made available under another license, check the
license tag for each file to get additional information.
# Contributor: Maxim Karasev <begs@disroot.org>
# Maintainer: mio <miyopan@e.email>
pkgname=bsd-games
pkgver=3.3
pkgrel=2
pkgdesc="traditional text mode games from BSD"
url="https://bsd-games.sourceforge.io/"
arch="all"
license="BSD-3-Clause"
install="$pkgname.post-install"
makedepends="ncurses-dev coreutils" # configure causes busybox expr error
subpackages="$pkgname-doc"
source="https://sourceforge.net/projects/bsd-games/files/bsd-games-$pkgver.tar.gz
 0001-bsd-games-scores-dir.patch
 "
options="!check" # no tests

build() {
 # some GNU autoconf options are ignored, but it works
 ./configure \
```

```
  --build=$CBUILD \
  --host=$CHOST \
  --prefix=/usr \
  --sysconfdir=/etc \
  --mandir=/usr/share/man \
  --scoredir=/usr/share/$pkgname
 make
}

package() {
 make DESTDIR="$pkgdir" install
 install -Dm644 LICENSE "$pkgdir"/usr/share/licenses/bsd-games/LICENSE
}

sha512sums="
aaf36d09d4fe68514a5c279063d7e77a9a9a84c447037cba974b29faa07eb80c2aab2379d0699c196b5c27ffe1b2bb2c6
8d3390143e0e62d5e3d210ccfb61294
  bsd-games-3.3.tar.gz
e1def0d4835a877242c4173fae862e278a7858738e0bacacbb045a42bcabec2aa7c72d000bbd2421ce35fe66cdc1f52c0
577b7e278029ca5ed50f7aab22319f6  0001-bsd-games-scores-dir.patch
"
# Contributor: Carlo Landmeter <clandmeter@alpinelinux.org>
# Maintainer: Kevin Daudt <kdaudt@alpinelinux.org>
pkgname=spdx-licenses
pkgver=3.24.0
pkgrel=0
pkgdesc="Various data formats for the SPDX License List"
url="https://spdx.org/"
arch="noarch"
options="!check" # no test suite
license="CC-BY-3.0"
source="license-list-data-$pkgver.tar.gz::https://github.com/spdx/license-list-data/archive/v$pkgver.tar.gz"
builddir="$srcdir/license-list-data-$pkgver"
subpackages="$pkgname-list"

_types="html json rdfa rdfnt rdfturtle rdfxml template text"

for type in $_types; do
 subpackages="$subpackages $pkgname-$type:_subpkg"
done

package() {
 mkdir -p "$pkgdir"
}

_subpkg() {
 local type=${subpkgname/$pkgname-/}
 pkgdesc="$pkgdesc ($type)"
```

```
 install_if="$pkgname=$pkgver-r$pkgrel"
 mkdir -p "$subpkgdir"/usr/share/spdx
 cp -r "$builddir"/$type "$subpkgdir"/usr/share/spdx/
}

list() {
 pkgdesc="$pkgdesc (licence list)"
 mkdir -p "$subpkgdir"/usr/share/spdx
 local i; for i in "$builddir"/text/*.txt;
 do
  local license=${i##*/}
  echo ${license%.*} >> "$subpkgdir"/usr/share/spdx/license.lst
 done
}

sha512sums="
6eb81424e1b3173dbd8e17859b2e15dfe1c2af8f4da59b7dad0729c038a4cbdba95c34c2c546285fcdbbd41562e39575e
6a6ebb9463b70121e0a12b99d1307e7  license-list-data-3.24.0.tar.gz
"
```

mini_sendmail - accept email on behalf of real sendmail

Copyright 1999,2015 by Jef Poskanzer <jef@mail.acme.com>.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING,
 BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

1.21 swaggo-swag 1.16.6

1.21.1 Available under license :

MIT License

Copyright (c) 2017 Eason Lin

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.22 github.com/swaggo/http-swagger 1.3.4

1.22.1 Available under license :

MIT License

Copyright (c) 2018 Swaggo

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.23 confluentinc-confluent-kafka-go 2.11.0

1.23.1 Available under license :

LICENSE

---

librdkafka - Apache Kafka C driver library

Copyright (c) 2012-2022, Magnus Edenhill
2023, Confluent Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LICENSE.cjson

For cJSON.c and cJSON.h:

Copyright (c) 2009-2017 Dave Gamble and cJSON contributors

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished
 to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

LICENSE.crc32c

For src/crc32c.c copied (with modifications) from
http://stackoverflow.com/a/17646775/1821055

/* crc32c.c -- compute CRC-32C using the Intel crc32 instruction
* Copyright (C) 2013 Mark Adler
* Version 1.1 1 Aug 2013 Mark Adler
*/

/*
 This software is provided 'as-is',
 without any express or implied
 warranty. In no event will the author be held liable for any damages
 arising from the use of this software.

 Permission is granted to anyone to use this software for any purpose,
 including commercial applications, and to alter it and redistribute it
 freely, subject to the following restrictions:

 1. The origin of this software must not be misrepresented; you must not
    claim that you wrote the original software. If you use this software
    in a product, an acknowledgment in the product documentation would be
    appreciated but is not required.
 2. Altered source versions must be plainly marked as such, and must not be
    misrepresented as being the original software.
 3. This notice may not be removed or altered from any source distribution.

Mark Adler
madler@alumni.caltech.edu
*/

LICENSE.fnv1a
---
parts of src/rdfnv1a.c: http://www.isthe.com/chongo/src/fnv/hash_32a.c

Please
do not copyright this code. This code is in the public domain.

LANDON CURT NOLL DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL LANDON CURT NOLL BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

By:
chongo <Landon Curt Noll> /\oo/\
http://www.isthe.com/chongo/

Share and Enjoy! :-)

LICENSE.hdrhistogram

This license covers src/rdhdrhistogram.c which is a C port of
Coda Hale's Golang HdrHistogram https://github.com/codahale/hdrhistogram
at revision 3a0bb77429bd3a61596f5e8a3172445844342120

The MIT License
(MIT)

Copyright (c) 2014 Coda Hale

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE

LICENSE.lz4

---

src/rdxxhash.[ch] src/lz4*.[ch]: git@github.com:lz4/lz4.git 5ff839680134437dbf4678f3d0c7b371d84f4964

LZ4 Library
Copyright (c) 2011-2020, Yann Collet
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this
list of conditions and the following disclaimer in the documentation and/or
other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LICENSE.murmur2

---

parts of src/rdmurmur2.c: git@github.com:abrandoned/murmur2.git

MurMurHash2 Library
//---
// MurmurHash2 was written by Austin Appleby, and is placed in the public
// domain. The author hereby disclaims copyright to this source code.

Permission is hereby granted, free of charge, to any person
 obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

LICENSE.nanopb

For
 files in src/nanopb :
https://github.com/nanopb/nanopb/blob/8ef41e0ebd45daaf19459a011f67e66224b247cd/LICENSE.txt

Copyright (c) 2011 Petteri Aimonen <jpa at nanopb.mail.kapsi.fi>

This software is provided 'as-is', without any express or
implied warranty. In no event will the authors be held liable
for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any
purpose, including commercial applications, and to alter it and
redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you
  must not claim that you wrote the original software. If you use
  this software in a product, an acknowledgment in the product
  documentation would be appreciated but is not required.

2. Altered source versions must be plainly marked as such, and

must not be misrepresented as being the original software.

3. This notice may
not be removed or altered from any source
distribution.

LICENSE.opentelemetry

For files in src/opentelemetry: https://github.com/open-telemetry/opentelemetry-proto/blob/81a296f9dba23e32d77f46d58c8ea4244a2157a6/LICENSE

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes
of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or

Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You

institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution
incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE
text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with

the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding
such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event
and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent
with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier

identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

LICENSE.pycrc

The following license applies to the files rdcrc32.c and rdcrc32.h which
have been generated by the pycrc tool.

==========

Copyright (c) 2006-2012, Thomas Pircher <tehpeh@gmx.net>

Permission is hereby granted,
free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in

all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

LICENSE.queue

For
sys/queue.h:

* Copyright (c) 1991, 1993
* The Regents of the University of California. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 4. Neither the name of the University nor the names of its contributors
* may be used to endorse or promote products derived from this software
* without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
* ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* @(#)queue.h 8.5 (Berkeley) 8/20/94
* $FreeBSD$

LICENSE.regexp

---

regexp.c and regexp.h from https://github.com/ccxvii/minilibs sha 875c33568b5a4aa4fb3dd0c52ea98f7f0e5ca684

"
These libraries are in the public domain (or the equivalent where that is not
possible). You can do anything you want with them. You have no legal obligation to do anything else, although I appreciate attribution.
"

LICENSE.snappy

```
################################################################################
# LICENSE.snappy covers files: snappy.c, snappy.h, snappy_compat.h   #
# originally retrieved from http://github.com/andikleen/snappy-c     #
# git revision 8015f2d28739b9a6076ebaa6c53fe27bc238d219              #
################################################################################
```

The snappy-c code is under the same license as the original snappy source

Copyright 2011 Intel Corporation All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions
in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Intel Corporation nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING

NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LICENSE.tinycthread

From https://github.com/tinycthread/tinycthread/README.txt c57166cd510ffb5022dd5f127489b131b61441b9

License

Copyright (c) 2012 Marcus Geelnard
2013-2014 Evan Nemerson

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
claim that you wrote the original software. If you use this software
in a product, an acknowledgment in the product documentation would be
appreciated but is not required.

2. Altered source versions must be plainly marked as such, and must not be
misrepresented as being the original software.

3. This notice may not be removed or altered from any source
distribution.

LICENSE.wingetopt

For the files wingetopt.c wingetopt.h downloaded from https://github.com/alex85k/wingetopt

/*
* Copyright (c) 2002 Todd C. Miller <Todd.Miller@courtesan.com>
*
* Permission to use, copy, modify, and distribute this software for any
* purpose with or without fee is hereby granted, provided that the above
* copyright notice and this permission notice appear in all copies.
*
* THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
* WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF

* MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
* ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR
 ANY DAMAGES
* WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
* ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
* OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
*
* Sponsored in part by the Defense Advanced Research Projects
* Agency (DARPA) and Air Force Research Laboratory, Air Force
* Materiel Command, USAF, under agreement number F39502-99-1-0512.
*/
/*-
* Copyright (c) 2000 The NetBSD Foundation, Inc.
* All rights reserved.
*
* This code is derived from software contributed to The NetBSD Foundation
* by Dieter Baron and Thomas Klausner.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice,
 this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
* THIS SOFTWARE IS PROVIDED BY THE NETBSD FOUNDATION, INC. AND CONTRIBUTORS
* ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE FOUNDATION OR CONTRIBUTORS
* BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
* POSSIBILITY OF SUCH DAMAGE.
*/
Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You"
(or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations,
or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent

to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems
that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants
to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work
or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not

pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution
of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each

Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental,
or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted
against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "{}"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright {yyyy} {name of copyright owner}

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.24 github.com/aws/aws-sdk-go-v2/internal/configsources 1.4.2

1.24.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader

```
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }
```

```
 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer

 // License name.
 //
 // This member is required.
 LicenseName *string

 // Product name.
 //
```

```
 // This member is required.
 ProductName *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // Date and time range during which the license is valid, in ISO8601-UTC format.
 //
 // This member is required.
 Validity *types.DatetimeRange

 // Information about
 the license.
 LicenseMetadata []types.Metadata

 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]
```

```
jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
     - name: Run Scan code on pr ref
       run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
     # compare
     - name: License test
       run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
```

CheckoutBorrowLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever

InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

```
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
```

```
//   - Status
//
//
  - Fingerprint
//
//   - IssuerName
//
//   - Beneficiary
Filters []types.Filter

// Amazon Resource Names (ARNs) of the licenses.
LicenseArns []string

// Maximum number of results to return in a single call.
MaxResults *int32

// Token for the next set of results.
NextToken *string

noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

// Received license details.
Licenses []types.GrantedLicense

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
```

```
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
```

```
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}
```

```
type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
```

```
 return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
```

```
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if
```

```
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
```

```
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
```

```
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
```

```
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
```

```
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
```

```
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
```

```
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
```

```
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
```

```
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
```

```
 OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/DeregisterSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider
resource to deregister.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Name": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of name to filter by.</p>"
          }
        },
        "Values": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
          }
        },
        "Operator": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
          "traits": {
            "smithy.api#documentation": "<p>An operator for filtering results.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
```

```
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
           },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/GetRegisteredSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

         "traits": {
              "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
             }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token
```

```
status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
```

```
        "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
              }
            },
            "InstanceID": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
              }
            },
            "InstanceType": {
              "target": "smithy.api#String",
              "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
              }
            },
            "AccountID": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
              }
            },
            "Region": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
              }
            },
            "UsageOperation": {
              "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
              }
            },
            "ProductCode": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
              "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a
```

```
href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
                }
            },
            "LastUpdatedTime": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
                }
            },
            "SubscriptionName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
                }
            },
            "OsVersion": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
                }
            },
            "SubscriptionProviderCreateTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
                }
            },
            "SubscriptionProviderUpdateTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the registered \n\t\t\tthird-party Linux subscription provider.</p>"
                }
            },
            "DualSubscription": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for \n\t\t\tthe same software on your instance.</p>"
                }
            },
            "RegisteredWithSubscriptionProvider": {
                "target": "smithy.api#String",
                "traits": {
```

```
    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager Linux Subscriptions",
          "arnNamespace": "license-manager-linux-subscriptions",
          "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
```

```
"smithy.rules#endpointRuleSet": {
  "version": "1.0",
  "parameters": {
    "Region": {
      "builtIn": "AWS::Region",
      "required": false,
      "documentation": "The AWS region used to dispatch the request.",
      "type": "String"
    },
    "UseDualStack": {
      "builtIn": "AWS::UseDualStack",
      "required": true,
      "default": false,
      "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
       "type": "Boolean"
    },
    "UseFIPS": {
      "builtIn": "AWS::UseFIPS",
      "required": true,
      "default": false,
      "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
      "type": "Boolean"
    },
    "Endpoint": {
      "builtIn": "SDK::Endpoint",
      "required": false,
      "documentation": "Override the endpoint used to send this request",
      "type": "String"
    }
  },
  "rules": [
    {
      "conditions": [
        {
          "fn": "isSet",
          "argv": [
            {
              "ref": "Endpoint"
            }
          ]
        }
      ],
      "rules": [
        {
          "conditions": [
            {
```

```
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }

        ],
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                  "type": "error"
                },
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            {
                              "ref": "UseDualStack"
                            },
                            true
                          ]

}
                    ],
                    "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                    "type": "error"
                  },
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": {
                        "ref": "Endpoint"
                      },
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],
                "type": "tree"

              }
             ],
```

```
    "type": "tree"
  },
  {
    "conditions": [],
    "rules": [
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Region"
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {

    "fn": "aws.partition",
                    "argv": [
                      {
                        "ref": "Region"
                      }
                    ],
                    "assign": "PartitionResult"
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {

                      "ref": "UseFIPS"
                          },
                          true
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
```

```
                    },
                    true
                ]
            }

    ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

                },
                                            "supportsFIPS"
                                        ]
                                    }
                                ]
                            },
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                                        {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],

        "rules": [
                                    {
```

```
                                        "conditions": [],
                                        "endpoint": {
                                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],

                        "type": "tree"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                            "type": "error"
                        }
                    ],
                    "type": "tree"
                },
                {

            "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {

                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "fn": "getAttr",
                                            "argv": [
```

```
                                {
                                    "ref": "PartitionResult"
                                },
                                "supportsFIPS"
                            ]
                        },
                        true

                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS is enabled
but this partition does not support FIPS",
            "type": "error"
        }
    ],
    "type": "tree"
},
{
    "conditions": [
        {
            "fn": "booleanEquals",
            "argv": [
                {
                    "ref": "UseDualStack"
```

```
                    },
                    true

                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            true,
                            {
                                "fn": "getAttr",
                                "argv": [
                                    {

                                    "ref": "PartitionResult"
                                    },
                                    "supportsDualStack"
                                ]
                            }
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [],
                        "rules": [

    {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"

                    }
                ],
                "type": "tree"
            },
```

```
                                    {
                                        "conditions": [],
                                        "error": "DualStack is enabled but this partition does not support DualStack",
                                        "type": "error"
                                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "rules": [
                                    {
                                        "conditions": [],
                                        "endpoint": {
                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
            }
        ],
        "type": "tree"
    }
]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"
```

```
    }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": true,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": true,
          "UseDualStack": false
        }
      },
      {

    "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
          }

  },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": false
        }
```

```
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
        }
       },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
        }
```

```
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }

     },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
```

```
                {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                  },
                  "params": {

              "Region": "us-iso-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                    }
                  },
                  "params": {
                    "Region": "us-iso-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
                  "expect": {
                    "error": "DualStack is enabled but this partition does not support DualStack"
                  },
                  "params": {
                    "Region": "us-iso-east-1",
                    "UseFIPS": false,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
             }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",
```

```
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }
          },
          "params": {
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
```

```
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled LinuxSubscriptionsDiscovery"

       },
            {
              "name": "Disabled",
```

```
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

  {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
```

```
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n              <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n <code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n <code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n <code>InstanceType</code>\n              </p>\n            </li>\n            <li>\n              <p>\n <code>ProductCode</code>\n              </p>\n            </li>\n            <li>\n              <p>\n <code>Region</code>\n              </p>\n            </li>\n            <li>\n              <p>\n <code>Status</code>\n              </p>\n            </li>\n            <li>\n              <p>\n <code>UsageOperation</code>\n              </p>\n            </li>\n          </ul>\n          <p>For each filter, you can use one of the following <code>Operator</code>\n  values to \n  \t\tdefine the behavior of the filter:</p>\n          <ul>\n            <li>\n              <p>\n <code>contains</code>\n              </p>\n            </li>\n            <li>\n              <p>\n <code>equals</code>\n              </p>\n            </li>\n            <li>\n              <p>\n <code>Notequal</code>\n              </p>\n            </li>\n          </ul>"
                }
            },
            "MaxResults": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
          "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
              "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
            }
          },
          "NextToken": {

         "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n       <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n        <p>The valid names for this filter are:</p>\n        <ul>\n          <li>\n            <p>\n              <code>Subscription</code>\n            </p>\n          </li>\n        </ul>\n        <p>The
       valid Operators for this filter are:</p>\n        <ul>\n          <li>\n            <p>\n              <code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n              <code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n              <code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
```

```
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "Subscriptions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
            "traits": {
              "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
             "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
          "target":
```

```
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "RegisteredSubscriptionProviders"
            }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSources": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
                "traits": {
                    "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }

  },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
          "traits": {
            "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
          }
        },

         "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
          },
          "errors": [
            {

        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "resourceArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                 "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
                 "smithy.api#httpLabel": {},
                 "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "tags": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
              "name": "CONTAINS",
              "value": "Contains",
              "documentation": "Contains operator"
            }
          ],
          "smithy.api#length": {
            "min": 1,
            "max": 20
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
```

```
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/RegisterSubscriptionProvider"

            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
            }
```

```
            },
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"

   }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "InProgress",
```

```
            "value": "InProgress",
            "documentation": "InProgress status"
          },
          {
            "name": "Completed",
            "value": "Completed",
            "documentation": "Completed status"
          },
          {
            "name": "Successful",
            "value": "Successful",
            "documentation": "Successful status"
          },
          {
            "name": "Failed",
            "value": "Failed",
            "documentation": "Failed status"
          }
        ]
      }
    },

    "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
          }
        }
      },
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        },
        "smithy.api#uniqueItems": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
          "Name":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the subscription.</p>"
            }
          },
          "Type": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS.</p>"
            }
          },
          "InstanceCount": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
            "traits": {
              "smithy.api#documentation": "<p>The total amount of running instances using this subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
```

```
      "traits": {
        "smithy.api#enum": [

{
            "name": "RedHat",
            "value": "RedHat",
            "documentation": "RedHat subscription provider namespace"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "ACTIVE",
            "value": "ACTIVE",
            "documentation": "ACTIVE status"
          },
          {
            "name": "INVALID",
            "value": "INVALID",

 "documentation": "INVALID status"
          },
          {
            "name": "PENDING",
            "value": "PENDING",
            "documentation": "PENDING status"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
```

```
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
        "type": "structure",
        "members":
 {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tags": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
         "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        },
        "tagKeys": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
          "traits": {

       "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
            "smithy.api#httpQuery": "tagKeys",
            "smithy.api#required": {}
          }
```

```
        }
    },
    "traits": {
        "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
    "type": "structure",
    "members": {},
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

 },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
        },
        "smithy.api#idempotent": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
    "type": "structure",
    "members": {
        "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
```

```
            "traits": {
              "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
              "smithy.api#required": {}
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n integration has been enabled, and which Regions data will be aggregated from.</p>",
              "smithy.api#required": {}
            }
          },
          "AllowUpdate": {
            "target":
 "smithy.api#Boolean",
            "traits": {
              "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
             "traits": {
              "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n integration has been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
            }
```

```
            },
            "StatusMessage": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
               "traits": {
                  "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
               }

        },
            "HomeRegions": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                  "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
         }
      }
   }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
```

```
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string
```

```
 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
```

```
 return
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
```

```
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
```

```
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
```

```
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
```

```
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
```

```
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
```

InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above

copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
```

details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP \n\t\t\taddresses, and the credential provider for user administration. "
            }
          },
          "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
              "smithy.api#documentation": " The type of Active Directory either a self-managed Active Directory or an \n\t\t\tAmazon Web Services Managed Active Directory. "
            }
          }
        },
        "traits": {
          "smithy.api#documentation": " Details about an Active Directory identity provider. "
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
          "DomainName": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " The domain name for the Active Directory. "
            }
          },
          "DomainIpv4List": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
            "traits": {
              "smithy.api#documentation": " A list of domain IPv4 addresses that are used for the Active Directory. ",
              "smithy.api#length": {
                "min": 1,
                "max": 2
              }
            }
          },
          "DomainCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": " Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration. "
            }
          },
          "DomainNetworkSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
            "traits": {

```
                "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for \n\t\t\tuser administration in the Active Directory.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "SELF_MANAGED",
                "value": "SELF_MANAGED",
                "documentation": "SELF_MANAGED type of Active Directory"
              },
              {
                "name": "AWS_MANAGED",
                "value": "AWS_MANAGED",
                "documentation": "AWS_MANAGED type of Active Directory"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Arn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUser": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
 {
              "code": 200,
              "method": "POST",
              "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                "smithy.api#required": {}
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
              }
            }
          },
          "traits": {

        "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
          "type": "integer"
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
         }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
        "smithy.api#error": "server"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },

       {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
```

```
license server.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                "smithy.api#required": {}
              }
            },
            "LicenseServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
          "SecretsManagerCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
         ],
         "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "LicenseServerEndpointArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                  "smithy.api#required": {}
               }
            },
             "ServerType": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
               "traits": {
                  "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
```

```
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}

    }
     },
     "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
     },
     "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
```

```
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

      }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
```

```
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to disassociate.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummary":
{
              "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
          "type": "structure",
          "members": {
            "Subnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory domain.</p>",
                "smithy.api#length": {
                  "min": 1
                },

      "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Filter": {
          "type": "structure",
          "members": {
```

```
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
```

```
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
                }
            },
            "FailureMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
          "type": "list",
          "member": {

            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
              }
            }
          },
```

```
        "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },

    "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance user.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
              }
            },
            "AssociationDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
              }
            },
            "DisassociationDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
```

```
    "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
         "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
         },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",
```

```
            "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
                "Region":
{
                    "builtIn": "AWS::Region",
                    "required": false,
                    "documentation": "The AWS region used to dispatch the request.",
                    "type": "String"
                },
                "UseDualStack": {
                    "builtIn": "AWS::UseDualStack",
                    "required": true,
                    "default": false,
                    "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                    "type": "Boolean"
                },
                "UseFIPS": {
                    "builtIn": "AWS::UseFIPS",
                    "required": true,
                    "default": false,
                    "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                    "type": "Boolean"
                },
                "Endpoint": {
                    "builtIn": "SDK::Endpoint",
                    "required": false,
                    "documentation": "Override the endpoint used to send this request",
```

```
        "type": "String"
      }
    },
    "rules": [
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Endpoint"
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [
              {

                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
```

```
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                  "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Region"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "aws.partition",

                    "argv": [
                      {
                        "ref": "Region"
                      }
                    ],
                    "assign": "PartitionResult"
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },
```

```
true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

"fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      }
                    ]
                  },

                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }
```

```
                ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [

 {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
```

```
                "argv": [

            {
                        "ref": "PartitionResult"
                    },
                    "supportsFIPS"
                ]
            },
            true
        ]
    }
],
"rules": [
    {
        "conditions": [],
        "endpoint": {

"url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
            "properties": {},
            "headers": {}
        },
        "type": "endpoint"
    }
],
"type": "tree"
},
{
    "conditions": [],
    "error": "FIPS is enabled but this partition does not support FIPS",
    "type": "error"

}
    ],
    "type": "tree"
},
{
    "conditions": [
        {
            "fn": "booleanEquals",
            "argv": [
                {
                    "ref": "UseDualStack"
                },
                true
            ]
        }
    ],
    "rules": [
```

```
                {

        "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        true,
                        {
                          "fn": "getAttr",
                          "argv": [
                            {
                              "ref": "PartitionResult"
                            },
                            "supportsDualStack"
                          ]

    }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

                ],
                    "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
                  "type": "error"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "endpoint": {
                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
```

```
                "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }
            ],
            "type": "tree"
        }
      ],
      "type": "tree"
    },
    {
      "conditions": [],
      "error": "Invalid Configuration: Missing Region",
      "type": "error"
    }
  ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect":
{
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",

    "UseFIPS": true,
        "UseDualStack": false
      }
```

```
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS":
true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
```

```
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
                {
                  "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint":
{
                      "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                     "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
                  },
                  "params": {
                    "Region": "us-iso-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false

}
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
```

```
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",

 "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
```

```
      "endpoint": {
            "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
```

```
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
          "members": {
```

```
            "IdentityProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
               }
            },
            "ServerType": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
               "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>"
               }
            },
            "ServerEndpoint": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
               }
            },
            "LicenseServerEndpointId": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
               }
            },
            "LicenseServerEndpointArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits":
 {
                  "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the
RDS \n\t\t\tlicense server.</p>"
               }
            },
            "LicenseServerEndpointProvisioningStatus": {
               "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                  "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
```

```
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },

         "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
```

```
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
    "type": "string",
    "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
    }
},
 "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
    "type": "list",
    "member": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
          "type": "structure",
          "members": {
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>",
                "smithy.api#required": {}
              }
            },
            "ServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n            <li>\n                <p>Product</p>\n            </li>\n
        <li>\n                <p>DirectoryId</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                "smithy.api#required": {}
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },

      {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/instance/ListInstances"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "InstanceSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
         "type": "structure",
         "members":
 {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
```

```
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/ListLicenseServerEndpoints"
          },

        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "LicenseServerEndpoints"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
```

```
                }
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n              <p>IdentityProviderArn</p>\n            </li>\n          </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoints": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
          "type":
```

```
 "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
```

```
{
        "type": "structure",
        "members": {
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
             "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n
</li>\n          <li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
```

```
        "members": {
          "ProductUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

          }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
             }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "InstanceUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
         "type": "structure",
         "members": {
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance, which
provides user-based subscriptions.</p>",
                  "smithy.api#required": {}
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
```

```
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
```

```
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
```

```
        "type": "structure",
        "members": {
          "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
 {
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
```

```
"<p>Metadata that describes the results of an identity provider operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
      "type": "string",
      "traits": {
        "smithy.api#length": {

         "min": 5,
          "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
      "type": "structure",
      "members": {
        "Endpoint": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
            "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
```

```
                "documentation": ""
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
          "type": "structure",
          "members": {
            "message": {

  "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Settings": {
          "type": "structure",
          "members": {
            "Subnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
                "smithy.api#length": {
                  "min": 1
                },
                "smithy.api#required": {}
              }
            },
            "SecurityGroupId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

             "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

      },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/StartProductSubscription"
        }

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
```

```
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {

 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
```

```
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
```

```
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StopProductSubscription"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
               }
            },
            "IdentityProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
               }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }

  }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
```

```
 "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "Tags": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
"<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
          "smithy.api#error": "client"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {

       "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
        "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}

      }
        },
        "TagKeys": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
          "traits": {
            "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
            "smithy.api#httpQuery": "tagKeys",
            "smithy.api#required": {}
          }
        }
```

```
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
            "smithy.api#http": {

     "code": 200,
                "method": "POST",
                "uri": "/identity-provider/UpdateIdentityProviderSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
```

```
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#required": {}
            }
          }
        },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A parameter is not valid.</p>",
        "smithy.api#error": "client"
      }
```

```
      }
   }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
```

```
CheckInLicenseOutput struct {
// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
```

```
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}
```

```
func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
```

Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their

Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf

of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step

ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization

OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.25 aws-sdk-go-v2-aws-protocol-eventstream 1.7.0

1.25.1 Available under license :

Apache License
Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including

the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or

Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the

origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier

identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.26 github.com/aws/aws-sdk-go-v2/service/internal/endpoint-discovery 1.11.2

1.26.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop

```
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
name: License Scan

on: [pull_request]

jobs:
 licensescan:
  name: License Scan
  runs-on: ubuntu-latest
  strategy:
   matrix:
    python-version: [3.9]

  steps:
   - name: Checkout target
    uses: actions/checkout@v2
    with:
     path: sdkbase
     ref: ${{ github.base_ref }}
   - name: Checkout this ref
    uses: actions/checkout@v2
    with:
     path: new-ref
```

```
        fetch-depth: 0
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
```

```
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer
```

```
// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata
```

```
 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
```

```
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
return &awsmiddleware.RegisterServiceMetadata{
 Region:       region,
```

```
 ServiceID:     ServiceID,
 OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
 spanInitializeStart
 InterceptExecution
 RegisterServiceMetadata
 legacyEndpointContextSetter
 SetLogger
 OperationInputValidation
 spanInitializeEnd
 Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
 Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
 Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
 Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
```

RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning

```
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {
```

```
 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
  - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
```

```
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
```

```
 spanInitializeEnd
Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
```

```
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
```

```
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
 err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
```

```
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
```

```
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
```

```
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
```

```
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
```

```
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.
```

```
package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
```

```
    // This member is required.
    Entitlements []types.EntitlementData

    // Key fingerprint identifying the license.
    //
    // This member is required.
    KeyFingerprint *string

    // Product SKU.
    //
    // This member is required.
    ProductSKU *string

    // License beneficiary.
    Beneficiary *string

    // Node ID.
    NodeId *string

    noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

    // Checkout type.
    CheckoutType types.CheckoutType

    // Allowed license entitlements.
    EntitlementsAllowed []types.EntitlementData

    // Date and time at which the license checkout expires.
    Expiration *string

    // Date and time at which the license checkout is issued.
    IssuedAt *string

    // Amazon Resource Name (ARN) of the checkout license.
    LicenseArn
    *string

    // License consumption token.
    LicenseConsumptionToken *string

    // Node ID.
    NodeId *string

    // Signed token.
    SignedToken *string
```

```
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
```

```
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}
```

```
func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
```

```
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
            }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
           },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/GetRegisteredSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

       "traits": {
            "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
```

```
                }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"
```

```
        },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
      "type": "structure",
      "members": {
        "AmiId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
          }
        },
        "InstanceID": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
          }
        },
        "InstanceType": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>The instance type of the resource.</p>"
          }
        },
        "AccountID": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of the instance.</p>"
          }
        },
        "Region": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
          }
        },
        "UsageOperation": {
          "target": "smithy.api#String",

   "traits": {
            "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
```

```
            }
        },
        "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a
href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-
operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
        },
        "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance
details.</p>"
            }
        },
        "SubscriptionName": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
            }
        },
        "OsVersion": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
            }
        },
        "SubscriptionProviderCreateTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
        },
        "SubscriptionProviderUpdateTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
            }
        },
        "DualSubscription": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
```

\n\t\t\tthe same software on your instance. "
            }
          },
          "RegisteredWithSubscriptionProvider": {
            "target": "smithy.api#String",
            "traits": {

    "smithy.api#documentation": " Indicates that your instance uses a BYOL license subscription from \n\t\t\ta third-party Linux subscription provider that you've registered with License Manager. "
            }
          }
        },
        "traits": {
          "smithy.api#documentation": " Details discovered information about a running instance using Linux subscriptions. "
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 " An exception occurred with the service. ",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"

```
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
    }
  ],
  "traits": {
    "aws.api#service": {
      "sdkId": "License Manager Linux Subscriptions",
      "arnNamespace": "license-manager-linux-subscriptions",
      "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
    },
    "aws.auth#sigv4": {
      "name": "license-manager-linux-subscriptions"
    },
    "aws.protocols#restJson1": {},
    "smithy.api#cors": {
      "additionalAllowedHeaders": [
        "*",
        "content-type",
        "x-amz-content-sha256",
        "x-amz-user-agent",
        "x-amzn-platform-id",
        "x-amzn-trace-id"
      ],
      "additionalExposedHeaders": [
        "x-amzn-errortype",
        "x-amzn-requestid",
```

```
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
```

```
        }
      ],
      "rules": [
        {
          "conditions": [
            {
              "fn": "booleanEquals",
              "argv": [
                {
                  "ref": "UseFIPS"
                },
                true
              ]
            }

    ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]

}
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },
                  "properties": {},
                  "headers": {}
                },
                "type": "endpoint"
```

```
            }
          ],
          "type": "tree"

    }
    ],
    "type": "tree"
},
{
    "conditions": [],
    "rules": [
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Region"
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {

    "fn": "aws.partition",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ],
                  "assign": "PartitionResult"
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {

                    "ref": "UseFIPS"
                        },
                        true
                      ]
```

```
                },
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseDualStack"
                    },
                    true
                  ]
                }

    ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"

    },
                                "supportsFIPS"
                            ]
                          }
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [

                             {
                                "ref": "PartitionResult"
                              },
                              "supportsDualStack"
                            ]
                          }
                        ]
                      }
                    ],
```

```
                "rules": [
                  {
                    "conditions": [],

        "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }
                  ],

                "type": "tree"
                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {

        "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
```

```
                "fn": "booleanEquals",
                    "argv": [
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      },
                      true

                  ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "rules": [
                        {
                          "conditions": [],
                          "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                            "headers": {}
                          },
                          "type": "endpoint"
                        }
                      ],
                      "type": "tree"
                    }
                  ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "FIPS is enabled
 but this partition does not support FIPS",
                  "type": "error"
                }
              ],
              "type": "tree"
            },
            {
```

```
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true

                ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {

                                            "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "rules": [

        {
                                        "conditions": [],
                                        "endpoint": {
                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
```

```
                                    "type": "tree"

                            }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
]
},
"smithy.rules#endpointTests": {
"testCases": [
```

```
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
        }
```

```
    },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
          }
        },
        "params": {
          "Region": "cn-north-1",
          "UseFIPS": true,
          "UseDualStack": true
        }
      },
      {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
          }
        },
        "params": {
          "Region": "cn-north-1",
          "UseFIPS": true,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
          }
         },
        "params": {
          "Region": "cn-north-1",
          "UseFIPS": false,
          "UseDualStack": true
        }
      },
```

```
            {
              "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
                }

             },
              "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
                }
              },
```

```
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {

    "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
```

```
enabled",
                "expect": {
                  "error": "DualStack is enabled but this partition does not support DualStack"
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
                  }
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS":
false,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                   }
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false
                }
              },
```

```
                {
                  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "error": "DualStack is enabled but this partition does not support DualStack"
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {

                 "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                    }
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }

        },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }
                  },
```

```
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
```

```
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

            },
            {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "OrganizationIntegration": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
          "traits": {
            "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n              <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceType</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>ProductCode</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Region</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Status</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>UsageOperation</code>\n              </p>\n            </li>\n          </ul>\n          <p>For each filter, you can use one of the following <code>Operator</code>
```

```
values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
            "Instances": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
                }
            },
            "NextToken": {

          "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListLinuxSubscriptions"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",

   "items": "Subscriptions"
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
      "type": "structure",
      "members": {
        "Filters": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
```

```
match a certain subscription's name.</p>\n        <p>The valid names for this filter are:</p>\n        <ul>\n
<li>\n            <p>\n                <code>Subscription</code>\n            </p>\n        </li>\n        </ul>\n
<p>The
 valid Operators for this filter are:</p>\n        <ul>\n        <li>\n            <p>\n
<code>contains</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>equals</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n        </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
```

```
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
          },
          "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",
              "items": "RegisteredSubscriptionProviders"
            }
          }

        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSources": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
            }
        },
        "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                "smithy.api#range": {
                    "min": 1,
                    "max": 100
                }
            }

 },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
                "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
        },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
      },
      "errors": [
        {

     "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
        "smithy.api#http": {
          "method": "GET",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#readonly": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
                    "documentation": "Equal operator"
                },
                {
                    "name": "NOT_EQUAL",
                    "value": "NotEqual",
                    "documentation": "Not equal operator"
                },
                {
                    "name": "CONTAINS",
                    "value": "Contains",
                    "documentation": "Contains operator"
                }
            ],
            "smithy.api#length": {
                "min": 1,
                "max": 20
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled OrganizationIntegration"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
```

```
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
            }
          },
```

```
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"
```

```
}
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "InProgress",
          "value": "InProgress",
          "documentation": "InProgress status"
        },
        {
          "name": "Completed",
          "value": "Completed",
          "documentation": "Completed status"
        },
        {
          "name": "Successful",
          "value": "Successful",
          "documentation": "Successful status"
        },
        {
          "name": "Failed",
          "value": "Failed",
          "documentation": "Failed status"
        }
      ]
    }
  },

  "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
    "type": "list",
    "member": {
      "target": "smithy.api#String",
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        }
      }
    },
    "traits": {
      "smithy.api#length": {
        "min": 1,
        "max": 100
      },
      "smithy.api#uniqueItems": {}
    }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
      "type": "structure",
      "members": {
        "Name":
{
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the subscription.</p>"
          }
        },
        "Type": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS.</p>"
          }
        },
        "InstanceCount": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>The total amount of running instances using this subscription.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
```

```
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [

 {
                "name": "RedHat",
                "value": "RedHat",
                "documentation": "RedHat subscription provider namespace"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "ACTIVE",
              "value": "ACTIVE",
              "documentation": "ACTIVE status"
            },
            {
              "name": "INVALID",
              "value": "INVALID",

   "documentation": "INVALID status"
            },
            {
              "name": "PENDING",
              "value": "PENDING",
              "documentation": "PENDING status"
            }
          ]
        }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
      "type": "structure",
      "members":
{
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services resource to which to add the specified \n\t\t\tmetadata tags.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
```

```
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

          "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
          },
```

```
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
```

```
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
          }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
          "type": "structure",
          "members": {
              "message": {
                  "target": "smithy.api#String"
              }
          },
          "traits": {
              "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
              "smithy.api#error": "client"
          }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
```

```
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
```

```
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
```

```
//
// This member is required.
WorkspaceId *string

// A token from Grafana Labs that ties your Amazon Web Services account with a
// Grafana Labs account. For more information, see [Link your account with Grafana Labs].
//
// [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
GrafanaToken *string

noSmithyDocumentSerde
}

type AssociateLicenseOutput
struct {

// A structure containing data about the workspace.
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
```

```
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
```

```
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",

```
            "traits": {
                "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
        },
        "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
        },
        "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
                "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
    "type": "structure",
    "members": {
      "DomainName": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
        }
      },
      "DomainIpv4List": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
        "traits": {
          "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
          "smithy.api#length": {
            "min": 1,
            "max": 2
          }
        }
      },
      "DomainCredentialsProvider": {
        "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
              },
              "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>Contains network access and credential details that are needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
                }
              ]
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#Arn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
 {
            "type": "operation",
            "input": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n          </note>",
            "smithy.api#http":
 {
              "code": 200,
              "method": "POST",
              "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
          "type": "structure",
          "members": {
            "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
              "smithy.api#required": {}
            }
          },
           "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },

        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
```

```
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
              "traits": {
                "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
```

```
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}

      }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Directory": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
```

```
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary":
{
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
         "type": "structure",
         "members": {
            "Subnets": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                  "smithy.api#length": {
                     "min": 1
                  },
```

```
    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
              }
            },
            "FailureMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
          "type": "list",
          "member": {

            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
    "type": "structure",
    "members": {
        "Username": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

"IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
```

```
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
```

```
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
    "type": "structure",
    "members": {
        "message": {
            "target": "smithy.api#String"
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
         "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
         },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
```

```
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",

          "x-api-key",
            "authorization",
            "x-amz-date",
            "x-amz-security-token",
            "Access-Control-Allow-Headers",
            "Access-Control-Allow-Methods",
            "Access-Control-Allow-Origin"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region":
{
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
              "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
```

```
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
            "type": "Boolean"
          },
          "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
             ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [
                  {

                    "fn": "booleanEquals",
                    "argv": [
                      {
```

```
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "aws.partition",

                      "argv": [
                        {
                          "ref": "Region"
                        }
                      ],
                      "assign": "PartitionResult"
                    }
```

```
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },
```

true

```
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
```

"fn": "booleanEquals",

```
                            "argv": [
                              true,
                              {
                                "fn": "getAttr",
                                "argv": [
                                  {
                                    "ref": "PartitionResult"
                                  },
                                  "supportsFIPS"
                                ]
                              }
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              true,
```

```
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }

                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }

    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                    "type": "error"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [

 {
                            "ref": "UseFIPS"
                        },
                        true
                    ]
```

```
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "fn": "getAttr",
                                    "argv": [

        {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

    "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS is enabled but this partition does not support FIPS",
                    "type": "error"

}
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {

        "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]

          }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

            ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
```

```
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
{
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint":
{
                  "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
```

```
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
```

```
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

    },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",

  "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
```

```
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

     "endpoint": {
            "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
 false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
```

```
                },
                {
                  "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                  "expect": {
                    "error": "Invalid Configuration:
 Dualstack and custom endpoint are not supported"
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

  "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
                }
            },
            "LicenseServerEndpointId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits":
```

```
{
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
              }
            },
            "LicenseServerEndpointProvisioningStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
              "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
              }
            },
            "LicenseServers": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
              }
            },

           "CreationTime": {
              "target": "smithy.api#Timestamp",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
          "type": "string"
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

      "type": "string",
          "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
              "name": "PROVISIONED",
              "value": "PROVISIONED",
              "documentation": ""
            },
            {
              "name": "DELETING",
              "value": "DELETING",
              "documentation": ""
            },
            {
              "name": "DELETION_FAILED",
              "value": "DELETION_FAILED",
              "documentation": ""

           },
            {
              "name": "DELETED",
              "value": "DELETED",
              "documentation": ""
            }
          ]
       }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
       "type": "string",
       "traits": {
          "smithy.api#enum": [
            {
              "name": "HEALTHY",
              "value": "HEALTHY",
              "documentation": ""
            },
            {
              "name": "UNHEALTHY",
              "value": "UNHEALTHY",
              "documentation": ""
            },
```

```
                {
                    "name": "NOT_APPLICABLE",
                    "value": "NOT_APPLICABLE",
                    "documentation": ""
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
        "type": "structure",
        "members": {
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
```

```
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n        <li>\n        <p>Product</p>\n        </li>\n
        <li>\n        <p>DirectoryId</p>\n        </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                    "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
 that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                    "smithy.api#required": {}
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
 empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
 next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
```

```
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },

{
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
      }
    ],
    "traits": {
      "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
      "smithy.api#http": {
        "code": 200,
        "method": "POST",
        "uri": "/instance/ListInstances"
      },
      "smithy.api#paginated": {
        "inputToken": "NextToken",
        "outputToken": "NextToken",
        "pageSize": "MaxResults",
        "items": "InstanceSummaries"
      }
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
    "type": "structure",
    "members":
```

```
{
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
      <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
      "type": "structure",
      "members": {
        "InstanceSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
          }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/license-server/ListLicenseServerEndpoints"
        },

      "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "LicenseServerEndpoints"
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
      "type": "structure",
      "members": {
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n        <li>\n          <p>IdentityProviderArn</p>\n        </li>\n      </ul>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
      "type": "structure",
      "members": {
        "LicenseServerEndpoints": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
"operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " Lists the user-based subscription products available from an identity provider. ",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"

```
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
```

```
This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "ProductUserSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

           }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
```

```
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
    "type": "structure",
    "members": {
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
```

```
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {

            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
               }
            },
            "SubscriptionStartDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The start date of a subscription.</p>"
               }
            },
            "SubscriptionEndDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The end date of a subscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
         "type":
 "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
         "type": "structure",
         "members": {
```

```
            "RdsSalCredentialsProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
```

```
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
          "type": "structure",
          "members": {
            "IdentityProvider": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>",
                "smithy.api#required": {}
              }
            },
            "Settings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
              "traits":
 {
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
```

```
                    "min": 1
                }
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
    "type": "string",
    "traits": {
        "smithy.api#length": {

         "min": 5,
            "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
    "type": "structure",
    "members": {
        "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more servers.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
    "type": "union",
    "members": {
        "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

           "traits": {
              "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688
communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
              "smithy.api#required": {}
            }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StartProductSubscription"
            }

      }
       },
       "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
          "type": "structure",
          "members": {
             "Username": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                   "smithy.api#required": {}
                }
             },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                   "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                   "smithy.api#required": {}
                }
             },
             "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                   "smithy.api#required": {}
                }
             },
             "Domain": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
                }
             },
             "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                   "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
                }
```

```
  }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/user/StopProductSubscription"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
              }
            },
            "IdentityProvider": {
              "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
              }
            },
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }

    }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

 "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
 {
        "type": "structure",
        "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {
```

```
      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
```

```
            "type": "structure",
            "members": {
                "message": {
                    "target": "smithy.api#String"
                }
            },
            "traits": {
                "smithy.api#documentation": "<p>A parameter is not valid.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
```

```
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
```

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation

spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.27 github.com/aws/smithy-go 1.22.5

1.27.1 Available under license :

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise

designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any

risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

1.28 perks 1.0.1

1.28.1 Available under license :

Copyright (C) 2013 Blake Mizerany

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION

OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.29 github.com/aws/aws-sdk-go-v2/service/internal/accept-encoding 1.13.0

1.29.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a

copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a

cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with

the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.30 zgo.at/zcache/v2 2.2.0

1.30.1 Available under license :

Copyright (c) 2012-2019 Patrick Mylund Nielsen and the go-cache contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.31 scanelf 1.3.8-r1

1.31.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses
are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their

rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission
to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program
or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute
verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate

copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish,
that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Program,
and can
be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program
(or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program
in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering
access to copy from a designated place, then offering equivalent
access to copy the source code from the same place counts as
distribution of the source code, even though third parties are not
compelled
to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program

except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is

implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute
software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies
a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED
BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED

OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version
2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical
commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

1.32 github.com/aws/aws-sdk-go-v2/service/internal/presigned-url 1.13.2

1.32.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd

Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
name: License Scan

on: [pull_request]

jobs:

```
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
     - name: Run Scan code on pr ref
       run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
     # compare
     - name: License test
       run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
```

```
//
// This member is required.
ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag
```

```
 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
```

```
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
 return err
```

```
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
```

```
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
```

InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection

spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength

SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
"context"
"fmt"
awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
"github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
"github.com/aws/smithy-go/middleware"
smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns

```
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense
```

```
 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
```

```
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
```

```
err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if
err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
```

```
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
```

```
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {
```

```
 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
```

```
 return err
}
if err := addProtocolFinalizerMiddlewares(stack,
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
```

```
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata
```

```
 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
```

```
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
```

```
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
```

```
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string
```

```
 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
```

```
 return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
```

```
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
```

```
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData
```

```
// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
```

```
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.

```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },

    {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
               "smithy.api#required": {}
             }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
```

```
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
```

```
        "traits": {
            "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
          }
        },
        "SubscriptionProviderStatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
          }
        },
        "LastSuccessfulDataRetrievalTime": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
      },
      "errors": [
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
```

```
            },
            "StatusMessage": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
               "traits": {
                  "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
               }
            },
            "HomeRegions": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                  "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
         "type": "structure",
         "members": {
            "AmiId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
               }
            },
            "InstanceID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
               }
            },
            "InstanceType": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>The instance type of the resource.</p>"
               }
            },
            "AccountID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
               }
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
```

```
            "smithy.api#documentation": "<p>The status of the instance.</p>"
          }
        },
        "Region": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
          }
        },
        "UsageOperation": {
          "target": "smithy.api#String",

   "traits": {
            "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
          }
        },
        "ProductCode": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
          "traits": {
            "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
          }
        },
        "LastUpdatedTime": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
          }
        },
        "SubscriptionName": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
          }
        },
        "OsVersion": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
          }
        },
        "SubscriptionProviderCreateTime": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
          },
          "SubscriptionProviderUpdateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
            }
          },
          "DualSubscription": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
            }
          },
          "RegisteredWithSubscriptionProvider": {
            "target": "smithy.api#String",
            "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
```

```
            "smithy.api#documentation":
"<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
          "type": "service",
          "version": "2018-05-10",
          "operations": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
             },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
            }
          ],
          "traits": {
            "aws.api#service": {
              "sdkId": "License Manager Linux Subscriptions",
               "arnNamespace": "license-manager-linux-subscriptions",
              "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
```

```
        },
        "aws.auth#sigv4": {
          "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
```

```
      "Endpoint": {
        "builtIn": "SDK::Endpoint",
        "required": false,
        "documentation": "Override the endpoint used to send this request",
        "type": "String"
      }
    },
    "rules": [
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Endpoint"
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }

],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
```

```
                                ]

}
                            ],
                            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                            "type": "error"
                        },
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": {
                                    "ref": "Endpoint"
                                },
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"

                }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "isSet",
                                "argv": [
                                    {
                                        "ref": "Region"
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
                                    {

                "fn": "aws.partition",
                                        "argv": [
                                            {
                                                "ref": "Region"
```

```
                }
            ],
            "assign": "PartitionResult"
        }
    ],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {

                      "ref": "UseFIPS"
                        },
                        true
                    ]
                },
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
                    ]
                }

],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                true,
                                {
                                    "fn": "getAttr",
                                    "argv": [
                                        {
                                            "ref": "PartitionResult"

},
                                        "supportsFIPS"
                                    ]
                                }
                            ]
                        },
```

```
                {
                  "fn": "booleanEquals",
                  "argv": [
                    true,
                    {
                      "fn": "getAttr",
                      "argv": [

                       {
                            "ref": "PartitionResult"
                        },
                        "supportsDualStack"
                      ]
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [],

    "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }
                  ],

            "type": "tree"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",

              "type": "error"
            }
          ],
          "type": "tree"
        },
```

```
                                {

            "conditions": [
                                    {
                                       "fn": "booleanEquals",
                                       "argv": [
                                          {
                                             "ref": "UseFIPS"
                                          },
                                          true
                                       ]
                                    }
                                 ],
                                 "rules": [
                                    {
                                       "conditions": [
                                          {

                           "fn": "booleanEquals",
                                             "argv": [
                                                {
                                                   "fn": "getAttr",
                                                   "argv": [
                                                      {
                                                         "ref": "PartitionResult"
                                                      },
                                                      "supportsFIPS"
                                                   ]
                                                },
                                                true

                                          ]
                                       }
                                    ],
                                    "rules": [
                                       {
                                          "conditions": [],
                                          "rules": [
                                             {
                                                "conditions": [],
                                                "endpoint": {
                                                   "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                                   "headers": {}
                                                },
                                                "type": "endpoint"
```

```
                    }
                  ],
                  "type": "tree"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "FIPS is enabled
but this partition does not support FIPS",
              "type": "error"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
            {
              "fn": "booleanEquals",
              "argv": [
                {
                  "ref": "UseDualStack"
                },
                true

      ]
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    true,
                    {
                      "fn": "getAttr",
                      "argv": [
                        {

                          "ref": "PartitionResult"
                        },
                        "supportsDualStack"
                      ]
                    }
                  ]
                }
```

```
                ],
                "rules": [
                    {
                        "conditions": [],
                        "rules": [

        {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"

                }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "DualStack is enabled but this partition does not support DualStack",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "rules": [
            {
                "conditions": [],
                "endpoint": {
                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                    "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
    }
],
```

```
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ],
    "type": "tree"
  }
 ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
```

```
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
                }

    },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
```

```
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
              }

            },
              "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
              },
              "params": {

           "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
```

```
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
```

```
      "UseDualStack": true
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
       }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "error": "DualStack is enabled but this partition does not support DualStack"
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {

   "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
      }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
    "expect": {
      "endpoint": {
        "url": "https://example.com"
      }
```

```
    },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://example.com"
                  }
                },
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

 "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
```

```
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

        },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

 {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n        <li>\n  <p>\n            <code>AccountID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n    <code>AmiID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>DualSubscription</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceType</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>ProductCode</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Region</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Status</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>UsageOperation</code>\n          </p>\n        </li>\n      </ul>\n      <p>For each filter, you can use one of the following <code>Operator</code>\n values to \n  \t\tdefine the behavior of the filter:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to\n start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
```

```
        "Instances": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
          }
        },
        "NextToken": {

      "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListLinuxSubscriptions"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
```

```
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n
<li>\n              <p>\n                <code>Subscription</code>\n              </p>\n            </li>\n          </ul>\n
<p>The
 valid Operators for this filter are:</p>\n          <ul>\n            <li>\n              <p>\n
<code>contains</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>equals</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>Notequal</code>\n              </p>\n            </li>\n          </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
      "type": "structure",
      "members": {
        "Subscriptions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
```

```
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "RegisteredSubscriptionProviders"
            }
         }

      },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
         "type": "structure",
         "members": {
            "SubscriptionProviderSources": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
               "traits": {
                  "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }

    },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
       },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
         "type": "structure",
         "members": {
            "RegisteredSubscriptionProviders": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
```

```
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
          }
        },
        "SubscriptionProviderArn": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
          }
        },
```

```
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
                }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

  }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
                    "documentation": "Failed status"
                }
            ]
        }
    },

   "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
            }
          },
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            },
            "smithy.api#uniqueItems": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
          "type": "map",
          "key": {
            "target": "smithy.api#String"
          },
          "value": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
          "type": "structure",
          "members": {
            "Name":
{
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the subscription.</p>"
              }
            },
            "Type": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
              }
            },
            "InstanceCount": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
              "traits": {
                "smithy.api#documentation": "<p>The total amount of running instances using this
```

```
subscription.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
              ]
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
```

```
            },
            {
               "name": "INVALID",
               "value": "INVALID",

"documentation": "INVALID status"
            },
            {
               "name": "PENDING",
               "value": "PENDING",
               "documentation": "PENDING status"
            }
         ]
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
         "target": "smithy.api#String"
      },
      "traits": {
         "smithy.api#length": {
            "min": 0,
            "max": 50
         },
         "smithy.api#sensitive": {}
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
         }
      ],
      "traits": {
```

```
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
{
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
         "type": "map",
         "key": {
            "target": "smithy.api#String"
         },
```

```
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
         "type": "structure",
         "members": {
            "LinuxSubscriptionsDiscovery": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
               "traits": {
                  "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                  "smithy.api#required": {}
               }
            },
            "LinuxSubscriptionsDiscoverySettings": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
               "traits": {
                  "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                  "smithy.api#required": {}
               }
            },
            "AllowUpdate": {
               "target":
 "smithy.api#Boolean",
               "traits": {
                  "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
               }
            }
         }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
           "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
          }
        },
        "StatusMessage": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
          "traits": {
            "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
          }

     },
        "HomeRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
```

```
            "traits": {
                "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
```

```
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string
```

```
 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string
```

```
// License status.
Status types.LicenseDeletionStatus

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
        "type": "structure",
        "members": {
            "DirectoryId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
                "traits": {
                    "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
                }
            },
            "ActiveDirectorySettings":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
                }
            },
            "ActiveDirectoryType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
```

```
            },
            "DomainIpv4List": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 2
                  }
               }
            },
            "DomainCredentialsProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
               }
            },
            "DomainNetworkSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
               },
               {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
               }
```

```
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
```

```
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http":
 {
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
                }
            }
```

```
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
          "type": "union",
          "members": {
            "SecretsManagerCredentialsProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
              "traits": {
```

```
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
         "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
```

```
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
            "smithy.api#length": {
              "min": 1
            },

  "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Attribute": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
          }
        },
        "Operation": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
          }
        },
        "Value": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>Value of the filter.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
```

```
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
          },
          "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
              }
            },
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

    "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details \n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance user.</p>"
             }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
```

```
            "target": "smithy.api#String",
             "traits": {
               "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
           "smithy.api#error": "server",
          "smithy.api#httpError": 500
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
```

```
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
},
{
```

```
    "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
        ],
        "traits": {
            "aws.api#service": {
                "sdkId": "License Manager User Subscriptions",
                "arnNamespace": "license-manager-user-subscriptions",
                "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
                "name": "license-manager-user-subscriptions"
            },
            "aws.protocols#restJson1": {},
            "smithy.api#cors": {
                "additionalAllowedHeaders": [
                    "*",
                    "content-type",
                    "x-amz-content-sha256",
                    "x-amz-user-agent",
                    "x-amzn-platform-id",
                    "x-amzn-trace-id",
                    "content-length",

          "x-api-key",
                    "authorization",
                    "x-amz-date",
                    "x-amz-security-token",
                    "Access-Control-Allow-Headers",
                    "Access-Control-Allow-Methods",
                    "Access-Control-Allow-Origin"
                ],
                "additionalExposedHeaders": [
                    "x-amzn-errortype",
                    "x-amzn-requestid",
                    "x-amzn-trace-id"
                ]
            },
            "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to
utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager User Subscriptions",
            "smithy.rules#endpointRuleSet": {
                "version": "1.0",
                "parameters": {
                    "Region":
{
                        "builtIn": "AWS::Region",
                        "required": false,
                        "documentation": "The AWS region used to dispatch the request.",
```

```
            "type": "String"
        },
        "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
            "type": "Boolean"
        },
        "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
        },
        "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
```

```
                ]
              }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [
              {

                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "endpoint": {
              "url": {
                "ref": "Endpoint"
              },

"properties": {},
                "headers": {}
              },
              "type": "endpoint"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
            {
              "fn": "isSet",
              "argv": [
                {
                  "ref": "Region"
                }
              ]
            }
          ],
```

```
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "aws.partition",

                       "argv": [
                            {
                              "ref": "Region"
                            }
                          ],
                          "assign": "PartitionResult"
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseFIPS"
                              },

true
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseDualStack"
                              },
                              true
                            ]
                          }
                        ],
                        "rules": [
                          {
                            "conditions": [
                              {

"fn": "booleanEquals",
                                  "argv": [
                                    true,
                                    {
                                      "fn": "getAttr",
                                      "argv": [
```

```
                                {
                                    "ref": "PartitionResult"
                                },
                                "supportsFIPS"
                            ]
                        }
                    ]
                },

            {
                "fn": "booleanEquals",
                "argv": [
                    true,
                    {
                        "fn": "getAttr",
                        "argv": [
                            {
                                "ref": "PartitionResult"
                            },
                            "supportsDualStack"
                        ]
                    }

        ]
                }
            ],
            "rules": [
                {
                    "conditions": [],
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [

{
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
```

```
                    },
                    {
                      "conditions": [],
                      "error": "FIPS is enabled but this partition does not support FIPS",
                      "type": "error"

}
                  ],
                  "type": "tree"
                },
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseDualStack"
                        },
                        true
                      ]
                    }
                  ],
                  "rules": [
                    {

    "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            true,
                            {
                              "fn": "getAttr",
                              "argv": [
                                {
                                  "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                              ]

    }
                            ]
                          }
                        ],
                        "rules": [
                          {
                            "conditions": [],
                            "endpoint": {
                              "url": "https://license-manager-user-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

                            ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
```

```
{
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",

    "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint":
{
                        "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",
```

```
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
         "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
```

```
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
```

```
      },
      "params": {
        "Region": "us-isob-east-1",

  "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

       "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
```

```
false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                    "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
    }
  }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
  "type": "structure",
  "members": {
    "ProvisioningStatus": {
      "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
       "traits": {
         "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
```

```
\n\t\t\tlicense server.</p>"
                }
            },
            "HealthStatus": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
                }
            },
            "Ipv4Address": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

  "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
        },
        "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
        },
        "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
        },
        "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
        },
        "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
        },

       "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
        }
    },
    "traits": {
      "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
    }
  },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
      "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
      "type": "structure",
      "members": {
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>",
            "smithy.api#required": {}
          }
        },
        "ServerSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
            "smithy.api#required": {}
          }
        }
      },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {

        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/identity-provider/ListIdentityProviders"
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
```

```
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
     "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
```

contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria. "
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": " The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/ListLicenseServerEndpoints"
            },

          "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
          "type": "structure",
          "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                 "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
```

```
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
             "traits": {
               "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                 "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
```

```
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n          <p>Status</p>\n          </li>\n          <li>\n          <p>Username</p>\n
</li>\n          <li>\n          <p>Domain</p>\n          </li>\n          </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

         }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
```

```
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {

    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
```

```
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
         "type": "structure",
         "members": {
            "IdentityProvider": {

     "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                  "smithy.api#required": {}
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
               "traits":
```

```
{
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",
```

```
    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
            "smithy.api#length": {

             "min": 5,
                "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
            "Endpoint": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
             "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
```

```
                "smithy.api#length": {
                    "min": 1
                },
                "smithy.api#required": {}
            }
        },
        "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
            }

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n        <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
```

```
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
              }
            },
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
          "type": "structure",
          "members": {
            "ProductUserSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                "smithy.api#required": {}
              }

    }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StringList": {
          "type": "list",
          "member": {
```

```
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
```

```
        "traits": {
          "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
```

```
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

           "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
```

configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the: \n \n \n Subnets which you want to add to provision VPC endpoints. \n \n \n Subnets which you want to remove the VPC endpoints from. \n \n \n Security
group ID which permits traffic to the VPC endpoints. \n \n ",
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
"type": "structure",
"members": {
"IdentityProviderSummary": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
"traits": {
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
"type": "structure",
"members": {
"AddSubnets": {

"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets in which License Manager will create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers. ",
"smithy.api#required": {}
}
},
"RemoveSubnets": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets to remove. ",
"smithy.api#required": {}
}
},
"SecurityGroupId": {
"target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

```
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if
```

```
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
```

Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.33 aws-sdk-go-v2-service-s3 1.86.0

1.33.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation

source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this

License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided

that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
   the Work or Derivative Works thereof, You may choose to offer,
   and charge a fee for, acceptance of support, warranty, indemnity,
   or other liability obligations and/or rights consistent with this
   License. However, in accepting such obligations, You may act only
   on Your own behalf and on Your sole responsibility, not on behalf
   of any other Contributor, and only if You agree to indemnify,
   defend, and hold each Contributor harmless for any liability
    incurred by, or claims asserted against, such Contributor by reason
   of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

   To apply the Apache License to your work, attach the following
   boilerplate notice, with the fields enclosed by brackets "[]"
   replaced with your own identifying information. (Don't include
   the brackets!) The text should be enclosed in the appropriate
   comment syntax for the file format. We also recommend that a
   file or class name and description of purpose be included on the
   same "printed page" as the copyright notice for easier
   identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

 Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.34 aws-sdk-go-v2-internal-endpoints 2.7.2

1.34.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter

SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

```
package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
```

```
ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
```

```
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
```

```
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
```

```
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
```

```
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
```

Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent

AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step

```
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)
```

```
// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {
```

```
 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
```

```
 return
err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if
err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
```

```
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
```

```
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {
```

```
 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
```

```
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack,
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
```

```
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
```

```
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
```

```
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
```

```
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
```

```
err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if
err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}
```

```
func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
```

```
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
```

```
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
```

```
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
```

```
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
```

```
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutLicense",
 }
}
AWS SDK for Go
Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.
{
   "smithy": "2.0",
   "shapes": {
      "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
         "type": "integer"
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
         "type": "long"
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },

      {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
                }
            },
```

```
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

       "traits": {
            "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
           }
        },
        "SubscriptionProviderStatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
          }
        },
        "LastSuccessfulDataRetrievalTime": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
      "type": "operation",
      "input": {
        "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
      },
      "output": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
          "type": "structure",
          "members": {}
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
              "traits": {
```

```
                "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }
            },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                 "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
            "AmiId": {
                "target": "smithy.api#String",
                "traits": {
                "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
                }
            },
            "InstanceID": {
                "target": "smithy.api#String",
                "traits": {
                "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
                }
            },
            "InstanceType": {
                "target": "smithy.api#String",
                "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
                }
            },
            "AccountID": {
                "target": "smithy.api#String",
                "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
                }
            },
```

```
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of the instance.</p>"
          }
        },
        "Region": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
          }
        },
        "UsageOperation": {
          "target": "smithy.api#String",

   "traits": {
            "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
          }
        },
        "ProductCode": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
          "traits": {
            "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
          }
        },
        "LastUpdatedTime": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
          }
        },
        "SubscriptionName": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
          }
        },
        "OsVersion": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
```

```
            }
        },
        "SubscriptionProviderCreateTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
        },
        "SubscriptionProviderUpdateTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
            }
        },
        "DualSubscription": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
            }
        },
        "RegisteredWithSubscriptionProvider": {
            "target": "smithy.api#String",
            "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
```

```
            }
        },
        "traits": {
            "smithy.api#documentation":
"<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
            }
        ],
        "traits": {
            "aws.api#service": {
```

```
      "sdkId": "License Manager Linux Subscriptions",
       "arnNamespace": "license-manager-linux-subscriptions",
      "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
    },
    "aws.auth#sigv4": {
      "name": "license-manager-linux-subscriptions"
    },
    "aws.protocols#restJson1": {},
    "smithy.api#cors": {
      "additionalAllowedHeaders": [
        "*",
        "content-type",
        "x-amz-content-sha256",
        "x-amz-user-agent",
        "x-amzn-platform-id",
        "x-amzn-trace-id"
      ],
      "additionalExposedHeaders": [
        "x-amzn-errortype",
        "x-amzn-requestid",
        "x-amzn-trace-id"
      ]
    },
    "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
    "smithy.api#title": "AWS License Manager Linux Subscriptions",
    "smithy.rules#endpointRuleSet": {
      "version": "1.0",
      "parameters": {
        "Region": {
          "builtIn": "AWS::Region",
          "required": false,
          "documentation": "The AWS region used to dispatch the request.",
          "type": "String"
        },
        "UseDualStack": {
          "builtIn": "AWS::UseDualStack",
          "required": true,
          "default": false,
          "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
           "type": "Boolean"
        },
        "UseFIPS": {
          "builtIn": "AWS::UseFIPS",
          "required": true,
          "default": false,
          "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
```

```
configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
        },
        "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }

    ],
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
```

```
                                "ref": "UseDualStack"
                            },
                            true
                        ]

}
                    ],
                    "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "endpoint": {
                        "url": {
                            "ref": "Endpoint"
                        },
                        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }
            ],
            "type": "tree"

        }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "isSet",
                        "argv": [
                            {
                                "ref": "Region"
                            }
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
```

```
                "fn": "aws.partition",
                        "argv": [
                          {
                            "ref": "Region"
                          }
                        ],
                        "assign": "PartitionResult"
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {

                          "ref": "UseFIPS"
                              },
                              true
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseDualStack"
                              },
                              true
                            ]
                          }

],
                        "rules": [
                          {
                            "conditions": [
                              {
                                "fn": "booleanEquals",
                                "argv": [
                                  true,
                                  {
                                    "fn": "getAttr",
                                    "argv": [
                                      {
                                        "ref": "PartitionResult"

                    },
                                          "supportsFIPS"
```

```
                ]
              }
            ]
          },
          {
            "fn": "booleanEquals",
            "argv": [
              true,
              {
                "fn": "getAttr",
                "argv": [

                 {
                      "ref": "PartitionResult"
                  },
                  "supportsDualStack"
                ]
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [],

    "rules": [
                {
                  "conditions": [],
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                    "properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],

            "type": "tree"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
              "type": "error"
```

```
                }
            ],
            "type": "tree"
        },
        {

    "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseFIPS"
                        },
                        true
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {

                "fn": "booleanEquals",
                            "argv": [
                                {
                                    "fn": "getAttr",
                                    "argv": [
                                        {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true

                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",
```

```
    "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],
                                    "type": "tree"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "error": "FIPS is enabled
but this partition does not support FIPS",
                            "type": "error"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseDualStack"
                                },
                                true


                ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        true,
                                        {
                                            "fn": "getAttr",
                                            "argv": [
                                                {

                                                "ref": "PartitionResult"
                                                },
                                                "supportsDualStack"
```

```
                                    ]
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "rules": [

        {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"

                    }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
```

```
                        ],
                        "type": "tree"
                      }
                    ],
                    "type": "tree"
                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
              }
            ],
            "type": "tree"
          }
        ]
      },
      "smithy.rules#endpointTests": {
        "testCases": [
          {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

        }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
```

```
                {

            "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
                  }
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
                  }

        },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                  }
                },
                "params": {
                  "Region": "cn-north-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {

          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
```

```
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

    "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
                {
                  "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
                    }

                 },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                  },
                  "params": {
```

```
            "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
              }
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
            "expect": {
              "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
              }
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS":
false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
```

```
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": true,
      "UseDualStack": true
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
       }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "error": "DualStack is enabled but this partition does not support DualStack"
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {

   "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
      }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
    "expect": {
```

```
                "endpoint": {
                  "url": "https://example.com"
                }

        },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://example.com"
                  }
                },
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

  "Region": "us-east-1",
                  "UseFIPS": false,
```

```
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

        },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
```

```
"<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
```

```
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n             <li>\n                <p>\n                   <code>AccountID</code>\n                </p>\n             </li>\n             <li>\n                <p>\n                   <code>AmiID</code>\n                </p>\n             </li>\n             <li>\n                <p>\n                   <code>DualSubscription</code>\n                </p>\n             </li>\n             <li>\n                <p>\n                   <code>InstanceID</code>\n                </p>\n             </li>\n             <li>\n                <p>\n                   <code>InstanceType</code>\n                </p>\n             </li>\n             <li>\n                <p>\n                   <code>ProductCode</code>\n                </p>\n             </li>\n             <li>\n                <p>\n                   <code>Region</code>\n                </p>\n             </li>\n             <li>\n                <p>\n                   <code>Status</code>\n                </p>\n             </li>\n             <li>\n                <p>\n                   <code>UsageOperation</code>\n                </p>\n             </li>\n          </ul>\n          <p>For each filter, you can use one of the following <code>Operator</code>\n values to \n  \t\tdefine the behavior of the filter:</p>\n          <ul>\n             <li>\n                <p>\n                   <code>contains</code>\n                </p>\n             </li>\n             <li>\n                <p>\n                   <code>equals</code>\n                </p>\n             </li>\n             <li>\n                <p>\n                   <code>Notequal</code>\n                </p>\n             </li>\n          </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
          "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
              "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
            }
          },
          "NextToken": {

       "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
           {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/subscription/ListLinuxSubscriptions"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",

  "items": "Subscriptions"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n      <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n      <p>The valid names for this filter are:</p>\n      <ul>\n        <li>\n          <p>\n            <code>Subscription</code>\n          </p>\n        </li>\n      </ul>\n      <p>The valid Operators for this filter are:</p>\n      <ul>\n        <li>\n          <p>\n            <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n            <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n            <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
```

```
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
```

```
resources for your account.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "RegisteredSubscriptionProviders"
            }
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
         "type": "structure",
         "members": {
            "SubscriptionProviderSources": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
               "traits": {
                  "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }

   },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
          "traits": {
            "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
          }
        },

        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
      },
      "errors": [
        {

      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
```

```
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "resourceArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                 "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
                 "smithy.api#httpLabel": {},
                 "smithy.api#required": {}
               }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "tags": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
           }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "EQUAL",
                "value": "Equal",
                "documentation": "Equal operator"
              },
              {
```

```
                "name": "NOT_EQUAL",
                "value": "NotEqual",
                "documentation": "Not equal operator"
              },
              {
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
            }
```

```
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
              "traits": {
                "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
              }
            },
            "SubscriptionProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
              }
            },
            "SubscriptionProviderStatus": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
              "traits": {
                "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
 {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
              }
            },
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
        },
        "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
            }
        },
        "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
                "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
            }
        },
        "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
            }
        },
        "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "InProgress",
              "value": "InProgress",
              "documentation": "InProgress status"
            },
            {
              "name": "Completed",
              "value": "Completed",
              "documentation": "Completed status"
            },
            {
              "name": "Successful",
              "value": "Successful",
              "documentation": "Successful status"
            },
            {
              "name": "Failed",
              "value": "Failed",
              "documentation": "Failed status"
            }
          ]
        }
```

```
    },

    "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#length": {
                    "min": 1,
                    "max": 100
                }
            }
        },
        "traits": {
            "smithy.api#length": {
                "min": 1,
                "max": 100
            },
            "smithy.api#uniqueItems": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
            "Name":
{
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the subscription.</p>"
                }
            },
            "Type": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
                }
```

```
            },
            "InstanceCount": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
               "traits": {
                  "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
         "type": "string",
         "traits": {
            "smithy.api#enum": [

 {
                  "name": "RedHat",
                  "value": "RedHat",
                  "documentation": "RedHat subscription provider namespace"
               }
            ]
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
         "type": "string",
         "traits": {
```

```
        "smithy.api#enum": [
          {
            "name": "ACTIVE",
            "value": "ACTIVE",
            "documentation": "ACTIVE status"
          },
          {
            "name": "INVALID",
            "value": "INVALID",

"documentation": "INVALID status"
          },
          {
            "name": "PENDING",
            "value": "PENDING",
            "documentation": "PENDING status"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
        "type": "structure",
        "members":
{
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
```

```
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
          "type": "structure",
          "members": {
            "resourceArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}
              }
            },
            "tagKeys": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
              "traits": {

             "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                "smithy.api#httpQuery": "tagKeys",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"
```

```
    },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/UpdateServiceSettings"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
            "smithy.api#required": {}
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
          "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
            "smithy.api#required": {}
          }
        },
        "AllowUpdate": {
          "target":
 "smithy.api#Boolean",
          "traits": {
            "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
```

```
Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }

    },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
        "type": "structure",
```

```
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
```

```
the request.
//
// This member is required.
ClientToken *string

// Digital signature method. The possible value is JSON Web Signature (JWS)
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string
```

```
// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
```

```
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
```

```
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
```

```
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
```

```
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
```

```
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
```

```
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
```

GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE

OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
          }
        },
        "ActiveDirectoryType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
          "traits": {
            "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
```

```
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
            },
            "DomainIpv4List": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 2
                    }
                }
            },
            "DomainCredentialsProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
            },
            "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "SELF_MANAGED",
                    "value": "SELF_MANAGED",
```

```
                "documentation": "SELF_MANAGED type of Active Directory"
              },
              {
                "name": "AWS_MANAGED",
                "value": "AWS_MANAGED",
                "documentation": "AWS_MANAGED type of Active Directory"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Arn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
 {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
```

```
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n         <note>\n          <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
{
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
                }
```

```
            },
            "Tags": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
               }
            }
         },
         "traits": {

      "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
         "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
             }
         },
         "traits": {
            "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current
state of the\n\t\t\tresource.</p>",
            "smithy.api#error": "server"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
```

```
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

        {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
```

Active Directory that contains user identity details. ",
"smithy.api#required": {}
}
},
"LicenseServerSettings": {
"target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
"traits": {
"smithy.api#documentation": " The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server. ",
"smithy.api#required": {}
}
},
"Tags": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
"traits": {
"smithy.api#documentation": " The tags that apply for the license server endpoint. "
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
"type": "structure",
"members": {
"IdentityProviderArn": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
"traits": {
"smithy.api#documentation": " The Amazon Resource Name (ARN) of the identity provider specified in the request. "
}
},
"LicenseServerEndpointArn": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
"traits": {
"smithy.api#documentation": " The ARN of the <code>LicenseServerEndpoint</code> resource. "
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {

```
        "type": "union",
        "members": {
          "SecretsManagerCredentialsProvider":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
         "traits": {
            "smithy.api#output": {}
        }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
         },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/identity-provider/DeregisterIdentityProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
      "type": "structure",
      "members": {
        "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
```

```
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
     },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
         },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/DisassociateUser"
        },
        "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
      "type": "structure",
      "members": {
        "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
            }
          },
          "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary":
 {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
              "smithy.api#length": {
                "min": 1
              },

    "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Attribute": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
            }
          },
          "Value": {
            "target": "smithy.api#String",
            "traits":
 {
              "smithy.api#documentation": "<p>Value of the filter.</p>"
            }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
                    "smithy.api#required": {}
                }
```

```
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of the
identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
              }
            },
            "FailureMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
          "type": "list",
          "member": {

            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
```

```
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
            }
        },
        "Products": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
             "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
            }
        },
        "LastStatusCheckDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
    "type": "structure",
    "members": {
        "Username": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
```

```
                "smithy.api#required": {}
            }
        },
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

    "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
             }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
          },
          "DisassociationDate": {
            "target": "smithy.api#String",
             "traits": {
              "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
           "smithy.api#error": "server",
          "smithy.api#httpError": 500
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
        }
      },
```

```
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
         },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
         },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
            },
            {

   "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
         ],
         "traits": {
            "aws.api#service": {
               "sdkId": "License Manager User Subscriptions",
               "arnNamespace": "license-manager-user-subscriptions",
               "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
               "name": "license-manager-user-subscriptions"
            },
            "aws.protocols#restJson1": {},
            "smithy.api#cors": {
               "additionalAllowedHeaders": [
                  "*",
                  "content-type",
                  "x-amz-content-sha256",
                  "x-amz-user-agent",
                  "x-amzn-platform-id",
                  "x-amzn-trace-id",
                  "content-length",

    "x-api-key",
                  "authorization",
                  "x-amz-date",
                  "x-amz-security-token",
                  "Access-Control-Allow-Headers",
                  "Access-Control-Allow-Methods",
                  "Access-Control-Allow-Origin"
               ],
               "additionalExposedHeaders": [
                  "x-amzn-errortype",
                  "x-amzn-requestid",
                  "x-amzn-trace-id"
               ]
            },
            "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to
utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager User Subscriptions",
            "smithy.rules#endpointRuleSet": {
               "version": "1.0",
```

```
            "parameters": {
              "Region":
{
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
support dual-stack, dispatching the request MAY return an error.",
                "type": "Boolean"
              },
              "UseFIPS": {
                "builtIn": "AWS::UseFIPS",
                "required": true,
                "default": false,
                "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
                "type": "Boolean"
              },
              "Endpoint": {
                "builtIn": "SDK::Endpoint",
                "required": false,
                "documentation": "Override the endpoint used to send this request",
                "type": "String"
              }
            },
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "isSet",
                    "argv": [
                      {
                        "ref": "Endpoint"
                      }
                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
```

```
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [
                  {

                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
```

```
                {
                  "ref": "Region"
                }
              ]
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "aws.partition",

                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ],
                  "assign": "PartitionResult"
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseFIPS"
                        },

true
                      ]
                    },
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseDualStack"
                        },
                        true
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [
                        {
```

```
"fn": "booleanEquals",
                                    "argv": [
                                      true,
                                      {
                                        "fn": "getAttr",
                                        "argv": [
                                          {
                                            "ref": "PartitionResult"
                                          },
                                          "supportsFIPS"
                                        ]
                                      }
                                    ]
                                  },

                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                      true,
                                      {
                                        "fn": "getAttr",
                                        "argv": [
                                          {
                                            "ref": "PartitionResult"
                                          },
                                          "supportsDualStack"
                                        ]
                                      }

                              ]
                                  }
                                ],
                                "rules": [
                                  {
                                    "conditions": [],
                                    "endpoint": {
                                      "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                      "properties": {},
                                      "headers": {}
                                    },
                                    "type": "endpoint"
                                  }

  ],
                                "type": "tree"
                              },
                              {
```

```
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [

 {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "fn": "getAttr",
                        "argv": [

{
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      },
                      true
                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                      "properties": {},
```

```
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

}
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

    "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]

    }
                            ]
                        }
```

```
                                    ],
                                    "rules": [
                                        {
                                            "conditions": [],
                                            "endpoint": {
                                                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }

                                ],
                                    "type": "tree"
                                },
                                {
                                    "conditions": [],
                                    "error": "DualStack is enabled but this partition does not support DualStack",
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                        "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
```

```
        "smithy.rules#endpointTests": {
          "testCases": [
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
              "expect":
{
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint":
```

```
{
                    "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS":
true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": true,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "endpoint":
{
                    "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
```

```
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
              }
            },
            "params": {
              "Region": "us-gov-east-1",
              "UseFIPS": false,
               "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
              }
            },
            "params": {
              "Region": "us-gov-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
              }
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": false

    }
          },
```

```
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
```

```
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",

  "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

     "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
```

```
                    }
                },
                "params": {
                    "UseFIPS": false,
                    "UseDualStack":
false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                    "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
    }
  }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
    "type": "structure",
    "members": {
```

```
            "ProvisioningStatus": {
               "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
                "traits": {
                  "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
               }
            },
            "HealthStatus": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
               "traits": {
                  "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
               }
            },
            "Ipv4Address": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
               }
            },
            "ServerType": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
               "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>"
               }
            },
            "ServerEndpoint": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

    "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
```

```
\n\t\t\taddress of the RDS license server endpoint.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
            }
          },
          "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
              "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the
RDS \n\t\t\tlicense server.</p>"
            }
          },
          "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
              "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent
the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },

         "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when License Manager created the license server
endpoint.</p>"
            }
          }
        },
```

```
        "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop
Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

   "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
              "name": "PROVISIONED",
              "value": "PROVISIONED",
              "documentation": ""
            },
            {
              "name": "DELETING",
              "value": "DELETING",
              "documentation": ""
            },
            {
              "name": "DELETION_FAILED",
              "value": "DELETION_FAILED",
              "documentation": ""

           },
            {
              "name": "DELETED",
              "value": "DELETED",
```

```
                "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "HEALTHY",
              "value": "HEALTHY",
              "documentation": ""
            },
            {
              "name": "UNHEALTHY",
              "value": "UNHEALTHY",
              "documentation": ""
            },
            {
              "name": "NOT_APPLICABLE",
              "value": "NOT_APPLICABLE",
              "documentation": ""
            }
          ]
        }
      },
       "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
        "type": "structure",
        "members": {
          "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of license server.</p>",
              "smithy.api#required": {}
            }
          },
          "ServerSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
```

```
your \n\t\t\tserver.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
```

```
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "IdentityProviderSummaries"
        }
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
      "type": "structure",
      "members": {
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n      <ul>\n        <li>\n          <p>Product</p>\n        </li>\n
      <li>\n          <p>DirectoryId</p>\n        </li>\n      </ul>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

        "traits": {
            "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
```

```
                "smithy.api#required": {}
            }
        },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
     "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/instance/ListInstances"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>Status</p>\n            </li>\n
          <li>\n                <p>InstanceId</p>\n            </li>\n        </ul>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
```

```
      "members": {
        "InstanceSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
         },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
```

```
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/ListLicenseServerEndpoints"
            },

        "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                 "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
        },
```

```
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoints": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
                 "traits": {
                    "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n
</li>\n          <li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target":
"com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
        "smithy.api#http": {
          "method": "GET",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#readonly": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}

       }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
```

```
"com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
    "type": "structure",
    "members": {
        "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
```

```
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
```

```
            "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
            "smithy.api#required": {}
          }
        },
        "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
          "traits": {
            "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of a product for this user.</p>",
            "smithy.api#required": {}
          }
        },
        "ProductUserArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
          }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
          }
        },
        "Domain": {
          "target": "smithy.api#String",
          "traits": {

        "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
          }
        },
        "SubscriptionStartDate": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The start date of a subscription.</p>"
          }
        },
        "SubscriptionEndDate": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The end date of a subscription.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                    "smithy.api#required": {}
                }
```

```
            },
            "Settings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
              "traits":
{
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

        "smithy.api#error": "client",
            "smithy.api#httpError": 404
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
          "type": "structure",
          "members": {
            "SecretId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                "smithy.api#length": {
                  "min": 1
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
          "type": "string",
          "traits": {
            "smithy.api#length": {

           "min": 5,
              "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
          "type": "structure",
          "members": {
            "Endpoint": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
              }
            }
          },
```

```
        "traits": {
          "smithy.api#documentation": "<p>A network endpoint through which you can access one or more servers.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
        "type": "union",
        "members": {
          "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
             "traits": {
               "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
             }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
```

```
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
            "smithy.api#length": {
              "min": 1
            },
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
            "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/user/StartProductSubscription"
            }

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
```

```
  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
                }

  }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
            "ProductUserSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"
```

```
    },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
```

```
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }

    }
        },
        "traits": {
```

```
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation":
"<p>The tags to apply to the specified resource.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {

       "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
```

```
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

          }
            },
            "TagKeys": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
              "traits": {
                "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                "smithy.api#httpQuery": "tagKeys",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
```

```
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
        "type": "structure",
        "members": {
          "AddSubnets": {

         "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
              "smithy.api#required": {}
            }
          },
          "RemoveSubnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
                "smithy.api#required": {}
              }
            },
            "SecurityGroupId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
              "traits": {
                "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
          }
        }
      }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
```

```
 params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
```

```
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
```

```
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
```

setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of

the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or

agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning

Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS

ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.35 aws-sdk-go-v2-service-dynamodbstreams 1.28.0

1.35.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection

```
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer
```

```
// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
```

```
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
```

```
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
```

```
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
```

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS

```
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
  - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
```

```
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string
```

```
 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
```

```
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
 err != nil {
  return err
 }
```

```
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
```

```
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
```

```
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
```

```
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
```

```
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string
```

```
// License entitlements.
//
// This member is required.
Entitlements []types.EntitlementData

// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string
```

```
 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
```

```
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
```

```
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
```

```
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
```

```
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/DeregisterSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                 "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider
resource to deregister.</p>",
                 "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
          "type": "structure",
          "members": {
            "Name": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of name to filter by.</p>"
               }
            },
            "Values": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
              }
            },
            "Operator": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/GetRegisteredSubscriptionProvider"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

          "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
              }
            },
            "SubscriptionProviderStatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
              }
            },
            "LastSuccessfulDataRetrievalTime": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
          "type": "operation",
          "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
```

```
            "uri": "/subscription/GetServiceSettings"

          },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
          "type": "structure",
          "members": {}
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
              "traits": {
                "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
              }
            },
            "StatusMessage": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
              "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
              }
            },
            "HomeRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
              }
            }
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
          "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
          },
          "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
          },
          "AccountID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
          },
          "Region": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
          },
          "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
              "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-
```

subscriptions-usage-operation.html\">Usage\n operation values in the License Manager User Guide. "
}
},
"ProductCode": {
"target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
"traits": {
"smithy.api#documentation": " The product code for the instance. For more information, see Usage\n operation values in the License Manager User Guide . "
}
},
"LastUpdatedTime": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The time in which the last discovery updated the instance details. "
}
},
"SubscriptionName": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The name of the license subscription that the instance uses. "
}
},
"OsVersion": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The operating system software version that runs on your instance. "
}
},
"SubscriptionProviderCreateTime": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The timestamp when you registered
the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses. "
}
},
"SubscriptionProviderUpdateTime": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The timestamp from the last time that the instance synced with the registered \n\t\t\tthird-party Linux subscription provider. "
}
},
"DualSubscription": {
"target": "smithy.api#String",

```
            "traits": {
                "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for \n\t\t\tthe same software on your instance.</p>"
            }
          },
          "RegisteredWithSubscriptionProvider": {
            "target": "smithy.api#String",
            "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta third-party Linux subscription provider that you've registered with License Manager.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
          },
```

```
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
     },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
    }
  ],
  "traits": {
    "aws.api#service": {
      "sdkId": "License Manager Linux Subscriptions",
       "arnNamespace": "license-manager-linux-subscriptions",
      "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
    },
    "aws.auth#sigv4": {
      "name": "license-manager-linux-subscriptions"
    },
    "aws.protocols#restJson1": {},
    "smithy.api#cors": {
      "additionalAllowedHeaders": [
        "*",
        "content-type",
        "x-amz-content-sha256",
        "x-amz-user-agent",
        "x-amzn-platform-id",
        "x-amzn-trace-id"
      ],
      "additionalExposedHeaders": [
```

```
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
```

```
                    }
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }

    ],
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]

}
                            ],
                            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                            "type": "error"
                        },
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": {
                                    "ref": "Endpoint"
                                },
                                "properties": {},
                                "headers": {}
```

```
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"

    }
    ],
    "type": "tree"
},
{
    "conditions": [],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Region"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {

    "fn": "aws.partition",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ],
                            "assign": "PartitionResult"
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {

                                "ref": "UseFIPS"
                                        },
```

```
                    true
                ]
            },
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseDualStack"
                    },
                    true
                ]
            }

    ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

            },
                                        "supportsFIPS"
                                    ]
                                }
                            ]
                        },
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                true,
                                {
                                    "fn": "getAttr",
                                    "argv": [

                                     {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]
```

```
                }
            ],
            "rules": [
                {
                    "conditions": [],

        "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-linux-subscriptions-fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],

                "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both",
            "type": "error"
        }
    ],
    "type": "tree"
},
{

    "conditions": [
        {
            "fn": "booleanEquals",
            "argv": [
                {
                    "ref": "UseFIPS"
                },
                true
            ]
        }
    ],
    "rules": [
        {
```

```
                "conditions": [
                    {

            "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true

                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS is enabled
 but this partition does not support FIPS",
                "type": "error"
            }
        ],
        "type": "tree"
```

```
                    },
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            {
                              "ref": "UseDualStack"
                            },
                            true

                ]
                        }
                      ],
                      "rules": [
                        {
                          "conditions": [
                            {
                              "fn": "booleanEquals",
                              "argv": [
                                true,
                                {
                                  "fn": "getAttr",
                                  "argv": [
                                    {

                                      "ref": "PartitionResult"
                                    },
                                    "supportsDualStack"
                                  ]
                                }
                              ]
                            }
                          ],
                          "rules": [
                            {
                              "conditions": [],
                              "rules": [

    {
                                  "conditions": [],
                                  "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                  },
                                  "type": "endpoint"
```

```
                                        }
                                    ],
                                    "type": "tree"

                            }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
]
},
```

```
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
```

```
                }

        },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

 "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
             },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
```

```
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }

     },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
```

```
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

        "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
```

```
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
```

```
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
```

```
                },
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
```

```
                {
                    "name": "Enabled",
                    "value": "Enabled",
                    "documentation": "Enabled LinuxSubscriptionsDiscovery"

            },
                {
                    "name": "Disabled",
                    "value": "Disabled",
                    "documentation": "Disabled LinuxSubscriptionsDiscovery"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
        "type": "structure",
        "members": {
            "SourceRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "OrganizationIntegration": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
                "traits": {
                    "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },

  {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptionInstances"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "Instances"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n    \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n              <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceType</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>ProductCode</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Region</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Status</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>UsageOperation</code>\n              </p>\n            </li>\n          </ul>\n          <p>For each filter, you can use
```

```
one of the following <code>Operator</code>
 values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n             <p>\n
<code>contains</code>\n             </p>\n          </li>\n          <li>\n             <p>\n
<code>equals</code>\n             </p>\n          </li>\n          <li>\n             <p>\n
<code>Notequal</code>\n             </p>\n          </li>\n        </ul>"
                }
             },
             "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                   "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
             },
             "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                   "smithy.api#length": {
                      "min": 1,
                      "max": 16384
                   }
                }
             }
          },
          "traits": {
             "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
       },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
          "type": "structure",
          "members": {
             "Instances": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
                "traits": {
                   "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
                }
             },
             "NextToken": {

           "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
             }
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
           {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptions"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",

   "items": "Subscriptions"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
```

<code>Subscription</code> with an optional operator to see subscriptions that match,\n partially match, or don't match a certain subscription's name. \n The valid names for this filter are: \n \n \n \n <code>Subscription</code>\n \n \n \n The valid Operators for this filter are: \n \n \n \n <code>contains</code>\n \n \n \n \n <code>equals</code>\n \n \n \n \n <code>Notequal</code>\n \n \n "
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": " The maximum items to return in a request. "
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response. ",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "Subscriptions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
            "traits": {
              "smithy.api#documentation": " An array that contains subscription objects. "
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects. "

```
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListRegisteredSubscriptionProviders"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "RegisteredSubscriptionProviders"
          }
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSources": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
            "traits": {
              "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }

  },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
          "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

           "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
```

```
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
             }
          }
        },
```

```
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
      "type": "structure",
      "members": {
        "tags": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
          "traits": {
            "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "EQUAL",
            "value": "Equal",
            "documentation": "Equal operator"
          },
          {
            "name": "NOT_EQUAL",
            "value": "NotEqual",
            "documentation": "Not equal operator"
          },
          {
            "name": "CONTAINS",
            "value": "Contains",
            "documentation": "Contains operator"
          }
        ],
        "smithy.api#length": {
          "min": 1,
          "max": 20
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
      "type": "string",
      "traits": {
```

```
            "smithy.api#enum": [
               {
                  "name": "Enabled",
                  "value": "Enabled",
                  "documentation": "Enabled OrganizationIntegration"
               },
               {
                  "name": "Disabled",
                  "value": "Disabled",
                  "documentation": "Disabled OrganizationIntegration"
               }
            ]
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
         "type": "list",
         "member": {
            "target": "smithy.api#String"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
          },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/RegisterSubscriptionProvider"
```

```
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
            "smithy.api#required": {}
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
            "smithy.api#required": {}
          }
        },
        "Tags": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
          "traits": {
            "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
          }
        },
        "SubscriptionProviderArn": {
          "target": "smithy.api#String",
          "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
                "traits": {
                "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                 "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
```

```
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"
```

```
}
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "InProgress",
          "value": "InProgress",
          "documentation": "InProgress status"
        },
        {
          "name": "Completed",
          "value": "Completed",
          "documentation": "Completed status"
        },
        {
          "name": "Successful",
          "value": "Successful",
          "documentation": "Successful status"
        },
        {
          "name": "Failed",
          "value": "Failed",
          "documentation": "Failed status"
        }
      ]
    }
  },

 "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
    "type": "list",
    "member": {
      "target": "smithy.api#String",
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        }
      }
    },
    "traits": {
      "smithy.api#length": {
        "min": 1,
        "max": 100
      },
      "smithy.api#uniqueItems": {}
```

```
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
            "Name":
{
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the subscription.</p>"
                }
            },
            "Type": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [

 {
            "name": "RedHat",
            "value": "RedHat",
            "documentation": "RedHat subscription provider namespace"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "ACTIVE",
            "value": "ACTIVE",
            "documentation": "ACTIVE status"
          },
          {
            "name": "INVALID",
            "value": "INVALID",

   "documentation": "INVALID status"
          },
          {
            "name": "PENDING",
            "value": "PENDING",
            "documentation": "PENDING status"
          }
        ]
      }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
      "type": "structure",
      "members":
{
        "resourceArn": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services resource to which to add the specified \n\t\t\tmetadata tags.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
             "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
```

```
            "tagKeys": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
               "traits": {

             "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                  "smithy.api#httpQuery": "tagKeys",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/UpdateServiceSettings"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
```

```
from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
          }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
          "type": "structure",
          "members": {
              "message": {
                  "target": "smithy.api#String"
              }
          },
          "traits": {
              "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
              "smithy.api#error": "client"
          }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
```

```
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
```

```
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
```

```
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType
```

```
 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
```

```
 return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
```

```
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
```

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",

```
            "traits": {
                "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
        },
        "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
        },
        "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
                "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
      "type": "structure",
      "members": {
        "DomainName": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
          }
        },
        "DomainIpv4List": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
          "traits": {
            "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
            "smithy.api#length": {
              "min": 1,
              "max": 2
            }
          }
        },
        "DomainCredentialsProvider": {
          "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
            },
            "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for \n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "SELF_MANAGED",
                    "value": "SELF_MANAGED",
                    "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                    "name": "AWS_MANAGED",
                    "value": "AWS_MANAGED",
                    "documentation": "AWS_MANAGED type of Active Directory"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n          </note>",
            "smithy.api#http":
 {
              "code": 200,
              "method": "POST",
              "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
          "type": "structure",
          "members": {
            "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
              "smithy.api#required": {}
            }
          },
           "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },

        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
```

```
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
      "type": "structure",
      "members": {
        "LicenseServerEndpoint": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
          "traits": {
            "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
```

```
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}

      }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Directory": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
```

```
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary":
{
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
         "type": "structure",
         "members": {
            "Subnets": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                  "smithy.api#length": {
                     "min": 1
                  },
```

```
    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
              }
            },
            "FailureMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
          "type": "list",
          "member": {

            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
    "type": "structure",
    "members": {
        "Username": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

"IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
```

```
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
```

```
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
    "type": "structure",
    "members": {
        "message": {
            "target": "smithy.api#String"
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
         "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
         },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
```

```
        "smithy.api#cors": {
            "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",

            "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
                "Region":
{
                    "builtIn": "AWS::Region",
                    "required": false,
                    "documentation": "The AWS region used to dispatch the request.",
                    "type": "String"
                },
                "UseDualStack": {
                    "builtIn": "AWS::UseDualStack",
                    "required": true,
                    "default": false,
                    "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                    "type": "Boolean"
                },
                "UseFIPS": {
                    "builtIn": "AWS::UseFIPS",
                    "required": true,
```

```
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
            "type": "Boolean"
          },
          "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
             ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [
                  {

                    "fn": "booleanEquals",
                    "argv": [
                      {
```

```
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "aws.partition",

                      "argv": [
                        {
                          "ref": "Region"
                        }
                      ],
                      "assign": "PartitionResult"
                    }
```

```
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseFIPS"
                                    },
```

true

```
                                ]
                            },
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseDualStack"
                                    },
                                    true
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
                                    {
```

"fn": "booleanEquals",

```
                                        "argv": [
                                            true,
                                            {
                                                "fn": "getAttr",
                                                "argv": [
                                                    {
                                                        "ref": "PartitionResult"
                                                    },
                                                    "supportsFIPS"
                                                ]
                                            }
                                        ]
                                    },
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            true,
```

```
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }

                            ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

    ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [

 {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
```

```
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "fn": "getAttr",
                                    "argv": [

        {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

    "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS is enabled but this partition does not support FIPS",
                    "type": "error"

}
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {

        "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]

          }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

            ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
```

```
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                            "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
{
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint":
{
                  "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
```

```
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
```

```
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

    },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",

  "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
```

```
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

     "endpoint": {
            "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
 false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
```

```
                },
                {
                  "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                  "expect": {
                    "error": "Invalid Configuration:
 Dualstack and custom endpoint are not supported"
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>"
              }
            },
            "ServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
              }
            },
            "LicenseServerEndpointId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits":
```

```
{
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
              }
            },
            "LicenseServerEndpointProvisioningStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
              "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
              }
            },
            "LicenseServers": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
              }
            },

           "CreationTime": {
              "target": "smithy.api#Timestamp",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
          "type": "string"
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

      "type": "string",
          "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
              "name": "PROVISIONED",
              "value": "PROVISIONED",
              "documentation": ""
            },
            {
              "name": "DELETING",
              "value": "DELETING",
              "documentation": ""
            },
            {
              "name": "DELETION_FAILED",
              "value": "DELETION_FAILED",
              "documentation": ""

           },
            {
              "name": "DELETED",
              "value": "DELETED",
              "documentation": ""
            }
          ]
       }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
       "type": "string",
       "traits": {
          "smithy.api#enum": [
            {
              "name": "HEALTHY",
              "value": "HEALTHY",
              "documentation": ""
            },
            {
              "name": "UNHEALTHY",
              "value": "UNHEALTHY",
              "documentation": ""
            },
```

```
                {
                    "name": "NOT_APPLICABLE",
                    "value": "NOT_APPLICABLE",
                    "documentation": ""
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
        "type": "structure",
        "members": {
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
```

```
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n        <li>\n        <p>Product</p>\n        </li>\n
        <li>\n        <p>DirectoryId</p>\n        </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                    "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
 that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                    "smithy.api#required": {}
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
 empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
 next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
```

```
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },

{
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
      }
    ],
    "traits": {
      "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
      "smithy.api#http": {
        "code": 200,
        "method": "POST",
        "uri": "/instance/ListInstances"
      },
      "smithy.api#paginated": {
        "inputToken": "NextToken",
        "outputToken": "NextToken",
        "pageSize": "MaxResults",
        "items": "InstanceSummaries"
      }
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
    "type": "structure",
    "members":
```

```
{
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
      <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
      "type": "structure",
      "members": {
        "InstanceSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
          }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/license-server/ListLicenseServerEndpoints"
        },

      "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "LicenseServerEndpoints"
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
      "type": "structure",
      "members": {
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n        <li>\n          <p>IdentityProviderArn</p>\n        </li>\n      </ul>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
      "type": "structure",
      "members": {
        "LicenseServerEndpoints": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " Lists the user-based subscription products available from an identity provider. ",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"

```
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
```

```
This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "ProductUserSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

           }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
```

```
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
    "type": "structure",
    "members": {
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
```

```
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {

            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
              }
            },
            "SubscriptionStartDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The start date of a subscription.</p>"
              }
            },
            "SubscriptionEndDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The end date of a subscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
          "type":
 "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
          "type": "structure",
          "members": {
```

```
            "RdsSalCredentialsProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
```

```
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
          "type": "structure",
          "members": {
            "IdentityProvider": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>",
                "smithy.api#required": {}
              }
            },
            "Settings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
              "traits":
 {
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
```

```
                    "min": 1
                }
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
    "type": "string",
    "traits": {
        "smithy.api#length": {

     "min": 5,
            "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
    "type": "structure",
    "members": {
        "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more servers.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
    "type": "union",
    "members": {
        "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

           "traits": {
              "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688
communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
              "smithy.api#required": {}
            }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StartProductSubscription"
            }

      }
       },
       "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
          "type": "structure",
          "members": {
             "Username": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                   "smithy.api#required": {}
                }
             },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                   "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                   "smithy.api#required": {}
                }
             },
             "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                   "smithy.api#required": {}
                }
             },
             "Domain": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
                }
             },
             "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                   "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
                }
```

```
  }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "ProductUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }

    }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

 "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
 {
        "type": "structure",
        "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {
```

```
      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
```

```
            "type": "structure",
            "members": {
                "message": {
                    "target": "smithy.api#String"
                }
            },
            "traits": {
                "smithy.api#documentation": "<p>A parameter is not valid.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
```

```
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
```

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation

spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.36 utmps 0.1.2.3-r2

1.36.1 Available under license :

Copyright (c) 2018-2024 Laurent Bercot <ska-skaware@skarnet.org>

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.37 go-playground-locales 0.14.1

1.37.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Go Playground

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.38 github.com/aws/aws-sdk-go-v2/service/internal/s3shared 1.19.2

1.38.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody

```
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string
```

```
// Unique, case-sensitive identifier that you provide to ensure the idempotency of
// the request.
//
//
This member is required.
ClientToken *string

// Configuration for consumption of the license. Choose a provisional
// configuration for workloads running with continuous connectivity. Choose a
// borrow configuration for workloads with offline usage.
//
// This member is required.
ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange
```

```
 // Information about
 the license.
 LicenseMetadata []types.Metadata

 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }
```

```
if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
```

```
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CreateLicense",
 }
}
```

```
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
```

```
        path: sdkbase
        ref: ${{ github.base_ref }}
    - name: Checkout this ref
      uses: actions/checkout@v2
      with:
        path: new-ref
        fetch-depth: 0
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
```

ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd

Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
```

```
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
```

```
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
```

```
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
```

```
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata
```

```
 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
```

```
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
 err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
```

```
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
```

```
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
```

```
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
```

```
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
```

```
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options);
err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
```

```
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
```

```
 return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
```

```
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string
```

```
 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.

```
{
  "smithy": "2.0",
  "shapes": {
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
        "type": "integer"
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/DeregisterSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
            "smithy.api#required": {}
          }
```

```
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of name to filter by.</p>"
                 }
            },
            "Values": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
                }
            },
            "Operator": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
                "traits": {
                    "smithy.api#documentation": "<p>An operator for filtering results.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
```

```
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

       "traits": {
            "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
          }
        },
        "SubscriptionProviderStatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
          }
        },
        "LastSuccessfulDataRetrievalTime": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
          }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
      "type": "operation",
      "input": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/GetServiceSettings"

       },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
      "type": "structure",
      "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
```

```
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }
            },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                 "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
            "AmiId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
                }
            },
            "InstanceID": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
                }
            },
            "InstanceType": {
                "target": "smithy.api#String",
```

```
            "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
        },
        "AccountID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
        "Region": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
        },
        "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
        },
        "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
        },
        "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
        },
```

```
            "SubscriptionName": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
               }
            },
            "OsVersion": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
               }
            },
            "SubscriptionProviderCreateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
               }
            },
            "SubscriptionProviderUpdateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
               }
            },
            "DualSubscription": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
               }
            },
            "RegisteredWithSubscriptionProvider": {
               "target": "smithy.api#String",
               "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
         }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>An exception occurred with the service.</p>",
        "smithy.api#error": "server"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
      "type": "service",
      "version": "2018-05-10",
      "operations": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
         },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
          }
        ],
        "traits": {
          "aws.api#service": {
            "sdkId": "License Manager Linux Subscriptions",
             "arnNamespace": "license-manager-linux-subscriptions",
            "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
          },
          "aws.auth#sigv4": {
            "name": "license-manager-linux-subscriptions"
          },
          "aws.protocols#restJson1": {},
          "smithy.api#cors": {
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id"
            ],
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager,
    you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager Linux Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region": {
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
```

```
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                 "type": "Boolean"
            },
            "UseFIPS": {
                "builtIn": "AWS::UseFIPS",
                "required": true,
                "default": false,
                "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                "type": "Boolean"
            },
            "Endpoint": {
                "builtIn": "SDK::Endpoint",
                "required": false,
                "documentation": "Override the endpoint used to send this request",
                "type": "String"
            }
        },
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "isSet",
                        "argv": [
                            {
                                "ref": "Endpoint"
                            }
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            }

    ],
                        "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
```

```
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]

}
                            ],
                            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                            "type": "error"
                        },
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": {
                                    "ref": "Endpoint"
                                },
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"

                }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "isSet",
                                "argv": [
                                    {
```

```
                        "ref": "Region"
                      }
                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {

              "fn": "aws.partition",
                        "argv": [
                          {
                            "ref": "Region"
                          }
                        ],
                        "assign": "PartitionResult"
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {

                             "ref": "UseFIPS"
                              },
                              true
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseDualStack"
                              },
                              true
                            ]
                          }

  ],
                        "rules": [
                          {
                            "conditions": [
                              {
                                "fn": "booleanEquals",
```

```
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [
                      {
                        "ref": "PartitionResult"

},
                    "supportsFIPS"
                    ]
                  }
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [

                     {
                        "ref": "PartitionResult"
                      },
                      "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [],

    "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],
```

```
                "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {

    "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {

            "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true

                    ]
                    }
                ],
```

```
                "rules": [
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS is enabled
 but this partition does not support FIPS",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseDualStack"
                    },
                    true

            ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
```

```
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [
                      {

                        "ref": "PartitionResult"
                      },
                      "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [],
                "rules": [

    {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],
                "type": "tree"

            }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "DualStack is enabled but this partition does not support DualStack",
              "type": "error"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [],
          "rules": [
```

```
                                    {
                                      "conditions": [],
                                      "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                      },
                                      "type": "endpoint"
                                    }
                                  ],
                                  "type": "tree"
                                }
                              ],
                              "type": "tree"
                            }
                          ],
                          "type": "tree"
                        },
                        {
                          "conditions": [],
                          "error": "Invalid Configuration: Missing Region",
                          "type": "error"
                        }
                      ],
                      "type": "tree"
                    }
                  ]
                },
                "smithy.rules#endpointTests": {
                  "testCases": [
                    {
                      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
                      "expect": {
                        "endpoint": {
                          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

                    }
                      },
                      "params": {
                        "Region": "us-east-1",
                        "UseFIPS": true,
                        "UseDualStack": true
                      }
                    },
                    {
                      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                      "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {

      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
```

```
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {

    "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
           },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

     "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }

         },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

        "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
```

```
                "Region": "us-iso-east-1",
                "UseFIPS":
false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                 }
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {

          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                }
```

```
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {

      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
```

```
            },
            {
              "documentation": "For custom endpoint with fips disabled and dualstack enabled",
              "expect": {
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
              },
              "params": {

"Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true,
                "Endpoint": "https://example.com"
              }
            },
            {
              "documentation": "Missing region",
              "expect": {
                "error": "Invalid Configuration: Missing Region"
              }
            }
          ],
          "version": "1.0"
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "Enabled",
            "value": "Enabled",
            "documentation": "Enabled LinuxSubscriptionsDiscovery"

     },
          {
            "name": "Disabled",
            "value": "Disabled",
            "documentation": "Disabled LinuxSubscriptionsDiscovery"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "OrganizationIntegration": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
            "traits": {
              "smithy.api#documentation":
"<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },

  {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptionInstances"
          },
          "smithy.api#idempotent": {},
```

```
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n          <li>\n
  <p>\n                <code>AccountID</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
      <code>AmiID</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>DualSubscription</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>InstanceID</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>InstanceType</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>ProductCode</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>Region</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>Status</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>UsageOperation</code>\n              </p>\n          </li>\n        </ul>\n        <p>For each filter, you can use
one of the following <code>Operator</code>
 values to \n  \t\tdefine the behavior of the filter:</p>\n          <ul>\n          <li>\n              <p>\n
<code>contains</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>equals</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>Notequal</code>\n              </p>\n          </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
```

```
                    "min": 1,
                    "max": 16384
                }
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
    "type": "structure",
    "members": {
        "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
                "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
            }
        },
        "NextToken": {

     "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
        }
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
```

```
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n  <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n  <li>\n              <p>\n                  <code>Subscription</code>\n              </p>\n          </li>\n      </ul>\n  <p>The
  valid Operators for this filter are:</p>\n          <ul>\n          <li>\n              <p>\n  <code>contains</code>\n              </p>\n          </li>\n          <li>\n              <p>\n  <code>equals</code>\n              </p>\n          </li>\n          <li>\n              <p>\n  <code>Notequal</code>\n              </p>\n          </li>\n      </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
          "type": "structure",
          "members": {
            "Subscriptions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
               "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
          },
          "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "RegisteredSubscriptionProviders"
        }
      }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSources": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
          "traits": {
            "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
          }
        },
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }

  },
        "NextToken": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
          "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
            }
          },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
         }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "EQUAL",
            "value": "Equal",
            "documentation": "Equal operator"
          },
          {
            "name": "NOT_EQUAL",
            "value": "NotEqual",
            "documentation": "Not equal operator"
          },
          {
            "name": "CONTAINS",
            "value": "Contains",
            "documentation": "Contains operator"
          }
        ],
        "smithy.api#length": {
          "min": 1,
          "max": 20
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "Enabled",
            "value": "Enabled",
            "documentation": "Enabled OrganizationIntegration"
          },
          {
            "name": "Disabled",
            "value": "Disabled",
            "documentation": "Disabled OrganizationIntegration"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
```

```
Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
                "traits": {
                    "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
                }
            },
            "SubscriptionProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
```

```
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
                "traits": {
                    "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
                }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed
third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and
license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider,
License Manager can get subscription data from the registered provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "InProgress",
                "value": "InProgress",
                "documentation": "InProgress status"
              },
              {
                "name": "Completed",
                "value": "Completed",
                "documentation": "Completed status"
              },
              {
                "name": "Successful",
```

```
                "value": "Successful",
                "documentation": "Successful status"
              },
              {
                "name": "Failed",
                "value": "Failed",
                "documentation": "Failed status"
              }
            ]
          }
        },

        "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
            }
          },
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            },
            "smithy.api#uniqueItems": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
          "type": "map",
          "key": {
            "target": "smithy.api#String"
          },
          "value": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
          "type": "structure",
          "members": {
            "Name":
{
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the subscription.</p>"
```

```
            }
          },
          "Type": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
            }
          },
          "InstanceCount": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
            "traits": {
              "smithy.api#documentation": "<p>The total amount of running instances using this
 subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [

 {
              "name": "RedHat",
              "value": "RedHat",
              "documentation": "RedHat subscription provider namespace"
            }
          ]
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "ACTIVE",
            "value": "ACTIVE",
            "documentation": "ACTIVE status"
          },
          {
            "name": "INVALID",
            "value": "INVALID",

"documentation": "INVALID status"
          },
          {
            "name": "PENDING",
            "value": "PENDING",
            "documentation": "PENDING status"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
        "type": "structure",
        "members":
{
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
```

```
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
             "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tagKeys": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
                "traits": {

              "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                    "smithy.api#httpQuery": "tagKeys",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
```

```
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

    },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
```

```
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }

        },
            "HomeRegions": {
```

```
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }
```

```
 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
```

```
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
```

```
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options)) (*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
```

```
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
```

```
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
```

```
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
```

```
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string
```

```
 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
```

```
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
```

```
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
```

spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR

A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP \n\t\t\taddresses, and the credential provider for user administration.</p>"
          }
        },
        "ActiveDirectoryType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
          "traits": {
            "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
          }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
            },
            "DomainIpv4List": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 2
                    }
                }
            },
            "DomainCredentialsProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
            },
            "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "SELF_MANAGED",
                    "value": "SELF_MANAGED",
                    "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                    "name": "AWS_MANAGED",
                    "value": "AWS_MANAGED",
                    "documentation": "AWS_MANAGED type of Active Directory"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
              }
            ],
            "traits": {
              "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n        <note>\n          <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
              "smithy.api#http":
{
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
              },
              "smithy.api#idempotent": {}
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
            "type": "structure",
            "members": {
              "Username": {
                "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                  "smithy.api#required": {}
                }
              },
              "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
                  "smithy.api#required": {}
                }
              },
              "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                  "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                  "smithy.api#required": {}
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current
```

```
state of the\n\t\t\tresource.</p>",
            "smithy.api#error": "server"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
```

```
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
              "smithy.api#required": {}
            }
          },
          "LicenseServerSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
          "SecretsManagerCredentialsProvider":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
```

```
resource that was deleted.</p>"
                }
              }
            },
             "traits": {
              "smithy.api#output": {}
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
            "type": "operation",
            "input": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
            },
            "output": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
            },
            "errors": [
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
               },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
              }
            ],
            "traits": {
              "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
              "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
              },
              "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
 {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
```

```
    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/DisassociateUser"
        },
```

```
            "smithy.api#idempotent": {}

        }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
            "type": "structure",
            "members": {
                "Username": {
                    "target": "smithy.api#String",
                    "traits": {
                        "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                    }
                },
                "InstanceId": {
                    "target": "smithy.api#String",
                    "traits": {
                        "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                    }
                },
                "IdentityProvider": {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                    "traits": {
                        "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                    }
                },
                "InstanceUserArn": {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                    "traits": {
                        "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                    }
                },
                "Domain": {
                    "target": "smithy.api#String",
                    "traits": {
                        "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
                    }
                }
            },
            "traits": {
                "smithy.api#input": {}
            }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
```

```
        "type": "structure",
        "members": {
          "InstanceUserSummary":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
              "smithy.api#length": {
                "min": 1
              },

    "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Attribute": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
```

```
            }
          },
          "Value": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>Value of the filter.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
          "ActiveDirectoryIdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
             "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
              "smithy.api#required": {}
            }
          },
```

```
        "Settings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
            "smithy.api#required": {}
          }
        },
        "Product": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of the identity provider.</p>",
            "smithy.api#required": {}
          }
        },
        "IdentityProviderArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
          }
        },
        "FailureMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes an identity provider.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
      "type": "list",
      "member": {

        "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
      "type": "structure",
      "members": {
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
            "smithy.api#required": {}
          }
        },
        "Products": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
           "traits": {
            "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
            "smithy.api#required": {}
          }
        },
        "LastStatusCheckDate": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The date of the last status check.</p>"
          }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
      "type": "structure",
      "members": {
        "Username": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
            "smithy.api#required": {}
          }
        },
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },

    "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
          "traits": {
            "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
            "smithy.api#required": {}
          }
        },
        "InstanceUserArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
           }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
          }
        },
```

```
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
             "smithy.api#error": "server",
            "smithy.api#httpError": 500
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
```

```
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
      },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",

         "x-api-key",
            "authorization",
            "x-amz-date",
            "x-amz-security-token",
            "Access-Control-Allow-Headers",
            "Access-Control-Allow-Methods",
            "Access-Control-Allow-Origin"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
```

```
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region":
{
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
              "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
```

```
                }
            ]
        }
    ],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseFIPS"
                        },
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [
                {

                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": {
                    "ref": "Endpoint"
                },

"properties": {},
                "headers": {}
            },
            "type": "endpoint"
        }
```

```
      ],
      "type": "tree"
    },
    {
      "conditions": [
        {
          "fn": "isSet",
          "argv": [
            {
              "ref": "Region"
            }
          ]
        }
      ],
      "rules": [
        {
          "conditions": [
            {
              "fn": "aws.partition",

              "argv": [
                {
                  "ref": "Region"
                }
              ],
              "assign": "PartitionResult"
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
```

true

```
                    ]
                  },
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
```

```
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

 "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      }
                    ]
                  },

                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }

            ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
```

```
                    },
                    "type": "endpoint"
                }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [

  {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [

                {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true
                        ]
                    }
```

```
                                ],
                                "rules": [
                                    {
                                        "conditions": [],
                                        "endpoint": {

                "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS is enabled but this partition does not support FIPS",
                                "type": "error"

}
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]
                                }
                            ],
                            "rules": [
                                {

        "conditions": [
                                        {
                                            "fn": "booleanEquals",
                                            "argv": [
                                                true,
                                                {
                                                    "fn": "getAttr",
                                                    "argv": [
                                                        {
```

```
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]

        }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }

                ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "DualStack is enabled but this partition does not support DualStack",
                    "type": "error"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

            "properties": {},
                "headers": {}
            },
            "type": "endpoint"
        }
    ],
    "type": "tree"
  }
],
"type": "tree"
```

```
            },
            {
              "conditions": [],
              "error": "Invalid Configuration: Missing Region",
              "type": "error"
            }
          ]
        },
        "smithy.rules#endpointTests": {
          "testCases": [
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
              "expect":
{
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
```

```
            "endpoint":
{
                "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
        },
        "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
        }
    },
    {
        "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
        },
        "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
        "expect": {
            "endpoint":
{
                "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
```

```
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false

        }
              },
              {
                "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                  "error": "DualStack is enabled but this partition does not support DualStack"
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                  }

            },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
                "expect": {
                  "endpoint": {
```

```
                "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
              }
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
              "Region": "us-isob-east-1",

"UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
              }
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
            "expect": {

           "endpoint": {
                "url": "https://example.com"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false,
              "Endpoint": "https://example.com"
            }
```

```
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "Missing region",
      "expect": {
        "error": "Invalid Configuration: Missing Region"
      }
    }
  ],
```

```
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
        "type": "structure",
        "members": {
          "ProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
             "traits": {
               "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
            }
          },
          "HealthStatus": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
            "traits": {
              "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
            }
          },
          "Ipv4Address": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
            }
          },
          "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of license server.</p>"
```

```
            }
        },
        "ServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network \n\t\t\taddress of the RDS license server endpoint.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
        },
        "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
        },
        "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
        },
        "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
        },
        "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
        },
```

```
            "CreationTime": {
                "target": "smithy.api#Timestamp",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "PROVISIONING",
                    "value": "PROVISIONING",
                    "documentation": ""
                },
                {
                    "name": "PROVISIONING_FAILED",
                    "value": "PROVISIONING_FAILED",
                    "documentation": ""
                },
                {
                    "name": "PROVISIONED",
                    "value": "PROVISIONED",
                    "documentation": ""
                },
                {
                    "name": "DELETING",
                    "value": "DELETING",
                    "documentation": ""
                },
                {
```

```
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
    "type": "string",
    "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
    }
},
 "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
    "type": "structure",
    "members": {
        "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>",
```

```
                "smithy.api#required": {}
              }
            },
            "ServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
```

```
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n            <li>\n                <p>Product</p>\n            </li>\n
        <li>\n                <p>DirectoryId</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
```

```
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
         "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
    {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
```

```
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
            "InstanceSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
```

```
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/ListLicenseServerEndpoints"
            },

         "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "LicenseServerEndpoints"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
         "type": "structure",
         "members": {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>IdentityProviderArn</p>\n            </li>\n         </ul>"
               }
            },
```

```
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
         "type": "structure",
         "members": {
            "LicenseServerEndpoints": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
                "traits": {
                  "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
         "type":
 "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
```

```
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n
</li>\n          <li>\n            <p>Domain</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
          "type": "structure",
          "members": {
            "ProductUserSummaries": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

```
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
    }
      }
    },
    "traits": {
      "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
    "type": "structure",
    "members": {
      "Tags": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
        "traits": {
          "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
        }
      }
    },
    "traits": {
      "smithy.api#output": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
```

```
      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummaries": {

             "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
         "type": "structure",
         "members": {
            "Username":
{
               "target": "smithy.api#String",
               "traits": {
```

```
                "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
                "smithy.api#required": {}
            }
        },
        "Product": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                "smithy.api#required": {}
            }
        },
        "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a product for this user.</p>",
                "smithy.api#required": {}
            }
        },
        "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {

        "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "SubscriptionStartDate": {
            "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/RegisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
{
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
"<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
```

```
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

       "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
```

```
        "members": {
          "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
        "type": "union",
        "members": {
          "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
             "traits": {
              "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

  "target": "smithy.api#String"
            }
        },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
            "smithy.api#length": {
              "min": 1
            },
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
            "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

        },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/StartProductSubscription"
          }

    }
     },
     "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
       "type": "structure",
       "members": {
         "Username": {
           "target": "smithy.api#String",
           "traits": {
             "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
             "smithy.api#required": {}
           }
         },
         "IdentityProvider": {
           "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
           "traits": {
             "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
```

```
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {

 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                "smithy.api#required": {}
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
              }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/StopProductSubscription"
        }
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
      "type": "structure",
      "members": {
        "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
            }
          },
          "IdentityProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
```

```
                "smithy.api#required": {}
            }

    }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
"<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
```

```
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
 {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
```

```
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

          }
            },
            "TagKeys": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
              "traits": {
                "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                "smithy.api#httpQuery": "tagKeys",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
```

```
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
```

```
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
               }
            },
            "UpdateSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
               "traits": {
                  "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n            <li>\n               <p>Subnets which you want to add to provision VPC endpoints.</p>\n            </li>\n
      <li>\n               <p>Subnets which you want to remove the VPC endpoints from.</p>\n            </li>\n
<li>\n               <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n            </li>\n         </ul>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
         "type": "structure",
         "members": {
            "IdentityProviderSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
               "traits": {
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
         "type": "structure",
         "members": {
            "AddSubnets": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
```

```
                "smithy.api#required": {}
              }
            },
            "RemoveSubnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
                "smithy.api#required": {}
              }
            },
            "SecurityGroupId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
              "traits": {
                "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
          }
        }
      }
    }
    // Code generated by smithy-go-codegen DO NOT EDIT.

    package licensemanager

    import (
     "context"
     "fmt"
     awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
     "github.com/aws/smithy-go/middleware"
     smithyhttp "github.com/aws/smithy-go/transport/http"
```

```
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
```

```
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
 nil {
  return err
```

```
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of,

the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this
License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You

meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate

comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop

Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.39 githubcomgoopenapispec 0.21.0

1.39.1 Available under license :

```
// Copyright 2015 go-swagger maintainers
//
// Licensed under the Apache License, Version 2.0 (the "License");
// you may not use this file except in compliance with the License.
// You may obtain a copy of the License at
//
//    http://www.apache.org/licenses/LICENSE-2.0
//
// Unless required by applicable law or agreed to in writing, software
// distributed under the License is distributed on an "AS IS" BASIS,
// WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
// See the License for the specific language governing permissions and
// limitations under the License.

package spec

import (
 "encoding/json"
```

```
 "github.com/go-openapi/swag"
)

// License information for the exposed API.
//
// For more information: http://goo.gl/8us55a#licenseObject
type License struct {
 LicenseProps
 VendorExtensible
}

// LicenseProps holds the properties of a License object
type LicenseProps struct {
 Name string `json:"name,omitempty"`
 URL  string `json:"url,omitempty"`
}

// UnmarshalJSON
 hydrates License from json
func (l *License) UnmarshalJSON(data []byte) error {
 if err := json.Unmarshal(data, &l.LicenseProps); err != nil {
  return err
 }
 return json.Unmarshal(data, &l.VendorExtensible)
}

// MarshalJSON produces License as json
func (l License) MarshalJSON() ([]byte, error) {
 b1, err := json.Marshal(l.LicenseProps)
 if err != nil {
  return nil, err
 }
 b2, err := json.Marshal(l.VendorExtensible)
 if err != nil {
  return nil, err
 }
 return swag.ConcatJSON(b1, b2), nil
}
```

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent

to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works

that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS,

WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.

```
  You may obtain a copy of the License at

      http://www.apache.org/licenses/LICENSE-2.0

   Unless required by applicable law or agreed to in writing, software
  distributed under the License is distributed on an "AS IS" BASIS,
  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
  See the License for the specific language governing permissions and
  limitations under the License.
// Copyright 2015 go-swagger maintainers
//
// Licensed under the Apache License, Version 2.0 (the "License");
// you may not use this file except in compliance with the License.
// You may obtain a copy of the License at
//
//    http://www.apache.org/licenses/LICENSE-2.0
//
// Unless required by applicable law or agreed to in writing, software
// distributed under the License is distributed on an "AS IS" BASIS,
// WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
// See the License for the specific language governing permissions and
// limitations under the License.

package spec

import (
 "encoding/json"
 "testing"

 "github.com/stretchr/testify/assert"
 "github.com/stretchr/testify/require"
)

var license = License{
 LicenseProps:     LicenseProps{Name: "the name", URL: "the url"},
 VendorExtensible: VendorExtensible{Extensions: map[string]interface{}{"x-license": "custom term"}}}

const licenseJSON = `{
 "name": "the name",
 "url": "the url",
 "x-license": "custom
 term"
}`

func TestIntegrationLicense(t *testing.T) {

 // const licenseYAML = "name: the name\nurl: the url\n"
```

```
b, err := json.MarshalIndent(license, "", "\t")
require.NoError(t, err)
assert.Equal(t, licenseJSON, string(b))

actual := License{}
err = json.Unmarshal([]byte(licenseJSON), &actual)
require.NoError(t, err)
assert.EqualValues(t, license, actual)
}
```

1.40 jsonreference 0.21.0

1.40.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,

and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable

by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only

on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.41 github.com/aws/aws-sdk-go-v2/config 1.30.3

1.41.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd

Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (

```
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
```

```
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {
```

```
// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
```

```
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
```

Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd

Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware

```
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
```

```
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense
```

```
 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
```

```
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
```

```
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if
err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}
```

```
func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
```

```
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
```

```
//   - Beneficiary
//
//   - ProductSKU
//
//   - Fingerprint
//
//   - Status
Filters
[]types.Filter

// Amazon Resource Names (ARNs) of the licenses.
LicenseArns []string

// Maximum number of results to return in a single call.
MaxResults *int32

// Token for the next set of results.
NextToken *string

noSmithyDocumentSerde
}

type ListLicensesOutput struct {

// License details.
Licenses []types.License

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
```

```
if err := addProtocolFinalizerMiddlewares(stack,
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
```

```
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
```

```
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
```

```
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
```

```
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if
err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
```

```
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}
```

```
type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string
```

```
// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
```

```
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
```

```
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },

        {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/DeregisterSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
```

```
            "Name": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of name to filter by.</p>"
               }
            },
            "Values": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
              }
            },
            "Operator": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
              "traits": {
                "smithy.api#documentation": "<p>An operator for filtering results.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
          "type":
 "list",
          "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
          },
          "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/GetRegisteredSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

          "traits": {
              "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
```

```
specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
                 }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
         "type": "structure",
         "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
         "type": "structure",
         "members": {
            "LinuxSubscriptionsDiscovery": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
               "traits": {
                  "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
               }
            },
            "LinuxSubscriptionsDiscoverySettings": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
               "traits": {
                  "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
               }
            },
            "Status": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
               }
            },
            "StatusMessage": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
          "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
          },
          "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
          },
          "AccountID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
```

```
            },
            "Region": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
               }
            },
            "UsageOperation": {
               "target": "smithy.api#String",

   "traits": {
                  "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
               }
            },
            "ProductCode": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
               "traits": {
                  "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
               }
            },
            "LastUpdatedTime": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
               }
            },
            "SubscriptionName": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
               }
            },
            "OsVersion": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
               }
            },
            "SubscriptionProviderCreateTime": {
               "target": "smithy.api#String",
               "traits": {
```

```
                "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
              }
            },
            "SubscriptionProviderUpdateTime": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
              }
            },
            "DualSubscription": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
              }
            },
            "RegisteredWithSubscriptionProvider": {
              "target": "smithy.api#String",
              "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation":
```

```
"<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
            }
        ],
        "traits": {
            "aws.api#service": {
                "sdkId": "License Manager Linux Subscriptions",
                 "arnNamespace": "license-manager-linux-subscriptions",
                "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
            },
```

```
        "aws.auth#sigv4": {
          "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
```

```
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }

],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
```

```
}
                                ],
                                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                                "type": "error"
                            },
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": {
                                        "ref": "Endpoint"
                                    },
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"

                    }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "isSet",
                                    "argv": [
                                        {
                                            "ref": "Region"
                                        }
                                    ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [
                                        {

                    "fn": "aws.partition",
                                                "argv": [
                                                    {
                                                        "ref": "Region"
                                                    }
```

```
                ],
                "assign": "PartitionResult"
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {

                      "ref": "UseFIPS"
                            },
                            true
                        ]
                    },
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }

],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

},
                                                "supportsFIPS"
                                            ]
                                        }
                                    ]
                                },
                                {
```

```
                                    "fn": "booleanEquals",
                                    "argv": [
                                      true,
                                      {
                                        "fn": "getAttr",
                                        "argv": [

                                         {
                                              "ref": "PartitionResult"
                                          },
                                          "supportsDualStack"
                                        ]
                                      }
                                    ]
                                  }
                                ],
                                "rules": [
                                  {
                                    "conditions": [],

      "rules": [
                                      {
                                        "conditions": [],
                                        "endpoint": {
                                          "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                          "properties": {},
                                          "headers": {}
                                        },
                                        "type": "endpoint"
                                      }
                                    ],

                          "type": "tree"
                                  }
                                ],
                                "type": "tree"
                              },
                              {
                                "conditions": [],
                                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",

                                "type": "error"
                              }
                            ],
                            "type": "tree"
                          },
                          {
```

```
            "conditions": [
                                    {
                                       "fn": "booleanEquals",
                                       "argv": [
                                          {
                                             "ref": "UseFIPS"
                                          },
                                          true
                                       ]
                                    }
                                 ],
                                 "rules": [
                                    {
                                       "conditions": [
                                          {

                           "fn": "booleanEquals",
                                             "argv": [
                                                {
                                                   "fn": "getAttr",
                                                   "argv": [
                                                      {
                                                         "ref": "PartitionResult"
                                                      },
                                                      "supportsFIPS"
                                                   ]
                                                },
                                                true

                                          ]
                                       }
                                    ],
                                    "rules": [
                                       {
                                          "conditions": [],
                                          "rules": [
                                             {
                                                "conditions": [],
                                                "endpoint": {
                                                   "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                                   "headers": {}
                                                },
                                                "type": "endpoint"
                                             }
```

```
                ],
                "type": "tree"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [],
            "error": "FIPS is enabled
but this partition does not support FIPS",
            "type": "error"
          }
        ],
        "type": "tree"
      },
      {
        "conditions": [
          {
            "fn": "booleanEquals",
            "argv": [
              {
                "ref": "UseDualStack"
              },
              true

    ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [
                      {

                        "ref": "PartitionResult"
                      },
                      "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
```

```
                "rules": [
                  {
                    "conditions": [],
                    "rules": [

        {
                        "conditions": [],
                        "endpoint": {
                          "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                          "properties": {},
                          "headers": {}
                        },
                        "type": "endpoint"
                      }
                    ],
                    "type": "tree"

                }
                  ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
                  "type": "error"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "rules": [
                {
                  "conditions": [],
                  "endpoint": {
                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                    "properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            }
          ],
          "type": "tree"
```

```
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
            }
        ],
        "type": "tree"
    }
  ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
```

```
                "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
              }

        },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
           },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

    "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
```

```
            }

        },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

      "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
```

```
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
       }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "error": "DualStack is enabled but this partition does not support DualStack"
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {

   "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
      }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
    "expect": {
      "endpoint": {
        "url": "https://example.com"
      }
```

```
    },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://example.com"
                  }
                },
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

 "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
```

```
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

        },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

 {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n        <li>\n  <p>\n            <code>AccountID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n    <code>AmiID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>DualSubscription</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceType</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>ProductCode</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Region</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Status</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>UsageOperation</code>\n          </p>\n        </li>\n      </ul>\n      <p>For each filter, you can use one of the following <code>Operator</code>\n values to \n  \t\tdefine the behavior of the filter:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
```

```
        "Instances": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
          }
        },
        "NextToken": {

      "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListLinuxSubscriptions"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
```

```
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n
<li>\n              <p>\n                <code>Subscription</code>\n              </p>\n            </li>\n          </ul>\n
<p>The
 valid Operators for this filter are:</p>\n          <ul>\n            <li>\n              <p>\n
<code>contains</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>equals</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>Notequal</code>\n              </p>\n            </li>\n          </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
      "type": "structure",
      "members": {
        "Subscriptions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
```

```
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "RegisteredSubscriptionProviders"
            }
         }

      },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
         "type": "structure",
         "members": {
            "SubscriptionProviderSources": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
               "traits": {
                  "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }

    },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
       },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
         "type": "structure",
         "members": {
            "RegisteredSubscriptionProviders": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
               "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
               "name": "EQUAL",
               "value": "Equal",
               "documentation": "Equal operator"
            },
            {
               "name": "NOT_EQUAL",
               "value": "NotEqual",
               "documentation": "Not equal operator"
            },
            {
```

```
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
          }
        },
        "SubscriptionProviderArn": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
          }
        },
```

```
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
               }
            },
            "SubscriptionProviderStatusMessage": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
               }
            },
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

  }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
                    "documentation": "Failed status"
                }
            ]
        }
    },

   "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
            }
          },
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            },
            "smithy.api#uniqueItems": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
          "type": "map",
          "key": {
            "target": "smithy.api#String"
          },
          "value": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
          "type": "structure",
          "members": {
            "Name":
{
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the subscription.</p>"
              }
            },
            "Type": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
              }
            },
            "InstanceCount": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
              "traits": {
                "smithy.api#documentation": "<p>The total amount of running instances using this
```

```
subscription.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
              ]
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
```

```
            },
            {
               "name": "INVALID",
               "value": "INVALID",

"documentation": "INVALID status"
            },
            {
               "name": "PENDING",
               "value": "PENDING",
               "documentation": "PENDING status"
            }
         ]
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
         "target": "smithy.api#String"
      },
      "traits": {
         "smithy.api#length": {
            "min": 0,
            "max": 50
         },
         "smithy.api#sensitive": {}
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
         }
      ],
      "traits": {
```

```
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
{
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
         "type": "map",
         "key": {
            "target": "smithy.api#String"
         },
```

```
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
         "type": "structure",
         "members": {
            "LinuxSubscriptionsDiscovery": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
               "traits": {
                  "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                  "smithy.api#required": {}
               }
            },
            "LinuxSubscriptionsDiscoverySettings": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
               "traits": {
                  "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                  "smithy.api#required": {}
               }
            },
            "AllowUpdate": {
               "target":
 "smithy.api#Boolean",
               "traits": {
                  "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
               }
            }
         }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
           "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
          }
        },
        "StatusMessage": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
          "traits": {
            "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
          }

      },
        "HomeRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
```

```
            "traits": {
                "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
```

```
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string
```

```
// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string
```

```
// License status.
Status types.LicenseDeletionStatus

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
        "type": "structure",
        "members": {
            "DirectoryId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
                "traits": {
                    "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
                }
            },
            "ActiveDirectorySettings":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
                }
            },
            "ActiveDirectoryType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
```

```
            },
            "DomainIpv4List": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 2
                  }
               }
            },
            "DomainCredentialsProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
               }
            },
            "DomainNetworkSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
               },
               {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
               }
```

```
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n          <note>\n             <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
```

```
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http":
 {
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
                }
            }
```

```
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
          "type": "union",
          "members": {
            "SecretsManagerCredentialsProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
              "traits": {
```

```
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
```

```
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
            "smithy.api#length": {
              "min": 1
            },

  "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Attribute": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
          }
        },
        "Operation": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
          }
        },
        "Value": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>Value of the filter.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
          "ActiveDirectoryIdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
```

```
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
          },
          "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
              }
            },
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

    "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details \n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance user.</p>"
             }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
```

```
            "target": "smithy.api#String",
             "traits": {
               "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
           "smithy.api#error": "server",
          "smithy.api#httpError": 500
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
```

```
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
},
{
```

```
    "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
        ],
        "traits": {
            "aws.api#service": {
                "sdkId": "License Manager User Subscriptions",
                "arnNamespace": "license-manager-user-subscriptions",
                "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
                "name": "license-manager-user-subscriptions"
            },
            "aws.protocols#restJson1": {},
            "smithy.api#cors": {
                "additionalAllowedHeaders": [
                    "*",
                    "content-type",
                    "x-amz-content-sha256",
                    "x-amz-user-agent",
                    "x-amzn-platform-id",
                    "x-amzn-trace-id",
                    "content-length",

          "x-api-key",
                    "authorization",
                    "x-amz-date",
                    "x-amz-security-token",
                    "Access-Control-Allow-Headers",
                    "Access-Control-Allow-Methods",
                    "Access-Control-Allow-Origin"
                ],
                "additionalExposedHeaders": [
                    "x-amzn-errortype",
                    "x-amzn-requestid",
                    "x-amzn-trace-id"
                ]
            },
            "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to
utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager User Subscriptions",
            "smithy.rules#endpointRuleSet": {
                "version": "1.0",
                "parameters": {
                    "Region":
{
                        "builtIn": "AWS::Region",
                        "required": false,
                        "documentation": "The AWS region used to dispatch the request.",
```

```
            "type": "String"
        },
        "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
            "type": "Boolean"
        },
        "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
        },
        "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
```

```
                ]
              }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [
              {

                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "endpoint": {
              "url": {
                "ref": "Endpoint"
              },

"properties": {},
                "headers": {}
              },
              "type": "endpoint"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
            {
              "fn": "isSet",
              "argv": [
                {
                  "ref": "Region"
                }
              ]
            }
          ],
```

```
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "aws.partition",

                       "argv": [
                            {
                              "ref": "Region"
                            }
                          ],
                          "assign": "PartitionResult"
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseFIPS"
                              },

true
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseDualStack"
                              },
                              true
                            ]
                          }
                        ],
                        "rules": [
                          {
                            "conditions": [
                              {

"fn": "booleanEquals",
                                  "argv": [
                                    true,
                                    {
                                      "fn": "getAttr",
                                      "argv": [
```

```
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            }
                        ]
                    },

                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [
                                {
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }

            ]
                }
            ],
            "rules": [
                {
                    "conditions": [],
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }

    ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
            "type": "error"
        }
    ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [

{
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
```

```
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

}
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

    "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]

    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

                            ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
```

```
{
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",

      "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint":
{
                        "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",
```

```
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
         "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false

    }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
```

```
      },
      "params": {
        "Region": "us-isob-east-1",

  "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

       "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
```

```
false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                    "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
    }
  }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
  "type": "structure",
  "members": {
    "ProvisioningStatus": {
      "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
      "traits": {
        "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
```

```
\n\t\t\tlicense server.</p>"
                }
            },
            "HealthStatus": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
                }
            },
            "Ipv4Address": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

  "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
        },
        "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
        },
        "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
        },
        "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
        },
        "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
        },

       "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
        }
    },
    "traits": {
      "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
    }
  },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
      "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
      "type": "structure",
      "members": {
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>",
            "smithy.api#required": {}
          }
        },
        "ServerSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
            "smithy.api#required": {}
          }
        }
      },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {

        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/identity-provider/ListIdentityProviders"
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
```

```
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
```

contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria. "
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": " The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/ListLicenseServerEndpoints"
            },

          "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
          "type": "structure",
          "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                 "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
```

```
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
             "traits": {
               "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                 "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
```

```
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n          <p>Status</p>\n          </li>\n          <li>\n          <p>Username</p>\n
</li>\n          <li>\n          <p>Domain</p>\n          </li>\n          </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#readonly": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

           }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
```

```
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {

    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
```

```
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
         "type": "structure",
         "members": {
            "IdentityProvider": {

     "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                  "smithy.api#required": {}
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
               "traits":
```

```
{
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",
```

```
    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
            "smithy.api#length": {

             "min": 5,
                "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
            "Endpoint": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
             "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
```

```
                "smithy.api#length": {
                    "min": 1
                },
                "smithy.api#required": {}
            }
        },
        "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
            }

        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n        <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
```

```
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
              }
            },
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
          "type": "structure",
          "members": {
            "ProductUserSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                "smithy.api#required": {}
              }

    }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StringList": {
          "type": "list",
          "member": {
```

```
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
```

```
        "traits": {
            "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
```

```
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

           "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
```

configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the: \n \n \n Subnets which you want to add to provision VPC endpoints. \n \n \n Subnets which you want to remove the VPC endpoints from. \n \n \n Security
group ID which permits traffic to the VPC endpoints. \n \n ",
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
"type": "structure",
"members": {
"IdentityProviderSummary": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
"traits": {
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
"type": "structure",
"members": {
"AddSubnets": {

"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets in which License Manager will create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers. ",
"smithy.api#required": {}
}
},
"RemoveSubnets": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets to remove. ",
"smithy.api#required": {}
}
},
"SecurityGroupId": {
"target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

```
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if
```

```
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
```

Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.42 easyjson 0.9.0

1.42.1 Available under license :

Copyright (c) 2016 Mail.Ru Group

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.43 swaggo-http-swagger 1.3.4

1.43.1 Available under license :

MIT License

Copyright (c) 2018 Swaggo

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.44 githubcomgoopenapiswag 0.23.1

1.44.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,

including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of

this
License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside

or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
   the Work or Derivative Works thereof, You may choose to offer,
   and charge a fee for, acceptance of support, warranty, indemnity,
   or other liability obligations and/or rights consistent with this
   License. However, in accepting such obligations, You may act only
   on Your own behalf and on Your sole responsibility, not on behalf
   of any other Contributor, and only if You agree to indemnify,
   defend, and hold each Contributor harmless for any liability
    incurred by, or claims asserted against, such Contributor by reason
   of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

   To apply the Apache License to your work, attach the following
   boilerplate notice, with the fields enclosed by brackets "[]"
   replaced with your own identifying information. (Don't include
   the brackets!) The text should be enclosed in the appropriate
   comment syntax for the file format. We also recommend that a
   file or class name and description of purpose be included on the
   same "printed page" as the copyright notice for easier
   identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

 Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.45 x-crypto 0.40.0

1.45.1 Available under license :

Copyright 2009 The Go Authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.46 libcap 2.71-r0

1.46.1 Available under license :

/* SPDX-License-Identifier: BSD-3-Clause OR GPL-2.0-only */

Unless otherwise *explicitly* stated, the following text describes the
licensed conditions under which the contents of this libcap/cap release
may be used and distributed.

The licensed conditions are one or the other of these two Licenses:

- BSD 3-clause
- GPL v2.0

BSD 3-clause:

Redistribution and use in source and binary forms of libcap/cap, with
or without modification, are permitted provided that the following
conditions are met:

1. Redistributions of source code must retain any existing copyright

notice, and this entire permission notice in its entirety,
including the disclaimer of warranties.

2. Redistributions in binary form must reproduce all prior and current
copyright notices, this list of conditions, and the following
disclaimer in the documentation and/or other materials provided
with the distribution.

3.
The name of any author may not be used to endorse or promote
products derived from this software without their specific prior
written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

GPL v2.0:

ALTERNATIVELY, this product may be distributed under the
terms of the
GNU General Public License (v2.0 - see below), in which case the
provisions of the GNU GPL are required INSTEAD OF the above
restrictions. (This clause is necessary due to a potential conflict
between the GNU GPL and the restrictions contained in a BSD-style
copyright.)

Full text of gpl-2.0.txt:

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses,

in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities
other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the
Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your

cost of physically performing source distribution, a complete

machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components
(compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However,
nothing else grants you permission to modify or
distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed
on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity
of any
such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License

incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software
Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL
ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your

school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which
 makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License.
/* SPDX-License-Identifier: BSD-3-Clause OR GPL-2.0-only */

Unless otherwise *explicitly* stated, the following text describes the
licensed conditions under which the contents of this libcap/psx release
may be used and distributed.

The licensed conditions are one or the other of these two Licenses:

 - BSD 3-clause
 - GPL v2.0

BSD 3-clause:

Redistribution and use in source and binary forms of libcap/psx, with
or without modification, are permitted provided that the following
conditions are met:

1. Redistributions of source code must retain any existing copyright
  notice, and this entire permission notice in its entirety,
  including the disclaimer of warranties.

2. Redistributions in binary form must reproduce all prior and current
  copyright notices, this list of conditions, and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.

3.
 The name of any author may not be used to endorse or promote
  products derived from this software without their specific prior
  written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

GPL v2.0:

ALTERNATIVELY, this product may be distributed under the
terms of the
GNU General Public License (v2.0 - see below), in which case the
provisions of the GNU GPL are required INSTEAD OF the above
restrictions. (This clause is necessary due to a potential conflict
between the GNU GPL and the restrictions contained in a BSD-style
copyright.)

Full text of gpl-2.0.txt:

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users.
This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program"

means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities
other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the
Program or any portion
of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program
under
these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but

does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete

machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source

code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot

distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software

Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software
Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL
ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information
on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which
makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General

Public License instead of this License.
/* SPDX-License-Identifier: BSD-3-Clause OR GPL-2.0-only */

Unless otherwise *explicitly* stated, the following text describes the
licensed conditions under which the contents of this libcap release
may be used and distributed.

The licensed conditions are one or the other of these two Licenses:

 - BSD 3-clause
 - GPL v2.0

BSD 3-clause:

Redistribution and use in source and binary forms of libcap, with
or without modification, are permitted provided that the following
conditions are met:

1. Redistributions of source code must retain any existing copyright
  notice, and this entire permission notice in its entirety,
  including the disclaimer of warranties.

2. Redistributions in binary form must reproduce all prior and current
  copyright notices, this list of conditions, and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.

3. The name
 of any author may not be used to endorse or promote
  products derived from this software without their specific prior
  written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

GPL v2.0:

ALTERNATIVELY, this product may be distributed under the terms of
the
GNU General Public License (v2.0 - see below), in which case the
provisions of the GNU GPL are required INSTEAD OF the above
restrictions.

Full text of gpl-2.0.txt:

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using
it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make

sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free
use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program
is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you

conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition,
mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily
used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If
distribution of executable or object code is made by offering
access to copy from a designated place, then offering equivalent
access to copy the source code from the same place counts as
distribution of the source code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program

except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is

implemented
by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new
versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of
preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED

OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING
ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it
starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public
License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License.
/* SPDX-License-Identifier: BSD-3-Clause OR LGPL-2.0-or-later */

Unless otherwise *explicitly* stated the following text describes the
licensed conditions under which the contents of this module release
may be distributed:

Redistribution and use in source and binary forms of this module, with
or without modification, are permitted provided that the following
conditions are met:

1. Redistributions of source code must retain any existing copyright
notice, and this entire permission notice in its entirety,
including the disclaimer of warranties.

2. Redistributions in binary form must reproduce all prior and current
copyright notices, this list of conditions, and the following

disclaimer in the documentation and/or other materials provided
with the distribution.

3. The name of any author may not be used to endorse or promote
products derived from this software without their specific prior
written
permission.

ALTERNATIVELY, this product may be distributed under the terms of the
GNU Library General Public License, in which case the provisions of
the GNU LGPL are required INSTEAD OF the above restrictions. (This
clause is necessary due to a potential conflict between the GNU LGPL
and the restrictions contained in a BSD-style copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF
ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

1.47 logrus 1.9.3

1.47.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Simon Eskildsen

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.48 libssl3 3.3.4-r0

1.48.1 Available under license :

This software is copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software; you can redistribute it and/or modify it under
the same terms as the Perl 5 programming language system itself.

Terms of the Perl programming language system itself

a) the GNU General Public License as published by the Free
Software Foundation; either version 1, or (at your option) any
later version, or
b) the "Artistic License"

--- The GNU General Public License, Version 1, February 1989 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

The GNU General Public License, Version 1, February 1989

GNU GENERAL PUBLIC LICENSE
Version 1, February 1989

Copyright (C) 1989 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The license agreements of most software companies try to keep users
at the mercy of those companies. By contrast, our General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. The
General Public License applies to the Free Software Foundation's
software and to any other program whose authors commit to using it.

You can use it for your programs, too.

When we speak of free software, we are referring to freedom, not price. Specifically, the General Public License is designed to make sure that you have the freedom to give away or sell copies of free software, that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of a such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must tell them their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

The precise terms and conditions
for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any work containing the Program or a portion of it, either verbatim or with modifications. Each licensee is addressed as "you".

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and

appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this General Public License and to the absence of any warranty; and give any other recipients of the
Program a copy of this General Public License
along with the Program. You may charge a fee for the physical act of transferring a copy.

2. You may modify your copy or copies of the Program or any portion of it, and copy and distribute such modifications under the terms of Paragraph 1 above, provided that you also do the following:

a) cause the modified files to carry prominent notices stating that you changed the files and the date of any change; and

b) cause the whole of any work that you distribute or publish, that in whole or in part contains the Program or any part thereof, either with or without modifications, to be licensed at no charge to all third parties under the terms of this General Public License (except that you may choose to grant warranty protection to some or all third parties, at your option).

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive
use
in the simplest and most usual way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this General Public License.

d) You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

Mere aggregation of another independent work with the Program (or its derivative) on a volume of a storage or distribution medium does not bring the other work under the scope of these terms.

3. You may copy and distribute the Program (or a portion or derivative of it, under Paragraph 2) in object code or executable form under the terms of Paragraphs 1 and 2 above provided that you also do one of the following:

a) accompany it with the complete corresponding
machine-readable
source code, which must be distributed under the terms of Paragraphs 1 and 2 above; or,

b) accompany it with a written offer, valid for at least three
years, to give any third party free (except for a nominal charge
for the cost of distribution) a complete machine-readable copy of the
corresponding source code, to be distributed under the terms of
Paragraphs 1 and 2 above; or,

c) accompany it with the information you received as to where the
corresponding source code may be obtained. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or executable form alone.)

Source code for a work means the preferred form of the work for making
modifications to it. For an executable file, complete source code means
all the source code for all modules it contains; but, as a special
exception, it need not include source code for modules which are standard
libraries that
accompany the operating system on which the executable
file runs, or for standard header files or definitions files that
accompany that operating system.

4. You may not copy, modify, sublicense, distribute or transfer the
Program except as expressly provided under this General Public License.
Any attempt otherwise to copy, modify, sublicense, distribute or transfer
the Program is void, and will automatically terminate your rights to use
the Program under this License. However, parties who have received
copies, or rights to use copies, from you under this General Public
License will not have their licenses terminated so long as such parties
remain in full compliance.

5. By copying, distributing or modifying the Program (or any work based
on the Program) you indicate your acceptance of this license to do so,
and all its terms and conditions.

6. Each time you redistribute the Program (or any work based on the
Program), the recipient automatically receives a license from the
original
licensor to copy, distribute or modify the Program subject to these
terms and conditions. You may not impose any further restrictions on the
recipients' exercise of the rights granted herein.

7. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number of the license which applies to it and "any

later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the license, you may choose any version ever published by the Free Software Foundation.

8. If you wish to incorporate parts of the Program into other free programs whose distribution
conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

9. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY
SERVICING,
REPAIR OR CORRECTION.

10. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to humanity, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so,

attach the following notices to the program. It is safest to
attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the
"copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 1, or (at your option)
any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free
Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19xx name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the
appropriate parts of the General Public License. Of course, the
commands you use may be called something other than `show w' and `show
c'; they could even be mouse-clicks or menu items--whatever suits your
program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here a sample; alter
the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
program `Gnomovision' (a program to direct compilers to make passes
at assemblers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

That's all there is to it!

--- The Artistic License 1.0 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

The Artistic License 1.0

The Artistic License

Preamble

The intent of this document is to state the conditions under which a Package may be copied, such that the Copyright Holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

Definitions:

- "Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection
of files created through
textual modification.
- "Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder.
- "Copyright Holder" is whoever is named in the copyright or copyrights for the package.
- "You" is you, if you're thinking about copying or distributing this Package.
- "Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)
- "Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You may make and give away verbatim copies of

the source form of the
Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as ftp.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified
Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide a separate manual page for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) accompany any non-standard executables with their corresponding Standard Version executables, giving the non-standard executables non-standard names,
and clearly documenting the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this

Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that you do not advertise this Package as a product of your own.

6. The scripts and library files supplied as input to or produced as output from the programs of this Package do not automatically fall under the copyright of this Package, but belong to whomever generated them, and may be sold commercially, and may be aggregated with this Package.

7. C or perl subroutines supplied by you and linked into this Package shall not
be considered part of this Package.

8. The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.

9. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

Apache License
Version 2.0, January 2004
https://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity

exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the

Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents

of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,

work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.49 protobuf 1.36.6

1.49.1 Available under license :

Copyright (c) 2018 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE

OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.50 pam 1.6.1-r1

1.50.1 Available under license :

Unless otherwise *explicitly* stated the following text describes the
licensed conditions under which the contents of this Linux-PAM release
may be distributed:

Redistribution and use in source and binary forms of Linux-PAM, with
or without modification, are permitted provided that the following
conditions are met:

1. Redistributions of source code must retain any existing copyright
  notice, and this entire permission notice in its entirety,
  including the disclaimer of warranties.

2. Redistributions in binary form must reproduce all prior and current
  copyright notices, this list of conditions, and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.

3. The name of any author may not be used to endorse or promote
  products derived from this software without their specific prior
  written permission.

ALTERNATIVELY, this product may be distributed
 under the terms of the
GNU General Public License, in which case the provisions of the GNU
GPL are required INSTEAD OF the above restrictions. (This clause is
necessary due to a potential conflict between the GNU GPL and the
restrictions contained in a BSD-style copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

Unless otherwise *explicitly* stated the following text describes the
licensed conditions under which the contents of this libpamc release
may be distributed:

Redistribution and use in source and binary forms of libpamc,
with or without modification, are permitted provided that the
following conditions are met:

1. Redistributions of source code must retain any existing copyright
  notice, and this entire permission notice in its entirety,
  including the disclaimer of warranties.

2. Redistributions in binary form must reproduce all prior and current
  copyright notices, this list of conditions, and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.

3. The name of any author may not be used to endorse or promote
  products derived from this software without their specific prior
  written permission.

ALTERNATIVELY, this product may be distributed under
 the terms of the
GNU Library General Public License (LGPL), in which case the
provisions of the GNU LGPL are required INSTEAD OF the above
restrictions. (This clause is necessary due to a potential conflict
between the GNU LGPL and the restrictions contained in a BSD-style
copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

1.51 go-playground-universal-translator 0.18.1

1.51.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Go Playground

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.52 wojtekwanczyk-average 0.0.0-20240221125520-eb722bafaeb3

1.52.1 Available under license :

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS

"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.53 apk-tools 2.14.6-r3

1.53.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the
freedom
to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions

translate to certain responsibilities for you if you distribute copies of
the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or
for a fee, you must give the recipients all the rights that you have. You
must make sure that they, too, receive or can get the source code. And you
must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2)
offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for
each author's protection and ours, we want to make certain that
everyone understands that there is no warranty for this free software. If
the software is modified by someone else and passed on, we want its recipients
to know that what they have is not the original, so that any problems introduced
by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We
wish to avoid the danger that redistributors of a free program will individually
obtain patent licenses, in effect making the program proprietary. To prevent
this, we have made it clear that any patent must be licensed for everyone's
free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification
follow.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice
placed by the copyright holder saying it may be distributed under
the terms
of this General Public License. The "Program", below, refers to any such program
or work, and a "work based on the Program" means either the Program or any
derivative work under copyright law: that is to say, a work containing the
Program or a portion of it, either verbatim or with modifications and/or translated
into another language. (Hereinafter, translation is included without limitation
in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered
by this License; they are outside its scope. The act of running the Program
is not restricted, and the output from the Program is covered only if its
contents constitute a work based on the Program (independent of having been
made by running the Program). Whether that is true depends on what the Program
does.

1. You may copy and distribute verbatim copies of the Program's source code

as you receive it, in any medium, provided that you conspicuously
and appropriately
publish on each copy an appropriate copyright notice and disclaimer of warranty;
keep intact all the notices that refer to this License and to the absence
of any warranty; and give any other recipients of the Program a copy of this
License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you
may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it,
thus forming a work based on the Program, and copy and distribute such modifications
or work under the terms of Section 1 above, provided that you also meet all
of these conditions:

a) You must cause the modified files to carry prominent notices stating that
you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or
in part contains or is derived from the Program or any part thereof, to be
licensed as a whole at no charge
to all third parties under the terms of this
License.

c) If the modified program normally reads commands interactively when run,
you must cause it, when started running for such interactive use in the most
ordinary way, to print or display an announcement including an appropriate
copyright notice and a notice that there is no warranty (or else, saying that
you provide a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this License.
(Exception: if the Program itself is interactive but does not normally print
such an announcement, your work based on the Program is not required to print
an announcement.)

These requirements apply to the modified work as a whole. If identifiable
sections of that work are not derived from the Program, and can be reasonably
considered independent and separate works in themselves, then this License,
and its terms, do not apply to those sections when you distribute them as
separate works.
But when you distribute the same sections as part of a whole
which is a work based on the Program, the distribution of the whole must be
on the terms of this License, whose permissions for other licensees extend
to the entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest your
rights to work written entirely by you; rather, the intent is to exercise
the right to control the distribution of derivative or collective works based

on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it
with the complete corresponding machine-readable source code,
which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means
all
the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program

is void, and will automatically terminate
your rights under this License. However, parties who have received copies,
or rights, from you under this License will not have their licenses terminated
so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed
it. However, nothing else grants you permission to modify or distribute the
Program or its derivative works. These actions are prohibited by law if you
do not accept this License. Therefore, by modifying or distributing the Program
(or any work based on the Program), you indicate your acceptance of this License
to do so, and all its terms and conditions for copying, distributing or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program),
the recipient automatically receives a license from the original licensor
to copy, distribute or modify the Program subject to these terms and conditions.
You may
not impose any further restrictions on the recipients' exercise of
the rights granted herein. You are not responsible for enforcing compliance
by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement
or for any other reason (not limited to patent issues), conditions are imposed
on you (whether by court order, agreement or otherwise) that contradict the
conditions of this License, they do not excuse you from the conditions of
this License. If you cannot distribute so as to satisfy simultaneously your
obligations under this License and any other pertinent obligations, then as
a consequence you may not distribute the Program at all. For example, if a
patent license would not permit royalty-free redistribution of the Program
by all those who receive copies directly or indirectly through you, then the
only way you could satisfy both it and this License would be to refrain entirely
from distribution of the Program.

If any portion of
this section is held invalid or unenforceable under any
particular circumstance, the balance of the section is intended to apply and
the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents
or other property right claims or to contest validity of any such claims;
this section has the sole purpose of protecting the integrity of the free
software distribution system, which is implemented by public license practices.
Many people have made generous contributions to the wide range of software
distributed through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing to
distribute software through any other system and a licensee cannot impose
that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY

GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.
END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and an idea of what it does.>

Copyright (C)< yyyy> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate

parts of the General Public License. Of course, the commands you use may be
called something other than `show w' and `show c'; they could even be mouse-clicks
or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school,
if any, to sign a "copyright
 disclaimer" for the program, if necessary. Here
is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision'
(which makes passes at compilers) written by James Hacker.

<signature of Ty Coon >, 1 April 1989 Ty Coon, President of Vice This General
Public License does not permit incorporating your program into proprietary
programs. If your program is a subroutine library, you may consider it more
useful to permit linking proprietary applications with the library. If this
is what you want to do, use the GNU Lesser General Public License instead
of this License.

1.54 github.com/aws/aws-sdk-go-v2/aws/protocol/eventstream 1.7.0

1.54.1 Available under license :

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
  - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
```

```
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
```

```
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return
err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
```

```
  ComputePayloadHash
  setLegacyContextSigningOptions
  Signing
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  OperationDeserializer
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
```

```
        uses: actions/setup-python@v2
        with:
          python-version: ${{ matrix.python-version }}
      # ScanCode
      - name: Self-configure scancode
        working-directory: ./scancode-toolkit
        run: ./scancode --help
      - name: Run Scan code on target
        run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
      - name: Run Scan code on pr ref
        run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
      # compare
      - name: License test
        run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
ListLicenses
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  Signing
```

```
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  OperationDeserializer
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType
```

```
//
The ID of the workspace to remove the Grafana Enterprise license from.
//
// This member is required.
WorkspaceId *string

noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

// A structure containing information about the workspace.
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
```

```
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
```

```
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
```

```
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus
```

```
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
```

```
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
```

```
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
```

```
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack);
err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
 spanInitializeStart
 RegisterServiceMetadata
 legacyEndpointContextSetter
 SetLogger
 OperationInputValidation
 spanInitializeEnd
 Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 OperationSerializer
 Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
 Finalize stack step
 spanRetryLoop
 Retry
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 Signing
 Deserialize stack step
```

AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
CheckInLicense
Initialize stack step
spanInitializeStart
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer

```
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  Signing
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  OperationDeserializer
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
```

```
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
```

```
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return
 nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }
```

```
 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer

 // License name.
 //
 // This member is required.
 LicenseName *string

 // Product name.
```

```
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
```

```
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.

```
AssociateLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
```

```
 Signing
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 OperationDeserializer
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
```

```
    // This member is required.
    ClientToken *string

    // Digital signature method. The possible value is JSON Web Signature (JWS)
    // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
    //
    // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
    //
    // This member is required.
    DigitalSignatureMethod types.DigitalSignatureMethod

    // License entitlements. Partial checkouts are not supported.
    //
    // This member is required.
    Entitlements []types.EntitlementData

    // Amazon Resource Name (ARN) of the license. The license must use the borrow
    // consumption configuration.
    //
    // This member is required.
    LicenseArn *string

    // Information about constraints.
    CheckoutMetadata []types.Metadata

    // Node ID.
    NodeId *string

    noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

    // Information about constraints.
    CheckoutMetadata []types.Metadata

    // Allowed license entitlements.
    EntitlementsAllowed
    []types.EntitlementData

    // Date and time at which the license checkout expires.
    Expiration *string

    // Date and time at which the license checkout is issued.
    IssuedAt *string

    // Amazon Resource Name (ARN) of the license.
    LicenseArn *string
```

```
// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
```

```
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
```

```
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
{
  "smithy": "2.0",
  "shapes": {
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
        "type": "integer"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
        "type": "long"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
        "type": "operation",
        "input": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },

        {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/DeregisterSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                 "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider
resource to deregister.</p>",
                 "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
```

```
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/GetRegisteredSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

          "traits": {
                "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
                 }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
```

```
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/GetServiceSettings"

           },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
          "type": "structure",
          "members": {}
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
              }
```

```
            },
            "Status": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
               }
            },
            "StatusMessage": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
               "traits": {
                  "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
               }
            },
            "HomeRegions": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                  "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
         "type": "structure",
         "members": {
            "AmiId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
               }
            },
            "InstanceID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
               }
            },
            "InstanceType": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>The instance type of the resource.</p>"
               }
            },
            "AccountID": {
               "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
        "Region": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
        },
        "UsageOperation": {
            "target": "smithy.api#String",

  "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
        },
        "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
        },
        "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
        },
        "SubscriptionName": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
            }
        },
        "OsVersion": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
            }
          },
          "SubscriptionProviderCreateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
          },
          "SubscriptionProviderUpdateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
            }
          },
          "DualSubscription": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
            }
          },
          "RegisteredWithSubscriptionProvider": {
            "target": "smithy.api#String",
            "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
```

```
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>An exception occurred with the service.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
           },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
```

```
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager Linux Subscriptions",
           "arnNamespace": "license-manager-linux-subscriptions",
          "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
```

```
            "builtIn": "AWS::UseFIPS",
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
          },
          "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }

      ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "rules": [
                  {
                    "conditions": [
```

```
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseDualStack"
                                },
                                true
                            ]

}
                        ],
                        "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                        "type": "error"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": {
                                "ref": "Endpoint"
                            },
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],
                "type": "tree"

            }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "isSet",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
```

```
                "conditions": [
                    {

            "fn": "aws.partition",
                        "argv": [
                            {
                                "ref": "Region"
                            }
                        ],
                        "assign": "PartitionResult"
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {

                              "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            },
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseDualStack"
                                    },
                                    true
                                ]
                            }

],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            true,
                                            {
                                                "fn": "getAttr",
                                                "argv": [
                                                    {
                                                        "ref": "PartitionResult"
```

```
                },
                                "supportsFIPS"
                            ]
                        }
                    ]
                },
                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [

                             {
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [],

        "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],

                "type": "tree"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
```

```
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {

      "conditions": [
            {
              "fn": "booleanEquals",
              "argv": [
                {
                  "ref": "UseFIPS"
                },
                true
              ]
            }
          ],
          "rules": [
            {
              "conditions": [
                {

          "fn": "booleanEquals",
                  "argv": [
                    {
                      "fn": "getAttr",
                      "argv": [
                        {
                          "ref": "PartitionResult"
                        },
                        "supportsFIPS"
                      ]
                    },
                    true

                ]
                }
              ],
              "rules": [
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
```

```
                                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled
 but this partition does not support FIPS",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true

        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
```

```
                                        "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "rules": [

        {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"

                }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                            "properties": {},
                            "headers": {}
```

```
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
]
},
"smithy.rules#endpointTests": {
"testCases": [
{
"documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
"expect": {
"endpoint": {
"url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
},
"params": {
"Region": "us-east-1",
"UseFIPS": true,
"UseDualStack": true
}
},
{
"documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
"expect": {
"endpoint": {
"url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
}
},
"params": {
"Region": "us-east-1",
"UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {

      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
```

```
"documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                      }
                    },
                    "params": {
                      "Region": "cn-north-1",
                      "UseFIPS": true,
                      "UseDualStack": false
                    }
                  },
                  {
                    "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                      }
                     },
                    "params": {
                      "Region": "cn-north-1",
                      "UseFIPS": false,
                      "UseDualStack": true
                    }
                  },
                  {
                    "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
                      }
                    },
                    "params": {
                      "Region": "cn-north-1",
                      "UseFIPS": false,
                      "UseDualStack": false
                    }
                  },
                  {

 "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
                      }
                    },
                    "params": {
                      "Region": "us-gov-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": true
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }

     },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
        }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
        }
    },
    {
        "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
        "expect": {
```

```
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

        "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
```

```
{
  "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
  "expect": {
    "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": true,
    "UseDualStack": true
  }
},
{
  "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
  "expect": {
    "endpoint": {
      "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
     }
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": true,
    "UseDualStack": false
  }
},
{
  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
  "expect": {
    "error": "DualStack is enabled but this partition does not support DualStack"
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": false,
    "UseDualStack": true
  }
},
{

 "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
  "expect": {
    "endpoint": {
      "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
    }
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": false,
    "UseDualStack": false
  }
```

```
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {

      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
      },
```

```
                "params": {

 "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled LinuxSubscriptionsDiscovery"

       },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
        "type": "structure",
        "members": {
          "SourceRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "OrganizationIntegration": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
                "traits": {
                    "smithy.api#documentation":
"<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n          <li>\n
  <p>\n              <code>AccountID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
    <code>AmiID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>DualSubscription</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceType</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>ProductCode</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Region</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Status</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>UsageOperation</code>\n            </p>\n          </li>\n        </ul>\n        <p>For each filter, you can use
one of the following <code>Operator</code>
 values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
```

```
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
            "Instances": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
                }
            },
            "NextToken": {

     "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",

   "items": "Subscriptions"
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
         "type": "structure",
         "members": {
            "Filters": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n         <p>The valid names for this filter are:</p>\n         <ul>\n
<li>\n               <p>\n                  <code>Subscription</code>\n               </p>\n            </li>\n         </ul>\n
<p>The
 valid Operators for this filter are:</p>\n         <ul>\n            <li>\n               <p>\n
<code>contains</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>equals</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>Notequal</code>\n               </p>\n            </li>\n         </ul>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 16384
                  }
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "Subscriptions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
            "traits": {
              "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
             "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
```

```
        ],
        "traits": {
          "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListRegisteredSubscriptionProviders"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "RegisteredSubscriptionProviders"
          }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSources": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
          "traits": {
            "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
          }
        },
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }

  },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
          }
        }
      },
```

```
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
          "traits": {
            "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
          }
        },

        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
      },
      "errors": [
        {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
```

```
      "traits": {
        "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
        "smithy.api#http": {
          "method": "GET",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#readonly": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
      "type": "structure",
      "members": {
        "tags": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
          "traits": {
            "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "EQUAL",
            "value": "Equal",
```

```
                "documentation": "Equal operator"
              },
              {
                "name": "NOT_EQUAL",
                "value": "NotEqual",
                "documentation": "Not equal operator"
              },
              {
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
```

```
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
```

```
            }
        },
        "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
                "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
        },
        "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
            }
        },
        "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
                "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
            }
        },
        "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
            }
        },
        "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed
third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and
license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider,
License Manager can get subscription data from the registered provider.</p>"
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
```

```
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
```

```
                "documentation": "Failed status"
              }
            ]
          }
        },

      "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            }
          }
        },
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
          },
          "smithy.api#uniqueItems": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
          "Name":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the subscription.</p>"
            }
          },
          "Type": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
```

```
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS.</p>"
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": "<p>The total amount of running instances using this subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
```

```
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "ACTIVE",
          "value": "ACTIVE",
          "documentation": "ACTIVE status"
        },
        {
          "name": "INVALID",
          "value": "INVALID",

"documentation": "INVALID status"
        },
        {
          "name": "PENDING",
          "value": "PENDING",
          "documentation": "PENDING status"
        }
      ]
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
    "type": "list",
    "member": {
      "target": "smithy.api#String"
    },
    "traits": {
      "smithy.api#length": {
        "min": 0,
        "max": 50
      },
      "smithy.api#sensitive": {}
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
     },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
 {
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        }
```

```
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

        },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                "smithy.api#required": {}
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                "smithy.api#required": {}
              }
            },
            "AllowUpdate": {
              "target":
```

```
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
                }

     },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated data for Linux\n      subscriptions.</p>"
                }
            }
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
          "smithy.api#error": "client"
        }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }
```

```
 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
```

```
err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack);
 err != nil {
  return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
```

```
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
```

```
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
}
```

```
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack);
 err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
```

SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
GetLicense
Initialize stack step
spanInitializeStart
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput

ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS

"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP \n\t\t\taddresses, and the credential provider for user administration.</p>"
          }
        },
        "ActiveDirectoryType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
          "traits": {
            "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
```

```
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
            },
            "DomainIpv4List": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 2
                    }
                }
            },
            "DomainCredentialsProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
            },
            "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "SELF_MANAGED",
              "value": "SELF_MANAGED",
              "documentation": "SELF_MANAGED type of Active Directory"
            },
            {
              "name": "AWS_MANAGED",
              "value": "AWS_MANAGED",
              "documentation": "AWS_MANAGED type of Active Directory"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
{
               "code": 200,
               "method": "POST",
               "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
                  "smithy.api#required": {}
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
```

```
                "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                "smithy.api#required": {}
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
              }
            }
          },
          "traits": {

        "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
          "type": "integer"
        },
        "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
             }
          },
```

```
        "traits": {
            "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

        {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
      "type": "structure",
      "members": {
        "IdentityProviderArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
            "smithy.api#required": {}
          }
        },
        "LicenseServerSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
            "smithy.api#required": {}
          }
        },
        "Tags": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
          "traits": {
            "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
      "type": "structure",
      "members": {
        "IdentityProviderArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
          }
        },
        "LicenseServerEndpointArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
```

```
                "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
            }
          }
        },
         "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/DeregisterIdentityProvider"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
```

```
        "traits": {
            "smithy.api#output": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
```

```
            "uri": "/user/DisassociateUser"
        },
        "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
      "type": "structure",
      "members": {
        "Username": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
          }
        },
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
          }
        },
        "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
          "traits": {
            "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
          }
        },
        "InstanceUserArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
          }
        },
        "Domain": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
      "type": "structure",
      "members": {
        "InstanceUserSummary":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
          "traits": {
            "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
            "smithy.api#length": {
              "min": 1
            },

  "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Attribute": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
          }
        },
        "Operation": {
          "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
            }
        },
        "Value": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>Value of the filter.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#FilterList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
    "type": "union",
    "members": {
        "ActiveDirectoryIdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
             "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
    "type": "structure",
    "members": {
        "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
                "smithy.api#required": {}
```

```
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
          },
          "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
          "type": "list",
```

```
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },

    "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                 }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
              }
            },
            "AssociationDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
              }
            },
            "DisassociationDate": {
              "target": "smithy.api#String",
               "traits": {
                "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
             "smithy.api#error": "server",
            "smithy.api#httpError": 500
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
```

```
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",

       "x-api-key",
            "authorization",
            "x-amz-date",
            "x-amz-security-token",
            "Access-Control-Allow-Headers",
            "Access-Control-Allow-Methods",
            "Access-Control-Allow-Origin"
          ],
```

```
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager User Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region":
{
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                "type": "Boolean"
              },
              "UseFIPS": {
                "builtIn": "AWS::UseFIPS",
                "required": true,
                "default": false,
                "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                "type": "Boolean"
              },
              "Endpoint": {
                "builtIn": "SDK::Endpoint",
                "required": false,
                "documentation": "Override the endpoint used to send this request",
                "type": "String"
              }
            },
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "isSet",
```

```
            "argv": [
              {
                "ref": "Endpoint"
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [
              {

                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "endpoint": {
              "url": {
                "ref": "Endpoint"
              },

      "properties": {},
                "headers": {}
```

```
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Region"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "aws.partition",

                    "argv": [
                      {
                        "ref": "Region"
                      }
                    ],
                    "assign": "PartitionResult"
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },

true
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
```

```
                "ref": "UseDualStack"
              },
              true
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {
"fn": "booleanEquals",
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [
                      {
                        "ref": "PartitionResult"
                      },
                      "supportsFIPS"
                    ]
                  }
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [
                      {
                        "ref": "PartitionResult"
                      },
                      "supportsDualStack"
                    ]
                  }
        ]
              }
            ],
            "rules": [
              {
                "conditions": [],
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-
```

```
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

    ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [

 {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "fn": "getAttr",
                                                "argv": [

                                {
                                                        "ref": "PartitionResult"
                                                    },
                                                    "supportsFIPS"
                                                ]
                                            },
```

```
                                    true
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {

            "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

}
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseDualStack"
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {

    "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        true,
                                        {
```

```
                                    "fn": "getAttr",
                                    "argv": [
                                        {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                    ]

            }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }

                    ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "endpoint": {
                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
```

```
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "Invalid Configuration: Missing Region",
              "type": "error"
            }
          ]
        },
        "smithy.rules#endpointTests": {
          "testCases": [
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
              "expect":
{
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
```

```
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS":
true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
```

```
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
```

```
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
         "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
```

```
                "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
              }
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": false

}
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
```

```
disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                      }
                    },
                    "params": {
                      "Region": "us-isob-east-1",
                      "UseFIPS": true,
                      "UseDualStack": false
                    }
                  },
                  {
                    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
                    "expect": {
                      "error": "DualStack is enabled but this partition does not support DualStack"
                    },
                    "params": {
                      "Region": "us-isob-east-1",

 "UseFIPS": false,
                      "UseDualStack": true
                    }
                  },
                  {
                    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                      }
                    },
                    "params": {
                      "Region": "us-isob-east-1",
                      "UseFIPS": false,
                      "UseDualStack": false
                    }
                  },
                  {
                    "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
                    "expect": {

                     "endpoint": {
                        "url": "https://example.com"
                      }
                    },
                    "params": {
                      "Region": "us-east-1",
                      "UseFIPS": false,
```

```
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }
          },
          "params": {
            "UseFIPS": false,
            "UseDualStack":
false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with fips enabled and dualstack disabled",
          "expect": {
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with fips disabled and dualstack enabled",
          "expect": {
            "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "Missing region",
          "expect": {
            "error": "Invalid Configuration: Missing Region"
```

```
                    }
                }
            ],
            "version": "1.0"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
    "type": "structure",
    "members": {
        "ProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
             "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
            }
        },
        "HealthStatus": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
            "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
            }
        },
        "Ipv4Address": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
    "type": "structure",
    "members": {
        "IdentityProviderArn": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
            }
        },
        "ServerType": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of license server.</p>"
            }
          },
          "ServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
              "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network \n\t\t\taddress of the RDS license server endpoint.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
          },
          "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
              "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
          },
          "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
              "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
```

```
            },

           "CreationTime": {
              "target": "smithy.api#Timestamp",
              "traits": {
                 "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
              }
           }
        },
        "traits": {
           "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
     },
     "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
     },
     "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
           "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
     },
     "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
           "smithy.api#enum": [
              {
                 "name": "PROVISIONING",
                 "value": "PROVISIONING",
                 "documentation": ""
              },
              {
                 "name": "PROVISIONING_FAILED",
                 "value": "PROVISIONING_FAILED",
                 "documentation": ""
              },
              {
                 "name": "PROVISIONED",
                 "value": "PROVISIONED",
                 "documentation": ""
              },
              {
                 "name": "DELETING",
                 "value": "DELETING",
                 "documentation": ""
```

```
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
    "type": "string",
    "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
    }
},
 "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
    "type": "structure",
    "members": {
        "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The type of license server.</p>",
              "smithy.api#required": {}
            }
          },
          "ServerSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {

          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/ListIdentityProviders"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
            "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
            "smithy.api#required": {}
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
      "type": "operation",
       "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },

        {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/instance/ListInstances"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceSummaries"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
          "type": "structure",
          "members":
 {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>Status</p>\n            </li>\n
```

```
<li>\n <p>InstanceId</p>\n </li>\n </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/ListLicenseServerEndpoints"
          },

       "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "LicenseServerEndpoints"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
             "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>IdentityProviderArn</p>\n          </li>\n        </ul>"
```

```
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
 {
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
```

```
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
             "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n        <li>\n          <p>Status</p>\n        </li>\n        <li>\n          <p>Username</p>\n
</li>\n        <li>\n          <p>Domain</p>\n        </li>\n      </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#readonly": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags you want to retrieve.</p>",
```

```
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}

     }
       }
    },
    "traits": {
       "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
    "type": "structure",
    "members": {
       "Tags": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
          "traits": {
             "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
          }
       }
    },
    "traits": {
       "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
       "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
       "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
       {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
       },
       {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
       },
       {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
       },
       {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
       },
       {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
       },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
 request.</p>"
                }
            },
            "Filters": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
```

```
{
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
                "smithy.api#required": {}
            }
        },
        "Product": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                "smithy.api#required": {}
            }
        },
        "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
         "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a product for this user.</p>",
                "smithy.api#required": {}
            }
        },
        "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {

        "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
            }
```

```
            },
            "SubscriptionStartDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The start date of a subscription.</p>"
               }
            },
            "SubscriptionEndDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The end date of a subscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
user.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
         "type":
 "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
         "type": "structure",
         "members": {
            "RdsSalCredentialsProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
```

```
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/RegisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
```

```
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
 {
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
```

```
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

         "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
      "type": "structure",
      "members": {
        "Endpoint": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
            "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {
```

```
  "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
            "Subnets": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
                "traits": {
                    "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
                    "smithy.api#length": {
                        "min": 1
                    },
                    "smithy.api#required": {}
                }
            },
            "SecurityGroupId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

             "traits": {
                    "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
         },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
        },
        "errors": [
            {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

        },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n        <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/StartProductSubscription"
          }

    }
     },
     "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
       "type": "structure",
       "members": {
         "Username": {
           "target": "smithy.api#String",
           "traits": {
             "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
             "smithy.api#required": {}
           }
         },
         "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n        <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

  }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
```

```
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
```

```
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
            }
          },
          "IdentityProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
                "smithy.api#required": {}
            }

    }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

  "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
```

```
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

          }
            },
            "TagKeys": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
              "traits": {
                "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                "smithy.api#httpQuery": "tagKeys",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

       "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
```

```
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },

            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
                }
            },
            "UpdateSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
                "traits": {
                    "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n            <li>\n                <p>Subnets which you want to add to provision VPC endpoints.</p>\n            </li>\n
        <li>\n                <p>Subnets which you want to remove the VPC endpoints from.</p>\n            </li>\n
<li>\n                <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n            </li>\n        </ul>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
                "traits": {
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
        "type": "structure",
        "members": {
            "AddSubnets": {
```

```
        "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
              "smithy.api#required": {}
            }
          },
          "RemoveSubnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
            "traits": {
              "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A parameter is not valid.</p>",
          "smithy.api#error": "client"
        }
      }
    }
  }
}
```


Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner

or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices

stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
ListReceivedLicenses
Initialize stack step
spanInitializeStart
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper

```
  RequestIDRetriever
  OperationDeserializer
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}
```

```
type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
```

```
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
```

```
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CheckoutLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
```

spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

1.55 asn1-ber 1.5.8-0.20250403174932-29230038a667

1.55.1 Available under license :

The MIT License (MIT)

Copyright (c) 2011-2015 Michael Mitton (mmitton@gmail.com)
Portions copyright (c) 2015-2016 go-asn1-ber Authors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,

WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.56 aws-sdk-go-v2-service-internal-checksum 1.8.2

1.56.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a

copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a

cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with

the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.57 github.com/aws/aws-sdk-go-v2/internal/v4a 1.4.2

1.57.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput

```
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
```

```
  strategy:
    matrix:
      python-version: [3.9]

  steps:
    - name: Checkout target
      uses: actions/checkout@v2
      with:
        path: sdkbase
        ref: ${{ github.base_ref }}
    - name: Checkout this ref
      uses: actions/checkout@v2
      with:
        path: new-ref
        fetch-depth: 0
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
       uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration
```

```
// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}
```

```
type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
```

```
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
```

```
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
```

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop

Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection

```
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string
```

```
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
```

```
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
```

```
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
  }
 }
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
```

```
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
```

```
//
//   - Fingerprint
//
//   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
```

```
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
```

```
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
```

```
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)
```

```
// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
```

```
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
```

```
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options);
err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
```

```
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
```

```
GetLicenseOutput struct {

// License details.
License *types.License

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
```

```
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
```

```
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {
```

```
//
Checkout type.
//
// This member is required.
CheckoutType types.CheckoutType

// Unique, case-sensitive identifier that you provide to ensure the idempotency of
// the request.
//
// This member is required.
ClientToken *string

// License entitlements.
//
// This member is required.
Entitlements []types.EntitlementData

// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
```

```
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
```

```
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
```

```
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
```

```
            },

        {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/DeregisterSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

        "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
```

```
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
             }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
        },
        "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
      "type": "structure",
      "members": {
        "AmiId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
        },
        "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
        },
        "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
        },
        "AccountID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
```

```
            "Region": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
               }
            },
            "UsageOperation": {
               "target": "smithy.api#String",

   "traits": {
                  "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
               }
            },
            "ProductCode": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
               "traits": {
                  "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
               }
            },
            "LastUpdatedTime": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
               }
            },
            "SubscriptionName": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
               }
            },
            "OsVersion": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
               }
            },
            "SubscriptionProviderCreateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp when you registered
```

```
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
                }
            },
            "SubscriptionProviderUpdateTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
                }
            },
            "DualSubscription": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
                }
            },
            "RegisteredWithSubscriptionProvider": {
                "target": "smithy.api#String",
                "traits": {

      "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
```

```
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
       },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
      }
    ],
    "traits": {
      "aws.api#service": {
        "sdkId": "License Manager Linux Subscriptions",
         "arnNamespace": "license-manager-linux-subscriptions",
        "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
      },
      "aws.auth#sigv4": {
        "name": "license-manager-linux-subscriptions"
```

```
    },
    "aws.protocols#restJson1": {},
    "smithy.api#cors": {
      "additionalAllowedHeaders": [
        "*",
        "content-type",
        "x-amz-content-sha256",
        "x-amz-user-agent",
        "x-amzn-platform-id",
        "x-amzn-trace-id"
      ],
      "additionalExposedHeaders": [
        "x-amzn-errortype",
        "x-amzn-requestid",
        "x-amzn-trace-id"
      ]
    },
    "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
    "smithy.api#title": "AWS License Manager Linux Subscriptions",
    "smithy.rules#endpointRuleSet": {
      "version": "1.0",
      "parameters": {
        "Region": {
          "builtIn": "AWS::Region",
          "required": false,
          "documentation": "The AWS region used to dispatch the request.",
          "type": "String"
        },
        "UseDualStack": {
          "builtIn": "AWS::UseDualStack",
          "required": true,
          "default": false,
          "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
           "type": "Boolean"
        },
        "UseFIPS": {
          "builtIn": "AWS::UseFIPS",
          "required": true,
          "default": false,
          "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
          "type": "Boolean"
        },
        "Endpoint": {
          "builtIn": "SDK::Endpoint",
          "required": false,
```

```
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }

],
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]
```

```
}
                        ],
                        "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                        "type": "error"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": {
                                "ref": "Endpoint"
                            },
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],
                "type": "tree"

            }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "isSet",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {

            "fn": "aws.partition",
                                    "argv": [
                                        {
                                            "ref": "Region"
                                        }
                                    ],
```

```
                "assign": "PartitionResult"
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {

                    "ref": "UseFIPS"
                            },
                            true
                        ]
                    },
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }

],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

        },
                                    "supportsFIPS"
                                ]
                            }
                        ]
                    },
                    {
                        "fn": "booleanEquals",
```

```
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [

                     {
                          "ref": "PartitionResult"
                       },
                       "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [],

    "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],

            "type": "tree"
                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
```

```
            "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
                    true
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {

          "fn": "booleanEquals",
                      "argv": [
                        {
                          "fn": "getAttr",
                          "argv": [
                            {
                              "ref": "PartitionResult"
                            },
                            "supportsFIPS"
                          ]
                        },
                        true

                    ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "rules": [
                        {
                          "conditions": [],
                          "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                            "headers": {}
                          },
                          "type": "endpoint"
                        }
                      ],
```

```
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS is enabled
but this partition does not support FIPS",
            "type": "error"
        }
    ],
    "type": "tree"
},
{
    "conditions": [
        {
            "fn": "booleanEquals",
            "argv": [
                {
                    "ref": "UseDualStack"
                },
                true

            ]
        }
    ],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [
                                {

                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }
                    ]
                }
            ],
            "rules": [
```

```
                                    {
                                        "conditions": [],
                                        "rules": [

        {
                                                "conditions": [],
                                                "endpoint": {
                                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                    "properties": {},
                                                    "headers": {}
                                                },
                                                "type": "endpoint"
                                            }
                                        ],
                                        "type": "tree"

                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
```

```
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
            }
        ],
        "type": "tree"
    }
  ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
```

```
                "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
              }

        },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
```

```
            }

        },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

      "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
```

```
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
       }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "error": "DualStack is enabled but this partition does not support DualStack"
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {

   "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
      }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
    "expect": {
      "endpoint": {
        "url": "https://example.com"
      }
```

```
    },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://example.com"
                  }
                },
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

 "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
```

```
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

        },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

 {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n        <li>\n  <p>\n            <code>AccountID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n    <code>AmiID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>DualSubscription</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceType</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>ProductCode</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Region</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Status</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>UsageOperation</code>\n          </p>\n        </li>\n      </ul>\n      <p>For each filter, you can use one of the following <code>Operator</code>\n values to \n  \t\tdefine the behavior of the filter:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
```

```
            "Instances": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
               "traits": {
                  "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
               }
            },
            "NextToken": {

         "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
```

```
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n
<li>\n              <p>\n                <code>Subscription</code>\n              </p>\n            </li>\n          </ul>\n
<p>The
 valid Operators for this filter are:</p>\n          <ul>\n            <li>\n              <p>\n
<code>contains</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>equals</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>Notequal</code>\n              </p>\n            </li>\n          </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
      "type": "structure",
      "members": {
        "Subscriptions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
```

```
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "RegisteredSubscriptionProviders"
            }
         }

      },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
         "type": "structure",
         "members": {
            "SubscriptionProviderSources": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
               "traits": {
                  "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }

    },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
       },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
         "type": "structure",
         "members": {
            "RegisteredSubscriptionProviders": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
               "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
               "name": "EQUAL",
               "value": "Equal",
               "documentation": "Equal operator"
            },
            {
               "name": "NOT_EQUAL",
               "value": "NotEqual",
               "documentation": "Not equal operator"
            },
            {
```

```
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
          }
        },
        "SubscriptionProviderArn": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
          }
        },
```

```
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
               }
            },
            "SubscriptionProviderStatusMessage": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
               }
            },
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

  }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
                    "documentation": "Failed status"
                }
            ]
        }
    },

   "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
            }
          },
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            },
            "smithy.api#uniqueItems": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
          "type": "map",
          "key": {
            "target": "smithy.api#String"
          },
          "value": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
          "type": "structure",
          "members": {
            "Name":
{
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the subscription.</p>"
              }
            },
            "Type": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
              }
            },
            "InstanceCount": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
              "traits": {
                "smithy.api#documentation": "<p>The total amount of running instances using this
```

```
subscription.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
              ]
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                  "name": "ACTIVE",
                  "value": "ACTIVE",
                  "documentation": "ACTIVE status"
```

```
            },
            {
               "name": "INVALID",
               "value": "INVALID",

"documentation": "INVALID status"
            },
            {
               "name": "PENDING",
               "value": "PENDING",
               "documentation": "PENDING status"
            }
         ]
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
         "target": "smithy.api#String"
      },
      "traits": {
         "smithy.api#length": {
            "min": 0,
            "max": 50
         },
         "smithy.api#sensitive": {}
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
         }
      ],
      "traits": {
```

```
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
{
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
         "type": "map",
         "key": {
            "target": "smithy.api#String"
         },
```

```
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
           "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
          }
        },
        "StatusMessage": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
          "traits": {
            "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
          }

     },
        "HomeRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
```

```
            "traits": {
                "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
```

```
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string
```

```
// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string
```

```
// License status.
Status types.LicenseDeletionStatus

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
        "type": "structure",
        "members": {
            "DirectoryId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
                "traits": {
                    "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
                }
            },
            "ActiveDirectorySettings":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
                }
            },
            "ActiveDirectoryType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
```

```
            },
            "DomainIpv4List": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 2
                  }
               }
            },
            "DomainCredentialsProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
               }
            },
            "DomainNetworkSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
               },
               {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
               }
```

```
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
```

```
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http":
 {
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
                }
            }
```

```
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
          "type": "union",
          "members": {
            "SecretsManagerCredentialsProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
              "traits": {
```

```
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
         "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
```

```
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
            "smithy.api#length": {
              "min": 1
            },

  "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Attribute": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
          }
        },
        "Operation": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
          }
        },
        "Value": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>Value of the filter.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
```

```
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
          },
          "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
              }
            },
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

    "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details \n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance user.</p>"
             }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
```

```
            "target": "smithy.api#String",
             "traits": {
               "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
           "smithy.api#error": "server",
          "smithy.api#httpError": 500
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
```

```
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
},
{
```

```
    "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
        ],
        "traits": {
            "aws.api#service": {
                "sdkId": "License Manager User Subscriptions",
                "arnNamespace": "license-manager-user-subscriptions",
                "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
                "name": "license-manager-user-subscriptions"
            },
            "aws.protocols#restJson1": {},
            "smithy.api#cors": {
                "additionalAllowedHeaders": [
                    "*",
                    "content-type",
                    "x-amz-content-sha256",
                    "x-amz-user-agent",
                    "x-amzn-platform-id",
                    "x-amzn-trace-id",
                    "content-length",

          "x-api-key",
                    "authorization",
                    "x-amz-date",
                    "x-amz-security-token",
                    "Access-Control-Allow-Headers",
                    "Access-Control-Allow-Methods",
                    "Access-Control-Allow-Origin"
                ],
                "additionalExposedHeaders": [
                    "x-amzn-errortype",
                    "x-amzn-requestid",
                    "x-amzn-trace-id"
                ]
            },
            "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to
utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager User Subscriptions",
            "smithy.rules#endpointRuleSet": {
                "version": "1.0",
                "parameters": {
                    "Region":
{
                        "builtIn": "AWS::Region",
                        "required": false,
                        "documentation": "The AWS region used to dispatch the request.",
```

```
            "type": "String"
        },
        "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
            "type": "Boolean"
        },
        "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
        },
        "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
```

```
                ]
              }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [
              {

                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "endpoint": {
              "url": {
                "ref": "Endpoint"
              },

"properties": {},
                "headers": {}
              },
              "type": "endpoint"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
            {
              "fn": "isSet",
              "argv": [
                {
                  "ref": "Region"
                }
              ]
            }
          ],
```

```
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "aws.partition",

                       "argv": [
                            {
                              "ref": "Region"
                            }
                          ],
                          "assign": "PartitionResult"
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseFIPS"
                              },

true
                              ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseDualStack"
                              },
                              true
                            ]
                          }
                        ],
                        "rules": [
                          {
                            "conditions": [
                              {

"fn": "booleanEquals",
                                  "argv": [
                                    true,
                                    {
                                      "fn": "getAttr",
                                      "argv": [
```

```
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            }
                        ]
                    },

                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [
                                {
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }

            ]
                }
            ],
            "rules": [
                {
                    "conditions": [],
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }

    ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
            "type": "error"
        }
    ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [

{
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
```

```
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

}
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

    "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]

    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

                            ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
```

```
{
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",

      "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint":
{
                        "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",
```

```
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
         "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false

    }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
```

```
        },
        "params": {
          "Region": "us-isob-east-1",

  "UseFIPS": false,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
          }
        },
        "params": {
          "Region": "us-isob-east-1",
          "UseFIPS": false,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
        "expect": {

         "endpoint": {
            "url": "https://example.com"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": false,
          "Endpoint": "https://example.com"
        }
      },
      {
        "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
        "expect": {
          "endpoint": {
            "url": "https://example.com"
          }
        },
        "params": {
          "UseFIPS": false,
          "UseDualStack":
```

```
false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                    "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
    }
  }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
  "type": "structure",
  "members": {
    "ProvisioningStatus": {
      "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
      "traits": {
        "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
```

```
\n\t\t\tlicense server.</p>"
                }
            },
            "HealthStatus": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
                }
            },
            "Ipv4Address": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

  "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
        },
        "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
        },
        "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
        },
        "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
        },
        "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
        },

       "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
        }
    },
    "traits": {
      "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
    }
  },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
      "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
      "type": "structure",
      "members": {
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>",
            "smithy.api#required": {}
          }
        },
        "ServerSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
            "smithy.api#required": {}
          }
        }
      },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {

        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/identity-provider/ListIdentityProviders"
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
```

```
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
```

contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria. "
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": " The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/ListLicenseServerEndpoints"
            },

          "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
          "type": "structure",
          "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                 "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
```

```
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
             "traits": {
               "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListProductSubscriptions"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "ProductUserSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
 {
        "type": "structure",
        "members": {
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
             "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
```

```
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n        <li>\n        <p>Status</p>\n        </li>\n        <li>\n        <p>Username</p>\n
</li>\n        <li>\n        <p>Domain</p>\n        </li>\n        </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

         }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
```

```
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {

    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
```

```
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
         "type": "structure",
         "members": {
            "IdentityProvider": {

     "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                  "smithy.api#required": {}
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
               "traits":
```

```
{
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",
```

```
    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
            "smithy.api#length": {

             "min": 5,
                "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
            "Endpoint": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
             "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
```

```
                "smithy.api#length": {
                    "min": 1
                },
                "smithy.api#required": {}
            }
        },
        "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
            }

    }
     },
     "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n        <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
```

```
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
              }
            },
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
          "type": "structure",
          "members": {
            "ProductUserSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                "smithy.api#required": {}
              }

    }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StringList": {
          "type": "list",
          "member": {
```

```
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
```

```
        "traits": {
          "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
```

```
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

           "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
```

configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the: \n \n \n Subnets which you want to add to provision VPC endpoints. \n \n \n Subnets which you want to remove the VPC endpoints from. \n \n \n Security
group ID which permits traffic to the VPC endpoints. \n \n ",
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
"type": "structure",
"members": {
"IdentityProviderSummary": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
"traits": {
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
"type": "structure",
"members": {
"AddSubnets": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets in which License Manager will create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers. ",
"smithy.api#required": {}
}
},
"RemoveSubnets": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets to remove. ",
"smithy.api#required": {}
}
},
"SecurityGroupId": {
"target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

```
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if
```

```
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
```

Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.58 aws-sdk-go-v2-config 1.30.3

1.58.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt

```
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }
```

```
 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer

 // License name.
 //
 // This member is required.
 LicenseName *string

 // Product name.
```

```
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
```

```
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]
```

```
jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
     - name: Run Scan code on pr ref
       run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
     # compare
     - name: License test
       run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
```

are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer

InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper

RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step

```
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
```

```
//
//   - Status
//
//
  - Fingerprint
//
//   - IssuerName
//
//   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
```

```
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
```

```
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
```

```
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string
```

```
 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
```

```
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
```

```
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
```

```
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }
```

```
if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
```

```
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
```

```
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
```

```
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
```

```
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData
```

```
// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
```

```
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
```

```
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
```

```
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
        "type": "integer"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
        "type": "long"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
        "type": "operation",
        "input": {
           "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
        },
        "output": {
           "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
        },
        "errors": [
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
           },
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
           },

     {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
           },
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
           }
        ],
        "traits": {
           "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
           "smithy.api#http": {
              "code": 200,
              "method": "POST",
```

```
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

         "traits": {
            "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
          }
        },
```

```
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
```

```
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
          "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
          },
          "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
          },
          "AccountID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
          },
          "Region": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
          },
          "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
              "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
          },
```

```
        "ProductCode": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
          "traits": {
            "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a
href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-
operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
          }
        },
        "LastUpdatedTime": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The time in which the last discovery updated the instance
details.</p>"
          }
        },
        "SubscriptionName": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
          }
        },
        "OsVersion": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
          }
        },
        "SubscriptionProviderCreateTime": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
          }
        },
        "SubscriptionProviderUpdateTime": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
          }
        },
        "DualSubscription": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
          }
```

```
            },
            "RegisteredWithSubscriptionProvider": {
               "target": "smithy.api#String",
               "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
         "type": "service",
         "version": "2018-05-10",
         "operations": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
        }
    ],
    "traits": {
        "aws.api#service": {
            "sdkId": "License Manager Linux Subscriptions",
            "arnNamespace": "license-manager-linux-subscriptions",
            "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
            "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
            "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
```

```
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
                }
              ],
```

```
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            }

        ],
                        "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                        "type": "error"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "ref": "UseDualStack"
                                            },
                                            true
                                        ]

}
                                ],
                                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                                "type": "error"
                            },
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": {
                                        "ref": "Endpoint"
                                    },
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
```

```
            "type": "tree"

        }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "isSet",
                        "argv": [
                            {
                                "ref": "Region"
                            }
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {

        "fn": "aws.partition",
                                "argv": [
                                    {
                                        "ref": "Region"
                                    }
                                ],
                                "assign": "PartitionResult"
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {

                                      "ref": "UseFIPS"
                                            },
                                            true
                                        ]
                                    },
                                    {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }

    ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"

            },
                                "supportsFIPS"
                            ]
                          }
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [

                             {
                                "ref": "PartitionResult"
                              },
                              "supportsDualStack"
                            ]
                          }
                        ]
                      }
                    ],
                    "rules": [
                      {
```

```
                "conditions": [],

        "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],

            "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {

        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
```

```
                "fn": "booleanEquals",
                    "argv": [
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      },
                      true

                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }
                  ],
                  "type": "tree"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "FIPS is enabled
 but this partition does not support FIPS",
              "type": "error"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
```

```
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "ref": "UseDualStack"
                                            },
                                            true

                                ]
                                    }
                                ],
                                "rules": [
                                    {
                                        "conditions": [
                                            {
                                                "fn": "booleanEquals",
                                                "argv": [
                                                    true,
                                                    {
                                                        "fn": "getAttr",
                                                        "argv": [
                                                            {

                                                            "ref": "PartitionResult"
                                                            },
                                                            "supportsDualStack"
                                                        ]
                                                    }
                                                ]
                                            }
                                        ],
                                        "rules": [
                                            {
                                                "conditions": [],
                                                "rules": [

        {
                                                        "conditions": [],
                                                        "endpoint": {
                                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                            "properties": {},
                                                            "headers": {}
                                                        },
                                                        "type": "endpoint"
                                                    }
                                                ],
                                                "type": "tree"
```

```
                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
]
},
"smithy.rules#endpointTests": {
"testCases": [
{
```

```
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

 "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
        }
```

```
    },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
          }
        },
        "params": {
          "Region": "cn-north-1",
          "UseFIPS": true,
          "UseDualStack": true
        }
      },
      {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
          }
        },
        "params": {
          "Region": "cn-north-1",
          "UseFIPS": true,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
          }
         },
        "params": {
          "Region": "cn-north-1",
          "UseFIPS": false,
          "UseDualStack": true
        }
      },
```

```
                {
                  "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
                    }
                  },
                  "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
                    }

                 },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
                    }
                  },
```

```
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {

    "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
```

```
enabled",
                "expect": {
                  "error": "DualStack is enabled but this partition does not support DualStack"
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
                  }
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS":
false,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                   }
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false
                }
              },
```

```
                {
                  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "error": "DualStack is enabled but this partition does not support DualStack"
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {

                 "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                    }
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }

        },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }
                  },
```

```
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
```

```
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

            },
            {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "OrganizationIntegration": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
          "traits": {
            "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n              <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceType</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>ProductCode</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Region</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Status</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>UsageOperation</code>\n              </p>\n            </li>\n          </ul>\n          <p>For each filter, you can use one of the following <code>Operator</code>
```

```
values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
          "type": "structure",
          "members": {
            "Instances": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
              }
            },
            "NextToken": {

           "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListLinuxSubscriptions"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",

  "items": "Subscriptions"
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
      "type": "structure",
      "members": {
        "Filters": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
```

```
match a certain subscription's name.</p>\n        <p>The valid names for this filter are:</p>\n        <ul>\n
<li>\n            <p>\n                <code>Subscription</code>\n            </p>\n        </li>\n        </ul>\n
<p>The
 valid Operators for this filter are:</p>\n        <ul>\n        <li>\n            <p>\n
<code>contains</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>equals</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n        </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
```

```
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
          },
          "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",
              "items": "RegisteredSubscriptionProviders"
            }
          }

        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSources": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
            }
        },
        "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                "smithy.api#range": {
                    "min": 1,
                    "max": 100
                }
            }

 },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
                "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
        },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
      },
      "errors": [
        {

     "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
        "smithy.api#http": {
          "method": "GET",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#readonly": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
                    "documentation": "Equal operator"
                },
                {
                    "name": "NOT_EQUAL",
                    "value": "NotEqual",
                    "documentation": "Not equal operator"
                },
                {
                    "name": "CONTAINS",
                    "value": "Contains",
                    "documentation": "Contains operator"
                }
            ],
            "smithy.api#length": {
                "min": 1,
                "max": 20
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled OrganizationIntegration"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
```

```
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
            }
          },
```

```
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"
```

```
}
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "InProgress",
          "value": "InProgress",
          "documentation": "InProgress status"
        },
        {
          "name": "Completed",
          "value": "Completed",
          "documentation": "Completed status"
        },
        {
          "name": "Successful",
          "value": "Successful",
          "documentation": "Successful status"
        },
        {
          "name": "Failed",
          "value": "Failed",
          "documentation": "Failed status"
        }
      ]
    }
  },

  "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
    "type": "list",
    "member": {
      "target": "smithy.api#String",
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        }
      }
    },
    "traits": {
      "smithy.api#length": {
        "min": 1,
        "max": 100
      },
      "smithy.api#uniqueItems": {}
    }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
      "type": "structure",
      "members": {
        "Name":
{
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the subscription.</p>"
          }
        },
        "Type": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS.</p>"
          }
        },
        "InstanceCount": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>The total amount of running instances using this subscription.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
```

```
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [

 {
                "name": "RedHat",
                "value": "RedHat",
                "documentation": "RedHat subscription provider namespace"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "ACTIVE",
              "value": "ACTIVE",
              "documentation": "ACTIVE status"
            },
            {
              "name": "INVALID",
              "value": "INVALID",

   "documentation": "INVALID status"
            },
            {
              "name": "PENDING",
              "value": "PENDING",
              "documentation": "PENDING status"
            }
          ]
        }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
      "type": "structure",
      "members":
{
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services resource to which to add the specified \n\t\t\tmetadata tags.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
```

```
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

          "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
          },
```

```
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
```

```
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
          }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
          "type": "structure",
          "members": {
              "message": {
                  "target": "smithy.api#String"
              }
          },
          "traits": {
              "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
              "smithy.api#error": "client"
          }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
```

```
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
```

```
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
```

```
//
// This member is required.
WorkspaceId *string

// A token from Grafana Labs that ties your Amazon Web Services account with a
// Grafana Labs account. For more information, see [Link your account with Grafana Labs].
//
// [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
GrafanaToken *string

noSmithyDocumentSerde
}

type AssociateLicenseOutput
struct {

// A structure containing data about the workspace.
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
```

```
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
```

```
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",

```
            "traits": {
                "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
        },
        "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
        },
        "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
                "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
      "type": "structure",
      "members": {
        "DomainName": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
          }
        },
        "DomainIpv4List": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
          "traits": {
            "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
            "smithy.api#length": {
              "min": 1,
              "max": 2
            }
          }
        },
        "DomainCredentialsProvider": {
          "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
            },
            "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for \n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "SELF_MANAGED",
                    "value": "SELF_MANAGED",
                    "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                    "name": "AWS_MANAGED",
                    "value": "AWS_MANAGED",
                    "documentation": "AWS_MANAGED type of Active Directory"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n          </note>",
            "smithy.api#http":
 {
              "code": 200,
              "method": "POST",
              "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
          "type": "structure",
          "members": {
            "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
              "smithy.api#required": {}
            }
          },
           "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },

        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
```

```
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
              "traits": {
                "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
          "type": "structure",
          "members": {
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n          </p>"
              }
            },
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
              }
```

```
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}

      }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Directory": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
```

```
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary":
{
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
         "type": "structure",
         "members": {
            "Subnets": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                  "smithy.api#length": {
                     "min": 1
                  },
```

```
    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
              }
            },
            "FailureMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
          "type": "list",
          "member": {

            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
    "type": "structure",
    "members": {
        "Username": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

"IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
```

```
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
```

```
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
    "type": "structure",
    "members": {
        "message": {
            "target": "smithy.api#String"
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
         "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
         },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
```

```
        "smithy.api#cors": {
            "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",

            "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
                "Region":
{
                    "builtIn": "AWS::Region",
                    "required": false,
                    "documentation": "The AWS region used to dispatch the request.",
                    "type": "String"
                },
                "UseDualStack": {
                    "builtIn": "AWS::UseDualStack",
                    "required": true,
                    "default": false,
                    "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                    "type": "Boolean"
                },
                "UseFIPS": {
                    "builtIn": "AWS::UseFIPS",
                    "required": true,
```

```
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
            "type": "Boolean"
          },
          "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
             ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [
                  {

                    "fn": "booleanEquals",
                    "argv": [
                      {
```

```
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "aws.partition",

                      "argv": [
                        {
                          "ref": "Region"
                        }
                      ],
                      "assign": "PartitionResult"
                    }
```

```
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },
```

true

```
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
```

"fn": "booleanEquals",

```
                            "argv": [
                              true,
                              {
                                "fn": "getAttr",
                                "argv": [
                                  {
                                    "ref": "PartitionResult"
                                  },
                                  "supportsFIPS"
                                ]
                              }
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              true,
```

```
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }

                            ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

    ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [

 {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
```

```
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "fn": "getAttr",
                                    "argv": [

{
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

"url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS is enabled but this partition does not support FIPS",
                    "type": "error"

}
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {

        "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]

          }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

            ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
```

```
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                            "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
{
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint":
{
                  "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
```

```
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
```

```
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

    },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",

  "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
```

```
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

     "endpoint": {
            "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
 false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
```

```
                },
                {
                  "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                  "expect": {
                    "error": "Invalid Configuration:
 Dualstack and custom endpoint are not supported"
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>"
              }
            },
            "ServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
              }
            },
            "LicenseServerEndpointId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits":
```

```
{
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
              }
            },
            "LicenseServerEndpointProvisioningStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
              "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
              }
            },
            "LicenseServers": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
              }
            },

           "CreationTime": {
              "target": "smithy.api#Timestamp",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
          "type": "string"
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

      "type": "string",
          "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
              "name": "PROVISIONED",
              "value": "PROVISIONED",
              "documentation": ""
            },
            {
              "name": "DELETING",
              "value": "DELETING",
              "documentation": ""
            },
            {
              "name": "DELETION_FAILED",
              "value": "DELETION_FAILED",
              "documentation": ""

           },
            {
              "name": "DELETED",
              "value": "DELETED",
              "documentation": ""
            }
          ]
       }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
       "type": "string",
       "traits": {
          "smithy.api#enum": [
            {
              "name": "HEALTHY",
              "value": "HEALTHY",
              "documentation": ""
            },
            {
              "name": "UNHEALTHY",
              "value": "UNHEALTHY",
              "documentation": ""
            },
```

```
                {
                    "name": "NOT_APPLICABLE",
                    "value": "NOT_APPLICABLE",
                    "documentation": ""
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
        "type": "structure",
        "members": {
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
```

```
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n        <li>\n        <p>Product</p>\n        </li>\n
        <li>\n        <p>DirectoryId</p>\n        </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                    "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
 that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                    "smithy.api#required": {}
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
 empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
 next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
```

```
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },

{
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
      }
    ],
    "traits": {
      "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
      "smithy.api#http": {
        "code": 200,
        "method": "POST",
        "uri": "/instance/ListInstances"
      },
      "smithy.api#paginated": {
        "inputToken": "NextToken",
        "outputToken": "NextToken",
        "pageSize": "MaxResults",
        "items": "InstanceSummaries"
      }
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
    "type": "structure",
    "members":
```

```
{
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
      <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
      "type": "structure",
      "members": {
        "InstanceSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
          }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/license-server/ListLicenseServerEndpoints"
        },

      "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "LicenseServerEndpoints"
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
      "type": "structure",
      "members": {
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n        <li>\n          <p>IdentityProviderArn</p>\n        </li>\n      </ul>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
      "type": "structure",
      "members": {
        "LicenseServerEndpoints": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
"operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " Lists the user-based subscription products available from an identity provider. ",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"

```
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
```

```
This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "ProductUserSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

           }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
```

```
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
    "type": "structure",
    "members": {
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
```

```
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {

            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
               }
            },
            "SubscriptionStartDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The start date of a subscription.</p>"
               }
            },
            "SubscriptionEndDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The end date of a subscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
         "type":
 "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
         "type": "structure",
         "members": {
```

```
            "RdsSalCredentialsProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
```

```
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
          "type": "structure",
          "members": {
            "IdentityProvider": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>",
                "smithy.api#required": {}
              }
            },
            "Settings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
              "traits":
 {
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
```

```
                    "min": 1
                }
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
    "type": "string",
    "traits": {
        "smithy.api#length": {

     "min": 5,
            "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
    "type": "structure",
    "members": {
        "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more servers.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
    "type": "union",
    "members": {
        "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

           "traits": {
              "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688
communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
              "smithy.api#required": {}
            }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StartProductSubscription"
            }

      }
       },
       "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
          "type": "structure",
          "members": {
             "Username": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                   "smithy.api#required": {}
                }
             },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                   "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                   "smithy.api#required": {}
                }
             },
             "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                   "smithy.api#required": {}
                }
             },
             "Domain": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
                }
             },
             "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                   "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
                }
```

```
 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "ProductUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }

    }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

 "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
 {
        "type": "structure",
        "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {
```

```
      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
```

```
            "type": "structure",
            "members": {
                "message": {
                    "target": "smithy.api#String"
                }
            },
            "traits": {
                "smithy.api#documentation": "<p>A parameter is not valid.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
```

```
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
```

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation

spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.59 locales 0.14.1

1.59.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Go Playground

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.60 protobuf-go 1.36.6

1.60.1 Available under license :

Copyright (c) 2018 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.61 readline 8.2.13-r0

1.61.1 Available under license :

@c The GNU Free Documentation License.
@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.
@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other
functional and useful document @dfn{free} in the sense of freedom: to
assure everyone the effective freedom to copy and redistribute it,
with or without modifying it, either commercially or noncommercially.
Secondarily, this License preserves for the author and publisher a way
to get credit for their work, while not being considered responsible
for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative
works of the document
must themselves be free in the same sense. It
complements the GNU General Public License, which is a copyleft
license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

@item
APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The ``Document'', below, refers
to any such manual or work. Any member of the public is a licensee, and is addressed as ``you''. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A ``Modified Version'' of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A ``Secondary Section'' is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political
position regarding
them.

The ``Invariant Sections'' are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The ``Cover Texts'' are certain short passages of text that are listed,

as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A ``Transparent'' copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not ``Transparent'' is called ``Opaque''.

Examples of suitable formats for Transparent copies include plain @sc{ascii} without markup, Texinfo input format, La@TeX{} input format, @acronym{SGML} or @acronym{XML} using a publicly available @acronym{DTD}, and standard-conforming simple @acronym{HTML}, PostScript or @acronym{PDF} designed for human modification. Examples of transparent image formats include @acronym{PNG}, @acronym{XCF} and @acronym{JPG}. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, @acronym{SGML} or @acronym{XML} for which the @acronym{DTD} and/or processing tools are not generally available, and the machine-generated @acronym{HTML}, PostScript or @acronym{PDF} produced by some word processors for output purposes only.

The ``Title Page'' means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, ``Title Page'' means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

The ``publisher'' means any person or entity that distributes copies of the Document to the public.

A section ``Entitled XYZ'' means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as ``Acknowledgements'', ``Dedications'', ``Endorsements'', or ``History''.) To ``Preserve the Title''

of such a section when you modify the Document means that it remains a section ``Entitled XYZ'' according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

@item
VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever
to those of this License. You may not use
technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

@item
COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible.
You may add other material on the covers in addition.
Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that
this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

@item
MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

@enumerate A
@item
Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from
those of previous versions
(which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

@item
List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

@item
State on the Title page the name of the publisher of the Modified Version, as the publisher.

@item
Preserve all the copyright notices of the Document.

@item
Add an appropriate copyright notice for your modifications
adjacent to the other copyright notices.

@item
Include, immediately after the copyright notices, a license notice
giving the public permission to use the Modified Version under the
terms of this License, in the form shown in
the Addendum below.

@item
Preserve in that license notice the full lists of Invariant Sections
and required Cover Texts given in the Document's license notice.

@item
Include an unaltered copy of this License.

@item
Preserve the section Entitled ``History'', Preserve its Title, and add
to it an item stating at least the title, year, new authors, and
publisher of the Modified Version as given on the Title Page. If
there is no section Entitled ``History'' in the Document, create one
stating the title, year, authors, and publisher of the Document as
given on its Title Page, then add an item describing the Modified
Version as stated in the previous sentence.

@item
Preserve the network location, if any, given in the Document for
public access to a Transparent copy of the Document, and likewise
the network locations given in the Document for previous versions
it was based on. These may be placed in the ``History'' section.
You may omit a network location for a work that was published at
least
four years before the Document itself, or if the original
publisher of the version it refers to gives permission.

@item
For any section Entitled ``Acknowledgements'' or ``Dedications'', Preserve
the Title of the section, and preserve in the section all the
substance and tone of each of the contributor acknowledgements and/or
dedications given therein.

@item
Preserve all the Invariant Sections of the Document,

unaltered in their text and in their titles. Section numbers
or the equivalent are not considered part of the section titles.

@item
Delete any section Entitled ``Endorsements". Such a section
may not be included in the Modified Version.

@item
Do not retitle any existing section to be Entitled ``Endorsements" or
to conflict in title with any Invariant Section.

@item
Preserve any Warranty Disclaimers.
@end enumerate

If the Modified Version includes new front-matter sections or
appendices that qualify as Secondary Sections and contain no material
copied from the Document,
 you may at your option designate some or all
of these sections as invariant. To do this, add their titles to the
list of Invariant Sections in the Modified Version's license notice.
These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements", provided it contains
nothing but endorsements of your Modified Version by various
parties---for example, statements of peer review or that the text has
been approved by an organization as the authoritative definition of a
standard.

You may add a passage of up to five words as a Front-Cover Text, and a
passage of up to 25 words as a Back-Cover Text, to the end of the list
of Cover Texts in the Modified Version. Only one passage of
Front-Cover Text and one of Back-Cover Text may be added by (or
through arrangements made by) any one entity. If the Document already
includes a cover text for the same cover, previously added by you or
by arrangement made by the same entity you are acting on behalf
 of,
you may not add another; but you may replace the old one, on explicit
permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License
give permission to use their names for publicity for or to assert or
imply endorsement of any Modified Version.

@item
COMBINING DOCUMENTS

You may combine the Document with other documents released under this

License, under the terms defined in section 4 above for modified
versions, provided that you include in the combination all of the
Invariant Sections of all of the original documents, unmodified, and
list them all as Invariant Sections of your combined work in its
license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and
multiple identical Invariant Sections may be replaced with a single
copy. If there are multiple Invariant Sections with the same name but
different contents, make the title of
 each such section unique by
adding at the end of it, in parentheses, the name of the original
author or publisher of that section if known, or else a unique number.
Make the same adjustment to the section titles in the list of
Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History"
in the various original documents, forming one section Entitled
``History"; likewise combine any sections Entitled ``Acknowledgements",
and any sections Entitled ``Dedications". You must delete all
sections Entitled ``Endorsements."

@item
COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents
released under this License, and replace the individual copies of this
License in the various documents with a single copy that is included in
the collection, provided that you follow the rules of this License for
verbatim copying of each of the documents in all other respects.

You may extract
 a single document from such a collection, and distribute
it individually under this License, provided you insert a copy of this
License into the extracted document, and follow this License in all
other respects regarding verbatim copying of that document.

@item
AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate
and independent documents or works, in or on a volume of a storage or
distribution medium, is called an ``aggregate" if the copyright
resulting from the compilation is not used to limit the legal rights
of the compilation's users beyond what the individual works permit.
When the Document is included in an aggregate, this License does not
apply to the other works in the aggregate which are not themselves
derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these
copies of the Document, then if the Document is less than one half of
the entire aggregate, the Document's Cover Texts may
be placed on
covers that bracket the Document within the aggregate, or the
electronic equivalent of covers if the Document is in electronic form.
Otherwise they must appear on printed covers that bracket the whole
aggregate.

@item
TRANSLATION

Translation is considered a kind of modification, so you may
distribute translations of the Document under the terms of section 4.
Replacing Invariant Sections with translations requires special
permission from their copyright holders, but you may include
translations of some or all Invariant Sections in addition to the
original versions of these Invariant Sections. You may include a
translation of this License, and all the license notices in the
Document, and any Warranty Disclaimers, provided that you also include
the original English version of this License and the original versions
of those notices and disclaimers. In case of a disagreement between
the translation and the original version of this License or a notice
or disclaimer, the original
version will prevail.

If a section in the Document is Entitled ``Acknowledgements",
``Dedications", or ``History", the requirement (section 4) to Preserve
its Title (section 1) will typically require changing the actual
title.

@item
TERMINATION

You may not copy, modify, sublicense, or distribute the Document
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense, or distribute it is void, and
will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license
from a particular copyright holder is reinstated (a) provisionally,
unless and until the copyright holder explicitly and finally
terminates your license, and (b) permanently, if the copyright holder
fails to notify you of the violation by some reasonable means prior to
60 days after the cessation.

Moreover, your license from a particular copyright holder is

reinstated permanently if the copyright holder notifies
you of the
violation by some reasonable means, this is the first time you have
received notice of violation of this License (for any work) from that
copyright holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination of your rights under this section does not terminate the
licenses of parties who have received copies or rights from you under
this License. If your rights have been terminated and not permanently
reinstated, receipt of a copy of some or all of the same material does
not give you any rights to use it.

@item
FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions
of the GNU Free Documentation License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns. See
@uref{http://www.gnu.org/copyleft/}.

Each version of the License is given a distinguishing version number.
If the Document specifies that
a particular numbered version of this
License ``or any later version'' applies to it, you have the option of
following the terms and conditions either of that specified version or
of any later version that has been published (not as a draft) by the
Free Software Foundation. If the Document does not specify a version
number of this License, you may choose any version ever published (not
as a draft) by the Free Software Foundation. If the Document
specifies that a proxy can decide which future versions of this
License can be used, that proxy's public statement of acceptance of a
version permanently authorizes you to choose that version for the
Document.

@item
RELICENSING

``Massive Multiauthor Collaboration Site'' (or ``MMC Site'') means any
World Wide Web server that publishes copyrightable works and also
provides prominent facilities for anybody to edit those works. A
public wiki that anybody can edit is an example of such a server. A
``Massive Multiauthor Collaboration'' (or ``MMC'')
contained in the
site means any set of copyrightable works thus published on the MMC
site.

``CC-BY-SA'' means the Creative Commons Attribution-Share Alike 3.0
license published by Creative Commons Corporation, a not-for-profit
corporation with a principal place of business in San Francisco,
California, as well as future copyleft versions of that license
published by that same organization.

``Incorporate'' means to publish or republish a Document, in whole or
in part, as part of another Document.

An MMC is ``eligible for relicensing'' if it is licensed under this
License, and if all works that were first published under this License
somewhere other than this MMC, and subsequently incorporated in whole
or in part into the MMC, (1) had no cover texts or invariant sections,
and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site
under CC-BY-SA on the same site at any time before August 1, 2009,
provided the
 MMC is eligible for relicensing.

@end enumerate

@page
@heading ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

@smallexample
@group
 Copyright (C) @var{year} @var{your name}.
 Permission is granted to copy, distribute and/or modify this document
 under the terms of the GNU Free Documentation License, Version 1.3
 or any later version published by the Free Software Foundation;
 with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
 Texts. A copy of the license is included in the section entitled ``GNU
 Free Documentation License''.
@end group
@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the ``with@dots{}Texts.'' line with this:

@smallexample
@group
  with the Invariant Sections being @var{list their titles}, with
  the Front-Cover

Texts being @var{list}, and with the Back-Cover Texts
being @var{list}.
@end group
@end smallexample

If you have Invariant Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of
free software license, such as the GNU General Public License,
to permit their use in free software.

@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:
GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you

distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which
contains
a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program).

Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies
of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in
whole
or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Program,
and can be reasonably considered
independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the

entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based
on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or
executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering
access to copy from a designated place, then offering equivalent

access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other

circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through
any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number
of this License which applies to it and "any
later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN
IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License,
or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the

GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and
`show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for

software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those

products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions
of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is

not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users
can regenerate automatically from other parts of the Corresponding
Source.

The Corresponding Source for a work in source code form is that
same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of
copyright on the Program, and are irrevocable provided the stated
conditions are met. This License explicitly affirms your unlimited
permission to run the unmodified Program. The output from running a
covered work is covered
by this License only if the output, given its
content, constitutes a covered work. This License acknowledges your
rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not
convey, without conditions so long as your license otherwise remains
in force. You may convey covered works to others for the sole purpose
of having them make modifications exclusively for you, or provide you
with facilities for running those works, provided that you comply with
the terms of this License in conveying all material for which you do
not control copyright. Those thus making or running the covered works
for you must do so exclusively on your behalf, under your direction
and control, on terms that prohibit them from making any copies of
your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under
the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological
measure under any applicable law fulfilling obligations under article
11 of the WIPO copyright treaty adopted on 20 December 1996, or
similar laws prohibiting or restricting circumvention of such
measures.

When you convey a covered work, you waive any legal power to forbid
circumvention of technological measures to the extent such circumvention
is effected by exercising rights under this License with respect to
the covered work, and you disclaim any intention to limit operation or
modification of the work as a means of enforcing, against the work's
users, your or third parties' legal rights to forbid circumvention of

technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to
"keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution

medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years
and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in
the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)
that supports equivalent copying facilities, provided you maintain
clear directions next to the object code saying where to find the

Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions;
the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights
granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of

rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this

License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you
have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"
WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS

THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where
the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.

1.62 swag 0.23.1

1.62.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all

other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

See the License for the specific language governing permissions and limitations under the License.

1.63 skalibs 2.14.3.0-r0

1.63.1 Available under license :

Copyright (c) 2011-2024 Laurent Bercot <ska-skaware@skarnet.org>

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.64 github.com/aws/aws-sdk-go-v2/credentials 1.18.3

1.64.1 Available under license :

GetLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent

```
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
```

```
 params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
```

```
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata
```

```
 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
```

```
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
```

```
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
```

```
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
```

Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions

InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity

```
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
```

```
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
  - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
```

```
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
```

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

```
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string
```

```
 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
```

```
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
 return err
```

```
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
```

```
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
```

```
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
```

```
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
```

```
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
return &awsmiddleware.RegisterServiceMetadata{
 Region:
      region,
 ServiceID:     ServiceID,
 OperationName: "GetLicense",
```

```
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
```

```
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
```

```
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
```

```
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
```

```
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
```

```
            "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/DeregisterSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
         "type": "structure",
         "members": {
            "SubscriptionProviderArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
         "type": "structure",
         "members": {
            "Name": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The type of name to filter by.</p>"
                }
            },
            "Values": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                  "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
               }
            },
```

```
            "Operator": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
                "traits": {
                    "smithy.api#documentation": "<p>An operator for filtering results.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
```

```
            "uri": "/subscription/GetRegisteredSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

         "traits": {
              "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
          "smithy.api#http": {
            "code": 200,
```

```
            "method": "POST",
            "uri": "/subscription/GetServiceSettings"

        },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
```

```
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
          "type": "structure",
          "members": {
            "AmiId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
              }
            },
            "InstanceID": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
              }
            },
            "InstanceType": {
              "target": "smithy.api#String",
              "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
              }
            },
            "AccountID": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
              }
            },
            "Region": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
              }
            },
            "UsageOperation": {
              "target": "smithy.api#String",

    "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For
```

more information, see\n Usage\n operation values in the License Manager User Guide. "
}
},
"ProductCode": {
"target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
"traits": {
"smithy.api#documentation": " The product code for the instance. For more information, see Usage\n operation values in the License Manager User Guide . "
}
},
"LastUpdatedTime": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The time in which the last discovery updated the instance details. "
}
},
"SubscriptionName": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The name of the license subscription that the instance uses. "
}
},
"OsVersion": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The operating system software version that runs on your instance. "
}
},
"SubscriptionProviderCreateTime": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The timestamp when you registered
the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses. "
}
},
"SubscriptionProviderUpdateTime": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The timestamp from the last time that the instance synced with the registered \n\t\t\tthird-party Linux subscription provider. "
}
},
"DualSubscription": {

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for \n\t\t\tthe same software on your instance.</p>"
            }
          },
          "RegisteredWithSubscriptionProvider": {
            "target": "smithy.api#String",
            "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta third-party Linux subscription provider that you've registered with License Manager.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
```

```
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
     },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
    }
  ],
  "traits": {
    "aws.api#service": {
      "sdkId": "License Manager Linux Subscriptions",
       "arnNamespace": "license-manager-linux-subscriptions",
      "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
    },
    "aws.auth#sigv4": {
      "name": "license-manager-linux-subscriptions"
    },
    "aws.protocols#restJson1": {},
    "smithy.api#cors": {
      "additionalAllowedHeaders": [
        "*",
        "content-type",
        "x-amz-content-sha256",
        "x-amz-user-agent",
        "x-amzn-platform-id",
        "x-amzn-trace-id"
      ],
```

```
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager Linux Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region": {
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
                 "type": "Boolean"
              },
              "UseFIPS": {
                "builtIn": "AWS::UseFIPS",
                "required": true,
                "default": false,
                "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                "type": "Boolean"
              },
              "Endpoint": {
                "builtIn": "SDK::Endpoint",
                "required": false,
                "documentation": "Override the endpoint used to send this request",
                "type": "String"
              }
            },
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "isSet",
                    "argv": [
                      {
```

```
                        "ref": "Endpoint"
                    }
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }

    ],
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]

}
                            ],
                            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                            "type": "error"
                        },
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": {
                                    "ref": "Endpoint"
                                },
                                "properties": {},
```

```
                "headers": {}
              },
              "type": "endpoint"
            }
          ],
          "type": "tree"

      }
      ],
      "type": "tree"
    },
    {
      "conditions": [],
      "rules": [
        {
          "conditions": [
            {
              "fn": "isSet",
              "argv": [
                {
                  "ref": "Region"
                }
              ]
            }
          ],
          "rules": [
            {
              "conditions": [
                {

      "fn": "aws.partition",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ],
                  "assign": "PartitionResult"
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
```

```
                "ref": "UseFIPS"
                    },
                    true
                ]
                },
                {
                "fn": "booleanEquals",
                "argv": [
                    {
                    "ref": "UseDualStack"
                    },
                    true
                ]
                }

    ],
                "rules": [
                {
                "conditions": [
                    {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                        "fn": "getAttr",
                        "argv": [
                            {
                            "ref": "PartitionResult"

            },
                            "supportsFIPS"
                        ]
                        }
                    ]
                    },
                    {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                        "fn": "getAttr",
                        "argv": [

                        {
                            "ref": "PartitionResult"
                        },
                        "supportsDualStack"
                        ]
```

```
                                        }
                                    ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [],

        "rules": [
                                        {
                                            "conditions": [],
                                            "endpoint": {
                                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],

                                "type": "tree"
                                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {

            "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            }
                        ],
```

```
                "rules": [
                    {
                        "conditions": [
                            {

                    "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsFIPS"
                                        ]
                                    },
                                    true

                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "rules": [
                                    {
                                        "conditions": [],
                                        "endpoint": {
                                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled
 but this partition does not support FIPS",
                        "type": "error"
                    }
```

```
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true

        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {

                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "rules": [

    {
                                                "conditions": [],
                                                "endpoint": {
                                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                    "properties": {},
                                                    "headers": {}
```

```
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"

                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
```

```
    ]
  },
  "smithy.rules#endpointTests": {
    "testCases": [
      {
        "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

    }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": true,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": true,
          "UseDualStack": false
        }
      },
      {

     "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
        "expect": {
```

```
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
                }

            },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                    }
                },
                "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                    }
                },
                "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                    }
                 },
                "params": {
                    "Region": "cn-north-1",
```

```
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

    "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }

         },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

        "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
```

```
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
         }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
          "expect": {
            "endpoint": {
```

```
                    "url": "https://example.com"
                }
            },
            "params": {
                "UseFIPS": false,
                "UseDualStack": false,
                "Endpoint": "https://example.com"
            }
        },
        {

            "documentation": "For custom endpoint with fips enabled and dualstack disabled",
            "expect": {
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": false,
                "Endpoint": "https://example.com"
            }
        },
        {
            "documentation": "For custom endpoint with fips disabled and dualstack enabled",
            "expect": {
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
            },
            "params": {

"Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true,
                "Endpoint": "https://example.com"
            }
        },
        {
            "documentation": "Missing region",
            "expect": {
                "error": "Invalid Configuration: Missing Region"
            }
        }
    ],
    "version": "1.0"
  }
 }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
  "type": "string",
```

```
      "traits": {
        "smithy.api#enum": [
          {
            "name": "Enabled",
            "value": "Enabled",
            "documentation": "Enabled LinuxSubscriptionsDiscovery"

     },
          {
            "name": "Disabled",
            "value": "Disabled",
            "documentation": "Disabled LinuxSubscriptionsDiscovery"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "OrganizationIntegration": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
          "traits": {
            "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
      },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },

  {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptionInstances"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "Instances"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
 {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n          <li>\n
  <p>\n              <code>AccountID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
    <code>AmiID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>DualSubscription</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceType</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>ProductCode</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Region</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
```

<code>Status</code>\n \n \n \n \n
<code>UsageOperation</code>\n \n \n \n For each filter, you can use one of the following <code>Operator</code>
values to \n \t\tdefine the behavior of the filter: \n \n \n \n
<code>contains</code>\n \n \n \n \n
<code>equals</code>\n \n \n \n \n
<code>Notequal</code>\n \n \n "
}
},
"MaxResults": {
"target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
"traits": {
"smithy.api#documentation": " The maximum items to return in a request. "
}
},
"NextToken": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " A token to specify where to
start paginating. This \n\tis the nextToken from a previously truncated response. ",
"smithy.api#length": {
"min": 1,
"max": 16384
}
}
}
},
"traits": {
"smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
}
},
"com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
"type": "structure",
"members": {
"Instances": {
"target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
"traits": {
"smithy.api#documentation": " An array that contains instance objects. "
}
},
"NextToken": {

"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects. "

```
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
           {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptions"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",

   "items": "Subscriptions"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
```

```
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n       <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n        <p>The valid names for this filter are:</p>\n        <ul>\n            <li>\n              <p>\n                <code>Subscription</code>\n              </p>\n            </li>\n        </ul>\n        <p>The
 valid Operators for this filter are:</p>\n        <ul>\n            <li>\n              <p>\n                <code>contains</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>equals</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Notequal</code>\n              </p>\n            </li>\n        </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
          "type": "structure",
          "members": {
            "Subscriptions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
               "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
```

isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects. "
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " List Bring Your Own License (BYOL) subscription registration
resources for your account. ",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "RegisteredSubscriptionProviders"
            }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",

```
        "members": {
          "SubscriptionProviderSources": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
            "traits": {
              "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }

  },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
          "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

           "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
            }
```

```
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
      "type": "structure",
      "members": {
        "tags": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
          "traits": {
            "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "EQUAL",
            "value": "Equal",
            "documentation": "Equal operator"
          },
          {
            "name": "NOT_EQUAL",
            "value": "NotEqual",
            "documentation": "Not equal operator"
          },
          {
            "name": "CONTAINS",
            "value": "Contains",
            "documentation": "Contains operator"
          }
        ],
        "smithy.api#length": {
          "min": 1,
          "max": 20
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
```

```
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled OrganizationIntegration"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
```

access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token. "
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": " A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status. "
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider. "
            }
          }
        },
        "traits": {
          "smithy.api#documentation": " A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider. "
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": " Unable to find the requested Amazon Web Services resource. ",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {

```
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"

    }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "InProgress",
              "value": "InProgress",
              "documentation": "InProgress status"
            },
            {
              "name": "Completed",
              "value": "Completed",
              "documentation": "Completed status"
            },
            {
              "name": "Successful",
              "value": "Successful",
              "documentation": "Successful status"
            },
            {
              "name": "Failed",
              "value": "Failed",
              "documentation": "Failed status"
            }
          ]
        }
      },

      "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            }
          }
        },
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
```

```
            },
            "smithy.api#uniqueItems": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
            "Name":
{
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the subscription.</p>"
                }
            },
            "Type": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [

 {
                "name": "RedHat",
                "value": "RedHat",
                "documentation": "RedHat subscription provider namespace"
              }
            ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "ACTIVE",
              "value": "ACTIVE",
              "documentation": "ACTIVE status"
            },
            {
              "name": "INVALID",
              "value": "INVALID",

  "documentation": "INVALID status"
            },
            {
              "name": "PENDING",
              "value": "PENDING",
              "documentation": "PENDING status"
            }
```

```
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
        "type": "structure",
        "members":
```

```
{
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
         "type": "map",
         "key": {
            "target": "smithy.api#String"
         },
         "value": {
            "target": "smithy.api#String"
         },
         "traits": {
            "smithy.api#length": {
               "min": 0,
               "max": 50
            },
            "smithy.api#sensitive": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
```

```
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
```

```
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
```

```
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
              "smithy.api#required": {}
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
              "smithy.api#required": {}
            }
          },
          "AllowUpdate": {
            "target":
 "smithy.api#Boolean",
            "traits": {
              "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData
```

```
 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
```

```
 ServiceID:     ServiceID,
 OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
```

```
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }
```

```
if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
```

```
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack,
options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
```

```
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
```

```
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
  return err
 }
```

```
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
```

CheckInLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {

```
        "type": "structure",
        "members": {
          "DirectoryId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
            "traits": {
              "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
          },
          "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
          },
          "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
              "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
          "DomainName": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
            }
          },
          "DomainIpv4List": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
            "traits": {
              "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 2
              }
```

```
            }
          },
          "DomainCredentialsProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
            }
          },
          "DomainNetworkSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "SELF_MANAGED",
              "value": "SELF_MANAGED",
              "documentation": "SELF_MANAGED type of Active Directory"
            },
            {
              "name": "AWS_MANAGED",
              "value": "AWS_MANAGED",
              "documentation": "AWS_MANAGED type of Active Directory"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
{
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
```

```
"com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
    "type": "structure",
    "members": {
      "Username": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
          "smithy.api#required": {}
        }
      },
      "InstanceId": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
          "smithy.api#required": {}
        }
      },
      "IdentityProvider": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
        "traits": {
          "smithy.api#documentation": "<p>The identity provider for the user.</p>",
          "smithy.api#required": {}
        }
      },
      "Domain": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
        }
      },
      "Tags": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
        "traits": {
          "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
        }
      }
    },
    "traits": {

  "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
    "type": "structure",
    "members": {
      "InstanceUserSummary": {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
    },
    "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
             }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                  "smithy.api#required": {}
               }
            },
            "Tags": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
          "SecretsManagerCredentialsProvider":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
```

```
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
```

<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete. ",
                "smithy.api#required": {}
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": " The type of License Server that the delete request refers to. ",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
              "traits": {
                "smithy.api#documentation": " Shows details from the <code>LicenseServerEndpoint</code> resource that was deleted. "
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
         "type": "structure",
         "members": {
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
```

```
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

      }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
```

```
                "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
              }
            },
            "InstanceUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummary":
{
              "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
          "type": "structure",
          "members": {
            "Subnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                "smithy.api#length": {
```

```
                    "min": 1
                },

    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
```

```
        "members": {
          "ActiveDirectoryIdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
             "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
               }
            },
            "FailureMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
         "type": "list",
         "member": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
         "type": "structure",
         "members": {
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                  "smithy.api#required": {}
               }
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                  "smithy.api#required": {}
               }
            },
            "Products": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
                "traits": {
                  "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                  "smithy.api#required": {}
               }
```

```
            },
            "LastStatusCheckDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date of the last status check.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                  "smithy.api#required": {}
               }
            },

      "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
```

```
\n\t\t\tabout the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                 }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
                }
            },
            "AssociationDate": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
                }
            },
            "DisassociationDate": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
```

```
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
   "type": "list",
   "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
   }
},
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
   "type": "structure",
   "members": {
      "message": {
         "target": "smithy.api#String"
      }
   },
   "traits": {
      "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
       "smithy.api#error": "server",
      "smithy.api#httpError": 500
   }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
   "type": "string",
   "traits": {
      "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
   }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
   "type": "list",
   "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
   }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
   "type": "service",
   "version": "2018-05-10",
   "operations": [
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
       },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
      },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
            },
            {
"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
        ],
        "traits": {
            "aws.api#service": {
              "sdkId": "License Manager User Subscriptions",
              "arnNamespace": "license-manager-user-subscriptions",
              "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
```

```
            "name": "license-manager-user-subscriptions"
          },
          "aws.protocols#restJson1": {},
          "smithy.api#cors": {
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id",
              "content-length",

        "x-api-key",
              "authorization",
              "x-amz-date",
              "x-amz-security-token",
              "Access-Control-Allow-Headers",
              "Access-Control-Allow-Methods",
              "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager User Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region":
{
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                "type": "Boolean"
              },
```

```
        "UseFIPS": {
          "builtIn": "AWS::UseFIPS",
          "required": true,
          "default": false,
          "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
          "type": "Boolean"
        },
        "Endpoint": {
          "builtIn": "SDK::Endpoint",
          "required": false,
          "documentation": "Override the endpoint used to send this request",
          "type": "String"
        }
      },
      "rules": [
        {
          "conditions": [
            {
              "fn": "isSet",
              "argv": [
                {
                  "ref": "Endpoint"
                }
              ]
            }
           ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
                    true
                  ]
                }
              ],
              "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
              "type": "error"
            },
            {
              "conditions": [
                {
```

```
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Region"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "aws.partition",

                    "argv": [
                      {
                        "ref": "Region"
                      }
```

```
                ],
                "assign": "PartitionResult"
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
```

true

```
                    ]
                  },
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
```

"fn": "booleanEquals",

```
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"
                              },
                              "supportsFIPS"
                            ]
                          }
                        ]
                      },
```

```
                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }

                ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }

    ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
```

```
{
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "fn": "getAttr",
                                            "argv": [

                                {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsFIPS"
                                        ]
                                    },
                                    true
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {

                        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

    }
                    ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

        "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        true,
                                        {
                                            "fn": "getAttr",
                                            "argv": [
                                                {
                                                    "ref": "PartitionResult"
                                                },
                                                "supportsDualStack"
                                            ]

         }
                                    ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
```

```
                ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "DualStack is enabled but this partition does not support DualStack",
                    "type": "error"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

            "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
      }
    ],
    "type": "tree"
  },
  {
    "conditions": [],
    "error": "Invalid Configuration: Missing Region",
    "type": "error"
  }
 ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect":
{
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",

    "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS":
true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint":
{
                "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
```

```
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false

    }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

            },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                  }
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                  "error": "DualStack is enabled but this partition does not support DualStack"
                },
                "params": {
                  "Region": "us-isob-east-1",

  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
```

```
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

     "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
 false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
```

```
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
        "type": "structure",
        "members": {
          "ProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
             "traits": {
               "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
            }
          },
          "HealthStatus": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
            "traits": {
              "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
            }
          },
```

```
            "Ipv4Address": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
               }
            },
            "ServerType": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
               "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>"
               }
            },
            "ServerEndpoint": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
               }
            },
            "LicenseServerEndpointId": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
```

```
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
{
              "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the
RDS \n\t\t\tlicense server.</p>"
            }
          },
          "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
              "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent
the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },

         "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when License Manager created the license server
endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop
Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
```

```
                {
                  "name": "UNHEALTHY",
                  "value": "UNHEALTHY",
                  "documentation": ""
                },
                {
                  "name": "NOT_APPLICABLE",
                  "value": "NOT_APPLICABLE",
                  "documentation": ""
                }
              ]
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
            "type": "structure",
            "members": {
              "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>",
                  "smithy.api#required": {}
                }
              },
              "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                  "smithy.api#required": {}
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
            "type": "operation",
            "input": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
            },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single request.</p>"
            }
        },
        "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n <ul>\n <li>\n <p>Product</p>\n </li>\n <li>\n <p>DirectoryId</p>\n </li>\n </ul>"
            }
        },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
    "type": "structure",
    "members": {
        "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                "smithy.api#required": {}
            }
        },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
```

```
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
     "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/instance/ListInstances"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
        }
    }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
      "type": "structure",
      "members":
{
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
      "type": "structure",
      "members": {
        "InstanceSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next
```

token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
"type": "operation",
"input": {
"target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
},
"output": {
"target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
},
"errors": [
{
"target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
}
],
"traits": {
"smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",
"smithy.api#http": {
"code": 200,
"method": "POST",
"uri": "/license-server/ListLicenseServerEndpoints"
},
"smithy.api#paginated": {
"inputToken": "NextToken",

```
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "LicenseServerEndpoints"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>IdentityProviderArn</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
```

```
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
         "type":
 "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
```

```
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
```

```
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

            }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
   "type": "operation",
   "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
   },
   "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
   "errors": [
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
       }
   ],
   "traits": {
      "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
      "smithy.api#http": {
         "code": 200,
         "method": "POST",
         "uri": "/user/ListUserAssociations"
      },
      "smithy.api#paginated": {
         "inputToken": "NextToken",
         "outputToken": "NextToken",
         "pageSize": "MaxResults",
         "items": "InstanceUserSummaries"
      }
   }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
```

```
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
```

```
        "InstanceUserSummaries": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
      "type": "structure",
      "members": {
        "Username":
{
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
            "smithy.api#required": {}
          }
        },
        "Product": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
            "smithy.api#required": {}
          }
        },
        "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
          "traits": {
            "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
            "smithy.api#required": {}
          }
        },
         "Status": {
          "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
{
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {

   "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits":
{
                    "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
"<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

    "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

           "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
          "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
        "type": "union",
        "members": {
          "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
             "traits": {
              "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

"target": "smithy.api#String"
            }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity
```

provider. \n <note>\n Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as Pending billing status) in Amazon Web Services Billing. For more information, see Viewing your\n\t\t\t\tmonthly charges in the Amazon Web Services Billing User Guide. \n </note>",
"smithy.api#http": {
"code": 200,
"method": "POST",
"uri": "/user/StartProductSubscription"
}

}
},
"com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
"type": "structure",
"members": {
"Username": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The user name from the identity provider of the user. ",
"smithy.api#required": {}
}
},
"IdentityProvider": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
"traits": {
"smithy.api#documentation": " An object that specifies details for the identity provider. ",
"smithy.api#required": {}
}
},
"Product": {
"target": "smithy.api#String",
"traits": {

"smithy.api#documentation": " The name of the user-based subscription product. \n Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n ",
"smithy.api#required": {}
}
},
"Domain": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The domain name of the Active Directory that contains the user for whom to start the product \n\t\t\tsubscription. "
}
},

```
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
              }

  }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
```

```
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
                  "smithy.api#required": {}
               }

   }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
         "type": "list",
         "member": {
            "target": "smithy.api#String"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
         }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

"min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        },
        "Tags": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
          "traits": {
            "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
```

```
to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

            }
               },
               "TagKeys": {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
                  "traits": {
                     "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                     "smithy.api#httpQuery": "tagKeys",
                     "smithy.api#required": {}
                  }
               }
            },
            "traits": {
               "smithy.api#input": {}
            }
         },
         "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
            "type": "structure",
            "members": {},
            "traits": {
               "smithy.api#output": {}
            }
         },
         "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
            "type": "operation",
            "input": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
             },
            "output": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
            },
            "errors": [
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
               }
            ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
            "smithy.api#http": {

       "code": 200,
                "method": "POST",
                "uri": "/identity-provider/UpdateIdentityProviderSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },

            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
                }
            },
            "UpdateSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
                "traits": {
                    "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n <ul>\n            <li>\n                <p>Subnets which you want to add to provision VPC endpoints.</p>\n            </li>\n       <li>\n                <p>Subnets which you want to remove the VPC endpoints from.</p>\n            </li>\n <li>\n                <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n            </li>\n        </ul>",
                    "smithy.api#required": {}
                }
            }
        },
```

```
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
                "traits": {
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
        "type": "structure",
        "members": {
            "AddSubnets": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
                    "smithy.api#required": {}
                }
            },
            "RemoveSubnets": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
                    "smithy.api#required": {}
                }
            },
            "SecurityGroupId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
```

```
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A parameter is not valid.</p>",
          "smithy.api#error": "client"
        }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {
```

```
 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
```

```
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
```

```
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
```

InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership

of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or

documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.65 stdlib go1.24.4

1.65.1 Available under license :

```
// Copyright 2024 The Go Authors. All rights reserved.
// Use of this source code is governed by a BSD-style
// license that can be found in the LICENSE file.

package copyright

import (
 "bytes"
 "internal/testenv"
 "io"
 "io/fs"
 "os"
 "path/filepath"
 "testing"
)

var copyright = []byte("Copyright")

var permitted = [][]byte{
 []byte("// Code generated by "),
 []byte("// Code generated from "),
 []byte("// Created by cgo -cdefs"),
 []byte("// DO NOT EDIT\n// generated by:"),
 []byte("// Empty assembly file"),
 []byte("// Generated using cgo"),
 []byte("// Original source:\n//\thttp://www.zorinaq.com/papers/md5-amd64.html"), // public domain crypto/md5
 []byte("// created by cgo -cdefs"),
 []byte("// go run mkasm.go"),
 []byte("// mkerrors"),
 []byte("// mksys"),
 []byte("// run\n// Code generated by"), // cmd/compile/internal/test/constFold_test.go
}

func TestCopyright(t *testing.T) {
 buf := make([]byte, 2048)
 filepath.WalkDir(filepath.Join(testenv.GOROOT(t), "src"), func(path string,
 d fs.DirEntry, err error) error {
  if d.IsDir() && (d.Name() == "testdata" || d.Name() == "vendor") {
   return filepath.SkipDir
```

```
 }
 switch filepath.Ext(d.Name()) {
 default:
  return nil
 case ".s", ".go":
  // check
 }

 f, err := os.Open(path)
 if err != nil {
  t.Error(err)
  return nil
 }
 defer f.Close()
 n, err := f.Read(buf)
 if err != nil && err != io.EOF {
  t.Error(err)
  return nil
 }
 b := buf[:n]
 if bytes.Contains(b, copyright) {
  return nil
 }
 for _, ok := range permitted {
  if bytes.HasPrefix(b, ok) {
   return nil
  }
 }
 t.Errorf("%s: missing copyright notice", path)
 return nil
 })
}
```

Copyright 2009 The Go Authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

  * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
  * Neither the name of Google LLC nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
The Go source code and supporting files in this directory
are covered by the usual Go license (see ../../../../LICENSE).

When building with GOEXPERIMENT=boringcrypto, the following applies.

The goboringcrypto_linux_amd64.syso object file is built
from BoringSSL source code by build/build.sh and is covered
by the BoringSSL license reproduced below and also at
https://boringssl.googlesource.com/boringssl/+/fips-20220613/LICENSE.

BoringSSL is a fork of OpenSSL. As such, large parts of it fall under OpenSSL
licensing. Files that are completely new have a Google copyright and an ISC
license. This license is reproduced at the bottom of this file.

Contributors to BoringSSL are required to follow the CLA rules for Chromium:
https://cla.developers.google.com/clas

Some files from Intel are under yet another license, which is also included
underneath.

The OpenSSL toolkit stays under a dual license, i.e. both the conditions of the
OpenSSL License and the original SSLeay license apply to the toolkit.
See below
for the actual license texts. Actually both licenses are BSD-style Open Source
licenses. In case of any license issues related to OpenSSL please contact
openssl-core@openssl.org.

The following are Google-internal bug numbers where explicit permission from
some authors is recorded for use of their work. (This is purely for our own
record keeping.)
27287199
27287880
27287883

OpenSSL License

```
/* ====================================================================
* Copyright (c) 1998-2011 The OpenSSL Project.  All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following
 disclaimer in
*    the documentation and/or other materials provided with the
*    distribution.
*
* 3. All advertising materials mentioning features or use of this
*    software must display the following acknowledgment:
*    "This product includes software developed by the OpenSSL Project
*    for use in the OpenSSL Toolkit. (http://www.openssl.org/)"
*
* 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to
*    endorse or promote products derived from this software without
*    prior written permission. For written permission, please contact
*    openssl-core@openssl.org.
*
* 5. Products derived from this software may not be called "OpenSSL"
*    nor may "OpenSSL" appear in their names without prior written
*    permission of the OpenSSL Project.
*
* 6. Redistributions of any form whatsoever must retain the following
*    acknowledgment:
*    "This product includes software developed by the OpenSSL Project
*    for use in the OpenSSL Toolkit
 (http://www.openssl.org/)"
*
* THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS" AND ANY
* EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED.  IN NO EVENT SHALL THE OpenSSL PROJECT OR
* ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
* LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
* STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
```

* OF THE POSSIBILITY OF SUCH DAMAGE.
* ==
*
* This product includes cryptographic software written by Eric Young
* (eay@cryptsoft.com). This product
 includes software written by Tim
* Hudson (tjh@cryptsoft.com).
*
*/

Original SSLeay License

/* Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)
* All rights reserved.
*
* This package is an SSL implementation written
* by Eric Young (eay@cryptsoft.com).
* The implementation was written so as to conform with Netscapes SSL.
*
* This library is free for commercial and non-commercial use as long as
* the following conditions are aheared to. The following conditions
* apply to all code found in this distribution, be it the RC4, RSA,
* lhash, DES, etc., code; not just the SSL code. The SSL documentation
* included with this distribution is covered by the same copyright terms
* except that the holder is Tim Hudson (tjh@cryptsoft.com).
*
* Copyright remains Eric Young's, and as such any Copyright notices in
* the code are not to be removed.
* If this package is used in a product, Eric Young should be given attribution
* as the author of
 the parts of the library used.
* This can be in the form of a textual message at program startup or
* in documentation (online or textual) provided with the package.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software
*   must display the following acknowledgement:
*   "This product includes cryptographic software written by
*   Eric Young (eay@cryptsoft.com)"
*   The word 'cryptographic' can be left out if the rouines from the library

* being used are
not cryptographic related :-).
* 4. If you include any Windows specific code (or a derivative thereof) from
* the apps directory (application code) you must include an acknowledgement:
* "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"
*
* THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF
* SUCH DAMAGE.
*
* The licence and distribution terms for any publically available version or
* derivative of this code cannot be changed. i.e. this code cannot simply be
* copied and put under another distribution licence
* [including the GNU Public Licence.]
*/

ISC license used for completely new code in BoringSSL:

/* Copyright (c) 2015, Google Inc.
*
* Permission to use, copy, modify, and/or distribute this software for any
* purpose with or without fee is hereby granted, provided that the above
* copyright notice and this permission notice appear in all copies.
*
* THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
* WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
* MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY
* SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
* WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION
* OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN
* CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE. */

Some files from Intel carry the following license:

Copyright (c) 2012, Intel Corporation
#

All rights reserved.
#
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:
#
* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
#
* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the
distribution.
#
* Neither the name of the Intel Corporation nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.
#
#
THIS SOFTWARE IS PROVIDED BY INTEL CORPORATION
 ""AS IS"" AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTEL CORPORATION OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
People who have agreed to one of the CLAs and can contribute patches.
The AUTHORS file lists the copyright holders; this file
lists people. For example, Google employees are listed here
but not in AUTHORS, because Google holds the copyright.
#
https://developers.google.com/open-source/cla/individual
https://developers.google.com/open-source/cla/corporate
#
Names should be added to this file as:
Name <email address>
Raul Silvera <rsilvera@google.com>
Tipp Moseley <tipp@google.com>
Hyoun Kyu Cho <netforce@google.com>
Martin Spier <spiermar@gmail.com>
Taco de Wolff <tacodewolff@gmail.com>
Andrew Hunter <andrewhhunter@gmail.com>

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

                                 Apache License
                           Version 2.0, January 2004
                        http://www.apache.org/licenses/

 TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

 1. Definitions.

    "License" shall mean the terms and conditions for use, reproduction,
    and distribution as defined by Sections 1 through 9 of this document.

    "Licensor" shall mean the copyright owner or entity authorized by
    the copyright owner that is granting the License.

    "Legal Entity" shall mean the union of the acting entity and all
    other entities that control, are controlled by, or are under common
    control with that entity. For the purposes of this definition,
    "control" means (i) the power, direct or indirect, to cause the
    direction or management of such entity, whether by contract or

otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one

of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be

liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Copyright (c) 2015 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Copyright 2015 The Go Authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google LLC nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE

FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Copyright 2009-2017 Andrea Leofreddi <a.leofreddi@vleo.net>. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY COPYRIGHT HOLDERS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS
OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL COPYRIGHT HOLDERS OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation are those of the authors and should not be interpreted as representing official policies, either expressed or implied, of Andrea Leofreddi.

1.66 github.com/aws/aws-sdk-go-v2/service/sts 1.36.0

1.66.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer

```
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
```

```
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
```

```
// the request.
//
//
This member is required.
ClientToken *string

// Configuration for consumption of the license. Choose a provisional
// configuration for workloads running with continuous connectivity. Choose a
// borrow configuration for workloads with offline usage.
//
// This member is required.
ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange
```

```
// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
```

```
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
```

```
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
```

ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization

OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step

```
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
```

```
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
```

```
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
```

```
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
```

```
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return
err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if
```

```
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
```

```
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
```

```
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack,
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
```

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

```
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}
```

```
type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
```

```
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options);
err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if
```

```
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
```

```
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
```

```
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
```

```
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
```

```
c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.

```
{
   "smithy": "2.0",
   "shapes": {
      "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
         "type": "integer"
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
         "type": "long"
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/DeregisterSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider
resource to deregister.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of name to filter by.</p>"
                }
            },
            "Values": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
                }
            },
            "Operator": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
                "traits": {
                    "smithy.api#documentation": "<p>An operator for filtering results.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
```

```
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
```

```
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

         "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
                 }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
      "type": "operation",
      "input": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/GetServiceSettings"

       },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
      "type": "structure",
      "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
          "traits": {
```

```
                "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
              "traits": {
                "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
              }
            },
            "StatusMessage": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
              "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
              }
            },
            "HomeRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
          "type": "structure",
          "members": {
            "AmiId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
              }
            },
            "InstanceID": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
              }
            },
            "InstanceType": {
              "target": "smithy.api#String",
              "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
```

```
            }
        },
        "AccountID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
        "Region": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
        },
        "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
        },
        "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
        },
        "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
        },
        "SubscriptionName": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
              }
            },
            "OsVersion": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
              }
            },
            "SubscriptionProviderCreateTime": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
              }
            },
            "SubscriptionProviderUpdateTime": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
              }
            },
            "DualSubscription": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
              }
            },
            "RegisteredWithSubscriptionProvider": {
              "target": "smithy.api#String",
              "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
          "type": "list",
          "member": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation":
"<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
          "type": "service",
          "version": "2018-05-10",
          "operations": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
             },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
          }
        ],
        "traits": {
          "aws.api#service": {
            "sdkId": "License Manager Linux Subscriptions",
             "arnNamespace": "license-manager-linux-subscriptions",
            "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
          },
          "aws.auth#sigv4": {
            "name": "license-manager-linux-subscriptions"
          },
          "aws.protocols#restJson1": {},
          "smithy.api#cors": {
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id"
            ],
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager,
    you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager Linux Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region": {
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
```

```
support dual-stack, dispatching the request MAY return an error.",
                "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseFIPS"
                        },
                        true
                      ]
                    }

        ],
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                  "type": "error"
                },
                {
```

```
                "conditions": [],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]

}
                    ],
                    "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                    "type": "error"
                  },
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": {
                        "ref": "Endpoint"
                      },
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],
                "type": "tree"

              }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "isSet",
                      "argv": [
                        {
                          "ref": "Region"
                        }
                      ]
```

```
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {

        "fn": "aws.partition",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ],
                            "assign": "PartitionResult"
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {

                                  "ref": "UseFIPS"
                                        },
                                        true
                                    ]
                                },
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]
                                }

    ],
                            "rules": [
                                {
                                    "conditions": [
                                        {
                                            "fn": "booleanEquals",
                                            "argv": [
                                                true,
                                                {
```

```
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

                    },
                                            "supportsFIPS"
                                        ]
                                    }
                                ]
                            },
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                                         {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],

        "rules": [
                                        {
                                            "conditions": [],
                                            "endpoint": {
                                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],

                    "type": "tree"
                                }
                            ],
```

```
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {

    "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {

            "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true

                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [],
```

```
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "FIPS is enabled
but this partition does not support FIPS",
        "type": "error"
    }
],
"type": "tree"
},
{
"conditions": [
    {
        "fn": "booleanEquals",
        "argv": [
            {
                "ref": "UseDualStack"
            },
            true

]
    }
],
"rules": [
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    true,
                    {
```

```
                                        "fn": "getAttr",
                                        "argv": [
                                            {

                                            "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "rules": [

        {
                                        "conditions": [],
                                        "endpoint": {
                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"

                    }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "error": "DualStack is enabled but this partition does not support DualStack",
                            "type": "error"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
```

```
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
      },
      {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
      }
    ],
    "type": "tree"
  }
 ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
```

```
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

  "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
```

```
        },
        {

    "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
             },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {

     "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
              }
```

```
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }

    },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
```

```
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {

    "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
```

```
false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                }
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {

            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                }
            },
            "params": {
```

```
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }
          },
          "params": {
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {

          "documentation": "For custom endpoint with fips enabled and dualstack disabled",
          "expect": {
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
```

```
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled LinuxSubscriptionsDiscovery"

     },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
        "type": "structure",
        "members": {
          "SourceRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
```

```
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "OrganizationIntegration": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
                "traits": {
                    "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
```

```
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n          <li>\n
  <p>\n                <code>AccountID</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
      <code>AmiID</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>DualSubscription</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>InstanceID</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>InstanceType</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>ProductCode</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>Region</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>Status</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>UsageOperation</code>\n              </p>\n          </li>\n        </ul>\n        <p>For each filter, you can use
one of the following <code>Operator</code>
 values to \n  \t\tdefine the behavior of the filter:</p>\n          <ul>\n          <li>\n              <p>\n
<code>contains</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>equals</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>Notequal</code>\n              </p>\n          </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
```

```
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
          "type": "structure",
          "members": {
            "Instances": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
              }
            },
            "NextToken": {

           "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

   "items": "Subscriptions"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n        <p>The valid names for this filter are:</p>\n        <ul>\n <li>\n            <p>\n                <code>Subscription</code>\n            </p>\n        </li>\n        </ul>\n <p>The
 valid Operators for this filter are:</p>\n        <ul>\n          <li>\n            <p>\n <code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n <code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n <code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
```

```
 the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

             },
            {
```

```
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "RegisteredSubscriptionProviders"
            }
        }

    },
     "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSources": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
                "traits": {
                    "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }

  },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
            "RegisteredSubscriptionProviders": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
                "traits": {
                    "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
                }
            },

             "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {

         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
```

```
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
                    "documentation": "Equal operator"
                },
                {
                    "name": "NOT_EQUAL",
                    "value": "NotEqual",
                    "documentation": "Not equal operator"
                },
                {
                    "name": "CONTAINS",
                    "value": "Contains",
                    "documentation": "Contains operator"
                }
            ],
            "smithy.api#length": {
                "min": 1,
                "max": 20
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "Enabled",
                    "value": "Enabled",
                    "documentation": "Enabled OrganizationIntegration"
                },
                {
                    "name": "Disabled",
                    "value": "Disabled",
                    "documentation": "Disabled OrganizationIntegration"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/RegisterSubscriptionProvider"

        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
            "smithy.api#required": {}
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
            "smithy.api#required": {}
```

```
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
 {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
 {
              "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider,
```

```
License Manager can get subscription data from the registered provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "InProgress",
              "value": "InProgress",
              "documentation": "InProgress status"
            },
            {
              "name": "Completed",
              "value": "Completed",
              "documentation": "Completed status"
            },
            {
              "name": "Successful",
              "value": "Successful",
              "documentation": "Successful status"
```

```
            },
            {
              "name": "Failed",
              "value": "Failed",
              "documentation": "Failed status"
            }
          ]
        }
      },

      "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            }
          }
        },
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
          },
          "smithy.api#uniqueItems": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
          "Name":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the subscription.</p>"
            }
          },
```

```
            "Type": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": "<p>The total amount of running instances using this
 subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
```

```
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "ACTIVE",
            "value": "ACTIVE",
            "documentation": "ACTIVE status"
          },
          {
            "name": "INVALID",
            "value": "INVALID",

"documentation": "INVALID status"
          },
          {
            "name": "PENDING",
            "value": "PENDING",
            "documentation": "PENDING status"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
        "type": "structure",
        "members":
{
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
             "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tagKeys": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
                "traits": {

              "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                    "smithy.api#httpQuery": "tagKeys",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

    },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/UpdateServiceSettings"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
            "smithy.api#required": {}
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
          "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
            "smithy.api#required": {}
```

```
            }
          },
          "AllowUpdate": {
            "target":
 "smithy.api#Boolean",
            "traits": {
              "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
             "traits": {
              "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
            }

       },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
          }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
          "type": "structure",
          "members": {
              "message": {
                  "target": "smithy.api#String"
              }
          },
          "traits": {
              "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
              "smithy.api#error": "client"
          }
      }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
```

```
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
```

```
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
```

```
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
```

```
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
```

```
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
 middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string
```

```
 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
```

```
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
```

```
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
```

Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT

OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
          }
        },
        "ActiveDirectoryType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
          "traits": {
            "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
          }
        }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
            },
            "DomainIpv4List": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 2
                    }
                }
            },
            "DomainCredentialsProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
            },
            "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
```

```
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "SELF_MANAGED",
              "value": "SELF_MANAGED",
              "documentation": "SELF_MANAGED type of Active Directory"
            },
            {
              "name": "AWS_MANAGED",
              "value": "AWS_MANAGED",
              "documentation": "AWS_MANAGED type of Active Directory"
            }
          ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
{
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
```

```
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
               }
            },
            "Tags": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
               }
            }
         },
         "traits": {

      "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
         "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
             }
         },
         "traits": {
            "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
```

```
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
```

```
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
              "smithy.api#required": {}
            }
          },
          "LicenseServerSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
            }
```

```
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
          "type": "union",
          "members": {
            "SecretsManagerCredentialsProvider":
 {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
              "traits": {
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
           },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/DeregisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
```

```
    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/DisassociateUser"
        },
        "smithy.api#idempotent": {}
```

```
    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
      "type": "structure",
      "members": {
        "Username": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
          }
        },
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
          }
        },
        "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
          "traits": {
            "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
          }
        },
        "InstanceUserArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
          }
        },
        "Domain": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
      "type": "structure",
```

```
        "members": {
          "InstanceUserSummary":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
              "smithy.api#length": {
                "min": 1
              },

    "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Attribute": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
            }
```

```
            },
            "Value": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>Value of the filter.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
         "type": "union",
         "members": {
            "ActiveDirectoryIdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
         "type": "structure",
         "members": {
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
```

```
        "Settings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
            "smithy.api#required": {}
          }
        },
        "Product": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of the identity provider.</p>",
            "smithy.api#required": {}
          }
        },
        "IdentityProviderArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
          }
        },
        "FailureMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes an identity provider.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
      "type": "list",
      "member": {

        "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
      "type": "structure",
      "members": {
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
            "smithy.api#required": {}
          }
        },
        "Products": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
           "traits": {
            "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
            "smithy.api#required": {}
          }
        },
        "LastStatusCheckDate": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The date of the last status check.</p>"
          }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
      "type": "structure",
      "members": {
        "Username": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
            "smithy.api#required": {}
          }
        },
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },

    "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
          "traits": {
            "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
            "smithy.api#required": {}
          }
        },
        "InstanceUserArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
           }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
          }
        },
```

```
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
             "smithy.api#error": "server",
            "smithy.api#httpError": 500
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
```

```
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",

         "x-api-key",
            "authorization",
            "x-amz-date",
            "x-amz-security-token",
            "Access-Control-Allow-Headers",
            "Access-Control-Allow-Methods",
            "Access-Control-Allow-Origin"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
```

```
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region":
{
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
              "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
```

```
                }
            ]
        }
    ],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseFIPS"
                        },
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [
                {

                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": {
                    "ref": "Endpoint"
                },

"properties": {},
                "headers": {}
            },
            "type": "endpoint"
        }
```

```
      ],
      "type": "tree"
    },
    {
      "conditions": [
        {
          "fn": "isSet",
          "argv": [
            {
              "ref": "Region"
            }
          ]
        }
      ],
      "rules": [
        {
          "conditions": [
            {
              "fn": "aws.partition",

              "argv": [
                {
                  "ref": "Region"
                }
              ],
              "assign": "PartitionResult"
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
```

true

```
                    ]
                  },
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
```

```
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

 "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      }
                    ]
                  },

                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }

            ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
```

```
                    },
                    "type": "endpoint"
                }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [

  {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [

                {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true
                        ]
                    }
```

```
                                    ],
                                    "rules": [
                                        {
                                            "conditions": [],
                                            "endpoint": {

                "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],
                                    "type": "tree"
                                },
                                {
                                    "conditions": [],
                                    "error": "FIPS is enabled but this partition does not support FIPS",
                                    "type": "error"

}
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "ref": "UseDualStack"
                                            },
                                            true
                                        ]
                                    }
                                ],
                                "rules": [
                                    {

        "conditions": [
                                            {
                                                "fn": "booleanEquals",
                                                "argv": [
                                                    true,
                                                    {
                                                        "fn": "getAttr",
                                                        "argv": [
                                                            {
```

```
                                        "ref": "PartitionResult"
                                    },
                                    "supportsDualStack"
                                ]

        }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }

                    ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "endpoint": {
                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

            "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
    }
],
"type": "tree"
```

```
            },
            {
              "conditions": [],
              "error": "Invalid Configuration: Missing Region",
              "type": "error"
            }
          ]
        },
        "smithy.rules#endpointTests": {
          "testCases": [
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
              "expect":
{
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
```

```
            "endpoint":
{
                "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
                "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
```

```
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false

        }
              },
              {
                "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                  "error": "DualStack is enabled but this partition does not support DualStack"
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                  }

            },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
                "expect": {
                  "endpoint": {
```

```
                "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
              }
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
              "Region": "us-isob-east-1",

"UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
              }
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
            "expect": {

           "endpoint": {
                "url": "https://example.com"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false,
              "Endpoint": "https://example.com"
            }
```

```
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "Missing region",
      "expect": {
        "error": "Invalid Configuration: Missing Region"
      }
    }
  ],
```

```
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
        "type": "structure",
        "members": {
          "ProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
             "traits": {
               "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
            }
          },
          "HealthStatus": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
            "traits": {
              "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
            }
          },
          "Ipv4Address": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
            }
          },
          "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of license server.</p>"
```

```
            }
          },
          "ServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network \n\t\t\taddress of the RDS license server endpoint.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
          },
          "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
              "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
          },
          "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
              "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },
```

```
            "CreationTime": {
                "target": "smithy.api#Timestamp",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "PROVISIONING",
                    "value": "PROVISIONING",
                    "documentation": ""
                },
                {
                    "name": "PROVISIONING_FAILED",
                    "value": "PROVISIONING_FAILED",
                    "documentation": ""
                },
                {
                    "name": "PROVISIONED",
                    "value": "PROVISIONED",
                    "documentation": ""
                },
                {
                    "name": "DELETING",
                    "value": "DELETING",
                    "documentation": ""
                },
                {
```

```
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
    "type": "string",
    "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
    }
},
 "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
    "type": "structure",
    "members": {
        "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>",
```

```
                "smithy.api#required": {}
              }
            },
            "ServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
```

```
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/ListIdentityProviders"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
```

```
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
         "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
    {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
```

```
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
            "InstanceSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
```

```
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/ListLicenseServerEndpoints"
            },

         "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "LicenseServerEndpoints"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
         "type": "structure",
         "members": {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>IdentityProviderArn</p>\n            </li>\n         </ul>"
               }
            },
```

```
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
         "type": "structure",
         "members": {
            "LicenseServerEndpoints": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
                "traits": {
                  "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
         "type":
 "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
```

```
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n          <p>Status</p>\n          </li>\n          <li>\n          <p>Username</p>\n
</li>\n          <li>\n          <p>Domain</p>\n          </li>\n          </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

```
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
    }
      }
    },
    "traits": {
      "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
    "type": "structure",
    "members": {
      "Tags": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
        "traits": {
          "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
        }
      }
    },
    "traits": {
      "smithy.api#output": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
```

```
      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummaries": {

             "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
         "type": "structure",
         "members": {
            "Username":
{
               "target": "smithy.api#String",
               "traits": {
```

```
                "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
                "smithy.api#required": {}
            }
        },
        "Product": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                "smithy.api#required": {}
            }
        },
        "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a product for this user.</p>",
                "smithy.api#required": {}
            }
        },
        "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {

        "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "SubscriptionStartDate": {
            "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/RegisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
 {
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
```

```
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

       "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
```

```
        "members": {
          "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
        "type": "union",
        "members": {
          "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
             "traits": {
              "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

  "target": "smithy.api#String"
            }
        },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
            "smithy.api#length": {
              "min": 1
            },
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
            "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
            }

    }
     },
     "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
```

```
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {

 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                "smithy.api#required": {}
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
              }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/StopProductSubscription"
        }
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
      "type": "structure",
      "members": {
        "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
            }
          },
          "IdentityProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
```

```
                "smithy.api#required": {}
            }

    }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
"<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
```

```
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
```

```
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

          }
            },
            "TagKeys": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
              "traits": {
                "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                "smithy.api#httpQuery": "tagKeys",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
```

```
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
```

```
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
               }
            },
            "UpdateSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
               "traits": {
                  "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n            <li>\n               <p>Subnets which you want to add to provision VPC endpoints.</p>\n            </li>\n
      <li>\n               <p>Subnets which you want to remove the VPC endpoints from.</p>\n            </li>\n
<li>\n               <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n            </li>\n         </ul>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
         "type": "structure",
         "members": {
            "IdentityProviderSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
               "traits": {
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
         "type": "structure",
         "members": {
            "AddSubnets": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
```

```
                "smithy.api#required": {}
              }
            },
            "RemoveSubnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
                "smithy.api#required": {}
              }
            },
            "SecurityGroupId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
              "traits": {
                "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
          }
        }
      }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
```

```
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
```

```
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
 nil {
  return err
```

```
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of,

the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this
License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You

meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate

comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop

Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.67 iputils-clockdiff 20240905-r0

1.67.1 Available under license :

arping: GPL-2.0-or-later
clockdiff: BSD-3-Clause
ping: BSD-3-Clause
tracepath: GPL-2.0-or-later

Files containing license texts are available in Documentation directory.
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their

rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the
Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the

notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause
any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is

void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed

through that system in reliance on consistent application of that
system; it is up to the author/donor to
decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS

TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

  Gnomovision version 69, Copyright (C) year name of author
  Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute
it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
 is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.68 iputils-arping 20240905-r0

1.68.1 Available under license :

arping: GPL-2.0-or-later
clockdiff: BSD-3-Clause
ping: BSD-3-Clause
tracepath: GPL-2.0-or-later

Files containing license texts are available in Documentation directory.
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following

disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the

Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source

code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For
example, if a patent
license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,

THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.69 kelseyhightower-envconfig 1.4.0

1.69.1 Available under license :

Copyright (c) 2013 Kelsey Hightower

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do

so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.70 aws-sdk-go-v2-feature-dynamodb-attributevalue 1.20.2

1.70.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry

```
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
```

```
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer

 // License name.
 //
 // This member is required.
 LicenseName *string
```

```
 // Product name.
 //
 // This member is required.
 ProductName *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // Date and time range during which the license is valid, in ISO8601-UTC format.
 //
 // This member is required.
 Validity *types.DatetimeRange

 // Information about
 the license.
 LicenseMetadata []types.Metadata

 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
```

```
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan
```

```
on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
     - name: Run Scan code on pr ref
       run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
     # compare
     - name: License test
```

run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
CheckoutBorrowLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization

OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody

ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning

```
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
```

```
//   - ProductSKU
//
//   - Status
//
//
  - Fingerprint
//
//   - IssuerName
//
//   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
```

```
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
```

```
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
```

```
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string
```

```
 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
```

```
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
```

```
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
```

```
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }
```

```
if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
```

```
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
```

```
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
```

```
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
```

```
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData
```

```
// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
```

```
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
```

```
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
```

```
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
        "type": "integer"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
        "type": "long"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
        "type": "operation",
        "input": {
           "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
        },
        "output": {
           "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
        },
        "errors": [
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
           },
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
           },

     {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
           },
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
           }
        ],
        "traits": {
           "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
           "smithy.api#http": {
              "code": 200,
              "method": "POST",
```

```
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

       "traits": {
            "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
          }
        },
```

```
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
```

```
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
          "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
          },
          "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
          },
          "AccountID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
          },
          "Region": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
          },
          "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
              "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
          },
```

```
            "ProductCode": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
               "traits": {
                  "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a
href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-
operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
               }
            },
            "LastUpdatedTime": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The time in which the last discovery updated the instance
details.</p>"
               }
            },
            "SubscriptionName": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
               }
            },
            "OsVersion": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
               }
            },
            "SubscriptionProviderCreateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
               }
            },
            "SubscriptionProviderUpdateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
               }
            },
            "DualSubscription": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
               }
```

```
            },
            "RegisteredWithSubscriptionProvider": {
               "target": "smithy.api#String",
               "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
         "type": "service",
         "version": "2018-05-10",
         "operations": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
```

```
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
       },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
      }
    ],
    "traits": {
      "aws.api#service": {
        "sdkId": "License Manager Linux Subscriptions",
         "arnNamespace": "license-manager-linux-subscriptions",
        "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
      },
      "aws.auth#sigv4": {
        "name": "license-manager-linux-subscriptions"
      },
      "aws.protocols#restJson1": {},
      "smithy.api#cors": {
        "additionalAllowedHeaders": [
          "*",
          "content-type",
          "x-amz-content-sha256",
          "x-amz-user-agent",
          "x-amzn-platform-id",
          "x-amzn-trace-id"
        ],
        "additionalExposedHeaders": [
          "x-amzn-errortype",
          "x-amzn-requestid",
          "x-amzn-trace-id"
        ]
```

```
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
                }
              ],
```

```
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            }

        ],
                        "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                        "type": "error"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "ref": "UseDualStack"
                                            },
                                            true
                                        ]

}
                                ],
                                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                                "type": "error"
                            },
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": {
                                        "ref": "Endpoint"
                                    },
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
```

```
            "type": "tree"

        }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "isSet",
                        "argv": [
                            {
                                "ref": "Region"
                            }
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {

        "fn": "aws.partition",
                                "argv": [
                                    {
                                        "ref": "Region"
                                    }
                                ],
                                "assign": "PartitionResult"
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {

                                      "ref": "UseFIPS"
                                            },
                                            true
                                        ]
                                    },
                                    {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }

    ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"

            },
                                "supportsFIPS"
                              ]
                            }
                          ]
                        },
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            true,
                            {
                              "fn": "getAttr",
                              "argv": [

                               {
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                              ]
                            }
                          ]
                        }
                      ],
                      "rules": [
                        {
```

```
                "conditions": [],

        "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],

            "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {

        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
```

```
                "fn": "booleanEquals",
                    "argv": [
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      },
                      true

                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }
                  ],
                  "type": "tree"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "FIPS is enabled
 but this partition does not support FIPS",
              "type": "error"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
```

```
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "ref": "UseDualStack"
                                            },
                                            true

                                ]
                                    }
                                ],
                                "rules": [
                                    {
                                        "conditions": [
                                            {
                                                "fn": "booleanEquals",
                                                "argv": [
                                                    true,
                                                    {
                                                        "fn": "getAttr",
                                                        "argv": [
                                                            {

                                                            "ref": "PartitionResult"
                                                            },
                                                            "supportsDualStack"
                                                        ]
                                                    }
                                                ]
                                            }
                                        ],
                                        "rules": [
                                            {
                                                "conditions": [],
                                                "rules": [

        {
                                                        "conditions": [],
                                                        "endpoint": {
                                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                            "properties": {},
                                                            "headers": {}
                                                        },
                                                        "type": "endpoint"
                                                    }
                                                ],
                                                "type": "tree"
```

```
                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
]
},
"smithy.rules#endpointTests": {
"testCases": [
{
```

```
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

 "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
        }
```

```
        },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

 "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
             },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
```

```
                {
                  "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
                    }
                  },
                  "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
                    }

                 },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
                    }
                  },
```

```
            "params": {
              "Region": "us-gov-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
              }
            },
            "params": {
              "Region": "us-gov-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {

        "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
              }
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
```

```
enabled",
                "expect": {
                  "error": "DualStack is enabled but this partition does not support DualStack"
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
                  }
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS":
false,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                   }
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false
                }
              },
```

```
                {
                  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "error": "DualStack is enabled but this partition does not support DualStack"
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {

                 "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                    }
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }

        },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }
                  },
```

```
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
```

```
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

            },
            {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "OrganizationIntegration": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
          "traits": {
            "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n              <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceType</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>ProductCode</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Region</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Status</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>UsageOperation</code>\n              </p>\n            </li>\n          </ul>\n          <p>For each filter, you can use one of the following <code>Operator</code>
```

```
values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
            "Instances": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
                }
            },
            "NextToken": {

          "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListLinuxSubscriptions"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",

  "items": "Subscriptions"
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
      "type": "structure",
      "members": {
        "Filters": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
```

```
match a certain subscription's name.</p>\n        <p>The valid names for this filter are:</p>\n        <ul>\n
<li>\n            <p>\n                <code>Subscription</code>\n            </p>\n        </li>\n        </ul>\n
<p>The
 valid Operators for this filter are:</p>\n        <ul>\n        <li>\n            <p>\n
<code>contains</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>equals</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n        </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
```

```
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
          },
          "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",
              "items": "RegisteredSubscriptionProviders"
            }
          }

        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSources": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
            }
        },
        "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                "smithy.api#range": {
                    "min": 1,
                    "max": 100
                }
            }

 },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
                "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
        },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
      },
      "errors": [
        {

     "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
        "smithy.api#http": {
          "method": "GET",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#readonly": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
                    "documentation": "Equal operator"
                },
                {
                    "name": "NOT_EQUAL",
                    "value": "NotEqual",
                    "documentation": "Not equal operator"
                },
                {
                    "name": "CONTAINS",
                    "value": "Contains",
                    "documentation": "Contains operator"
                }
            ],
            "smithy.api#length": {
                "min": 1,
                "max": 20
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled OrganizationIntegration"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
```

```
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
            }
          },
```

```
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"
```

```
}
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "InProgress",
          "value": "InProgress",
          "documentation": "InProgress status"
        },
        {
          "name": "Completed",
          "value": "Completed",
          "documentation": "Completed status"
        },
        {
          "name": "Successful",
          "value": "Successful",
          "documentation": "Successful status"
        },
        {
          "name": "Failed",
          "value": "Failed",
          "documentation": "Failed status"
        }
      ]
    }
  },

  "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
    "type": "list",
    "member": {
      "target": "smithy.api#String",
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        }
      }
    },
    "traits": {
      "smithy.api#length": {
        "min": 1,
        "max": 100
      },
      "smithy.api#uniqueItems": {}
    }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
      "type": "structure",
      "members": {
        "Name":
{
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the subscription.</p>"
          }
        },
        "Type": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
          }
        },
        "InstanceCount": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
```

```
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [

 {
                "name": "RedHat",
                "value": "RedHat",
                "documentation": "RedHat subscription provider namespace"
              }
            ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "ACTIVE",
              "value": "ACTIVE",
              "documentation": "ACTIVE status"
            },
            {
              "name": "INVALID",
              "value": "INVALID",

   "documentation": "INVALID status"
            },
            {
              "name": "PENDING",
              "value": "PENDING",
              "documentation": "PENDING status"
            }
          ]
        }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
      "type": "structure",
      "members":
{
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services resource to which to add the specified \n\t\t\tmetadata tags.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
```

```
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

          "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
          },
```

```
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
```

```
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
          }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
          "type": "structure",
          "members": {
              "message": {
                  "target": "smithy.api#String"
              }
          },
          "traits": {
              "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
              "smithy.api#error": "client"
          }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
```

```
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
```

```
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
```

```
//
// This member is required.
WorkspaceId *string

// A token from Grafana Labs that ties your Amazon Web Services account with a
// Grafana Labs account. For more information, see [Link your account with Grafana Labs].
//
// [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
GrafanaToken *string

noSmithyDocumentSerde
}

type AssociateLicenseOutput
struct {

// A structure containing data about the workspace.
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
```

```
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
```

```
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",

```
            "traits": {
                "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
        },
        "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
        },
        "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
                "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
    "type": "structure",
    "members": {
        "DomainName": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
            }
        },
        "DomainIpv4List": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
            "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                "smithy.api#length": {
                    "min": 1,
                    "max": 2
                }
            }
        },
        "DomainCredentialsProvider": {
            "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
              },
              "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>Contains network access and credential details that are needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
                }
              ]
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#Arn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
 {
            "type": "operation",
            "input": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n          </note>",
            "smithy.api#http":
 {
              "code": 200,
              "method": "POST",
              "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
          "type": "structure",
          "members": {
            "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
              "smithy.api#required": {}
            }
          },
           "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },

        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
```

```
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
      "type": "structure",
      "members": {
        "LicenseServerEndpoint": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
          "traits": {
            "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
```

```
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}

      }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Directory": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
```

```
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary":
{
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
         "type": "structure",
         "members": {
            "Subnets": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                  "smithy.api#length": {
                     "min": 1
                  },
```

```
    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
              }
            },
            "FailureMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
          "type": "list",
          "member": {

            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
    "type": "structure",
    "members": {
        "Username": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

"IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
```

```
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
```

```
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
    "type": "structure",
    "members": {
        "message": {
            "target": "smithy.api#String"
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
         "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
         },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
```

```
        "smithy.api#cors": {
            "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",

            "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
                "Region":
{
                    "builtIn": "AWS::Region",
                    "required": false,
                    "documentation": "The AWS region used to dispatch the request.",
                    "type": "String"
                },
                "UseDualStack": {
                    "builtIn": "AWS::UseDualStack",
                    "required": true,
                    "default": false,
                    "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                    "type": "Boolean"
                },
                "UseFIPS": {
                    "builtIn": "AWS::UseFIPS",
                    "required": true,
```

```
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
            "type": "Boolean"
          },
          "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
             ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [
                  {

                    "fn": "booleanEquals",
                    "argv": [
                      {
```

```
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "aws.partition",

                      "argv": [
                        {
                          "ref": "Region"
                        }
                      ],
                      "assign": "PartitionResult"
                    }
```

```
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },
```

true

```
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
```

"fn": "booleanEquals",

```
                            "argv": [
                              true,
                              {
                                "fn": "getAttr",
                                "argv": [
                                  {
                                    "ref": "PartitionResult"
                                  },
                                  "supportsFIPS"
                                ]
                              }
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              true,
```

```
                                    {
                                      "fn": "getAttr",
                                      "argv": [
                                        {
                                          "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                      ]
                                    }

                                ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

    ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [

 {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
```

```
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "fn": "getAttr",
                                    "argv": [

        {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

    "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS is enabled but this partition does not support FIPS",
                    "type": "error"

}
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {

        "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]

          }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

            ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
```

```
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                            "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
{
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint":
{
                  "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
```

```
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
```

```
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

    },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",

  "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
```

```
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

     "endpoint": {
            "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
 false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
```

```
                },
                {
                  "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                  "expect": {
                    "error": "Invalid Configuration:
 Dualstack and custom endpoint are not supported"
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

  "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
                }
            },
            "LicenseServerEndpointId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits":
```

```
{
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
              }
            },
            "LicenseServerEndpointProvisioningStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
              "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
              }
            },
            "LicenseServers": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
              }
            },

           "CreationTime": {
              "target": "smithy.api#Timestamp",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
          "type": "string"
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

      "type": "string",
          "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
              "name": "PROVISIONED",
              "value": "PROVISIONED",
              "documentation": ""
            },
            {
              "name": "DELETING",
              "value": "DELETING",
              "documentation": ""
            },
            {
              "name": "DELETION_FAILED",
              "value": "DELETION_FAILED",
              "documentation": ""

           },
            {
              "name": "DELETED",
              "value": "DELETED",
              "documentation": ""
            }
          ]
       }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
       "type": "string",
       "traits": {
          "smithy.api#enum": [
            {
              "name": "HEALTHY",
              "value": "HEALTHY",
              "documentation": ""
            },
            {
              "name": "UNHEALTHY",
              "value": "UNHEALTHY",
              "documentation": ""
            },
```

```
                {
                    "name": "NOT_APPLICABLE",
                    "value": "NOT_APPLICABLE",
                    "documentation": ""
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
        "type": "structure",
        "members": {
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
```

```
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n        <li>\n        <p>Product</p>\n        </li>\n
        <li>\n        <p>DirectoryId</p>\n        </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                    "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
 that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                    "smithy.api#required": {}
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
 empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
 next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
```

```
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },

{
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
      }
    ],
    "traits": {
      "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
      "smithy.api#http": {
        "code": 200,
        "method": "POST",
        "uri": "/instance/ListInstances"
      },
      "smithy.api#paginated": {
        "inputToken": "NextToken",
        "outputToken": "NextToken",
        "pageSize": "MaxResults",
        "items": "InstanceSummaries"
      }
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
    "type": "structure",
    "members":
```

```
{
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
      <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
      "type": "structure",
      "members": {
        "InstanceSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
          }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/license-server/ListLicenseServerEndpoints"
        },

      "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "LicenseServerEndpoints"
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
      "type": "structure",
      "members": {
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n        <li>\n          <p>IdentityProviderArn</p>\n        </li>\n      </ul>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
      "type": "structure",
      "members": {
        "LicenseServerEndpoints": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
"operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " Lists the user-based subscription products available from an identity provider. ",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"

```
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
```

```
This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "ProductUserSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

           }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
```

```
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
    "type": "structure",
    "members": {
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
```

```
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {

            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
              }
            },
            "SubscriptionStartDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The start date of a subscription.</p>"
              }
            },
            "SubscriptionEndDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The end date of a subscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
          "type":
 "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
          "type": "structure",
          "members": {
```

```
            "RdsSalCredentialsProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
```

```
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
          "type": "structure",
          "members": {
            "IdentityProvider": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>",
                "smithy.api#required": {}
              }
            },
            "Settings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
              "traits":
 {
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
```

```
                    "min": 1
                }
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
    "type": "string",
    "traits": {
        "smithy.api#length": {

     "min": 5,
            "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
    "type": "structure",
    "members": {
        "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more servers.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
    "type": "union",
    "members": {
        "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

           "traits": {
              "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688
communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
              "smithy.api#required": {}
            }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StartProductSubscription"
            }

      }
       },
       "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
          "type": "structure",
          "members": {
             "Username": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                   "smithy.api#required": {}
                }
             },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                   "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                   "smithy.api#required": {}
                }
             },
             "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                   "smithy.api#required": {}
                }
             },
             "Domain": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
                }
             },
             "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                   "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
                }
```

```
 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "ProductUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }

    }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

 "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
 {
        "type": "structure",
        "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {
```

```
      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
```

```
            "type": "structure",
            "members": {
                "message": {
                    "target": "smithy.api#String"
                }
            },
            "traits": {
                "smithy.api#documentation": "<p>A parameter is not valid.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
```

```
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
```

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation

spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.71 libbsd 0.12.2-r0

1.71.1 Available under license :

Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/

Files:
*
Copyright:
Copyright 2004-2024 Guillem Jover <guillem@hadrons.org>
License: BSD-3-clause

Files:
include/bsd/err.h
include/bsd/stdlib.h
include/bsd/sys/param.h
include/bsd/unistd.h
src/bsd_getopt.c
src/err.c
src/fgetln.c
src/progname.c
Copyright:
Copyright 2005, 2008-2012, 2019 Guillem Jover <guillem@hadrons.org>
Copyright 2005 Hector Garcia Alvarez
Copyright 2005 Aurelien Jarno
Copyright 2006 Robert Millan
Copyright 2018 Facebook, Inc.
License: BSD-3-clause

Files:
include/bsd/netinet/ip_icmp.h
include/bsd/sys/bitstring.h
include/bsd/sys/queue.h
include/bsd/sys/time.h
include/bsd/timeconv.h
include/bsd/vis.h
man/bitstring.3bsd
man/errc.3bsd
man/explicit_bzero.3bsd
man/fgetln.3bsd
man/fgetwln.3bsd
man/fpurge.3bsd
man/funopen.3bsd
man/getbsize.3bsd
man/heapsort.3bsd
man/nlist.3bsd
man/pwcache.3bsd

man/queue.3bsd
man/radixsort.3bsd
man/reallocarray.3bsd
man/reallocf.3bsd
man/setmode.3bsd
man/strmode.3bsd
man/strnstr.3bsd
man/strtoi.3bsd
man/strtou.3bsd
man/unvis.3bsd
man/vis.3bsd
man/wcslcpy.3bsd
src/getbsize.c
src/heapsort.c
src/merge.c
src/nlist.c
src/pwcache.c
src/radixsort.c
src/setmode.c
src/strmode.c
src/strnstr.c
src/strtoi.c
src/strtou.c
src/unvis.c
Copyright:
Copyright 1980, 1982, 1986, 1989-1994
The Regents of the University of California. All rights reserved.
Copyright 1992 Keith Muller.
Copyright 2001 Mike Barcroft <mike@FreeBSD.org>
.
Some code is derived from software contributed to Berkeley by
the American National Standards Committee X3, on Information
Processing Systems.
.
Some code is derived from software contributed to Berkeley by
Peter McIlroy.
.
Some code is derived from software contributed to Berkeley by
Ronnie Kon at Mindcraft Inc., Kevin Lew and Elmer Yglesias.
.
Some code is derived from software contributed to Berkeley by
Dave Borman at Cray Research, Inc.
.
Some code is
derived from software contributed to Berkeley by
Paul Vixie.
.
Some code is derived from software contributed to Berkeley by

Chris Torek.
.
Copyright UNIX System Laboratories, Inc.
All or some portions of this file are derived from material licensed
to the University of California by American Telephone and Telegraph
Co. or Unix System Laboratories, Inc. and are reproduced herein with
the permission of UNIX System Laboratories, Inc.
License: BSD-3-clause-Regents

Files:
src/vis.c
Copyright:
Copyright 1989, 1993
    The Regents of the University of California. All rights reserved.
.
Copyright 1999, 2005 The NetBSD Foundation, Inc.
All rights reserved.
License: BSD-3-clause-Regents and BSD-2-clause-NetBSD

Files:
include/bsd/libutil.h
Copyright:
Copyright 1996 Peter Wemm <peter@FreeBSD.org>.
All rights reserved.
Copyright 2002 Networks Associates Technology, Inc.
All rights reserved.
License: BSD-3-clause-author

Files:
man/timeradd.3bsd
Copyright:
Copyright
  2009 Jukka Ruohonen <jruohonen@iki.fi>
Copyright 1999 Kelly Yancey <kbyanc@posi.net>
All rights reserved.
License: BSD-3-clause-John-Birrell
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
3. Neither the name of the author nor the names of any co-contributors
   may be used to endorse or promote products derived from this software
   without specific prior written permission.
.

THIS SOFTWARE IS PROVIDED BY JOHN BIRRELL AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES
 OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

Files:
man/setproctitle.3bsd
Copyright:
Copyright 1995 Peter Wemm <peter@FreeBSD.org>
All rights reserved.
License: BSD-5-clause-Peter-Wemm
Redistribution and use in source and binary forms, with or without
modification, is permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice immediately at the beginning of the file, without
 modification,
   this list of conditions, and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
3. This work was done expressly for inclusion into FreeBSD. Other use
   is permitted provided this notation is included.
4. Absolutely no warranty of function or purpose is made by the author
   Peter Wemm.
5. Modifications may be freely made to this file providing the above
   conditions are met.

Files:
include/bsd/stringlist.h
man/arc4random.3bsd
man/fmtcheck.3bsd
man/humanize_number.3bsd
man/stringlist.3bsd
man/timeval.3bsd
src/fmtcheck.c
src/humanize_number.c
src/stringlist.c
src/strtonum.c
Copyright:

Copyright 1994, 1997-2000, 2002, 2008, 2010, 2014
The NetBSD Foundation, Inc.
Copyright 2013 John-Mark Gurney <jmg@FreeBSD.org>
All rights reserved.
.
Copyright 2014
The NetBSD Foundation, Inc.
All rights reserved.
.
Some code was derived from software contributed to The NetBSD Foundation
by Taylor R. Campbell.
.
Some code was contributed to The NetBSD Foundation by Allen Briggs.
.
Some code was contributed to The NetBSD Foundation by Luke Mewburn.
.
Some code is derived from software contributed to The NetBSD Foundation
by Jason R. Thorpe of the Numerical Aerospace Simulation Facility,
NASA Ames Research Center, by Luke Mewburn and by Tomas Svensson.
.
Some code is derived from software contributed to The NetBSD Foundation
by Julio M. Merino Vidal, developed as part of Google's Summer of Code
2005 program.
.
Some code is derived from software contributed to The NetBSD Foundation
by Christos Zoulas.
.
Some code is derived from software contributed to The NetBSD Foundation
by Jukka Ruohonen.
License: BSD-2-clause-NetBSD

Files:
include/bsd/sys/endian.h
man/byteorder.3bsd
man/closefrom.3bsd
man/expand_number.3bsd
man/flopen.3bsd
man/getpeereid.3bsd
man/pidfile.3bsd
src/expand_number.c
src/pidfile.c
src/reallocf.c
src/timeconv.c
Copyright:
Copyright 1998, M. Warner Losh <imp@freebsd.org>
All rights reserved.
.
Copyright 2001 Dima Dorfman.

All rights reserved.
.
Copyright 2001 FreeBSD Inc.
All rights reserved.
.
Copyright 2002 Thomas Moestl <tmm@FreeBSD.org>
All rights reserved.
.
Copyright 2002 Mike Barcroft <mike@FreeBSD.org>
All rights reserved.
.
Copyright 2005 Pawel Jakub Dawidek <pjd@FreeBSD.org>
All rights reserved.
.
Copyright 2005 Colin Percival
All rights reserved.
.
Copyright 2007 Eric Anderson <anderson@FreeBSD.org>
Copyright 2007 Pawel Jakub Dawidek <pjd@FreeBSD.org>
All rights reserved.
.
Copyright 2007 Dag-Erling Codan Smrgrav
All rights reserved.
.
Copyright 2009 Advanced Computing Technologies LLC
All rights reserved.
.
Copyright 2011 Guillem Jover <guillem@hadrons.org>
License: BSD-2-clause

Files:
src/flopen.c
Copyright:
Copyright 2007-2009
 Dag-Erling Codan Smrgrav
All rights reserved.
License: BSD-2-clause-verbatim
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer
   in this position and unchanged.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
.
THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND

ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

Files:
include/bsd/sys/tree.h
man/fparseln.3bsd
man/tree.3bsd
src/fparseln.c
Copyright:
Copyright 1997 Christos Zoulas.
All rights reserved.
.
Copyright 2002 Niels Provos <provos@citi.umich.edu>
All rights reserved.
License: BSD-2-clause-author

Files:
include/bsd/readpassphrase.h
man/readpassphrase.3bsd
man/strlcpy.3bsd
man/strtonum.3bsd
src/arc4random.c
src/arc4random_linux.h
src/arc4random_uniform.c
src/arc4random_unix.h
src/arc4random_win.h
src/closefrom.c
src/freezero.c
src/getentropy_aix.c
src/getentropy_bsd.c
src/getentropy_hpux.c
src/getentropy_hurd.c
src/getentropy_linux.c
src/getentropy_osx.c
src/getentropy_solaris.c
src/getentropy_win.c
src/readpassphrase.c
src/reallocarray.c
src/recallocarray.c

src/strlcat.c
src/strlcpy.c
test/explicit_bzero.c
test/strtonum.c
Copyright:
Copyright 2004 Ted Unangst and Todd Miller
All rights reserved.
.
Copyright 1996 David Mazieres <dm@uun.org>
Copyright 1998, 2000-2002, 2004-2005, 2007, 2010, 2012-2015
  Todd C. Miller <Todd.Miller@courtesan.com>
Copyright 2004 Ted Unangst
Copyright 2004 Otto Moerbeek <otto@drijf.net>
Copyright 2008 Damien Miller <djm@openbsd.org>
Copyright 2008, 2010-2011, 2016-2017 Otto Moerbeek <otto@drijf.net>
Copyright 2013 Markus Friedl <markus@openbsd.org>
Copyright 2014 Bob Beck <beck@obtuse.com>
Copyright 2014 Brent Cook <bcook@openbsd.org>
Copyright 2014 Pawel Jakub Dawidek <pjd@FreeBSD.org>
Copyright 2014 Theo de Raadt <deraadt@openbsd.org>
Copyright 2014 Google Inc.
Copyright 2015 Michael Felt <aixtools@gmail.com>
Copyright 2015, 2022 Guillem Jover <guillem@hadrons.org>
License:
 ISC
Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.
.
THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Files:
src/inet_net_pton.c
Copyright:
Copyright 1996 by Internet Software Consortium.
License: ISC-Original
Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice
 and this permission notice appear in all copies.
.
THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS

ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Files:
src/setproctitle.c
Copyright:
Copyright 2010 William Ahern
Copyright 2012 Guillem Jover <guillem@hadrons.org>
License: Expat
Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute,
 sublicense, and/or sell copies of the Software, and to permit
persons to whom the Software is furnished to do so, subject to the
following conditions:
.
The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.
.
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN
NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE
USE OR OTHER DEALINGS IN THE SOFTWARE.

Files:
src/explicit_bzero.c
src/chacha_private.h
Copyright:
None
License: public-domain
Public domain.

Files:
man/mdX.3bsd
Copyright:
None
License: Beerware
"THE BEER-WARE LICENSE" (Revision 42):

<phk@login.dkuug.dk> wrote this
file. As long as you retain this notice you
can do whatever you want with this stuff. If we meet some day, and you think
this stuff is worth it, you can buy me a beer in return. Poul-Henning Kamp

License: BSD-3-clause-Regents
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.
.
THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

License: BSD-3-clause-author
Redistribution and use in source and binary forms, with or without
modification, is permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions
in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
products derived from this software without specific prior written
permission.
.
THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE

FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: BSD-3-clause
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
   derived from this software without specific prior written permission.
.
THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: BSD-2-clause-NetBSD
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
.
THIS SOFTWARE IS PROVIDED BY THE NETBSD FOUNDATION, INC. AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE FOUNDATION OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR

CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: BSD-2-clause-author
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above
 copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
.
THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
 DAMAGE.

License: BSD-2-clause
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
.
THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,

DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.72 swaggo-files 1.0.1

1.72.1 Available under license :

MIT License

Copyright (c) 2019 Swaggo

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.73 github.com/aws/aws-sdk-go-v2/service/s3 1.86.0

1.73.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd

Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (

```
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
```

```
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {
```

```
// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
```

```
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
```

Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd

Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware

```
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
```

```
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense
```

```
 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
```

```
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
```

```
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if
err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}
```

```
func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
```

```
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
```

```
//   - Beneficiary
//
//   - ProductSKU
//
//   - Fingerprint
//
//   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
```

```
if err := addProtocolFinalizerMiddlewares(stack,
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
```

```
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
```

```
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
```

```
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
```

```
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if
err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
```

```
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}
```

```
type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string
```

```
// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
```

```
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
```

```
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },

        {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/DeregisterSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
```

```
            "Name": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The type of name to filter by.</p>"
               }
            },
            "Values": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                  "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
               }
            },
            "Operator": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
               "traits": {
                  "smithy.api#documentation": "<p>An operator for filtering results.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
         "type":
 "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
         },
         "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/GetRegisteredSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

          "traits": {
              "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
```

```
specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
                 }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
          "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
          },
          "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
          },
          "AccountID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
```

```
            },
            "Region": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
               }
            },
            "UsageOperation": {
               "target": "smithy.api#String",

   "traits": {
                  "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
               }
            },
            "ProductCode": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
               "traits": {
                  "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
               }
            },
            "LastUpdatedTime": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
               }
            },
            "SubscriptionName": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
               }
            },
            "OsVersion": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
               }
            },
            "SubscriptionProviderCreateTime": {
               "target": "smithy.api#String",
               "traits": {
```

```
                "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
              }
            },
            "SubscriptionProviderUpdateTime": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
              }
            },
            "DualSubscription": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
              }
            },
            "RegisteredWithSubscriptionProvider": {
              "target": "smithy.api#String",
              "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation":
```

```
"<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
          "type": "service",
          "version": "2018-05-10",
          "operations": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
             },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
            }
          ],
          "traits": {
            "aws.api#service": {
              "sdkId": "License Manager Linux Subscriptions",
               "arnNamespace": "license-manager-linux-subscriptions",
              "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
            },
```

```
        "aws.auth#sigv4": {
          "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
```

```
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }

],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
```

```
}
                                ],
                                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                                "type": "error"
                            },
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": {
                                        "ref": "Endpoint"
                                    },
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"

                    }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "isSet",
                                    "argv": [
                                        {
                                            "ref": "Region"
                                        }
                                    ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [
                                        {

                    "fn": "aws.partition",
                                            "argv": [
                                                {
                                                    "ref": "Region"
                                                }
```

```
                ],
                "assign": "PartitionResult"
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {

                      "ref": "UseFIPS"
                            },
                            true
                        ]
                    },
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }

],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

},
                                                "supportsFIPS"
                                        ]
                                    }
                                ]
                            },
                            {
```

```
                "fn": "booleanEquals",
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [

                     {
                          "ref": "PartitionResult"
                      },
                      "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [],

      "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],

          "type": "tree"
                    }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",

                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
```

```
            "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
                    true
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {

          "fn": "booleanEquals",
                      "argv": [
                        {
                          "fn": "getAttr",
                          "argv": [
                            {
                              "ref": "PartitionResult"
                            },
                            "supportsFIPS"
                          ]
                        },
                        true

                    ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "rules": [
                        {
                          "conditions": [],
                          "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                            "headers": {}
                          },
                          "type": "endpoint"
                        }
```

```
                ],
                "type": "tree"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [],
            "error": "FIPS is enabled
but this partition does not support FIPS",
            "type": "error"
          }
        ],
        "type": "tree"
      },
      {
        "conditions": [
          {
            "fn": "booleanEquals",
            "argv": [
              {
                "ref": "UseDualStack"
              },
              true

    ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [
                      {

                      "ref": "PartitionResult"
                      },
                      "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
```

```
                "rules": [
                  {
                    "conditions": [],
                    "rules": [

        {
                        "conditions": [],
                        "endpoint": {
                          "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                          "properties": {},
                          "headers": {}
                        },
                        "type": "endpoint"
                      }
                    ],
                    "type": "tree"

                }
                  ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
                  "type": "error"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "rules": [
                {
                  "conditions": [],
                  "endpoint": {
                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                    "properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            }
          ],
          "type": "tree"
```

```
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
            }
        ],
        "type": "tree"
    }
  ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
```

```
                "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
              }

        },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
```

```
            }

        },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

      "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
```

```
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
       }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "error": "DualStack is enabled but this partition does not support DualStack"
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {

   "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
      }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
    "expect": {
      "endpoint": {
        "url": "https://example.com"
      }
```

```
    },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://example.com"
                  }
                },
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

 "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
```

```
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

        },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

 {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n        <li>\n  <p>\n            <code>AccountID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n    <code>AmiID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>DualSubscription</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceType</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>ProductCode</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Region</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Status</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>UsageOperation</code>\n          </p>\n        </li>\n      </ul>\n      <p>For each filter, you can use one of the following <code>Operator</code>\n values to \n  \t\tdefine the behavior of the filter:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
```

```
            "Instances": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
               "traits": {
                  "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
               }
            },
            "NextToken": {

         "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
```

```
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n
<li>\n              <p>\n                <code>Subscription</code>\n              </p>\n            </li>\n          </ul>\n
<p>The
 valid Operators for this filter are:</p>\n          <ul>\n            <li>\n              <p>\n
<code>contains</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>equals</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>Notequal</code>\n              </p>\n            </li>\n          </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
      "type": "structure",
      "members": {
        "Subscriptions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
```

```
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "RegisteredSubscriptionProviders"
            }
         }

      },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
         "type": "structure",
         "members": {
            "SubscriptionProviderSources": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
               "traits": {
                  "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }

    },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
       },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
         "type": "structure",
         "members": {
            "RegisteredSubscriptionProviders": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
```

```
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
          }
        },
        "SubscriptionProviderArn": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
          }
        },
```

```
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
               }
            },
            "SubscriptionProviderStatusMessage": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
               }
            },
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

  }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
                    "documentation": "Failed status"
                }
            ]
        }
    },

   "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
            }
          },
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            },
            "smithy.api#uniqueItems": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
          "type": "map",
          "key": {
            "target": "smithy.api#String"
          },
          "value": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
          "type": "structure",
          "members": {
            "Name":
{
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the subscription.</p>"
              }
            },
            "Type": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
              }
            },
            "InstanceCount": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
              "traits": {
                "smithy.api#documentation": "<p>The total amount of running instances using this
```

```
subscription.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
              ]
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                  "name": "ACTIVE",
                  "value": "ACTIVE",
                  "documentation": "ACTIVE status"
```

```
            },
            {
              "name": "INVALID",
              "value": "INVALID",

"documentation": "INVALID status"
            },
            {
              "name": "PENDING",
              "value": "PENDING",
              "documentation": "PENDING status"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
         },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
```

```
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
{
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
         "type": "map",
         "key": {
            "target": "smithy.api#String"
         },
```

```
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
           "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
          }
        },
        "StatusMessage": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
          "traits": {
            "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
          }

     },
        "HomeRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
```

```
            "traits": {
                "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
```

```
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string
```

```
// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string
```

```
// License status.
Status types.LicenseDeletionStatus

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
        "type": "structure",
        "members": {
            "DirectoryId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
                "traits": {
                    "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
                }
            },
            "ActiveDirectorySettings":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
                }
            },
            "ActiveDirectoryType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
```

```
            },
            "DomainIpv4List": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 2
                  }
               }
            },
            "DomainCredentialsProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
               }
            },
            "DomainNetworkSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
               },
               {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
               }
```

```
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
```

```
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http":
 {
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
                }
            }
```

```
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
          "type": "union",
          "members": {
            "SecretsManagerCredentialsProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
              "traits": {
```

```
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
```

```
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
            "smithy.api#length": {
              "min": 1
            },

  "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Attribute": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
          }
        },
        "Operation": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
          }
        },
        "Value": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>Value of the filter.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
```

```
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
          },
          "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
              }
            },
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

    "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details \n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance user.</p>"
             }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
```

```
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
             "smithy.api#error": "server",
            "smithy.api#httpError": 500
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
```

```
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
},
{
```

```
    "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
          ],
          "traits": {
            "aws.api#service": {
              "sdkId": "License Manager User Subscriptions",
              "arnNamespace": "license-manager-user-subscriptions",
              "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
              "name": "license-manager-user-subscriptions"
            },
            "aws.protocols#restJson1": {},
            "smithy.api#cors": {
              "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",

           "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
              ],
              "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
              ]
            },
            "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to
utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager User Subscriptions",
            "smithy.rules#endpointRuleSet": {
              "version": "1.0",
              "parameters": {
                "Region":
{
                  "builtIn": "AWS::Region",
                  "required": false,
                  "documentation": "The AWS region used to dispatch the request.",
```

```
            "type": "String"
        },
        "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
            "type": "Boolean"
        },
        "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
        },
        "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
```

```
                    ]
                }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [
                {

                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": {
                    "ref": "Endpoint"
                },

"properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "isSet",
                "argv": [
                    {
                        "ref": "Region"
                    }
                ]
            }
        ],
```

```
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "aws.partition",

                       "argv": [
                            {
                              "ref": "Region"
                            }
                          ],
                          "assign": "PartitionResult"
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseFIPS"
                              },

true
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseDualStack"
                              },
                              true
                            ]
                          }
                        ],
                        "rules": [
                          {
                            "conditions": [
                              {

"fn": "booleanEquals",
                                  "argv": [
                                    true,
                                    {
                                      "fn": "getAttr",
                                      "argv": [
```

```
                                {
                                    "ref": "PartitionResult"
                                },
                                "supportsFIPS"
                            ]
                        }
                    ]
                },

            {
                "fn": "booleanEquals",
                "argv": [
                    true,
                    {
                        "fn": "getAttr",
                        "argv": [
                            {
                                "ref": "PartitionResult"
                            },
                            "supportsDualStack"
                        ]
                    }

        ]
                }
            ],
            "rules": [
                {
                    "conditions": [],
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [

{
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
```

```
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

}
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

    "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]

    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

                            ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
```

```
{
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",

      "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint":
{
                        "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",
```

```
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
         "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
```

```
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
```

```
      },
      "params": {
        "Region": "us-isob-east-1",

  "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

       "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
```

```
false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                    "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
    }
  }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
  "type": "structure",
  "members": {
    "ProvisioningStatus": {
      "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
       "traits": {
         "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
```

```
\n\t\t\tlicense server.</p>"
                }
            },
            "HealthStatus": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
                }
            },
            "Ipv4Address": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

  "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
        },
        "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
        },
        "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
        },
        "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
        },
        "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
        },

       "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
        }
    },
    "traits": {
      "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
    }
  },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
      "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
      "type": "structure",
      "members": {
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>",
            "smithy.api#required": {}
          }
        },
        "ServerSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
            "smithy.api#required": {}
          }
        }
      },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {

        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/identity-provider/ListIdentityProviders"
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
```

```
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
```

contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria. "
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": " The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/ListLicenseServerEndpoints"
            },

          "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
          "type": "structure",
          "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                 "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
```

```
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
             "traits": {
               "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListProductSubscriptions"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "ProductUserSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
 {
        "type": "structure",
        "members": {
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
             "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
```

```
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n          <p>Status</p>\n          </li>\n          <li>\n          <p>Username</p>\n
</li>\n          <li>\n          <p>Domain</p>\n          </li>\n          </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#readonly": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

           }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
```

```
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {

    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
```

```
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
         "type": "structure",
         "members": {
            "IdentityProvider": {

     "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                  "smithy.api#required": {}
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
               "traits":
```

```
{
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",
```

```
    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
            "smithy.api#length": {

             "min": 5,
                "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
            "Endpoint": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
             "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
```

```
                "smithy.api#length": {
                    "min": 1
                },
                "smithy.api#required": {}
            }
        },
        "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
            }

    }
     },
     "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n        <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
```

```
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
              }
            },
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
          "type": "structure",
          "members": {
            "ProductUserSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                "smithy.api#required": {}
              }

    }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StringList": {
          "type": "list",
          "member": {
```

```
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
```

```
        "traits": {
          "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
```

```
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

           "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
            "smithy.api#http": {

      "code": 200,
                "method": "POST",
                "uri": "/identity-provider/UpdateIdentityProviderSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },

            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
                }
            },
            "UpdateSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
                "traits": {
                    "smithy.api#documentation": "<p>Updates the registered identity providers product related
```

configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the: \n \n \n Subnets which you want to add to provision VPC endpoints. \n \n \n Subnets which you want to remove the VPC endpoints from. \n \n \n Security
group ID which permits traffic to the VPC endpoints. \n \n ",
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
"type": "structure",
"members": {
"IdentityProviderSummary": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
"traits": {
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
"type": "structure",
"members": {
"AddSubnets": {

"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets in which License Manager will create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers. ",
"smithy.api#required": {}
}
},
"RemoveSubnets": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets to remove. ",
"smithy.api#required": {}
}
},
"SecurityGroupId": {
"target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

```
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
```


```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if
```

```
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
```

Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.74 google-uuid 1.6.0

1.74.1 Available under license :

Paul Borman <borman@google.com>
bmatsuo
shawnps
theory
jboverfelt
dsymonds
cd1
wallclockbuilder
dansouza
Copyright (c) 2009,2014 Google Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT

OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.75 go-openapi-jsonpointer 0.21.1

1.75.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their

Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf

of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.76 zgo.at-zcache 2.2.0

1.76.1 Available under license :

Copyright (c) 2012-2019 Patrick Mylund Nielsen and the go-cache contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.77 github.com/aws/aws-sdk-go-v2/feature/s3/manager 1.18.3

1.77.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2

```
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
```

```
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer

 // License name.
 //
 // This member is required.
 LicenseName *string

 // Product name.
 //
 // This member is required.
 ProductName *string
```

```
 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // Date and time range during which the license is valid, in ISO8601-UTC format.
 //
 // This member is required.
 Validity *types.DatetimeRange

 // Information about
 the license.
 LicenseMetadata []types.Metadata

 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
```

```
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
```

```
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
```

```
  runs-on: ubuntu-latest
  strategy:
    matrix:
      python-version: [3.9]

  steps:
    - name: Checkout target
      uses: actions/checkout@v2
      with:
        path: sdkbase
        ref: ${{ github.base_ref }}
    - name: Checkout this ref
      uses: actions/checkout@v2
      with:
        path: new-ref
        fetch-depth: 0
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
       uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
```

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper

```
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
```

```
  - Fingerprint
//
//   - IssuerName
//
//   - Beneficiary
Filters []types.Filter

// Amazon Resource Names (ARNs) of the licenses.
LicenseArns []string

// Maximum number of results to return in a single call.
MaxResults *int32

// Token for the next set of results.
NextToken *string

noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

// Received license details.
Licenses []types.GrantedLicense

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
```

```
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
```

```
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
```

```
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
```

```
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {
```

```
// License details.
Licenses []types.License

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
```

```
 return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
 err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if
err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
```

```
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

```
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
```

```
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
```

```
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
```

```
}
if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
```

```
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string
```

```
 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go
Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": " Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account. ",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/DeregisterSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
      "type": "structure",

```
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
      "type":
 "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
      },
      "output": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
         },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/GetRegisteredSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation":
```

```
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

          "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
                 }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
```

```
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
         "type": "operation",
         "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/GetServiceSettings"

          },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
         "type": "structure",
         "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
```

```
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
```

```
            "InstanceID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
               }
            },
            "InstanceType": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>The instance type of the resource.</p>"
               }
            },
            "AccountID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
               }
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of the instance.</p>"
               }
            },
            "Region": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
               }
            },
            "UsageOperation": {
               "target": "smithy.api#String",

   "traits": {
                  "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
               }
            },
            "ProductCode": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
               "traits": {
                  "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
               }
```

```
        },
        "LastUpdatedTime": {
          "target": "smithy.api#String",
           "traits": {
             "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
          }
        },
        "SubscriptionName": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
          }
        },
        "OsVersion": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
          }
        },
        "SubscriptionProviderCreateTime": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
          }
        },
        "SubscriptionProviderUpdateTime": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the registered \n\t\t\tthird-party Linux subscription provider.</p>"
          }
        },
        "DualSubscription": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for \n\t\t\tthe same software on your instance.</p>"
          }
        },
        "RegisteredWithSubscriptionProvider": {
          "target": "smithy.api#String",
          "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta third-party Linux subscription provider that you've registered with License Manager.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager Linux Subscriptions",
           "arnNamespace": "license-manager-linux-subscriptions",
          "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
```

```
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
```

```
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }

        ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseDualStack"
                                },
                                true
                            ]

}
                    ],
                    "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "endpoint": {
                        "url": {
                            "ref": "Endpoint"
                        },
                        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }
            ],
            "type": "tree"

        }
        ],
        "type": "tree"
    },
    {
```

```
"conditions": [],
"rules": [
  {
    "conditions": [
      {
        "fn": "isSet",
        "argv": [
          {
            "ref": "Region"
          }
        ]
      }
    ],
    "rules": [
      {
        "conditions": [
          {

"fn": "aws.partition",
            "argv": [
              {
                "ref": "Region"
              }
            ],
            "assign": "PartitionResult"
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {

                "ref": "UseFIPS"
                  },
                  true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
```

```
                }

    ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

                },
                                        "supportsFIPS"
                                    ]
                                }
                            ]
                        },
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                true,
                                {
                                    "fn": "getAttr",
                                    "argv": [

                                     {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],

        "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-subscriptions-
```

```
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],

                                "type": "tree"
                                        }
                                    ],
                                    "type": "tree"
                                },
                                {
                                    "conditions": [],
                                    "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {

                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "ref": "UseFIPS"
                                            },
                                            true
                                        ]
                                    }
                                ],
                                "rules": [
                                    {
                                        "conditions": [
                                            {

                            "fn": "booleanEquals",
                                                "argv": [
                                                    {
                                                        "fn": "getAttr",
                                                        "argv": [
                                                            {
                                                                "ref": "PartitionResult"
                                                            },
```

```
                                    "supportsFIPS"
                                ]
                            },
                            true

                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS is enabled
but this partition does not support FIPS",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseDualStack"
                    },
                    true
```

```
                ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {

                                            "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "rules": [

        {
                                        "conditions": [],
                                        "endpoint": {
                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"

                    }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "DualStack is enabled but this partition does not support DualStack",
```

```
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ],
    "type": "tree"
}
]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
            },
            "params": {
```

```
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {

      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
```

```
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                    }
                },
                "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {

 "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                    }
                },
                "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                    }
                 },
                "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
                    }
                },
                "params": {
                    "Region": "cn-north-1",
```

```
            "UseFIPS": false,
            "UseDualStack": false
        }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }

     },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
        }
    },
    {
```

```
"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
                      }
                    },
                    "params": {
                      "Region": "us-gov-east-1",
                      "UseFIPS": false,
                      "UseDualStack": false
                    }
                  },
                  {
                    "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                    "expect": {
                      "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                    },
                    "params": {

                 "Region": "us-iso-east-1",
                      "UseFIPS": true,
                      "UseDualStack": true
                    }
                  },
                  {
                    "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                      }
                    },
                    "params": {
                      "Region": "us-iso-east-1",
                      "UseFIPS": true,
                      "UseDualStack": false
                    }
                  },
                  {
                    "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
                    "expect": {
                      "error": "DualStack is enabled but this partition does not support DualStack"
                    },
                    "params": {
                      "Region": "us-iso-east-1",
                      "UseFIPS": false,
                      "UseDualStack": true
                    }
```

```
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": true
```

```
      }
    },
    {

      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
```

```
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled LinuxSubscriptionsDiscovery"

      },
            {
              "name": "Disabled",
              "value": "Disabled",
```

```
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

    {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
```

```
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n    \t<code>Value</code>, such as <code>us-west</code>.</p>\n         <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n         <ul>\n            <li>\n               <p>\n                  <code>AccountID</code>\n               </p>\n            </li>\n            <li>\n               <p>\n                  <code>AmiID</code>\n               </p>\n            </li>\n            <li>\n               <p>\n                  <code>DualSubscription</code>\n               </p>\n            </li>\n            <li>\n               <p>\n                  <code>InstanceID</code>\n               </p>\n            </li>\n            <li>\n               <p>\n                  <code>InstanceType</code>\n               </p>\n            </li>\n            <li>\n               <p>\n                  <code>ProductCode</code>\n               </p>\n            </li>\n            <li>\n               <p>\n                  <code>Region</code>\n               </p>\n            </li>\n            <li>\n               <p>\n                  <code>Status</code>\n               </p>\n            </li>\n            <li>\n               <p>\n                  <code>UsageOperation</code>\n               </p>\n            </li>\n         </ul>\n         <p>For each filter, you can use one of the following <code>Operator</code>\n          values to \n          \t\tdefine the behavior of the filter:</p>\n         <ul>\n            <li>\n               <p>\n                  <code>contains</code>\n               </p>\n            </li>\n            <li>\n               <p>\n                  <code>equals</code>\n               </p>\n            </li>\n            <li>\n               <p>\n                  <code>Notequal</code>\n               </p>\n            </li>\n         </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
 parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
          "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
              "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
            }
          },
          "NextToken": {

         "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
 isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
 next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
           {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptions"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",

   "items": "Subscriptions"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n      <p>The valid names for this filter are:</p>\n      <ul>\n <li>\n          <p>\n            <code>Subscription</code>\n          </p>\n        </li>\n      </ul>\n <p>The
 valid Operators for this filter are:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
```

```
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
          "type": "structure",
          "members": {
            "Subscriptions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
               "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
```

```
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "RegisteredSubscriptionProviders"
            }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSources": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
                "traits": {
                    "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                "smithy.api#range": {
                  "min": 1,
                  "max": 100
                }
              }

  },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
          "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
            }
          },

           "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
             }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
              "name": "CONTAINS",
              "value": "Contains",
              "documentation": "Contains operator"
            }
          ],
          "smithy.api#length": {
            "min": 1,
            "max": 20
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
```

```
                "documentation": "Disabled OrganizationIntegration"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
                "smithy.api#required": {}
              }
            },
            "SecretArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
              "traits": {
                "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
              }
            },
            "SubscriptionProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
              }
            },
            "SubscriptionProviderStatus": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
              "traits": {
                "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
              }
```

```
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
                "traits": {
                    "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
                }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
                }
            },
```

```
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"

   }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "InProgress",
                  "value": "InProgress",
```

```
            "documentation": "InProgress status"
          },
          {
            "name": "Completed",
            "value": "Completed",
            "documentation": "Completed status"
          },
          {
            "name": "Successful",
            "value": "Successful",
            "documentation": "Successful status"
          },
          {
            "name": "Failed",
            "value": "Failed",
            "documentation": "Failed status"
          }
        ]
      }
    },

    "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
          }
        }
      },
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        },
        "smithy.api#uniqueItems": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
      "type": "structure",
      "members": {
        "Name":
{
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the subscription.</p>"
          }
        },
        "Type": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS.</p>"
          }
        },
        "InstanceCount": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>The total amount of running instances using this subscription.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
      "type": "string",
      "traits": {
```

```
            "smithy.api#enum": [

{
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
                },
                {
                    "name": "INVALID",
                    "value": "INVALID",

 "documentation": "INVALID status"
                },
                {
                    "name": "PENDING",
                    "value": "PENDING",
                    "documentation": "PENDING status"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
```

```
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
           },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
              "method": "PUT",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
          "type": "structure",
          "members":
 {
            "resourceArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}
              }
            },
            "tags": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
         "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        },
        "tagKeys": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
          "traits": {

         "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
            "smithy.api#httpQuery": "tagKeys",
            "smithy.api#required": {}
          }
        }
```

```
    },
    "traits": {
        "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
    "type": "structure",
    "members": {},
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

 },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
        },
        "smithy.api#idempotent": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
    "type": "structure",
    "members": {
        "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
```

```
                "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                "smithy.api#required": {}
            }
        },
        "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                "smithy.api#required": {}
            }
        },
        "AllowUpdate": {
            "target":
 "smithy.api#Boolean",
            "traits": {
                "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
```

```
            "StatusMessage": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
               "traits": {
                  "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
               }

        },
            "HomeRegions": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                  "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
         }
      }
   }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
```

```
 params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string
```

```
 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
```

```
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
```

```
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html#AMG-workspace-register-enterprise
```

```
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
```

```
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
```

```
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
```

```
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
```

```
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }
```

```
if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
```

```
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
```

OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer

in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
```

\n\t\t\taddresses, and the credential provider for user administration. "
            }
          },
          "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
              "smithy.api#documentation": " The type of Active Directory either a self-managed Active Directory or an \n\t\t\tAmazon Web Services Managed Active Directory. "
            }
          }
        },
        "traits": {
          "smithy.api#documentation": " Details about an Active Directory identity provider. "
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
          "DomainName": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " The domain name for the Active Directory. "
            }
          },
          "DomainIpv4List": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
            "traits": {
              "smithy.api#documentation": " A list of domain IPv4 addresses that are used for the Active Directory. ",
              "smithy.api#length": {
                "min": 1,
                "max": 2
              }
            }
          },
          "DomainCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": " Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration. "
            }
          },
          "DomainNetworkSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
            "traits": {
              "smithy.api#documentation": " The <code>DomainNetworkSettings</code> resource contains an

```
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "SELF_MANAGED",
                    "value": "SELF_MANAGED",
                    "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                    "name": "AWS_MANAGED",
                    "value": "AWS_MANAGED",
                    "documentation": "AWS_MANAGED type of Active Directory"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n        <note>\n          <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
          "smithy.api#http":
{
            "code": 200,
            "method": "POST",
            "uri": "/user/AssociateUser"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
```

```
subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
                }
            }
        },
        "traits": {

    "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
        "smithy.api#error": "server"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },

      {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
```

```
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                "smithy.api#required": {}
              }
            },
            "LicenseServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
          "type": "union",
          "members": {
            "SecretsManagerCredentialsProvider":
{
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
              "traits": {
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
           },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/DeleteLicenseServerEndpoint"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
              "smithy.api#required": {}
            }
          },
           "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
            "traits": {
              "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#output": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
         },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
```

```
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
```

```
information for the user to disassociate.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
        "type": "structure",
        "members": {
            "Subnets": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
                "traits": {
                    "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                    "smithy.api#length": {
                        "min": 1
                    },

   "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
            }
          },
          "Value": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>Value of the filter.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
          "ActiveDirectoryIdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
             "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
```

```
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
                }
            },
            "FailureMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
              "smithy.api#required": {}
            }
          },
          "Products": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
              "smithy.api#required": {}
            }
          },
          "LastStatusCheckDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
          }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },

    "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
```

```
user.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
                }
            },
            "AssociationDate": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
                }
            },
            "DisassociationDate": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
```

```
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
        "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",
```

```
            "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
                "Region":
{
                    "builtIn": "AWS::Region",
                    "required": false,
                    "documentation": "The AWS region used to dispatch the request.",
                    "type": "String"
                },
                "UseDualStack": {
                    "builtIn": "AWS::UseDualStack",
                    "required": true,
                    "default": false,
                    "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                    "type": "Boolean"
                },
                "UseFIPS": {
                    "builtIn": "AWS::UseFIPS",
                    "required": true,
                    "default": false,
                    "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                    "type": "Boolean"
                },
                "Endpoint": {
                    "builtIn": "SDK::Endpoint",
                    "required": false,
                    "documentation": "Override the endpoint used to send this request",
```

```
        "type": "String"
      }
    },
    "rules": [
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Endpoint"
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [
              {

                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
```

```
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Region"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "aws.partition",

                   "argv": [
                      {
                        "ref": "Region"
                      }
                    ],
                    "assign": "PartitionResult"
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },
```

```
true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

"fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      }
                    ]
                  },

                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }
```

```
                ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [

 {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
```

```
                "argv": [

            {
                        "ref": "PartitionResult"
                    },
                    "supportsFIPS"
                ]
            },
            true
        ]
    }
],
"rules": [
    {
        "conditions": [],
        "endpoint": {

"url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
            "properties": {},
            "headers": {}
        },
        "type": "endpoint"
    }
],
"type": "tree"
},
{
    "conditions": [],
    "error": "FIPS is enabled but this partition does not support FIPS",
    "type": "error"

}
    ],
    "type": "tree"
},
{
    "conditions": [
        {
            "fn": "booleanEquals",
            "argv": [
                {
                    "ref": "UseDualStack"
                },
                true
            ]
        }
    ],
    "rules": [
```

```
                {

        "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        true,
                        {
                          "fn": "getAttr",
                          "argv": [
                            {
                              "ref": "PartitionResult"
                            },
                            "supportsDualStack"
                          ]

        }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

                ],
                    "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
                  "type": "error"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "endpoint": {
                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
```

```
                "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          }
        ],
        "type": "tree"
      },
      {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
      }
    ]
  },
  "smithy.rules#endpointTests": {
    "testCases": [
      {
        "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
        "expect":
{
          "endpoint": {
            "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": true,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
          }
        },
        "params": {
          "Region": "us-east-1",

    "UseFIPS": true,
          "UseDualStack": false
        }
```

```
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS":
true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
```

```
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
                {
                  "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint":
{
                      "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                     "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
                  },
                  "params": {
                    "Region": "us-iso-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false

}
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
```

```
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",

 "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
```

```
      "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
```

```
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
      }
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
    "type": "structure",
    "members": {
      "ProvisioningStatus": {
        "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
         "traits": {
           "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
        }
      },
      "HealthStatus": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
        "traits": {
          "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
        }
      },
      "Ipv4Address": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
        }
      }
    },
    "traits": {
      "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
    "type": "structure",
    "members": {
```

```
            "IdentityProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
               }
            },
            "ServerType": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
               "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>"
               }
            },
            "ServerEndpoint": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
               }
            },
            "LicenseServerEndpointId": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
               }
            },
            "LicenseServerEndpointArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits":
 {
                  "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the
RDS \n\t\t\tlicense server.</p>"
               }
            },
            "LicenseServerEndpointProvisioningStatus": {
               "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                  "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
```

```
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },

         "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
```

```
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
     "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
          "type": "structure",
          "members": {
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>",
                "smithy.api#required": {}
              }
            },
            "ServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "IdentityProviderSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
         "type": "structure",
         "members": {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n            <li>\n                <p>Product</p>\n            </li>\n
        <li>\n                <p>DirectoryId</p>\n            </li>\n        </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
```

```
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                "smithy.api#required": {}
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },

      {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/instance/ListInstances"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "InstanceSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
         "type": "structure",
         "members":
 {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
```

```
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/ListLicenseServerEndpoints"
          },

        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "LicenseServerEndpoints"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
```

```
                }
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoints": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
          "type":
```

```
 "operation",
        "input": {
           "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
           "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
           }
        ],
        "traits": {
           "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
           "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/user/ListProductSubscriptions"
           },
           "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",
              "items": "ProductUserSummaries"
           }
        }
     },
     "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
```

```
{
        "type": "structure",
        "members": {
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
             "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n
</li>\n          <li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
```

```
        "members": {
          "ProductUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

          }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
             }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
```

```
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
```

```
        "type": "structure",
        "members": {
          "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
 {
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
```

```
"<p>Metadata that describes the results of an identity provider operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
      "type": "string",
      "traits": {
        "smithy.api#length": {

         "min": 5,
          "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
      "type": "structure",
      "members": {
        "Endpoint": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
            "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
```

```
                "documentation": ""
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
          "type": "structure",
          "members": {
            "message": {

  "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Settings": {
          "type": "structure",
          "members": {
            "Subnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
                "smithy.api#length": {
                  "min": 1
                },
                "smithy.api#required": {}
              }
            },
            "SecurityGroupId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

             "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

      },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/StartProductSubscription"
        }

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
```

```
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {

 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
```

```
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
```

```
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StopProductSubscription"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
               }
            },
            "IdentityProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
               }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }

  }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
```

```
 "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "Tags": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
"<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
          "smithy.api#error": "client"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {

       "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
        "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}

      }
        },
        "TagKeys": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
          "traits": {
            "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
            "smithy.api#httpQuery": "tagKeys",
            "smithy.api#required": {}
          }
        }
```

```
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
            "smithy.api#http": {

     "code": 200,
                "method": "POST",
                "uri": "/identity-provider/UpdateIdentityProviderSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
```

```
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#required": {}
            }
          }
        },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A parameter is not valid.</p>",
        "smithy.api#error": "client"
      }
```

```
      }
   }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
```

```
CheckInLicenseOutput struct {
// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
```

```
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}
```

```
func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
```

Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their

Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf

of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step

ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization

OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.78 spec 0.21.0

1.78.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Juan Breinlinger

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF
 OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.79 x-net 0.42.0

1.79.1 Available under license :

Copyright 2009 The Go Authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE
 FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.80 github.com/aws/aws-sdk-go-v2/internal/ini 1.8.3

1.80.1 Available under license :

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
```

```
    // This member is required.
    CheckoutType types.CheckoutType

    // Unique, case-sensitive identifier that you provide to ensure the idempotency of
    // the request.
    //
    // This member is required.
    ClientToken *string

    // License entitlements.
    //
    // This member is required.
    Entitlements []types.EntitlementData

    // Key fingerprint identifying the license.
    //
    // This member is required.
    KeyFingerprint *string

    // Product SKU.
    //
    // This member is required.
    ProductSKU *string

    // License beneficiary.
    Beneficiary *string

    // Node ID.
    NodeId *string

    noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

    // Checkout type.
    CheckoutType types.CheckoutType

    // Allowed license entitlements.
    EntitlementsAllowed []types.EntitlementData

    // Date and time at which the license checkout expires.
    Expiration *string

    // Date and time at which the license checkout is issued.
    IssuedAt *string

    // Amazon Resource Name (ARN) of the checkout license.
```

```
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
```

```
 return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
 return err
 }
 if err = addRetry(stack, options); err != nil {
 return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err !=
 nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
```

```
  ClientRequestID
  ComputeContentLength
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  Signing
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  OperationDeserializer
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
```

```
        path: new-ref
        fetch-depth: 0
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
```

```
 params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
```

```
err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err
 != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
```

```
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DisassociateLicense",
 }
}
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
          }
        },
        "ActiveDirectoryType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
          "traits": {
```

```
                "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
          "type": "structure",
          "members": {
            "DomainName": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
              }
            },
            "DomainIpv4List": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active Directory.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 2
                }
              }
            },
            "DomainCredentialsProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
              "traits": {
                "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration.</p>"
              }
            },
            "DomainNetworkSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
```

```
\n\t\t\tuser administration in the Active Directory.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "SELF_MANAGED",
              "value": "SELF_MANAGED",
              "documentation": "SELF_MANAGED type of Active Directory"
            },
            {
              "name": "AWS_MANAGED",
              "value": "AWS_MANAGED",
              "documentation": "AWS_MANAGED type of Active Directory"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
{
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

        {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
                }
            },
```

```
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
```

```
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
         "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
```

```
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/DeregisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",

            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
```

```
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Directory":
{
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
             {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
```

```
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest":
 {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"

               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
               }
```

```
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
          "type": "structure",
          "members": {
            "Subnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                "smithy.api#length": {
                  "min": 1
                },
                "smithy.api#required": {}

          }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Filter": {
          "type": "structure",
          "members": {
            "Attribute": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
```

```
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
            }
          },
          "Value": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation":
"<p>Value of the filter.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
          "ActiveDirectoryIdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
            "traits": {

              "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {

        "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the identity provider.</p>",

      "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
          },
          "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
       }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
      "type": "structure",
      "members": {
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
            "smithy.api#required": {}
          }
        },
        "Products": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
          "traits":
{
            "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
            "smithy.api#required": {}
          }
        },
        "LastStatusCheckDate": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The date of the last status check.</p>"
          }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList": {

  "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {

        "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
```

```
            }

    },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
            "target": "smithy.api#String",
            "traits": {

        "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
```

```
    "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
        "smithy.api#error": "server",
         "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"

    },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
```

```
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
      },
      {

       "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
       }
  ],
  "traits": {
    "aws.api#service": {
      "sdkId": "License Manager User Subscriptions",
      "arnNamespace": "license-manager-user-subscriptions",
      "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
    },
    "aws.auth#sigv4": {
      "name": "license-manager-user-subscriptions"
    },
    "aws.protocols#restJson1": {},
    "smithy.api#cors": {
      "additionalAllowedHeaders": [
        "*",
        "content-type",
        "x-amz-content-sha256",
        "x-amz-user-agent",
        "x-amzn-platform-id",
        "x-amzn-trace-id",
        "content-length",
        "x-api-key",
```

```
        "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
                "Region": {
                    "builtIn":
 "AWS::Region",
                    "required": false,
                    "documentation": "The AWS region used to dispatch the request.",
                    "type": "String"
                },
                "UseDualStack": {
                    "builtIn": "AWS::UseDualStack",
                    "required": true,
                    "default": false,
                    "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                    "type": "Boolean"
                },
                "UseFIPS": {
                    "builtIn": "AWS::UseFIPS",
                    "required": true,
                    "default": false,
                    "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured
 endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                    "type": "Boolean"
                },
                "Endpoint": {
                    "builtIn": "SDK::Endpoint",
                    "required": false,
                    "documentation": "Override the endpoint used to send this request",
```

```
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
            ],

        "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [
                  {

"fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
```

```
                {
                  "conditions": [],
                  "endpoint": {
                    "url": {
                      "ref": "Endpoint"
                    },
                    "properties": {},

                "headers": {}
                    },
                    "type": "endpoint"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "aws.partition",
                      "argv":
[
                        {
                          "ref": "Region"
                        }
                      ],
                      "assign": "PartitionResult"
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            {
                              "ref": "UseFIPS"
```

```
                    },
                    true

            ]
                },
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseDualStack"
                    },
                    true
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",

               "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"
                              },
                              "supportsFIPS"
                            ]
                          }
                        ]
                    },

{
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }
```

```
                                    ]

                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],

                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {

                    "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
```

```
                                    "fn": "getAttr",
                                    "argv": [
                                        {

                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS is enabled but this partition does not support FIPS",
                    "type": "error"
                }

        ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
```

```
                "rules": [
                  {
                    "conditions": [

                {
                        "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"
                              },
                              "supportsDualStack"
                            ]
                          }

            ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }
                  ],
                   "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
                  "type": "error"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "endpoint": {
                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
```

```
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }
                  ],
                  "type": "tree"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "Invalid Configuration: Missing Region",
              "type": "error"
            }
          ]
        },
        "smithy.rules#endpointTests": {
          "testCases": [
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint":
{
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": true,

          "UseDualStack": false
                }
              },
```

```
                {
                  "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {

   "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                    }
                  },
                  "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": true,
                    "UseDualStack":
 true
                  }
                },
                {
                  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                    }
```

```
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url":
"https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack":
false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
```

```
                {
                  "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url":
"https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack":
true
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "error": "FIPS and DualStack are enabled, but this partition
does not support one or both"
                  },
                  "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },

      {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },

    "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
```

```
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",

"expect": {
      "endpoint": {
        "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
      }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "error": "DualStack is enabled but this partition does not support DualStack"
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,

  "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
```

```
      "expect": {
        "endpoint": {

          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint":
 "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration: Dualstack and custom endpoint are
 not supported"
      },
      "params": {
        "Region": "us-east-1",
```

```
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information about a Remote Desktop Services (RDS) license
 server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
```

```
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",
                "traits": {
                    "smithy.api#documentation":
 "<p>The <code>ServerEndpoint</code> resource contains the network \n\t\t\taddress of the RDS license server
endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
                }
            },
            "LicenseServerEndpointId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation":
 "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
                }
            },
            "LicenseServerEndpointProvisioningStatus": {
                "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
```

```
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },
          "CreationTime": {

        "target": "smithy.api#Timestamp",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {
        "type": "string",
        "traits":
 {
          "smithy.api#enum": [
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
```

```
                "name": "PROVISIONED",
                "value": "PROVISIONED",
                "documentation": ""
              },
              {
                "name": "DELETING",
                "value": "DELETING",
                "documentation": ""
              },
              {
                "name": "DELETION_FAILED",
                "value": "DELETION_FAILED",
                "documentation": ""
              },
              {
                 "name": "DELETED",
                "value": "DELETED",
                "documentation": ""
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "HEALTHY",
                "value": "HEALTHY",
                "documentation": ""
              },
              {
                "name": "UNHEALTHY",
                "value": "UNHEALTHY",
                "documentation": ""
              },
              {
                "name": "NOT_APPLICABLE",
                "value": "NOT_APPLICABLE",
                "documentation": ""
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList":
    {
          "type": "list",
          "member": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
          "type": "structure",
          "members": {
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>",
                "smithy.api#required": {}
              }
            },
            "ServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for your \n\t\t\tserver.</p>",

               "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
            },

         "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
    <ul>\n        <li>\n        <p>Product</p>\n        </li>\n        <li>\n        <p>DirectoryId</p>\n
  </li>\n      </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",
                "traits": {

        "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                    "smithy.api#required": {}
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
        "input": {

  "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {

            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
```

```
\n\tfrom a previously truncated response.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>Status</p>\n            </li>\n            <li>\n                <p>InstanceId</p>\n
        </li>\n        </ul>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
            "InstanceSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When
 this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token
\n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/ListLicenseServerEndpoints"
          },
          "smithy.api#paginated": {

          "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "LicenseServerEndpoints"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
```

```
                }
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits":
{
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>IdentityProviderArn</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoints": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
               "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
          "type": "operation",
```

```
        "input": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
             "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListProductSubscriptions"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "ProductUserSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest": {
        "type":
```

```
 "structure",
        "members": {
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>"
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {

              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n
</li>\n          <li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"

         }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
```

```
        "type": "structure",
        "members": {
          "ProductUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to
 retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

        }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{ResourceArn}"
```

```
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}
              }
            }
          },
          "traits": {

      "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
          },
          "errors": [
             {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits":
{
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                    "smithy.api#required":
{}
                }
            },
            "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline
 results:</p>\n        <ul>\n          <li>\n            <p>Status</p>\n          </li>\n          <li>\n
<p>Username</p>\n          </li>\n          <li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
             "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",

            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory
 that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
 user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
 reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
```

```
        "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider": {
        "type":
 "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
```

```
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
             "traits": {
               "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
               "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>",
               "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
               "smithy.api#documentation": "<p>The registered identity providers product related configuration
 \n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
               "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
               "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
```

```
        "smithy.api#required": {}
                }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",
            "smithy.api#error": "client",
            "smithy.api#httpError": 404
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider":
 {
          "type": "structure",
          "members": {
            "SecretId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                "smithy.api#length": {
                  "min": 1
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
```

```
        "type": "string",
        "traits": {
          "smithy.api#length": {
            "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
          "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
        "type": "union",
        "members": {
          "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource
 contains settings to configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
```

```
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>The request failed because a service quota is exceeded.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
            "Subnets": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
                "traits": {
                    "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
                    "smithy.api#length": {
                        "min": 1
                    },
                    "smithy.api#required": {}
                }
            },
            "SecurityGroupId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that allows inbound
 TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation
servers.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings
such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the
VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from
resources\n\t\t\tin the VPC.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
        "type": "operation",
```

```
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
         },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
           }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity
provider.</p>\n        <note>\n          <p>Your estimated bill for charges on the number of users and related costs
will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status)
in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/StartProductSubscription"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type":
 "structure",
        "members": {
          "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code>
| <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse":
{
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
```

```
                "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
          },

 "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],

    "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity provider.</p>",
            "smithy.api#http": {
              "code": 200,
```

```
            "method": "POST",
            "uri": "/user/StopProductSubscription"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An
object that specifies details for the identity provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>"
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The
domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
      "type": "structure",
      "members": {
        "ProductUserSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
          "traits": {
            "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StringList": {
      "type": "list",
       "member": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
```

```
      "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Adds tags to a resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{ResourceArn}"
            },

      "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
         "type": "structure",
         "members": {
            "ResourceArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "Tags": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The tags to apply to the specified resource.</p>",
                  "smithy.api#required": {}
               }
            }
```

```
        },
        "traits":
{
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }

     },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes
 tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
 to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "TagKeys": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
                "traits": {

  "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                    "smithy.api#httpQuery": "tagKeys",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
```

```
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },

 "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}

       }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the
 identity provider to update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {

 "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
        "type": "structure",
```

```
        "members": {
          "AddSubnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint
 for products that\n\t\t\trequire connectivity to activation servers.</p>",
              "smithy.api#required": {}
            }
          },
          "RemoveSubnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
            "traits": {
              "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688
communication between resources in\n\t\t\tyour VPC and the VPC endpoints for activation servers.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>Updates the registered identity providers product related configuration settings such as\n\t\t\tthe subnets to
provision VPC endpoints.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A parameter is not valid.</p>",
          "smithy.api#error": "client"
        }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32
```

```
 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
```

```
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
```

```
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil
 {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
```

```
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
```

```
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if
err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err
 = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack);
 err != nil {
  return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  Signing
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
```

```
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  OperationDeserializer
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
```

```
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
```

```
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
```

```
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
 {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckInLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
```

```
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 Signing
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 OperationDeserializer
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
```

```
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
```

```
err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata
 {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
```

```
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
```

```
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
GetLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  Signing
 Deserialize stack step
  AddRawResponseToMetadata
```

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
ListReceivedLicenses
Initialize stack step
spanInitializeStart
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

AWS SDK for Go
Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.
// Code generated by smithy-go-codegen DO NOT EDIT.

```
package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
```

```
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
AssociateLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  UserAgent
```

AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
```

```
    {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The type of name to filter by.</p>"
              }
            },
            "Values": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
              }
            },
            "Operator": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
              "traits": {
                "smithy.api#documentation": "<p>An operator for filtering results.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
          "type":
 "list",
          "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
          },
          "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
             },
            {
```

```
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

         "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
                }
            },
```

```
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
                }
            },
            "SubscriptionProviderStatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
               }
            },
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
         "type": "operation",
         "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
```

```
current status.</p>"
                }
            },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                 "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
            "AmiId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
                }
            },
            "InstanceID": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
                }
            },
            "InstanceType": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>The instance type of the resource.</p>"
                }
            },
            "AccountID": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the instance.</p>"
                }
            },
            "Region": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
        },
        "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
        },
        "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
        },
        "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
        },
        "SubscriptionName": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
            }
        },
        "OsVersion": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
            }
        },
        "SubscriptionProviderCreateTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
```

```
            },
            "SubscriptionProviderUpdateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
               }
            },
            "DualSubscription": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
               }
            },
            "RegisteredWithSubscriptionProvider": {
               "target": "smithy.api#String",
               "traits": {

     "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
         }
      },
```

```
"com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
  "type": "service",
  "version": "2018-05-10",
  "operations": [
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
     },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
    }
  ],
  "traits": {
    "aws.api#service": {
      "sdkId": "License Manager Linux Subscriptions",
       "arnNamespace": "license-manager-linux-subscriptions",
      "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
    },
    "aws.auth#sigv4": {
      "name": "license-manager-linux-subscriptions"
    },
    "aws.protocols#restJson1": {},
```

```
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
```

```
        }
      },
      "rules": [
        {
          "conditions": [
            {
              "fn": "isSet",
              "argv": [
                {
                  "ref": "Endpoint"
                }
              ]
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
                    true
                  ]
                }

    ],
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                  "type": "error"
                },
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            {
                              "ref": "UseDualStack"
                            },
                            true
                          ]

}
                      ],
                      "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
```

```
                "type": "error"
            },
            {
                "conditions": [],
                "endpoint": {
                    "url": {
                        "ref": "Endpoint"
                    },
                    "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"

    }
    ],
    "type": "tree"
},
{
    "conditions": [],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Region"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {

    "fn": "aws.partition",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ],
                            "assign": "PartitionResult"
                        }
                    ],
```

```
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {

                                "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            },
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseDualStack"
                                    },
                                    true
                                ]
                            }

],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            true,
                                            {
                                                "fn": "getAttr",
                                                "argv": [
                                                    {
                                                        "ref": "PartitionResult"

                },
                                                        "supportsFIPS"
                                                    ]
                                                }
                                            ]
                                        },
                                        {
                                            "fn": "booleanEquals",
                                            "argv": [
                                                true,
                                                {
```

```
                                        "fn": "getAttr",
                                        "argv": [

                                      {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                      ]
                                    }
                                  ]
                                }
                              ],
                              "rules": [
                                {
                                  "conditions": [],

      "rules": [
                                    {
                                      "conditions": [],
                                      "endpoint": {
                                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                      },
                                      "type": "endpoint"
                                    }
                                  ],

                          "type": "tree"
                                }
                              ],
                              "type": "tree"
                            },
                            {
                              "conditions": [],
                              "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                              "type": "error"
                            }
                          ],
                          "type": "tree"
                        },
                        {

            "conditions": [
                            {
                              "fn": "booleanEquals",
```

```
                "argv": [
                  {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

        "fn": "booleanEquals",
                    "argv": [
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      },
                      true

                  ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "rules": [
                      {
                        "conditions": [],
                        "endpoint": {
                          "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                          "headers": {}
                        },
                        "type": "endpoint"
                      }
                    ],
                    "type": "tree"
                  }
                ],
```

```
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS is enabled
but this partition does not support FIPS",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true

        ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {

                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }
                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "rules": [
```

```
        {
                                                "conditions": [],
                                                "endpoint": {
                                                   "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                   "properties": {},
                                                   "headers": {}
                                                },
                                                "type": "endpoint"
                                             }
                                          ],
                                          "type": "tree"

                                    }
                                       ],
                                       "type": "tree"
                                    },
                                    {
                                       "conditions": [],
                                       "error": "DualStack is enabled but this partition does not support DualStack",
                                       "type": "error"
                                    }
                                 ],
                                 "type": "tree"
                              },
                              {
                                 "conditions": [],
                                 "rules": [
                                     {
                                       "conditions": [],
                                       "endpoint": {
                                          "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                          "properties": {},
                                          "headers": {}
                                       },
                                       "type": "endpoint"
                                    }
                                 ],
                                 "type": "tree"
                              }
                           ],
                           "type": "tree"
                        }
                     ],
                     "type": "tree"
                  },
```

```
            {
              "conditions": [],
              "error": "Invalid Configuration: Missing Region",
              "type": "error"
            }
          ],
          "type": "tree"
        }
      ]
    },
    "smithy.rules#endpointTests": {
      "testCases": [
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

      }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {

       "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
```

```
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
                }

    },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": true,
                "UseDualStack": false
            }
        },
        {
```

```
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }

      },
      "params": {
```

```
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

        "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
```

```
            "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
          }
        },
        "params": {
          "Region": "us-iso-east-1",
          "UseFIPS": true,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
        "expect": {
          "error": "DualStack is enabled but this partition does not support DualStack"
        },
        "params": {
          "Region": "us-iso-east-1",
          "UseFIPS": false,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
          }
        },
        "params": {
          "Region": "us-iso-east-1",
          "UseFIPS":
false,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
        "expect": {
          "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
        },
        "params": {
          "Region": "us-isob-east-1",
          "UseFIPS": true,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

     "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

},
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
```

```
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }
          },
          "params": {
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {

          "documentation": "For custom endpoint with fips enabled and dualstack disabled",
          "expect": {
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with fips disabled and dualstack enabled",
          "expect": {
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
          },
          "params": {

 "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "Missing region",
          "expect": {
            "error": "Invalid Configuration: Missing Region"
          }
```

```
                }
            ],
            "version": "1.0"
        }
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
    "type": "string",
    "traits": {
        "smithy.api#enum": [
            {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

 },
            {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
        ]
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
    "type": "structure",
    "members": {
        "SourceRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
            }
        },
        "OrganizationIntegration": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
            "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
    }
},
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },

 {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListLinuxSubscriptionInstances"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "Instances"
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
      "type": "structure",
      "members": {
        "Filters": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the
```

following values for the <code>Name</code> key \n \tto streamline results: \n \n \n \n <code>AccountID</code>\n \n \n \n \n <code>AmiID</code>\n \n \n \n \n <code>DualSubscription</code>\n \n \n \n \n <code>InstanceID</code>\n \n \n \n \n <code>InstanceType</code>\n \n \n \n \n <code>ProductCode</code>\n \n \n \n \n <code>Region</code>\n \n \n \n \n <code>Status</code>\n \n \n \n \n <code>UsageOperation</code>\n \n \n \n For each filter, you can use one of the following <code>Operator</code>
values to \n \t\tdefine the behavior of the filter: \n \n \n \n <code>contains</code>\n \n \n \n \n <code>equals</code>\n \n \n \n \n <code>Notequal</code>\n \n \n "
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": " The maximum items to return in a request. "
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " A token to specify where to
start paginating. This \n\tis the nextToken from a previously truncated response. ",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
          "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
              "smithy.api#documentation": " An array that contains instance objects. "
            }

```
            },
            "NextToken": {

        "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

   "items": "Subscriptions"
            }
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n      <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n      <p>The valid names for this filter are:</p>\n      <ul>\n        <li>\n          <p>\n            <code>Subscription</code>\n          </p>\n        </li>\n      </ul>\n      <p>The valid Operators for this filter are:</p>\n      <ul>\n        <li>\n          <p>\n            <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n            <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n            <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "Subscriptions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
            }
        },
        "NextToken": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
```

```
            "pageSize": "MaxResults",
            "items": "RegisteredSubscriptionProviders"
          }
        }

    },
     "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSources": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
            "traits": {
              "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }

  },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
          "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
            }
```

```
            },

           "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
         },
         "errors": [
            {

          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
            "smithy.api#http": {
               "method": "GET",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
         "type": "structure",
         "members": {
```

```
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                   "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
                   "smithy.api#httpLabel": {},
                   "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
         "type": "structure",
         "members": {
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
          }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "EQUAL",
                  "value": "Equal",
                  "documentation": "Equal operator"
               },
               {
                  "name": "NOT_EQUAL",
                  "value": "NotEqual",
                  "documentation": "Not equal operator"
               },
               {
                  "name": "CONTAINS",
                  "value": "Contains",
                  "documentation": "Contains operator"
               }
            ],
```

```
            "smithy.api#length": {
                "min": 1,
                "max": 20
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "Enabled",
                    "value": "Enabled",
                    "documentation": "Enabled OrganizationIntegration"
                },
                {
                    "name": "Disabled",
                    "value": "Disabled",
                    "documentation": "Disabled OrganizationIntegration"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
```

```
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
```

```
the offline token.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
                }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "InProgress",
                "value": "InProgress",
                "documentation": "InProgress status"
              },
              {
                "name": "Completed",
                "value": "Completed",
                "documentation": "Completed status"
              },
              {
                "name": "Successful",
                "value": "Successful",
                "documentation": "Successful status"
              },
              {
                "name": "Failed",
                "value": "Failed",
                "documentation": "Failed status"
              }
            ]
          }
        },

       "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
```

```
            }
          }
        },
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
          },
          "smithy.api#uniqueItems": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
          "Name":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the subscription.</p>"
            }
          },
          "Type": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
            }
          },
          "InstanceCount": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
            "traits": {
              "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
            }
          }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "ACTIVE",
                "value": "ACTIVE",
                "documentation": "ACTIVE status"
              },
              {
                "name": "INVALID",
                "value": "INVALID",
```

```
    "documentation": "INVALID status"
                },
                {
                    "name": "PENDING",
                    "value": "PENDING",
                    "documentation": "PENDING status"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{resourceArn}"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
        "type": "structure",
        "members":
{
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
```

```
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
          "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
```

```
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tagKeys": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
               "traits": {

              "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                  "smithy.api#httpQuery": "tagKeys",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
        },
        "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
             "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
            }
        },
        "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
                "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
            }
        },
        "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
            }

    },
        "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated data for Linux\n      subscriptions.</p>"
            }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
        "smithy.api#error": "client"
      }
    }
```

```
  }
}
ListLicenses
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  Signing
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  OperationDeserializer
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
CheckoutLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
```

OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
DeleteLicense
Initialize stack step
spanInitializeStart
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
OperationSerializer

Build stack step
ClientRequestID
ComputeContentLength
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
CreateLicense
Initialize stack step
spanInitializeStart
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd

```
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  Signing
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  OperationDeserializer
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
```

```
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
```

```
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err !=
 nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "AssociateLicense",
 }
}
```

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

                    Apache License
                Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including

the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or

Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the

origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier

```
    identification within third-party archives.

  Copyright [yyyy] [name of copyright owner]

  Licensed under the Apache License, Version 2.0 (the "License");
  you may not use this file except in compliance with the License.
  You may obtain a copy of the License at

      http://www.apache.org/licenses/LICENSE-2.0

   Unless required by applicable law or agreed to in writing, software
  distributed under the License is distributed on an "AS IS" BASIS,
  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
  See the License for the specific language governing permissions and
  limitations under the License.
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {
```

```
 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
  - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
```

```
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err !=
 nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
```

```
return &awsmiddleware.RegisterServiceMetadata{
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "ListReceivedLicenses",
}
}
```

```
{
  "smithy": "2.0",
  "metadata": {
     "suppressions": [
        {
           "id": "HttpMethodSemantics",
           "namespace": "*"
        },
        {
           "id": "HttpResponseCodeSemantics",
           "namespace": "*"
        },
        {
           "id": "PaginatedTrait",
           "namespace": "*"
        },
        {
           "id": "HttpHeaderTrait",
           "namespace": "*"
        },
        {
           "id": "HttpUriConflict",
           "namespace": "*"
        },
        {
           "id": "Service",
           "namespace": "*"
        }
     ]
  },
  "shapes": {
     "com.amazonaws.licensemanager#AWSLicenseManager": {
        "type": "service",
        "version": "2018-08-01",
        "operations": [
           {
              "target": "com.amazonaws.licensemanager#AcceptGrant"
           },

  {
              "target": "com.amazonaws.licensemanager#CheckInLicense"
           },
```

```
{
   "target": "com.amazonaws.licensemanager#CheckoutBorrowLicense"
},
{
   "target": "com.amazonaws.licensemanager#CheckoutLicense"
},
{
   "target": "com.amazonaws.licensemanager#CreateGrant"
},
{
   "target": "com.amazonaws.licensemanager#CreateGrantVersion"
},
{
   "target": "com.amazonaws.licensemanager#CreateLicense"
},
{
   "target": "com.amazonaws.licensemanager#CreateLicenseConfiguration"
},
{
   "target": "com.amazonaws.licensemanager#CreateLicenseConversionTaskForResource"
},
{
   "target": "com.amazonaws.licensemanager#CreateLicenseManagerReportGenerator"
 },
{
   "target": "com.amazonaws.licensemanager#CreateLicenseVersion"
},
{
   "target": "com.amazonaws.licensemanager#CreateToken"
},
{
   "target": "com.amazonaws.licensemanager#DeleteGrant"
},
{
   "target": "com.amazonaws.licensemanager#DeleteLicense"
},
{
   "target": "com.amazonaws.licensemanager#DeleteLicenseConfiguration"
},
{
   "target": "com.amazonaws.licensemanager#DeleteLicenseManagerReportGenerator"
},
{
   "target": "com.amazonaws.licensemanager#DeleteToken"
},
{
   "target": "com.amazonaws.licensemanager#ExtendLicenseConsumption"
```

```
},
    {
      "target": "com.amazonaws.licensemanager#GetAccessToken"
    },
    {
      "target": "com.amazonaws.licensemanager#GetGrant"
    },
    {
      "target": "com.amazonaws.licensemanager#GetLicense"
    },
    {
      "target": "com.amazonaws.licensemanager#GetLicenseConfiguration"
    },
    {
      "target": "com.amazonaws.licensemanager#GetLicenseConversionTask"
    },
    {
      "target": "com.amazonaws.licensemanager#GetLicenseManagerReportGenerator"
    },
    {
      "target": "com.amazonaws.licensemanager#GetLicenseUsage"
    },
    {
      "target": "com.amazonaws.licensemanager#GetServiceSettings"
    },
    {
      "target": "com.amazonaws.licensemanager#ListAssociationsForLicenseConfiguration"
     },
    {
      "target": "com.amazonaws.licensemanager#ListDistributedGrants"
    },
    {
      "target": "com.amazonaws.licensemanager#ListFailuresForLicenseConfigurationOperations"
    },
    {
      "target": "com.amazonaws.licensemanager#ListLicenseConfigurations"
    },
    {
      "target": "com.amazonaws.licensemanager#ListLicenseConversionTasks"
    },
    {
      "target": "com.amazonaws.licensemanager#ListLicenseManagerReportGenerators"
    },
    {
      "target": "com.amazonaws.licensemanager#ListLicenses"
    },
    {
      "target": "com.amazonaws.licensemanager#ListLicenseSpecificationsForResource"
```

```
},
{

  "target": "com.amazonaws.licensemanager#ListLicenseVersions"
},
{
   "target": "com.amazonaws.licensemanager#ListReceivedGrants"
},
{
   "target": "com.amazonaws.licensemanager#ListReceivedGrantsForOrganization"
},
{
   "target": "com.amazonaws.licensemanager#ListReceivedLicenses"
},
{
   "target": "com.amazonaws.licensemanager#ListReceivedLicensesForOrganization"
},
{
   "target": "com.amazonaws.licensemanager#ListResourceInventory"
},
{
   "target": "com.amazonaws.licensemanager#ListTagsForResource"
},
{
   "target": "com.amazonaws.licensemanager#ListTokens"
},
{
   "target": "com.amazonaws.licensemanager#ListUsageForLicenseConfiguration"
 },
{
   "target": "com.amazonaws.licensemanager#RejectGrant"
},
{
   "target": "com.amazonaws.licensemanager#TagResource"
},
{
   "target": "com.amazonaws.licensemanager#UntagResource"
},
{
   "target": "com.amazonaws.licensemanager#UpdateLicenseConfiguration"
},
{
   "target": "com.amazonaws.licensemanager#UpdateLicenseManagerReportGenerator"
},
{
   "target": "com.amazonaws.licensemanager#UpdateLicenseSpecificationsForResource"
},
{
```

```
            "target": "com.amazonaws.licensemanager#UpdateServiceSettings"
          }
        ],
        "traits": {
          "aws.api#service": {
            "sdkId": "License Manager",
            "arnNamespace": "license-manager",
            "cloudFormationName": "LicenseManager",
            "cloudTrailEventSource": "licensemanager.amazonaws.com",
            "endpointPrefix": "license-manager"
          },
          "aws.auth#sigv4": {
            "name": "license-manager"
          },
          "aws.protocols#awsJson1_1": {},
          "smithy.api#documentation": "<p>License Manager makes it easier to manage licenses from software vendors across multiple \n         Amazon Web Services accounts and on-premises servers.</p>",
          "smithy.api#title": "AWS License Manager",
          "smithy.api#xmlNamespace": {
            "uri": "https://license-manager.amazonaws.com/doc/2018_08_01"
          },
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region": {
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                "type": "Boolean"
              },
              "UseFIPS": {
                "builtIn": "AWS::UseFIPS",
                "required": true,
                "default": false,
                "documentation": "When true, send
 this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                "type": "Boolean"
              },
              "Endpoint": {
```

```
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]

              }
              ],
              "type": "tree",
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseFIPS"
                        },
                        true
                      ]
                    }
                  ],
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                  "type": "error"
                },
                {

    "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseDualStack"
                        },
                        true
                      ]
                    }
```

```
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "endpoint": {
              "url": {
                "ref": "Endpoint"
              },
              "properties": {},
              "headers": {}
            },
            "type": "endpoint"
          }
        ]
      },
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Region"
              }
            ]
          }
        ],
        "type": "tree",
        "rules": [
          {
            "conditions": [
              {
                "fn": "aws.partition",
                "argv": [
                  {
                    "ref": "Region"
                  }
                ],
                "assign": "PartitionResult"
              }
            ],
            "type": "tree",
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
```

```
                "argv": [
                  {
                    "ref":
"UseFIPS"
                  },
                  true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "type": "tree",
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]

                      }
                    ]
                  },
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
```

```
    "supportsDualStack"
                                        ]
                                      }
                                    ]
                                  }
                                ],
                                "type": "tree",
                                "rules": [
                                  {
                                    "conditions": [],
                                    "endpoint": {
                                      "url": "https://license-manager-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                      "properties": {},
                                      "headers": {}

                                },
                                    "type": "endpoint"
                                  }
                                ]
                              },
                              {
                                "conditions": [],
                                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                                "type": "error"
                              }
                            ]
                          },
                          {
                            "conditions": [
                              {
                                "fn": "booleanEquals",

                             "argv": [
                                    {
                                      "ref": "UseFIPS"
                                    },
                                    true
                                  ]
                              }
                            ],
                            "type": "tree",
                            "rules": [
                              {
                                "conditions": [
                                  {
```

```
                "fn": "booleanEquals",
                "argv": [
                  true,

            {
                    "fn": "getAttr",
                    "argv": [
                      {
                        "ref": "PartitionResult"
                      },
                      "supportsFIPS"
                    ]
                  }
                ]
              }
            ],
            "type": "tree",
            "rules": [

            {
                "conditions": [],
                "endpoint": {
                  "url": "https://license-manager-fips.{Region}.{PartitionResult#dnsSuffix}",
                  "properties": {},
                  "headers": {}
                },
                "type": "endpoint"
              }
            ]
          },
          {
            "conditions": [],
            "error": "FIPS is enabled but this
partition does not support FIPS",
            "type": "error"
          }
        ]
      },
      {
        "conditions": [
          {
            "fn": "booleanEquals",
            "argv": [
              {
                "ref": "UseDualStack"
              },
              true
            ]
```

```
            }
          ],
          "type": "tree",
           "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    true,
                    {
                      "fn": "getAttr",
                      "argv": [
                        {
                          "ref": "PartitionResult"
                        },

    "supportsDualStack"
                        ]
                      }
                    ]
                  }
                ],
                "type": "tree",
                "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-
manager.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}

          },
                    "type": "endpoint"
                  }
                ]
              },
              {
                "conditions": [],
                "error": "DualStack is enabled but this partition does not support DualStack",
                "type": "error"
              }
            ]
          },
          {
            "conditions": [],
            "endpoint": {
```

```
                            "url": "https://license-manager.{Region}.{PartitionResult#dnsSuffix}",
                             "properties": {},
                            "headers": {}
                          },
                          "type": "endpoint"
                        }
                      ]
                    }
                  ]
                },
                {
                  "conditions": [],
                  "error": "Invalid Configuration: Missing Region",
                  "type": "error"
                }
              ]
            },
            "smithy.rules#endpointTests": {
              "testCases": [
                {
                  "documentation": "For region af-south-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint":
{
                      "url": "https://license-manager.af-south-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "af-south-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region ap-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager.ap-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "ap-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                   }
                },
                {
                  "documentation": "For region ap-northeast-1 with FIPS disabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager.ap-northeast-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "ap-northeast-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region ap-northeast-2 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager.ap-northeast-2.amazonaws.com"
         }
      },
      "params": {
        "Region": "ap-northeast-2",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region ap-northeast-3 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager.ap-northeast-3.amazonaws.com"
        }
      },
      "params": {
        "Region": "ap-northeast-3",
        "UseFIPS": false,
        "UseDualStack": false
      }

  },
    {
      "documentation": "For region ap-south-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager.ap-south-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "ap-south-1",
        "UseFIPS": false,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region ap-southeast-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager.ap-southeast-1.amazonaws.com"

}
          },
          "params": {
            "Region": "ap-southeast-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region ap-southeast-2 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager.ap-southeast-2.amazonaws.com"
            }
          },
          "params": {
            "Region": "ap-southeast-2",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

"documentation": "For region ap-southeast-3 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager.ap-southeast-3.amazonaws.com"
            }
          },
          "params": {
            "Region": "ap-southeast-3",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region ca-central-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager.ca-central-1.amazonaws.com"
              }
            },

           "params": {
              "Region": "ca-central-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region eu-central-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager.eu-central-1.amazonaws.com"
              }
            },
            "params": {
              "Region": "eu-central-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region eu-north-1 with FIPS
disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager.eu-north-1.amazonaws.com"
              }
            },
            "params": {
              "Region": "eu-north-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region eu-south-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager.eu-south-1.amazonaws.com"
              }
            },
            "params": {
              "Region":
"eu-south-1",
              "UseFIPS": false,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region eu-west-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager.eu-west-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "eu-west-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region eu-west-2 with FIPS disabled and DualStack disabled",
          "expect": {

          "endpoint": {
              "url": "https://license-manager.eu-west-2.amazonaws.com"
            }
          },
          "params": {
            "Region": "eu-west-2",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region eu-west-3 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager.eu-west-3.amazonaws.com"
            }
          },
          "params": {
            "Region": "eu-west-3",
            "UseFIPS": false,

    "UseDualStack": false
          }
        },
        {
          "documentation": "For region me-south-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
```

```
            "url": "https://license-manager.me-south-1.amazonaws.com"
          }
        },
        "params": {
          "Region": "me-south-1",
          "UseFIPS": false,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region sa-east-1 with FIPS disabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager.sa-east-1.amazonaws.com"
           }
        },
        "params": {
          "Region": "sa-east-1",
          "UseFIPS": false,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager.us-east-1.amazonaws.com"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": false
        }

  },
      {
        "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-fips.us-east-1.amazonaws.com"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": true,
          "UseDualStack": false
        }
```

```
    },
    {
      "documentation": "For region us-east-2 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager.us-east-2.amazonaws.com"
        }

     },
      "params": {
        "Region": "us-east-2",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-east-2 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-fips.us-east-2.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-2",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region
us-west-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager.us-west-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-west-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-west-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-fips.us-west-1.amazonaws.com"
        }
```

```
        },
        "params": {

    "Region": "us-west-1",
          "UseFIPS": true,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region us-west-2 with FIPS disabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager.us-west-2.amazonaws.com"
          }
        },
        "params": {
          "Region": "us-west-2",
          "UseFIPS": false,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region us-west-2 with FIPS enabled and DualStack disabled",

"expect": {
          "endpoint": {
            "url": "https://license-manager-fips.us-west-2.amazonaws.com"
          }
        },
        "params": {
          "Region": "us-west-2",
          "UseFIPS": true,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-fips.us-east-1.api.aws"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": true,

          "UseDualStack": true
        }
```

```
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url":
"https://license-manager.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-northwest-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager.cn-northwest-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-northwest-1",
            "UseFIPS": false,
            "UseDualStack": false

    }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-fips.cn-north-1.api.amazonwebservices.com.cn"
            }
```

```
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-fips.cn-north-1.amazonaws.com.cn"
         }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager.cn-north-1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },

  {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
```

```
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-fips.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-west-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager.us-gov-west-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-west-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation":
"For region us-gov-west-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-fips.us-gov-west-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-west-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-fips.us-gov-east-1.api.aws"
        }
      },
```

```
    "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager.us-gov-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager.us-iso-east-1.c2s.ic.gov"
                    }
                },
                "params": {
                    "Region": "us-iso-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                "expect": {
                    "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                },
                "params": {
                    "Region": "us-iso-east-1",
                    "UseFIPS": true,
                     "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
```

```
                "url": "https://license-manager-fips.us-iso-east-1.c2s.ic.gov"
              }
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "error": "DualStack is enabled
but this partition does not support DualStack"
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager.us-isob-east-1.sc2s.sgov.gov"
              }
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },

        {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
```

```
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-fips.us-isob-east-1.sc2s.sgov.gov"
                    }
                },

            "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "error": "DualStack is enabled but this partition does not support DualStack"
                },
                "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",

        "expect": {
                    "endpoint": {
                        "url": "https://example.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://example.com"
                    }
                },
                "params": {
                    "UseFIPS": false,
```

```
        "UseDualStack": false,
                        "Endpoint": "https://example.com"
                    }
                },
                {
                    "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                    "expect": {
                        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                    },
                    "params": {
                        "Region": "us-east-1",
                        "UseFIPS": true,
                        "UseDualStack": false,
                        "Endpoint": "https://example.com"
                    }
                },
                {
                    "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                    "expect": {
                        "error":
"Invalid Configuration: Dualstack and custom endpoint are not supported"
                    },
                    "params": {
                        "Region": "us-east-1",
                        "UseFIPS": false,
                        "UseDualStack": true,
                        "Endpoint": "https://example.com"
                    }
                },
                {
                    "documentation": "Missing region",
                    "expect": {
                        "error": "Invalid Configuration: Missing Region"
                    }
                }
            ],
            "version": "1.0"
        }
      }
    },
    "com.amazonaws.licensemanager#AcceptGrant": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#AcceptGrantRequest"

},
        "output": {
```

```
        "target": "com.amazonaws.licensemanager#AcceptGrantResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanager#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanager#AuthorizationException"
        },
        {
          "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
        },
        {
          "target": "com.amazonaws.licensemanager#RateLimitExceededException"
        },
        {
          "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
        },
        {
          "target": "com.amazonaws.licensemanager#ServerInternalException"
        },
        {
          "target": "com.amazonaws.licensemanager#ValidationException"

}
      ],
      "traits": {
        "smithy.api#documentation": "<p>Accepts the specified grant.</p>"
      }
    },
    "com.amazonaws.licensemanager#AcceptGrantRequest": {
      "type": "structure",
      "members": {
        "GrantArn": {
          "target": "com.amazonaws.licensemanager#Arn",
          "traits": {
            "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the grant.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanager#AcceptGrantResponse": {
      "type": "structure",
      "members": {
```

```
            "GrantArn": {
              "target": "com.amazonaws.licensemanager#Arn",
              "traits": {
                "smithy.api#documentation": "<p>Grant
ARN.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanager#GrantStatus",
              "traits": {
                "smithy.api#documentation": "<p>Grant status.</p>"
              }
            },
            "Version": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Grant version.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanager#AccessDeniedException": {
          "type": "structure",
          "members": {
            "Message": {
              "target": "com.amazonaws.licensemanager#Message"
            }
          },
          "traits": {
            "aws.protocols#awsQueryError": {

  "code": "ServiceAccessDenied",
              "httpResponseCode": 401
            },
            "smithy.api#documentation": "<p>Access to resource denied.</p>",
            "smithy.api#error": "client",
            "smithy.api#httpError": 401
          }
        },
        "com.amazonaws.licensemanager#ActivationOverrideBehavior": {
          "type": "enum",
          "members": {
            "DISTRIBUTED_GRANTS_ONLY": {
              "target": "smithy.api#Unit",
              "traits": {
```

```
                "smithy.api#enumValue": "DISTRIBUTED_GRANTS_ONLY"
              }
            },
            "ALL_GRANTS_PERMITTED_BY_ISSUER": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "ALL_GRANTS_PERMITTED_BY_ISSUER"
              }
            }
          }
        },
        "com.amazonaws.licensemanager#AllowedOperation": {

      "type": "enum",
          "members": {
            "CREATE_GRANT": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "CreateGrant"
              }
            },
            "CHECKOUT_LICENSE": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "CheckoutLicense"
              }
            },
            "CHECKOUT_BORROW_LICENSE": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "CheckoutBorrowLicense"
              }
            },
            "CHECK_IN_LICENSE": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "CheckInLicense"
              }
            },
            "EXTEND_CONSUMPTION_LICENSE":
    {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "ExtendConsumptionLicense"
              }
            },
            "LIST_PURCHASED_LICENSES": {
              "target": "smithy.api#Unit",
```

```
            "traits": {
                "smithy.api#enumValue": "ListPurchasedLicenses"
            }
        },
        "CREATE_TOKEN": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "CreateToken"
            }
        }
    }
},
"com.amazonaws.licensemanager#AllowedOperationList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanager#AllowedOperation"
    },
    "traits": {
        "smithy.api#length": {
            "min": 1,
            "max":
7
        }
    }
},
"com.amazonaws.licensemanager#Arn": {
    "type": "string",
    "traits": {
        "smithy.api#length": {
            "min": 0,
            "max": 2048
        },
        "smithy.api#pattern": "^arn:aws(-(cn|us-gov|iso-b|iso-c|iso-d))?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-
z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=,@.-]{0,1023}$"
    }
},
"com.amazonaws.licensemanager#ArnList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanager#Arn"
    }
},
"com.amazonaws.licensemanager#AuthorizationException": {
    "type": "structure",
    "members": {
        "Message": {
            "target": "com.amazonaws.licensemanager#Message"
        }
```

```
        },
        "traits": {
          "aws.protocols#awsQueryError":
{
            "code": "AuthorizationFailure",
            "httpResponseCode": 403
          },
          "smithy.api#documentation": "<p>The Amazon Web Services user account does not have permission to
perform the action. Check the IAM\n        policy associated with this account.</p>",
          "smithy.api#error": "client",
          "smithy.api#httpError": 403
        }
      },
      "com.amazonaws.licensemanager#AutomatedDiscoveryInformation": {
        "type": "structure",
        "members": {
          "LastRunTime": {
            "target": "com.amazonaws.licensemanager#DateTime",
            "traits": {
              "smithy.api#documentation": "<p>Time that automated discovery last ran.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes automated discovery.</p>"
        }
      },

    "com.amazonaws.licensemanager#Boolean": {
        "type": "boolean",
        "traits": {
          "smithy.api#default": false
        }
      },
      "com.amazonaws.licensemanager#BorrowConfiguration": {
        "type": "structure",
        "members": {
          "AllowEarlyCheckIn": {
            "target": "com.amazonaws.licensemanager#BoxBoolean",
            "traits": {
              "smithy.api#documentation": "<p>Indicates whether early check-ins are allowed.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxTimeToLiveInMinutes": {
            "target": "com.amazonaws.licensemanager#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>Maximum time for the borrow configuration, in minutes.</p>",
```

```
                "smithy.api#required": {}
            }
        }

},
    "traits": {
        "smithy.api#documentation": "<p>Details about a borrow configuration.</p>"
    }
},
"com.amazonaws.licensemanager#BoxBoolean": {
    "type": "boolean"
},
"com.amazonaws.licensemanager#BoxInteger": {
    "type": "integer"
},
"com.amazonaws.licensemanager#BoxLong": {
    "type": "long"
},
"com.amazonaws.licensemanager#CheckInLicense": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanager#CheckInLicenseRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanager#CheckInLicenseResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanager#AuthorizationException"

 },
        {
            "target": "com.amazonaws.licensemanager#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
        },
        {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
        },
        {
            "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanager#ServerInternalException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Checks in the specified license. Check in a license when it is no longer
in use.</p>"
        }
    },
    "com.amazonaws.licensemanager#CheckInLicenseRequest":
{
        "type": "structure",
        "members": {
            "LicenseConsumptionToken": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>License consumption token.</p>",
                    "smithy.api#required": {}
                }
            },
            "Beneficiary": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>License beneficiary.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#CheckInLicenseResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanager#CheckoutBorrowLicense":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#CheckoutBorrowLicenseRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanager#CheckoutBorrowLicenseResponse"
        },
```

```
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#EntitlementNotAllowedException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#NoEntitlementsAllowedException"
            },
            {
                "target":
"com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#RedirectException"
            },
            {
                "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#UnsupportedDigitalSignatureMethodException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Checks out the specified license for offline use.</p>"
        }
    },
    "com.amazonaws.licensemanager#CheckoutBorrowLicenseRequest": {
        "type": "structure",
        "members":
{
            "LicenseArn": {
                "target": "com.amazonaws.licensemanager#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license. The license must
```

use the borrow consumption configuration. ",
"smithy.api#required": {}
}
},
"Entitlements": {
"target": "com.amazonaws.licensemanager#EntitlementDataList",
"traits": {
"smithy.api#documentation": " License entitlements. Partial checkouts are not supported. ",
"smithy.api#required": {}
}
},
"DigitalSignatureMethod": {
"target": "com.amazonaws.licensemanager#DigitalSignatureMethod",
"traits": {
"smithy.api#documentation": " Digital signature method. The possible
value is JSON Web Signature (JWS) algorithm PS384.\n For more information, see <a
href=\"https://tools.ietf.org/html/rfc7518#section-3.5\">RFC 7518 Digital Signature with RSASSA-PSS. ",
"smithy.api#required": {}
}
},
"NodeId": {
"target": "com.amazonaws.licensemanager#String",
"traits": {
"smithy.api#documentation": " Node ID. "
}
},
"CheckoutMetadata": {
"target": "com.amazonaws.licensemanager#MetadataList",
"traits": {
"smithy.api#documentation": " Information about constraints. "
}
},
"ClientToken": {
"target": "com.amazonaws.licensemanager#ClientToken",
"traits": {
"smithy.api#documentation":
" Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. ",
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanager#CheckoutBorrowLicenseResponse": {
"type": "structure",
"members": {

```
            "LicenseArn": {
               "target": "com.amazonaws.licensemanager#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license.</p>"
               }
            },
            "LicenseConsumptionToken": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>License consumption token.</p>"
               }
            },
            "EntitlementsAllowed":
{
               "target": "com.amazonaws.licensemanager#EntitlementDataList",
               "traits": {
                  "smithy.api#documentation": "<p>Allowed license entitlements.</p>"
               }
            },
            "NodeId": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Node ID.</p>"
               }
            },
            "SignedToken": {
               "target": "com.amazonaws.licensemanager#SignedToken",
               "traits": {
                  "smithy.api#documentation": "<p>Signed token.</p>"
               }
            },
            "IssuedAt": {
               "target": "com.amazonaws.licensemanager#ISO8601DateTime",
               "traits": {
                  "smithy.api#documentation": "<p>Date and time at which the license checkout
is issued.</p>"
               }
            },
            "Expiration": {
               "target": "com.amazonaws.licensemanager#ISO8601DateTime",
               "traits": {
                  "smithy.api#documentation": "<p>Date and time at which the license checkout expires.</p>"
               }
            },
            "CheckoutMetadata": {
               "target": "com.amazonaws.licensemanager#MetadataList",
               "traits": {
                  "smithy.api#documentation": "<p>Information about constraints.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#CheckoutLicense": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanager#CheckoutLicenseRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanager#CheckoutLicenseResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
          },
          {
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
          },
          {
            "target": "com.amazonaws.licensemanager#NoEntitlementsAllowedException"
          },
          {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
          },
          {
            "target": "com.amazonaws.licensemanager#RedirectException"
          },
          {
            "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
          },
          {
            "target":
"com.amazonaws.licensemanager#ServerInternalException"
          },
          {
            "target": "com.amazonaws.licensemanager#UnsupportedDigitalSignatureMethodException"
          },
          {
            "target": "com.amazonaws.licensemanager#ValidationException"
          }
        ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Checks out the specified license.</p>\n        <note>\n        <p>If the account that created the license is the same that is performing the check out, you must\n        specify the account as the beneficiary.</p>\n        </note>"
        }
    },
    "com.amazonaws.licensemanager#CheckoutLicenseRequest": {
        "type": "structure",
        "members": {
            "ProductSKU": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Product SKU.</p>",
                    "smithy.api#required": {}
                }
            },
            "CheckoutType": {
                "target": "com.amazonaws.licensemanager#CheckoutType",
                "traits": {
                    "smithy.api#documentation": "<p>Checkout type.</p>",
                    "smithy.api#required": {}
                }
            },
            "KeyFingerprint": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Key fingerprint identifying the license.</p>",
                    "smithy.api#required": {}
                }
            },
            "Entitlements": {
                "target": "com.amazonaws.licensemanager#EntitlementDataList",
                "traits": {
                    "smithy.api#documentation": "<p>License entitlements.</p>",

    "smithy.api#required": {}
                }
            },
            "ClientToken": {
                "target": "com.amazonaws.licensemanager#ClientToken",
                "traits": {
                    "smithy.api#documentation": "<p>Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.</p>",
                    "smithy.api#required": {}
                }
            },
            "Beneficiary": {
```

```
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>License beneficiary.</p>"
            }
        },
        "NodeId": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Node ID.</p>"
            }
        }
    },
    "traits": {

   "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanager#CheckoutLicenseResponse": {
    "type": "structure",
    "members": {
        "CheckoutType": {
            "target": "com.amazonaws.licensemanager#CheckoutType",
            "traits": {
                "smithy.api#documentation": "<p>Checkout type.</p>"
            }
        },
        "LicenseConsumptionToken": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>License consumption token.</p>"
            }
        },
        "EntitlementsAllowed": {
            "target": "com.amazonaws.licensemanager#EntitlementDataList",
            "traits": {
                "smithy.api#documentation": "<p>Allowed license entitlements.</p>"
            }
        },
         "SignedToken": {
            "target": "com.amazonaws.licensemanager#SignedToken",
            "traits": {
                "smithy.api#documentation": "<p>Signed token.</p>"
            }
        },
        "NodeId": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Node ID.</p>"
```

```
            }
          },
          "IssuedAt": {
            "target": "com.amazonaws.licensemanager#ISO8601DateTime",
            "traits": {
              "smithy.api#documentation": "<p>Date and time at which the license checkout is issued.</p>"
            }
          },
          "Expiration": {
            "target": "com.amazonaws.licensemanager#ISO8601DateTime",
            "traits": {
              "smithy.api#documentation": "<p>Date and
time at which the license checkout expires.</p>"
            }
          },
          "LicenseArn": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the checkout license.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#CheckoutType": {
        "type": "enum",
        "members": {
          "PROVISIONAL": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "PROVISIONAL"
            }
          },
          "PERPETUAL": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "PERPETUAL"
            }
           }
        }
      },
      "com.amazonaws.licensemanager#ClientRequestToken": {
        "type": "string",
        "traits": {
          "smithy.api#length": {
            "min": 1,
```

```
            "max": 36
          }
        }
      },
      "com.amazonaws.licensemanager#ClientToken": {
        "type": "string",
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 2048
          },
          "smithy.api#pattern": "^\\S+$"
        }
      },
      "com.amazonaws.licensemanager#ConflictException": {
        "type": "structure",
        "members": {
          "Message": {
            "target": "com.amazonaws.licensemanager#Message"
          }
        },
        "traits": {
          "aws.protocols#awsQueryError": {
            "code": "ConflictException",
            "httpResponseCode":
409
          },
          "smithy.api#documentation": "<p>There was a conflict processing the request. Try your request
again.</p>",
          "smithy.api#error": "client",
          "smithy.api#httpError": 409
        }
      },
      "com.amazonaws.licensemanager#ConsumedLicenseSummary": {
        "type": "structure",
        "members": {
          "ResourceType": {
            "target": "com.amazonaws.licensemanager#ResourceType",
            "traits": {
              "smithy.api#documentation": "<p>Resource type of the resource consuming a license.</p>"
            }
          },
          "ConsumedLicenses": {
            "target": "com.amazonaws.licensemanager#BoxLong",
            "traits": {
              "smithy.api#documentation": "<p>Number of licenses consumed by the resource.</p>"
            }
          }
```

```
        },

"traits": {
            "smithy.api#documentation": "<p>Details about license consumption.</p>"
        }
    },
    "com.amazonaws.licensemanager#ConsumedLicenseSummaryList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanager#ConsumedLicenseSummary"
        }
    },
    "com.amazonaws.licensemanager#ConsumptionConfiguration": {
        "type": "structure",
        "members": {
            "RenewType": {
                "target": "com.amazonaws.licensemanager#RenewType",
                "traits": {
                    "smithy.api#documentation": "<p>Renewal frequency.</p>"
                }
            },
            "ProvisionalConfiguration": {
                "target": "com.amazonaws.licensemanager#ProvisionalConfiguration",
                "traits": {
                    "smithy.api#documentation": "<p>Details about a provisional configuration.</p>"
                 }
            },
            "BorrowConfiguration": {
                "target": "com.amazonaws.licensemanager#BorrowConfiguration",
                "traits": {
                    "smithy.api#documentation": "<p>Details about a borrow configuration.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about a consumption configuration.</p>"
        }
    },
    "com.amazonaws.licensemanager#CreateGrant": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#CreateGrantRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanager#CreateGrantResponse"
        },
        "errors": [
            {
```

```
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target":
 "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a grant for the specified license. A grant shares the use of
 license\n        entitlements with a specific Amazon Web Services account, an organization, or an\n
 organizational unit (OU). For more
  information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/granted-
 licenses.html\">Granted licenses in License Manager</a> in the <i>License Manager User Guide</i>.</p>"
        }
    },
    "com.amazonaws.licensemanager#CreateGrantRequest": {
        "type": "structure",
        "members": {
            "ClientToken": {
                "target": "com.amazonaws.licensemanager#ClientToken",
                "traits": {
                    "smithy.api#documentation": "<p>Unique, case-sensitive identifier that you provide to ensure the
 idempotency of the request.</p>",
                    "smithy.api#required": {}
                }
            },
            "GrantName": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Grant name.</p>",
                    "smithy.api#required": {}
```

```
    }
        },
        "LicenseArn": {
          "target": "com.amazonaws.licensemanager#Arn",
          "traits": {
            "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license.</p>",
            "smithy.api#required": {}
          }
        },
        "Principals": {
          "target": "com.amazonaws.licensemanager#PrincipalArnList",
          "traits": {
            "smithy.api#documentation": "<p>The grant principals. You can specify one of the following as an
Amazon Resource Name\n        (ARN):</p>\n        <ul>\n        <li>\n        <p>An Amazon Web Services
account, which includes only the account specified.</p>\n        </li>\n        </ul>\n        <ul>\n        <li>\n
    <p>An organizational unit (OU), which includes all accounts in the OU.</p>\n        </li>\n        </ul>\n
<ul>\n
        <li>\n        <p>An organization, which will include all accounts across your organization.</p>\n
</li>\n        </ul>",
            "smithy.api#required": {}
          }
        },
        "HomeRegion": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Home Region of the grant.</p>",
            "smithy.api#required": {}
          }
        },
        "AllowedOperations": {
          "target": "com.amazonaws.licensemanager#AllowedOperationList",
          "traits": {
            "smithy.api#documentation": "<p>Allowed operations for the grant.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },

    "com.amazonaws.licensemanager#CreateGrantResponse": {
      "type": "structure",
      "members": {
        "GrantArn": {
          "target": "com.amazonaws.licensemanager#Arn",
          "traits": {
```

```
                "smithy.api#documentation": "<p>Grant ARN.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanager#GrantStatus",
              "traits": {
                "smithy.api#documentation": "<p>Grant status.</p>"
              }
            },
            "Version": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Grant version.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanager#CreateGrantVersion":
{
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanager#CreateGrantVersionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanager#CreateGrantVersionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
              "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
              "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
              "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
              "target": "com.amazonaws.licensemanager#ServerInternalException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a new version of the specified grant. For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/granted-licenses.html\">Granted licenses in License Manager</a> in the <i>License Manager User Guide</i>.</p>"
        }
    },
    "com.amazonaws.licensemanager#CreateGrantVersionRequest": {
        "type": "structure",
        "members": {
            "ClientToken": {
                "target": "com.amazonaws.licensemanager#ClientToken",
                "traits": {
                    "smithy.api#documentation": "<p>Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.</p>",

  "smithy.api#required": {}
                }
            },
            "GrantArn": {
                "target": "com.amazonaws.licensemanager#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the grant.</p>",
                    "smithy.api#required": {}
                }
            },
            "GrantName": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Grant name.</p>"
                }
            },
            "AllowedOperations": {
                "target": "com.amazonaws.licensemanager#AllowedOperationList",
                "traits": {
                    "smithy.api#documentation": "<p>Allowed operations for the grant.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanager#GrantStatus",
                "traits": {
                    "smithy.api#documentation": "<p>Grant status.</p>"
                }
            },
```

```
            "StatusReason": {
              "target": "com.amazonaws.licensemanager#StatusReasonMessage",
              "traits": {
                "smithy.api#documentation": "<p>Grant status reason.</p>"
              }
            },
            "SourceVersion": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Current version of the grant.</p>"
              }
            },
            "Options": {
              "target": "com.amazonaws.licensemanager#Options",
              "traits": {
                "smithy.api#documentation": "<p>The options specified for the grant.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanager#CreateGrantVersionResponse": {
          "type": "structure",
          "members": {
            "GrantArn": {
              "target": "com.amazonaws.licensemanager#Arn",
              "traits": {
                "smithy.api#documentation": "<p>Grant ARN.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanager#GrantStatus",
              "traits": {
                "smithy.api#documentation": "<p>Grant status.</p>"
              }
            },
            "Version": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>New version of the grant.</p>"
              }
            }
          },
          "traits":
{
            "smithy.api#output": {}
```

```
    }
  },
  "com.amazonaws.licensemanager#CreateLicense": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanager#CreateLicenseRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanager#CreateLicenseResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanager#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanager#AuthorizationException"
      },
      {
        "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
      },
      {
        "target": "com.amazonaws.licensemanager#RateLimitExceededException"
      },
      {
        "target": "com.amazonaws.licensemanager#RedirectException"
       },
      {
        "target": "com.amazonaws.licensemanager#ServerInternalException"
      },
      {
        "target": "com.amazonaws.licensemanager#ValidationException"
      }
    ],
    "traits": {
      "smithy.api#documentation": "<p>Creates a license.</p>"
    }
  },
  "com.amazonaws.licensemanager#CreateLicenseConfiguration": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanager#CreateLicenseConfigurationRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanager#CreateLicenseConfigurationResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanager#AccessDeniedException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
               "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
               "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
               "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
               "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a license configuration.</p>\n         <p>A license configuration is an abstraction of a customer license agreement that can be\n         consumed and enforced by License Manager. Components include specifications for the license\n         type (licensing by instance, socket, CPU, or vCPU), allowed tenancy (shared tenancy, \n         Dedicated Instance, Dedicated Host, or  all of these), license affinity  to host (how long a \n         license must be associated with a host), and the number of licenses purchased and used.</p>"
         }
      },
      "com.amazonaws.licensemanager#CreateLicenseConfigurationRequest": {
         "type": "structure",
         "members": {
            "Name": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Name of the license configuration.</p>",
                  "smithy.api#required": {}
               }
            },
            "Description": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Description of the license configuration.</p>"
               }
            },
            "LicenseCountingType": {
               "target": "com.amazonaws.licensemanager#LicenseCountingType",
               "traits": {
                  "smithy.api#documentation": "<p>Dimension used to track the license inventory.</p>",
                  "smithy.api#required": {}
               }
```

```
        },
        "LicenseCount": {
          "target": "com.amazonaws.licensemanager#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>Number of licenses managed by the license configuration.</p>"
          }
        },
        "LicenseCountHardLimit": {
          "target": "com.amazonaws.licensemanager#BoxBoolean",
          "traits": {
            "smithy.api#documentation": "<p>Indicates whether hard or soft license enforcement is used.
Exceeding a hard limit\n        blocks the launch of new instances.</p>"
          }
        },
        "LicenseRules": {
          "target":
 "com.amazonaws.licensemanager#StringList",
          "traits": {
            "smithy.api#documentation": "<p>License rules. The syntax is #name=value (for example,
#allowedTenancy=EC2-DedicatedHost). The available rules \n        vary by dimension, as follows.</p>\n
<ul>\n          <li>\n            <p>\n              <code>Cores</code> dimension: <code>allowedTenancy</code> |\n
          <code>licenseAffinityToHost</code> |\n            <code>maximumCores</code> |
<code>minimumCores</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Instances</code> dimension: <code>allowedTenancy</code> | \n            <code>maximumCores</code> |
<code>minimumCores</code> |\n            <code>maximumSockets</code> | <code>minimumSockets</code> |\n
        <code>maximumVcpus</code> | <code>minimumVcpus</code>\n            </p>\n          </li>\n
<li>\n
  <p>\n              <code>Sockets</code> dimension: <code>allowedTenancy</code> | \n
<code>licenseAffinityToHost</code> |\n            <code>maximumSockets</code> |
<code>minimumSockets</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>vCPUs</code> dimension: <code>allowedTenancy</code> | \n
<code>honorVcpuOptimization</code> | \n            <code>maximumVcpus</code> |
<code>minimumVcpus</code>\n            </p>\n          </li>\n        </ul>\n        <p>The unit for
<code>licenseAffinityToHost</code> is days and the range is 1 to 180. The possible \n        values for
<code>allowedTenancy</code> are <code>EC2-Default</code>, <code>EC2-DedicatedHost</code>, and \n
<code>EC2-DedicatedInstance</code>. The possible values for <code>honorVcpuOptimization</code> are \n
<code>True</code> and <code>False</code>.</p>"
          }
        },

  "Tags": {
          "target": "com.amazonaws.licensemanager#TagList",
          "traits": {
            "smithy.api#documentation": "<p>Tags to add to the license configuration.</p>"
          }
        },
        "DisassociateWhenNotFound": {
          "target": "com.amazonaws.licensemanager#BoxBoolean",
```

```
            "traits": {
                "smithy.api#documentation": "<p>When true, disassociates a resource when software is
uninstalled.</p>"
            }
          },
          "ProductInformationList": {
            "target": "com.amazonaws.licensemanager#ProductInformationList",
            "traits": {
              "smithy.api#documentation": "<p>Product information.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanager#CreateLicenseConfigurationResponse":
{
        "type": "structure",
        "members": {
          "LicenseConfigurationArn": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license configuration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#CreateLicenseConversionTaskForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanager#CreateLicenseConversionTaskForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanager#CreateLicenseConversionTaskForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
           },
          {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
          },
          {
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
               "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
               "target": "com.amazonaws.licensemanager#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a new license conversion task.</p>"
         }
      },
      "com.amazonaws.licensemanager#CreateLicenseConversionTaskForResourceRequest": {
         "type": "structure",
         "members": {
            "ResourceArn": {

               "target": "com.amazonaws.licensemanager#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the resource you are converting
the license type for.</p>",
                  "smithy.api#required": {}
               }
            },
            "SourceLicenseContext": {
               "target": "com.amazonaws.licensemanager#LicenseConversionContext",
               "traits": {
                  "smithy.api#documentation": "<p>Information that identifies the license type you are converting
from. \n\n         For the structure of the source license, see <a href=\"https://docs.aws.amazon.com/license-
manager/latest/userguide/conversion-procedures.html#conversion-cli\">Convert a license type using the CLI </a> in
the <i>License Manager User Guide</i>.</p>",
                  "smithy.api#required": {}
               }
            },
            "DestinationLicenseContext":
{
               "target": "com.amazonaws.licensemanager#LicenseConversionContext",
               "traits": {
                  "smithy.api#documentation": "<p>Information that identifies the license type you are converting to.
For the structure of the destination license, see <a href=\"https://docs.aws.amazon.com/license-
manager/latest/userguide/conversion-procedures.html#conversion-cli\">Convert a license type using the CLI </a> in
the <i>License Manager User Guide</i>.</p>",
                  "smithy.api#required": {}
               }
            }
```

```
    },
    "traits": {
      "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanager#CreateLicenseConversionTaskForResourceResponse": {
    "type": "structure",
    "members": {
      "LicenseConversionTaskId": {
        "target": "com.amazonaws.licensemanager#LicenseConversionTaskId",

    "traits": {
          "smithy.api#documentation": "<p>The ID of the created license type conversion task.</p>"
        }
      }
    },
    "traits": {
      "smithy.api#output": {}
    }
  },
  "com.amazonaws.licensemanager#CreateLicenseManagerReportGenerator": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanager#CreateLicenseManagerReportGeneratorRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanager#CreateLicenseManagerReportGeneratorResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanager#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanager#AuthorizationException"
      },
      {
        "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
       },
      {
        "target": "com.amazonaws.licensemanager#RateLimitExceededException"
      },
      {
        "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
      },
      {
        "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
      },
      {
```

```
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a report generator.</p>"
        }
    },
    "com.amazonaws.licensemanager#CreateLicenseManagerReportGeneratorRequest": {
        "type": "structure",
        "members": {
            "ReportGeneratorName":
{
                "target": "com.amazonaws.licensemanager#ReportGeneratorName",
                "traits": {
                    "smithy.api#documentation": "<p>Name of the report generator.</p>",
                    "smithy.api#required": {}
                }
            },
            "Type": {
                "target": "com.amazonaws.licensemanager#ReportTypeList",
                "traits": {
                    "smithy.api#documentation": "<p>Type of reports to generate. The following report types an be
generated:</p>\n            <ul>\n            <li>\n                <p>License configuration report - Reports the number and
details of consumed licenses for a license configuration.</p>\n            </li>\n            <li>\n                <p>Resource
report - Reports the tracked licenses and resource consumption for a license configuration.</p>\n            </li>\n
</ul>",
                    "smithy.api#required": {}

        }
            },
            "ReportContext": {
                "target": "com.amazonaws.licensemanager#ReportContext",
                "traits": {
                    "smithy.api#documentation": "<p>Defines the type of license configuration the report generator
tracks.</p>",
                    "smithy.api#required": {}
                }
            },
            "ReportFrequency": {
                "target": "com.amazonaws.licensemanager#ReportFrequency",
                "traits": {
                    "smithy.api#documentation": "<p>Frequency by which reports are generated.  Reports can be
generated daily, monthly, or weekly.</p>",
                    "smithy.api#required": {}
                }
```

```
            },
            "ClientToken": {
               "target": "com.amazonaws.licensemanager#ClientRequestToken",
               "traits": {
                  "smithy.api#documentation": "<p>Unique,
 case-sensitive identifier that you provide to ensure the idempotency of the request.</p>",
                  "smithy.api#required": {}
               }
            },
            "Description": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Description of the report generator.</p>"
               }
            },
            "Tags": {
               "target": "com.amazonaws.licensemanager#TagList",
               "traits": {
                  "smithy.api#documentation": "<p>Tags to add to the report generator.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanager#CreateLicenseManagerReportGeneratorResponse": {
         "type": "structure",
         "members": {
            "LicenseManagerReportGeneratorArn":
 {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the new report
 generator.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanager#CreateLicenseRequest": {
         "type": "structure",
         "members": {
            "LicenseName": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
```

```
                "smithy.api#documentation": "<p>License name.</p>",
                "smithy.api#required": {}
            }
        },
        "ProductName": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Product
name.</p>",
                "smithy.api#required": {}
            }
        },
        "ProductSKU": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Product SKU.</p>",
                "smithy.api#required": {}
            }
        },
        "Issuer": {
            "target": "com.amazonaws.licensemanager#Issuer",
            "traits": {
                "smithy.api#documentation": "<p>License issuer.</p>",
                "smithy.api#required": {}
            }
        },
        "HomeRegion": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Home Region for the license.</p>",
                "smithy.api#required": {}

  }
        },
        "Validity": {
            "target": "com.amazonaws.licensemanager#DatetimeRange",
            "traits": {
                "smithy.api#documentation": "<p>Date and time range during which the license is valid, in ISO8601-
UTC format.</p>",
                "smithy.api#required": {}
            }
        },
        "Entitlements": {
            "target": "com.amazonaws.licensemanager#EntitlementList",
            "traits": {
                "smithy.api#documentation": "<p>License entitlements.</p>",
                "smithy.api#required": {}
            }
```

```
            },
            "Beneficiary": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>License beneficiary.</p>",
                "smithy.api#required": {}
              }
            },
            "ConsumptionConfiguration": {
              "target": "com.amazonaws.licensemanager#ConsumptionConfiguration",
              "traits": {
                "smithy.api#documentation": "<p>Configuration for consumption of the license. Choose a provisional configuration for workloads\n running with continuous connectivity. Choose a borrow configuration for workloads with offline\n usage.</p>",
                "smithy.api#required": {}
              }
            },
            "LicenseMetadata": {
              "target": "com.amazonaws.licensemanager#MetadataList",
              "traits": {
                "smithy.api#documentation": "<p>Information about the license.</p>"
              }
            },
            "ClientToken": {
              "target": "com.amazonaws.licensemanager#ClientToken",
              "traits": {
                "smithy.api#documentation":
 "<p>Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanager#CreateLicenseResponse": {
          "type": "structure",
          "members": {
            "LicenseArn": {
              "target": "com.amazonaws.licensemanager#Arn",
              "traits": {
                "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanager#LicenseStatus",
              "traits": {
```

```
            "smithy.api#documentation": "<p>License status.</p>"
          }
        },
        "Version": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>License version.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanager#CreateLicenseVersion": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanager#CreateLicenseVersionRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanager#CreateLicenseVersionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanager#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanager#AuthorizationException"
        },
        {
          "target": "com.amazonaws.licensemanager#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanager#RateLimitExceededException"
        },
        {
          "target": "com.amazonaws.licensemanager#RedirectException"
        },
        {
          "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanager#ServerInternalException"
        },
        {
          "target": "com.amazonaws.licensemanager#ValidationException"
        }
      ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Creates a new version of the specified license.</p>"
        }
    },
    "com.amazonaws.licensemanager#CreateLicenseVersionRequest": {
        "type": "structure",
        "members": {
            "LicenseArn": {
                "target":
"com.amazonaws.licensemanager#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseName": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>License name.</p>",
                    "smithy.api#required": {}
                }
            },
            "ProductName": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Product name.</p>",
                    "smithy.api#required": {}
                }
            },
            "Issuer": {
                "target": "com.amazonaws.licensemanager#Issuer",
                "traits":
{
                    "smithy.api#documentation": "<p>License issuer.</p>",
                    "smithy.api#required": {}
                }
            },
            "HomeRegion": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Home Region of the license.</p>",
                    "smithy.api#required": {}
                }
            },
            "Validity": {
                "target": "com.amazonaws.licensemanager#DatetimeRange",
                "traits": {
                    "smithy.api#documentation": "<p>Date and time range during which the license is valid, in ISO8601-
```

```
UTC format.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseMetadata": {
                "target": "com.amazonaws.licensemanager#MetadataList",
                "traits": {
                    "smithy.api#documentation": "<p>Information about the license.</p>"
                }
            },
            "Entitlements": {
                "target": "com.amazonaws.licensemanager#EntitlementList",
                "traits": {
                    "smithy.api#documentation": "<p>License entitlements.</p>",
                    "smithy.api#required": {}
                }
            },
            "ConsumptionConfiguration": {
                "target": "com.amazonaws.licensemanager#ConsumptionConfiguration",
                "traits": {
                    "smithy.api#documentation": "<p>Configuration for consumption of the license. Choose a provisional
configuration for workloads\n          running with continuous connectivity. Choose a borrow configuration for
workloads with offline\n          usage.</p>",
                    "smithy.api#required": {}
                }
            },

  "Status": {
                "target": "com.amazonaws.licensemanager#LicenseStatus",
                "traits": {
                    "smithy.api#documentation": "<p>License status.</p>",
                    "smithy.api#required": {}
                }
            },
            "ClientToken": {
                "target": "com.amazonaws.licensemanager#ClientToken",
                "traits": {
                    "smithy.api#documentation": "<p>Unique, case-sensitive identifier that you provide to ensure the
idempotency of the request.</p>",
                    "smithy.api#required": {}
                }
            },
            "SourceVersion": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Current version of the license.</p>"
                }
            }
```

```
        },
        "traits": {

"smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#CreateLicenseVersionResponse": {
        "type": "structure",
        "members": {
            "LicenseArn": {
                "target": "com.amazonaws.licensemanager#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>License ARN.</p>"
                }
            },
            "Version": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>New version of the license.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanager#LicenseStatus",
                "traits": {
                    "smithy.api#documentation": "<p>License status.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output":
{}
        }
    },
    "com.amazonaws.licensemanager#CreateToken": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#CreateTokenRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanager#CreateTokenResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
```

```
            {
              "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
              "target": "com.amazonaws.licensemanager#RedirectException"
            },
            {
              "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },

      {
              "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
              "target": "com.amazonaws.licensemanager#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Creates a long-lived token.</p>\n          <p>A refresh token is a JWT token used to get an access token. With an access token,\n          you can call AssumeRoleWithWebIdentity to get role credentials that you can use to \n          call License Manager to manage the specified license.</p>"
          }
        },
        "com.amazonaws.licensemanager#CreateTokenRequest": {
          "type": "structure",
          "members": {
            "LicenseArn": {
              "target": "com.amazonaws.licensemanager#Arn",
              "traits":
{
                "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license. The ARN is mapped to the aud claim of the\n          JWT token.</p>",
                "smithy.api#required": {}
              }
            },
            "RoleArns": {
              "target": "com.amazonaws.licensemanager#ArnList",
              "traits": {
                "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the IAM roles to embed in the token. \n          License Manager does not check whether the roles are in use.</p>"
              }
            },
            "ExpirationInDays": {
              "target": "com.amazonaws.licensemanager#Integer",
              "traits": {
```

```
                "smithy.api#documentation": "<p>Token expiration, in days, counted from token creation. The default is 365 days.</p>"
              }
            },
            "TokenProperties": {
              "target": "com.amazonaws.licensemanager#MaxSize3StringList",
              "traits": {
                "smithy.api#documentation": "<p>Data specified by the caller to be included in the JWT token. The data is mapped\n          to the amr claim of the JWT token.</p>"
              }
            },
            "ClientToken": {
              "target": "com.amazonaws.licensemanager#ClientToken",
              "traits": {
                "smithy.api#documentation": "<p>Idempotency token, valid for 10 minutes.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanager#CreateTokenResponse": {
          "type": "structure",
          "members": {
            "TokenId": {
              "target": "com.amazonaws.licensemanager#String",

              "traits": {
                "smithy.api#documentation": "<p>Token ID.</p>"
              }
            },
            "TokenType": {
              "target": "com.amazonaws.licensemanager#TokenType",
              "traits": {
                "smithy.api#documentation": "<p>Token type.</p>"
              }
            },
            "Token": {
              "target": "com.amazonaws.licensemanager#TokenString",
              "traits": {
                "smithy.api#documentation": "<p>Refresh token, encoded as a JWT token.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
```

```
    }
  },
  "com.amazonaws.licensemanager#DateTime": {
    "type": "timestamp"
  },
  "com.amazonaws.licensemanager#DatetimeRange": {
    "type": "structure",
    "members": {
      "Begin": {
        "target": "com.amazonaws.licensemanager#ISO8601DateTime",
        "traits": {
          "smithy.api#documentation": "<p>Start of the time range.</p>",
          "smithy.api#required": {}
        }
      },
      "End": {
        "target": "com.amazonaws.licensemanager#ISO8601DateTime",
        "traits": {
          "smithy.api#documentation": "<p>End of the time range.</p>"
        }
      }
    },
    "traits": {
      "smithy.api#documentation": "<p>Describes a time range, in ISO8601-UTC format.</p>"
    }
  },
  "com.amazonaws.licensemanager#DeleteGrant": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanager#DeleteGrantRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanager#DeleteGrantResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanager#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanager#AuthorizationException"
      },
      {
        "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
      },
      {
        "target": "com.amazonaws.licensemanager#RateLimitExceededException"
      },
      {
```

```
                "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes
the specified grant.</p>"
        }
    },
    "com.amazonaws.licensemanager#DeleteGrantRequest": {
        "type": "structure",
        "members": {
            "GrantArn": {
                "target": "com.amazonaws.licensemanager#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the grant.</p>",
                    "smithy.api#required": {}
                }
            },
            "StatusReason": {
                "target": "com.amazonaws.licensemanager#StatusReasonMessage",
                "traits": {
                    "smithy.api#documentation": "<p>The Status reason for the delete request.</p>"
                }
            },
            "Version": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Current version of the
grant.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#DeleteGrantResponse": {
        "type": "structure",
        "members": {
            "GrantArn": {
                "target": "com.amazonaws.licensemanager#Arn",
```

```
            "traits": {
              "smithy.api#documentation": "<p>Grant ARN.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanager#GrantStatus",
            "traits": {
              "smithy.api#documentation": "<p>Grant status.</p>"
            }
          },
          "Version": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation":
"<p>Grant version.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#DeleteLicense": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanager#DeleteLicenseRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanager#DeleteLicenseResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
          },
          {
            "target": "com.amazonaws.licensemanager#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"

},
          {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanager#RedirectException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes the specified license.</p>"
        }
    },
    "com.amazonaws.licensemanager#DeleteLicenseConfiguration": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#DeleteLicenseConfigurationRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanager#DeleteLicenseConfigurationResponse"
        },

    "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes the specified license configuration.</p>\n         <p>You cannot delete a license configuration that is in use.</p>"
        }
    },
    "com.amazonaws.licensemanager#DeleteLicenseConfigurationRequest": {
        "type": "structure",
        "members":
```

```
{
            "LicenseConfigurationArn": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>ID of the license configuration.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanager#DeleteLicenseConfigurationResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanager#DeleteLicenseManagerReportGenerator": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanager#DeleteLicenseManagerReportGeneratorRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanager#DeleteLicenseManagerReportGeneratorResponse"
          },
         "errors": [
            {
               "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
               "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
               "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
               "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
               "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanager#ServerInternalException"
          },
          {
            "target": "com.amazonaws.licensemanager#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deletes the specified report generator.</p>\n        <p>This action deletes the report generator, which stops it from generating future reports.\n        The action cannot be reversed. It has no effect on the previous reports from this generator.</p>"
        }
      },
      "com.amazonaws.licensemanager#DeleteLicenseManagerReportGeneratorRequest": {
        "type": "structure",
        "members": {
          "LicenseManagerReportGeneratorArn": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the report generator to be deleted.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {

 "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanager#DeleteLicenseManagerReportGeneratorResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#DeleteLicenseRequest": {
        "type": "structure",
        "members": {
          "LicenseArn": {
            "target": "com.amazonaws.licensemanager#Arn",
            "traits": {
              "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license.</p>",
              "smithy.api#required": {}
            }
          },
          "SourceVersion": {
            "target": "com.amazonaws.licensemanager#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>Current version of the license.</p>",
              "smithy.api#required":
{}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanager#DeleteLicenseResponse": {
        "type": "structure",
        "members": {
          "Status": {
            "target": "com.amazonaws.licensemanager#LicenseDeletionStatus",
            "traits": {
              "smithy.api#documentation": "<p>License status.</p>"
            }
          },
          "DeletionDate": {
            "target": "com.amazonaws.licensemanager#ISO8601DateTime",
            "traits": {
              "smithy.api#documentation": "<p>Date when the license is deleted.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#DeleteToken": {
        "type": "operation",
         "input": {
          "target": "com.amazonaws.licensemanager#DeleteTokenRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanager#DeleteTokenResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
          },
          {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanager#RedirectException"
            },
            {
               "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanager#ServerInternalException"
            },

      {
               "target": "com.amazonaws.licensemanager#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Deletes the specified token. Must be called in the license home
Region.</p>"
         }
      },
      "com.amazonaws.licensemanager#DeleteTokenRequest": {
         "type": "structure",
         "members": {
            "TokenId": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Token ID.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanager#DeleteTokenResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}

       }
      },
      "com.amazonaws.licensemanager#DigitalSignatureMethod": {
         "type": "enum",
         "members": {
            "JWT_PS384": {
               "target": "smithy.api#Unit",
```

```
            "traits": {
              "smithy.api#enumValue": "JWT_PS384"
            }
          }
        }
      },
      "com.amazonaws.licensemanager#Entitlement": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Entitlement name.</p>",
              "smithy.api#required": {}
            }
          },
          "Value": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Entitlement resource. Use only
if the unit is None.</p>"
            }
          },
          "MaxCount": {
            "target": "com.amazonaws.licensemanager#Long",
            "traits": {
              "smithy.api#documentation": "<p>Maximum entitlement count. Use if the unit is not None.</p>"
            }
          },
          "Overage": {
            "target": "com.amazonaws.licensemanager#BoxBoolean",
            "traits": {
              "smithy.api#documentation": "<p>Indicates whether overages are allowed.</p>"
            }
          },
          "Unit": {
            "target": "com.amazonaws.licensemanager#EntitlementUnit",
            "traits": {
              "smithy.api#documentation": "<p>Entitlement unit.</p>",
              "smithy.api#required": {}
            }
          },
          "AllowCheckIn": {
            "target":
"com.amazonaws.licensemanager#BoxBoolean",
            "traits": {
              "smithy.api#documentation": "<p>Indicates whether check-ins are allowed.</p>"
            }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes a resource entitled for use with a license.</p>"
        }
    },
    "com.amazonaws.licensemanager#EntitlementData": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Entitlement data name.</p>",
                    "smithy.api#required": {}
                }
            },
            "Value": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Entitlement
data value.</p>"
                }
            },
            "Unit": {
                "target": "com.amazonaws.licensemanager#EntitlementDataUnit",
                "traits": {
                    "smithy.api#documentation": "<p>Entitlement data unit.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Data associated with an entitlement resource.</p>"
        }
    },
    "com.amazonaws.licensemanager#EntitlementDataList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanager#EntitlementData"
        }
    },
    "com.amazonaws.licensemanager#EntitlementDataUnit": {
        "type": "enum",
        "members": {
            "COUNT": {
                "target": "smithy.api#Unit",
                "traits": {
```

```
"smithy.api#enumValue": "Count"
                }
            },
            "NONE": {
                "target": "smithy.api#Unit",
                "traits": {
                    "smithy.api#enumValue": "None"
                }
            },
            "SECONDS": {
                "target": "smithy.api#Unit",
                "traits": {
                    "smithy.api#enumValue": "Seconds"
                }
            },
            "MICROSECONDS": {
                "target": "smithy.api#Unit",
                "traits": {
                    "smithy.api#enumValue": "Microseconds"
                }
            },
            "MILLISECONDS": {
                "target": "smithy.api#Unit",
                "traits": {
                    "smithy.api#enumValue": "Milliseconds"
                }
            },
            "BYTES": {
                "target": "smithy.api#Unit",
                 "traits": {
                    "smithy.api#enumValue": "Bytes"
                }
            },
            "KILOBYTES": {
                "target": "smithy.api#Unit",
                "traits": {
                    "smithy.api#enumValue": "Kilobytes"
                }
            },
            "MEGABYTES": {
                "target": "smithy.api#Unit",
                "traits": {
                    "smithy.api#enumValue": "Megabytes"
                }
            },
            "GIGABYTES": {
                "target": "smithy.api#Unit",
                "traits": {
```

```
                "smithy.api#enumValue": "Gigabytes"
              }
            },
            "TERABYTES": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "Terabytes"
              }
            },
            "BITS":
{
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "Bits"
              }
            },
            "KILOBITS": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "Kilobits"
              }
            },
            "MEGABITS": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "Megabits"
              }
            },
            "GIGABITS": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "Gigabits"
              }
            },
            "TERABITS": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "Terabits"

    }
            },
            "PERCENT": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "Percent"
              }
            },
            "BYTES_PER_SECOND": {
```

```
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Bytes/Second"
            }
          },
          "KILOBYTES_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Kilobytes/Second"
            }
          },
          "MEGABYTES_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Megabytes/Second"
            }
          },
          "GIGABYTES_PER_SECOND": {
            "target": "smithy.api#Unit",
             "traits": {
              "smithy.api#enumValue": "Gigabytes/Second"
            }
          },
          "TERABYTES_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Terabytes/Second"
            }
          },
          "BITS_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Bits/Second"
            }
          },
          "KILOBITS_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Kilobits/Second"
            }
          },
          "MEGABITS_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue":
"Megabits/Second"
            }
          },
```

```
            "GIGABITS_PER_SECOND": {
                "target": "smithy.api#Unit",
                "traits": {
                    "smithy.api#enumValue": "Gigabits/Second"
                }
            },
            "TERABITS_PER_SECOND": {
                "target": "smithy.api#Unit",
                "traits": {
                    "smithy.api#enumValue": "Terabits/Second"
                }
            },
            "COUNT_PER_SECOND": {
                "target": "smithy.api#Unit",
                "traits": {
                    "smithy.api#enumValue": "Count/Second"
                }
            }
        }
    },
    "com.amazonaws.licensemanager#EntitlementList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanager#Entitlement"
        }
    },
    "com.amazonaws.licensemanager#EntitlementNotAllowedException":
{
        "type": "structure",
        "members": {
            "Message": {
                "target": "com.amazonaws.licensemanager#Message"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The entitlement is not allowed.</p>",
            "smithy.api#error": "client",
            "smithy.api#httpError": 400
        }
    },
    "com.amazonaws.licensemanager#EntitlementUnit": {
        "type": "enum",
        "members": {
            "COUNT": {
                "target": "smithy.api#Unit",
                "traits": {
                    "smithy.api#enumValue": "Count"
                }
```

```
        },
        "NONE": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "None"
            }
        },
        "SECONDS":
{
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "Seconds"
            }
        },
        "MICROSECONDS": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "Microseconds"
            }
        },
        "MILLISECONDS": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "Milliseconds"
            }
        },
        "BYTES": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "Bytes"
            }
        },
        "KILOBYTES": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "Kilobytes"
             }
        },
        "MEGABYTES": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "Megabytes"
            }
        },
        "GIGABYTES": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "Gigabytes"
```

```
    }
},
"TERABYTES": {
    "target": "smithy.api#Unit",
    "traits": {
        "smithy.api#enumValue": "Terabytes"
    }
},
"BITS": {
    "target": "smithy.api#Unit",
    "traits": {
        "smithy.api#enumValue": "Bits"
    }
},
"KILOBITS": {
    "target": "smithy.api#Unit",
    "traits": {

     "smithy.api#enumValue": "Kilobits"
    }
},
"MEGABITS": {
    "target": "smithy.api#Unit",
    "traits": {
        "smithy.api#enumValue": "Megabits"
    }
},
"GIGABITS": {
    "target": "smithy.api#Unit",
    "traits": {
        "smithy.api#enumValue": "Gigabits"
    }
},
"TERABITS": {
    "target": "smithy.api#Unit",
    "traits": {
        "smithy.api#enumValue": "Terabits"
    }
},
"PERCENT": {
    "target": "smithy.api#Unit",
    "traits": {
        "smithy.api#enumValue": "Percent"
    }
},
"BYTES_PER_SECOND": {
    "target":
```

```
"smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Bytes/Second"
            }
          },
          "KILOBYTES_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Kilobytes/Second"
            }
          },
          "MEGABYTES_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Megabytes/Second"
            }
          },
          "GIGABYTES_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Gigabytes/Second"
            }
          },
          "TERABYTES_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {

"smithy.api#enumValue": "Terabytes/Second"
            }
          },
          "BITS_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Bits/Second"
            }
          },
          "KILOBITS_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Kilobits/Second"
            }
          },
          "MEGABITS_PER_SECOND": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Megabits/Second"
            }
          },
```

```
        "GIGABITS_PER_SECOND": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "Gigabits/Second"
          }
        },

    "TERABITS_PER_SECOND": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "Terabits/Second"
          }
        },
        "COUNT_PER_SECOND": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "Count/Second"
          }
        }
      }
    },
    "com.amazonaws.licensemanager#EntitlementUsage": {
      "type": "structure",
      "members": {
        "Name": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Entitlement usage name.</p>",
            "smithy.api#required": {}
          }
        },
        "ConsumedValue": {
          "target": "com.amazonaws.licensemanager#String",

        "traits": {
            "smithy.api#documentation": "<p>Resource usage consumed.</p>",
            "smithy.api#required": {}
          }
        },
        "MaxCount": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Maximum entitlement usage count.</p>"
          }
        },
        "Unit": {
          "target": "com.amazonaws.licensemanager#EntitlementDataUnit",
          "traits": {
```

```
                "smithy.api#documentation": "<p>Entitlement usage unit.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Usage associated with an entitlement resource.</p>"
          }
        },
        "com.amazonaws.licensemanager#EntitlementUsageList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanager#EntitlementUsage"
          }
        },
        "com.amazonaws.licensemanager#ExtendLicenseConsumption": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanager#ExtendLicenseConsumptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanager#ExtendLicenseConsumptionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
              "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
              "target": "com.amazonaws.licensemanager#RateLimitExceededException"
             },
            {
              "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
              "target": "com.amazonaws.licensemanager#ValidationException"
            }
          ],
          "traits": {
```

```
            "smithy.api#documentation": "<p>Extends the expiration date for license consumption.</p>"
        }
    },
    "com.amazonaws.licensemanager#ExtendLicenseConsumptionRequest": {
        "type": "structure",
        "members": {
            "LicenseConsumptionToken": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>License consumption token.</p>",
                    "smithy.api#required": {}

     }
            },
            "DryRun": {
                "target": "com.amazonaws.licensemanager#Boolean",
                "traits": {
                    "smithy.api#default": false,
                    "smithy.api#documentation": "<p>Checks whether you have the required permissions for the action,
without actually making the request. Provides an error response if you do not have the required permissions.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#ExtendLicenseConsumptionResponse": {
        "type": "structure",
        "members": {
            "LicenseConsumptionToken": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>License consumption token.</p>"
                }
            },

            "Expiration": {
                "target": "com.amazonaws.licensemanager#ISO8601DateTime",
                "traits": {
                    "smithy.api#documentation": "<p>Date and time at which the license consumption expires.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
```

```
    "com.amazonaws.licensemanager#FailedDependencyException": {
      "type": "structure",
      "members": {
        "Message": {
          "target": "com.amazonaws.licensemanager#Message"
        },
        "ErrorCode": {
          "target": "com.amazonaws.licensemanager#String"
        }
      },
      "traits": {
        "aws.protocols#awsQueryError": {
          "code": "FailedDependency",
          "httpResponseCode": 424
        },
        "smithy.api#documentation":
"<p>A dependency required to run the API is missing.</p>",
        "smithy.api#error": "client",
        "smithy.api#httpError": 424
      }
    },
    "com.amazonaws.licensemanager#Filter": {
      "type": "structure",
      "members": {
        "Name": {
          "target": "com.amazonaws.licensemanager#FilterName",
          "traits": {
            "smithy.api#documentation": "<p>Name of the filter. Filter names are case-sensitive.</p>"
          }
        },
        "Values": {
          "target": "com.amazonaws.licensemanager#FilterValues",
          "traits": {
            "smithy.api#documentation": "<p>The value of the filter, which is case-sensitive. You can only
specify one value for the filter.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter
 name and value pair that is used to return more specific results from a\n        describe operation. Filters can be used
to match a set of resources by specific criteria,\n        such as tags, attributes, or IDs.</p>"
      }
    },
    "com.amazonaws.licensemanager#FilterLimitExceededException": {
      "type": "structure",
      "members": {
        "Message": {
```

```
            "target": "com.amazonaws.licensemanager#Message"
          }
        },
        "traits": {
          "aws.protocols#awsQueryError": {
            "code": "FilterLimitExceeded",
            "httpResponseCode": 400
          },
          "smithy.api#documentation": "<p>The request uses too many filters or too many filter values.</p>",
          "smithy.api#error": "client",
          "smithy.api#httpError": 400
        }
      },
      "com.amazonaws.licensemanager#FilterList": {
        "type": "list",
         "member": {
          "target": "com.amazonaws.licensemanager#Filter"
        }
      },
      "com.amazonaws.licensemanager#FilterName": {
        "type": "string"
      },
      "com.amazonaws.licensemanager#FilterValue": {
        "type": "string"
      },
      "com.amazonaws.licensemanager#FilterValues": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanager#FilterValue",
          "traits": {
            "smithy.api#xmlName": "item"
          }
        }
      },
      "com.amazonaws.licensemanager#Filters": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanager#Filter",
          "traits": {
            "smithy.api#xmlName": "item"
          }
        }
      },
      "com.amazonaws.licensemanager#GetAccessToken": {
        "type": "operation",
        "input": {
           "target": "com.amazonaws.licensemanager#GetAccessTokenRequest"
        },
```

```
        "output": {
          "target": "com.amazonaws.licensemanager#GetAccessTokenResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
          },
          {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
          },
          {
            "target": "com.amazonaws.licensemanager#ServerInternalException"
          },
          {
            "target": "com.amazonaws.licensemanager#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Gets a temporary access token to use with
AssumeRoleWithWebIdentity. Access
 tokens\n        are valid for one hour.</p>"
        }
      },
      "com.amazonaws.licensemanager#GetAccessTokenRequest": {
        "type": "structure",
        "members": {
          "Token": {
            "target": "com.amazonaws.licensemanager#TokenString",
            "traits": {
              "smithy.api#documentation": "<p>Refresh token, encoded as a JWT token.</p>",
              "smithy.api#required": {}
            }
          },
          "TokenProperties": {
            "target": "com.amazonaws.licensemanager#MaxSize3StringList",
            "traits": {
              "smithy.api#documentation": "<p>Token properties to validate against those present in the JWT
token.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
```

```
    "com.amazonaws.licensemanager#GetAccessTokenResponse":
{
        "type": "structure",
        "members": {
            "AccessToken": {
                "target": "com.amazonaws.licensemanager#TokenString",
                "traits": {
                    "smithy.api#documentation": "<p>Temporary access token.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanager#GetGrant": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#GetGrantRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanager#GetGrantResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"

      },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
```

```
        "smithy.api#documentation": "<p>Gets detailed information about the specified grant.</p>"
    }
},
"com.amazonaws.licensemanager#GetGrantRequest": {
    "type": "structure",
    "members": {
        "GrantArn": {
            "target": "com.amazonaws.licensemanager#Arn",
             "traits": {
                "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the grant.</p>",
                "smithy.api#required": {}
            }
        },
        "Version": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Grant version.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanager#GetGrantResponse": {
    "type": "structure",
    "members": {
        "Grant": {
            "target": "com.amazonaws.licensemanager#Grant",
            "traits": {
                "smithy.api#documentation": "<p>Grant details.</p>"
            }
        }
    },
    "traits": {

"smithy.api#output": {}
    }
},
"com.amazonaws.licensemanager#GetLicense": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanager#GetLicenseRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanager#GetLicenseResponse"
    },
    "errors": [
```

```
        {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
        },
        {
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
        },
        {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
        },
        {
            "target": "com.amazonaws.licensemanager#ServerInternalException"

    },
        {
            "target": "com.amazonaws.licensemanager#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Gets detailed information about the specified license.</p>"
    }
},
"com.amazonaws.licensemanager#GetLicenseConfiguration": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanager#GetLicenseConfigurationRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanager#GetLicenseConfigurationResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
        },
        {
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
        },
        {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
        },
        {
            "target": "com.amazonaws.licensemanager#ServerInternalException"
        }
```

```
        ],
        "traits": {
            "smithy.api#documentation": "<p>Gets detailed information about the specified license
configuration.</p>"
        }
    },
    "com.amazonaws.licensemanager#GetLicenseConfigurationRequest": {
        "type": "structure",
        "members": {
            "LicenseConfigurationArn": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license
configuration.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits":
{
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#GetLicenseConfigurationResponse": {
        "type": "structure",
        "members": {
            "LicenseConfigurationId": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Unique ID for the license configuration.</p>"
                }
            },
            "LicenseConfigurationArn": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license configuration.</p>"
                }
            },
            "Name": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Name of the license configuration.</p>"
                 }
            },
            "Description": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Description of the license configuration.</p>"
```

```
        }
      },
      "LicenseCountingType": {
        "target": "com.amazonaws.licensemanager#LicenseCountingType",
        "traits": {
          "smithy.api#documentation": "<p>Dimension for which the licenses are counted.</p>"
        }
      },
      "LicenseRules": {
        "target": "com.amazonaws.licensemanager#StringList",
        "traits": {
          "smithy.api#documentation": "<p>License rules.</p>"
        }
      },
      "LicenseCount": {
        "target": "com.amazonaws.licensemanager#BoxLong",

       "traits": {
          "smithy.api#documentation": "<p>Number of available licenses.</p>"
        }
      },
      "LicenseCountHardLimit": {
        "target": "com.amazonaws.licensemanager#BoxBoolean",
        "traits": {
          "smithy.api#documentation": "<p>Sets the number of available licenses as a hard limit.</p>"
        }
      },
      "ConsumedLicenses": {
        "target": "com.amazonaws.licensemanager#BoxLong",
        "traits": {
          "smithy.api#documentation": "<p>Number of licenses assigned to resources.</p>"
        }
      },
      "Status": {
        "target": "com.amazonaws.licensemanager#String",
        "traits": {
          "smithy.api#documentation": "<p>License configuration status.</p>"
        }

    },
      "OwnerAccountId": {
        "target": "com.amazonaws.licensemanager#String",
        "traits": {
          "smithy.api#documentation": "<p>Account ID of the owner of the license configuration.</p>"
        }
      },
      "ConsumedLicenseSummaryList": {
        "target": "com.amazonaws.licensemanager#ConsumedLicenseSummaryList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Summaries of the licenses consumed by resources.</p>"
            }
        },
        "ManagedResourceSummaryList": {
            "target": "com.amazonaws.licensemanager#ManagedResourceSummaryList",
            "traits": {
                "smithy.api#documentation": "<p>Summaries of the managed resources.</p>"
            }
        },
        "Tags": {
            "target": "com.amazonaws.licensemanager#TagList",
             "traits": {
                "smithy.api#documentation": "<p>Tags for the license configuration.</p>"
            }
        },
        "ProductInformationList": {
            "target": "com.amazonaws.licensemanager#ProductInformationList",
            "traits": {
                "smithy.api#documentation": "<p>Product information.</p>"
            }
        },
        "AutomatedDiscoveryInformation": {
            "target": "com.amazonaws.licensemanager#AutomatedDiscoveryInformation",
            "traits": {
                "smithy.api#documentation": "<p>Automated discovery information.</p>"
            }
        },
        "DisassociateWhenNotFound": {
            "target": "com.amazonaws.licensemanager#BoxBoolean",
            "traits": {
                "smithy.api#documentation": "<p>When
true, disassociates a resource when software is uninstalled.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanager#GetLicenseConversionTask": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanager#GetLicenseConversionTaskRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanager#GetLicenseConversionTaskResponse"
    },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
          },
          {
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
          },
          {

 "target": "com.amazonaws.licensemanager#RateLimitExceededException"
          },
          {
            "target": "com.amazonaws.licensemanager#ServerInternalException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Gets information about the specified license type conversion task.</p>"
        }
      },
      "com.amazonaws.licensemanager#GetLicenseConversionTaskRequest": {
        "type": "structure",
        "members": {
          "LicenseConversionTaskId": {
            "target": "com.amazonaws.licensemanager#LicenseConversionTaskId",
            "traits": {
              "smithy.api#documentation": "<p>ID of the license type conversion task to retrieve information
on.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
       },
      "com.amazonaws.licensemanager#GetLicenseConversionTaskResponse": {
        "type": "structure",
        "members": {
          "LicenseConversionTaskId": {
            "target": "com.amazonaws.licensemanager#LicenseConversionTaskId",
            "traits": {
              "smithy.api#documentation": "<p>ID of the license type conversion task.</p>"
            }
          },
          "ResourceArn": {
```

```
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Amazon Resource Names (ARN) of the resources the license
conversion task is associated with.</p>"
            }
          },
          "SourceLicenseContext": {
            "target": "com.amazonaws.licensemanager#LicenseConversionContext",
            "traits": {
              "smithy.api#documentation": "<p>Information
 about the license type converted from.</p>"
            }
          },
          "DestinationLicenseContext": {
            "target": "com.amazonaws.licensemanager#LicenseConversionContext",
            "traits": {
              "smithy.api#documentation": "<p>Information about the license type converted to.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for the conversion task.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanager#LicenseConversionTaskStatus",
            "traits": {
              "smithy.api#documentation": "<p>Status of the license type conversion task.</p>"
            }
          },

  "StartTime": {
            "target": "com.amazonaws.licensemanager#DateTime",
            "traits": {
              "smithy.api#documentation": "<p>Time at which the license type conversion task was started .</p>"
            }
          },
          "LicenseConversionTime": {
            "target": "com.amazonaws.licensemanager#DateTime",
            "traits": {
              "smithy.api#documentation": "<p>Amount of time to complete the license type conversion.</p>"
            }
          },
          "EndTime": {
            "target": "com.amazonaws.licensemanager#DateTime",
            "traits": {
              "smithy.api#documentation": "<p>Time at which the license type conversion task was
```

```
completed.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanager#GetLicenseManagerReportGenerator":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#GetLicenseManagerReportGeneratorRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanager#GetLicenseManagerReportGeneratorResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"

         },
            {
                "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Gets information about the specified report generator.</p>"
        }
    },
```

```
    "com.amazonaws.licensemanager#GetLicenseManagerReportGeneratorRequest": {
      "type": "structure",
      "members": {
        "LicenseManagerReportGeneratorArn": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the report generator.</p>",
            "smithy.api#required":
{}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanager#GetLicenseManagerReportGeneratorResponse": {
      "type": "structure",
      "members": {
        "ReportGenerator": {
          "target": "com.amazonaws.licensemanager#ReportGenerator",
          "traits": {
            "smithy.api#documentation": "<p>A report generator that creates periodic reports about your license
configurations.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanager#GetLicenseRequest": {
      "type": "structure",
      "members": {
        "LicenseArn": {
          "target": "com.amazonaws.licensemanager#Arn",
          "traits": {

 "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license.</p>",
            "smithy.api#required": {}
          }
        },
        "Version": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>License version.</p>"
          }
        }
```

```
    },
    "traits": {
      "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanager#GetLicenseResponse": {
    "type": "structure",
    "members": {
      "License": {
        "target": "com.amazonaws.licensemanager#License",
        "traits": {
          "smithy.api#documentation": "<p>License details.</p>"
        }
      }
    },
    "traits": {
      "smithy.api#output": {}
    }
  },

"com.amazonaws.licensemanager#GetLicenseUsage": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanager#GetLicenseUsageRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanager#GetLicenseUsageResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanager#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanager#AuthorizationException"
      },
      {
        "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
      },
      {
        "target": "com.amazonaws.licensemanager#RateLimitExceededException"
      },
      {
        "target": "com.amazonaws.licensemanager#ServerInternalException"
      },
      {

"target": "com.amazonaws.licensemanager#ValidationException"
      }
```

```
        ],
        "traits": {
            "smithy.api#documentation": "<p>Gets detailed information about the usage of the specified license.</p>"
        }
    },
    "com.amazonaws.licensemanager#GetLicenseUsageRequest": {
        "type": "structure",
        "members": {
            "LicenseArn": {
                "target": "com.amazonaws.licensemanager#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#GetLicenseUsageResponse": {
        "type": "structure",
        "members": {
            "LicenseUsage": {
                "target":
"com.amazonaws.licensemanager#LicenseUsage",
                "traits": {
                    "smithy.api#documentation": "<p>License usage details.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanager#GetServiceSettings": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanager#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Gets the License Manager settings for the current Region.</p>"
        }
    },
    "com.amazonaws.licensemanager#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "S3BucketArn": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Regional S3 bucket path for storing reports, license trail event data,
discovery data,\n        and so on.</p>"

 }
            },
            "SnsTopicArn": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>SNS topic configured to receive notifications from License
Manager.</p>"
                }
            },
            "OrganizationConfiguration": {
                "target": "com.amazonaws.licensemanager#OrganizationConfiguration",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates whether Organizations is integrated with License
Manager for\n        cross-account discovery.</p>"
                }
            },
            "EnableCrossAccountsDiscovery": {
                "target": "com.amazonaws.licensemanager#BoxBoolean",
                "traits": {
```

```
                "smithy.api#documentation": "<p>Indicates whether cross-account discovery is enabled.</p>"
              }

          },
            "LicenseManagerResourceShareArn": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the resource share. The License
Manager management account \n         provides member accounts with access to this share.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanager#Grant": {
          "type": "structure",
          "members": {
            "GrantArn": {
              "target": "com.amazonaws.licensemanager#Arn",
              "traits": {
                "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the grant.</p>",
                "smithy.api#required": {}
              }
            },
            "GrantName": {

 "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Grant name.</p>",
                "smithy.api#required": {}
              }
            },
            "ParentArn": {
              "target": "com.amazonaws.licensemanager#Arn",
              "traits": {
                "smithy.api#documentation": "<p>Parent ARN.</p>",
                "smithy.api#required": {}
              }
            },
            "LicenseArn": {
              "target": "com.amazonaws.licensemanager#Arn",
              "traits": {
                "smithy.api#documentation": "<p>License ARN.</p>",
                "smithy.api#required": {}
              }
            },
```

```
        "GranteePrincipalArn": {
          "target": "com.amazonaws.licensemanager#Arn",
          "traits": {

"smithy.api#documentation": "<p>The grantee principal ARN.</p>",
            "smithy.api#required": {}
          }
        },
        "HomeRegion": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Home Region of the grant.</p>",
            "smithy.api#required": {}
          }
        },
        "GrantStatus": {
          "target": "com.amazonaws.licensemanager#GrantStatus",
          "traits": {
            "smithy.api#documentation": "<p>Grant status.</p>",
            "smithy.api#required": {}
          }
        },
        "StatusReason": {
          "target": "com.amazonaws.licensemanager#StatusReasonMessage",
          "traits": {
            "smithy.api#documentation": "<p>Grant status reason.</p>"
           }
        },
        "Version": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Grant version.</p>",
            "smithy.api#required": {}
          }
        },
        "GrantedOperations": {
          "target": "com.amazonaws.licensemanager#AllowedOperationList",
          "traits": {
            "smithy.api#documentation": "<p>Granted operations.</p>",
            "smithy.api#required": {}
          }
        },
        "Options": {
          "target": "com.amazonaws.licensemanager#Options",
          "traits": {
            "smithy.api#documentation": "<p>The options specified for the grant.</p>"
          }
        }
```

```
        },
        "traits": {
          "smithy.api#documentation":
"<p>Describes a grant.</p>"
        }
      },
      "com.amazonaws.licensemanager#GrantList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanager#Grant"
        }
      },
      "com.amazonaws.licensemanager#GrantStatus": {
        "type": "enum",
        "members": {
          "PENDING_WORKFLOW": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "PENDING_WORKFLOW"
            }
          },
          "PENDING_ACCEPT": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "PENDING_ACCEPT"
            }
          },
          "REJECTED": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "REJECTED"

          }
          },
          "ACTIVE": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "ACTIVE"
            }
          },
          "FAILED_WORKFLOW": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "FAILED_WORKFLOW"
            }
          },
          "DELETED": {
            "target": "smithy.api#Unit",
```

```
            "traits": {
              "smithy.api#enumValue": "DELETED"
            }
          },
          "PENDING_DELETE": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "PENDING_DELETE"
            }
          },
          "DISABLED": {
            "target": "smithy.api#Unit",
            "traits":
{
              "smithy.api#enumValue": "DISABLED"
            }
          },
          "WORKFLOW_COMPLETED": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "WORKFLOW_COMPLETED"
            }
          }
        }
      },
      "com.amazonaws.licensemanager#GrantedLicense": {
        "type": "structure",
        "members": {
          "LicenseArn": {
            "target": "com.amazonaws.licensemanager#Arn",
            "traits": {
              "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license.</p>"
            }
          },
          "LicenseName": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>License name.</p>"
            }

  },
          "ProductName": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Product name.</p>"
            }
          },
          "ProductSKU": {
```

```
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Product SKU.</p>"
            }
        },
        "Issuer": {
            "target": "com.amazonaws.licensemanager#IssuerDetails",
            "traits": {
                "smithy.api#documentation": "<p>Granted license issuer.</p>"
            }
        },
        "HomeRegion": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Home Region of the granted license.</p>"

         }
        },
        "Status": {
            "target": "com.amazonaws.licensemanager#LicenseStatus",
            "traits": {
                "smithy.api#documentation": "<p>Granted license status.</p>"
            }
        },
        "Validity": {
            "target": "com.amazonaws.licensemanager#DatetimeRange",
            "traits": {
                "smithy.api#documentation": "<p>Date and time range during which the granted license is valid, in
ISO8601-UTC format.</p>"
            }
        },
        "Beneficiary": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Granted license beneficiary.</p>"
            }
        },
        "Entitlements": {
            "target": "com.amazonaws.licensemanager#EntitlementList",
             "traits": {
                "smithy.api#documentation": "<p>License entitlements.</p>"
            }
        },
        "ConsumptionConfiguration": {
            "target": "com.amazonaws.licensemanager#ConsumptionConfiguration",
            "traits": {
                "smithy.api#documentation": "<p>Configuration for consumption of the license.</p>"
            }
```

```
        },
        "LicenseMetadata": {
          "target": "com.amazonaws.licensemanager#MetadataList",
          "traits": {
            "smithy.api#documentation": "<p>Granted license metadata.</p>"
          }
        },
        "CreateTime": {
          "target": "com.amazonaws.licensemanager#ISO8601DateTime",
          "traits": {
            "smithy.api#documentation": "<p>Creation time of the granted license.</p>"

  }
        },
        "Version": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Version of the granted license.</p>"
          }
        },
        "ReceivedMetadata": {
          "target": "com.amazonaws.licensemanager#ReceivedMetadata",
          "traits": {
            "smithy.api#documentation": "<p>Granted license received metadata.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes a license that is granted to a grantee.</p>"
      }
    },
    "com.amazonaws.licensemanager#GrantedLicenseList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanager#GrantedLicense"
      }
    },
    "com.amazonaws.licensemanager#ISO8601DateTime":
{
      "type": "string",
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#pattern": "^(-?(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|[0-
1][0-9]):([0-5][0-9]):([0-5][0-9])(\\.[0-9]+)?(Z|[+-](?:2[ 0-3]|[0-1][0-9]):[0-5][0-9])+$"
      }
```

```
    },
    "com.amazonaws.licensemanager#Integer": {
      "type": "integer"
    },
    "com.amazonaws.licensemanager#InvalidParameterValueException": {
      "type": "structure",
      "members": {
        "Message": {
          "target": "com.amazonaws.licensemanager#Message"
        }
      },
      "traits": {
        "aws.protocols#awsQueryError": {
          "code": "InvalidParameterValueProvided",
          "httpResponseCode": 400
        },
        "smithy.api#documentation":
"<p>One or more parameter values are not valid.</p>",
        "smithy.api#error": "client",
        "smithy.api#httpError": 400
      }
    },
    "com.amazonaws.licensemanager#InvalidResourceStateException": {
      "type": "structure",
      "members": {
        "Message": {
          "target": "com.amazonaws.licensemanager#Message"
        }
      },
      "traits": {
        "aws.protocols#awsQueryError": {
          "code": "InvalidResourceState",
          "httpResponseCode": 400
        },
        "smithy.api#documentation": "<p>License Manager cannot allocate a license to a resource because of its
state. </p>\n        <p>For example, you cannot allocate a license to an instance in the process of shutting\n
down.</p>",
        "smithy.api#error": "client",
        "smithy.api#httpError": 400
      }
    },

    "com.amazonaws.licensemanager#InventoryFilter": {
      "type": "structure",
      "members": {
        "Name": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
```

```
                "smithy.api#documentation": "<p>Name of the filter.</p>",
                "smithy.api#required": {}
              }
            },
            "Condition": {
              "target": "com.amazonaws.licensemanager#InventoryFilterCondition",
              "traits": {
                "smithy.api#documentation": "<p>Condition of the filter.</p>",
                "smithy.api#required": {}
              }
            },
            "Value": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Value of the filter.</p>"
              }
            }

  },
      "traits": {
        "smithy.api#documentation": "<p>An inventory filter.</p>"
      }
    },
    "com.amazonaws.licensemanager#InventoryFilterCondition": {
      "type": "enum",
      "members": {
        "EQUALS": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "EQUALS"
          }
        },
        "NOT_EQUALS": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "NOT_EQUALS"
          }
        },
        "BEGINS_WITH": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "BEGINS_WITH"
          }
        },
        "CONTAINS": {
          "target": "smithy.api#Unit",
          "traits": {
```

```
                    "smithy.api#enumValue": "CONTAINS"
                }
            }
        }
    },
    "com.amazonaws.licensemanager#InventoryFilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanager#InventoryFilter"
        }
    },
    "com.amazonaws.licensemanager#Issuer": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Issuer name.</p>",
                    "smithy.api#required": {}
                }
            },
            "SignKey": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Asymmetric KMS key from Key Management Service. The KMS
key must have a key usage
 of sign and verify, \n          and support the RSASSA-PSS SHA-256 signing algorithm.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about the issuer of a license.</p>"
        }
    },
    "com.amazonaws.licensemanager#IssuerDetails": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Issuer name.</p>"
                }
            },
            "SignKey": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Asymmetric KMS key from Key Management Service. The KMS
key must have a key usage of sign and verify, \n          and support the RSASSA-PSS SHA-256 signing
```

```
algorithm.</p>"
                }
            },
            "KeyFingerprint": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Issuer key fingerprint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details associated with the issuer of a license.</p>"
        }
    },
    "com.amazonaws.licensemanager#License": {
        "type": "structure",
        "members": {
            "LicenseArn": {
                "target": "com.amazonaws.licensemanager#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license.</p>"
                }
            },
            "LicenseName": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {

               "smithy.api#documentation": "<p>License name.</p>"
                }
            },
            "ProductName": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Product name.</p>"
                }
            },
            "ProductSKU": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Product SKU.</p>"
                }
            },
            "Issuer": {
                "target": "com.amazonaws.licensemanager#IssuerDetails",
                "traits": {
                    "smithy.api#documentation": "<p>License issuer.</p>"
                }
            },
```

```
        "HomeRegion": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {

        "smithy.api#documentation": "<p>Home Region of the license.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanager#LicenseStatus",
          "traits": {
            "smithy.api#documentation": "<p>License status.</p>"
          }
        },
        "Validity": {
          "target": "com.amazonaws.licensemanager#DatetimeRange",
          "traits": {
            "smithy.api#documentation": "<p>Date and time range during which the license is valid, in ISO8601-
UTC format.</p>"
          }
        },
        "Beneficiary": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>License beneficiary.</p>"
          }
        },
        "Entitlements": {

   "target": "com.amazonaws.licensemanager#EntitlementList",
          "traits": {
            "smithy.api#documentation": "<p>License entitlements.</p>"
          }
        },
        "ConsumptionConfiguration": {
          "target": "com.amazonaws.licensemanager#ConsumptionConfiguration",
          "traits": {
            "smithy.api#documentation": "<p>Configuration for consumption of the license.</p>"
          }
        },
        "LicenseMetadata": {
          "target": "com.amazonaws.licensemanager#MetadataList",
          "traits": {
            "smithy.api#documentation": "<p>License metadata.</p>"
          }
        },
        "CreateTime": {
          "target": "com.amazonaws.licensemanager#ISO8601DateTime",
          "traits": {
```

```
                "smithy.api#documentation": "<p>License
creation time.</p>"
            }
          },
          "Version": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>License version.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Software license that is managed in License Manager.</p>"
        }
      },
      "com.amazonaws.licensemanager#LicenseConfiguration": {
        "type": "structure",
        "members": {
          "LicenseConfigurationId": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Unique ID of the license configuration.</p>"
            }
          },
          "LicenseConfigurationArn": {
            "target": "com.amazonaws.licensemanager#String",
             "traits": {
              "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license configuration.</p>"
            }
          },
          "Name": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Name of the license configuration.</p>"
            }
          },
          "Description": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Description of the license configuration.</p>"
            }
          },
          "LicenseCountingType": {
            "target": "com.amazonaws.licensemanager#LicenseCountingType",
            "traits": {
              "smithy.api#documentation": "<p>Dimension to use to track the license inventory.</p>"
             }
          },
```

```
            "LicenseRules": {
               "target": "com.amazonaws.licensemanager#StringList",
               "traits": {
                  "smithy.api#documentation": "<p>License rules.</p>"
               }
            },
            "LicenseCount": {
               "target": "com.amazonaws.licensemanager#BoxLong",
               "traits": {
                  "smithy.api#documentation": "<p>Number of licenses managed by the license configuration.</p>"
               }
            },
            "LicenseCountHardLimit": {
               "target": "com.amazonaws.licensemanager#BoxBoolean",
               "traits": {
                  "smithy.api#documentation": "<p>Number of available licenses as a hard limit.</p>"
               }
            },
            "DisassociateWhenNotFound": {
               "target": "com.amazonaws.licensemanager#BoxBoolean",
                "traits": {
                  "smithy.api#documentation": "<p>When true, disassociates a resource when software is
uninstalled.</p>"
               }
            },
            "ConsumedLicenses": {
               "target": "com.amazonaws.licensemanager#BoxLong",
               "traits": {
                  "smithy.api#documentation": "<p>Number of licenses consumed. </p>"
               }
            },
            "Status": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Status of the license configuration.</p>"
               }
            },
            "OwnerAccountId": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Account ID of the license configuration's owner.</p>"

            }
            },
            "ConsumedLicenseSummaryList": {
               "target": "com.amazonaws.licensemanager#ConsumedLicenseSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Summaries for licenses consumed by various resources.</p>"
```

```
            }
          },
          "ManagedResourceSummaryList": {
            "target": "com.amazonaws.licensemanager#ManagedResourceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Summaries for managed resources.</p>"
            }
          },
          "ProductInformationList": {
            "target": "com.amazonaws.licensemanager#ProductInformationList",
            "traits": {
              "smithy.api#documentation": "<p>Product information.</p>"
            }
          },
          "AutomatedDiscoveryInformation": {

            "target": "com.amazonaws.licensemanager#AutomatedDiscoveryInformation",
            "traits": {
              "smithy.api#documentation": "<p>Automated discovery information.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A license configuration is an abstraction of a customer license agreement that can be\n consumed and enforced by License Manager. Components include specifications for the license\n type (licensing by instance, socket, CPU, or vCPU), allowed tenancy (shared tenancy, \n Dedicated Instance, Dedicated Host, or all of these), host affinity (how long a VM\n must be associated with a host), and the number of licenses purchased and used.</p>"
        }
      },
      "com.amazonaws.licensemanager#LicenseConfigurationAssociation": {
        "type": "structure",
        "members": {
          "ResourceArn":
{
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the resource.</p>"
            }
          },
          "ResourceType": {
            "target": "com.amazonaws.licensemanager#ResourceType",
            "traits": {
              "smithy.api#documentation": "<p>Type of server resource.</p>"
            }
          },
          "ResourceOwnerId": {
            "target": "com.amazonaws.licensemanager#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>ID of the Amazon Web Services account that owns the resource consuming licenses.</p>"
            }
        },
        "AssociationTime": {
            "target": "com.amazonaws.licensemanager#DateTime",
            "traits": {

    "smithy.api#documentation": "<p>Time when the license configuration was associated with the resource.</p>"
            }
        },
        "AmiAssociationScope": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Scope of AMI associations. The possible value is <code>cross-account</code>.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes an association with a license configuration.</p>"
      }
    },
    "com.amazonaws.licensemanager#LicenseConfigurationAssociations": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanager#LicenseConfigurationAssociation"
      }
    },
    "com.amazonaws.licensemanager#LicenseConfigurationStatus": {
      "type": "enum",
      "members":
{
        "AVAILABLE": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "AVAILABLE"
            }
        },
        "DISABLED": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "DISABLED"
            }
        }
      }
    },
```

```
    "com.amazonaws.licensemanager#LicenseConfigurationUsage": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the resource.</p>"
          }
        },
        "ResourceType": {
          "target": "com.amazonaws.licensemanager#ResourceType",
          "traits":
{
            "smithy.api#documentation": "<p>Type of resource.</p>"
          }
        },
        "ResourceStatus": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Status of the resource.</p>"
          }
        },
        "ResourceOwnerId": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>ID of the account that owns the resource.</p>"
          }
        },
        "AssociationTime": {
          "target": "com.amazonaws.licensemanager#DateTime",
          "traits": {
            "smithy.api#documentation": "<p>Time when the license configuration was initially associated with
the resource.</p>"
          }
        },

    "ConsumedLicenses": {
          "target": "com.amazonaws.licensemanager#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>Number of licenses consumed by the resource.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details about the usage of a resource associated with a license
configuration.</p>"
      }
    },
```

```
    "com.amazonaws.licensemanager#LicenseConfigurationUsageList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanager#LicenseConfigurationUsage"
      }
    },
    "com.amazonaws.licensemanager#LicenseConfigurations": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanager#LicenseConfiguration"
      }
    },
    "com.amazonaws.licensemanager#LicenseConversionContext": {

  "type": "structure",
      "members": {
        "UsageOperation": {
          "target": "com.amazonaws.licensemanager#UsageOperation",
          "traits": {
            "smithy.api#documentation": "<p>The Usage operation value that corresponds to the license type you
are converting your resource from.  For more information about which platforms correspond to which usage
operation values see <a href=\"https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/billing-info-
fields.html#billing-info\">Sample data: usage operation by platform\n      </a>\n        </p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Information about a license type conversion task.</p>"
      }
    },
    "com.amazonaws.licensemanager#LicenseConversionTask": {
      "type": "structure",
      "members": {
        "LicenseConversionTaskId": {

   "target": "com.amazonaws.licensemanager#LicenseConversionTaskId",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the license type conversion task.</p>"
          }
        },
        "ResourceArn": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource associated
with the license type\n        conversion task.</p>"
          }
        },
        "SourceLicenseContext": {
```

```
            "target": "com.amazonaws.licensemanager#LicenseConversionContext",
            "traits": {
              "smithy.api#documentation": "<p>Information about the license type this conversion task converted from.</p>"
            }
          },
          "DestinationLicenseContext": {
            "target": "com.amazonaws.licensemanager#LicenseConversionContext",
            "traits": {
              "smithy.api#documentation": "<p>Information about the license type this conversion task converted to.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanager#LicenseConversionTaskStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the conversion task.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for the conversion task.</p>"
            }
          },
          "StartTime": {
            "target": "com.amazonaws.licensemanager#DateTime",
            "traits": {
              "smithy.api#documentation": "<p>The time the conversion task was started at.</p>"
            }
          },
          "LicenseConversionTime": {
            "target": "com.amazonaws.licensemanager#DateTime",
            "traits": {
              "smithy.api#documentation": "<p>The time the usage operation value of the resource was changed.</p>"
            }
          },
          "EndTime": {
            "target": "com.amazonaws.licensemanager#DateTime",
            "traits": {
              "smithy.api#documentation": "<p>The time the conversion task was completed.</p>"
            }
          }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>Information about a license type conversion task.</p>"
          }
        },
        "com.amazonaws.licensemanager#LicenseConversionTaskId": {
          "type": "string",
          "traits": {

           "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#pattern": "^lct-[a-zA-Z0-9]*$"
          }
        },
        "com.amazonaws.licensemanager#LicenseConversionTaskStatus": {
          "type": "enum",
          "members": {
            "IN_PROGRESS": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "IN_PROGRESS"
              }
            },
            "SUCCEEDED": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "SUCCEEDED"
              }
            },
            "FAILED": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "FAILED"
              }
            }
          }
        },
        "com.amazonaws.licensemanager#LicenseConversionTasks":
    {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanager#LicenseConversionTask"
          }
        },
        "com.amazonaws.licensemanager#LicenseCountingType": {
          "type": "enum",
          "members": {
            "VCPU": {
```

```
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "vCPU"
            }
          },
          "INSTANCE": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Instance"
            }
          },
          "CORE": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "Core"
            }
          },
          "SOCKET": {
            "target": "smithy.api#Unit",
             "traits": {
              "smithy.api#enumValue": "Socket"
            }
          }
        }
      },
      "com.amazonaws.licensemanager#LicenseDeletionStatus": {
        "type": "enum",
        "members": {
          "PENDING_DELETE": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "PENDING_DELETE"
            }
          },
          "DELETED": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "DELETED"
            }
          }
        }
      },
      "com.amazonaws.licensemanager#LicenseList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanager#License"
        }
      },
```

```
"com.amazonaws.licensemanager#LicenseOperationFailure": {

    "type": "structure",
    "members": {
      "ResourceArn": {
        "target": "com.amazonaws.licensemanager#String",
        "traits": {
          "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the resource.</p>"
        }
      },
      "ResourceType": {
        "target": "com.amazonaws.licensemanager#ResourceType",
        "traits": {
          "smithy.api#documentation": "<p>Resource type.</p>"
        }
      },
      "ErrorMessage": {
        "target": "com.amazonaws.licensemanager#String",
        "traits": {
          "smithy.api#documentation": "<p>Error message.</p>"
        }
      },
      "FailureTime": {
        "target": "com.amazonaws.licensemanager#DateTime",
        "traits": {

"smithy.api#documentation": "<p>Failure time.</p>"
        }
      },
      "OperationName": {
        "target": "com.amazonaws.licensemanager#String",
        "traits": {
          "smithy.api#documentation": "<p>Name of the operation.</p>"
        }
      },
      "ResourceOwnerId": {
        "target": "com.amazonaws.licensemanager#String",
        "traits": {
          "smithy.api#documentation": "<p>ID of the Amazon Web Services account that owns the
resource.</p>"
        }
      },
      "OperationRequestedBy": {
        "target": "com.amazonaws.licensemanager#String",
        "traits": {
          "smithy.api#documentation": "<p>The requester is \"License Manager Automated Discovery\".</p>"
        }
      },
```

```
        "MetadataList": {

          "target": "com.amazonaws.licensemanager#MetadataList",
          "traits": {
            "smithy.api#documentation": "<p>Reserved.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes the failure of a license operation.</p>"
      }
    },
    "com.amazonaws.licensemanager#LicenseOperationFailureList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanager#LicenseOperationFailure"
      }
    },
    "com.amazonaws.licensemanager#LicenseSpecification": {
      "type": "structure",
      "members": {
        "LicenseConfigurationArn": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license
configuration.</p>",

            "smithy.api#required": {}
          }
        },
        "AmiAssociationScope": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Scope of AMI associations. The possible value is <code>cross-
account</code>.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details for associating a license configuration with a resource.</p>"
      }
    },
    "com.amazonaws.licensemanager#LicenseSpecifications": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanager#LicenseSpecification"
      }
    },
```

```
"com.amazonaws.licensemanager#LicenseStatus": {
    "type": "enum",
    "members": {
        "AVAILABLE": {
            "target": "smithy.api#Unit",

        "traits": {
                "smithy.api#enumValue": "AVAILABLE"
            }
        },
        "PENDING_AVAILABLE": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "PENDING_AVAILABLE"
            }
        },
        "DEACTIVATED": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "DEACTIVATED"
            }
        },
        "SUSPENDED": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "SUSPENDED"
            }
        },
        "EXPIRED": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "EXPIRED"
            }
        },

      "PENDING_DELETE": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "PENDING_DELETE"
            }
        },
        "DELETED": {
            "target": "smithy.api#Unit",
            "traits": {
                "smithy.api#enumValue": "DELETED"
            }
        }
    }
```

```
    },
    "com.amazonaws.licensemanager#LicenseUsage": {
      "type": "structure",
      "members": {
        "EntitlementUsages": {
          "target": "com.amazonaws.licensemanager#EntitlementUsageList",
          "traits": {
            "smithy.api#documentation": "<p>License entitlement usages.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes the entitlement usage associated with a license.</p>"

      }
    },
    "com.amazonaws.licensemanager#LicenseUsageException": {
      "type": "structure",
      "members": {
        "Message": {
          "target": "com.amazonaws.licensemanager#Message"
        }
      },
      "traits": {
        "aws.protocols#awsQueryError": {
          "code": "LicenseUsageFailure",
          "httpResponseCode": 412
        },
        "smithy.api#documentation": "<p>You do not have enough licenses available to support a new resource
launch.</p>",
        "smithy.api#error": "client",
        "smithy.api#httpError": 412
      }
    },
    "com.amazonaws.licensemanager#ListAssociationsForLicenseConfiguration": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanager#ListAssociationsForLicenseConfigurationRequest"
      },
      "output": {

   "target": "com.amazonaws.licensemanager#ListAssociationsForLicenseConfigurationResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanager#AccessDeniedException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#FilterLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the resource associations for the
 specified license configuration.</p>\n        <p>Resource associations need not consume licenses from a license
configuration. \n        For example, an AMI or a stopped instance might not consume a license (depending on \n
the license rules).</p>"
        }
    },
    "com.amazonaws.licensemanager#ListAssociationsForLicenseConfigurationRequest": {
        "type": "structure",
        "members": {
            "LicenseConfigurationArn": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of a license configuration.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanager#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>Maximum number of results
 to return in a single call.</p>"
                }
            },
            "NextToken": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Token for the next set of results.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanager#ListAssociationsForLicenseConfigurationResponse": {
        "type": "structure",
        "members": {
          "LicenseConfigurationAssociations": {
            "target": "com.amazonaws.licensemanager#LicenseConfigurationAssociations",
            "traits": {
              "smithy.api#documentation": "<p>Information about the associations for the license
configuration.</p>"
            }
          },
          "NextToken": {

 "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Token for the next set of results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#ListDistributedGrants": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanager#ListDistributedGrantsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanager#ListDistributedGrantsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
          },
          {
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
           },
          {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
          },
          {
            "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
          },
```

```
            {
              "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
              "target": "com.amazonaws.licensemanager#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the grants distributed for the specified license.</p>"
          }
        },
        "com.amazonaws.licensemanager#ListDistributedGrantsRequest": {
          "type": "structure",
          "members": {
            "GrantArns": {
              "target": "com.amazonaws.licensemanager#ArnList",
              "traits": {

            "smithy.api#documentation": "<p>Amazon Resource Names (ARNs) of the grants.</p>"
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanager#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>Filters to scope the results. The following filters are
supported:</p>\n        <ul>\n          <li>\n            <p>\n              <code>LicenseArn</code>\n            </p>\n
      </li>\n          <li>\n            <p>\n              <code>GrantStatus</code>\n            </p>\n          </li>\n
  <li>\n            <p>\n              <code>GranteePrincipalARN</code>\n            </p>\n          </li>\n
<li>\n            <p>\n              <code>ProductSKU</code>\n            </p>\n          </li>\n          <li>\n
<p>\n              <code>LicenseIssuerName</code>\n
        </p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Token for the next set of results.</p>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanager#MaxSize100",
              "traits": {
                "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanager#ListDistributedGrantsResponse": {
        "type": "structure",
        "members": {
          "Grants": {
            "target": "com.amazonaws.licensemanager#GrantList",

      "traits": {
                "smithy.api#documentation": "<p>Distributed grant details.</p>"
            }
          },
          "NextToken": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Token for the next set of results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#ListFailuresForLicenseConfigurationOperations": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanager#ListFailuresForLicenseConfigurationOperationsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanager#ListFailuresForLicenseConfigurationOperationsResponse"
        },
        "errors": [
          {

  "target": "com.amazonaws.licensemanager#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
          },
          {
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
          },
          {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
          },
          {
            "target": "com.amazonaws.licensemanager#ServerInternalException"
          }
```

```
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the license configuration operations that failed.</p>"
        }
    },
    "com.amazonaws.licensemanager#ListFailuresForLicenseConfigurationOperationsRequest": {
        "type": "structure",
        "members": {
            "LicenseConfigurationArn": {
                "target": "com.amazonaws.licensemanager#String",
                 "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name of the license configuration.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanager#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
                }
            },
            "NextToken": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Token for the next set of results.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#ListFailuresForLicenseConfigurationOperationsResponse":
{
        "type": "structure",
        "members": {
            "LicenseOperationFailureList": {
                "target": "com.amazonaws.licensemanager#LicenseOperationFailureList",
                "traits": {
                    "smithy.api#documentation": "<p>License configuration operations that failed.</p>"
                }
            },
            "NextToken": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Token for the next set of results.</p>"
                }
            }
```

```
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanager#ListLicenseConfigurations": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#ListLicenseConfigurationsRequest"
        },

   "output": {
            "target": "com.amazonaws.licensemanager#ListLicenseConfigurationsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#FilterLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the license configurations
 for your account.</p>"
        }
    },
    "com.amazonaws.licensemanager#ListLicenseConfigurationsRequest": {
        "type": "structure",
        "members": {
            "LicenseConfigurationArns": {
                "target": "com.amazonaws.licensemanager#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Names (ARN) of the license
configurations.</p>"
                }
```

```
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanager#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
               }
            },
            "NextToken": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Token for the next
 set of results.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanager#Filters",
               "traits": {
                  "smithy.api#documentation": "<p>Filters to scope the results. The following filters and logical
operators\n        are supported:</p>\n        <ul>\n            <li>\n                <p>\n
<code>licenseCountingType</code> - The dimension for which licenses are counted.\n                Possible values are
<code>vCPU</code> | <code>Instance</code> | <code>Core</code> | <code>Socket</code>.\n                Logical
operators are <code>EQUALS</code> | <code>NOT_EQUALS</code>.</p>\n            </li>\n            <li>\n
<p>\n                <code>enforceLicenseCount</code> - A Boolean value that indicates whether hard license
enforcement is used. \n                Logical operators are <code>EQUALS</code> |
<code>NOT_EQUALS</code>.</p>\n
    </li>\n            <li>\n                <p>\n                <code>usagelimitExceeded</code> - A Boolean value that
indicates whether the available licenses have been exceeded. \n                Logical operators are
<code>EQUALS</code> | <code>NOT_EQUALS</code>.</p>\n            </li>\n        </ul>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanager#ListLicenseConfigurationsResponse": {
         "type": "structure",
         "members": {
            "LicenseConfigurations": {
               "target": "com.amazonaws.licensemanager#LicenseConfigurations",
               "traits": {
                  "smithy.api#documentation": "<p>Information about the license configurations.</p>"
               }
            },
            "NextToken": {
               "target": "com.amazonaws.licensemanager#String",
```

```
      "traits": {
            "smithy.api#documentation": "<p>Token for the next set of results.</p>"
          }
        }
    },
    "traits": {
      "smithy.api#output": {}
    }
  },
  "com.amazonaws.licensemanager#ListLicenseConversionTasks": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanager#ListLicenseConversionTasksRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanager#ListLicenseConversionTasksResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanager#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanager#AuthorizationException"
      },
      {
        "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
      },
      {
        "target": "com.amazonaws.licensemanager#RateLimitExceededException"
      },
      {
        "target": "com.amazonaws.licensemanager#ServerInternalException"
      }
    ],
    "traits": {
      "smithy.api#documentation": "<p>Lists the license type conversion tasks for your account.</p>"
    }
  },
  "com.amazonaws.licensemanager#ListLicenseConversionTasksRequest": {
    "type": "structure",
    "members": {
      "NextToken": {
        "target": "com.amazonaws.licensemanager#String",
        "traits": {
          "smithy.api#documentation": "<p>Token for the next set of results.</p>"
        }
      },
      "MaxResults": {
```

```
                "target": "com.amazonaws.licensemanager#BoxInteger",
                "traits": {

    "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanager#Filters",
                "traits": {
                    "smithy.api#documentation": "<p>\n         Filters to scope the results. Valid filters are
<code>ResourceArns</code> and <code>Status</code>.\n      </p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#ListLicenseConversionTasksResponse": {
        "type": "structure",
        "members": {
            "LicenseConversionTasks": {
                "target": "com.amazonaws.licensemanager#LicenseConversionTasks",
                "traits": {
                    "smithy.api#documentation": "<p>Information about the license configuration tasks for your
account.</p>"
                }
            },
            "NextToken": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Token for the next set of results.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanager#ListLicenseManagerReportGenerators": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#ListLicenseManagerReportGeneratorsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanager#ListLicenseManagerReportGeneratorsResponse"
        },
        "errors": [
```

```
            {
              "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
              "target":
 "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
              "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
              "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
              "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
              "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
              "target": "com.amazonaws.licensemanager#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the report generators for your account.</p>"
          }
        },
        "com.amazonaws.licensemanager#ListLicenseManagerReportGeneratorsRequest":
 {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanager#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>Filters to scope the results. The following filters are supported:
</p>\n        <ul>\n          <li>\n            <p>\n              <code>LicenseConfigurationArn</code>\n
</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Token for the next set of results.</p>"
              }
            },
```

```
            "MaxResults": {
              "target": "com.amazonaws.licensemanager#MaxSize100",
              "traits":
{
                "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanager#ListLicenseManagerReportGeneratorsResponse": {
          "type": "structure",
          "members": {
            "ReportGenerators": {
              "target": "com.amazonaws.licensemanager#ReportGeneratorList",
              "traits": {
                "smithy.api#documentation": "<p>A report generator that creates periodic reports about your license
configurations.</p>"
              }
            },
            "NextToken": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Token for the next set of results.</p>"
              }

          }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanager#ListLicenseSpecificationsForResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanager#ListLicenseSpecificationsForResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanager#ListLicenseSpecificationsForResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanager#AuthorizationException"
```

```
            },
            {
              "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
              "target": "com.amazonaws.licensemanager#RateLimitExceededException"
             },
            {
              "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Describes the license configurations for the specified resource.</p>"
          }
        },
        "com.amazonaws.licensemanager#ListLicenseSpecificationsForResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of a resource that has an
associated license configuration.</p>",
                "smithy.api#required": {}
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanager#BoxInteger",
              "traits": {

           "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
              }
            },
            "NextToken": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Token for the next set of results.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanager#ListLicenseSpecificationsForResourceResponse": {
          "type": "structure",
          "members": {
            "LicenseSpecifications": {
```

```
            "target": "com.amazonaws.licensemanager#LicenseSpecifications",
            "traits": {
                "smithy.api#documentation": "<p>License configurations associated with a resource.</p>"
            }
        },
        "NextToken": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Token for the next set of results.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanager#ListLicenseVersions": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanager#ListLicenseVersionsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanager#ListLicenseVersionsResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
        },
        {
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
        },
        {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
        },
        {
            "target": "com.amazonaws.licensemanager#ServerInternalException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists all versions of the specified license.</p>"
    }
},
"com.amazonaws.licensemanager#ListLicenseVersionsRequest": {
    "type": "structure",
    "members": {
```

```
            "LicenseArn": {
              "target": "com.amazonaws.licensemanager#Arn",
              "traits": {
                "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license.</p>",
                "smithy.api#required": {}
              }
            },
            "NextToken": {
              "target": "com.amazonaws.licensemanager#String",
               "traits": {
                "smithy.api#documentation": "<p>Token for the next set of results.</p>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanager#MaxSize100",
              "traits": {
                "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanager#ListLicenseVersionsResponse": {
          "type": "structure",
          "members": {
            "Licenses": {
              "target": "com.amazonaws.licensemanager#LicenseList",
              "traits": {
                "smithy.api#documentation": "<p>License details.</p>"
              }
            },

      "NextToken": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Token for the next set of results.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanager#ListLicenses": {
          "type": "operation",
          "input": {
```

```
            "target": "com.amazonaws.licensemanager#ListLicensesRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanager#ListLicensesResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
              "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
             },
            {
              "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
              "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
              "target": "com.amazonaws.licensemanager#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the licenses for your account.</p>"
          }
        },
        "com.amazonaws.licensemanager#ListLicensesRequest": {
          "type": "structure",
          "members": {
            "LicenseArns": {
              "target": "com.amazonaws.licensemanager#ArnList",
              "traits": {
                "smithy.api#documentation": "<p>Amazon Resource Names (ARNs) of the licenses.</p>"
              }
            },

         "Filters": {
              "target": "com.amazonaws.licensemanager#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>Filters to scope the results. The following filters are
supported:</p>\n        <ul>\n          <li>\n            <p>\n              <code>Beneficiary</code>\n            </p>\n
        </li>\n          <li>\n            <p>\n              <code>ProductSKU</code>\n            </p>\n          </li>\n
    <li>\n            <p>\n              <code>Fingerprint</code>\n            </p>\n          </li>\n          <li>\n
<p>\n              <code>Status</code>\n            </p>\n          </li>\n        </ul>"
              }
```

```
        },
        "NextToken": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Token
for the next set of results.</p>"
          }
        },
        "MaxResults": {
          "target": "com.amazonaws.licensemanager#MaxSize100",
          "traits": {
            "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanager#ListLicensesResponse": {
      "type": "structure",
      "members": {
        "Licenses": {
          "target": "com.amazonaws.licensemanager#LicenseList",
          "traits": {
            "smithy.api#documentation": "<p>License details.</p>"
          }
        },
        "NextToken": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {

  "smithy.api#documentation": "<p>Token for the next set of results.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanager#ListReceivedGrants": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanager#ListReceivedGrantsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanager#ListReceivedGrantsResponse"
      },
```

```
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
             },
            {
                "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists grants that are received. Received grants are grants created while specifying the\n          recipient as this Amazon Web Services account, your organization, or an organizational unit\n          (OU) to which this member account belongs.</p>"
        }
    },
    "com.amazonaws.licensemanager#ListReceivedGrantsForOrganization": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#ListReceivedGrantsForOrganizationRequest"
         },
        "output": {
            "target": "com.amazonaws.licensemanager#ListReceivedGrantsForOrganizationResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target":
 "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the grants received for all accounts in the organization.</p>"
        }
    },
    "com.amazonaws.licensemanager#ListReceivedGrantsForOrganizationRequest": {
        "type": "structure",
        "members": {
            "LicenseArn": {
                "target": "com.amazonaws.licensemanager#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the received license.</p>",
                    "smithy.api#required": {}
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanager#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>Filters to scope the results. The following filters are
supported:</p>\n
    <ul>\n        <li>\n            <p>\n                <code>ParentArn</code>\n            </p>\n        </li>\n
<li>\n            <p>\n                <code>GranteePrincipalArn</code>\n            </p>\n        </li>\n    </ul>"
                }
            },
            "NextToken": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Token for the next set of results.</p>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanager#MaxSize100",
                "traits": {
                    "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
                }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanager#ListReceivedGrantsForOrganizationResponse":
{
        "type": "structure",
        "members": {
          "Grants": {
            "target": "com.amazonaws.licensemanager#GrantList",
            "traits": {
              "smithy.api#documentation": "<p>Lists the grants the organization has received.</p>"
            }
          },
          "NextToken": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Token for the next set of results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#ListReceivedGrantsRequest": {
        "type": "structure",
        "members": {
          "GrantArns": {
            "target": "com.amazonaws.licensemanager#ArnList",
             "traits": {
              "smithy.api#documentation": "<p>Amazon Resource Names (ARNs) of the grants.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanager#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>Filters to scope the results. The following filters are
supported:</p>\n        <ul>\n          <li>\n            <p>\n              <code>ProductSKU</code>\n            </p>\n
        </li>\n          <li>\n            <p>\n              <code>LicenseIssuerName</code>\n            </p>\n
</li>\n          <li>\n            <p>\n              <code>LicenseArn</code>\n            </p>\n          </li>\n
<li>\n            <p>\n              <code>GrantStatus</code>\n            </p>\n          </li>\n          <li>\n
<p>\n
        <code>GranterAccountId</code>\n            </p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
```

```
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Token for the next set of results.</p>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanager#MaxSize100",
            "traits": {
              "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanager#ListReceivedGrantsResponse": {
        "type": "structure",
        "members": {
          "Grants": {
            "target": "com.amazonaws.licensemanager#GrantList",
             "traits": {
              "smithy.api#documentation": "<p>Received grant details.</p>"
            }
          },
          "NextToken": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Token for the next set of results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#ListReceivedLicenses": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanager#ListReceivedLicensesRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanager#ListReceivedLicensesResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists received licenses.</p>"
        }
    },
    "com.amazonaws.licensemanager#ListReceivedLicensesForOrganization":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#ListReceivedLicensesForOrganizationRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanager#ListReceivedLicensesForOrganizationResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
```

```
            },
            {

        "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the licenses received for all accounts in the organization.</p>"
        }
    },
    "com.amazonaws.licensemanager#ListReceivedLicensesForOrganizationRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanager#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>Filters to scope the results. The following filters are
supported:</p>\n        <ul>\n            <li>\n                <p>\n                    <code>Beneficiary</code>\n                </p>\n
        </li>\n            <li>\n                <p>\n                    <code>ProductSKU</code>\n
            </p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Token for the next set of results.</p>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanager#MaxSize100",
                "traits": {
                    "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#ListReceivedLicensesForOrganizationResponse": {
        "type": "structure",
        "members": {
            "Licenses": {
                "target": "com.amazonaws.licensemanager#GrantedLicenseList",
```

```
            "traits": {
              "smithy.api#documentation": "<p>Lists the licenses the organization has received.</p>"
            }
          },
          "NextToken": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Token for the next set of results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#ListReceivedLicensesRequest": {
        "type": "structure",
        "members": {
          "LicenseArns": {
            "target": "com.amazonaws.licensemanager#ArnList",
            "traits": {
              "smithy.api#documentation": "<p>Amazon Resource Names (ARNs) of the licenses.</p>"
            }
          },

          "Filters": {
            "target": "com.amazonaws.licensemanager#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>Filters to scope the results. The following filters are
supported:</p>\n        <ul>\n          <li>\n            <p>\n              <code>ProductSKU</code>\n            </p>\n
        </li>\n          <li>\n            <p>\n              <code>Status</code>\n            </p>\n          </li>\n
<li>\n            <p>\n              <code>Fingerprint</code>\n            </p>\n          </li>\n          <li>\n
<p>\n              <code>IssuerName</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Beneficiary</code>\n            </p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Token for the next set of results.</p>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanager#MaxSize100",
            "traits": {
              "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
            }
          }
```

```
    },
    "traits": {
      "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanager#ListReceivedLicensesResponse": {
    "type": "structure",
    "members": {
      "Licenses": {
        "target": "com.amazonaws.licensemanager#GrantedLicenseList",
        "traits": {
          "smithy.api#documentation": "<p>Received license details.</p>"
        }
      },

     "NextToken": {
        "target": "com.amazonaws.licensemanager#String",
        "traits": {
          "smithy.api#documentation": "<p>Token for the next set of results.</p>"
        }
      }
    },
    "traits": {
      "smithy.api#output": {}
    }
  },
  "com.amazonaws.licensemanager#ListResourceInventory": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanager#ListResourceInventoryRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanager#ListResourceInventoryResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanager#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanager#AuthorizationException"
      },
      {
        "target": "com.amazonaws.licensemanager#FailedDependencyException"
      },
      {
        "target": "com.amazonaws.licensemanager#FilterLimitExceededException"
      },
      {
```

```
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
          },
          {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
          },
          {
            "target": "com.amazonaws.licensemanager#ServerInternalException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists resources managed using Systems Manager inventory.</p>"
        }
      },
      "com.amazonaws.licensemanager#ListResourceInventoryRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanager#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
            }
          },
          "NextToken": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Token for the next set of results.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanager#InventoryFilterList",
            "traits": {
              "smithy.api#documentation": "<p>Filters to scope the results. The following filters and logical
operators\n are supported:</p>\n <ul>\n <li>\n <p>\n <code>account_id</code>
- The ID of the Amazon Web Services account that owns the resource.\n Logical operators are
<code>EQUALS</code> | <code>NOT_EQUALS</code>.</p>\n
 </li>\n <li>\n <p>\n <code>application_name</code> - The name of the
application. \n Logical operators are <code>EQUALS</code> | <code>BEGINS_WITH</code>.</p>\n
 </li>\n <li>\n <p>\n <code>license_included</code> - The type of license included. \n
 Logical operators are <code>EQUALS</code> | <code>NOT_EQUALS</code>.\n Possible values
are <code>sql-server-enterprise</code> | \n <code>sql-server-standard</code> | \n <code>sql-
server-web</code> | \n <code>windows-server-datacenter</code>.</p>\n </li>\n <li>\n
 <p>\n <code>platform</code> - The platform of the resource.\n Logical operators are
<code>EQUALS</code> | <code>BEGINS_WITH</code>.</p>\n </li>\n <li>\n <p>\n
 <code>resource_id</code> - The ID of the resource. \n Logical operators are
<code>EQUALS</code> | <code>NOT_EQUALS</code>.</p>\n </li>\n <li>\n <p>\n
 <code>tag:<key></code> - The key/value combination of a tag assigned \n to the resource. Logical
operators are <code>EQUALS</code> (single account) or\n <code>EQUALS</code> |
<code>NOT_EQUALS</code> (cross account).</p>\n </li>\n </ul>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanager#ListResourceInventoryResponse": {
        "type": "structure",
        "members": {
          "ResourceInventoryList": {
            "target": "com.amazonaws.licensemanager#ResourceInventoryList",
            "traits": {
              "smithy.api#documentation": "<p>Information
about the resources.</p>"
            }
          },
          "NextToken": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Token for the next set of results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanager#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanager#ListTagsForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
          },
          {
            "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
          },
          {
            "target": "com.amazonaws.licensemanager#RateLimitExceededException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the tags for the specified license configuration.</p>"
        }
    },
    "com.amazonaws.licensemanager#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license
configuration.</p>",

    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanager#TagList",
                "traits": {
                    "smithy.api#documentation": "<p>Information about the tags.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanager#ListTokens": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#ListTokensRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanager#ListTokensResponse"
        },
```

```
        "errors":
[
            {
               "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
               "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
               "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
               "target": "com.amazonaws.licensemanager#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists your tokens.</p>"
         }
      },
      "com.amazonaws.licensemanager#ListTokensRequest": {
         "type": "structure",
         "members": {
            "TokenIds": {
               "target": "com.amazonaws.licensemanager#StringList",
               "traits": {

                  "smithy.api#documentation": "<p>Token IDs.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanager#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>Filters to scope the results. The following filter is supported:</p>\n
      <ul>\n          <li>\n          <p>\n          <code>LicenseArns</code>\n          </p>\n          </li>\n
</ul>"
               }
            },
            "NextToken": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Token for the next set of results.</p>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanager#MaxSize100",
```

```
            "traits": {
                "smithy.api#documentation":
"<p>Maximum number of results to return in a single call.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanager#ListTokensResponse": {
        "type": "structure",
        "members": {
          "Tokens": {
            "target": "com.amazonaws.licensemanager#TokenList",
            "traits": {
              "smithy.api#documentation": "<p>Received token details.</p>"
            }
          },
          "NextToken": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Token for the next set of results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanager#ListUsageForLicenseConfiguration":
{
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanager#ListUsageForLicenseConfigurationRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanager#ListUsageForLicenseConfigurationResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanager#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
          },
          {
            "target": "com.amazonaws.licensemanager#FilterLimitExceededException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
               "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
             {
               "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists all license usage records for a license configuration, displaying license\n consumption details by resource at a selected point in time. Use this action to audit the\n current license consumption for any license inventory and configuration.</p>"
         }
      },
      "com.amazonaws.licensemanager#ListUsageForLicenseConfigurationRequest": {
         "type": "structure",
         "members": {
            "LicenseConfigurationArn": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license configuration.</p>",
                  "smithy.api#required": {}
               }
            },
             "MaxResults": {
               "target": "com.amazonaws.licensemanager#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>Maximum number of results to return in a single call.</p>"
               }
            },
            "NextToken": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Token for the next set of results.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanager#Filters",
               "traits": {
                  "smithy.api#documentation": "<p>Filters to scope the results. The following filters and logical operators\n are supported:</p>\n <ul>\n <li>\n <p>\n <code>resourceArn</code> - The ARN of the license configuration resource.\n Logical operators are <code>EQUALS</code> | <code>NOT_EQUALS</code>.</p>\n </li>\n <li>\n <p>\n <code>resourceType</code> - The resource type
```

(<code>EC2_INSTANCE</code> | <code>EC2_HOST</code> | <code>EC2_AMI</code> |
<code>SYSTEMS_MANAGER_MANAGED_INSTANCE</code>). \n Logical operators are
<code>EQUALS</code> | <code>NOT_EQUALS</code>. \n \n \n \n
<code>resourceAccount</code> - The ID of the account that owns the resource. \n Logical operators
are <code>EQUALS</code> | <code>NOT_EQUALS</code>. \n \n "
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanager#ListUsageForLicenseConfigurationResponse": {
"type": "structure",
"members": {

"LicenseConfigurationUsageList": {
"target": "com.amazonaws.licensemanager#LicenseConfigurationUsageList",
"traits": {
"smithy.api#documentation": " Information about the license configurations. "
}
},
"NextToken": {
"target": "com.amazonaws.licensemanager#String",
"traits": {
"smithy.api#documentation": " Token for the next set of results. "
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanager#Location": {
"type": "string"
},
"com.amazonaws.licensemanager#Long": {
"type": "long"
},
"com.amazonaws.licensemanager#ManagedResourceSummary": {
"type": "structure",
"members": {
"ResourceType":
{
"target": "com.amazonaws.licensemanager#ResourceType",
"traits": {
"smithy.api#documentation": " Type of resource associated with a license. "
}

```
        },
        "AssociationCount": {
          "target": "com.amazonaws.licensemanager#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>Number of resources associated with licenses.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Summary information about a managed resource.</p>"
      }
    },
    "com.amazonaws.licensemanager#ManagedResourceSummaryList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanager#ManagedResourceSummary"
      }
    },
    "com.amazonaws.licensemanager#MaxSize100": {

    "type": "integer",
      "traits": {
        "smithy.api#range": {
          "min": 1,
          "max": 100
        }
      }
    },
    "com.amazonaws.licensemanager#MaxSize3StringList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanager#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 3
        }
      }
    },
    "com.amazonaws.licensemanager#Message": {
      "type": "string"
    },
    "com.amazonaws.licensemanager#Metadata": {
      "type": "structure",
      "members": {
        "Name": {
          "target": "com.amazonaws.licensemanager#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The key name.</p>"
            }
        },

    "Value": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>The value.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes key/value pairs.</p>"
    }
},
"com.amazonaws.licensemanager#MetadataList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanager#Metadata"
    }
},
"com.amazonaws.licensemanager#NoEntitlementsAllowedException": {
    "type": "structure",
    "members": {
        "Message": {
            "target": "com.amazonaws.licensemanager#Message"
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>There are no entitlements found for this license, or the entitlement maximum count is reached.</p>",
         "smithy.api#error": "client",
        "smithy.api#httpError": 400
    }
},
"com.amazonaws.licensemanager#Options": {
    "type": "structure",
    "members": {
        "ActivationOverrideBehavior": {
            "target": "com.amazonaws.licensemanager#ActivationOverrideBehavior",
            "traits": {
                "smithy.api#documentation": "<p>An activation option for your grant that determines the behavior of activating a grant.\n Activation options can only be used with granted licenses sourced from the Amazon Web Services Marketplace. Additionally, the operation must specify the value of <code>ACTIVE</code> for the\n <code>Status</code> parameter.</p>\n <ul>\n <li>\n <p>As a license administrator, you can optionally specify an\n <code>ActivationOverrideBehavior</code> when activating a grant.</p>\n
```

```
</li>\n <li>\n <p>As a grantor, you can optionally specify an\n <code>ActivationOverrideBehavior</code> when you activate a grant for a grantee\n account in your organization.</p>\n </li>\n <li>\n <p>As a grantee, if the grantor creating the distributed grant doesnt specify an\n <code>ActivationOverrideBehavior</code>, you can optionally specify one when you\n are activating the grant.</p>\n </li>\n </ul>\n <dl>\n <dt>DISTRIBUTED_GRANTS_ONLY</dt>\n <dd>\n <p>Use this value to activate a grant without replacing any member accounts\n active grants for the same product.</p>\n </dd>\n <dt>ALL_GRANTS_PERMITTED_BY_ISSUER</dt>\n <dd>\n <p>Use this value to activate a grant and disable other active grants in any\n member accounts
 for the same product. This action will also replace their\n previously activated grants with this activated grant.</p>\n </dd>\n </dl>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The options you can specify when you create a new version of a grant, such as activation\n override behavior. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/granted-licenses.html\">Granted licenses in License Manager</a> in the <i>License Manager User Guide</i>.</p>"
        }
    },
    "com.amazonaws.licensemanager#OrganizationConfiguration": {
        "type": "structure",
        "members": {
            "EnableIntegration": {
                "target": "com.amazonaws.licensemanager#Boolean",
                "traits": {
                    "smithy.api#default": false,
                    "smithy.api#documentation":
 "<p>Enables Organizations integration.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Configuration information for Organizations.</p>"
        }
    },
    "com.amazonaws.licensemanager#PrincipalArnList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanager#Arn"
        },
        "traits": {
            "smithy.api#length": {
                "min": 1,
                "max": 1
            }
```

```
        }
      },
      "com.amazonaws.licensemanager#ProductInformation": {
        "type": "structure",
        "members": {
          "ResourceType": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Resource type. The
possible values are <code>SSM_MANAGED</code> | <code>RDS</code>.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductInformationFilterList": {
            "target": "com.amazonaws.licensemanager#ProductInformationFilterList",
            "traits": {
              "smithy.api#documentation": "<p>A Product information filter consists of a
<code>ProductInformationFilterComparator</code> which is a logical operator, a
<code>ProductInformationFilterName</code> which specifies the type of filter being declared, and a
<code>ProductInformationFilterValue</code> that specifies the value to filter on. </p>\n          <p>Accepted values
for <code>ProductInformationFilterName</code> are listed here along with descriptions and valid options for
<code>ProductInformationFilterComparator</code>. </p>\n          <p>The following filters and are supported when
the resource type \n          is <code>SSM_MANAGED</code>:</p>\n
          <ul>\n            <li>\n              <p>\n                <code>Application Name</code> - The name of the
application.\n                Logical operator is <code>EQUALS</code>.</p>\n            </li>\n            <li>\n
<p>\n                <code>Application Publisher</code> - The publisher of the application.\n                Logical
operator is <code>EQUALS</code>.</p>\n            </li>\n            <li>\n              <p>\n
<code>Application Version</code> - The version of the application.\n                Logical operator is
<code>EQUALS</code>.</p>\n            </li>\n            <li>\n              <p>\n                <code>Platform
Name</code> - The name of the platform.\n                Logical operator is <code>EQUALS</code>.</p>\n
</li>\n            <li>\n              <p>\n                <code>Platform Type</code> - The platform type.\n
Logical operator is <code>EQUALS</code>.</p>\n
          </li>\n            <li>\n              <p>\n                <code>Tag:key</code> - The key of a tag attached to an
Amazon Web Services resource you wish to exclude from automated discovery. Logical operator is
<code>NOT_EQUALS</code>.  The key for your tag must be appended to <code>Tag:</code> following the
example: <code>Tag:name-of-your-key</code>. <code>ProductInformationFilterValue</code> is optional if you
are not using values for the key.\n                </p>\n            </li>\n            <li>\n              <p>\n
<code>AccountId</code> - The 12-digit ID of an Amazon Web Services account you wish to exclude from
automated discovery.\n                Logical operator is <code>NOT_EQUALS</code>.</p>\n            </li>\n
<li>\n              <p>\n                <code>License Included</code> - The type of license included.\n                Logical
operators are <code>EQUALS</code> and <code>NOT_EQUALS</code>.\n                Possible values are:
 <code>sql-server-enterprise</code> | \n                <code>sql-server-standard</code> | \n                <code>sql-server-
web</code> |  \n                <code>windows-server-datacenter</code>.</p>\n            </li>\n          </ul>\n
<p>The following filters and logical operators are supported when the resource type\n          is
<code>RDS</code>:</p>\n          <ul>\n            <li>\n              <p>\n                <code>Engine Edition</code> -
The edition of the database engine.\n                Logical operator is <code>EQUALS</code>.\n                Possible
values are: <code>oracle-ee</code> | <code>oracle-se</code> | <code>oracle-se1</code> | <code>oracle-
se2</code>.</p>\n            </li>\n            <li>\n              <p>\n                <code>License Pack</code> - The license
```

```
pack.\n            Logical operator is <code>EQUALS</code>.\n            Possible values are: <code>data
guard</code> | \n            <code>diagnostic pack sqlt</code> | \n
          <code>tuning pack sqlt</code> | \n            <code>ols</code> | \n            <code>olap</code>.</p>\n
    </li>\n        </ul>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes product information for a license configuration.</p>"
          }
        },
        "com.amazonaws.licensemanager#ProductInformationFilter": {
          "type": "structure",
          "members": {
            "ProductInformationFilterName": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Filter name.</p>",
                "smithy.api#required": {}
              }
            },
            "ProductInformationFilterValue": {
              "target": "com.amazonaws.licensemanager#StringList",

           "traits": {
                "smithy.api#documentation": "<p>Filter value.</p>"
              }
            },
            "ProductInformationFilterComparator": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Logical operator.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes product information filters.</p>"
          }
        },
        "com.amazonaws.licensemanager#ProductInformationFilterList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanager#ProductInformationFilter"
          }
        },
        "com.amazonaws.licensemanager#ProductInformationList": {
```

```
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanager#ProductInformation"
      }
    },
    "com.amazonaws.licensemanager#ProvisionalConfiguration": {
      "type": "structure",
      "members": {
        "MaxTimeToLiveInMinutes": {
          "target": "com.amazonaws.licensemanager#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>Maximum time for the provisional configuration, in minutes.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details about a provisional configuration.</p>"
      }
    },
    "com.amazonaws.licensemanager#RateLimitExceededException": {
      "type": "structure",
      "members": {
        "Message": {
          "target": "com.amazonaws.licensemanager#Message"
        }
      },
      "traits": {
        "aws.protocols#awsQueryError": {
          "code": "RateLimitExceeded",
          "httpResponseCode": 429
        },
        "smithy.api#documentation": "<p>Too many requests have been submitted. Try again after a brief
wait.</p>",
        "smithy.api#error": "client",
        "smithy.api#httpError": 429
      }
    },
    "com.amazonaws.licensemanager#ReceivedMetadata": {
      "type": "structure",
      "members": {
        "ReceivedStatus": {
          "target": "com.amazonaws.licensemanager#ReceivedStatus",
          "traits": {
            "smithy.api#documentation": "<p>Received status.</p>"
          }
        },
        "ReceivedStatusReason": {
```

```
            "target": "com.amazonaws.licensemanager#StatusReasonMessage",
            "traits": {
              "smithy.api#documentation": "<p>Received
status reason.</p>"
            }
          },
          "AllowedOperations": {
            "target": "com.amazonaws.licensemanager#AllowedOperationList",
            "traits": {
              "smithy.api#documentation": "<p>Allowed operations.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Metadata associated with received licenses and grants.</p>"
        }
      },
      "com.amazonaws.licensemanager#ReceivedStatus": {
        "type": "enum",
        "members": {
          "PENDING_WORKFLOW": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "PENDING_WORKFLOW"
            }
          },
          "PENDING_ACCEPT": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue":
"PENDING_ACCEPT"
            }
          },
          "REJECTED": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "REJECTED"
            }
          },
          "ACTIVE": {
            "target": "smithy.api#Unit",
            "traits": {
              "smithy.api#enumValue": "ACTIVE"
            }
          },
          "FAILED_WORKFLOW": {
            "target": "smithy.api#Unit",
            "traits": {
```

```
            "smithy.api#enumValue": "FAILED_WORKFLOW"
          }
        },
        "DELETED": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "DELETED"
          }
        },
        "DISABLED": {
          "target": "smithy.api#Unit",
           "traits": {
            "smithy.api#enumValue": "DISABLED"
          }
        },
        "WORKFLOW_COMPLETED": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "WORKFLOW_COMPLETED"
          }
        }
      }
    },
    "com.amazonaws.licensemanager#RedirectException": {
      "type": "structure",
      "members": {
        "Location": {
          "target": "com.amazonaws.licensemanager#Location",
          "traits": {
            "smithy.api#httpHeader": "Location"
          }
        },
        "Message": {
          "target": "com.amazonaws.licensemanager#Message"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>This is not the correct Region for the resource. Try again.</p>",
         "smithy.api#error": "client",
        "smithy.api#httpError": 308
      }
    },
    "com.amazonaws.licensemanager#RejectGrant": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanager#RejectGrantRequest"
      },
      "output": {
```

```
            "target": "com.amazonaws.licensemanager#RejectGrantResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target":
"com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Rejects the specified grant.</p>"
        }
    },
    "com.amazonaws.licensemanager#RejectGrantRequest": {
        "type": "structure",
        "members": {
            "GrantArn": {
                "target": "com.amazonaws.licensemanager#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the grant.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}

  }
    },
    "com.amazonaws.licensemanager#RejectGrantResponse": {
        "type": "structure",
```

```
      "members": {
        "GrantArn": {
          "target": "com.amazonaws.licensemanager#Arn",
          "traits": {
            "smithy.api#documentation": "<p>Grant ARN.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanager#GrantStatus",
          "traits": {
            "smithy.api#documentation": "<p>Grant status.</p>"
          }
        },
        "Version": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Grant version.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanager#RenewType":
{
      "type": "enum",
      "members": {
        "NONE": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "None"
          }
        },
        "WEEKLY": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "Weekly"
          }
        },
        "MONTHLY": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "Monthly"
          }
        }
      }
    },
```

```
    "com.amazonaws.licensemanager#ReportContext": {
      "type": "structure",
      "members": {
        "licenseConfigurationArns": {
          "target": "com.amazonaws.licensemanager#ArnList",
          "traits": {

      "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license configuration that this
generator reports on.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details of the license configuration that this generator reports on.</p>"
      }
    },
    "com.amazonaws.licensemanager#ReportFrequency": {
      "type": "structure",
      "members": {
        "value": {
          "target": "com.amazonaws.licensemanager#Integer",
          "traits": {
            "smithy.api#documentation": "<p>Number of times within the frequency period that a report is
generated.  \n         The only supported value is <code>1</code>.</p>"
          }
        },
        "period": {
          "target": "com.amazonaws.licensemanager#ReportFrequencyType",

          "traits": {
            "smithy.api#documentation": "<p>Time period between each report. The period can be daily, weekly,
or monthly.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details about how frequently reports are generated.</p>"
      }
    },
    "com.amazonaws.licensemanager#ReportFrequencyType": {
      "type": "enum",
      "members": {
        "DAY": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "DAY"
          }
```

```
            },
            "WEEK": {
               "target": "smithy.api#Unit",
               "traits": {
                  "smithy.api#enumValue": "WEEK"
               }
            },
            "MONTH": {
               "target": "smithy.api#Unit",
               "traits":
{
                  "smithy.api#enumValue": "MONTH"
               }
            }
         }
      },
      "com.amazonaws.licensemanager#ReportGenerator": {
         "type": "structure",
         "members": {
            "ReportGeneratorName": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Name of the report generator.</p>"
               }
            },
            "ReportType": {
               "target": "com.amazonaws.licensemanager#ReportTypeList",
               "traits": {
                  "smithy.api#documentation": "<p>Type of reports that are generated.</p>"
               }
            },
            "ReportContext": {
               "target": "com.amazonaws.licensemanager#ReportContext",
               "traits": {
                  "smithy.api#documentation": "<p>License
configuration type for this generator.</p>"
               }
            },
            "ReportFrequency": {
               "target": "com.amazonaws.licensemanager#ReportFrequency",
               "traits": {
                  "smithy.api#documentation": "<p>Details about how frequently reports are generated.</p>"
               }
            },
            "LicenseManagerReportGeneratorArn": {
               "target": "com.amazonaws.licensemanager#String",
               "traits": {
                  "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the report generator.</p>"
```

```
            }
        },
        "LastRunStatus": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Status of the last report generation attempt.</p>"
            }
        },
        "LastRunFailureReason":
{
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Failure message for the last report generation attempt.</p>"
            }
        },
        "LastReportGenerationTime": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Time the last report was generated at.</p>"
            }
        },
        "ReportCreatorAccount": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Web Services account ID used to create the report
generator.</p>"
            }
        },
        "Description": {
            "target": "com.amazonaws.licensemanager#String",

    "traits": {
                "smithy.api#documentation": "<p>Description of the report generator.</p>"
            }
        },
        "S3Location": {
            "target": "com.amazonaws.licensemanager#S3Location",
            "traits": {
                "smithy.api#documentation": "<p>Details of the S3 bucket that report generator reports are published
to.</p>"
            }
        },
        "CreateTime": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Time the report was created.</p>"
            }
        },
```

```
        "Tags": {
          "target": "com.amazonaws.licensemanager#TagList",
          "traits": {
            "smithy.api#documentation": "<p>Tags associated with the report generator.</p>"
          }

}
    },
    "traits": {
      "smithy.api#documentation": "<p>Describe the details of a report generator.</p>"
    }
  },
  "com.amazonaws.licensemanager#ReportGeneratorList": {
    "type": "list",
    "member": {
      "target": "com.amazonaws.licensemanager#ReportGenerator"
    }
  },
  "com.amazonaws.licensemanager#ReportGeneratorName": {
    "type": "string",
    "traits": {
      "smithy.api#length": {
        "min": 1,
        "max": 100
      }
    }
  },
  "com.amazonaws.licensemanager#ReportType": {
    "type": "enum",
    "members": {
      "LICENSE_CONFIGURATION_SUMMARY_REPORT": {
        "target": "smithy.api#Unit",
        "traits": {
          "smithy.api#enumValue": "LicenseConfigurationSummaryReport"
        }

  },
        "LICENSE_CONFIGURATION_USAGE_REPORT": {
          "target": "smithy.api#Unit",
          "traits": {
            "smithy.api#enumValue": "LicenseConfigurationUsageReport"
          }
        }
    }
  },
  "com.amazonaws.licensemanager#ReportTypeList": {
    "type": "list",
    "member": {
```

```
            "target": "com.amazonaws.licensemanager#ReportType"
          }
        },
        "com.amazonaws.licensemanager#ResourceInventory": {
          "type": "structure",
          "members": {
            "ResourceId": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>ID of the resource.</p>"
              }
            },
            "ResourceType": {
              "target": "com.amazonaws.licensemanager#ResourceType",
              "traits":
{
                "smithy.api#documentation": "<p>Type of resource.</p>"
              }
            },
            "ResourceArn": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the resource.</p>"
              }
            },
            "Platform": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Platform of the resource.</p>"
              }
            },
            "PlatformVersion": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Platform version of the resource in the inventory.</p>"
              }
            },
            "ResourceOwningAccountId":
{
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>ID of the account that owns the resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Details about a resource.</p>"
          }
```

```
},
"com.amazonaws.licensemanager#ResourceInventoryList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanager#ResourceInventory"
    }
},
"com.amazonaws.licensemanager#ResourceLimitExceededException": {
    "type": "structure",
    "members": {
        "Message": {
            "target": "com.amazonaws.licensemanager#Message"
        }
    },
    "traits": {
        "aws.protocols#awsQueryError": {
            "code": "ResourceLimitExceeded",

         "httpResponseCode": 400
        },
        "smithy.api#documentation": "<p>Your resource limits have been exceeded.</p>",
        "smithy.api#error": "client",
        "smithy.api#httpError": 400
    }
},
"com.amazonaws.licensemanager#ResourceNotFoundException": {
    "type": "structure",
    "members": {
        "Message": {
            "target": "com.amazonaws.licensemanager#Message"
        }
    },
    "traits": {
        "aws.protocols#awsQueryError": {
            "code": "InvalidResource.NotFound",
            "httpResponseCode": 400
        },
        "smithy.api#documentation": "<p>The resource cannot be found.</p>",
        "smithy.api#error": "client",
        "smithy.api#httpError": 400
    }
},
"com.amazonaws.licensemanager#ResourceType": {
    "type": "enum",
     "members": {
        "EC2_INSTANCE": {
            "target": "smithy.api#Unit",
            "traits": {
```

```
                "smithy.api#enumValue": "EC2_INSTANCE"
              }
            },
            "EC2_HOST": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "EC2_HOST"
              }
            },
            "EC2_AMI": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "EC2_AMI"
              }
            },
            "RDS": {
              "target": "smithy.api#Unit",
              "traits": {
                "smithy.api#enumValue": "RDS"
              }
            },
            "SYSTEMS_MANAGER_MANAGED_INSTANCE": {
              "target": "smithy.api#Unit",
              "traits": {
                 "smithy.api#enumValue": "SYSTEMS_MANAGER_MANAGED_INSTANCE"
              }
            }
          }
        },
        "com.amazonaws.licensemanager#S3Location": {
          "type": "structure",
          "members": {
            "bucket": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Name of the S3 bucket reports are published to.</p>"
              }
            },
            "keyPrefix": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                "smithy.api#documentation": "<p>Prefix of the S3 bucket reports are published to.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Details of the S3 bucket that report generator reports are published
to.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanager#ServerInternalException": {
        "type": "structure",
        "members": {
          "Message": {
            "target": "com.amazonaws.licensemanager#Message"
          }
        },
        "traits": {
          "aws.protocols#awsQueryError": {
            "code": "InternalError",
            "httpResponseCode": 500
          },
          "smithy.api#documentation": "<p>The server experienced an internal error. Try again.</p>",
          "smithy.api#error": "server",
          "smithy.api#httpError": 500
        }
      },
      "com.amazonaws.licensemanager#SignedToken": {
        "type": "string",
        "traits": {
          "smithy.api#length": {
            "min": 4096
          }
        }
      },
      "com.amazonaws.licensemanager#StatusReasonMessage": {
        "type": "string",
        "traits":
{
          "smithy.api#length": {
            "min": 0,
            "max": 400
          },
          "smithy.api#pattern": "^[\\s\\S]+$"
        }
      },
      "com.amazonaws.licensemanager#String": {
        "type": "string"
      },
      "com.amazonaws.licensemanager#StringList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanager#String"
        }
      },
      "com.amazonaws.licensemanager#Tag": {
```

```
        "type": "structure",
        "members": {
          "Key": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation": "<p>Tag key.</p>"
            }
          },
          "Value": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
              "smithy.api#documentation":
"<p>Tag value.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details about a tag for a license configuration.</p>"
        }
      },
      "com.amazonaws.licensemanager#TagKeyList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanager#String"
        }
      },
      "com.amazonaws.licensemanager#TagList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanager#Tag"
        }
      },
      "com.amazonaws.licensemanager#TagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanager#TagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanager#TagResourceResponse"
        },
        "errors": [
          {
            "target":
"com.amazonaws.licensemanager#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanager#AuthorizationException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Adds the specified tags to the specified license configuration.</p>"
        }
    },
    "com.amazonaws.licensemanager#TagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanager#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license
configuration.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanager#TagList",
                "traits": {
                    "smithy.api#documentation": "<p>One or more tags.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanager#TokenData": {
        "type": "structure",
        "members": {
```

```
            "TokenId": {
              "target": "com.amazonaws.licensemanager#String",
               "traits": {
                 "smithy.api#documentation": "<p>Token ID.</p>"
              }
            },
            "TokenType": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                 "smithy.api#documentation": "<p>Type of token generated. The supported value is
<code>REFRESH_TOKEN</code>.</p>"
              }
            },
            "LicenseArn": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                 "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license.</p>"
              }
            },
            "ExpirationTime": {
              "target": "com.amazonaws.licensemanager#ISO8601DateTime",
              "traits": {
                 "smithy.api#documentation": "<p>Token expiration time, in ISO8601-UTC
 format.</p>"
              }
            },
            "TokenProperties": {
              "target": "com.amazonaws.licensemanager#MaxSize3StringList",
              "traits": {
                 "smithy.api#documentation": "<p>Data specified by the caller.</p>"
              }
            },
            "RoleArns": {
              "target": "com.amazonaws.licensemanager#ArnList",
              "traits": {
                 "smithy.api#documentation": "<p>Amazon Resource Names (ARN) of the roles included in the
token.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanager#String",
              "traits": {
                 "smithy.api#documentation": "<p>Token status. The possible values are
<code>AVAILABLE</code> and <code>DELETED</code>.</p>"
              }
            }
          },
          "traits": {
```

```
            "smithy.api#documentation": "<p>Describes a token.</p>"
        }
    },
    "com.amazonaws.licensemanager#TokenList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanager#TokenData"
        }
    },
    "com.amazonaws.licensemanager#TokenString": {
        "type": "string",
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 4096
            },
            "smithy.api#pattern": "^\\S+$"
        }
    },
    "com.amazonaws.licensemanager#TokenType": {
        "type": "enum",
        "members": {
            "REFRESH_TOKEN": {
                "target": "smithy.api#Unit",
                "traits": {
                    "smithy.api#enumValue": "REFRESH_TOKEN"
                }
            }
        }
    },
    "com.amazonaws.licensemanager#UnsupportedDigitalSignatureMethodException":
{
        "type": "structure",
        "members": {
            "Message": {
                "target": "com.amazonaws.licensemanager#Message"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The digital signature method is unsupported. Try your request
again.</p>",
            "smithy.api#error": "client",
            "smithy.api#httpError": 400
        }
    },
    "com.amazonaws.licensemanager#UntagResource": {
        "type": "operation",
```

```
        "input": {
            "target": "com.amazonaws.licensemanager#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanager#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
             },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes the specified tags from the specified license
configuration.</p>"
        }
    },
    "com.amazonaws.licensemanager#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license
configuration.</p>",
                     "smithy.api#required": {}
                }
            },
            "TagKeys": {
                "target": "com.amazonaws.licensemanager#TagKeyList",
                "traits": {
                    "smithy.api#documentation": "<p>Keys identifying the tags to remove.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanager#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanager#UpdateLicenseConfiguration": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanager#UpdateLicenseConfigurationRequest"
        },
        "output": {

"target": "com.amazonaws.licensemanager#UpdateLicenseConfigurationResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Modifies the attributes of an existing license configuration.</p>"
         }
    },
    "com.amazonaws.licensemanager#UpdateLicenseConfigurationRequest": {
        "type": "structure",
        "members": {
            "LicenseConfigurationArn": {
                "target": "com.amazonaws.licensemanager#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the license
configuration.</p>",
                "smithy.api#required": {}
            }
        },
        "LicenseConfigurationStatus": {
            "target": "com.amazonaws.licensemanager#LicenseConfigurationStatus",
            "traits": {
                "smithy.api#documentation": "<p>New status of the license configuration.</p>"
            }
        },
        "LicenseRules": {
            "target": "com.amazonaws.licensemanager#StringList",
            "traits": {

 "smithy.api#documentation": "<p>New license rule. The only rule that you can add after you create a license\n
 configuration is licenseAffinityToHost.</p>"
            }
        },
        "LicenseCount": {
            "target": "com.amazonaws.licensemanager#BoxLong",
            "traits": {
                "smithy.api#documentation": "<p>New number of licenses managed by the license
configuration.</p>"
            }
        },
        "LicenseCountHardLimit": {
            "target": "com.amazonaws.licensemanager#BoxBoolean",
            "traits": {
                "smithy.api#documentation": "<p>New hard limit of the number of available licenses.</p>"
            }
        },
        "Name": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>New name
 of the license configuration.</p>"
            }
        },
        "Description": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>New description of the license configuration.</p>"
            }
        },
        "ProductInformationList": {
            "target": "com.amazonaws.licensemanager#ProductInformationList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>New product information.</p>"
            }
        },
        "DisassociateWhenNotFound": {
            "target": "com.amazonaws.licensemanager#BoxBoolean",
            "traits": {
                "smithy.api#documentation": "<p>When true, disassociates a resource when software is
uninstalled.</p>"
            }
        }
    },
    "traits":
{
        "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanager#UpdateLicenseConfigurationResponse": {
    "type": "structure",
    "members": {},
    "traits": {
      "smithy.api#output": {}
    }
  },
  "com.amazonaws.licensemanager#UpdateLicenseManagerReportGenerator": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanager#UpdateLicenseManagerReportGeneratorRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanager#UpdateLicenseManagerReportGeneratorResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanager#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanager#AuthorizationException"
      },
      {
        "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
       },
      {
        "target": "com.amazonaws.licensemanager#RateLimitExceededException"
      },
      {
        "target": "com.amazonaws.licensemanager#ResourceLimitExceededException"
      },
```

```
            {
                "target": "com.amazonaws.licensemanager#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            },
            {
                "target": "com.amazonaws.licensemanager#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates a report generator.</p>\n        <p>After you make changes to a report generator, it starts generating new reports within 60 minutes of being updated.</p>"
        }
    },
    "com.amazonaws.licensemanager#UpdateLicenseManagerReportGeneratorRequest": {
        "type": "structure",
        "members": {
            "LicenseManagerReportGeneratorArn": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the report generator to update.</p>",
                    "smithy.api#required": {}
                }
            },
            "ReportGeneratorName": {
                "target": "com.amazonaws.licensemanager#ReportGeneratorName",
                "traits": {
                    "smithy.api#documentation": "<p>Name of the report generator.</p>",
                    "smithy.api#required": {}
                }
            },
            "Type": {
                "target": "com.amazonaws.licensemanager#ReportTypeList",
                "traits": {
                    "smithy.api#documentation": "<p>Type of reports to generate. The following report types are supported:</p>\n        <ul>\n            <li>\n                <p>License configuration report - Reports the number and details of consumed licenses for a license configuration.</p>\n            </li>\n            <li>\n                <p>Resource report - Reports the tracked licenses and resource consumption for a license configuration.</p>\n            </li>\n        </ul>",
                    "smithy.api#required": {}
                }
            },
            "ReportContext": {
                "target": "com.amazonaws.licensemanager#ReportContext",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The report context.</p>",
                "smithy.api#required": {}
            }
        },
        "ReportFrequency": {
            "target": "com.amazonaws.licensemanager#ReportFrequency",
            "traits":
{
                "smithy.api#documentation": "<p>Frequency by which reports are generated.</p>",
                "smithy.api#required": {}
            }
        },
        "ClientToken": {
            "target": "com.amazonaws.licensemanager#ClientRequestToken",
            "traits": {
                "smithy.api#documentation": "<p>Unique, case-sensitive identifier that you provide to ensure the
idempotency of the request.</p>",
                "smithy.api#required": {}
            }
        },
        "Description": {
            "target": "com.amazonaws.licensemanager#String",
            "traits": {
                "smithy.api#documentation": "<p>Description of the report generator.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanager#UpdateLicenseManagerReportGeneratorResponse":
{
    "type": "structure",
    "members": {},
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanager#UpdateLicenseSpecificationsForResource": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanager#UpdateLicenseSpecificationsForResourceRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanager#UpdateLicenseSpecificationsForResourceResponse"
    },
    "errors": [
```

```
            {
                "target": "com.amazonaws.licensemanager#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanager#AuthorizationException"
            },
            {
                "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
            },

            {
                "target": "com.amazonaws.licensemanager#InvalidResourceStateException"
            },
            {
                "target": "com.amazonaws.licensemanager#LicenseUsageException"
            },
            {
                "target": "com.amazonaws.licensemanager#RateLimitExceededException"
            },
            {
                "target": "com.amazonaws.licensemanager#ServerInternalException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Adds or removes the specified license configurations for the specified
Amazon Web Services resource.</p>\n         <p>You can update the license specifications of AMIs, instances, and
hosts.\n         You cannot update the license specifications for launch templates and CloudFormation templates, \n
 as they send license configurations to the operation that creates the resource.</p>"
        }
    },

    "com.amazonaws.licensemanager#UpdateLicenseSpecificationsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanager#String",
                "traits": {
                    "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the Amazon Web Services
resource.</p>",
                    "smithy.api#required": {}
                }
            },
            "AddLicenseSpecifications": {
                "target": "com.amazonaws.licensemanager#LicenseSpecifications",
                "traits": {
                    "smithy.api#documentation": "<p>ARNs of the license configurations to add.</p>"
                }
            },
```

```
        "RemoveLicenseSpecifications": {
          "target": "com.amazonaws.licensemanager#LicenseSpecifications",
          "traits": {
            "smithy.api#documentation":
"<p>ARNs of the license configurations to remove.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanager#UpdateLicenseSpecificationsForResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanager#UpdateServiceSettings": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanager#UpdateServiceSettingsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanager#UpdateServiceSettingsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanager#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanager#AuthorizationException"
         },
        {
          "target": "com.amazonaws.licensemanager#InvalidParameterValueException"
        },
        {
          "target": "com.amazonaws.licensemanager#RateLimitExceededException"
        },
        {
          "target": "com.amazonaws.licensemanager#ServerInternalException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Updates License Manager settings for the current Region.</p>"
      }
    },
```

```
    "com.amazonaws.licensemanager#UpdateServiceSettingsRequest": {
      "type": "structure",
      "members": {
        "S3BucketArn": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the Amazon S3 bucket where
the License
 Manager information is stored.</p>"
          }
        },
        "SnsTopicArn": {
          "target": "com.amazonaws.licensemanager#String",
          "traits": {
            "smithy.api#documentation": "<p>Amazon Resource Name (ARN) of the Amazon SNS topic used
for License Manager alerts.</p>"
          }
        },
        "OrganizationConfiguration": {
          "target": "com.amazonaws.licensemanager#OrganizationConfiguration",
          "traits": {
            "smithy.api#documentation": "<p>Enables integration with Organizations for cross-account
discovery.</p>"
          }
        },
        "EnableCrossAccountsDiscovery": {
          "target": "com.amazonaws.licensemanager#BoxBoolean",
          "traits": {
            "smithy.api#documentation": "<p>Activates cross-account discovery.</p>"

      }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanager#UpdateServiceSettingsResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanager#UsageOperation": {
      "type": "string",
      "traits": {
        "smithy.api#length": {
```

```
                "min": 0,
                "max": 50
            }
        }
    },
    "com.amazonaws.licensemanager#ValidationException": {
        "type": "structure",
        "members": {
            "Message": {
                "target": "com.amazonaws.licensemanager#Message"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",

     "smithy.api#error": "client",
            "smithy.api#httpError": 400
        }
    }
  }
}
```


1.81 go-urn 1.4.0

1.81.1 Available under license :

MIT License

Copyright (c) 2018 Leonardo Di Donato

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
 WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.82 githubcommailrueasyjson 0.9.0

1.82.1 Available under license :

Copyright (c) 2016 Mail.Ru Group

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.83 mod 0.26.0

1.83.1 Available under license :

Copyright 2009 The Go Authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google LLC nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE

FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.84 github.com/gabriel-vasile/mimetype 1.4.9

1.84.1 Available under license :

MIT License

Copyright (c) 2018 Gabriel Vasile

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.85 busybox 1.37.0-r13

1.85.1 Available under license :

bzip2 applet in busybox is based on lightly-modified source
of bzip2 version 1.0.4. bzip2 source is distributed
under the following conditions (copied verbatim from LICENSE file)
==

This program, "bzip2", the associated library "libbzip2", and all
documentation, are copyright (C) 1996-2006 Julian R Seward. All
rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

2. The origin of this software must not be misrepresented; you must
  not claim that you wrote the original software. If you use this
  software in a product, an acknowledgment in the product
  documentation would be appreciated but is not required.

3. Altered source versions must be plainly marked as such, and must
  not be misrepresented
 as being the original software.

4. The name of the author may not be used to endorse or promote
  products derived from this software without specific prior written
  permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS
OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, Cambridge, UK.
jseward@bzip.org
bzip2/libbzip2 version 1.0.4 of 20 December 2006
--- A note on GPL versions

BusyBox is distributed under version 2 of the General Public License (included
in its entirety, below). Version 2 is the only version of this license which
this version of BusyBox (or modified versions derived from this one) may be
distributed under.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's
software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for
a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software

patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent
this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this
License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and
copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices

stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three

years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed
under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the
executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or
its derivative works. These actions are
prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict
the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity
of the free software distribution system, which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among

countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make
exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED
ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of
 Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

1.86 musl 1.2.5-r9

1.86.1 Available under license :

musl as a whole is licensed under the following standard MIT license:

Copyright 2005-2020 Rich Felker, et al.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
 LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Authors/contributors include:

A. Wilcox
Ada Worcester
Alex Dowad
Alex Suykov
Alexander Monakov
Andre McCurdy
Andrew Kelley
Anthony G. Basile
Aric Belsito
Arvid Picciani
Bartosz Brachaczek
Benjamin Peterson
Bobby Bingham
Boris Brezillon
Brent Cook
Chris Spiegel
Clment Vasseur
Daniel Micay
Daniel Sabogal
Daurnimator
David Carlier
David Edelsohn
Denys Vlasenko
Dmitry Ivanov
Dmitry V. Levin
Drew DeVault
Emil Renner Berthing
Fangrui Song
Felix Fietkau
Felix Janda
Gianluca Anzolin
Hauke Mehrtens
He X
Hiltjo Posthuma
Isaac Dunham
Jaydeep Patil
Jens Gustedt
Jeremy Huntwork
Jo-Philipp Wich
Joakim Sindholt
John Spencer
Julien Ramseier
Justin Cormack
Kaarle Ritvanen
Khem Raj
Kylie McClain
Leah Neukirchen

Luca Barbato
Luka
Perkov
M Farkas-Dyck (Strake)
Mahesh Bodapati
Markus Wichmann
Masanori Ogino
Michael Clark
Michael Forney
Mikhail Kremnyov
Natanael Copa
Nicholas J. Kain
orc
Pascal Cuoq
Patrick Oppenlander
Petr Hosek
Petr Skocik
Pierre Carrier
Reini Urban
Rich Felker
Richard Pennington
Ryan Fairfax
Samuel Holland
Segev Finer
Shiz
sin
Solar Designer
Stefan Kristiansson
Stefan O'Rear
Szabolcs Nagy
Timo Ters
Trutz Behn
Valentin Ochs
Will Dietz
William Haddon
William Pitcock

Portions of this software are derived from third-party works licensed under terms compatible with the above MIT license:

The TRE regular expression implementation (src/regex/reg* and src/regex/tre*) is Copyright 2001-2008 Ville Laurikari and licensed under a 2-clause BSD license (license text in the source files). The included version has been heavily modified by Rich Felker in 2012, in the interests of size, simplicity, and namespace cleanliness.

Much of the math library code (src/math/* and src/complex/*) is Copyright 1993,2004

Sun Microsystems or
Copyright 2003-2011 David Schultz or
Copyright 2003-2009 Steven G. Kargl or
Copyright 2003-2009 Bruce D. Evans or
Copyright 2008 Stephen L. Moshier or
Copyright 2017-2018 Arm Limited
and labelled as such in comments in the individual source files. All
have been licensed under extremely permissive terms.

The ARM memcpy code (src/string/arm/memcpy.S) is Copyright 2008
The Android Open Source Project and is licensed under a two-clause BSD
license. It was taken from Bionic libc, used on Android.

The AArch64 memcpy and memset code (src/string/aarch64/*) are
Copyright 1999-2019, Arm Limited.

The implementation of DES for crypt (src/crypt/crypt_des.c) is
Copyright 1994 David Burren. It is licensed under a BSD license.

The implementation of blowfish crypt (src/crypt/crypt_blowfish.c) was
originally written by Solar Designer and placed into the public
domain. The code also comes with a fallback permissive license for use
in jurisdictions that may not recognize the
public domain.

The smoothsort implementation (src/stdlib/qsort.c) is Copyright 2011
Valentin Ochs and is licensed under an MIT-style license.

The x86_64 port was written by Nicholas J. Kain and is licensed under
the standard MIT terms.

The mips and microblaze ports were originally written by Richard
Pennington for use in the ellcc project. The original code was adapted
by Rich Felker for build system and code conventions during upstream
integration. It is licensed under the standard MIT terms.

The mips64 port was contributed by Imagination Technologies and is
licensed under the standard MIT terms.

The powerpc port was also originally written by Richard Pennington,
and later supplemented and integrated by John Spencer. It is licensed
under the standard MIT terms.

All other files which have no copyright comments are original works
produced specifically for use as part of this library, written either
by Rich Felker, the main author of the library, or by one or more
contibutors listed

above. Details on authorship of individual files
can be found in the git version control history of the project. The
omission of copyright and license comments in each file is in the
interest of source tree size.

In addition, permission is hereby granted for all public header files
(include/* and arch/*/bits/*) and crt files intended to be linked into
applications (crt/*, ldso/dlstart.c, and arch/*/crt_arch.h) to omit
the copyright notice and permission notice otherwise required by the
license, and to use these files without any requirement of
attribution. These files include substantial contributions from:

Bobby Bingham
John Spencer
Nicholas J. Kain
Rich Felker
Richard Pennington
Stefan Kristiansson
Szabolcs Nagy

all of whom have explicitly granted such permission.

This file previously contained text expressing a belief that most of
the files covered by the above exception were sufficiently trivial not
to be subject to copyright, resulting in confusion over whether it
negated
the permissions granted in the license. In the spirit of
permissive licensing, and of not having licensing issues being an
obstacle to adoption, that text has been removed.

1.87 github.com/aws/aws-sdk-go-v2/internal/endpoints/v2 2.7.2

1.87.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput

```
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement
```

```
// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string
```

```
// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
```

```
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
```

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop

Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection

```
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string
```

```
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
```

```
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
```

```
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
  }
 }
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
```

```
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
```

```
//
//   - Fingerprint
//
//   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
```

```
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
```

```
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
```

```
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)
```

```
// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
```

```
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
```

```
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options);
err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
```

```
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
```

```
GetLicenseOutput struct {

// License details.
License *types.License

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
```

```
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
```

```
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {
```

```
//
Checkout type.
//
// This member is required.
CheckoutType types.CheckoutType

// Unique, case-sensitive identifier that you provide to ensure the idempotency of
// the request.
//
// This member is required.
ClientToken *string

// License entitlements.
//
// This member is required.
Entitlements []types.EntitlementData

// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
```

```
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
```

```
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
```

```
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
```

```
            },

        {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/DeregisterSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The type of name to filter by.</p>"
            }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

        "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
```

```
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
             }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
        },
        "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
      "type": "structure",
      "members": {
        "AmiId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
        },
        "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
        },
        "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
        },
        "AccountID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
```

```
            "Region": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
               }
            },
            "UsageOperation": {
               "target": "smithy.api#String",

   "traits": {
                  "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
               }
            },
            "ProductCode": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
               "traits": {
                  "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
               }
            },
            "LastUpdatedTime": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
               }
            },
            "SubscriptionName": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
               }
            },
            "OsVersion": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
               }
            },
            "SubscriptionProviderCreateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp when you registered
```

```
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
                }
            },
            "SubscriptionProviderUpdateTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
                }
            },
            "DualSubscription": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
                }
            },
            "RegisteredWithSubscriptionProvider": {
                "target": "smithy.api#String",
                "traits": {

      "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
```

```
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
       },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
      }
    ],
    "traits": {
      "aws.api#service": {
        "sdkId": "License Manager Linux Subscriptions",
         "arnNamespace": "license-manager-linux-subscriptions",
        "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
      },
      "aws.auth#sigv4": {
        "name": "license-manager-linux-subscriptions"
```

```
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
```

```
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }

],
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]
```

```
}
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },
                  "properties": {},
                  "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"

          }
          ],
          "type": "tree"
        },
        {
          "conditions": [],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {

          "fn": "aws.partition",
                        "argv": [
                          {
                            "ref": "Region"
                          }
                        ],
```

```
                "assign": "PartitionResult"
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {

                    "ref": "UseFIPS"
                            },
                            true
                        ]
                    },
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }

],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

            },
                                        "supportsFIPS"
                                    ]
                                }
                            ]
                        },
                        {
                            "fn": "booleanEquals",
```

```
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [

                     {
                          "ref": "PartitionResult"
                       },
                       "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [],

    "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],

            "type": "tree"
                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
```

```
            "conditions": [
                                {
                                   "fn": "booleanEquals",
                                   "argv": [
                                      {
                                         "ref": "UseFIPS"
                                      },
                                      true
                                   ]
                                }
                             ],
                             "rules": [
                                {
                                   "conditions": [
                                      {

                          "fn": "booleanEquals",
                                         "argv": [
                                            {
                                               "fn": "getAttr",
                                               "argv": [
                                                  {
                                                     "ref": "PartitionResult"
                                                  },
                                                  "supportsFIPS"
                                               ]
                                            },
                                            true

                                      ]
                                         }
                                      ],
                                      "rules": [
                                         {
                                            "conditions": [],
                                            "rules": [
                                               {
                                                  "conditions": [],
                                                  "endpoint": {
                                                     "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                                     "headers": {}
                                                  },
                                                  "type": "endpoint"
                                               }
                                            ],
```

```
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS is enabled
but this partition does not support FIPS",
            "type": "error"
        }
    ],
    "type": "tree"
},
{
    "conditions": [
        {
            "fn": "booleanEquals",
            "argv": [
                {
                    "ref": "UseDualStack"
                },
                true

            ]
        }
    ],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [
                                {

                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }
                    ]
                }
            ],
            "rules": [
```

```
                                        {
                                            "conditions": [],
                                            "rules": [

        {
                                                    "conditions": [],
                                                    "endpoint": {
                                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                        "properties": {},
                                                        "headers": {}
                                                    },
                                                    "type": "endpoint"
                                                }
                                            ],
                                            "type": "tree"

                                }
                                    ],
                                    "type": "tree"
                                },
                                {
                                    "conditions": [],
                                    "error": "DualStack is enabled but this partition does not support DualStack",
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"
                        }
                    ],
                    "type": "tree"
```

```
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
            }
        ],
        "type": "tree"
    }
  ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
```

```
                "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
              }

        },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
```

```
            }

        },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

       "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
```

```
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
       }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "error": "DualStack is enabled but this partition does not support DualStack"
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {

   "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
      }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
    "expect": {
      "endpoint": {
        "url": "https://example.com"
      }
```

```
    },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://example.com"
                  }
                },
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

 "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
```

```
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

        },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

 {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n        <li>\n  <p>\n            <code>AccountID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n    <code>AmiID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>DualSubscription</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceType</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>ProductCode</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Region</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Status</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>UsageOperation</code>\n          </p>\n        </li>\n      </ul>\n      <p>For each filter, you can use one of the following <code>Operator</code>\n values to \n  \t\tdefine the behavior of the filter:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
```

```
            "Instances": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
               "traits": {
                  "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
               }
            },
            "NextToken": {

         "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
```

```
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n
<li>\n              <p>\n                <code>Subscription</code>\n              </p>\n            </li>\n          </ul>\n
<p>The
 valid Operators for this filter are:</p>\n          <ul>\n            <li>\n              <p>\n
<code>contains</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>equals</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>Notequal</code>\n              </p>\n            </li>\n          </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
      "type": "structure",
      "members": {
        "Subscriptions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
```

```
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "RegisteredSubscriptionProviders"
            }
         }

      },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
         "type": "structure",
         "members": {
            "SubscriptionProviderSources": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
               "traits": {
                  "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }

    },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
       },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
         "type": "structure",
         "members": {
            "RegisteredSubscriptionProviders": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
```

```
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
          }
        },
        "SubscriptionProviderArn": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
          }
        },
```

```
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
               }
            },
            "SubscriptionProviderStatusMessage": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
               }
            },
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

  }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
                    "documentation": "Failed status"
                }
            ]
        }
    },

   "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
            }
          },
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            },
            "smithy.api#uniqueItems": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
          "type": "map",
          "key": {
            "target": "smithy.api#String"
          },
          "value": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
          "type": "structure",
          "members": {
            "Name":
{
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the subscription.</p>"
              }
            },
            "Type": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
              }
            },
            "InstanceCount": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
              "traits": {
                "smithy.api#documentation": "<p>The total amount of running instances using this
```

```
subscription.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
              ]
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
```

```
            },
            {
              "name": "INVALID",
              "value": "INVALID",

"documentation": "INVALID status"
            },
            {
              "name": "PENDING",
              "value": "PENDING",
              "documentation": "PENDING status"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
         },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
```

```
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
{
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
         "type": "map",
         "key": {
            "target": "smithy.api#String"
         },
```

```
        "value": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
             "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
         "type": "structure",
         "members": {
            "LinuxSubscriptionsDiscovery": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
               "traits": {
                  "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                  "smithy.api#required": {}
               }
            },
            "LinuxSubscriptionsDiscoverySettings": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
               "traits": {
                  "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                  "smithy.api#required": {}
               }
            },
            "AllowUpdate": {
               "target":
 "smithy.api#Boolean",
               "traits": {
                  "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
               }
            }
         }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
           "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
          }
        },
        "StatusMessage": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
          "traits": {
            "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
          }

     },
        "HomeRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
```

```
            "traits": {
                "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
```

```
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string
```

```
 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string
```

```
// License status.
Status types.LicenseDeletionStatus

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
        "type": "structure",
        "members": {
            "DirectoryId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
                "traits": {
                    "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
                }
            },
            "ActiveDirectorySettings":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
                }
            },
            "ActiveDirectoryType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
```

```
            },
            "DomainIpv4List": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 2
                  }
               }
            },
            "DomainCredentialsProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
               }
            },
            "DomainNetworkSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
               },
               {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
               }
```

```
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
```

```
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http":
 {
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
                }
            }
```

```
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
```

```
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
         "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
```

```
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
            "smithy.api#length": {
              "min": 1
            },

  "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Attribute": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
          }
        },
        "Operation": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
          }
        },
        "Value": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>Value of the filter.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
```

```
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
          },
          "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
              }
            },
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

    "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details \n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance user.</p>"
             }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
```

```
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
             "smithy.api#error": "server",
            "smithy.api#httpError": 500
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
```

```
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
},
{
```

```
    "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
          ],
          "traits": {
            "aws.api#service": {
              "sdkId": "License Manager User Subscriptions",
              "arnNamespace": "license-manager-user-subscriptions",
              "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
              "name": "license-manager-user-subscriptions"
            },
            "aws.protocols#restJson1": {},
            "smithy.api#cors": {
              "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",

           "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
              ],
              "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
              ]
            },
            "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to
utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager User Subscriptions",
            "smithy.rules#endpointRuleSet": {
              "version": "1.0",
              "parameters": {
                "Region":
{
                  "builtIn": "AWS::Region",
                  "required": false,
                  "documentation": "The AWS region used to dispatch the request.",
```

```
            "type": "String"
        },
        "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
            "type": "Boolean"
        },
        "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
        },
        "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
```

```
                ]
              }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [
              {

                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "endpoint": {
              "url": {
                "ref": "Endpoint"
              },

"properties": {},
                "headers": {}
              },
              "type": "endpoint"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
            {
              "fn": "isSet",
              "argv": [
                {
                  "ref": "Region"
                }
              ]
            }
          ],
```

```
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "aws.partition",

                       "argv": [
                            {
                              "ref": "Region"
                            }
                          ],
                          "assign": "PartitionResult"
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseFIPS"
                              },

true
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseDualStack"
                              },
                              true
                            ]
                          }
                        ],
                        "rules": [
                          {
                            "conditions": [
                              {

"fn": "booleanEquals",
                                  "argv": [
                                    true,
                                    {
                                      "fn": "getAttr",
                                      "argv": [
```

```
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            }
                        ]
                    },

                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [
                                {
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }

            ]
                }
            ],
            "rules": [
                {
                    "conditions": [],
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }

    ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
            "type": "error"
        }
    ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [

{
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
```

```
                    },
                    {
                      "conditions": [],
                      "error": "FIPS is enabled but this partition does not support FIPS",
                      "type": "error"

}
                  ],
                  "type": "tree"
                },
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseDualStack"
                        },
                        true
                      ]
                    }
                  ],
                  "rules": [
                    {

    "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            true,
                            {
                              "fn": "getAttr",
                              "argv": [
                                {
                                  "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                              ]

    }
                            ]
                          }
                        ],
                        "rules": [
                          {
                            "conditions": [],
                            "endpoint": {
                              "url": "https://license-manager-user-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

                            ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
```

```
{
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",

      "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint":
{
                        "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",
```

```
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
         "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
```

```
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
```

```
      },
      "params": {
        "Region": "us-isob-east-1",

  "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

       "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
```

```
false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                    "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
    }
  }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
  "type": "structure",
  "members": {
    "ProvisioningStatus": {
      "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
       "traits": {
         "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
```

```
\n\t\t\tlicense server.</p>"
                }
            },
            "HealthStatus": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
                }
            },
            "Ipv4Address": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

  "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
        },
        "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
        },
        "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
        },
        "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
        },
        "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
        },

       "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
        }
    },
    "traits": {
      "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
    }
  },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
      "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
      "type": "structure",
      "members": {
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>",
            "smithy.api#required": {}
          }
        },
        "ServerSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
            "smithy.api#required": {}
          }
        }
      },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {

        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/identity-provider/ListIdentityProviders"
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
```

```
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
```

contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria. "
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/ListLicenseServerEndpoints"
            },

          "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
          "type": "structure",
          "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                 "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
```

```
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
             "traits": {
               "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                 "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
```

```
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n            <p>Status</p>\n            </li>\n            <li>\n            <p>Username</p>\n
</li>\n            <li>\n            <p>Domain</p>\n            </li>\n            </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

         }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
```

```
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {

    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
```

```
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
         "type": "structure",
         "members": {
            "IdentityProvider": {

     "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                  "smithy.api#required": {}
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
               "traits":
```

```
{
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",
```

```
    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
            "smithy.api#length": {

             "min": 5,
                "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
            "Endpoint": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
             "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
```

```
                "smithy.api#length": {
                    "min": 1
                },
                "smithy.api#required": {}
            }
        },
        "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
            }

    }
     },
     "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n        <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
```

```
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
              }
            },
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
          "type": "structure",
          "members": {
            "ProductUserSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                "smithy.api#required": {}
              }

    }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StringList": {
          "type": "list",
          "member": {
```

```
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
```

```
        "traits": {
          "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
```

```
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

           "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
```

configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the: \n \n \n Subnets which you want to add to provision VPC endpoints. \n \n \n Subnets which you want to remove the VPC endpoints from. \n \n \n Security
group ID which permits traffic to the VPC endpoints. \n \n ",
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
"type": "structure",
"members": {
"IdentityProviderSummary": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
"traits": {
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
"type": "structure",
"members": {
"AddSubnets": {

"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets in which License Manager will create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers. ",
"smithy.api#required": {}
}
},
"RemoveSubnets": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets to remove. ",
"smithy.api#required": {}
}
},
"SecurityGroupId": {
"target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

```
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if
```

```
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
```

Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.88 depth 1.2.1

1.88.1 Available under license :

BSD 3-Clause License

Copyright (c) 2017, News UK & Ireland Ltd
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the copyright holder nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED.
IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE

OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.89 github.com/hashicorp/golang-lru/v2 2.0.7

1.89.1 Available under license :

Copyright (c) 2014 HashiCorp, Inc.

Mozilla Public License, version 2.0

1. Definitions

1.1. "Contributor"

means each individual or legal entity that creates, contributes to the creation of, or owns Covered Software.

1.2. "Contributor Version"

means the combination of the Contributions of others (if any) used by a Contributor and that particular Contributor's Contribution.

1.3. "Contribution"

means Covered Software of a particular Contributor.

1.4. "Covered Software"

means Source Code Form to which the initial Contributor has attached the notice in Exhibit A, the Executable Form of such Source Code Form, and Modifications of such Source Code Form, in each case including portions thereof.

1.5. "Incompatible With Secondary Licenses"
means

a. that the initial Contributor has attached the notice described in Exhibit B to the Covered Software; or

b. that the Covered Software was made available under the terms of version 1.1 or earlier of the License, but not also under the terms of a Secondary License.

1.6. "Executable Form"

means any form of the work other than Source Code Form.

1.7. "Larger Work"

means a work that combines Covered Software with other material, in a separate file or files, that is not Covered Software.

1.8. "License"

means this document.

1.9. "Licensable"

means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently, any and all of the rights conveyed by this License.

1.10. "Modifications"

means any of the following:

a. any file in Source Code Form that results from an addition to, deletion from, or modification of the contents of Covered Software; or

b. any new file in Source Code Form that contains any Covered Software.

1.11. "Patent Claims" of a Contributor

means any patent claim(s), including without limitation, method, process, and apparatus claims, in any patent Licensable by such Contributor that would be infringed, but for the grant of the License, by the making, using, selling, offering for sale, having made, import, or transfer of either its Contributions or its Contributor Version.

1.12. "Secondary License"

means either the GNU General Public License, Version 2.0, the GNU Lesser General Public License, Version 2.1, the GNU Affero General Public License, Version 3.0, or any later versions of those licenses.

1.13. "Source Code Form"

means the form of the work preferred for making modifications.

1.14. "You" (or "Your")

means an individual or a legal entity exercising rights under this License. For legal entities, "You" includes any entity that controls, is controlled by, or is under common control with You. For purposes of this definition, "control" means (a) the power, direct or indirect, to cause

the direction or
management of such entity, whether by contract or
otherwise, or (b) ownership of more than fifty percent (50%) of the
outstanding shares or beneficial ownership of such entity.

2. License Grants and Conditions

2.1. Grants

Each Contributor hereby grants You a world-wide, royalty-free,
non-exclusive license:

a. under intellectual property rights (other than patent or trademark)
Licensable by such Contributor to use, reproduce, make available,
modify, display, perform, distribute, and otherwise exploit its
Contributions, either on an unmodified basis, with Modifications, or
as part of a Larger Work; and

b. under Patent Claims of such Contributor to make, use, sell, offer for
sale, have made, import, and otherwise transfer either its
Contributions or its Contributor Version.

2.2. Effective Date

The licenses granted in Section 2.1 with respect to any Contribution
become effective for each Contribution
on the date the Contributor first
distributes such Contribution.

2.3. Limitations on Grant Scope

The licenses granted in this Section 2 are the only rights granted under
this License. No additional rights or licenses will be implied from the
distribution or licensing of Covered Software under this License.
Notwithstanding Section 2.1(b) above, no patent license is granted by a
Contributor:

a. for any code that a Contributor has removed from Covered Software; or

b. for infringements caused by: (i) Your and any other third party's
modifications of Covered Software, or (ii) the combination of its
Contributions with other software (except as part of its Contributor
Version); or

c. under Patent Claims infringed by Covered Software in the absence of
its Contributions.

This License does not grant any rights in the trademarks, service marks, or logos of any Contributor (except as may be necessary to comply with the notice requirements in Section 3.4).

2.4. Subsequent Licenses

No Contributor makes additional grants as a result of Your choice to distribute the Covered Software under a subsequent version of this License (see Section 10.2) or under the terms of a Secondary License (if permitted under the terms of Section 3.3).

2.5. Representation

Each Contributor represents that the Contributor believes its Contributions are its original creation(s) or it has sufficient rights to grant the rights to its Contributions conveyed by this License.

2.6. Fair Use

This License is not intended to limit any rights You have under applicable copyright doctrines of fair use, fair dealing, or other equivalents.

2.7. Conditions

Sections 3.1, 3.2, 3.3, and 3.4 are conditions of the licenses granted in Section 2.1.

3. Responsibilities

3.1. Distribution of Source Form

All distribution of Covered Software in Source Code Form, including any Modifications that You create or to which You contribute, must be under the terms of this License. You must inform recipients that the Source Code Form of the Covered Software is governed by the terms of this License, and how they can obtain a copy of this License. You may not attempt to alter or restrict the recipients' rights in the Source Code Form.

3.2. Distribution of Executable Form

If You distribute Covered Software in Executable Form then:

a. such Covered Software must also be made available in Source Code Form,

as described in Section 3.1, and You must inform recipients of the Executable Form how they can obtain a copy of such Source Code Form by reasonable means in a timely manner, at a charge no more than the cost of distribution to the recipient; and

b. You may distribute such Executable Form under the terms of this License, or sublicense it under different terms, provided that the license for the Executable Form does not attempt to limit or alter the recipients' rights in the Source Code Form under this License.

3.3. Distribution of a Larger Work

You may create and distribute a Larger Work under terms of Your choice, provided that You also comply with the requirements of this License for the Covered Software. If the Larger Work is a combination of Covered Software with a work governed by one or more Secondary Licenses, and the Covered Software is not Incompatible With Secondary Licenses, this License permits You to additionally distribute such Covered Software under the terms of such Secondary License(s), so that the recipient of the Larger Work may, at their option, further distribute the Covered Software under the terms of either this License or such Secondary License(s).

3.4. Notices

You may not remove or alter the substance of any license notices (including copyright notices, patent notices, disclaimers of warranty, or limitations of liability) contained within the Source Code Form of the Covered Software, except that You may alter any license notices to the extent required to remedy known factual inaccuracies.

3.5. Application of Additional Terms

You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, You may do so only on Your own behalf, and not on behalf of any Contributor. You must make it absolutely clear that any such warranty, support, indemnity, or liability obligation is offered by You alone, and You hereby agree to indemnify every Contributor for any liability incurred by such Contributor as a result of warranty, support, indemnity or liability terms You offer. You may include additional disclaimers of warranty and limitations of liability specific to any jurisdiction.

4.

Inability to Comply Due to Statute or Regulation

If it is impossible for You to comply with any of the terms of this License with respect to some or all of the Covered Software due to statute, judicial order, or regulation then You must: (a) comply with the terms of this License to the maximum extent possible; and (b) describe the limitations and the code they affect. Such description must be placed in a text file included with all distributions of the Covered Software under this License. Except to the extent prohibited by statute or regulation, such description must be sufficiently detailed for a recipient of ordinary skill to be able to understand it.

5. Termination

5.1. The rights granted under this License will terminate automatically if You fail to comply with any of its terms. However, if You become compliant, then the rights granted under this License from a particular Contributor are reinstated (a) provisionally, unless and
until such Contributor
explicitly and finally terminates Your grants, and (b) on an ongoing basis, if such Contributor fails to notify You of the non-compliance by some reasonable means prior to 60 days after You have come back into compliance. Moreover, Your grants from a particular Contributor are reinstated on an ongoing basis if such Contributor notifies You of the non-compliance by some reasonable means, this is the first time You have received notice of non-compliance with this License from such Contributor, and You become compliant prior to 30 days after Your receipt of the notice.

5.2. If You initiate litigation against any entity by asserting a patent infringement claim (excluding declaratory judgment actions, counter-claims, and cross-claims) alleging that a Contributor Version directly or indirectly infringes any patent, then the rights granted to You by any and all Contributors for the Covered Software under
Section
2.1 of this License shall terminate.

5.3. In the event of termination under Sections 5.1 or 5.2 above, all end user license agreements (excluding distributors and resellers) which have been validly granted by You or Your distributors under this License prior to termination shall survive termination.

6. Disclaimer of Warranty

Covered Software is provided under this License on an "as is" basis, without warranty of any kind, either expressed, implied, or statutory, including, without limitation, warranties that the Covered Software is free of defects, merchantable, fit for a particular purpose or non-infringing.

The entire risk as to the quality and performance of the Covered Software is with You. Should any Covered Software prove defective in any respect, You (not any Contributor) assume the cost of any necessary servicing, repair, or correction. This disclaimer of warranty constitutes an essential part of this License. No use of any Covered Software is authorized under this License except under this disclaimer.

7. Limitation of Liability

Under no circumstances and under no legal theory, whether tort (including negligence), contract, or otherwise, shall any Contributor, or anyone who distributes Covered Software as permitted above, be liable to You for any direct, indirect, special, incidental, or consequential damages of any character including, without limitation, damages for lost profits, loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses, even if such party shall have been informed of the possibility of such damages. This limitation of liability shall not apply to liability for death or personal injury resulting from such party's negligence to the extent applicable law prohibits such limitation. Some jurisdictions do not allow the exclusion or limitation of incidental or consequential damages, so this exclusion and limitation may not apply to You.

8. Litigation

Any litigation relating to this License may be brought only in the courts of a jurisdiction where the defendant maintains its principal place of business and such litigation shall be governed by laws of that jurisdiction, without reference to its conflict-of-law provisions. Nothing in this Section shall prevent a party's ability to bring cross-claims or counter-claims.

9. Miscellaneous

This License represents the complete agreement concerning the subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. Any law or regulation which provides that the language of a contract shall be construed against the drafter shall not be used to construe this License against a Contributor.

10. Versions of the License

10.1. New Versions

Mozilla Foundation is the license steward.
Except as provided in Section
10.3, no one other than the license steward has the right to modify or publish new versions of this License. Each version will be given a distinguishing version number.

10.2. Effect of New Versions

You may distribute the Covered Software under the terms of the version of the License under which You originally received the Covered Software, or under the terms of any subsequent version published by the license steward.

10.3. Modified Versions

If you create software not governed by this License, and you want to create a new license for such software, you may create and use a modified version of this License if you rename the license and remove any references to the name of the license steward (except to note that such modified license differs from this License).

10.4. Distributing Source Code Form that is Incompatible With Secondary Licenses If You choose to distribute Source
Code Form that is
Incompatible With Secondary Licenses under the terms of this version of the License, the notice described in Exhibit B of this License must be attached.

Exhibit A - Source Code Form License Notice

This Source Code Form is subject to the
terms of the Mozilla Public License, v.
2.0. If a copy of the MPL was not
distributed with this file, You can
obtain one at
http://mozilla.org/MPL/2.0/.

If it is not possible or desirable to put the notice in a particular file, then You may include the notice in a location (such as a LICENSE file in a relevant directory) where a recipient would be likely to look for such a notice.

You may add additional accurate notices of copyright ownership.

Exhibit B - "Incompatible With Secondary Licenses" Notice

This Source Code Form is "Incompatible
With Secondary Licenses", as defined by

the Mozilla Public License, v. 2.0.
This license applies to simplelru/list.go

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.90 aws-sdk-go-v2-service-internal-presigned-url 1.13.2

1.90.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step

```
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
name: License Scan

on: [pull_request]

jobs:
 licensescan:
```

```
  name: License Scan
  runs-on: ubuntu-latest
  strategy:
    matrix:
      python-version: [3.9]

  steps:
    - name: Checkout target
      uses: actions/checkout@v2
      with:
        path: sdkbase
        ref: ${{ github.base_ref }}
    - name: Checkout this ref
      uses: actions/checkout@v2
      with:
        path: new-ref
        fetch-depth: 0
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
       uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.
```

```
package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
```

ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde

```
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
```

```
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
```

```
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
```

InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step

spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent

```
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
```

```
 params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
```

```
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return
err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if
err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}
```

```
func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
```

```
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
```

```
//
//   - ProductSKU
//
//   - Fingerprint
//
//   - Status
Filters
[]types.Filter

// Amazon Resource Names (ARNs) of the licenses.
LicenseArns []string

// Maximum number of results to return in a single call.
MaxResults *int32

// Token for the next set of results.
NextToken *string

noSmithyDocumentSerde
}

type ListLicensesOutput struct {

// License details.
Licenses []types.License

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack,
```

```
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
```

```
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
```

```
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
```

```
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
```

```
 ServiceID:     ServiceID,
 OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}
```

```
type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
```

```
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
```

```
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
```

```
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {
```

```
//
Checkout type.
//
// This member is required.
CheckoutType types.CheckoutType

// Unique, case-sensitive identifier that you provide to ensure the idempotency of
// the request.
//
// This member is required.
ClientToken *string

// License entitlements.
//
// This member is required.
Entitlements []types.EntitlementData

// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string
```

```
// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
```

```
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
```

```
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
```

```
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },

    {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
            }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

        "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
```

```
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
             }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
        },
        "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
      "type": "structure",
      "members": {
        "AmiId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
        },
        "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
        },
        "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
        },
        "AccountID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
```

```
            "Region": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
               }
            },
            "UsageOperation": {
               "target": "smithy.api#String",

   "traits": {
                  "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
               }
            },
            "ProductCode": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
               "traits": {
                  "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
               }
            },
            "LastUpdatedTime": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
               }
            },
            "SubscriptionName": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
               }
            },
            "OsVersion": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
               }
            },
            "SubscriptionProviderCreateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp when you registered
```

```
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
                }
            },
            "SubscriptionProviderUpdateTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
                }
            },
            "DualSubscription": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
                }
            },
            "RegisteredWithSubscriptionProvider": {
                "target": "smithy.api#String",
                "traits": {

      "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
```

```
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
       },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
      }
    ],
    "traits": {
      "aws.api#service": {
        "sdkId": "License Manager Linux Subscriptions",
         "arnNamespace": "license-manager-linux-subscriptions",
        "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
      },
      "aws.auth#sigv4": {
        "name": "license-manager-linux-subscriptions"
```

```
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
```

```
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }

],
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]
```

```
}
                        ],
                        "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                        "type": "error"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": {
                                "ref": "Endpoint"
                            },
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],
                "type": "tree"

            }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "isSet",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {

            "fn": "aws.partition",
                                    "argv": [
                                        {
                                            "ref": "Region"
                                        }
                                    ],
```

```
                "assign": "PartitionResult"
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {

                    "ref": "UseFIPS"
                            },
                            true
                        ]
                    },
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }

],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

        },
                                    "supportsFIPS"
                                ]
                            }
                        ]
                    },
                    {
                        "fn": "booleanEquals",
```

```
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [

                     {
                          "ref": "PartitionResult"
                       },
                       "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [],

    "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],

            "type": "tree"
                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
```

```
            "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
                    true
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {

          "fn": "booleanEquals",
                      "argv": [
                        {
                          "fn": "getAttr",
                          "argv": [
                            {
                              "ref": "PartitionResult"
                            },
                            "supportsFIPS"
                          ]
                        },
                        true

                    ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "rules": [
                        {
                          "conditions": [],
                          "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                            "headers": {}
                          },
                          "type": "endpoint"
                        }
                      ],
```

```
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS is enabled
but this partition does not support FIPS",
            "type": "error"
        }
    ],
    "type": "tree"
},
{
    "conditions": [
        {
            "fn": "booleanEquals",
            "argv": [
                {
                    "ref": "UseDualStack"
                },
                true

            ]
        }
    ],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [
                                {

                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }
                    ]
                }
            ],
            "rules": [
```

```
                                        {
                                            "conditions": [],
                                            "rules": [

        {
                                                    "conditions": [],
                                                    "endpoint": {
                                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                        "properties": {},
                                                        "headers": {}
                                                    },
                                                    "type": "endpoint"
                                                }
                                            ],
                                            "type": "tree"

                                }
                                    ],
                                    "type": "tree"
                                },
                                {
                                    "conditions": [],
                                    "error": "DualStack is enabled but this partition does not support DualStack",
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"
                        }
                    ],
                    "type": "tree"
```

```
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
            }
        ],
        "type": "tree"
    }
  ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
```

```
                "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
              }

        },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
```

```
            }

        },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

      "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
```

```
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
       }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "error": "DualStack is enabled but this partition does not support DualStack"
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {

   "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
      }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
    "expect": {
      "endpoint": {
        "url": "https://example.com"
      }
```

```
    },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://example.com"
                  }
                },
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

 "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
```

```
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

        },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

 {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n        <li>\n  <p>\n            <code>AccountID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n    <code>AmiID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>DualSubscription</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceType</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>ProductCode</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Region</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Status</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>UsageOperation</code>\n          </p>\n        </li>\n      </ul>\n      <p>For each filter, you can use one of the following <code>Operator</code>\n values to \n  \t\tdefine the behavior of the filter:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
```

```
            "Instances": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
               "traits": {
                  "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
               }
            },
            "NextToken": {

         "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
```

```
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n
<li>\n              <p>\n                  <code>Subscription</code>\n              </p>\n          </li>\n          </ul>\n
<p>The
 valid Operators for this filter are:</p>\n          <ul>\n          <li>\n              <p>\n
<code>contains</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>equals</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>Notequal</code>\n              </p>\n          </li>\n          </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
      "type": "structure",
      "members": {
        "Subscriptions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
      "type": "operation",
      "input": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
      },
      "output": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
```

```
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "RegisteredSubscriptionProviders"
            }
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
         "type": "structure",
         "members": {
            "SubscriptionProviderSources": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
               "traits": {
                  "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }

   },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
         "type": "structure",
         "members": {
            "RegisteredSubscriptionProviders": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
```

```
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
          }
        },
        "SubscriptionProviderArn": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
          }
        },
```

```
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
               }
            },
            "SubscriptionProviderStatusMessage": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
               }
            },
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

  }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
                    "documentation": "Failed status"
                }
            ]
        }
    },

   "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
            }
          },
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            },
            "smithy.api#uniqueItems": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
          "type": "map",
          "key": {
            "target": "smithy.api#String"
          },
          "value": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
          "type": "structure",
          "members": {
            "Name":
{
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the subscription.</p>"
              }
            },
            "Type": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
              }
            },
            "InstanceCount": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
              "traits": {
                "smithy.api#documentation": "<p>The total amount of running instances using this
```

```
subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
```

```
            },
            {
              "name": "INVALID",
              "value": "INVALID",

"documentation": "INVALID status"
            },
            {
              "name": "PENDING",
              "value": "PENDING",
              "documentation": "PENDING status"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
         },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
```

```
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
{
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
         "type": "map",
         "key": {
            "target": "smithy.api#String"
         },
```

```
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
           "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
          }
        },
        "StatusMessage": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
          "traits": {
            "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
          }

     },
        "HomeRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
```

```
            "traits": {
                "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
```

```
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string
```

```
 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string
```

```
// License status.
Status types.LicenseDeletionStatus

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
        "type": "structure",
        "members": {
            "DirectoryId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
                "traits": {
                    "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
                }
            },
            "ActiveDirectorySettings":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
                }
            },
            "ActiveDirectoryType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
```

```
            },
            "DomainIpv4List": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 2
                  }
               }
            },
            "DomainCredentialsProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
               }
            },
            "DomainNetworkSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
               },
               {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
               }
```

```
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
```

```
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http":
 {
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
                }
            }
```

```
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

         {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
```

```
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
```

```
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary":
{
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
            "smithy.api#length": {
              "min": 1
            },

  "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Attribute": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
          }
        },
        "Operation": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
          }
        },
        "Value": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>Value of the filter.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
```

```
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
          },
          "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
              }
            },
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

    "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details \n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance user.</p>"
             }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
```

```
            "target": "smithy.api#String",
             "traits": {
               "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
           "smithy.api#error": "server",
          "smithy.api#httpError": 500
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
```

```
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
},
{
```

```
    "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
          ],
          "traits": {
            "aws.api#service": {
              "sdkId": "License Manager User Subscriptions",
              "arnNamespace": "license-manager-user-subscriptions",
              "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
              "name": "license-manager-user-subscriptions"
            },
            "aws.protocols#restJson1": {},
            "smithy.api#cors": {
              "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",

           "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
              ],
              "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
              ]
            },
            "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to
utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager User Subscriptions",
            "smithy.rules#endpointRuleSet": {
              "version": "1.0",
              "parameters": {
                "Region":
{
                  "builtIn": "AWS::Region",
                  "required": false,
                  "documentation": "The AWS region used to dispatch the request.",
```

```
            "type": "String"
          },
          "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
            "type": "Boolean"
          },
          "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
          },
          "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
```

```
                    ]
                }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [
                {

                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": {
                    "ref": "Endpoint"
                },

"properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "isSet",
                "argv": [
                    {
                        "ref": "Region"
                    }
                ]
            }
        ],
```

```
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "aws.partition",

                       "argv": [
                            {
                              "ref": "Region"
                            }
                          ],
                          "assign": "PartitionResult"
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseFIPS"
                              },

true
                              ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseDualStack"
                              },
                              true
                            ]
                          }
                        ],
                        "rules": [
                          {
                            "conditions": [
                              {

"fn": "booleanEquals",
                                  "argv": [
                                    true,
                                    {
                                      "fn": "getAttr",
                                      "argv": [
```

```
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            }
                        ]
                    },

                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [
                                {
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }

            ]
                }
            ],
            "rules": [
                {
                    "conditions": [],
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }

    ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
            "type": "error"
        }
    ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [

{
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
```

```
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

}
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

    "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]

    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

                            ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
```

```
{
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",

        "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint":
{
                        "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",
```

```
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
         "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
```

```
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
```

```
        },
        "params": {
          "Region": "us-isob-east-1",

  "UseFIPS": false,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
          }
        },
        "params": {
          "Region": "us-isob-east-1",
          "UseFIPS": false,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
        "expect": {

         "endpoint": {
            "url": "https://example.com"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": false,
          "Endpoint": "https://example.com"
        }
      },
      {
        "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
        "expect": {
          "endpoint": {
            "url": "https://example.com"
          }
        },
        "params": {
          "UseFIPS": false,
          "UseDualStack":
```

```
false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                    "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
    }
  }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
  "type": "structure",
  "members": {
    "ProvisioningStatus": {
      "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
      "traits": {
        "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
```

```
\n\t\t\tlicense server.</p>"
                }
            },
            "HealthStatus": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
                }
            },
            "Ipv4Address": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

  "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
        },
        "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
        },
        "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
        },
        "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
        },
        "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
        },

       "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
        }
    },
    "traits": {
      "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
    }
  },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
      "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
      "type": "structure",
      "members": {
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>",
            "smithy.api#required": {}
          }
        },
        "ServerSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
            "smithy.api#required": {}
          }
        }
      },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {

        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/identity-provider/ListIdentityProviders"
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
```

```
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },

      {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
```

contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria. "
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": " The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/ListLicenseServerEndpoints"
            },

          "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
          "type": "structure",
          "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                 "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
```

```
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
             "traits": {
               "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                 "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
```

```
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n        <li>\n        <p>Status</p>\n        </li>\n        <li>\n        <p>Username</p>\n
</li>\n        <li>\n        <p>Domain</p>\n        </li>\n        </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

         }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
```

```
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {

    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
```

```
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
         "type": "structure",
         "members": {
            "IdentityProvider": {

     "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                  "smithy.api#required": {}
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
               "traits":
```

```
{
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",
```

```
    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
            "smithy.api#length": {

             "min": 5,
                "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
            "Endpoint": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
             "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
```

```
                "smithy.api#length": {
                    "min": 1
                },
                "smithy.api#required": {}
            }
        },
        "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
            }

    }
     },
     "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n        <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
```

```
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
              }
            },
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
          "type": "structure",
          "members": {
            "ProductUserSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                "smithy.api#required": {}
              }

    }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StringList": {
          "type": "list",
          "member": {
```

```
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
```

```
        "traits": {
          "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
```

```
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

           "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
            "smithy.api#http": {

      "code": 200,
                "method": "POST",
                "uri": "/identity-provider/UpdateIdentityProviderSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },

            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
                }
            },
            "UpdateSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
                "traits": {
                    "smithy.api#documentation": "<p>Updates the registered identity providers product related
```

configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the: \n \n \n Subnets which you want to add to provision VPC endpoints. \n \n \n Subnets which you want to remove the VPC endpoints from. \n \n \n Security
group ID which permits traffic to the VPC endpoints. \n \n ",
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
"type": "structure",
"members": {
"IdentityProviderSummary": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
"traits": {
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
"type": "structure",
"members": {
"AddSubnets": {

"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets in which License Manager will create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers. ",
"smithy.api#required": {}
}
},
"RemoveSubnets": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets to remove. ",
"smithy.api#required": {}
}
},
"SecurityGroupId": {
"target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

```
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if
```

```
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
    ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
```

Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.91 pax-utils 1.3.8-r1

1.91.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses
are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid

anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission
to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program
or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program

is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute
verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish,
that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work are not derived from the Program,
and can
be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based

on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled
to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based
on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit
royalty-free redistribution of the Program by
all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under

any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute
software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies
a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED
BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY
OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version
2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical
commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

1.92 githubcomgoopenapijsonreference 0.21.0

1.92.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain

separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without

modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include

the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.93 aws-sdk-go-v2-feature-ec2-imds 1.18.2

1.93.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd

```
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer

 // License name.
```

```
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
```

```
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
```

```
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
```

```
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
     - name: Run Scan code on pr ref
```

run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt

compare

- name: License test

run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi

CheckoutBorrowLicense

Initialize stack step

spanInitializeStart

InterceptExecution

RegisterServiceMetadata

legacyEndpointContextSetter

SetLogger

OperationInputValidation

spanInitializeEnd

Serialize stack step

spanBuildRequestStart

setOperationInput

ResolveEndpoint

InterceptBeforeSerialization

OperationSerializer

InterceptAfterSerialization

Build stack step

ClientRequestID

ComputeContentLength

SetCredentialSourceMiddleware

UserAgent

AddTimeOffsetMiddleware

RecursionDetection

spanBuildRequestEnd

Finalize stack step

spanRetryLoop

InterceptBeforeRetryLoop

Retry

InterceptAttempt

RetryMetricsHeader

ResolveAuthScheme

GetIdentity

ResolveEndpointV2

disableHTTPS

ComputePayloadHash

setLegacyContextSigningOptions

InterceptBeforeSigning

Signing

InterceptAfterSigning

Deserialize stack step

AddRawResponseToMetadata

ErrorCloseResponseBody

CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning

Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash

```
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
  - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
```

SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

```
package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32
```

```
 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
```

```
 return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
 return err
 }
 if err = addRetry(stack, options); err != nil {
 return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
 err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
```

```
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
```

```
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }
```

```
 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
```

```
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
```

```
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
```

```
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string
```

```
 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string
```

```
// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
        "type": "integer"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
        "type": "long"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
        "type": "operation",
        "input": {
           "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
        },
        "output": {
           "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
        },
        "errors": [
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
           },
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
           },

     {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
           },
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
           }
        ],
        "traits": {
           "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
```

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/DeregisterSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider
resource to deregister.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of name to filter by.</p>"
                 }
            },
            "Values": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
                }
            },
            "Operator": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
      "type":
 "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
      },
      "output": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
         },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/GetRegisteredSubscriptionProvider"
        },
```

```
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

          "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
```

```
last \n\t\t\tsuccessful subscription data request.</p>"
                }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"
```

```
        },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
      "type": "structure",
      "members": {
        "AmiId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
          }
        },
        "InstanceID": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
          }
        },
        "InstanceType": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>The instance type of the resource.</p>"
          }
        },
        "AccountID": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of the instance.</p>"
          }
        },
        "Region": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
          }
        },
        "UsageOperation": {
          "target": "smithy.api#String",

   "traits": {
            "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User
```

```
Guide</i>.</p>"
                }
            },
            "ProductCode": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
                "traits": {
                    "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a
href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-
operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
                }
            },
            "LastUpdatedTime": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The time in which the last discovery updated the instance
details.</p>"
                }
            },
            "SubscriptionName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
                }
            },
            "OsVersion": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
                }
            },
            "SubscriptionProviderCreateTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
                }
            },
            "SubscriptionProviderUpdateTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
                }
            },
            "DualSubscription": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for \n\t\t\tthe same software on your instance.</p>"
                }
            },
            "RegisteredWithSubscriptionProvider": {
                "target": "smithy.api#String",
                "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta third-party Linux subscription provider that you've registered with License Manager.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
        }
    ],
    "traits": {
        "aws.api#service": {
            "sdkId": "License Manager Linux Subscriptions",
            "arnNamespace": "license-manager-linux-subscriptions",
            "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
            "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
            "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
```

```
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
```

```
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }

    ],
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]

}
                        ],
                        "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                        "type": "error"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": {
                                "ref": "Endpoint"
                            },
                            "properties": {},
                            "headers": {}
                        },
```

```
                "type": "endpoint"
            }
          ],
          "type": "tree"

    }
     ],
    "type": "tree"
},
{
    "conditions": [],
    "rules": [
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Region"
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {

    "fn": "aws.partition",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ],
                  "assign": "PartitionResult"
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {

                    "ref": "UseFIPS"
                          },
                          true
```

```
            ]
          },
          {
            "fn": "booleanEquals",
            "argv": [
              {
                "ref": "UseDualStack"
              },
              true
            ]
          }

    ],
                "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    true,
                    {
                      "fn": "getAttr",
                      "argv": [
                        {
                          "ref": "PartitionResult"

        },
                        "supportsFIPS"
                      ]
                    }
                  ]
                },
                {
                  "fn": "booleanEquals",
                  "argv": [
                    true,
                    {
                      "fn": "getAttr",
                      "argv": [

                       {
                          "ref": "PartitionResult"
                        },
                        "supportsDualStack"
                      ]
                    }
                  ]
                }
```

```
                ],
                "rules": [
                    {
                        "conditions": [],

    "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],

                "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {

        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
```

```
                                    {

                            "fn": "booleanEquals",
                                        "argv": [
                                          {
                                            "fn": "getAttr",
                                            "argv": [
                                              {
                                                "ref": "PartitionResult"
                                              },
                                              "supportsFIPS"
                                            ]
                                          },
                                          true

                                      ]
                                        }
                                      ],
                                      "rules": [
                                        {
                                          "conditions": [],
                                          "rules": [
                                            {
                                              "conditions": [],
                                              "endpoint": {
                                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                                "headers": {}
                                              },
                                              "type": "endpoint"
                                            }
                                          ],
                                          "type": "tree"
                                        }
                                      ],
                                      "type": "tree"
                                    },
                                    {
                                      "conditions": [],
                                      "error": "FIPS is enabled
 but this partition does not support FIPS",
                                      "type": "error"
                                    }
                                  ],
                                  "type": "tree"
                                },
```

```
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseDualStack"
                        },
                        true

            ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            true,
                            {
                              "fn": "getAttr",
                              "argv": [
                                {

                                  "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                              ]
                            }
                          ]
                        }
                      ],
                      "rules": [
                        {
                          "conditions": [],
                          "rules": [

    {
                                "conditions": [],
                                "endpoint": {
                                  "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                  "properties": {},
                                  "headers": {}
                                },
                                "type": "endpoint"
                              }
```

```
                                    ],
                                    "type": "tree"

                            }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
]
},
"smithy.rules#endpointTests": {
```

```
"testCases": [
  {
    "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
    },
    "params": {
      "Region": "us-east-1",
      "UseFIPS": true,
      "UseDualStack": true
    }
  },
  {
    "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
    },
    "params": {
      "Region": "us-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {

 "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
        }
    },
    "params": {
      "Region": "us-east-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {
    "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
        }
```

```
        },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
             },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
```

```
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }

     },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
        }
```

```
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {

    "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
```

```
enabled",
                "expect": {
                  "error": "DualStack is enabled but this partition does not support DualStack"
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
                  }
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS":
false,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                   }
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false
                }
              },
```

```
                {
                  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "error": "DualStack is enabled but this partition does not support DualStack"
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {

                 "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                    }
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }

        },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }
                  },
```

```
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
```

```
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

            },
            {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "OrganizationIntegration": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
          "traits": {
            "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n              <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceType</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>ProductCode</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Region</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Status</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>UsageOperation</code>\n              </p>\n            </li>\n          </ul>\n          <p>For each filter, you can use one of the following <code>Operator</code>
```

```
values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
          "type": "structure",
          "members": {
            "Instances": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
              }
            },
            "NextToken": {

           "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListLinuxSubscriptions"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",

  "items": "Subscriptions"
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
      "type": "structure",
      "members": {
        "Filters": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
```

```
match a certain subscription's name.</p>\n        <p>The valid names for this filter are:</p>\n        <ul>\n
<li>\n            <p>\n                <code>Subscription</code>\n            </p>\n        </li>\n        </ul>\n
<p>The
 valid Operators for this filter are:</p>\n        <ul>\n        <li>\n            <p>\n
<code>contains</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>equals</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n        </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
```

```
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
          },
          "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",
              "items": "RegisteredSubscriptionProviders"
            }
          }

        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSources": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
            }
        },
        "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                "smithy.api#range": {
                    "min": 1,
                    "max": 100
                }
            }

 },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
                "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
        },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
      },
      "errors": [
        {

     "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
        "smithy.api#http": {
          "method": "GET",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#readonly": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
                    "documentation": "Equal operator"
                },
                {
                    "name": "NOT_EQUAL",
                    "value": "NotEqual",
                    "documentation": "Not equal operator"
                },
                {
                    "name": "CONTAINS",
                    "value": "Contains",
                    "documentation": "Contains operator"
                }
            ],
            "smithy.api#length": {
                "min": 1,
                "max": 20
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled OrganizationIntegration"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
```

```
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
            }
          },
```

```
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"
```

```
}
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "InProgress",
          "value": "InProgress",
          "documentation": "InProgress status"
        },
        {
          "name": "Completed",
          "value": "Completed",
          "documentation": "Completed status"
        },
        {
          "name": "Successful",
          "value": "Successful",
          "documentation": "Successful status"
        },
        {
          "name": "Failed",
          "value": "Failed",
          "documentation": "Failed status"
        }
      ]
    }
  },

  "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
    "type": "list",
    "member": {
      "target": "smithy.api#String",
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        }
      }
    },
    "traits": {
      "smithy.api#length": {
        "min": 1,
        "max": 100
      },
      "smithy.api#uniqueItems": {}
    }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
      "type": "structure",
      "members": {
        "Name":
{
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the subscription.</p>"
          }
        },
        "Type": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS.</p>"
          }
        },
        "InstanceCount": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>The total amount of running instances using this subscription.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
```

```
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [

 {
                "name": "RedHat",
                "value": "RedHat",
                "documentation": "RedHat subscription provider namespace"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "ACTIVE",
              "value": "ACTIVE",
              "documentation": "ACTIVE status"
            },
            {
              "name": "INVALID",
              "value": "INVALID",

   "documentation": "INVALID status"
            },
            {
              "name": "PENDING",
              "value": "PENDING",
              "documentation": "PENDING status"
            }
          ]
        }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
      "type": "structure",
      "members":
{
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services resource to which to add the specified \n\t\t\tmetadata tags.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
```

```
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

          "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
          },
```

```
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
```

```
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
          }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
          "type": "structure",
          "members": {
              "message": {
                  "target": "smithy.api#String"
              }
          },
          "traits": {
              "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
              "smithy.api#error": "client"
          }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
```

```
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
```

```
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
```

```
//
// This member is required.
WorkspaceId *string

// A token from Grafana Labs that ties your Amazon Web Services account with a
// Grafana Labs account. For more information, see [Link your account with Grafana Labs].
//
// [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
GrafanaToken *string

noSmithyDocumentSerde
}

type AssociateLicenseOutput
struct {

// A structure containing data about the workspace.
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
```

```
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
```

```
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",

```
            "traits": {
                "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
        },
        "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
        },
        "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
                "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
      "type": "structure",
      "members": {
        "DomainName": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
          }
        },
        "DomainIpv4List": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
          "traits": {
            "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
            "smithy.api#length": {
              "min": 1,
              "max": 2
            }
          }
        },
        "DomainCredentialsProvider": {
          "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
              },
              "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>Contains network access and credential details that are needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
                }
              ]
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#Arn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
 {
            "type": "operation",
            "input": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n          </note>",
            "smithy.api#http":
 {
              "code": 200,
              "method": "POST",
              "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
          "type": "structure",
          "members": {
            "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
              "smithy.api#required": {}
            }
          },
           "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

    "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },

        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
```

```
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/DeleteLicenseServerEndpoint"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
              "traits": {
                "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
```

```
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}

      }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Directory": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
```

```
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary":
{
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
         "type": "structure",
         "members": {
            "Subnets": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                  "smithy.api#length": {
                     "min": 1
                  },
```

```
    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
              }
            },
            "FailureMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
          "type": "list",
          "member": {

            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
    "type": "structure",
    "members": {
        "Username": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

"IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
```

```
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
```

```
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
    "type": "structure",
    "members": {
        "message": {
            "target": "smithy.api#String"
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
         "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
         },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
```

```
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",

          "x-api-key",
            "authorization",
            "x-amz-date",
            "x-amz-security-token",
            "Access-Control-Allow-Headers",
            "Access-Control-Allow-Methods",
            "Access-Control-Allow-Origin"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region":
{
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
              "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
```

```
                "default": false,
                "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
                "type": "Boolean"
            },
            "Endpoint": {
                "builtIn": "SDK::Endpoint",
                "required": false,
                "documentation": "Override the endpoint used to send this request",
                "type": "String"
            }
        },
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "isSet",
                        "argv": [
                            {
                                "ref": "Endpoint"
                            }
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            }
                        ],
                        "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                        "type": "error"
                    },
                    {
                        "conditions": [
                            {

                                "fn": "booleanEquals",
                                "argv": [
                                    {
```

```
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "aws.partition",

                      "argv": [
                        {
                          "ref": "Region"
                        }
                      ],
                      "assign": "PartitionResult"
                    }
```

```
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },
```

true

```
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
```

"fn": "booleanEquals",

```
                            "argv": [
                              true,
                              {
                                "fn": "getAttr",
                                "argv": [
                                  {
                                    "ref": "PartitionResult"
                                  },
                                  "supportsFIPS"
                                ]
                              }
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              true,
```

```
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }

                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }

    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                    "type": "error"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [

 {
                            "ref": "UseFIPS"
                        },
                        true
                    ]
```

```
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "fn": "getAttr",
                      "argv": [

        {
                          "ref": "PartitionResult"
                        },
                        "supportsFIPS"
                      ]
                    },
                    true
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [],
                  "endpoint": {

    "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                    "properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "FIPS is enabled but this partition does not support FIPS",
              "type": "error"

}
          ],
          "type": "tree"
        },
        {
          "conditions": [
            {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {

        "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]

          }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

            ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
```

```
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
{
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint":
{
                  "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
```

```
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
```

```
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

    },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",

  "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
```

```
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
    "expect": {

   "endpoint": {
        "url": "https://example.com"
      }
    },
    "params": {
      "Region": "us-east-1",
      "UseFIPS": false,
      "UseDualStack": false,
      "Endpoint": "https://example.com"
    }
  },
  {
    "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
    "expect": {
      "endpoint": {
        "url": "https://example.com"
      }
    },
    "params": {
      "UseFIPS": false,
      "UseDualStack":
 false,
      "Endpoint": "https://example.com"
    }
  },
  {
    "documentation": "For custom endpoint with fips enabled and dualstack disabled",
    "expect": {
      "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
    },
    "params": {
      "Region": "us-east-1",
      "UseFIPS": true,
      "UseDualStack": false,
      "Endpoint": "https://example.com"
    }
```

```
                },
                {
                  "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                  "expect": {
                    "error": "Invalid Configuration:
 Dualstack and custom endpoint are not supported"
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>"
              }
            },
            "ServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
              }
            },
            "LicenseServerEndpointId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits":
```

```
{
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
              }
            },
            "LicenseServerEndpointProvisioningStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
              "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
              }
            },
            "LicenseServers": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
              }
            },

           "CreationTime": {
              "target": "smithy.api#Timestamp",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
          "type": "string"
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

      "type": "string",
          "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
              "name": "PROVISIONED",
              "value": "PROVISIONED",
              "documentation": ""
            },
            {
              "name": "DELETING",
              "value": "DELETING",
              "documentation": ""
            },
            {
              "name": "DELETION_FAILED",
              "value": "DELETION_FAILED",
              "documentation": ""

           },
            {
              "name": "DELETED",
              "value": "DELETED",
              "documentation": ""
            }
         ]
      }
   },
   "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
         "smithy.api#enum": [
            {
              "name": "HEALTHY",
              "value": "HEALTHY",
              "documentation": ""
            },
            {
              "name": "UNHEALTHY",
              "value": "UNHEALTHY",
              "documentation": ""
            },
```

```
                {
                    "name": "NOT_APPLICABLE",
                    "value": "NOT_APPLICABLE",
                    "documentation": ""
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
        "type": "structure",
        "members": {
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
```

```
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n        <li>\n        <p>Product</p>\n        </li>\n
        <li>\n        <p>DirectoryId</p>\n        </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                    "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
 that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                    "smithy.api#required": {}
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
 empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
 next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
```

```
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },

{
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
      }
    ],
    "traits": {
      "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
      "smithy.api#http": {
        "code": 200,
        "method": "POST",
        "uri": "/instance/ListInstances"
      },
      "smithy.api#paginated": {
        "inputToken": "NextToken",
        "outputToken": "NextToken",
        "pageSize": "MaxResults",
        "items": "InstanceSummaries"
      }
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
    "type": "structure",
    "members":
```

```
{
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n
         <li>\n               <p>InstanceId</p>\n            </li>\n         </ul>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
         "type": "structure",
         "members": {
            "InstanceSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/license-server/ListLicenseServerEndpoints"
        },

      "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "LicenseServerEndpoints"
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
      "type": "structure",
      "members": {
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n        <li>\n          <p>IdentityProviderArn</p>\n        </li>\n      </ul>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
      "type": "structure",
      "members": {
        "LicenseServerEndpoints": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " Lists the user-based subscription products available from an identity provider. ",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"

```
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
```

```
This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "ProductUserSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

           }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
```

```
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
    "type": "structure",
    "members": {
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
```

```
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {

            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
              }
            },
            "SubscriptionStartDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The start date of a subscription.</p>"
              }
            },
            "SubscriptionEndDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The end date of a subscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
          "type":
 "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
          "type": "structure",
          "members": {
```

```
            "RdsSalCredentialsProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
```

```
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
          "type": "structure",
          "members": {
            "IdentityProvider": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>",
                "smithy.api#required": {}
              }
            },
            "Settings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
              "traits":
 {
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
```

```
                    "min": 1
                }
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
    "type": "string",
    "traits": {
        "smithy.api#length": {

     "min": 5,
            "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
    "type": "structure",
    "members": {
        "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more servers.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
    "type": "union",
    "members": {
        "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

           "traits": {
              "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688
communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
              "smithy.api#required": {}
            }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StartProductSubscription"
            }

      }
       },
       "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
          "type": "structure",
          "members": {
             "Username": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                   "smithy.api#required": {}
                }
             },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                   "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                   "smithy.api#required": {}
                }
             },
             "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                   "smithy.api#required": {}
                }
             },
             "Domain": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
                }
             },
             "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                   "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
                }
```

```
 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "ProductUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }

    }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

 "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
 {
        "type": "structure",
        "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {
```

```
      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
```

```
            "type": "structure",
            "members": {
                "message": {
                    "target": "smithy.api#String"
                }
            },
            "traits": {
                "smithy.api#documentation": "<p>A parameter is not valid.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
```

```
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
```

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation

spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.94 ldap 3.4.11

1.94.1 Available under license :

Copyright (c) 2004-2018 Fabien Potencier

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is furnished
to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
 WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.95 aws-sdk-go-v2-service-sso 1.27.0

1.95.1 Available under license :

GetLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID

```
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
```

```
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string
```

```
// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string
```

```
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
```

```
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
```

```
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}
```

```
func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
```

```
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
```

InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2

disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt

```
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }
```

```
 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
```

```
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
```

DeleteLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

```
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
```

```
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
```

```
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
```

```
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
```

```
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
```

```
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
```

```
 Region:
      region,
 ServiceID:     ServiceID,
 OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType
```

```
// Unique, case-sensitive identifier that you provide to ensure the idempotency of
// the request.
//
// This member is required.
ClientToken *string

// License entitlements.
//
// This member is required.
Entitlements []types.EntitlementData

// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string
```

```
// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
```

```
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
```

```
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
            }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
```

```
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
           },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
```

registered to your account. ",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation":
 " The Amazon Resource Name (ARN) of the BYOL registration resource to get details for. ",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation": " The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request. "
              }
            },
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

           "traits": {
                "smithy.api#documentation": " The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request. "
              }
            },
            "SecretArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
              "traits": {
                "smithy.api#documentation": " The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request. "

```
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
                }
            },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
            "AmiId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
                }
            },
            "InstanceID": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
                }
            },
            "InstanceType": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>The instance type of the resource.</p>"
                }
            },
            "AccountID": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the instance.</p>"
                }
            },
            "Region": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
                }
            },
            "UsageOperation": {
```

```
            "target": "smithy.api#String",

    "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
          },
          "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
              "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
          },
          "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
              "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
          },
          "SubscriptionName": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
            }
          },
          "OsVersion": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
            }
          },
          "SubscriptionProviderCreateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
          },
          "SubscriptionProviderUpdateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
```

```
registered \n\t\t\tthird-party Linux subscription provider.</p>"
                }
            },
            "DualSubscription": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
                }
            },
            "RegisteredWithSubscriptionProvider": {
                "target": "smithy.api#String",
                "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
         },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
        }
    ],
    "traits": {
        "aws.api#service": {
            "sdkId": "License Manager Linux Subscriptions",
             "arnNamespace": "license-manager-linux-subscriptions",
            "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
            "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
            "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
```

```
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
```

```
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseFIPS"
                        },
                        true
                      ]
                    }

        ],
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                  "type": "error"
                },
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            {
                              "ref": "UseDualStack"
                            },
                            true
                          ]

}
                      ],
                      "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                      "type": "error"
                    },
                    {
                      "conditions": [],
                      "endpoint": {
```

```
                    "url": {
                        "ref": "Endpoint"
                    },
                    "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"

    }
    ],
    "type": "tree"
},
{
    "conditions": [],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Region"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {

    "fn": "aws.partition",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ],
                            "assign": "PartitionResult"
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
```

```
                "argv": [
                  {

              "ref": "UseFIPS"
                  },
                  true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }

],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"

        },
                              "supportsFIPS"
                          ]
                        }
                      ]
                    },
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        true,
                        {
                          "fn": "getAttr",
                          "argv": [

                           {
                                "ref": "PartitionResult"
```

```
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],

    "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],

                        "type": "tree"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                            "type": "error"
                        }
                    ],
                    "type": "tree"
                },
                {

        "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
```

```
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

                "fn": "booleanEquals",
                        "argv": [
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"
                              },
                              "supportsFIPS"
                            ]
                          },
                          true

                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "rules": [
                        {
                          "conditions": [],
                          "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                            "headers": {}
                          },
                          "type": "endpoint"
                        }
                      ],
                      "type": "tree"
                    }
                  ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "FIPS is enabled
```

```
but this partition does not support FIPS",
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true

                    ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [
                                        {
                                            "fn": "booleanEquals",
                                            "argv": [
                                                true,
                                                {
                                                    "fn": "getAttr",
                                                    "argv": [
                                                        {

                                                            "ref": "PartitionResult"
                                                        },
                                                        "supportsDualStack"
                                                    ]
                                                }
                                            ]
                                        }
                                    ],
                                    "rules": [
                                        {
                                            "conditions": [],
                                            "rules": [

        {
                                                    "conditions": [],
                                                    "endpoint": {
                                                        "url": "https://license-manager-linux-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],
                                    "type": "tree"

                            }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
```

```
            ],
            "type": "tree"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

    }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": false
            }
        },
        {

     "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
```

```
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
                }

        },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {

 "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
                "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                }
```

```
    },
    "params": {
      "Region": "cn-north-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {
    "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
      }
    },
    "params": {
      "Region": "cn-north-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
      }
    },
    "params": {
      "Region": "us-gov-east-1",
      "UseFIPS": true,
      "UseDualStack": true
    }
  },
  {
    "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
      }

   },
    "params": {
      "Region": "us-gov-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
```

```
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                  },
                  "params": {

               "Region": "us-iso-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                    }
                  },
                  "params": {
                    "Region": "us-iso-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
             }
          },
```

```
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

     "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

},
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
```

```
disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://example.com"
                      }
                    },
                    "params": {
                      "UseFIPS": false,
                      "UseDualStack": false,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {

                    "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                    "expect": {
                      "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                    },
                    "params": {
                      "Region": "us-east-1",
                      "UseFIPS": true,
                      "UseDualStack": false,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {
                    "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                    "expect": {
                      "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                    },
                    "params": {

 "Region": "us-east-1",
                      "UseFIPS": false,
                      "UseDualStack": true,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {
                    "documentation": "Missing region",
                    "expect": {
                      "error": "Invalid Configuration: Missing Region"
                    }
                  }
                ],
                "version": "1.0"
              }
            }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "Enabled",
            "value": "Enabled",
            "documentation": "Enabled LinuxSubscriptionsDiscovery"

    },
          {
            "name": "Disabled",
            "value": "Disabled",
            "documentation": "Disabled LinuxSubscriptionsDiscovery"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "OrganizationIntegration": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
          "traits": {
            "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n
  <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
      <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
```

<code>InstanceType</code>\n \n \n \n \n
<code>ProductCode</code>\n \n \n \n \n
<code>Region</code>\n \n \n \n \n
<code>Status</code>\n \n \n \n \n
<code>UsageOperation</code>\n \n \n \n For each filter, you can use one of the following <code>Operator</code>
values to \n \t\tdefine the behavior of the filter: \n \n \n \n
<code>contains</code>\n \n \n \n \n
<code>equals</code>\n \n \n \n \n
<code>Notequal</code>\n \n \n "
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": " The maximum items to return in a request. "
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " A token to specify where to
start paginating. This \n\tis the nextToken from a previously truncated response. ",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
          "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
              "smithy.api#documentation": " An array that contains instance objects. "
            }
          },
          "NextToken": {

       "target": "smithy.api#String",
            "traits": {

```
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

  "items": "Subscriptions"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
```

```
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n partially match, or don't match a certain subscription's name.</p>\n <p>The valid names for this filter are:</p>\n <ul>\n <li>\n <p>\n <code>Subscription</code>\n </p>\n </li>\n </ul>\n <p>The valid Operators for this filter are:</p>\n <ul>\n <li>\n <p>\n <code>contains</code>\n </p>\n </li>\n <li>\n <p>\n <code>equals</code>\n </p>\n </li>\n <li>\n <p>\n <code>Notequal</code>\n </p>\n </li>\n </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
```

```
            "target": "smithy.api#String",
             "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListRegisteredSubscriptionProviders"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "RegisteredSubscriptionProviders"
          }
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSources": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
          "traits": {
            "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
          }
        },
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }

  },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
          "traits": {
            "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
          }
        },

       "NextToken": {
          "target": "smithy.api#String",
          "traits": {
```

```
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
          },
          "errors": [
            {

         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "resourceArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                 "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
```

```
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
      "type": "structure",
      "members": {
        "tags": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
          "traits": {
            "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "EQUAL",
            "value": "Equal",
            "documentation": "Equal operator"
          },
          {
            "name": "NOT_EQUAL",
            "value": "NotEqual",
            "documentation": "Not equal operator"
          },
          {
            "name": "CONTAINS",
            "value": "Contains",
            "documentation": "Contains operator"
          }
        ],
        "smithy.api#length": {
          "min": 1,
          "max": 20
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "Enabled",
            "value": "Enabled",
            "documentation": "Enabled OrganizationIntegration"
          },
          {
            "name": "Disabled",
            "value": "Disabled",
            "documentation": "Disabled OrganizationIntegration"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
        "smithy.api#http": {
```

```
                "code": 200,
                "method": "POST",
                "uri": "/subscription/RegisterSubscriptionProvider"

            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
              "traits": {
                "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
                "smithy.api#required": {}
              }
            },
            "SecretArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
              "traits": {
                "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
              }
```

```
            },
            "SubscriptionProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
         "type": "structure",
         "members": {
            "SubscriptionProviderArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
               }
            },
            "SubscriptionProviderSource": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
               "traits": {
                  "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
               }
            },
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
```

```
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "InProgress",
              "value": "InProgress",
              "documentation": "InProgress status"
            },
            {
              "name": "Completed",
              "value": "Completed",
              "documentation": "Completed status"
            },
            {
              "name": "Successful",
              "value": "Successful",
              "documentation": "Successful status"
            },
            {
              "name": "Failed",
              "value": "Failed",
              "documentation": "Failed status"
            }
          ]
        }
      },

      "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            }
          }
        },
        "traits": {
          "smithy.api#length": {
```

```
            "min": 1,
            "max": 100
          },
          "smithy.api#uniqueItems": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
          "Name":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the subscription.</p>"
            }
          },
          "Type": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
            }
          },
          "InstanceCount": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
            "traits": {
              "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
```

```
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
                },
                {
                    "name": "INVALID",
                    "value": "INVALID",

   "documentation": "INVALID status"
                },
                {
                    "name": "PENDING",
                    "value": "PENDING",
```

```
                "documentation": "PENDING status"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
           },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
              "method": "PUT",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
```

```
        "type": "structure",
        "members":
{
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
        "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
```

```
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}
              }
            },
            "tagKeys": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
              "traits": {

            "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                "smithy.api#httpQuery": "tagKeys",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

         },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
```

```
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                "smithy.api#required": {}
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                "smithy.api#required": {}
              }
            },
            "AllowUpdate": {
              "target":
 "smithy.api#Boolean",
              "traits": {
                "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
```

```
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                   "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
               }
            },
            "StatusMessage": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
               "traits": {
                  "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
               }

       },
            "HomeRegions": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                  "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated data for Linux\n      subscriptions.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
         }
      }
   }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
```

```
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
```

```
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
```

```
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
```

```
 Region:        region,
 ServiceID:     ServiceID,
 OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
```

```
//
// This member is required.
LicenseType types.LicenseType

// The ID of the workspace to associate the license with.
//
// This member is required.
WorkspaceId *string

// A token from Grafana Labs that ties your Amazon Web Services account with a
// Grafana Labs account. For more information, see [Link your account with Grafana Labs].
//
// [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
GrafanaToken *string

noSmithyDocumentSerde
}

type AssociateLicenseOutput
struct {

// A structure containing data about the workspace.
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}
```

```
if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
```

```
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
```

```
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
  return err
```

```
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
```

CheckInLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {

```
        "type": "structure",
        "members": {
          "DirectoryId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
            "traits": {
              "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
          },
          "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
          },
          "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
              "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
          "DomainName": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
            }
          },
          "DomainIpv4List": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
            "traits": {
              "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 2
              }
```

```
            }
          },
          "DomainCredentialsProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
            }
          },
          "DomainNetworkSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "SELF_MANAGED",
              "value": "SELF_MANAGED",
              "documentation": "SELF_MANAGED type of Active Directory"
            },
            {
              "name": "AWS_MANAGED",
              "value": "AWS_MANAGED",
              "documentation": "AWS_MANAGED type of Active Directory"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
{
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
```

```
"com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
    "type": "structure",
    "members": {
      "Username": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
          "smithy.api#required": {}
        }
      },
      "InstanceId": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
          "smithy.api#required": {}
        }
      },
      "IdentityProvider": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
        "traits": {
          "smithy.api#documentation": "<p>The identity provider for the user.</p>",
          "smithy.api#required": {}
        }
      },
      "Domain": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
        }
      },
      "Tags": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
        "traits": {
          "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
        }
      }
    },
    "traits": {

  "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
    "type": "structure",
    "members": {
      "InstanceUserSummary": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },

        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                  "smithy.api#required": {}
               }
            },
            "Tags": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
          "SecretsManagerCredentialsProvider":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
```

```
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
```

<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete. ",
                "smithy.api#required": {}
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": " The type of License Server that the delete request refers to. ",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
              "traits": {
                "smithy.api#documentation": " Shows details from the <code>LicenseServerEndpoint</code> resource that was deleted. "
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
         "type": "structure",
         "members": {
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity provider to deregister.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
```

```
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

      }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
```

```
                "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
              }
            },
            "InstanceUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummary":
{
              "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
          "type": "structure",
          "members": {
            "Subnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                "smithy.api#length": {
```

```
                    "min": 1
                },

    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
```

```
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
```

```
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
               }
            },
            "FailureMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
         "type": "list",
         "member": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
         "type": "structure",
         "members": {
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                  "smithy.api#required": {}
               }
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                  "smithy.api#required": {}
               }
            },
            "Products": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
                "traits": {
                  "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                  "smithy.api#required": {}
               }
```

```
            },
            "LastStatusCheckDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date of the last status check.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                  "smithy.api#required": {}
               }
            },

      "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
```

```
\n\t\t\tabout the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                 }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
                }
            },
            "AssociationDate": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
                }
            },
            "DisassociationDate": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
```

```
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
    "type": "structure",
    "members": {
        "message": {
            "target": "smithy.api#String"
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
         "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
         },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
            },
            {
"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
          ],
          "traits": {
            "aws.api#service": {
              "sdkId": "License Manager User Subscriptions",
              "arnNamespace": "license-manager-user-subscriptions",
              "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
```

```
            "name": "license-manager-user-subscriptions"
          },
          "aws.protocols#restJson1": {},
          "smithy.api#cors": {
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id",
              "content-length",

        "x-api-key",
              "authorization",
              "x-amz-date",
              "x-amz-security-token",
              "Access-Control-Allow-Headers",
              "Access-Control-Allow-Methods",
              "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager User Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region":
{
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                "type": "Boolean"
              },
```

```
        "UseFIPS": {
          "builtIn": "AWS::UseFIPS",
          "required": true,
          "default": false,
          "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
          "type": "Boolean"
        },
        "Endpoint": {
          "builtIn": "SDK::Endpoint",
          "required": false,
          "documentation": "Override the endpoint used to send this request",
          "type": "String"
        }
      },
      "rules": [
        {
          "conditions": [
            {
              "fn": "isSet",
              "argv": [
                {
                  "ref": "Endpoint"
                }
              ]
            }
           ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
                    true
                  ]
                }
              ],
              "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
              "type": "error"
            },
            {
              "conditions": [
                {
```

```
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Region"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "aws.partition",

                    "argv": [
                      {
                        "ref": "Region"
                      }
```

```
                ],
                "assign": "PartitionResult"
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
```

true

```
                    ]
                  },
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
```

"fn": "booleanEquals",

```
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"
                              },
                              "supportsFIPS"
                            ]
                          }
                        ]
                      },
```

```
                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }

                ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }

    ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
```

```
{
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "fn": "getAttr",
                                            "argv": [

                                {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsFIPS"
                                        ]
                                    },
                                    true
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {

                        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

    }
                    ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]

         }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
```

```
                        ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "error": "DualStack is enabled but this partition does not support DualStack",
                            "type": "error"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],
                "type": "tree"
            }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
{
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",

    "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS":
true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint":
{
                "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
```

```
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false

    }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

            },
              "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
              },
              "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                }
              },
              "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
              },
              "params": {
                "Region": "us-isob-east-1",

  "UseFIPS": false,
                "UseDualStack": true
              }
            },
```

```
                {
                  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                    }
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
                  "expect": {

                 "endpoint": {
                      "url": "https://example.com"
                    }
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }
                  },
                  "params": {
                    "UseFIPS": false,
                    "UseDualStack":
 false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                  "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                  },
```

```
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
        "type": "structure",
        "members": {
          "ProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
             "traits": {
               "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
            }
          },
          "HealthStatus": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
            "traits": {
              "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
            }
          },
```

```
        "Ipv4Address": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
      "type": "structure",
      "members": {
        "IdentityProviderArn": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
          }
        },
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>"
          }
        },
        "ServerEndpoint": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
            "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
          }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
          }
        },
        "LicenseServerEndpointId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
```

```
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
{
              "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the
RDS \n\t\t\tlicense server.</p>"
            }
          },
          "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
              "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent
the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },

         "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when License Manager created the license server
endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop
Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
```

```
                {
                    "name": "UNHEALTHY",
                    "value": "UNHEALTHY",
                    "documentation": ""
                },
                {
                    "name": "NOT_APPLICABLE",
                    "value": "NOT_APPLICABLE",
                    "documentation": ""
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
        "type": "structure",
        "members": {
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single request.</p>"
            }
        },
        "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n <ul>\n <li>\n <p>Product</p>\n </li>\n <li>\n <p>DirectoryId</p>\n </li>\n </ul>"
            }
        },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
    "type": "structure",
    "members": {
        "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                "smithy.api#required": {}
            }
        },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
```

```
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
     "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/instance/ListInstances"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
        }
    }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
      "type": "structure",
      "members":
{
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
      "type": "structure",
      "members": {
        "InstanceSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next
```

token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
"type": "operation",
"input": {
"target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
},
"output": {
"target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
},
"errors": [
{
"target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
}
],
"traits": {
"smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",
"smithy.api#http": {
"code": 200,
"method": "POST",
"uri": "/license-server/ListLicenseServerEndpoints"
},
"smithy.api#paginated": {
"inputToken": "NextToken",

```
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                 "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoints": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
                 "traits": {
                    "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
                }
```

```
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
         "type":
 "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
```

```
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
```

```
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

             }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
   "type": "operation",
   "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
   },
   "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
   "errors": [
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
       }
   ],
   "traits": {
      "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
      "smithy.api#http": {
         "code": 200,
         "method": "POST",
         "uri": "/user/ListUserAssociations"
      },
      "smithy.api#paginated": {
         "inputToken": "NextToken",
         "outputToken": "NextToken",
         "pageSize": "MaxResults",
         "items": "InstanceUserSummaries"
      }
   }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
```

```
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
```

```
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                 "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
          "type": "structure",
          "members": {
            "Username":
 {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
                 "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                 "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                 "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                 "smithy.api#required": {}
              }
            },
             "Status": {
              "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
{
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {

   "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits":
{
                    "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
"<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

    "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

           "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
          "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
        "type": "union",
        "members": {
          "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

"target": "smithy.api#String"
            }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity
```

provider. \n <note>\n Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as Pending billing status) in Amazon Web Services Billing. For more information, see Viewing your\n\t\t\t\tmonthly charges in the Amazon Web Services Billing User Guide. \n </note>",
"smithy.api#http": {
"code": 200,
"method": "POST",
"uri": "/user/StartProductSubscription"
}

}
},
"com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
"type": "structure",
"members": {
"Username": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The user name from the identity provider of the user. ",
"smithy.api#required": {}
}
},
"IdentityProvider": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
"traits": {
"smithy.api#documentation": " An object that specifies details for the identity provider. ",
"smithy.api#required": {}
}
},
"Product": {
"target": "smithy.api#String",
"traits": {

"smithy.api#documentation": " The name of the user-based subscription product. \n Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n ",
"smithy.api#required": {}
}
},
"Domain": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The domain name of the Active Directory that contains the user for whom to start the product \n\t\t\tsubscription. "
}
},

```
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
              }

  }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
```

```
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
                  "smithy.api#required": {}
               }

   }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
         "type": "list",
         "member": {
            "target": "smithy.api#String"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
         }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

"min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        },
        "Tags": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
          "traits": {
            "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {

         "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
        "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
```

```
to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

            }
               },
               "TagKeys": {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
                  "traits": {
                     "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                     "smithy.api#httpQuery": "tagKeys",
                     "smithy.api#required": {}
                  }
               }
            },
            "traits": {
               "smithy.api#input": {}
            }
         },
         "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
            "type": "structure",
            "members": {},
            "traits": {
               "smithy.api#output": {}
            }
         },
         "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
            "type": "operation",
            "input": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
             },
            "output": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
            },
            "errors": [
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
               }
            ],
```

```
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

       "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n <ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n <li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
```

```
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
```

```
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A parameter is not valid.</p>",
          "smithy.api#error": "client"
        }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {
```

```
 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
```

```
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
```

```
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
```

InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership

of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or

documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.96 aws-sdk-go-v2-internal-v4a 1.4.2

1.96.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work

(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work

or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.97 x-tools 0.35.0

1.97.1 Available under license :

MIT License

Copyright (c) 2022 GO-JEK Tech

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.98 swag 1.16.6

1.98.1 Available under license :

MIT License

Copyright (c) 2017 Eason Lin

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.99 github.com/aws/aws-sdk-go-v2/feature/dynamodb/attributevalue 1.20.2

1.99.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation

spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
name: License Scan

on: [pull_request]

```
jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
     - name: Run Scan code on pr ref
       run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
     # compare
     - name: License test
       run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
```

```
//
// This member is required.
ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag
```

```
 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
```

```
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
 return err
```

```
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
```

```
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
```

InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection

spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength

SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
"context"
"fmt"
awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
"github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
"github.com/aws/smithy-go/middleware"
smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns

```
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense
```

```
 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
```

```
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
```

```
err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if
err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
```

```
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
```

```
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {
```

```
 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
```

```
 return err
}
if err := addProtocolFinalizerMiddlewares(stack,
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
```

```
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata
```

```
 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
```

```
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
```

```
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
```

```
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string
```

```
 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
```

```
 return err
 }
 if err = addRetry(stack, options); err != nil {
 return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
 err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
```

```
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
```

```
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData
```

```
// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
```

```
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.

```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },

    {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
               "smithy.api#required": {}
             }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
```

```
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
```

```
        "traits": {
            "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
          }
        },
        "SubscriptionProviderStatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
          }
        },
        "LastSuccessfulDataRetrievalTime": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
      },
      "errors": [
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
```

```
            },
            "StatusMessage": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
               "traits": {
                  "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
               }
            },
            "HomeRegions": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                  "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
         "type": "structure",
         "members": {
            "AmiId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
               }
            },
            "InstanceID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
               }
            },
            "InstanceType": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>The instance type of the resource.</p>"
               }
            },
            "AccountID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
               }
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
```

```
                "smithy.api#documentation": "<p>The status of the instance.</p>"
              }
            },
            "Region": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
              }
            },
            "UsageOperation": {
              "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
              }
            },
            "ProductCode": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
              "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
              }
            },
            "LastUpdatedTime": {
              "target": "smithy.api#String",
               "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
              }
            },
            "SubscriptionName": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
              }
            },
            "OsVersion": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
              }
            },
            "SubscriptionProviderCreateTime": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
          },
          "SubscriptionProviderUpdateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
            }
          },
          "DualSubscription": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
            }
          },
          "RegisteredWithSubscriptionProvider": {
            "target": "smithy.api#String",
            "traits": {

     "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
```

```
            "smithy.api#documentation":
"<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
            }
        ],
        "traits": {
            "aws.api#service": {
                "sdkId": "License Manager Linux Subscriptions",
                 "arnNamespace": "license-manager-linux-subscriptions",
                "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
```

```
        },
        "aws.auth#sigv4": {
          "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
```

```
      "Endpoint": {
        "builtIn": "SDK::Endpoint",
        "required": false,
        "documentation": "Override the endpoint used to send this request",
        "type": "String"
      }
    },
    "rules": [
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Endpoint"
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }

],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
```

```
                                ]

}
                            ],
                            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                            "type": "error"
                        },
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": {
                                    "ref": "Endpoint"
                                },
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"

                }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "isSet",
                                "argv": [
                                    {
                                        "ref": "Region"
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
                                    {

                "fn": "aws.partition",
                                        "argv": [
                                            {
                                                "ref": "Region"
```

```
                }
            ],
            "assign": "PartitionResult"
        }
    ],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {

                      "ref": "UseFIPS"
                        },
                        true
                    ]
                },
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
                    ]
                }

],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                true,
                                {
                                    "fn": "getAttr",
                                    "argv": [
                                        {
                                            "ref": "PartitionResult"

},
                                        "supportsFIPS"
                                    ]
                                }
                            ]
                        },
```

```
                                        {
                                            "fn": "booleanEquals",
                                            "argv": [
                                                true,
                                                {
                                                    "fn": "getAttr",
                                                    "argv": [

                                                     {
                                                            "ref": "PartitionResult"
                                                        },
                                                        "supportsDualStack"
                                                    ]
                                                }
                                            ]
                                        }
                                    ],
                                    "rules": [
                                        {
                                            "conditions": [],

        "rules": [
                                                {
                                                    "conditions": [],
                                                    "endpoint": {
                                                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                        "properties": {},
                                                        "headers": {}
                                                    },
                                                    "type": "endpoint"
                                                }
                                            ],

                                "type": "tree"
                                        }
                                    ],
                                    "type": "tree"
                                },
                                {
                                    "conditions": [],
                                    "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",

                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
```

```
                                {

            "conditions": [
                                    {
                                       "fn": "booleanEquals",
                                       "argv": [
                                          {
                                             "ref": "UseFIPS"
                                          },
                                          true
                                       ]
                                    }
                                 ],
                                 "rules": [
                                    {
                                       "conditions": [
                                          {

                           "fn": "booleanEquals",
                                             "argv": [
                                                {
                                                   "fn": "getAttr",
                                                   "argv": [
                                                      {
                                                         "ref": "PartitionResult"
                                                      },
                                                      "supportsFIPS"
                                                   ]
                                                },
                                                true

                                          ]
                                       }
                                    ],
                                    "rules": [
                                       {
                                          "conditions": [],
                                          "rules": [
                                             {
                                                "conditions": [],
                                                "endpoint": {
                                                   "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                                   "headers": {}
                                                },
                                                "type": "endpoint"
```

```
                    }
                  ],
                  "type": "tree"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "FIPS is enabled
but this partition does not support FIPS",
              "type": "error"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
            {
              "fn": "booleanEquals",
              "argv": [
                {
                  "ref": "UseDualStack"
                },
                true

      ]
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    true,
                    {
                      "fn": "getAttr",
                      "argv": [
                        {

                          "ref": "PartitionResult"
                        },
                        "supportsDualStack"
                      ]
                    }
                  ]
                }
```

```
                ],
                "rules": [
                  {
                    "conditions": [],
                    "rules": [

        {
                        "conditions": [],
                        "endpoint": {
                          "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                          "properties": {},
                          "headers": {}
                        },
                        "type": "endpoint"
                      }
                    ],
                    "type": "tree"

                }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "DualStack is enabled but this partition does not support DualStack",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [],
            "rules": [
              {
                "conditions": [],
                "endpoint": {
                  "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                  "properties": {},
                  "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          }
        ],
```

```
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ],
    "type": "tree"
  }
 ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
            }

      },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
```

```
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
              }

            },
              "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
              },
              "params": {

           "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
```

```
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
```

```
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
```

```
    },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://example.com"
                  }
                },
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

 "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
```

```
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

        },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

 {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n        <li>\n  <p>\n            <code>AccountID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n    <code>AmiID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>DualSubscription</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceType</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>ProductCode</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Region</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Status</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>UsageOperation</code>\n          </p>\n        </li>\n      </ul>\n      <p>For each filter, you can use one of the following <code>Operator</code>\n values to \n  \t\tdefine the behavior of the filter:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
```

```
            "Instances": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
               "traits": {
                  "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
               }
            },
            "NextToken": {

         "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
```

```
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n
<li>\n              <p>\n                <code>Subscription</code>\n              </p>\n            </li>\n          </ul>\n
<p>The
 valid Operators for this filter are:</p>\n          <ul>\n            <li>\n              <p>\n
<code>contains</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>equals</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>Notequal</code>\n              </p>\n            </li>\n          </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
      "type": "structure",
      "members": {
        "Subscriptions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
```

```
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "RegisteredSubscriptionProviders"
            }
         }

      },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
         "type": "structure",
         "members": {
            "SubscriptionProviderSources": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
               "traits": {
                  "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }

    },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
       },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
         "type": "structure",
         "members": {
            "RegisteredSubscriptionProviders": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
```

```
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
          }
        },
        "SubscriptionProviderArn": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
          }
        },
```

```
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
               }
            },
            "SubscriptionProviderStatusMessage": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
               }
            },
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

  }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
                    "documentation": "Failed status"
                }
            ]
        }
    },

   "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
            }
          },
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            },
            "smithy.api#uniqueItems": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
          "type": "map",
          "key": {
            "target": "smithy.api#String"
          },
          "value": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
          "type": "structure",
          "members": {
            "Name":
{
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the subscription.</p>"
              }
            },
            "Type": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
              }
            },
            "InstanceCount": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
              "traits": {
                "smithy.api#documentation": "<p>The total amount of running instances using this
```

```
subscription.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
              ]
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                  "name": "ACTIVE",
                  "value": "ACTIVE",
                  "documentation": "ACTIVE status"
```

```
            },
            {
               "name": "INVALID",
               "value": "INVALID",

"documentation": "INVALID status"
            },
            {
               "name": "PENDING",
               "value": "PENDING",
               "documentation": "PENDING status"
            }
         ]
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
         "target": "smithy.api#String"
      },
      "traits": {
         "smithy.api#length": {
            "min": 0,
            "max": 50
         },
         "smithy.api#sensitive": {}
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
         }
      ],
      "traits": {
```

```
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
{
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
         "type": "map",
         "key": {
            "target": "smithy.api#String"
         },
```

```
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
         "type": "structure",
         "members": {
            "LinuxSubscriptionsDiscovery": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
               "traits": {
                  "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                  "smithy.api#required": {}
               }
            },
            "LinuxSubscriptionsDiscoverySettings": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
               "traits": {
                  "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                  "smithy.api#required": {}
               }
            },
            "AllowUpdate": {
               "target":
 "smithy.api#Boolean",
               "traits": {
                  "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
               }
            }
         }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
           "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
          }
        },
        "StatusMessage": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
          "traits": {
            "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
          }

     },
        "HomeRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated data for Linux\n      subscriptions.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
```

```
            "traits": {
                "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
```

```
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string
```

```
// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string
```

```
 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
"smithy": "2.0",
"shapes": {
"com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
"type": "structure",
"members": {

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
        "type": "structure",
        "members": {
            "DirectoryId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
                "traits": {
                    "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
                }
            },
            "ActiveDirectorySettings":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
                }
            },
            "ActiveDirectoryType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
```

```
            },
            "DomainIpv4List": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 2
                  }
               }
            },
            "DomainCredentialsProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
               }
            },
            "DomainNetworkSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
               },
               {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
               }
```

```
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
```

```
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http":
 {
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
                }
            }
```

```
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

         {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                "smithy.api#required": {}
            }
        },
        "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
                "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
    "type": "structure",
    "members": {
        "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
            }
        },
        "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
    "type": "union",
    "members": {
        "SecretsManagerCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
            "traits": {
```

```
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
```

```
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
            "smithy.api#length": {
              "min": 1
            },

  "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Attribute": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
          }
        },
        "Operation": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
          }
        },
        "Value": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>Value of the filter.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
```

```
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
          },
          "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
              }
            },
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

    "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details \n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance user.</p>"
             }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
```

```
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
             "smithy.api#error": "server",
            "smithy.api#httpError": 500
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
```

```
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
},
{
```

```
    "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
          ],
          "traits": {
            "aws.api#service": {
              "sdkId": "License Manager User Subscriptions",
              "arnNamespace": "license-manager-user-subscriptions",
              "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
              "name": "license-manager-user-subscriptions"
            },
            "aws.protocols#restJson1": {},
            "smithy.api#cors": {
              "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",

           "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
              ],
              "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
              ]
            },
            "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to
utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager User Subscriptions",
            "smithy.rules#endpointRuleSet": {
              "version": "1.0",
              "parameters": {
                "Region":
{
                  "builtIn": "AWS::Region",
                  "required": false,
                  "documentation": "The AWS region used to dispatch the request.",
```

```
            "type": "String"
        },
        "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
            "type": "Boolean"
        },
        "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
        },
        "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
```

```
                ]
              }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [
              {

                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "endpoint": {
              "url": {
                "ref": "Endpoint"
              },

"properties": {},
                "headers": {}
              },
              "type": "endpoint"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
            {
              "fn": "isSet",
              "argv": [
                {
                  "ref": "Region"
                }
              ]
            }
          ],
```

```
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "aws.partition",

                       "argv": [
                            {
                              "ref": "Region"
                            }
                          ],
                          "assign": "PartitionResult"
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseFIPS"
                              },

true
                              ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseDualStack"
                              },
                              true
                            ]
                          }
                        ],
                        "rules": [
                          {
                            "conditions": [
                              {

"fn": "booleanEquals",
                                  "argv": [
                                    true,
                                    {
                                      "fn": "getAttr",
                                      "argv": [
```

```
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            }
                        ]
                    },

                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [
                                {
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }

            ]
                }
            ],
            "rules": [
                {
                    "conditions": [],
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }

    ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
            "type": "error"
        }
    ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [

{
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
```

```
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

}
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

    "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]

    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

                            ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
```

```
{
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",

      "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint":
{
                        "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",
```

```
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS":
true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": true,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "endpoint":
{
                    "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
         "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
```

```
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
```

```
        },
        "params": {
          "Region": "us-isob-east-1",

  "UseFIPS": false,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
          }
        },
        "params": {
          "Region": "us-isob-east-1",
          "UseFIPS": false,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
        "expect": {

         "endpoint": {
            "url": "https://example.com"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": false,
          "Endpoint": "https://example.com"
        }
      },
      {
        "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
        "expect": {
          "endpoint": {
            "url": "https://example.com"
          }
        },
        "params": {
          "UseFIPS": false,
          "UseDualStack":
```

```
false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                    "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
    }
  }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
  "type": "structure",
  "members": {
    "ProvisioningStatus": {
      "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
       "traits": {
         "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
```

```
\n\t\t\tlicense server.</p>"
                }
            },
            "HealthStatus": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
                }
            },
            "Ipv4Address": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

  "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
        },
        "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
        },
        "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
        },
        "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
        },
        "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
        },

       "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
        }
    },
    "traits": {
      "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
    }
  },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
      "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
      "type": "structure",
      "members": {
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>",
            "smithy.api#required": {}
          }
        },
        "ServerSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
            "smithy.api#required": {}
          }
        }
      },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {

        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/identity-provider/ListIdentityProviders"
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
```

```
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
```

```
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
```

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/ListLicenseServerEndpoints"
            },

          "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
          "type": "structure",
          "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                 "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
```

```
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
             "traits": {
               "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                 "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
```

```
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n          <p>Status</p>\n          </li>\n          <li>\n          <p>Username</p>\n
</li>\n          <li>\n          <p>Domain</p>\n          </li>\n          </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

         }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
```

```
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {

    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
```

```
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
         "type": "structure",
         "members": {
            "IdentityProvider": {

     "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                  "smithy.api#required": {}
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
               "traits":
```

```
{
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",
```

```
    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
            "smithy.api#length": {

             "min": 5,
                "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
            "Endpoint": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
             "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
```

```
                "smithy.api#length": {
                    "min": 1
                },
                "smithy.api#required": {}
            }
        },
        "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
            }

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n        <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
```

```
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
              }
            },
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
          "type": "structure",
          "members": {
            "ProductUserSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                "smithy.api#required": {}
              }

    }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StringList": {
          "type": "list",
          "member": {
```

```
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
```

```
        "traits": {
          "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
```

```
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

           "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
            "smithy.api#http": {

      "code": 200,
                "method": "POST",
                "uri": "/identity-provider/UpdateIdentityProviderSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },

            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
                }
            },
            "UpdateSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
                "traits": {
                    "smithy.api#documentation": "<p>Updates the registered identity providers product related
```

configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the: \n \n \n Subnets which you want to add to provision VPC endpoints. \n \n \n Subnets which you want to remove the VPC endpoints from. \n \n \n Security
group ID which permits traffic to the VPC endpoints. \n \n ",
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
"type": "structure",
"members": {
"IdentityProviderSummary": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
"traits": {
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
"type": "structure",
"members": {
"AddSubnets": {

"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets in which License Manager will create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers. ",
"smithy.api#required": {}
}
},
"RemoveSubnets": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets to remove. ",
"smithy.api#required": {}
}
},
"SecurityGroupId": {
"target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

```
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if
```

```
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
```

Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.100 iputils-ping 20240905-r0

1.100.1 Available under license :

arping: GPL-2.0-or-later
clockdiff: BSD-3-Clause
ping: BSD-3-Clause
tracepath: GPL-2.0-or-later

Files containing license texts are available in Documentation directory.
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so

that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause
any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections

1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include
anything that is normally distributed (in either source or binary
form) with the major components (compiler, kernel, and so on) of the
operating system on which the executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering
access to copy from a designated place, then offering equivalent
access to copy the source code from the same place counts as
distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense or distribute the Program is
void, and will automatically terminate your rights under this License.
However, parties who have received copies, or rights, from you under
this License will not have their licenses terminated so long as such
parties remain in full compliance.

5. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Program or its derivative works. These actions are
prohibited by law if you do not accept this License. Therefore, by
modifying or distributing the Program (or any work based on the
Program), you indicate your acceptance of this License to do so, and

all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the

original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR

THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by
the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may

be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
 is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.101 x-mod 0.26.0

1.101.1 Available under license :

Copyright 2009 The Go Authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE
 FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,

DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.102 tre 0.8.0-r2

1.102.1 Available under license :

This is the license, copyright notice, and disclaimer for TRE, a regex matching package (library and tools) with support for approximate matching.

Copyright (c) 2001-2009 Ville Laurikari <vl@iki.fi>
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.103 procfs 0.17.0

1.103.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally

submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the

content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

procfs provides functions to retrieve system, kernel and process
metrics from the pseudo-filesystem proc.

Copyright 2014-2015 The Prometheus Authors

This product includes software developed at
SoundCloud Ltd. (http://soundcloud.com/).

1.104 github.com/swaggo/files 1.0.1

1.104.1 Available under license :

MIT License

Copyright (c) 2019 Swaggo

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.105 yaml 3.0.1

1.105.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
*  Licensed to the Apache Software Foundation (ASF) under one
*  or more contributor license agreements.  See the NOTICE file
*  distributed with this work for additional information
*  regarding copyright ownership.  The ASF licenses this file
*  to you under the Apache License, Version 2.0 (the
*  "License"); you may not use this file except in compliance
*  with the License.  You may obtain a copy of the License at
*
*    http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing,
*  software distributed under the License is distributed on an
*  "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
*  KIND, either express or implied.  See the License for the
*  specific language governing permissions and limitations
*  under the License.
*/
```

Found in path(s):

* /groovy-yaml-3-0-1-sources-jar/org/apache/groovy/yaml/util/YamlConverter.java
* /groovy-yaml-3-0-1-sources-jar/groovy/yaml/YamlBuilder.java
*
 /groovy-yaml-3-0-1-sources-jar/groovy/yaml/YamlSlurper.java
* /groovy-yaml-3-0-1-sources-jar/groovy/yaml/YamlRuntimeException.java

1.106 alpine-baselayout-data 3.6.8-r1

1.106.1 Available under license :

```
# Automatically generated by apkbuild-cpan, template 1
# Contributor: Francesco Colista <francesco.colista@gmail.com>
# Maintainer: Francesco Colista <francesco.colista@gmail.com>
pkgname=perl-software-license
_pkgreal=Software-License
pkgver=0.103004
pkgrel=0
pkgdesc="packages that provide templated software licenses"
url="http://search.cpan.org/dist/Software-License/"
arch="noarch"
license="GPL PerlArtistic"
```

```
cpandepends="perl-text-template perl-data-section perl-sub-install"
cpanmakedepends="    "
depends="$cpandepends"
makedepends="perl-dev $cpanmakedepends"
subpackages="$pkgname-doc"
source="http://search.cpan.org/CPAN/authors/id/R/RJ/RJBS/$_pkgreal-$pkgver.tar.gz"

_builddir="$srcdir/$_pkgreal-$pkgver"

prepare() {
 cd "$_builddir"
 export CFLAGS=`perl -MConfig -E 'say $Config{ccflags}'`
 PERL_MM_USE_DEFAULT=1 perl Makefile.PL INSTALLDIRS=vendor
}

build() {
 cd "$_builddir"
 export CFLAGS=`perl -MConfig -E 'say $Config{ccflags}'`
 make && make test
}

package() {
 cd "$_builddir"
 make
 DESTDIR="$pkgdir" install || return 1
 find "$pkgdir" \( -name perllocal.pod -o -name .packlist \) -delete
}

md5sums="0c5fd53d93818566234578b27d667b35  Software-License-0.103004.tar.gz"
IMPORTANT - READ BEFORE COPYING, INSTALLING OR USING.
Do not use or load this software and any associated materials
(collectively, the "Software") until you have carefully read the
following terms and conditions. By loading or using the Software, you
agree to the terms of this Agreement. If you do not wish to so agree,
do not install or use the Software.

1. COPYRIGHT NOTICE
Some or all of this work - Copyright  1999-2011, Intel Corp. All
rights reserved.

2. LICENSE

2.1. This is your license from Intel Corp. under its intellectual
property rights. You may have additional license terms from the party
that provided you this software, covering your right to use that
party's intellectual property rights.

2.2. Intel grants, free of charge, to any person ("Licensee")
```

obtaining a copy of the source code appearing in this file ("Covered Code") an irrevocable, perpetual, worldwide license under Intel's copyrights in the base code distributed originally by Intel ("Original Intel
Code") to copy, make derivatives, distribute, use and display any portion of the Covered Code in any form, with the right to sublicense such rights; and

2.3. Intel grants Licensee a non-exclusive and non-transferable patent license (with the right to sublicense), under only those claims of Intel patents that are infringed by the Original Intel Code, to make, use, sell, offer to sell, and import the Covered Code and derivative works thereof solely to the minimum extent necessary to exercise the above copyright license, and in no event shall the patent license extend to any additions to or modifications of the Original Intel Code. No other license or right is granted directly or by implication, estoppel or otherwise; The above copyright and patent license is granted only if the following conditions are met:

3. CONDITIONS

3.1. Redistribution of Source with Rights to Further Distribute Source. Redistribution of source code of any substantial portion of the Covered Code or
modification with rights to further distribute
source must include the above Copyright Notice, the above License, this list of Conditions, and the following Disclaimer and Export Compliance provision. In addition, Licensee must cause all Covered Code to which Licensee contributes to contain a file documenting the changes Licensee made to create that Covered Code and the date of any change. Licensee must include in that file the documentation of any changes made by any predecessor Licensee. Licensee must include a prominent statement that the modification is derived, directly or indirectly, from Original Intel Code.

3.2. Redistribution of Source with no Rights to Further Distribute Source. Redistribution of source code of any substantial portion of the Covered Code or modification without rights to further distribute source must include the following Disclaimer and Export Compliance provision in the documentation and/or other materials provided with distribution. In addition,
Licensee may not authorize further
sublicense of source of any portion of the Covered Code, and must include terms to the effect that the license from Licensee to its licensee is limited to the intellectual property embodied in the software Licensee provides to its licensee, and not to intellectual property embodied in modifications its licensee may make.

3.3. Redistribution of Executable. Redistribution in executable form of any substantial portion of the Covered Code or modification must reproduce the above Copyright Notice, and the following Disclaimer and Export Compliance provision in the documentation and/or other materials provided with the distribution.

3.4. Intel retains all right, title, and interest in and to the Original Intel Code.

3.5. Neither the name Intel nor any other trademark owned or controlled by Intel shall be used in advertising or otherwise to promote the sale, use or other dealings in products derived from or relating to the Covered
Code without prior written authorization from
Intel.

4. DISCLAIMER AND EXPORT COMPLIANCE

4.1. INTEL MAKES NO WARRANTY OF ANY KIND REGARDING ANY SOFTWARE PROVIDED HERE. ANY SOFTWARE ORIGINATING FROM INTEL OR DERIVED FROM INTEL SOFTWARE IS PROVIDED "AS IS," AND INTEL WILL NOT PROVIDE ANY SUPPORT, ASSISTANCE, INSTALLATION, TRAINING OR OTHER SERVICES. INTEL WILL NOT PROVIDE ANY UPDATES, ENHANCEMENTS OR EXTENSIONS. INTEL SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY, NONINFRINGEMENT AND FITNESS FOR A PARTICULAR PURPOSE.

4.2. IN NO EVENT SHALL INTEL HAVE ANY LIABILITY TO LICENSEE, ITS LICENSEES OR ANY OTHER THIRD PARTY, FOR ANY LOST PROFITS, LOST DATA, LOSS OF USE OR COSTS OF PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES, OR FOR ANY INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THIS AGREEMENT, UNDER ANY CAUSE OF ACTION OR THEORY OF LIABILITY, AND IRRESPECTIVE OF WHETHER INTEL HAS ADVANCE NOTICE OF THE POSSIBILITY OF SUCH DAMAGES. THESE LIMITATIONS
SHALL APPLY NOTWITHSTANDING THE
FAILURE OF THE ESSENTIAL PURPOSE OF ANY LIMITED REMEDY.

4.3. Licensee shall not export, either directly or indirectly, any of this software or system incorporating such software without first obtaining any required license or other approval from the U. S. Department of Commerce or any other agency or department of the United States Government. In the event Licensee exports any such software from the United States or re-exports any such software from a foreign destination, Licensee shall ensure that the distribution and export/re-export of the software is in compliance with all laws, regulations, orders, or other restrictions of the U.S. Export Administration Regulations. Licensee agrees that neither it nor any of its subsidiaries will export/re-export any technical data, process, software, or service, directly or indirectly, to any country for which

the United States government or any agency thereof requires an export license, other governmental approval, or letter of assurance, without first obtaining such license, approval or letter.

INTEL SOFTWARE LICENSE AGREEMENT

IMPORTANT - READ BEFORE COPYING, INSTALLING OR USING.
Do not use or load this software and any associated materials (collectively, the "Software") until you have carefully read the following terms and conditions. By loading or using the Software, you agree to the terms of this Agreement. If you do not wish to so agree, do not install or use the Software.

LICENSES: Please Note:
- If you are a network administrator, the "Site License" below shall apply to you.
- If you are an end user, the "Single User License" shall apply to you.
- If you are an original equipment manufacturer (OEM), the "OEM License" shall apply to you.

SITE LICENSE. You may copy the Software onto your organization's computers for your organization's use, and you may make a reasonable number of back-up copies of the Software, subject to these conditions:

1. This Software is licensed for use only in conjunction with Intel component products. Use of the Software in conjunction with non-Intel component products is not licensed hereunder.
2. You may not copy, modify, rent, sell, distribute or transfer any part of the Software except as provided in this Agreement, and you agree to prevent unauthorized copying of the Software.
3. You may not reverse engineer, decompile, or disassemble the Software.
4. You may not sublicense or permit simultaneous use of the Software by more than one user.
5. The Software may include portions offered on terms in addition to those set out here, as set out in a license accompanying those portions.

SINGLE USER LICENSE. You may copy the Software onto a single computer for your personal, noncommercial use, and you may make one back-up copy of the Software, subject to these conditions:

1. This Software is licensed for use only in conjunction with Intel component products. Use of the Software in conjunction with non-Intel component products is not licensed hereunder.
2. You may not copy, modify, rent, sell, distribute or transfer any part of the Software except as provided in this Agreement, and you agree to prevent unauthorized copying of the Software.
3. You may not reverse engineer, decompile, or disassemble the Software.

4. You may not sublicense or permit simultaneous use of the Software by more than one user.
5. The Software may include portions offered on terms in addition to those set out here, as set out in a license accompanying those portions.

OEM LICENSE: You may reproduce and distribute the Software only as an integral part of or incorporated in Your product or as a standalone Software maintenance update for existing end users of Your products, excluding any other standalone products, subject to these conditions:

1. This Software is licensed for use only in conjunction with Intel component products. Use of the Software in conjunction with non-Intel component products is not licensed hereunder.
2. You may not copy, modify, rent, sell, distribute or transfer any part of the Software except as provided in this Agreement, and you agree to prevent unauthorized copying of the Software.
3. You may not reverse engineer, decompile, or disassemble the Software.
4. You may only distribute the Software to your customers pursuant to a written license agreement. Such license agreement may be a "break-the-seal" license agreement. At a minimum such license shall safeguard Intel's ownership rights to the Software.
5. The Software may include portions offered on terms in addition to those set out here, as set out in a license accompanying those portions.

NO OTHER RIGHTS. No rights or licenses are granted by Intel to You, expressly or by implication, with respect to any proprietary information or patent, copyright, mask work, trademark, trade secret, or other intellectual property right owned or controlled by Intel, except as expressly provided in this Agreement.

OWNERSHIP OF SOFTWARE AND COPYRIGHTS. Title to all copies of the Software remains with Intel or its suppliers. The Software is copyrighted and protected by the laws of the United States and other countries, and international treaty provisions. You may not remove any copyright notices from the Software. Intel may make changes to the Software, or to items referenced therein, at any time without notice, but is not obligated to support or update the Software. Except as otherwise expressly provided, Intel grants no express or implied right under Intel patents, copyrights, trademarks, or other intellectual property rights. You may transfer the Software only if the recipient agrees to be fully bound by these terms and if you retain no copies of the Software.

LIMITED MEDIA WARRANTY. If the Software has been delivered by Intel on physical media, Intel warrants the media to be free from material physical defects for a period of ninety days after delivery by Intel. If such a defect is found, return the media to Intel for replacement or alternate delivery of

the Software as Intel may select.

EXCLUSION OF OTHER WARRANTIES. EXCEPT AS PROVIDED
ABOVE, THE SOFTWARE IS
PROVIDED "AS IS" WITHOUT ANY EXPRESS OR IMPLIED WARRANTY OF ANY KIND
INCLUDING WARRANTIES OF MERCHANTABILITY, NONINFRINGEMENT, OR FITNESS FOR A
PARTICULAR PURPOSE. Intel does not warrant or assume responsibility for the
accuracy or completeness of any information, text, graphics, links or other
items contained within the Software.

LIMITATION OF LIABILITY. IN NO EVENT SHALL INTEL OR ITS SUPPLIERS BE LIABLE
FOR ANY DAMAGES WHATSOEVER (INCLUDING, WITHOUT LIMITATION, LOST PROFITS,
BUSINESS INTERRUPTION, OR LOST INFORMATION) ARISING OUT OF THE USE OF OR
INABILITY TO USE THE SOFTWARE, EVEN IF INTEL HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES. SOME JURISDICTIONS PROHIBIT EXCLUSION OR
LIMITATION OF LIABILITY FOR IMPLIED WARRANTIES OR CONSEQUENTIAL OR INCIDENTAL
DAMAGES, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. YOU MAY ALSO HAVE
OTHER LEGAL RIGHTS THAT VARY FROM JURISDICTION TO JURISDICTION.

TERMINATION OF THIS AGREEMENT. Intel may terminate this Agreement
at any time
if you violate its terms. Upon termination, you will immediately destroy the
Software or return all copies of the Software to Intel.

APPLICABLE LAWS. Claims arising under this Agreement shall be governed by the
laws of California, excluding its principles of conflict of laws and the
United Nations Convention on Contracts for the Sale of Goods. You may not
export the Software in violation of applicable export laws and regulations.
Intel is not obligated under any other agreements unless they are in writing
and signed by an authorized representative of Intel.

GOVERNMENT RESTRICTED RIGHTS. The Software is provided with "RESTRICTED
RIGHTS." Use, duplication, or disclosure by the Government is subject to
restrictions as set forth in FAR52.227-14 and DFAR252.227-7013 et seq. or its
successor. Use of the Software by the Government constitutes acknowledgment
of Intel's proprietary rights therein. Contractor or Manufacturer is Intel
2200 Mission College Blvd., Santa Clara, CA
95052.

```
/*
* Copyright (c) 1983, 1988 Regents of the University of California.
* All rights reserved.
*
* Redistribution and use in source and binary forms are permitted
* provided that the above copyright notice and this paragraph are
* duplicated in all such forms and that any documentation,
* advertising materials, and other materials related to such
* distribution and use acknowledge that the software was developed
* by the University of California, Berkeley.  The name of the
```

```
* University may not be used to endorse or promote products derived
* from this software without specific prior written permission.
* THIS SOFTWARE IS PROVIDED ``AS IS'' AND WITHOUT ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED
* WARRANTIES OF MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.
*/
# Contributor: Fabian Affolter <fabian@affolter-engineering.ch>
# Maintainer: Fabian Affolter <fabian@affolter-engineering.ch>
pkgname=py-flake8-copyright
_pkgname=flake8-copyright
pkgver=0.2.0
pkgrel=0
pkgdesc="Extension for flake8 which checks for copyrights"
url="https://github.com/savoirfairelinux/flake8-copyright"
arch="noarch"
license="MIT"
depends="flake8"
makedepends="python3-dev"
source="https://files.pythonhosted.org/packages/source/${_pkgname:0:1}/$_pkgname/$_pkgname-$pkgver.tar.gz"
builddir="$srcdir"/$_pkgname-$pkgver

build() {
 cd "$builddir"
 python3 setup.py build || return 1
}

package() {
 cd "$builddir"
 python3 setup.py install --prefix=/usr --root="$pkgdir" || return 1
}

md5sums="c6348990c6d74933bf5d5f6a55a14bdf  flake8-copyright-0.2.0.tar.gz"
sha256sums="aeef26eb4d5223c9cd5b101e68175fcef6d2b353bf36da688fdde62fccfe2b73  flake8-copyright-
0.2.0.tar.gz"
sha512sums="bab1bfaeed3a525ac3c7da12b1f2ec338c204cc69b72d05cd39560e528faff5d586c3b1be9570f4a977a7e
2417b586e543bfba12abce256b2023c8c4993eeb90
  flake8-copyright-0.2.0.tar.gz"
SQLite Copyright
SQLite is in the
Public Domain
```

All of the deliverable code in SQLite has been dedicated to the public domain by the authors. All code authors, and representatives of the companies they work for, have signed affidavits dedicating their contributions to the public domain and originals of those signed affidavits are stored in a firesafe at the main offices of Hwaci. Anyone is free to copy, modify, publish, use, compile, sell, or distribute the original SQLite code, either in source code form or as a compiled binary, for any purpose, commercial or non-commercial, and by any means.

The previous paragraph applies to the deliverable code in SQLite - those parts of the SQLite library that you actually bundle and ship with a larger application. Portions of the documentation and some code used as part of the build process might fall under other licenses. The details here are unclear. We do not worry about the licensing of the documentation and build code so much because none
of these things are part of the core deliverable SQLite library.

All of the deliverable code in SQLite has been written from scratch. No code has been taken from other projects or from the open internet. Every line of code can be traced back to its original author, and all of those authors have public domain dedications on file. So the SQLite code base is clean and is uncontaminated with licensed code from other projects.
Obtaining An Explicit License To Use SQLite

Even though SQLite is in the public domain and does not require a license, some users want to obtain a license anyway. Some reasons for obtaining a license include:
You are using SQLite in a jurisdiction that does not recognize the public domain.
You are using SQLite in a jurisdiction that does not recognize the right of an author to dedicate their work to the public domain.
You want to hold a tangible legal document as evidence that you have the legal right to use and distribute SQLite.
Your legal department tells
you that you have to purchase a license.

If you feel like you really have to purchase a license for SQLite, Hwaci, the company that employs the architect and principal developers of SQLite, will sell you one.
Contributed Code

In order to keep SQLite completely free and unencumbered by copyright, all new contributors to the SQLite code base are asked to dedicate their contributions to the public domain. If you want to send a patch or enhancement for possible inclusion in the SQLite source tree, please accompany the patch with the following statement:
The author or authors of this code dedicate any and all copyright interest in this code to the public domain. We make this dedication for the benefit of the public at large and to the detriment of our heirs and successors. We intend this dedication to be an overt act of relinquishment in perpetuity of all present and future rights to this code under copyright law.

We are not able to accept patches or changes to SQLite that are not accompanied
by a statement such as the above. In addition, if you make changes or enhancements as an employee, then a simple statement such as the above is insufficient. You must also send by surface mail a copyright release signed by a company officer. A signed original of the copyright release should be mailed to:
Hwaci
6200 Maple Cove Lane
Charlotte, NC 28269
USA

A template copyright release is available in PDF or HTML. You can use this release to make future changes.

see http://www.sqlite.org/copyright.html
Copyright (c) 2016 The Khronos Group Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software source and associated documentation files (the "Materials"),
to deal in the Materials without restriction, including without limitation
the rights to use, copy, modify, compile, merge, publish, distribute,
sublicense, and/or sell copies of the Materials, and to permit persons to
whom the Materials are furnished to do so, subject the following terms and
conditions:

All modifications to the Materials used to create a binary that is
distributed to third parties shall be provided to Khronos with an
unrestricted license to use for the purposes of implementing bug fixes and
enhancements to the Materials;

If the binary is used as part of an OpenCL(TM) implementation, whether binary
is distributed together with or separately to that implementation, then
recipient must become an OpenCL Adopter and follow the published OpenCL
conformance process for that implementation,
details at:
http://www.khronos.org/conformance/;

The above copyright notice, the OpenCL trademark license, and this permission
notice shall be included in all copies or substantial portions of the
Materials.

THE MATERIALS ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE MATERIALS OR THE USE OR OTHER DEALINGS IN THE MATERIALS.

OpenCL is a trademark of Apple Inc. used under license by Khronos.
mini_sendmail - accept email on behalf of real sendmail

Copyright 1999,2015 by Jef Poskanzer <jef@mail.acme.com>.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING,
 BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.
Automatically generated by apkbuild-cpan, template 1
Contributor: Valery Kartel <valery.kartel@gmail.com>
Maintainer: Valery Kartel <valery.kartel@gmail.com>
pkgname=perl-bsd-resource
_pkgreal=BSD-Resource
pkgver=1.2909
pkgrel=1
pkgdesc="Perl extension implements the BSD process resource limit functions"
url="http://search.cpan.org/dist/BSD-Resource/"
arch="all"
license="GPL PerlArtistic"
cpandepends=""
cpanmakedepends="   "
depends="$cpandepends"
makedepends="perl-dev $cpanmakedepends"
subpackages="$pkgname-doc"
source="http://search.cpan.org/CPAN/authors/id/J/JH/JHI/$_pkgreal-$pkgver.tar.gz"

_builddir="$srcdir/$_pkgreal-$pkgver"

prepare() {
 cd "$_builddir"
 export CFLAGS=`perl -MConfig -E 'say $Config{ccflags}'`
 PERL_MM_USE_DEFAULT=1 perl Makefile.PL INSTALLDIRS=vendor
}

build() {
 cd "$_builddir"
 export CFLAGS=`perl -MConfig -E 'say $Config{ccflags}'`
 make && make test || return 1
}

package() {
 cd "$_builddir"
 make DESTDIR="$pkgdir" install || return 1
 find "$pkgdir"
 \(-name perllocal.pod -o -name .packlist \) -delete
}

```
md5sums="3c6dd2fa953088aa87e263f40818d012  BSD-Resource-1.2909.tar.gz"
sha256sums="c47d460e2bd00d8d049f6ff4a0f1f61957e289e8de45af5fc79e851e2e855e06  BSD-Resource-
1.2909.tar.gz"
sha512sums="5f489eaac5089e82081b7cf51d62638750e443751b49415407354da96b17771819b5e6e85529faa41ddd
85743363750157943c7f7700276cce2bd40a429fa430  BSD-Resource-1.2909.tar.gz"
# Maintainer: Natanael Copa <ncopa@alpinelinux.org>
pkgname=libart-lgpl
pkgver=2.3.21
pkgrel=5
pkgdesc="A library for high-performance 2D graphics"
url="http://www.levien.com/libart/"
arch="all"
license="LGPL"
depends=
makedepends=
subpackages="$pkgname-dev"
source="http://ftp.gnome.org/pub/GNOME/sources/libart_lgpl/2.3/libart_lgpl-$pkgver.tar.bz2
 "

_builddir="$srcdir"/libart_lgpl-$pkgver

prepare() {
 cd "$_builddir"
 update_config_sub || return 1
}
build() {
 cd "$_builddir"
 ./configure \
  --build=$CBUILD \
  --host=$CHOST \
  --prefix=/usr \
  || return 1
 make || return 1
}

package() {
 cd "$_builddir"
 make DESTDIR="$pkgdir" install || return 1
}

md5sums="08559ff3c67fd95d57b0c5e91a6b4302  libart_lgpl-2.3.21.tar.bz2"
```

1.107 github.com/aws/aws-sdk-go-v2/service/dynamodbstreams 1.28.0

1.107.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer

```
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
```

```
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
```

```
// the request.
//
//
This member is required.
ClientToken *string

// Configuration for consumption of the license. Choose a provisional
// configuration for workloads running with continuous connectivity. Choose a
// borrow configuration for workloads with offline usage.
//
// This member is required.
ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange
```

```
 // Information about
 the license.
 LicenseMetadata []types.Metadata

 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
```

```
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
```

```
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
```

ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization

OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step

```
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
```

```
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
```

```
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
```

```
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
```

```
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return
err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if
```

```
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
```

```
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
```

```
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack,
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
```

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

```
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}
```

```
type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
```

```
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options);
err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if
```

```
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
```

```
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
```

```
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
```

```
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
```

```
c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.

```
{
   "smithy": "2.0",
   "shapes": {
      "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
         "type": "integer"
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
         "type": "long"
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/DeregisterSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of name to filter by.</p>"
                }
            },
            "Values": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
                }
            },
            "Operator": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
                "traits": {
                    "smithy.api#documentation": "<p>An operator for filtering results.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
```

```
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
```

```
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

          "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
                 }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
      "type": "operation",
      "input": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/GetServiceSettings"

       },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
      "type": "structure",
      "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
          "traits": {
```

```
                "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
              "traits": {
                "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
              }
            },
            "StatusMessage": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
              "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
              }
            },
            "HomeRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
          "type": "structure",
          "members": {
            "AmiId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
              }
            },
            "InstanceID": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
              }
            },
            "InstanceType": {
              "target": "smithy.api#String",
              "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
```

```
            }
        },
        "AccountID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
        "Region": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
        },
        "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
        },
        "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
        },
        "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
        },
        "SubscriptionName": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
              }
            },
            "OsVersion": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
              }
            },
            "SubscriptionProviderCreateTime": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
              }
            },
            "SubscriptionProviderUpdateTime": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
              }
            },
            "DualSubscription": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
              }
            },
            "RegisteredWithSubscriptionProvider": {
              "target": "smithy.api#String",
              "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
          "type": "list",
          "member": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation":
"<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
          "type": "service",
          "version": "2018-05-10",
          "operations": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
             },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
          }
        ],
        "traits": {
          "aws.api#service": {
            "sdkId": "License Manager Linux Subscriptions",
             "arnNamespace": "license-manager-linux-subscriptions",
            "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
          },
          "aws.auth#sigv4": {
            "name": "license-manager-linux-subscriptions"
          },
          "aws.protocols#restJson1": {},
          "smithy.api#cors": {
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id"
            ],
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager,
    you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager Linux Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region": {
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
```

```
support dual-stack, dispatching the request MAY return an error.",
                "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseFIPS"
                        },
                        true
                      ]
                    }

        ],
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                  "type": "error"
                },
                {
```

```
                "conditions": [],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]

}
                    ],
                    "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                    "type": "error"
                  },
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": {
                        "ref": "Endpoint"
                      },
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],
                "type": "tree"

              }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "isSet",
                      "argv": [
                        {
                          "ref": "Region"
                        }
                      ]
```

```
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {

        "fn": "aws.partition",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ],
                            "assign": "PartitionResult"
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {

                                  "ref": "UseFIPS"
                                        },
                                        true
                                    ]
                                },
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]
                                }

    ],
                            "rules": [
                                {
                                    "conditions": [
                                        {
                                            "fn": "booleanEquals",
                                            "argv": [
                                                true,
                                                {
```

```
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

                    },
                                            "supportsFIPS"
                                        ]
                                    }
                                ]
                            },
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                                         {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],

        "rules": [
                                        {
                                            "conditions": [],
                                            "endpoint": {
                                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],

                     "type": "tree"
                                }
                            ],
```

```
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {

    "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {

            "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true

                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [],
```

```
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "FIPS is enabled
but this partition does not support FIPS",
        "type": "error"
    }
],
"type": "tree"
},
{
"conditions": [
    {
        "fn": "booleanEquals",
        "argv": [
            {
                "ref": "UseDualStack"
            },
            true

]
    }
],
"rules": [
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    true,
                    {
```

```
                                        "fn": "getAttr",
                                        "argv": [
                                            {

                                            "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "rules": [

        {
                                        "conditions": [],
                                        "endpoint": {
                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"

                    }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "error": "DualStack is enabled but this partition does not support DualStack",
                            "type": "error"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
```

```
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
      },
      {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
      }
    ],
    "type": "tree"
  }
 ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
```

```
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": true,
          "UseDualStack": false
        }
      },
      {

    "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
          }

    },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
          }
        },
        "params": {
          "Region": "cn-north-1",
          "UseFIPS": true,
          "UseDualStack": true
        }
```

```
        },
        {

    "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
             },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {

     "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
              }
```

```
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }

    },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
```

```
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {

    "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
```

```
false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                 }
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {

          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                }
            },
            "params": {
```

```
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }
          },
          "params": {
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {

          "documentation": "For custom endpoint with fips enabled and dualstack disabled",
          "expect": {
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
```

```
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled LinuxSubscriptionsDiscovery"

     },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
        "type": "structure",
        "members": {
          "SourceRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
```

```
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "OrganizationIntegration": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
                "traits": {
                    "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
```

```
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "Instances"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n          <li>\n
  <p>\n              <code>AccountID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
    <code>AmiID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>DualSubscription</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceType</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>ProductCode</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Region</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Status</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>UsageOperation</code>\n            </p>\n          </li>\n        </ul>\n        <p>For each filter, you can use
one of the following <code>Operator</code>
 values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
```

```
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
          "type": "structure",
          "members": {
            "Instances": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
              }
            },
            "NextToken": {

           "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

   "items": "Subscriptions"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n       <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n <li>\n              <p>\n                  <code>Subscription</code>\n              </p>\n          </li>\n          </ul>\n <p>The
       valid Operators for this filter are:</p>\n          <ul>\n          <li>\n              <p>\n <code>contains</code>\n              </p>\n          </li>\n          <li>\n              <p>\n <code>equals</code>\n              </p>\n          </li>\n          <li>\n              <p>\n <code>Notequal</code>\n              </p>\n          </li>\n          </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
```

```
 the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
```

```
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "RegisteredSubscriptionProviders"
            }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSources": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
                "traits": {
                    "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }

 },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
            "RegisteredSubscriptionProviders": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
                "traits": {
                    "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
                }
            },

             "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {

         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
```

```
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
                    "documentation": "Equal operator"
                },
                {
                    "name": "NOT_EQUAL",
                    "value": "NotEqual",
                    "documentation": "Not equal operator"
                },
                {
                    "name": "CONTAINS",
                    "value": "Contains",
                    "documentation": "Contains operator"
                }
            ],
            "smithy.api#length": {
                "min": 1,
                "max": 20
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "Enabled",
                    "value": "Enabled",
                    "documentation": "Enabled OrganizationIntegration"
                },
                {
                    "name": "Disabled",
                    "value": "Disabled",
                    "documentation": "Disabled OrganizationIntegration"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/RegisterSubscriptionProvider"

        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
            "smithy.api#required": {}
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
            "smithy.api#required": {}
```

```
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
 {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
 {
              "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider,
```

```
License Manager can get subscription data from the registered provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "InProgress",
              "value": "InProgress",
              "documentation": "InProgress status"
            },
            {
              "name": "Completed",
              "value": "Completed",
              "documentation": "Completed status"
            },
            {
              "name": "Successful",
              "value": "Successful",
              "documentation": "Successful status"
```

```
            },
            {
              "name": "Failed",
              "value": "Failed",
              "documentation": "Failed status"
            }
          ]
        }
      },

      "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            }
          }
        },
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
          },
          "smithy.api#uniqueItems": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
          "Name":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the subscription.</p>"
            }
          },
```

```
            "Type": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": "<p>The total amount of running instances using this
 subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
```

```
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "ACTIVE",
            "value": "ACTIVE",
            "documentation": "ACTIVE status"
          },
          {
            "name": "INVALID",
            "value": "INVALID",

"documentation": "INVALID status"
          },
          {
            "name": "PENDING",
            "value": "PENDING",
            "documentation": "PENDING status"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
        "type": "structure",
        "members":
{
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
             "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tagKeys": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
                "traits": {

              "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                    "smithy.api#httpQuery": "tagKeys",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

    },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/UpdateServiceSettings"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
            "smithy.api#required": {}
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
          "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
            "smithy.api#required": {}
```

```
            }
          },
          "AllowUpdate": {
            "target":
 "smithy.api#Boolean",
            "traits": {
              "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
             "traits": {
              "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
            }

       },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
          }
        }
      }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
```

```
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
```

```
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
```

```
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
```

```
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
```

```
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string
```

```
 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
```

```
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
```

```
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
```

Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT

OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
          }
        },
        "ActiveDirectoryType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
          "traits": {
            "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
          }
        }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
            },
            "DomainIpv4List": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 2
                    }
                }
            },
            "DomainCredentialsProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
            },
            "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
```

```
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "SELF_MANAGED",
              "value": "SELF_MANAGED",
              "documentation": "SELF_MANAGED type of Active Directory"
            },
            {
              "name": "AWS_MANAGED",
              "value": "AWS_MANAGED",
              "documentation": "AWS_MANAGED type of Active Directory"
            }
          ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
```

```
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n          </note>",
            "smithy.api#http":
 {
              "code": 200,
              "method": "POST",
              "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                "smithy.api#required": {}
              }
```

```
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
               }
            },
            "Tags": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
               }
            }
         },
         "traits": {

      "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
         "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
             }
         },
         "traits": {
            "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
```

```
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
```

```
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
              "smithy.api#required": {}
            }
          },
          "LicenseServerSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
            }
```

```
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
          "type": "union",
          "members": {
            "SecretsManagerCredentialsProvider":
 {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
              "traits": {
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
           },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/DeregisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
```

```
    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/DisassociateUser"
        },
        "smithy.api#idempotent": {}
```

```
    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
      "type": "structure",
      "members": {
        "Username": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
          }
        },
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
          }
        },
        "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
          "traits": {
            "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
          }
        },
        "InstanceUserArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
          }
        },
        "Domain": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
      "type": "structure",
```

```
        "members": {
          "InstanceUserSummary":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
              "smithy.api#length": {
                "min": 1
              },

    "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Attribute": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
            }
```

```
            },
            "Value": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>Value of the filter.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
         "type": "union",
         "members": {
            "ActiveDirectoryIdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
         "type": "structure",
         "members": {
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
```

```
        "Settings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
            "smithy.api#required": {}
          }
        },
        "Product": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of the identity provider.</p>",
            "smithy.api#required": {}
          }
        },
        "IdentityProviderArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
          }
        },
        "FailureMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes an identity provider.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
      "type": "list",
      "member": {

        "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
      "type": "structure",
      "members": {
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
            "smithy.api#required": {}
          }
        },
        "Products": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
           "traits": {
            "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
            "smithy.api#required": {}
          }
        },
        "LastStatusCheckDate": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The date of the last status check.</p>"
          }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
      "type": "structure",
      "members": {
        "Username": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
            "smithy.api#required": {}
          }
        },
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },

    "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
          "traits": {
            "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
            "smithy.api#required": {}
          }
        },
        "InstanceUserArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
           }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
          }
        },
```

```
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
             "smithy.api#error": "server",
            "smithy.api#httpError": 500
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
```

```
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
      },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",

         "x-api-key",
            "authorization",
            "x-amz-date",
            "x-amz-security-token",
            "Access-Control-Allow-Headers",
            "Access-Control-Allow-Methods",
            "Access-Control-Allow-Origin"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
```

```
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region":
{
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
              "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
```

```
                }
            ]
        }
    ],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseFIPS"
                        },
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [
                {

                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": {
                    "ref": "Endpoint"
                },

"properties": {},
                "headers": {}
            },
            "type": "endpoint"
        }
```

```
      ],
      "type": "tree"
    },
    {
      "conditions": [
        {
          "fn": "isSet",
          "argv": [
            {
              "ref": "Region"
            }
          ]
        }
      ],
      "rules": [
        {
          "conditions": [
            {
              "fn": "aws.partition",

              "argv": [
                {
                  "ref": "Region"
                }
              ],
              "assign": "PartitionResult"
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },

true
                  ]
                },
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseDualStack"
                    },
                    true
```

```
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

 "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      }
                    ]
                  },

                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }

            ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
```

```
                },
                "type": "endpoint"
              }

    ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [

  {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "fn": "getAttr",
                        "argv": [

                {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      },
                      true
                    ]
                  }
```

```
                                ],
                                "rules": [
                                    {
                                        "conditions": [],
                                        "endpoint": {

                "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS is enabled but this partition does not support FIPS",
                                "type": "error"

}
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]
                                }
                            ],
                            "rules": [
                                {

        "conditions": [
                                        {
                                            "fn": "booleanEquals",
                                            "argv": [
                                                true,
                                                {
                                                    "fn": "getAttr",
                                                    "argv": [
                                                        {
```

```
                                        "ref": "PartitionResult"
                                    },
                                    "supportsDualStack"
                                ]

        }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }

                    ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "endpoint": {
                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

            "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
    }
],
"type": "tree"
```

```
            },
            {
              "conditions": [],
              "error": "Invalid Configuration: Missing Region",
              "type": "error"
            }
          ]
        },
        "smithy.rules#endpointTests": {
          "testCases": [
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
              "expect":
{
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
```

```
            "endpoint":
{
                "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
                "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
```

```
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": false

    }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
              }
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
              "Region": "us-isob-east-1",

"UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
              }
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
            "expect": {

           "endpoint": {
                "url": "https://example.com"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false,
              "Endpoint": "https://example.com"
            }
```

```
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "Missing region",
      "expect": {
        "error": "Invalid Configuration: Missing Region"
      }
    }
  ],
```

```
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
        "type": "structure",
        "members": {
          "ProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
             "traits": {
               "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
            }
          },
          "HealthStatus": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
            "traits": {
              "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
            }
          },
          "Ipv4Address": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
            }
          },
          "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of license server.</p>"
```

```
            }
          },
          "ServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network \n\t\t\taddress of the RDS license server endpoint.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
          },
          "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
              "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
          },
          "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
              "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },
```

```
            "CreationTime": {
                "target": "smithy.api#Timestamp",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "PROVISIONING",
                    "value": "PROVISIONING",
                    "documentation": ""
                },
                {
                    "name": "PROVISIONING_FAILED",
                    "value": "PROVISIONING_FAILED",
                    "documentation": ""
                },
                {
                    "name": "PROVISIONED",
                    "value": "PROVISIONED",
                    "documentation": ""
                },
                {
                    "name": "DELETING",
                    "value": "DELETING",
                    "documentation": ""
                },
                {
```

```
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
    "type": "string",
    "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
    }
},
 "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
    "type": "structure",
    "members": {
        "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>",
```

```
                "smithy.api#required": {}
              }
            },
            "ServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
```

```
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/ListIdentityProviders"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
```

```
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
         "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
    {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
```

```
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
            "InstanceSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
```

```
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/ListLicenseServerEndpoints"
            },

         "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "LicenseServerEndpoints"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
         "type": "structure",
         "members": {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>IdentityProviderArn</p>\n            </li>\n         </ul>"
               }
            },
```

```
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
         "type": "structure",
         "members": {
            "LicenseServerEndpoints": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
                "traits": {
                  "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
         "type":
 "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
```

```
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n
</li>\n          <li>\n            <p>Domain</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
          "type": "structure",
          "members": {
            "ProductUserSummaries": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

```
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
    }
      }
    },
    "traits": {
      "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
    "type": "structure",
    "members": {
      "Tags": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
        "traits": {
          "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
        }
      }
    },
    "traits": {
      "smithy.api#output": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
```

```
      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummaries": {

             "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
         "type": "structure",
         "members": {
            "Username":
{
               "target": "smithy.api#String",
               "traits": {
```

```
                "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
                "smithy.api#required": {}
            }
        },
        "Product": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                "smithy.api#required": {}
            }
        },
        "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a product for this user.</p>",
                "smithy.api#required": {}
            }
        },
        "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {

        "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "SubscriptionStartDate": {
            "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/RegisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
{
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
"<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
```

```
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

       "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
```

```
        "members": {
          "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
        "type": "union",
        "members": {
          "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
             "traits": {
              "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

  "target": "smithy.api#String"
            }
        },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
            "smithy.api#length": {
              "min": 1
            },
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
            "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
              }
            ],
            "traits": {
              "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
              "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
              }

        }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
```

```
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {

 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                "smithy.api#required": {}
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
              }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/StopProductSubscription"
        }
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
      "type": "structure",
      "members": {
        "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
            }
          },
          "IdentityProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
```

```
                "smithy.api#required": {}
            }

    }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
"<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
```

```
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
```

```
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

          }
            },
            "TagKeys": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
              "traits": {
                "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                "smithy.api#httpQuery": "tagKeys",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
```

```
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
```

```
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
               }
            },
            "UpdateSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
               "traits": {
                  "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n            <li>\n               <p>Subnets which you want to add to provision VPC endpoints.</p>\n            </li>\n
      <li>\n               <p>Subnets which you want to remove the VPC endpoints from.</p>\n            </li>\n
<li>\n               <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n            </li>\n         </ul>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
         "type": "structure",
         "members": {
            "IdentityProviderSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
               "traits": {
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
         "type": "structure",
         "members": {
            "AddSubnets": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
```

```
                "smithy.api#required": {}
            }
        },
        "RemoveSubnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
                "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
                "smithy.api#required": {}
            }
        },
        "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
            "traits": {
                "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A parameter is not valid.</p>",
        "smithy.api#error": "client"
      }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
```

```
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
```

```
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
 nil {
  return err
```

```
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of,

the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this
License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You

meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate

comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop

Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.108 aws-sdk-go-v2-service-ssooidc 1.32.0

1.108.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID

```
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
```

```
      uses: actions/checkout@v2
      with:
        path: sdkbase
        ref: ${{ github.base_ref }}
    - name: Checkout this ref
      uses: actions/checkout@v2
      with:
        path: new-ref
        fetch-depth: 0
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
```

```
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
```

```
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
```

```
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
```

```
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
```

```
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
```

setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity

ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry

```
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
```

```
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
```

```
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
```

```
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
```

```
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
```

```
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
```

```
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
```

```
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
```

```
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
```

```
 Region:
      region,
 ServiceID:     ServiceID,
 OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType
```

```
// Unique, case-sensitive identifier that you provide to ensure the idempotency of
// the request.
//
// This member is required.
ClientToken *string

// License entitlements.
//
// This member is required.
Entitlements []types.EntitlementData

// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string
```

```
// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
```

```
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
```

```
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
            }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
```

```
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
           },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
```

registered to your account. ",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation":
 " The Amazon Resource Name (ARN) of the BYOL registration resource to get details for. ",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation": " The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request. "
              }
            },
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

           "traits": {
                "smithy.api#documentation": " The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request. "
              }
            },
            "SecretArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
              "traits": {
                "smithy.api#documentation": " The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request. "

```
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
                }
            },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
          "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
          },
          "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
          },
          "AccountID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
          },
          "Region": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
          },
          "UsageOperation": {
```

```
            "target": "smithy.api#String",

    "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
          },
          "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
              "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
          },
          "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
              "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
          },
          "SubscriptionName": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
            }
          },
          "OsVersion": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
            }
          },
          "SubscriptionProviderCreateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
          },
          "SubscriptionProviderUpdateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
```

```
registered \n\t\t\tthird-party Linux subscription provider.</p>"
                }
            },
            "DualSubscription": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
                }
            },
            "RegisteredWithSubscriptionProvider": {
                "target": "smithy.api#String",
                "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
         },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
        }
    ],
    "traits": {
        "aws.api#service": {
            "sdkId": "License Manager Linux Subscriptions",
             "arnNamespace": "license-manager-linux-subscriptions",
            "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
            "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
            "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
```

```
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
```

```
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseFIPS"
                        },
                        true
                      ]
                    }

        ],
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                  "type": "error"
                },
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            {
                              "ref": "UseDualStack"
                            },
                            true
                          ]

}
                      ],
                      "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                      "type": "error"
                    },
                    {
                      "conditions": [],
                      "endpoint": {
```

```
                    "url": {
                        "ref": "Endpoint"
                    },
                    "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"

    }
    ],
    "type": "tree"
},
{
    "conditions": [],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Region"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {

    "fn": "aws.partition",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ],
                            "assign": "PartitionResult"
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
```

```
                "argv": [
                  {

              "ref": "UseFIPS"
                  },
                  true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }

],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"

        },
                              "supportsFIPS"
                          ]
                        }
                      ]
                    },
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        true,
                        {
                          "fn": "getAttr",
                          "argv": [

                           {
                                "ref": "PartitionResult"
```

```
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],

    "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],

                "type": "tree"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {

        "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseFIPS"
                            },
                            true
```

```
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

          "fn": "booleanEquals",
                      "argv": [
                        {
                          "fn": "getAttr",
                          "argv": [
                            {
                              "ref": "PartitionResult"
                            },
                            "supportsFIPS"
                          ]
                        },
                        true

                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "rules": [
                      {
                        "conditions": [],
                        "endpoint": {
                          "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                          "headers": {}
                        },
                        "type": "endpoint"
                      }
                    ],
                    "type": "tree"
                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS is enabled
```

```
but this partition does not support FIPS",
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true

                    ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [
                                        {
                                            "fn": "booleanEquals",
                                            "argv": [
                                                true,
                                                {
                                                    "fn": "getAttr",
                                                    "argv": [
                                                        {

                                                            "ref": "PartitionResult"
                                                        },
                                                        "supportsDualStack"
                                                    ]
                                                }
                                            ]
                                        }
                                    ],
                                    "rules": [
                                        {
                                            "conditions": [],
                                            "rules": [

        {
                                                    "conditions": [],
                                                    "endpoint": {
                                                        "url": "https://license-manager-linux-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],
                                    "type": "tree"

                            }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
```

```
        ],
        "type": "tree"
      }
    ]
  },
  "smithy.rules#endpointTests": {
    "testCases": [
      {
        "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

    }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": true,
          "UseDualStack": true
        }
      },
      {
        "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": true,
          "UseDualStack": false
        }
      },
      {

     "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
          }
        },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": true
        }
      },
```

```
                {
                  "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
                    }

            },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                    }
                  },
                  "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                  }
                },
                {

   "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                    }
                  },
                  "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                    }
```

```
    },
    "params": {
      "Region": "cn-north-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {
    "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
      }
    },
    "params": {
      "Region": "cn-north-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
      }
    },
    "params": {
      "Region": "us-gov-east-1",
      "UseFIPS": true,
      "UseDualStack": true
    }
  },
  {
    "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
      }

   },
    "params": {
      "Region": "us-gov-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
```

```
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                  },
                  "params": {

               "Region": "us-iso-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                    }
                  },
                  "params": {
                    "Region": "us-iso-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
             }
          },
```

```
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

     "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

},
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
```

```
disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://example.com"
                      }
                    },
                    "params": {
                      "UseFIPS": false,
                      "UseDualStack": false,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {

                    "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                    "expect": {
                      "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                    },
                    "params": {
                      "Region": "us-east-1",
                      "UseFIPS": true,
                      "UseDualStack": false,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {
                    "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                    "expect": {
                      "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                    },
                    "params": {

 "Region": "us-east-1",
                      "UseFIPS": false,
                      "UseDualStack": true,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {
                    "documentation": "Missing region",
                    "expect": {
                      "error": "Invalid Configuration: Missing Region"
                    }
                  }
                ],
                "version": "1.0"
              }
            }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "Enabled",
            "value": "Enabled",
            "documentation": "Enabled LinuxSubscriptionsDiscovery"

    },
          {
            "name": "Disabled",
            "value": "Disabled",
            "documentation": "Disabled LinuxSubscriptionsDiscovery"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "OrganizationIntegration": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
          "traits": {
            "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n
  <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
    <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
```

<code>InstanceType</code>\n \n \n \n \n
<code>ProductCode</code>\n \n \n \n \n
<code>Region</code>\n \n \n \n \n
<code>Status</code>\n \n \n \n \n
<code>UsageOperation</code>\n \n \n \n For each filter, you can use one of the following <code>Operator</code>
values to \n \t\tdefine the behavior of the filter: \n \n \n \n
<code>contains</code>\n \n \n \n \n
<code>equals</code>\n \n \n \n \n
<code>Notequal</code>\n \n \n "
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": " The maximum items to return in a request. "
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " A token to specify where to
start paginating. This \n\tis the nextToken from a previously truncated response. ",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
          "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
              "smithy.api#documentation": " An array that contains instance objects. "
            }
          },
          "NextToken": {

       "target": "smithy.api#String",
            "traits": {

```
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

  "items": "Subscriptions"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
```

```
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n         <p>The valid names for this filter are:</p>\n         <ul>\n
<li>\n               <p>\n                  <code>Subscription</code>\n               </p>\n            </li>\n         </ul>\n
<p>The
 valid Operators for this filter are:</p>\n         <ul>\n            <li>\n               <p>\n
<code>contains</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>equals</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>Notequal</code>\n               </p>\n            </li>\n         </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
```

```
            "target": "smithy.api#String",
             "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListRegisteredSubscriptionProviders"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "RegisteredSubscriptionProviders"
          }
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSources": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
          "traits": {
            "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
          }
        },
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }

  },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
          "traits": {
            "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
          }
        },

       "NextToken": {
          "target": "smithy.api#String",
          "traits": {
```

```
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
          },
          "errors": [
            {

         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "resourceArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                 "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
```

```
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
      "type": "structure",
      "members": {
        "tags": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
          "traits": {
            "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "EQUAL",
            "value": "Equal",
            "documentation": "Equal operator"
          },
          {
            "name": "NOT_EQUAL",
            "value": "NotEqual",
            "documentation": "Not equal operator"
          },
          {
            "name": "CONTAINS",
            "value": "Contains",
            "documentation": "Contains operator"
          }
        ],
        "smithy.api#length": {
          "min": 1,
          "max": 20
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "Enabled",
            "value": "Enabled",
            "documentation": "Enabled OrganizationIntegration"
          },
          {
            "name": "Disabled",
            "value": "Disabled",
            "documentation": "Disabled OrganizationIntegration"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
        "smithy.api#http": {
```

```
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
```

```
            },
            "SubscriptionProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
         "type": "structure",
         "members": {
            "SubscriptionProviderArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
               }
            },
            "SubscriptionProviderSource": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
               "traits": {
                  "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
               }
            },
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
```

```
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "InProgress",
              "value": "InProgress",
              "documentation": "InProgress status"
            },
            {
              "name": "Completed",
              "value": "Completed",
              "documentation": "Completed status"
            },
            {
              "name": "Successful",
              "value": "Successful",
              "documentation": "Successful status"
            },
            {
              "name": "Failed",
              "value": "Failed",
              "documentation": "Failed status"
            }
          ]
        }
      },

      "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            }
          }
        },
        "traits": {
          "smithy.api#length": {
```

```
                "min": 1,
                "max": 100
            },
            "smithy.api#uniqueItems": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
            "Name":
{
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the subscription.</p>"
                }
            },
            "Type": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
```

```
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
                },
                {
                    "name": "INVALID",
                    "value": "INVALID",

   "documentation": "INVALID status"
                },
                {
                    "name": "PENDING",
                    "value": "PENDING",
```

```
                "documentation": "PENDING status"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
           },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
              "method": "PUT",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
```

```
        "type": "structure",
        "members":
{
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
        "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
```

```
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}
              }
            },
            "tagKeys": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
              "traits": {

            "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                "smithy.api#httpQuery": "tagKeys",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

         },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
```

```
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                "smithy.api#required": {}
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                "smithy.api#required": {}
              }
            },
            "AllowUpdate": {
              "target":
 "smithy.api#Boolean",
              "traits": {
                "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
```

```
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                   "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
               }
            },
            "StatusMessage": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
               "traits": {
                  "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
               }

       },
            "HomeRegions": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                  "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated data for Linux\n      subscriptions.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
         }
      }
   }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
```

```
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
```

```
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
```

```
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
```

```
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
```

```
//
// This member is required.
LicenseType types.LicenseType

// The ID of the workspace to associate the license with.
//
// This member is required.
WorkspaceId *string

// A token from Grafana Labs that ties your Amazon Web Services account with a
// Grafana Labs account. For more information, see [Link your account with Grafana Labs].
//
// [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
GrafanaToken *string

noSmithyDocumentSerde
}

type AssociateLicenseOutput
struct {

// A structure containing data about the workspace.
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}
```

```
if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
```

```
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
```

```
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
  return err
```

```
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
```

CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {

```
        "type": "structure",
        "members": {
          "DirectoryId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
            "traits": {
              "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
          },
          "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
          },
          "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
              "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
          "DomainName": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
            }
          },
          "DomainIpv4List": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
            "traits": {
              "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 2
              }
```

```
            }
          },
          "DomainCredentialsProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
            }
          },
          "DomainNetworkSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "SELF_MANAGED",
              "value": "SELF_MANAGED",
              "documentation": "SELF_MANAGED type of Active Directory"
            },
            {
              "name": "AWS_MANAGED",
              "value": "AWS_MANAGED",
              "documentation": "AWS_MANAGED type of Active Directory"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
{
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
```

```
"com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
    "type": "structure",
    "members": {
      "Username": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
          "smithy.api#required": {}
        }
      },
      "InstanceId": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
          "smithy.api#required": {}
        }
      },
      "IdentityProvider": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
        "traits": {
          "smithy.api#documentation": "<p>The identity provider for the user.</p>",
          "smithy.api#required": {}
        }
      },
      "Domain": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
        }
      },
      "Tags": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
        "traits": {
          "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
        }
      }
    },
    "traits": {

  "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
    "type": "structure",
    "members": {
      "InstanceUserSummary": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },

        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                  "smithy.api#required": {}
               }
            },
            "Tags": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
          "SecretsManagerCredentialsProvider":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
```

```
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
```

<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete. ",
                "smithy.api#required": {}
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": " The type of License Server that the delete request refers to. ",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
              "traits": {
                "smithy.api#documentation": " Shows details from the <code>LicenseServerEndpoint</code> resource that was deleted. "
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
         "type": "structure",
         "members": {
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity provider to deregister.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
```

```
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

      }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
```

```
                "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
              }
            },
            "InstanceUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummary":
{
              "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
          "type": "structure",
          "members": {
            "Subnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                "smithy.api#length": {
```

```
                    "min": 1
                },

    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
```

```
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
```

```
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
               }
            },
            "FailureMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
         "type": "list",
         "member": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
         "type": "structure",
         "members": {
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                  "smithy.api#required": {}
               }
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                  "smithy.api#required": {}
               }
            },
            "Products": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
                "traits": {
                  "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                  "smithy.api#required": {}
               }
```

```
            },
            "LastStatusCheckDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date of the last status check.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                  "smithy.api#required": {}
               }
            },

      "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
```

```
\n\t\t\tabout the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                 }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
                }
            },
            "AssociationDate": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
                }
            },
            "DisassociationDate": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
```

```
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
   "type": "list",
   "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
   }
},
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
   "type": "structure",
   "members": {
      "message": {
         "target": "smithy.api#String"
      }
   },
   "traits": {
      "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
       "smithy.api#error": "server",
      "smithy.api#httpError": 500
   }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
   "type": "string",
   "traits": {
      "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
   }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
   "type": "list",
   "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
   }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
   "type": "service",
   "version": "2018-05-10",
   "operations": [
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
       },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
      },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
            },
            {
"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
        ],
        "traits": {
            "aws.api#service": {
              "sdkId": "License Manager User Subscriptions",
              "arnNamespace": "license-manager-user-subscriptions",
              "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
```

```
            "name": "license-manager-user-subscriptions"
          },
          "aws.protocols#restJson1": {},
          "smithy.api#cors": {
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id",
              "content-length",

        "x-api-key",
              "authorization",
              "x-amz-date",
              "x-amz-security-token",
              "Access-Control-Allow-Headers",
              "Access-Control-Allow-Methods",
              "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager User Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region":
{
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                "type": "Boolean"
              },
```

```
        "UseFIPS": {
          "builtIn": "AWS::UseFIPS",
          "required": true,
          "default": false,
          "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
          "type": "Boolean"
        },
        "Endpoint": {
          "builtIn": "SDK::Endpoint",
          "required": false,
          "documentation": "Override the endpoint used to send this request",
          "type": "String"
        }
      },
      "rules": [
        {
          "conditions": [
            {
              "fn": "isSet",
              "argv": [
                {
                  "ref": "Endpoint"
                }
              ]
            }
           ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
                    true
                  ]
                }
              ],
              "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
              "type": "error"
            },
            {
              "conditions": [
                {
```

```
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "aws.partition",

                      "argv": [
                        {
                          "ref": "Region"
                        }
```

```
                ],
                "assign": "PartitionResult"
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
```

true

```
                    ]
                  },
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
```

"fn": "booleanEquals",

```
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"
                              },
                              "supportsFIPS"
                            ]
                          }
                        ]
                      },
```

```
                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }

                ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }

    ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
```

```
{
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "fn": "getAttr",
                                            "argv": [

                                {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsFIPS"
                                        ]
                                    },
                                    true
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {

                        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

    }
                    ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]

         }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
```

```
                ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "DualStack is enabled but this partition does not support DualStack",
                    "type": "error"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

            "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
      }
    ],
    "type": "tree"
  },
  {
    "conditions": [],
    "error": "Invalid Configuration: Missing Region",
    "type": "error"
  }
 ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect":
{
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",

    "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS":
true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint":
{
                "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
```

```
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false

    }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

            },
              "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
              },
              "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                }
              },
              "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
              },
              "params": {
                "Region": "us-isob-east-1",

  "UseFIPS": false,
                "UseDualStack": true
              }
            },
```

```
                {
                  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                    }
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
                  "expect": {

                   "endpoint": {
                      "url": "https://example.com"
                    }
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }
                  },
                  "params": {
                    "UseFIPS": false,
                    "UseDualStack":
 false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                  "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                  },
```

```
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
        "type": "structure",
        "members": {
          "ProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
             "traits": {
               "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
            }
          },
          "HealthStatus": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
            "traits": {
              "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
            }
          },
```

```
            "Ipv4Address": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
               }
            },
            "ServerType": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
               "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>"
               }
            },
            "ServerEndpoint": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
               }
            },
            "LicenseServerEndpointId": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
```

```
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
{
              "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the
RDS \n\t\t\tlicense server.</p>"
            }
          },
          "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
              "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent
the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },

         "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when License Manager created the license server
endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop
Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
```

```
                {
                    "name": "UNHEALTHY",
                    "value": "UNHEALTHY",
                    "documentation": ""
                },
                {
                    "name": "NOT_APPLICABLE",
                    "value": "NOT_APPLICABLE",
                    "documentation": ""
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
        "type": "structure",
        "members": {
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single request.</p>"
            }
        },
        "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n <ul>\n <li>\n <p>Product</p>\n </li>\n <li>\n <p>DirectoryId</p>\n </li>\n </ul>"
            }
        },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
    "type": "structure",
    "members": {
        "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                "smithy.api#required": {}
            }
        },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
```

```
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
     "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/instance/ListInstances"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
        }
    }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
      "type": "structure",
      "members":
{
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
      "type": "structure",
      "members": {
        "InstanceSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next
```

token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
"type": "operation",
"input": {
"target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
},
"output": {
"target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
},
"errors": [
{
"target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
}
],
"traits": {
"smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",
"smithy.api#http": {
"code": 200,
"method": "POST",
"uri": "/license-server/ListLicenseServerEndpoints"
},

"smithy.api#paginated": {
"inputToken": "NextToken",

```
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "LicenseServerEndpoints"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>IdentityProviderArn</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
```

```
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
         "type":
 "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
```

```
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
```

```
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

             }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
```

```
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
```

```
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                 "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
          "type": "structure",
          "members": {
            "Username":
 {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
                 "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                 "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                 "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                 "smithy.api#required": {}
              }
            },
             "Status": {
              "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
{
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {

   "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits":
{
                    "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
"<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

    "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

           "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
          "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
        "type": "union",
        "members": {
          "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
             "traits": {
              "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

"target": "smithy.api#String"
            }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity
```

provider. \n <note>\n Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as Pending billing status) in Amazon Web Services Billing. For more information, see Viewing your\n\t\t\t\tmonthly charges in the Amazon Web Services Billing User Guide. \n </note>",
"smithy.api#http": {
"code": 200,
"method": "POST",
"uri": "/user/StartProductSubscription"
}

}
},
"com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
"type": "structure",
"members": {
"Username": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The user name from the identity provider of the user. ",
"smithy.api#required": {}
}
},
"IdentityProvider": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
"traits": {
"smithy.api#documentation": " An object that specifies details for the identity provider. ",
"smithy.api#required": {}
}
},
"Product": {
"target": "smithy.api#String",
"traits": {

"smithy.api#documentation": " The name of the user-based subscription product. \n Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n ",
"smithy.api#required": {}
}
},
"Domain": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The domain name of the Active Directory that contains the user for whom to start the product \n\t\t\tsubscription. "
}
},

```
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
              }

  }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
```

```
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
                  "smithy.api#required": {}
               }

   }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
         "type": "list",
         "member": {
            "target": "smithy.api#String"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
         }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

"min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        },
        "Tags": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
          "traits": {
            "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
```

```
to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

            }
               },
               "TagKeys": {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
                  "traits": {
                     "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                     "smithy.api#httpQuery": "tagKeys",
                     "smithy.api#required": {}
                  }
               }
            },
            "traits": {
               "smithy.api#input": {}
            }
         },
         "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
            "type": "structure",
            "members": {},
            "traits": {
               "smithy.api#output": {}
            }
         },
         "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
            "type": "operation",
            "input": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
             },
            "output": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
            },
            "errors": [
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
               }
            ],
```

```
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

       "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n <ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n <li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
```

```
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
```

```
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A parameter is not valid.</p>",
          "smithy.api#error": "client"
        }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {
```

```
// License consumption token.
//
// This member is required.
LicenseConsumptionToken *string

// License beneficiary.
Beneficiary *string

noSmithyDocumentSerde
}

type
CheckInLicenseOutput struct {
// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
```

```
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
```

```
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
```

InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership

of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or

documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.109 libmd 1.1.0-r0

1.109.1 Available under license :

Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/

Files:
*
Copyright:
Copyright 2009, 2011, 2016 Guillem Jover <guillem@hadrons.org>
License: BSD-3-clause
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
   derived from this software without specific prior written permission.
.
THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR A PARTICULAR
 PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL
THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS;
OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Files:
include/sha2.h
src/sha2.c
Copyright:
Copyright 2000-2001, Aaron D. Gifford
All rights reserved.
License: BSD-3-clause-Aaron-D-Gifford
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions

are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce
 the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holder nor the names of contributors
   may be used to endorse or promote products derived from this software
   without specific prior written permission.
.
THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTOR(S) ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTOR(S) BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE
 OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

Files:
include/rmd160.h
src/rmd160.c
Copyright:
Copyright 2001 Markus Friedl. All rights reserved.
License: BSD-2-clause
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
.
THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE
 FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Files:
src/md2.c
Copyright:
Copyright (c) 2001 The NetBSD Foundation, Inc.
All rights reserved.
.
This code is derived from software contributed to The NetBSD Foundation
by Andrew Brown.
License: BSD-2-clause-NetBSD
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must
 reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
.
THIS SOFTWARE IS PROVIDED BY THE NETBSD FOUNDATION, INC. AND CONTRIBUTORS
``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE FOUNDATION OR CONTRIBUTORS
BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

Files:
man/rmd160.3
man/sha1.3
man/sha2.3
Copyright:
 Copyright 1997, 2003, 2004 Todd C. Miller <Todd.Miller@courtesan.com>
License: ISC
Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.
.
THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR

ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Files:
man/mdX.3
src/helper.c
Copyright:
Poul-Henning Kamp <phk@login.dkuug.dk>
License: Beerware
"THE BEER-WARE LICENSE" (Revision 42):
<phk@login.dkuug.dk> wrote this file. As long as you retain
this notice you
can do whatever you want with this stuff. If we meet some day, and you think
this stuff is worth it, you can buy me a beer in return. Poul-Henning Kamp

Files:
include/md4.h
src/md4.c
Copyright:
Colin Plumb
Todd C. Miller
License: public-domain-md4
This code implements the MD4 message-digest algorithm.
The algorithm is due to Ron Rivest. This code was
written by Colin Plumb in 1993, no copyright is claimed.
This code is in the public domain; do with it what you wish.
Todd C. Miller modified the MD5 code to do MD4 based on RFC 1186.

Files:
include/md5.h
src/md5.c
Copyright:
Colin Plumb
License: public-domain-md5
This code implements the MD5 message-digest algorithm.
The algorithm is due to Ron Rivest. This code was
written by Colin Plumb in 1993, no copyright is claimed.
This code is in the public domain; do with it what you wish.

Files:
include/sha1.h
src/sha1.c
Copyright:
Steve Reid <steve@edmweb.com>
License: public-domain-sha1
100% Public

Domain

1.110 github.com/aws/aws-sdk-go-v2/service/dynamodb 1.46.0

1.110.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step

```
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
```

```
Beneficiary *string

// Unique, case-sensitive identifier that you provide to ensure the idempotency of
// the request.
//
//
This member is required.
ClientToken *string

// Configuration for consumption of the license. Choose a provisional
// configuration for workloads running with continuous connectivity. Choose a
// borrow configuration for workloads with offline usage.
//
// This member is required.
ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
```

```
 // This member is required.
 Validity *types.DatetimeRange

 // Information about
 the license.
 LicenseMetadata []types.Metadata

 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
```

```
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
```

```
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
```

```
      uses: actions/checkout@v2
      with:
        path: sdkbase
        ref: ${{ github.base_ref }}
    - name: Checkout this ref
      uses: actions/checkout@v2
      with:
        path: new-ref
        fetch-depth: 0
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
```

spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter

SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

```
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter
```

```
 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
```

```
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
```

```
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
```

```
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
```

```
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
```

```
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
```

```
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
```

```
 OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
```

```
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
```

```
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
```

```
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
```

```
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options);
err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }
```

```
 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
```

```
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
```

```
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
```

```
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string
```

```
 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
```

```
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
AWS SDK for Go
Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.
{
   "smithy": "2.0",
   "shapes": {
      "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
```

```
        "type": "integer"
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
        "type": "long"
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },

      {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider
resource to deregister.</p>",
               "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
      },
      "output": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
         },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/GetRegisteredSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

         "traits": {
              "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
             }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
```

```
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/GetServiceSettings"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
```

```
            },
            "LinuxSubscriptionsDiscoverySettings": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
               "traits": {
                  "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
               }
            },
            "Status": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
               }
            },
            "StatusMessage": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
               "traits": {
                  "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
               }
            },
            "HomeRegions": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                  "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
         "type": "structure",
         "members": {
            "AmiId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
               }
            },
            "InstanceID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
               }
            },
            "InstanceType": {
```

```
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
        },
        "AccountID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
        "Region": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
        },
        "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
        },
        "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
        },
        "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
```

```
            },
            "SubscriptionName": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
               }
            },
            "OsVersion": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
               }
            },
            "SubscriptionProviderCreateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
               }
            },
            "SubscriptionProviderUpdateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
               }
            },
            "DualSubscription": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
               }
            },
            "RegisteredWithSubscriptionProvider": {
               "target": "smithy.api#String",
               "traits": {

     "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
         }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>An exception occurred with the service.</p>",
        "smithy.api#error": "server"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
      "type": "service",
      "version": "2018-05-10",
      "operations": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
            }
        ],
        "traits": {
            "aws.api#service": {
                "sdkId": "License Manager Linux Subscriptions",
                 "arnNamespace": "license-manager-linux-subscriptions",
                "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
                "name": "license-manager-linux-subscriptions"
            },
            "aws.protocols#restJson1": {},
            "smithy.api#cors": {
                "additionalAllowedHeaders": [
                    "*",
                    "content-type",
                    "x-amz-content-sha256",
                    "x-amz-user-agent",
                    "x-amzn-platform-id",
                    "x-amzn-trace-id"
                ],
                "additionalExposedHeaders": [
                    "x-amzn-errortype",
                    "x-amzn-requestid",
                    "x-amzn-trace-id"
                ]
            },
            "smithy.api#documentation": "<p>With License Manager,
you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager Linux Subscriptions",
            "smithy.rules#endpointRuleSet": {
                "version": "1.0",
                "parameters": {
                    "Region": {
                        "builtIn": "AWS::Region",
                        "required": false,
                        "documentation": "The AWS region used to dispatch the request.",
                        "type": "String"
                    },
                    "UseDualStack": {
```

```
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                 "type": "Boolean"
              },
              "UseFIPS": {
                "builtIn": "AWS::UseFIPS",
                "required": true,
                "default": false,
                "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                "type": "Boolean"
              },
              "Endpoint": {
                "builtIn": "SDK::Endpoint",
                "required": false,
                "documentation": "Override the endpoint used to send this request",
                "type": "String"
              }
            },
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "isSet",
                    "argv": [
                      {
                        "ref": "Endpoint"
                      }
                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },
                          true
                        ]
                      }
```

```
        ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseDualStack"
                                    },
                                    true
                                ]

}
                            ],
                            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                            "type": "error"
                        },
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": {
                                    "ref": "Endpoint"
                                },
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"

                }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "isSet",
```

```
                "argv": [
                  {
                    "ref": "Region"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

        "fn": "aws.partition",
                    "argv": [
                      {
                        "ref": "Region"
                      }
                    ],
                    "assign": "PartitionResult"
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {

                       "ref": "UseFIPS"
                          },
                          true
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
                      }

    ],
                    "rules": [
                      {
                        "conditions": [
```

```
                                        {
                                          "fn": "booleanEquals",
                                          "argv": [
                                            true,
                                            {
                                              "fn": "getAttr",
                                              "argv": [
                                                {
                                                  "ref": "PartitionResult"

                    },
                                                "supportsFIPS"
                                              ]
                                            }
                                          ]
                                        },
                                        {
                                          "fn": "booleanEquals",
                                          "argv": [
                                            true,
                                            {
                                              "fn": "getAttr",
                                              "argv": [

                                               {
                                                  "ref": "PartitionResult"
                                                },
                                                "supportsDualStack"
                                              ]
                                            }
                                          ]
                                        }
                                      ],
                                      "rules": [
                                        {
                                          "conditions": [],

        "rules": [
                                            {
                                              "conditions": [],
                                              "endpoint": {
                                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                              },
                                              "type": "endpoint"
                                            }
```

```
                                    ],

                "type": "tree"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                            "type": "error"
                        }
                    ],
                    "type": "tree"
                },
                {

        "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {

            "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "fn": "getAttr",
                                            "argv": [
                                                {
                                                    "ref": "PartitionResult"
                                                },
                                                "supportsFIPS"
                                            ]
                                        },
                                        true
```

```
                                    ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [],
                                    "rules": [
                                        {
                                            "conditions": [],
                                            "endpoint": {
                                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],
                                    "type": "tree"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "error": "FIPS is enabled
but this partition does not support FIPS",
                            "type": "error"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseDualStack"
                                },
                                true

                ]
                        }
                    ],
                    "rules": [
                        {
```

```
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {

                          "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }
                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "rules": [

        {
                          "conditions": [],
                          "endpoint": {
                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                            "properties": {},
                            "headers": {}
                          },
                          "type": "endpoint"
                        }
                      ],
                      "type": "tree"

                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "DualStack is enabled but this partition does not support DualStack",
                "type": "error"
              }
            ],
            "type": "tree"
          },
```

```
                                {
                                    "conditions": [],
                                    "rules": [
                                        {
                                            "conditions": [],
                                            "endpoint": {
                                                "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],
                                    "type": "tree"
                                }
                            ],
                            "type": "tree"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "Invalid Configuration: Missing Region",
                    "type": "error"
                }
            ],
            "type": "tree"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

        }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
```

```
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {

      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
```

```
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {

"documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
        }
       },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
```

```
"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
                  }
                },
                "params": {
                  "Region": "us-gov-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
                  }

               },
                "params": {
                  "Region": "us-gov-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
                  }
                },
                "params": {
                  "Region": "us-gov-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
              {

            "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
                  }
                },
```

```
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {

    "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
```

```
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
             }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }
          },
          "params": {
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {

          "documentation": "For custom endpoint with fips enabled and dualstack disabled",
          "expect": {
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
```

```
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                    "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
      }
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "Enabled",
          "value": "Enabled",
          "documentation": "Enabled LinuxSubscriptionsDiscovery"

   },
        {
          "name": "Disabled",
          "value": "Disabled",
          "documentation": "Disabled LinuxSubscriptionsDiscovery"
        }
      ]
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
    "type": "structure",
```

```
        "members": {
          "SourceRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "OrganizationIntegration": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
            "traits": {
              "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },


  {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/subscription/ListLinuxSubscriptionInstances"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "Instances"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n          <li>\n
  <p>\n              <code>AccountID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
    <code>AmiID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>DualSubscription</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceType</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>ProductCode</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Region</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Status</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>UsageOperation</code>\n            </p>\n          </li>\n        </ul>\n        <p>For each filter, you can use
one of the following <code>Operator</code>
 values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
          "type": "structure",
          "members": {
            "Instances": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
              }
            },
            "NextToken": {

           "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

   "items": "Subscriptions"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n      <p>The valid names for this filter are:</p>\n      <ul>\n <li>\n          <p>\n              <code>Subscription</code>\n          </p>\n      </li>\n      </ul>\n <p>The
 valid Operators for this filter are:</p>\n      <ul>\n      <li>\n          <p>\n <code>contains</code>\n          </p>\n      </li>\n      <li>\n          <p>\n <code>equals</code>\n          </p>\n      </li>\n      <li>\n          <p>\n <code>Notequal</code>\n          </p>\n      </li>\n      </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
```

```
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 16384
                  }
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "Subscriptions": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
               "traits": {
                  "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
         "type": "operation",
         "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
         },
         "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
         },
         "errors": [
            {
```

```
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "RegisteredSubscriptionProviders"
            }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSources": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
                "traits": {
                    "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
```

```
  },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
          "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
            }
          },

           "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {
```

```
"target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
              "name": "CONTAINS",
              "value": "Contains",
              "documentation": "Contains operator"
            }
          ],
          "smithy.api#length": {
            "min": 1,
            "max": 20
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled OrganizationIntegration"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
```

```
      "member": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/RegisterSubscriptionProvider"

         },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
            "smithy.api#required": {}
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
              "traits": {
                "smithy.api#documentation": "<p>The Linux subscription provider that you registered.</p>"
              }
            },
            "SubscriptionProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
              }
            },
            "SubscriptionProviderStatus": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
              "traits": {
                "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
```

```
{
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed
third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
          }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and
license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider,
License Manager can get subscription data from the registered provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

  }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
```

```
            {
              "name": "Successful",
              "value": "Successful",
              "documentation": "Successful status"
            },
            {
              "name": "Failed",
              "value": "Failed",
              "documentation": "Failed status"
            }
          ]
        }
      },

      "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            }
          }
        },
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
          },
          "smithy.api#uniqueItems": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
          "Name":
{
            "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The name of the subscription.</p>"
            }
          },
          "Type": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS.</p>"
            }
          },
          "InstanceCount": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
            "traits": {
              "smithy.api#documentation": "<p>The total amount of running instances using this subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [

 {
              "name": "RedHat",
              "value": "RedHat",
              "documentation": "RedHat subscription provider namespace"
            }
```

```
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "ACTIVE",
            "value": "ACTIVE",
            "documentation": "ACTIVE status"
          },
          {
            "name": "INVALID",
            "value": "INVALID",

"documentation": "INVALID status"
          },
          {
            "name": "PENDING",
            "value": "PENDING",
            "documentation": "PENDING status"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
              "method": "PUT",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
          "type": "structure",
          "members":
{
            "resourceArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}
              }
            },
            "tags": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                "smithy.api#required": {}
              }
            }
          },
```

```
      "traits": {
        "smithy.api#input": {}
      }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
```

```
    "members": {},
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

 },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
        },
        "smithy.api#idempotent": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
    "type": "structure",
    "members": {
         "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
                "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                "smithy.api#required": {}
            }
        },
        "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>",
                "smithy.api#required": {}
              }
            },
            "AllowUpdate": {
              "target": "smithy.api#Boolean",
              "traits": {
                "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
              "traits": {
                "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
              }
            },
            "StatusMessage": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
              "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
              }
```

```
        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
          "smithy.api#error": "client"
        }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
```

```
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata
```

```
// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
```

```
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
```

```
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
```

```
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options)) (*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
```

```
struct {

// A structure containing data about the workspace.
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
```

```
//
// This member is required.
LicenseArn *string

// Current version of the license.
//
// This member is required.
SourceVersion
*string

noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

// Date when the license is deleted.
DeletionDate *string

// License status.
Status types.LicenseDeletionStatus

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
```

```
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
```

UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP \n\t\t\taddresses, and the credential provider for user administration.</p>"
          }
        },
        "ActiveDirectoryType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
          "traits": {
```

```
                "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
          "type": "structure",
          "members": {
            "DomainName": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
              }
            },
            "DomainIpv4List": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active Directory.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 2
                }
              }
            },
            "DomainCredentialsProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
              "traits": {
                "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration.</p>"
              }
            },
            "DomainNetworkSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
```

```
\n\t\t\tuser administration in the Active Directory.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "SELF_MANAGED",
              "value": "SELF_MANAGED",
              "documentation": "SELF_MANAGED type of Active Directory"
            },
            {
              "name": "AWS_MANAGED",
              "value": "AWS_MANAGED",
              "documentation": "AWS_MANAGED type of Active Directory"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
{
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

        {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
                }
            },
```

```
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
```

```
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
         "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
```

```
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                    "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
     },
     "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
     },
     "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
```

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

        }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
            "type": "structure",
            "members": {
                "Username": {
                    "target": "smithy.api#String",
                    "traits": {
                        "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                    }
                },
                "InstanceId": {
                    "target": "smithy.api#String",
                    "traits": {
                        "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                    }
                },
                "IdentityProvider": {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                    "traits": {
                        "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                    }
                },
                "InstanceUserArn": {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                    "traits": {
                        "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                    }
                },
                "Domain": {
                    "target": "smithy.api#String",
                    "traits": {
                        "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
                    }
                }
            },
```

```
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
              "smithy.api#length": {
                "min": 1
              },

    "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Attribute": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
```

```
            },
            "Operation": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
               }
            },
            "Value": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>Value of the filter.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
         "type": "union",
         "members": {
            "ActiveDirectoryIdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
         "type": "structure",
         "members": {
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
```

```
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
                "smithy.api#required": {}
            }
        },
        "Product": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
        },
        "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an identity provider.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
    "type": "list",
```

```
      "member": {

        "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
      "type": "structure",
      "members": {
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
            "smithy.api#required": {}
          }
        },
        "Products": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
           "traits": {
            "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
            "smithy.api#required": {}
          }
        },
        "LastStatusCheckDate": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The date of the last status check.</p>"
          }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
```

```
{
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },

      "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
             }
          },
          "StatusMessage": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
          },
          "DisassociationDate": {
            "target": "smithy.api#String",
             "traits": {
              "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
           "smithy.api#error": "server",
          "smithy.api#httpError": 500
        }
```

```
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
          },
          {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
          }
        ],
        "traits": {
          "aws.api#service": {
            "sdkId": "License Manager User Subscriptions",
            "arnNamespace": "license-manager-user-subscriptions",
            "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
          },
          "aws.auth#sigv4": {
            "name": "license-manager-user-subscriptions"
          },
          "aws.protocols#restJson1": {},
          "smithy.api#cors": {
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id",
              "content-length",

           "x-api-key",
              "authorization",
              "x-amz-date",
              "x-amz-security-token",
              "Access-Control-Allow-Headers",
              "Access-Control-Allow-Methods",
```

```
            "Access-Control-Allow-Origin"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region":
{
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
              "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
```

```
    {
      "fn": "isSet",
      "argv": [
        {
          "ref": "Endpoint"
        }
      ]
    }
  ],
 "rules": [
    {
      "conditions": [
        {
          "fn": "booleanEquals",
          "argv": [
            {
              "ref": "UseFIPS"
            },
            true
          ]
        }
      ],
      "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
      "type": "error"
    },
    {
      "conditions": [
        {

          "fn": "booleanEquals",
          "argv": [
            {
              "ref": "UseDualStack"
            },
            true
          ]
        }
      ],
      "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
      "type": "error"
    },
    {
      "conditions": [],
      "endpoint": {
        "url": {
          "ref": "Endpoint"
        },
```

```
        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Region"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "aws.partition",

                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ],
                            "assign": "PartitionResult"
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseFIPS"
                                        },
```

true

```
                                    ]
                                },
                                {
                                    "fn": "booleanEquals",
```

```
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

"fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      }
                    ]
                  },

                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }

            ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                  "properties": {},
                  "headers": {}
                },
                "type": "endpoint"
              }

    ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
              "type": "error"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
            {
              "fn": "booleanEquals",
              "argv": [

 {
                  "ref": "UseFIPS"
                },
                true
              ]
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "fn": "getAttr",
                      "argv": [

        {
                          "ref": "PartitionResult"
                        },
                        "supportsFIPS"
```

```
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS is enabled but this partition does not support FIPS",
                    "type": "error"

}
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

    "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
```

```
                                    true,
                                    {
                                      "fn": "getAttr",
                                      "argv": [
                                        {
                                          "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                      ]

            }
                                    ]
                                  }
                                ],
                                "rules": [
                                  {
                                    "conditions": [],
                                    "endpoint": {
                                      "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                      "properties": {},
                                      "headers": {}
                                    },
                                    "type": "endpoint"
                                  }

                            ],
                                "type": "tree"
                              },
                              {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                              }
                            ],
                            "type": "tree"
                          },
                          {
                            "conditions": [],
                            "endpoint": {
                              "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                    "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                          }
```

```
                    ],
                    "type": "tree"
                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
              }
            ]
          },
          "smithy.rules#endpointTests": {
            "testCases": [
              {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
                "expect":
{
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                  }
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                  }
                },
                "params": {
                  "Region": "us-east-1",

        "UseFIPS": true,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
```

```
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
```

```
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
         "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
```

```
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false

}
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
        }

  },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
```

```
                {
                  "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                    }
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "error": "DualStack is enabled but this partition does not support DualStack"
                  },
                  "params": {
                    "Region": "us-isob-east-1",

 "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                    }
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
                  "expect": {

                   "endpoint": {
                      "url": "https://example.com"
                    }
                  },
                  "params": {
```

```
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }
          },
          "params": {
            "UseFIPS": false,
            "UseDualStack":
false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with fips enabled and dualstack disabled",
          "expect": {
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with fips disabled and dualstack enabled",
          "expect": {
            "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "Missing region",
```

```
                    "expect": {
                        "error": "Invalid Configuration: Missing Region"
                    }
                }
            ],
            "version": "1.0"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
    "type": "structure",
    "members": {
        "ProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
             "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
            }
        },
        "HealthStatus": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
            "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
            }
        },
        "Ipv4Address": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
    "type": "structure",
    "members": {
        "IdentityProviderArn": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
            }
```

```
        },
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>"
          }
        },
        "ServerEndpoint": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
            "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network \n\t\t\taddress of the RDS license server endpoint.</p>"
          }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
          }
        },
        "LicenseServerEndpointId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
          }
        },
        "LicenseServerEndpointArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits":
 {
            "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
          }
        },
        "LicenseServerEndpointProvisioningStatus": {
          "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
          "traits": {
            "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
          }
        },
        "LicenseServers": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent
```

```
the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
                }
            },

            "CreationTime": {
                "target": "smithy.api#Timestamp",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "PROVISIONING",
                    "value": "PROVISIONING",
                    "documentation": ""
                },
                {
                    "name": "PROVISIONING_FAILED",
                    "value": "PROVISIONING_FAILED",
                    "documentation": ""
                },
                {
                    "name": "PROVISIONED",
                    "value": "PROVISIONED",
                    "documentation": ""
                },
                {
                    "name": "DELETING",
```

```
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
    "type": "string",
    "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
    }
},
 "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
    "type": "structure",
    "members": {
```

```
            "ServerType": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
               "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>",
                  "smithy.api#required": {}
               }
            },
            "ServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n            <li>\n                <p>Product</p>\n            </li>\n
        <li>\n                <p>DirectoryId</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                "smithy.api#required": {}
            }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },

      {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/instance/ListInstances"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "InstanceSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
         "type": "structure",
         "members":
 {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
```

```
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>Status</p>\n            </li>\n
          <li>\n                <p>InstanceId</p>\n            </li>\n        </ul>"
                }
              }
            },
            "traits": {
              "smithy.api#input": {}
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
            "type": "structure",
            "members": {
              "InstanceSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
                "traits": {
                  "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
                }
              },
              "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#output": {}
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
            "type": "operation",
            "input": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
            },
            "output": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
            },
            "errors": [
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
              },
              {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/license-server/ListLicenseServerEndpoints"
            },

          "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",
              "items": "LicenseServerEndpoints"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
          "type": "structure",
          "members": {
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                "smithy.api#range": {
                  "min": 1,
                  "max": 100
                }
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
```

```
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n              <p>IdentityProviderArn</p>\n          </li>\n      </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListProductSubscriptions"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "ProductUserSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
```

Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n "
}
},
"IdentityProvider": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
"traits": {
"smithy.api#documentation": " An object that specifies details for the identity provider. ",
"smithy.api#required": {}
}
},
"MaxResults": {
"target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
"traits": {
"smithy.api#documentation": " The maximum number of results to return from a single
request. "
}
},
"Filters": {
"target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
"traits": {
"smithy.api#documentation": " You can use the following filters to streamline results: \n
\n \n Status \n \n \n Username \n
\n \n Domain \n \n "
}
},
"NextToken": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " A token to specify where to start paginating.
This is the nextToken \n\tfrom a previously truncated response. "
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
"type": "structure",
"members": {
"ProductUserSummaries": {
"target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
"traits": {
"smithy.api#documentation": " Metadata that describes the list product subscriptions
operation. "
}

```
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target":
"com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
               "method": "GET",
               "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
         "type": "structure",
         "members": {
            "ResourceArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags you want to retrieve.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

          }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
```

```
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
```

```
        "members": {
            "Username":
 {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a product for this user.</p>",
                    "smithy.api#required": {}
                }
            },
            "ProductUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
```

```
            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
                }
            },
            "SubscriptionStartDate": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The start date of a subscription.</p>"
                }
            },
            "SubscriptionEndDate": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The end date of a subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
            "RdsSalCredentialsProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
```

```
{
        "type": "operation",
        "input": {
           "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
           "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
           },
           {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
           }
        ],
        "traits": {
           "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
           "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/identity-provider/RegisterIdentityProvider"
           },
           "smithy.api#idempotent": {}
        }
     },
     "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
           "IdentityProvider": {
```

```
    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
 {
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
```

```
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

   "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
            "smithy.api#length": {
```

```
          "min": 5,
              "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
          "type": "structure",
          "members": {
            "Endpoint": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
          "type": "union",
          "members": {
            "RdsSalSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "RDS_SAL",
                "value": "RDS_SAL",
                "documentation": ""
              }
            ]
          }
        },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {

  "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
            "smithy.api#length": {
              "min": 1
            },
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

          "traits": {
            "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
```

```
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

        },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/StartProductSubscription"
          }

    }
     },
     "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n          <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

  }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
```

```
                "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity provider.</p>",
            "smithy.api#http": {
              "code": 200,
```

```
            "method": "POST",
            "uri": "/user/StopProductSubscription"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
            }
          },
          "IdentityProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
      "type": "structure",
      "members": {
        "ProductUserSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
          "traits": {
            "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
            "smithy.api#required": {}
          }

  }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
    "com.amazonaws.licensemanagerusersubscriptions#StringList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

 "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
```

```
"<p>The tags to apply to the specified resource.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
```

```
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

        }
            },
            "TagKeys": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
                "traits": {
                    "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                    "smithy.api#httpQuery": "tagKeys",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

       "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
```

```
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },

            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
               }
            },
            "UpdateSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
               "traits": {
                  "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n            <li>\n               <p>Subnets which you want to add to provision VPC endpoints.</p>\n            </li>\n
      <li>\n               <p>Subnets which you want to remove the VPC endpoints from.</p>\n            </li>\n
<li>\n               <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n            </li>\n         </ul>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
         "type": "structure",
         "members": {
            "IdentityProviderSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
               "traits": {
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A parameter is not valid.</p>",
        "smithy.api#error": "client"
      }
    }
  }
}
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata
```

```
 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
```

```
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
 nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
```

```
 ServiceID:
    ServiceID,
 OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
 spanInitializeStart
 InterceptExecution
 RegisterServiceMetadata
 legacyEndpointContextSetter
 SetLogger
 OperationInputValidation
 spanInitializeEnd
 Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
 Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
 Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
 Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
```

ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work

(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work

or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent

AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID

ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.111 go-yaml 3.0.1

1.111.1 Available under license :

Copyright 2011-2016 Canonical Ltd.

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software

distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

This project is covered by two different licenses: MIT and Apache.

MIT License

The following files were ported to Go from C files of libyaml, and thus
are still covered by their original MIT license, with the additional
copyright staring in 2011 when the project was ported over:

  apic.go emitterc.go parserc.go readerc.go scannerc.go
  writerc.go yamlh.go yamlprivateh.go

Copyright (c) 2006-2010 Kirill Simonov
Copyright (c) 2006-2011 Kirill Simonov

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial
 portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

Apache License

All the remaining project files are covered by the Apache license:

Copyright (c) 2011-2019 Canonical Ltd

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR
CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.112 aws-sdk-go-v2-feature-s3-manager 1.18.3

1.112.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2

```
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
```

```
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer

 // License name.
 //
 // This member is required.
 LicenseName *string

 // Product name.
 //
 // This member is required.
 ProductName *string
```

```
 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // Date and time range during which the license is valid, in ISO8601-UTC format.
 //
 // This member is required.
 Validity *types.DatetimeRange

 // Information about
 the license.
 LicenseMetadata []types.Metadata

 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
```

```
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
```

```
  runs-on: ubuntu-latest
  strategy:
    matrix:
      python-version: [3.9]

  steps:
    - name: Checkout target
      uses: actions/checkout@v2
      with:
        path: sdkbase
        ref: ${{ github.base_ref }}
    - name: Checkout this ref
      uses: actions/checkout@v2
      with:
        path: new-ref
        fetch-depth: 0
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
```

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper

```
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
```

```
  - Fingerprint
//
//   - IssuerName
//
//   - Beneficiary
Filters []types.Filter

// Amazon Resource Names (ARNs) of the licenses.
LicenseArns []string

// Maximum number of results to return in a single call.
MaxResults *int32

// Token for the next set of results.
NextToken *string

noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

// Received license details.
Licenses []types.GrantedLicense

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
```

```
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
```

```
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
```

```
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
```

```
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {
```

```
// License details.
Licenses []types.License

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
```

```
 return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
 err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if
err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
```

```
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

```
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
```

```
//
// This member is required.
LicenseType types.LicenseType

//
The ID of the workspace to remove the Grafana Enterprise license from.
//
// This member is required.
WorkspaceId *string

noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

// A structure containing information about the workspace.
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
```

```
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
```

```
}
if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
```

```
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string
```

```
 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go
Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": " Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account. ",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/DeregisterSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
      "type": "structure",

```
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
      "type":
 "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
      },
      "output": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
         },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/GetRegisteredSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation":
```

```
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

          "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
                 }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
```

```
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
         "type": "operation",
         "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/GetServiceSettings"

          },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
         "type": "structure",
         "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
```

```
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
```

```
            "InstanceID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
               }
            },
            "InstanceType": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>The instance type of the resource.</p>"
               }
            },
            "AccountID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
               }
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of the instance.</p>"
               }
            },
            "Region": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
               }
            },
            "UsageOperation": {
               "target": "smithy.api#String",

   "traits": {
                  "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
               }
            },
            "ProductCode": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
               "traits": {
                  "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
               }
```

```
        },
        "LastUpdatedTime": {
          "target": "smithy.api#String",
           "traits": {
             "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
          }
        },
        "SubscriptionName": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
          }
        },
        "OsVersion": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
          }
        },
        "SubscriptionProviderCreateTime": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
          }
        },
        "SubscriptionProviderUpdateTime": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the registered \n\t\t\tthird-party Linux subscription provider.</p>"
          }
        },
        "DualSubscription": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for \n\t\t\tthe same software on your instance.</p>"
          }
        },
        "RegisteredWithSubscriptionProvider": {
          "target": "smithy.api#String",
          "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta third-party Linux subscription provider that you've registered with License Manager.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager Linux Subscriptions",
           "arnNamespace": "license-manager-linux-subscriptions",
          "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
```

```
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
```

```
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }

        ],
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                  "type": "error"
                },
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            {
                              "ref": "UseDualStack"
                            },
                            true
                          ]

}
                      ],
                      "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                      "type": "error"
                    },
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": {
                          "ref": "Endpoint"
                        },
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }
                  ],
                  "type": "tree"

              }
              ],
             "type": "tree"
            },
            {
```

```
"conditions": [],
"rules": [
  {
    "conditions": [
      {
        "fn": "isSet",
        "argv": [
          {
            "ref": "Region"
          }
        ]
      }
    ],
    "rules": [
      {
        "conditions": [
          {

"fn": "aws.partition",
            "argv": [
              {
                "ref": "Region"
              }
            ],
            "assign": "PartitionResult"
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {

                "ref": "UseFIPS"
                  },
                  true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
```

```
                }

    ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

                    },
                                        "supportsFIPS"
                                    ]
                                }
                            ]
                        },
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                true,
                                {
                                    "fn": "getAttr",
                                    "argv": [

                                     {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],

        "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-subscriptions-
```

```
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],

                                "type": "tree"
                                        }
                                    ],
                                    "type": "tree"
                                },
                                {
                                    "conditions": [],
                                    "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {

                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "ref": "UseFIPS"
                                            },
                                            true
                                        ]
                                    }
                                ],
                                "rules": [
                                    {
                                        "conditions": [
                                            {

                            "fn": "booleanEquals",
                                                "argv": [
                                                    {
                                                        "fn": "getAttr",
                                                        "argv": [
                                                            {
                                                                "ref": "PartitionResult"
                                                            },
```

```
                                        "supportsFIPS"
                                    ]
                                },
                                true

                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS is enabled
but this partition does not support FIPS",
                    "type": "error"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
```

```
                ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {

                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "rules": [

        {
                                        "conditions": [],
                                        "endpoint": {
                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"

                    }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
```

```
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ],
    "type": "tree"
}
]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
            },
            "params": {
```

```
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {

      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
```

```
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                    }
                },
                "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {

 "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                    }
                },
                "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                    }
                 },
                "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
                    }
                },
                "params": {
                    "Region": "cn-north-1",
```

```
            "UseFIPS": false,
            "UseDualStack": false
        }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }

     },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
        }
    },
    {
```

```
"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
                      }
                    },
                    "params": {
                      "Region": "us-gov-east-1",
                      "UseFIPS": false,
                      "UseDualStack": false
                    }
                  },
                  {
                    "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                    "expect": {
                      "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                    },
                    "params": {

                 "Region": "us-iso-east-1",
                      "UseFIPS": true,
                      "UseDualStack": true
                    }
                  },
                  {
                    "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                      }
                    },
                    "params": {
                      "Region": "us-iso-east-1",
                      "UseFIPS": true,
                      "UseDualStack": false
                    }
                  },
                  {
                    "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
                    "expect": {
                      "error": "DualStack is enabled but this partition does not support DualStack"
                    },
                    "params": {
                      "Region": "us-iso-east-1",
                      "UseFIPS": false,
                      "UseDualStack": true
                    }
```

```
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": true
```

```
      }
    },
    {

      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
```

```
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled LinuxSubscriptionsDiscovery"

      },
            {
              "name": "Disabled",
              "value": "Disabled",
```

```
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

    {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
```

```
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n    \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n              <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceType</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>ProductCode</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Region</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Status</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>UsageOperation</code>\n              </p>\n            </li>\n          </ul>\n          <p>For each filter, you can use one of the following <code>Operator</code>\n           values to \n    \t\tdefine the behavior of the filter:</p>\n          <ul>\n            <li>\n              <p>\n                <code>contains</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>equals</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Notequal</code>\n              </p>\n            </li>\n          </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
 parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
          "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
              "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
            }
          },
          "NextToken": {

         "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
 isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
 next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptions"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",

   "items": "Subscriptions"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n      <p>The valid names for this filter are:</p>\n      <ul>\n <li>\n          <p>\n            <code>Subscription</code>\n          </p>\n        </li>\n      </ul>\n <p>The
 valid Operators for this filter are:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
```

```
        },
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
            "smithy.api#length": {
              "min": 1,
              "max": 16384
            }
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
      "type": "structure",
      "members": {
        "Subscriptions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
      "type": "operation",
      "input": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
```

```
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "RegisteredSubscriptionProviders"
            }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSources": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
                "traits": {
                    "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                "smithy.api#range": {
                  "min": 1,
                  "max": 100
                }
              }

  },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
          "traits": {
            "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
          }
        },

        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
              "name": "CONTAINS",
              "value": "Contains",
              "documentation": "Contains operator"
            }
          ],
          "smithy.api#length": {
            "min": 1,
            "max": 20
          }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
```

```
                "documentation": "Disabled OrganizationIntegration"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
                "smithy.api#required": {}
              }
            },
            "SecretArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
              "traits": {
                "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
              }
            },
            "SubscriptionProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
              }
            },
            "SubscriptionProviderStatus": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
              "traits": {
                "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
              }
```

```
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
                "traits": {
                    "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
                }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
                }
            },
```

```
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"

   }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "InProgress",
                  "value": "InProgress",
```

```
            "documentation": "InProgress status"
          },
          {
            "name": "Completed",
            "value": "Completed",
            "documentation": "Completed status"
          },
          {
            "name": "Successful",
            "value": "Successful",
            "documentation": "Successful status"
          },
          {
            "name": "Failed",
            "value": "Failed",
            "documentation": "Failed status"
          }
        ]
      }
    },

    "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
          }
        }
      },
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        },
        "smithy.api#uniqueItems": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
      "type": "structure",
      "members": {
        "Name":
{
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the subscription.</p>"
          }
        },
        "Type": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS.</p>"
          }
        },
        "InstanceCount": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>The total amount of running instances using this subscription.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
      "type": "string",
      "traits": {
```

```
            "smithy.api#enum": [

{
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
                },
                {
                    "name": "INVALID",
                    "value": "INVALID",

 "documentation": "INVALID status"
                },
                {
                    "name": "PENDING",
                    "value": "PENDING",
                    "documentation": "PENDING status"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
```

```
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
        "type": "structure",
        "members":
{
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
         "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        },
        "tagKeys": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
          "traits": {

         "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
            "smithy.api#httpQuery": "tagKeys",
            "smithy.api#required": {}
          }
        }
```

```
    },
    "traits": {
        "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
    "type": "structure",
    "members": {},
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

 },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
        },
        "smithy.api#idempotent": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
    "type": "structure",
    "members": {
        "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
```

```
                "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                "smithy.api#required": {}
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                "smithy.api#required": {}
              }
            },
            "AllowUpdate": {
              "target":
 "smithy.api#Boolean",
              "traits": {
                "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
               "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
              "traits": {
                "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
              }
            },
```

```
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
```

```
 params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string
```

```
 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
```

```
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
```

```
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html#AMG-workspace-register-enterprise
```

```
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
```

```
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
```

```
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
```

```
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
```

```
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }
```

```
if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
```

```
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
```

OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer

in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
```

\n\t\t\taddresses, and the credential provider for user administration. "
            }
          },
          "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
              "smithy.api#documentation": " The type of Active Directory either a self-managed Active Directory or an \n\t\t\tAmazon Web Services Managed Active Directory. "
            }
          }
        },
        "traits": {
          "smithy.api#documentation": " Details about an Active Directory identity provider. "
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
          "DomainName": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " The domain name for the Active Directory. "
            }
          },
          "DomainIpv4List": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
            "traits": {
              "smithy.api#documentation": " A list of domain IPv4 addresses that are used for the Active Directory. ",
              "smithy.api#length": {
                "min": 1,
                "max": 2
              }
            }
          },
          "DomainCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": " Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration. "
            }
          },
          "DomainNetworkSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
            "traits": {
              "smithy.api#documentation": " The <code>DomainNetworkSettings</code> resource contains an

```
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "SELF_MANAGED",
                    "value": "SELF_MANAGED",
                    "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                    "name": "AWS_MANAGED",
                    "value": "AWS_MANAGED",
                    "documentation": "AWS_MANAGED type of Active Directory"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n        <note>\n          <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
          "smithy.api#http":
{
            "code": 200,
            "method": "POST",
            "uri": "/user/AssociateUser"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
```

```
subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
                }
            }
        },
        "traits": {

    "smithy.api#input": {}
        }
     },
     "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
         }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
        "smithy.api#error": "server"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },

       {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
```

```
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                "smithy.api#required": {}
              }
            },
            "LicenseServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
          "type": "union",
          "members": {
            "SecretsManagerCredentialsProvider":
{
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
              "traits": {
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
           },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/DeleteLicenseServerEndpoint"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
              "smithy.api#required": {}
            }
          },
           "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
            "traits": {
              "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#output": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
         },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
```

```
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
```

```
information for the user to disassociate.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
        "type": "structure",
        "members": {
            "Subnets": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
                "traits": {
                    "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                    "smithy.api#length": {
                        "min": 1
                    },

   "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
            }
          },
          "Value": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>Value of the filter.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
          "ActiveDirectoryIdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
             "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
```

```
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
                }
            },
            "FailureMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
              "smithy.api#required": {}
            }
          },
          "Products": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
              "smithy.api#required": {}
            }
          },
          "LastStatusCheckDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
          }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },

    "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
```

```
user.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
                }
            },
            "AssociationDate": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
                }
            },
            "DisassociationDate": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
```

```
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
        "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",
```

```
            "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
                "Region":
{
                    "builtIn": "AWS::Region",
                    "required": false,
                    "documentation": "The AWS region used to dispatch the request.",
                    "type": "String"
                },
                "UseDualStack": {
                    "builtIn": "AWS::UseDualStack",
                    "required": true,
                    "default": false,
                    "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                    "type": "Boolean"
                },
                "UseFIPS": {
                    "builtIn": "AWS::UseFIPS",
                    "required": true,
                    "default": false,
                    "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                    "type": "Boolean"
                },
                "Endpoint": {
                    "builtIn": "SDK::Endpoint",
                    "required": false,
                    "documentation": "Override the endpoint used to send this request",
```

```
      "type": "String"
    }
  },
  "rules": [
    {
      "conditions": [
        {
          "fn": "isSet",
          "argv": [
            {
              "ref": "Endpoint"
            }
          ]
        }
      ],
      "rules": [
        {
          "conditions": [
            {
              "fn": "booleanEquals",
              "argv": [
                {
                  "ref": "UseFIPS"
                },
                true
              ]
            }
          ],
          "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
          "type": "error"
        },
        {
          "conditions": [
            {

              "fn": "booleanEquals",
              "argv": [
                {
                  "ref": "UseDualStack"
                },
                true
              ]
            }
          ],
          "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
          "type": "error"
        },
        {
```

```
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Region"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "aws.partition",

                   "argv": [
                      {
                        "ref": "Region"
                      }
                    ],
                    "assign": "PartitionResult"
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },
```

```
true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

"fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      }
                    ]
                  },

                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }
```

```
                ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [

 {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
```

```
                "argv": [

            {
                        "ref": "PartitionResult"
                    },
                    "supportsFIPS"
                ]
            },
            true
        ]
    }
],
"rules": [
    {
        "conditions": [],
        "endpoint": {

"url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
            "properties": {},
            "headers": {}
        },
        "type": "endpoint"
    }
],
"type": "tree"
},
{
    "conditions": [],
    "error": "FIPS is enabled but this partition does not support FIPS",
    "type": "error"

}
    ],
    "type": "tree"
},
{
    "conditions": [
        {
            "fn": "booleanEquals",
            "argv": [
                {
                    "ref": "UseDualStack"
                },
                true
            ]
        }
    ],
    "rules": [
```

```
                {

        "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        true,
                        {
                          "fn": "getAttr",
                          "argv": [
                            {
                              "ref": "PartitionResult"
                            },
                            "supportsDualStack"
                          ]

        }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

                ],
                    "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
                  "type": "error"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "endpoint": {
                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
```

```
                "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }
            ],
            "type": "tree"
        }
      ],
      "type": "tree"
    },
    {
      "conditions": [],
      "error": "Invalid Configuration: Missing Region",
      "type": "error"
    }
  ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect":
{
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",

    "UseFIPS": true,
        "UseDualStack": false
      }
```

```
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS":
true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
```

```
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false

}
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
```

```
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",

 "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
```

```
      "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
```

```
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
          "members": {
```

```
            "IdentityProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
               }
            },
            "ServerType": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
               "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>"
               }
            },
            "ServerEndpoint": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
               }
            },
            "LicenseServerEndpointId": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
               }
            },
            "LicenseServerEndpointArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits":
{
                  "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the
RDS \n\t\t\tlicense server.</p>"
               }
            },
            "LicenseServerEndpointProvisioningStatus": {
               "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                  "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
```

```
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },

         "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
```

```
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

         },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
       ]
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
    "type": "string",
    "traits": {
       "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
       ]
    }
},
 "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
    "type": "list",
    "member": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
          "type": "structure",
          "members": {
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>",
                "smithy.api#required": {}
              }
            },
            "ServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "IdentityProviderSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
         "type": "structure",
         "members": {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n            <li>\n                <p>Product</p>\n            </li>\n
        <li>\n                <p>DirectoryId</p>\n            </li>\n        </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
```

```
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                "smithy.api#required": {}
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },

      {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/instance/ListInstances"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "InstanceSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
         "type": "structure",
         "members":
 {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
```

```
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/ListLicenseServerEndpoints"
          },

        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "LicenseServerEndpoints"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
```

```
                }
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoints": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
          "type":
```

```
 "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
```

```
{
        "type": "structure",
        "members": {
           "Product": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
              }
           },
           "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                 "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                 "smithy.api#required": {}
              }
           },
           "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                 "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
           },
           "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {
                 "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n           <li>\n              <p>Status</p>\n           </li>\n           <li>\n              <p>Username</p>\n
</li>\n           <li>\n              <p>Domain</p>\n           </li>\n        </ul>"
              }
           },
           "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
              }
           }
        },
        "traits": {
           "smithy.api#input": {}
        }
     },
     "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
```

```
        "members": {
          "ProductUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

          }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
             }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "InstanceUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
         "type": "structure",
         "members": {
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance, which
provides user-based subscriptions.</p>",
                  "smithy.api#required": {}
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
```

```
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
```

```
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
```

```
        "type": "structure",
        "members": {
          "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
 {
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
```

```
"<p>Metadata that describes the results of an identity provider operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
      "type": "string",
      "traits": {
        "smithy.api#length": {

         "min": 5,
          "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
      "type": "structure",
      "members": {
        "Endpoint": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
            "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
```

```
                "documentation": ""
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
          "type": "structure",
          "members": {
            "message": {

  "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Settings": {
          "type": "structure",
          "members": {
            "Subnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
                "smithy.api#length": {
                  "min": 1
                },
                "smithy.api#required": {}
              }
            },
            "SecurityGroupId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

             "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

      },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/StartProductSubscription"
        }

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
```

```
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {

 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
```

```
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
```

```
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StopProductSubscription"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
               }
            },
            "IdentityProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
               }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }

  }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
```

```
 "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "Tags": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
"<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
          "smithy.api#error": "client"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {

       "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
        "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}

      }
        },
        "TagKeys": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
          "traits": {
            "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
            "smithy.api#httpQuery": "tagKeys",
            "smithy.api#required": {}
          }
        }
```

```
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
            "smithy.api#http": {

     "code": 200,
                "method": "POST",
                "uri": "/identity-provider/UpdateIdentityProviderSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
```

```
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },

            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
                }
            },
            "UpdateSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
                "traits": {
                    "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n            <li>\n                <p>Subnets which you want to add to provision VPC endpoints.</p>\n            </li>\n
        <li>\n                <p>Subnets which you want to remove the VPC endpoints from.</p>\n            </li>\n
<li>\n                <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n            </li>\n        </ul>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
                "traits": {
                    "smithy.api#required": {}
                }
            }
        },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A parameter is not valid.</p>",
        "smithy.api#error": "client"
      }
```

```
      }
   }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
```

```
CheckInLicenseOutput struct {
// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
```

```
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}
```

```
func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
```

Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their

Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf

of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step

ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization

OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.113 validator 10.27.0

1.113.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Dean Karn

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.114 github.com/wojtekwanczyk/average 0.0.0-20240221125520-eb722bafaeb3

1.114.1 Available under license :

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,

DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.115 prometheus-common 0.65.0

1.115.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct

or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.116 go-ntlmssp 0.0.0-20221128193559-754e69321358

1.116.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Microsoft

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.117 x-text 0.27.0

1.117.1 Available under license :

Copyright 2009 The Go Authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google LLC nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.118 ssl-client 1.37.0-r13

1.118.1 Available under license :

Automatically generated by apkbuild-cpan, template 4
Contributor: Valery Kartel <valery.kartel@gmail.com>
Maintainer: Celeste <cielesti@protonmail.com>

```
maintainer="Celeste <cielesti@protonmail.com>"
pkgname=perl-bsd-resource
pkgver=1.2911
pkgrel=10
#_pkgreal is used by apkbuild-cpan to find modules at MetaCpan
_pkgreal=BSD-Resource
pkgdesc="Perl extension implements the BSD process resource limit functions"
url="https://metacpan.org/release/BSD-Resource/"
arch="all"
license="Artistic-2.0 OR LGPL-2.0"
depends="perl"
makedepends="perl-dev"
subpackages="$pkgname-doc"
source="https://cpan.metacpan.org/authors/id/J/JH/JHI/BSD-Resource-$pkgver.tar.gz"
builddir="$srcdir/$_pkgreal-$pkgver"

build() {
 export CFLAGS=$(perl -MConfig -E 'say $Config{ccflags}')
 PERL_MM_USE_DEFAULT=1 perl -I. Makefile.PL \
  INSTALLDIRS=vendor \
  NO_PACKLIST=1 \
  NO_PERLLOCAL=1
 make
}

check() {
 export CFLAGS=$(perl -MConfig -E 'say $Config{ccflags}')
 make test
}

package() {
 make DESTDIR="$pkgdir" install
}

sha512sums="
d0032d41c7c0468ed1c6d8f57b885f6cb97a5039d754c8cb60b2067daedaf53bd15fb6561a3d0f828df16dfa5417f663b
8065ba65f4fea16dc9262728b3b6b85
  BSD-Resource-1.2911.tar.gz
"
bzip2 applet in busybox is based on lightly-modified source
of bzip2 version 1.0.4. bzip2 source is distributed
under the following conditions (copied verbatim from LICENSE file)
------------------------------------------------------------


This program, "bzip2", the associated library "libbzip2", and all
documentation, are copyright (C) 1996-2006 Julian R Seward.  All
rights reserved.
```

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

2. The origin of this software must not be misrepresented; you must
  not claim that you wrote the original software. If you use this
  software in a product, an acknowledgment in the product
  documentation would be appreciated but is not required.

3. Altered source versions must be plainly marked as such, and must
  not be misrepresented
 as being the original software.

4. The name of the author may not be used to endorse or promote
  products derived from this software without specific prior written
  permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS
OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, Cambridge, UK.
jseward@bzip.org
bzip2/libbzip2 version 1.0.4 of 20 December 2006
--- A note on GPL versions

BusyBox is distributed under version 2 of the General Public License (included
in its entirety, below). Version 2 is the only version of this license which
this version of BusyBox (or modified versions derived from this one) may be
distributed under.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's
software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for
a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software

patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent
this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this
License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the
notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and
copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices

stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three

years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed
under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the
executable runs, unless that component
itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or
its derivative works. These actions are
prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict
the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity
of the free software distribution system, which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among

countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make
exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED
ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of
 Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.
Contributor: Maxim Karasev <begs@disroot.org>
Maintainer: mio <miyopan@e.email>
pkgname=bsd-games
pkgver=3.3
pkgrel=2
pkgdesc="traditional text mode games from BSD"
url="https://bsd-games.sourceforge.io/"
arch="all"
license="BSD-3-Clause"
install="$pkgname.post-install"
makedepends="ncurses-dev coreutils" # configure causes busybox expr error
subpackages="$pkgname-doc"
source="https://sourceforge.net/projects/bsd-games/files/bsd-games-$pkgver.tar.gz
 0001-bsd-games-scores-dir.patch
 "
options="!check" # no tests

build() {
 # some GNU autoconf options are ignored, but it works
 ./configure \
  --build=$CBUILD \
  --host=$CHOST \
  --prefix=/usr \
  --sysconfdir=/etc \
  --mandir=/usr/share/man \
  --scoredir=/usr/share/$pkgname
 make
}

package() {
 make DESTDIR="$pkgdir" install
 install -Dm644 LICENSE "$pkgdir"/usr/share/licenses/bsd-games/LICENSE

}

sha512sums="
aaf36d09d4fe68514a5c279063d7e77a9a9a84c447037cba974b29faa07eb80c2aab2379d0699c196b5c27ffe1b2bb2c68d3390143e0e62d5e3d210ccfb61294
  bsd-games-3.3.tar.gz
e1def0d4835a877242c4173fae862e278a7858738e0bacacbb045a42bcabec2aa7c72d000bbd2421ce35fe66cdc1f52c0577b7e278029ca5ed50f7aab22319f6 0001-bsd-games-scores-dir.patch
"

MIT License

Copyright (c) 2023 Leaf Corcoran

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
 WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
 Vintage Dreams Waves v 2.0. for Creative Labs' AWE Soundcards
(EMU Soundfont 2 Format)

Copyright (c) Ian Wilson, 1996 (Updated January 1998)

This soundfont is freeware. You may freely use and/or redistribute it subject
to the following terms:
1. It is not altered, edited, modified, ripped, or converted to other formats,
except for private use only.
2. It is distributed with this copyright notice.

This soundfont is distributed WITHOUT WARRANTY, and without the implied
warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. No liability
or damages can be inferred upon the said copyright owner, Ian Wilson.

Any feedback, contact Ian Wilson.
vintagedreamworks@hotmail.com

```
http://www.geocities.com/SiliconValley/Campus/8645/index.html
http://members.nbci.com/silicon39/
http://www.mp3.com/silicon39
https://analoguesque.x10host.com/
# Contributor: Carlo Landmeter <clandmeter@alpinelinux.org>
# Maintainer: Kevin Daudt <kdaudt@alpinelinux.org>
pkgname=spdx-licenses
pkgver=3.24.0
pkgrel=0
pkgdesc="Various data formats for the SPDX License List"
url="https://spdx.org/"
arch="noarch"
options="!check" # no test suite
license="CC-BY-3.0"
source="license-list-data-$pkgver.tar.gz::https://github.com/spdx/license-list-data/archive/v$pkgver.tar.gz"
builddir="$srcdir/license-list-data-$pkgver"
subpackages="$pkgname-list"

_types="html json rdfa rdfnt rdfturtle rdfxml template text"

for type in $_types; do
 subpackages="$subpackages $pkgname-$type:_subpkg"
done

package() {
 mkdir -p "$pkgdir"
}

_subpkg() {
 local type=${subpkgname/$pkgname-/}
 pkgdesc="$pkgdesc ($type)"
 install_if="$pkgname=$pkgver-r$pkgrel"
 mkdir -p "$subpkgdir"/usr/share/spdx
 cp -r "$builddir"/$type "$subpkgdir"/usr/share/spdx/
}

list() {
 pkgdesc="$pkgdesc (licence list)"
 mkdir -p "$subpkgdir"/usr/share/spdx
 local i; for i in "$builddir"/text/*.txt;
 do
  local license=${i##*/}
  echo ${license%.*} >> "$subpkgdir"/usr/share/spdx/license.lst
 done
}

sha512sums="
6eb81424e1b3173dbd8e17859b2e15dfe1c2af8f4da59b7dad0729c038a4cbdba95c34c2c546285fcdbbd41562e39575e
```

```
6a6ebb9463b70121e0a12b99d1307e7  license-list-data-3.24.0.tar.gz
"
# Maintainer: Natanael Copa <ncopa@alpinelinux.org>
pkgname=libart-lgpl
pkgver=2.3.21
pkgrel=8
pkgdesc="A library for high-performance 2D graphics"
url="https://www.levien.com/libart/"
arch="all"
options="!check"  # No test suite.
license="LGPL-2.0-or-later"
subpackages="$pkgname-dev"
source="https://download.gnome.org/sources/libart_lgpl/2.3/libart_lgpl-$pkgver.tar.bz2
 "

builddir="$srcdir"/libart_lgpl-$pkgver

prepare() {
 update_config_sub
 default_prepare
}

build() {
 ./configure \
  --build=$CBUILD \
  --host=$CHOST \
  --prefix=/usr
 make
}

package() {
 make DESTDIR="$pkgdir" install
}

sha512sums="8a632a6a4da59e5e8c02ec2f5a57e36d182b325b46513765425e5f171ff9ae326af1b133725beba28f7e7
6654309e001aee9bace727b5b4c8589405256a3c020  libart_lgpl-2.3.21.tar.bz2"
mini_sendmail - accept email on behalf of real sendmail

Copyright  1999,2015 by Jef Poskanzer <jef@mail.acme.com>.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
```

documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING,
 BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

```
# Contributor: Patrycja Rosa <alpine@ptrcnull.me>
# Maintainer: Patrycja Rosa <alpine@ptrcnull.me>
pkgname=bsd-compat-headers
pkgver=0.7.2
pkgrel=6
pkgdesc="BSD compatibility headers (cdefs, queue, tree)"
url="https://gitlab.alpinelinux.org/alpine/aports"
arch="noarch"
license="BSD-2-Clause AND BSD-3-Clause"
source="
 cdefs.h
 queue.h
 tree.h
"
builddir="$srcdir"
options="!check" # just headers

package() {
 mkdir -p "$pkgdir"
 install -Dm644 -t "$pkgdir"/usr/include/sys \
  cdefs.h queue.h tree.h
}
sha512sums="
37c8fc73c7aea7b490f7850927e2bb91d12137c9e59e22c084146d515696dbc7973b5de92f4c987ba080dd2502ba8312
7006442c3f019b6447a620c0cae73178  cdefs.h
2f0d5e6e4dc3350285cf17009265dddcbe12431c111868eea39bc8cb038ab7c1f2acacbb21735c4e9d4a1fd106a8fc0f86
11ea33987d4faba37dde5ce6da0750  queue.h
d9ac210d81feb8ad2655bc80fb065d3fe20ae4417b32b4a1711e6738a4870140005c13373b5d1846ef3ce5ae6da45f2da
cef2092881eded0a2e94f6a07752ef3  tree.h
"
```

Original Copyright (c) 1985 by Supoj Sutanthavibul
Parts Copyright (c) 1989-2012 by Brian V. Smith
Parts Copyright (c) 1991 by Paul King
Other Copyrights may be found in various files

Main Xfig copyright notice:

Any party obtaining a copy of these files is granted, free of charge, a full and unrestricted irrevocable, world-wide, paid up, royalty-free, nonexclusive right and license to deal in this software and documentation files (the "Software"), including without limitation the rights to use, copy, modify, merge, publish and/or distribute copies of the Software, and to permit persons who receive copies from any such party to do so, with the only requirement being that this copyright notice remain intact.

No representations are made about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

Parts Copyright (C) 1993 by Alan Richardson (mppa3@uk.ac.sussex.syma)
The text rotation code in w_rottext.c was written by Alan Richardson.
The above copyright notice holds for this work as well.

Parts Copyright (c) 1994 by Anthony Dekker
The Kohonen neural network code for color optimization was written by Anthony Dekker.

Parts Copyright (c) 1995 by C. Blanc and C. Schlick
The X-Spline code was written Carole Blanc (blanc@labri.u-bordeaux.fr) and Christophe Schlick (schlick@labri.u-bordeaux.fr) starting from an initial implementation done by C. Feuille, S. Grosbois, L. Maziere and L. Minihot as a student practice (Universite Bordeaux, France). For additional information about X-splines, see:
"X-Splines: A Spline Model Designed for the End User" by C. Blanc and C. Schlick, Proceedings of SIGGRAPH'95
http://dept-info.labri.u-bordeaux.fr/~schlick/DOC/sig1.html
/* $NetBSD: queue.h,v 1.70 2015/11/02 15:21:23 christos Exp $ */

/*
* Copyright (c) 1991, 1993
* The Regents of the University of California. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the University nor the names of its contributors
*   may be used to endorse or promote products derived from this software
*   without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING,
 BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE

```
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* @(#)queue.h 8.5 (Berkeley) 8/20/94
*/

#ifndef _SYS_QUEUE_H_
#define _SYS_QUEUE_H_

/*
* This file defines five types of data structures: singly-linked lists,
* lists, simple queues, tail queues, and circular queues.
*
* A singly-linked list is headed by a single forward pointer. The
* elements are singly linked for minimum space and
 pointer manipulation
* overhead at the expense of O(n) removal for arbitrary elements. New
* elements can be added to the list after an existing element or at the
* head of the list.  Elements being removed from the head of the list
* should use the explicit macro for this purpose for optimum
* efficiency. A singly-linked list may only be traversed in the forward
* direction.  Singly-linked lists are ideal for applications with large
* datasets and few or no removals or for implementing a LIFO queue.
*
* A list is headed by a single forward pointer (or an array of forward
* pointers for a hash table header). The elements are doubly linked
* so that an arbitrary element can be removed without a need to
* traverse the list. New elements can be added to the list before
* or after an existing element or at the head of the list. A list
* may only be traversed in the forward direction.
*
* A simple queue is headed by a pair of pointers, one the head of the
* list and the
 other to the tail of the list. The elements are singly
* linked to save space, so elements can only be removed from the
* head of the list. New elements can be added to the list after
* an existing element, at the head of the list, or at the end of the
* list. A simple queue may only be traversed in the forward direction.
*
* A tail queue is headed by a pair of pointers, one to the head of the
* list and the other to the tail of the list. The elements are doubly
* linked so that an arbitrary element can be removed without a need to
* traverse the list. New elements can be added to the list before or
```

```
* after an existing element, at the head of the list, or at the end of
* the list. A tail queue may be traversed in either direction.
*
* A circle queue is headed by a pair of pointers, one to the head of the
* list and the other to the tail of the list. The elements are doubly
* linked so that an arbitrary element can be removed without a need to
* traverse the list. New elements
 can be added to the list before or after
* an existing element, at the head of the list, or at the end of the list.
* A circle queue may be traversed in either direction, but has a more
* complex end of list detection.
*
* For details on the use of these macros, see the queue(3) manual page.
*/

/*
* Include the definition of NULL only on NetBSD because sys/null.h
* is not available elsewhere.  This conditional makes the header
* portable and it can simply be dropped verbatim into any system.
* The caveat is that on other systems some other header
* must provide NULL before the macros can be used.
*/
#ifdef __NetBSD__
#include <sys/null.h>
#endif

#if defined(QUEUEDEBUG)
# if defined(_KERNEL)
#  define QUEUEDEBUG_ABORT(...) panic(__VA_ARGS__)
# else
#  include <err.h>
#  define QUEUEDEBUG_ABORT(...) err(1, __VA_ARGS__)
# endif
#endif

/*
* Singly-linked List definitions.
*/
#define SLIST_HEAD(name, type)      \
struct name {       \
 struct type *slh_first; /* first
 element */   \
}

#define SLIST_HEAD_INITIALIZER(head)     \
 { NULL }

#define SLIST_ENTRY(type)      \
```

```
struct {        \
 struct type *sle_next; /* next element */   \
}

/*
* Singly-linked List access methods.
*/
#define SLIST_FIRST(head) ((head)->slh_first)
#define SLIST_END(head)  NULL
#define SLIST_EMPTY(head) ((head)->slh_first == NULL)
#define SLIST_NEXT(elm, field) ((elm)->field.sle_next)

#define SLIST_FOREACH(var, head, field)     \
 for((var) = (head)->slh_first;     \
     (var) != SLIST_END(head);     \
     (var) = (var)->field.sle_next)

#define SLIST_FOREACH_SAFE(var, head, field, tvar)   \
 for ((var) = SLIST_FIRST((head));    \
     (var) != SLIST_END(head) &&     \
     ((tvar) = SLIST_NEXT((var), field), 1);   \
     (var) = (tvar))

/*
* Singly-linked List functions.
*/
#define SLIST_INIT(head) do {      \
 (head)->slh_first = SLIST_END(head);    \
} while (/*CONSTCOND*/0)

#define SLIST_INSERT_AFTER(slistelm, elm, field) do {   \
 (elm)->field.sle_next = (slistelm)->field.sle_next;  \
 (slistelm)->field.sle_next
 = (elm);    \
} while (/*CONSTCOND*/0)

#define SLIST_INSERT_HEAD(head, elm, field) do {    \
 (elm)->field.sle_next = (head)->slh_first;   \
 (head)->slh_first = (elm);     \
} while (/*CONSTCOND*/0)

#define SLIST_REMOVE_AFTER(slistelm, field) do {    \
 (slistelm)->field.sle_next =     \
     SLIST_NEXT(SLIST_NEXT((slistelm), field), field);  \
} while (/*CONSTCOND*/0)

#define SLIST_REMOVE_HEAD(head, field) do {     \
 (head)->slh_first = (head)->slh_first->field.sle_next;  \
```

```
} while (/*CONSTCOND*/0)

#define SLIST_REMOVE(head, elm, type, field) do {   \
 if ((head)->slh_first == (elm)) {    \
  SLIST_REMOVE_HEAD((head), field);   \
 }       \
 else {       \
  struct type *curelm = (head)->slh_first;  \
  while(curelm->field.sle_next != (elm))   \
   curelm = curelm->field.sle_next;  \
  curelm->field.sle_next =    \
      curelm->field.sle_next->field.sle_next;  \
 }       \
} while (/*CONSTCOND*/0)


/*
* List definitions.
 */
#define LIST_HEAD(name, type)      \
struct name {       \
 struct type *lh_first; /* first element */   \
}

#define LIST_HEAD_INITIALIZER(head)     \
 { NULL }

#define LIST_ENTRY(type)      \
struct {       \
 struct type *le_next; /* next element */   \
 struct type **le_prev; /* address of previous next element */ \
}

/*
* List access methods.
*/
#define LIST_FIRST(head)  ((head)->lh_first)
#define LIST_END(head)   NULL
#define LIST_EMPTY(head)  ((head)->lh_first == LIST_END(head))
#define LIST_NEXT(elm, field)  ((elm)->field.le_next)

#define LIST_FOREACH(var, head, field)     \
 for ((var) = ((head)->lh_first);    \
     (var) != LIST_END(head);     \
     (var) = ((var)->field.le_next))

#define LIST_FOREACH_SAFE(var, head, field, tvar)   \
 for ((var) = LIST_FIRST((head));    \
```

```
    (var) != LIST_END(head) &&     \
    ((tvar) = LIST_NEXT((var), field), 1);   \
    (var) = (tvar))

#define LIST_MOVE(head1, head2) do {     \
 LIST_INIT((head2));      \
 if (!LIST_EMPTY((head1)))
 {     \
  (head2)->lh_first = (head1)->lh_first;   \
  LIST_INIT((head1));     \
 }       \
} while (/*CONSTCOND*/0)

/*
* List functions.
*/
#if defined(QUEUEDEBUG)
#define QUEUEDEBUG_LIST_INSERT_HEAD(head, elm, field)   \
 if ((head)->lh_first &&      \
    (head)->lh_first->field.le_prev != &(head)->lh_first) \
  QUEUEDEBUG_ABORT("LIST_INSERT_HEAD %p %s:%d", (head), \
      __FILE__, __LINE__);
#define QUEUEDEBUG_LIST_OP(elm, field)     \
 if ((elm)->field.le_next &&     \
    (elm)->field.le_next->field.le_prev !=   \
    &(elm)->field.le_next)     \
  QUEUEDEBUG_ABORT("LIST_* forw %p %s:%d", (elm),  \
      __FILE__, __LINE__);    \
 if (*(elm)->field.le_prev != (elm))    \
  QUEUEDEBUG_ABORT("LIST_* back %p %s:%d", (elm),  \
      __FILE__, __LINE__);
#define QUEUEDEBUG_LIST_POSTREMOVE(elm, field)    \
 (elm)->field.le_next = (void *)1L;    \
 (elm)->field.le_prev = (void *)1L;
#else
#define QUEUEDEBUG_LIST_INSERT_HEAD(head, elm, field)
#define QUEUEDEBUG_LIST_OP(elm,
 field)
#define QUEUEDEBUG_LIST_POSTREMOVE(elm, field)
#endif

#define LIST_INIT(head) do {      \
 (head)->lh_first = LIST_END(head);    \
} while (/*CONSTCOND*/0)

#define LIST_INSERT_AFTER(listelm, elm, field) do {   \
 QUEUEDEBUG_LIST_OP((listelm), field)    \
 if (((elm)->field.le_next = (listelm)->field.le_next) !=  \
```

```
    LIST_END(head))      \
  (listelm)->field.le_next->field.le_prev =  \
      &(elm)->field.le_next;    \
 (listelm)->field.le_next = (elm);    \
 (elm)->field.le_prev = &(listelm)->field.le_next;  \
} while (/*CONSTCOND*/0)

#define LIST_INSERT_BEFORE(listelm, elm, field) do {   \
 QUEUEDEBUG_LIST_OP((listelm), field)    \
 (elm)->field.le_prev = (listelm)->field.le_prev;  \
 (elm)->field.le_next = (listelm);    \
 *(listelm)->field.le_prev = (elm);    \
 (listelm)->field.le_prev = &(elm)->field.le_next;  \
} while (/*CONSTCOND*/0)

#define LIST_INSERT_HEAD(head, elm, field) do {    \
 QUEUEDEBUG_LIST_INSERT_HEAD((head), (elm), field)  \
 if (((elm)->field.le_next
 = (head)->lh_first) != LIST_END(head))\
  (head)->lh_first->field.le_prev = &(elm)->field.le_next;\
 (head)->lh_first = (elm);     \
 (elm)->field.le_prev = &(head)->lh_first;   \
} while (/*CONSTCOND*/0)

#define LIST_REMOVE(elm, field) do {     \
 QUEUEDEBUG_LIST_OP((elm), field)    \
 if ((elm)->field.le_next != NULL)    \
  (elm)->field.le_next->field.le_prev =    \
      (elm)->field.le_prev;    \
 *(elm)->field.le_prev = (elm)->field.le_next;   \
 QUEUEDEBUG_LIST_POSTREMOVE((elm), field)   \
} while (/*CONSTCOND*/0)

#define LIST_REPLACE(elm, elm2, field) do {    \
 if (((elm2)->field.le_next = (elm)->field.le_next) != NULL) \
  (elm2)->field.le_next->field.le_prev =   \
      &(elm2)->field.le_next;    \
 (elm2)->field.le_prev = (elm)->field.le_prev;   \
 *(elm2)->field.le_prev = (elm2);    \
 QUEUEDEBUG_LIST_POSTREMOVE((elm), field)   \
} while (/*CONSTCOND*/0)

/*
* Simple queue definitions.
*/
#define SIMPLEQ_HEAD(name, type)     \
struct name {        \
 struct
```

```
 type *sqh_first; /* first element */   \
 struct type **sqh_last; /* addr of last next element */  \
}

#define SIMPLEQ_HEAD_INITIALIZER(head)     \
 { NULL, &(head).sqh_first }

#define SIMPLEQ_ENTRY(type)      \
struct {        \
 struct type *sqe_next; /* next element */   \
}

/*
* Simple queue access methods.
*/
#define SIMPLEQ_FIRST(head)  ((head)->sqh_first)
#define SIMPLEQ_END(head)  NULL
#define SIMPLEQ_EMPTY(head)  ((head)->sqh_first == SIMPLEQ_END(head))
#define SIMPLEQ_NEXT(elm, field) ((elm)->field.sqe_next)

#define SIMPLEQ_FOREACH(var, head, field)    \
 for ((var) = ((head)->sqh_first);    \
     (var) != SIMPLEQ_END(head);     \
     (var) = ((var)->field.sqe_next))

#define SIMPLEQ_FOREACH_SAFE(var, head, field, next)   \
 for ((var) = ((head)->sqh_first);    \
     (var) != SIMPLEQ_END(head) &&    \
     ((next = ((var)->field.sqe_next)), 1);   \
     (var) = (next))

/*
* Simple queue functions.
*/
#define SIMPLEQ_INIT(head) do {      \
 (head)->sqh_first = NULL;     \
 (head)->sqh_last
 = &(head)->sqh_first;    \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_INSERT_HEAD(head, elm, field) do {   \
 if (((elm)->field.sqe_next = (head)->sqh_first) == NULL) \
  (head)->sqh_last = &(elm)->field.sqe_next;  \
 (head)->sqh_first = (elm);     \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_INSERT_TAIL(head, elm, field) do {   \
 (elm)->field.sqe_next = NULL;     \
```

```
 *(head)->sqh_last = (elm);     \
 (head)->sqh_last = &(elm)->field.sqe_next;   \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_INSERT_AFTER(head, listelm, elm, field) do {  \
 if (((elm)->field.sqe_next = (listelm)->field.sqe_next) == NULL)\
  (head)->sqh_last = &(elm)->field.sqe_next;  \
 (listelm)->field.sqe_next = (elm);    \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_REMOVE_HEAD(head, field) do {    \
 if (((head)->sqh_first = (head)->sqh_first->field.sqe_next) == NULL) \
  (head)->sqh_last = &(head)->sqh_first;   \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_REMOVE_AFTER(head, elm, field) do {   \
 if
 (((elm)->field.sqe_next = (elm)->field.sqe_next->field.sqe_next) \
    == NULL)       \
  (head)->sqh_last = &(elm)->field.sqe_next;  \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_REMOVE(head, elm, type, field) do {   \
 if ((head)->sqh_first == (elm)) {    \
  SIMPLEQ_REMOVE_HEAD((head), field);   \
 } else {       \
  struct type *curelm = (head)->sqh_first;  \
  while (curelm->field.sqe_next != (elm))   \
   curelm = curelm->field.sqe_next;  \
  if ((curelm->field.sqe_next =    \
   curelm->field.sqe_next->field.sqe_next) == NULL) \
      (head)->sqh_last = &(curelm)->field.sqe_next; \
 }       \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_CONCAT(head1, head2) do {    \
 if (!SIMPLEQ_EMPTY((head2))) {     \
  *(head1)->sqh_last = (head2)->sqh_first;  \
  (head1)->sqh_last = (head2)->sqh_last;  \
  SIMPLEQ_INIT((head2));     \
 }       \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_LAST(head, type, field)     \
 (SIMPLEQ_EMPTY((head)) ?      \
  NULL :       \
        ((struct type
```

```
 *)(void *)    \
  ((char *)((head)->sqh_last) - offsetof(struct type, field))))

/*
* Tail queue definitions.
*/
#define _TAILQ_HEAD(name, type, qual)     \
struct name {        \
 qual type *tqh_first;  /* first element */  \
 qual type *qual *tqh_last; /* addr of last next element */ \
}
#define TAILQ_HEAD(name, type) _TAILQ_HEAD(name, struct type,)

#define TAILQ_HEAD_INITIALIZER(head)     \
 { TAILQ_END(head), &(head).tqh_first }

#define _TAILQ_ENTRY(type, qual)     \
struct {        \
 qual type *tqe_next;  /* next element */  \
 qual type *qual *tqe_prev; /* address of previous next element */\
}
#define TAILQ_ENTRY(type) _TAILQ_ENTRY(struct type,)

/*
* Tail queue access methods.
*/
#define TAILQ_FIRST(head)  ((head)->tqh_first)
#define TAILQ_END(head)   (NULL)
#define TAILQ_NEXT(elm, field)  ((elm)->field.tqe_next)
#define TAILQ_LAST(head, headname) \
 (*(((struct headname *)(void *)((head)->tqh_last))->tqh_last))
#define TAILQ_PREV(elm, headname, field) \
 (*(((struct headname
 *)(void *)((elm)->field.tqe_prev))->tqh_last))
#define TAILQ_EMPTY(head)  (TAILQ_FIRST(head) == TAILQ_END(head))


#define TAILQ_FOREACH(var, head, field)     \
 for ((var) = ((head)->tqh_first);    \
     (var) != TAILQ_END(head);     \
     (var) = ((var)->field.tqe_next))

#define TAILQ_FOREACH_SAFE(var, head, field, next)   \
 for ((var) = ((head)->tqh_first);    \
     (var) != TAILQ_END(head) &&     \
     ((next) = TAILQ_NEXT(var, field), 1); (var) = (next))

#define TAILQ_FOREACH_REVERSE(var, head, headname, field)  \
```

```
 for ((var) = TAILQ_LAST((head), headname);   \
    (var) != TAILQ_END(head);     \
    (var) = TAILQ_PREV((var), headname, field))

#define TAILQ_FOREACH_REVERSE_SAFE(var, head, headname, field, prev) \
 for ((var) = TAILQ_LAST((head), headname);   \
    (var) != TAILQ_END(head) &&     \
    ((prev) = TAILQ_PREV((var), headname, field), 1); (var) = (prev))

/*
* Tail queue functions.
*/
#if defined(QUEUEDEBUG)
#define QUEUEDEBUG_TAILQ_INSERT_HEAD(head,
 elm, field)   \
 if ((head)->tqh_first &&     \
    (head)->tqh_first->field.tqe_prev != &(head)->tqh_first) \
  QUEUEDEBUG_ABORT("TAILQ_INSERT_HEAD %p %s:%d", (head), \
     __FILE__, __LINE__);
#define QUEUEDEBUG_TAILQ_INSERT_TAIL(head, elm, field)   \
 if (*(head)->tqh_last != NULL)     \
  QUEUEDEBUG_ABORT("TAILQ_INSERT_TAIL %p %s:%d", (head), \
     __FILE__, __LINE__);
#define QUEUEDEBUG_TAILQ_OP(elm, field)     \
 if ((elm)->field.tqe_next &&     \
    (elm)->field.tqe_next->field.tqe_prev !=   \
    &(elm)->field.tqe_next)     \
  QUEUEDEBUG_ABORT("TAILQ_* forw %p %s:%d", (elm), \
     __FILE__, __LINE__);    \
 if (*(elm)->field.tqe_prev != (elm))    \
  QUEUEDEBUG_ABORT("TAILQ_* back %p %s:%d", (elm), \
     __FILE__, __LINE__);
#define QUEUEDEBUG_TAILQ_PREREMOVE(head, elm, field)   \
 if ((elm)->field.tqe_next == NULL &&    \
    (head)->tqh_last != &(elm)->field.tqe_next)   \
  QUEUEDEBUG_ABORT("TAILQ_PREREMOVE head %p elm %p %s:%d",\
     (head), (elm), __FILE__,
 __LINE__);
#define QUEUEDEBUG_TAILQ_POSTREMOVE(elm, field)    \
 (elm)->field.tqe_next = (void *)1L;    \
 (elm)->field.tqe_prev = (void *)1L;
#else
#define QUEUEDEBUG_TAILQ_INSERT_HEAD(head, elm, field)
#define QUEUEDEBUG_TAILQ_INSERT_TAIL(head, elm, field)
#define QUEUEDEBUG_TAILQ_OP(elm, field)
#define QUEUEDEBUG_TAILQ_PREREMOVE(head, elm, field)
#define QUEUEDEBUG_TAILQ_POSTREMOVE(elm, field)
#endif
```

```
#define TAILQ_INIT(head) do {      \
 (head)->tqh_first = TAILQ_END(head);    \
 (head)->tqh_last = &(head)->tqh_first;    \
} while (/*CONSTCOND*/0)

#define TAILQ_INSERT_HEAD(head, elm, field) do {    \
 QUEUEDEBUG_TAILQ_INSERT_HEAD((head), (elm), field)  \
 if (((elm)->field.tqe_next = (head)->tqh_first) != TAILQ_END(head))\
  (head)->tqh_first->field.tqe_prev =    \
     &(elm)->field.tqe_next;    \
 else       \
  (head)->tqh_last = &(elm)->field.tqe_next;  \
 (head)->tqh_first = (elm);     \
 (elm)->field.tqe_prev = &(head)->tqh_first;   \
} while (/*CONSTCOND*/0)

#define TAILQ_INSERT_TAIL(head,
 elm, field) do {   \
 QUEUEDEBUG_TAILQ_INSERT_TAIL((head), (elm), field)  \
 (elm)->field.tqe_next = TAILQ_END(head);   \
 (elm)->field.tqe_prev = (head)->tqh_last;   \
 *(head)->tqh_last = (elm);     \
 (head)->tqh_last = &(elm)->field.tqe_next;   \
} while (/*CONSTCOND*/0)

#define TAILQ_INSERT_AFTER(head, listelm, elm, field) do {  \
 QUEUEDEBUG_TAILQ_OP((listelm), field)    \
 if (((elm)->field.tqe_next = (listelm)->field.tqe_next) !=  \
     TAILQ_END(head))      \
  (elm)->field.tqe_next->field.tqe_prev =   \
      &(elm)->field.tqe_next;    \
 else       \
  (head)->tqh_last = &(elm)->field.tqe_next;  \
 (listelm)->field.tqe_next = (elm);    \
 (elm)->field.tqe_prev = &(listelm)->field.tqe_next;  \
} while (/*CONSTCOND*/0)

#define TAILQ_INSERT_BEFORE(listelm, elm, field) do {   \
 QUEUEDEBUG_TAILQ_OP((listelm), field)    \
 (elm)->field.tqe_prev = (listelm)->field.tqe_prev;  \
 (elm)->field.tqe_next = (listelm);    \
 *(listelm)->field.tqe_prev = (elm);    \
 (listelm)->field.tqe_prev
 = &(elm)->field.tqe_next;  \
} while (/*CONSTCOND*/0)

#define TAILQ_REMOVE(head, elm, field) do {    \
```

```
 QUEUEDEBUG_TAILQ_PREREMOVE((head), (elm), field)  \
 QUEUEDEBUG_TAILQ_OP((elm), field)    \
 if (((elm)->field.tqe_next) != TAILQ_END(head))   \
  (elm)->field.tqe_next->field.tqe_prev =   \
      (elm)->field.tqe_prev;    \
 else       \
  (head)->tqh_last = (elm)->field.tqe_prev;  \
 *(elm)->field.tqe_prev = (elm)->field.tqe_next;   \
 QUEUEDEBUG_TAILQ_POSTREMOVE((elm), field);   \
} while (/*CONSTCOND*/0)

#define TAILQ_REPLACE(head, elm, elm2, field) do {   \
       if (((elm2)->field.tqe_next = (elm)->field.tqe_next) !=  \
     TAILQ_END(head))        \
             (elm2)->field.tqe_next->field.tqe_prev =  \
                 &(elm2)->field.tqe_next;    \
       else       \
             (head)->tqh_last = &(elm2)->field.tqe_next;  \
       (elm2)->field.tqe_prev = (elm)->field.tqe_prev;   \
       *(elm2)->field.tqe_prev = (elm2);    \
 QUEUEDEBUG_TAILQ_POSTREMOVE((elm),
 field);   \
} while (/*CONSTCOND*/0)

#define TAILQ_CONCAT(head1, head2, field) do {    \
 if (!TAILQ_EMPTY(head2)) {     \
  *(head1)->tqh_last = (head2)->tqh_first;  \
  (head2)->tqh_first->field.tqe_prev = (head1)->tqh_last; \
  (head1)->tqh_last = (head2)->tqh_last;   \
  TAILQ_INIT((head2));     \
 }       \
} while (/*CONSTCOND*/0)

/*
* Singly-linked Tail queue declarations.
*/
#define STAILQ_HEAD(name, type)      \
struct name {       \
 struct type *stqh_first; /* first element */  \
 struct type **stqh_last; /* addr of last next element */ \
}

#define STAILQ_HEAD_INITIALIZER(head)     \
 { NULL, &(head).stqh_first }

#define STAILQ_ENTRY(type)      \
struct {       \
 struct type *stqe_next; /* next element */   \
```

```
}

/*
* Singly-linked Tail queue access methods.
*/
#define STAILQ_FIRST(head) ((head)->stqh_first)
#define STAILQ_END(head) NULL
#define STAILQ_NEXT(elm, field) ((elm)->field.stqe_next)
#define STAILQ_EMPTY(head) (STAILQ_FIRST(head)
 == STAILQ_END(head))

/*
* Singly-linked Tail queue functions.
*/
#define STAILQ_INIT(head) do {      \
 (head)->stqh_first = NULL;     \
 (head)->stqh_last = &(head)->stqh_first;    \
} while (/*CONSTCOND*/0)

#define STAILQ_INSERT_HEAD(head, elm, field) do {   \
 if (((elm)->field.stqe_next = (head)->stqh_first) == NULL) \
  (head)->stqh_last = &(elm)->field.stqe_next;  \
 (head)->stqh_first = (elm);     \
} while (/*CONSTCOND*/0)

#define STAILQ_INSERT_TAIL(head, elm, field) do {   \
 (elm)->field.stqe_next = NULL;     \
 *(head)->stqh_last = (elm);     \
 (head)->stqh_last = &(elm)->field.stqe_next;   \
} while (/*CONSTCOND*/0)

#define STAILQ_INSERT_AFTER(head, listelm, elm, field) do {  \
 if (((elm)->field.stqe_next = (listelm)->field.stqe_next) == NULL)\
  (head)->stqh_last = &(elm)->field.stqe_next;  \
 (listelm)->field.stqe_next = (elm);    \
} while (/*CONSTCOND*/0)

#define STAILQ_REMOVE_HEAD(head, field) do {    \
 if (((head)->stqh_first = (head)->stqh_first->field.stqe_next)
 == NULL) \
  (head)->stqh_last = &(head)->stqh_first;   \
} while (/*CONSTCOND*/0)

#define STAILQ_REMOVE(head, elm, type, field) do {   \
 if ((head)->stqh_first == (elm)) {    \
  STAILQ_REMOVE_HEAD((head), field);   \
 } else {       \
  struct type *curelm = (head)->stqh_first;  \
```

```
  while (curelm->field.stqe_next != (elm))   \
   curelm = curelm->field.stqe_next;  \
  if ((curelm->field.stqe_next =    \
   curelm->field.stqe_next->field.stqe_next) == NULL) \
      (head)->stqh_last = &(curelm)->field.stqe_next; \
 }       \
} while (/*CONSTCOND*/0)

#define STAILQ_FOREACH(var, head, field)    \
 for ((var) = ((head)->stqh_first);    \
  (var);       \
  (var) = ((var)->field.stqe_next))

#define STAILQ_FOREACH_SAFE(var, head, field, tvar)   \
 for ((var) = STAILQ_FIRST((head));    \
     (var) && ((tvar) = STAILQ_NEXT((var), field), 1);  \
     (var) = (tvar))

#define STAILQ_CONCAT(head1, head2) do {    \
 if (!STAILQ_EMPTY((head2))) {     \
  *(head1)->stqh_last
 = (head2)->stqh_first;  \
  (head1)->stqh_last = (head2)->stqh_last;  \
  STAILQ_INIT((head2));     \
 }       \
} while (/*CONSTCOND*/0)

#define STAILQ_LAST(head, type, field)     \
 (STAILQ_EMPTY((head)) ?      \
  NULL :       \
        ((struct type *)(void *)    \
  ((char *)((head)->stqh_last) - offsetof(struct type, field))))


#ifndef _KERNEL
/*
* Circular queue definitions. Do not use. We still keep the macros
* for compatibility but because of pointer aliasing issues their use
* is discouraged!
*/

/*
* __launder_type():  We use this ugly hack to work around the the compiler
* noticing that two types may not alias each other and elide tests in code.
* We hit this in the CIRCLEQ macros when comparing 'struct name *' and
* 'struct type *' (see CIRCLEQ_HEAD()).  Modern compilers (such as GCC
* 4.8) declare these comparisons as always false, causing the code to
* not run as designed.
```

```
*
* This hack is only to be used for comparisons and thus can be fully const.
 * Do not use for assignment.
*
* If we ever choose to change the ABI of the CIRCLEQ macros, we could fix
* this by changing the head/tail sentinal values, but see the note above
* this one.
*/
static __inline const void * __launder_type(const void *);
static __inline const void *
__launder_type(const void *__x)
{
 __asm __volatile("" : "+r" (__x));
 return __x;
}

#if defined(QUEUEDEBUG)
#define QUEUEDEBUG_CIRCLEQ_HEAD(head, field)    \
 if ((head)->cqh_first != CIRCLEQ_ENDC(head) &&   \
    (head)->cqh_first->field.cqe_prev != CIRCLEQ_ENDC(head)) \
  QUEUEDEBUG_ABORT("CIRCLEQ head forw %p %s:%d", (head), \
       __FILE__, __LINE__);    \
 if ((head)->cqh_last != CIRCLEQ_ENDC(head) &&   \
    (head)->cqh_last->field.cqe_next != CIRCLEQ_ENDC(head)) \
  QUEUEDEBUG_ABORT("CIRCLEQ head back %p %s:%d", (head), \
       __FILE__, __LINE__);
#define QUEUEDEBUG_CIRCLEQ_ELM(head, elm, field)   \
 if ((elm)->field.cqe_next == CIRCLEQ_ENDC(head)) {  \
  if ((head)->cqh_last != (elm))    \
   QUEUEDEBUG_ABORT("CIRCLEQ
 elm last %p %s:%d", \
      (elm), __FILE__, __LINE__);   \
 } else {       \
  if ((elm)->field.cqe_next->field.cqe_prev != (elm)) \
   QUEUEDEBUG_ABORT("CIRCLEQ elm forw %p %s:%d", \
      (elm), __FILE__, __LINE__);   \
 }       \
 if ((elm)->field.cqe_prev == CIRCLEQ_ENDC(head)) {  \
  if ((head)->cqh_first != (elm))    \
   QUEUEDEBUG_ABORT("CIRCLEQ elm first %p %s:%d", \
      (elm), __FILE__, __LINE__);   \
 } else {       \
  if ((elm)->field.cqe_prev->field.cqe_next != (elm)) \
   QUEUEDEBUG_ABORT("CIRCLEQ elm prev %p %s:%d", \
      (elm), __FILE__, __LINE__);   \
 }
#define QUEUEDEBUG_CIRCLEQ_POSTREMOVE(elm, field)   \
 (elm)->field.cqe_next = (void *)1L;    \
```

```
 (elm)->field.cqe_prev = (void *)1L;
#else
#define QUEUEDEBUG_CIRCLEQ_HEAD(head, field)
#define QUEUEDEBUG_CIRCLEQ_ELM(head, elm, field)
#define QUEUEDEBUG_CIRCLEQ_POSTREMOVE(elm, field)
#endif

#define CIRCLEQ_HEAD(name, type)     \
struct name {        \
 struct type *cqh_first;  /*
 first element */  \
 struct type *cqh_last;  /* last element */  \
}

#define CIRCLEQ_HEAD_INITIALIZER(head)     \
 { CIRCLEQ_END(&head), CIRCLEQ_END(&head) }

#define CIRCLEQ_ENTRY(type)      \
struct {        \
 struct type *cqe_next;  /* next element */  \
 struct type *cqe_prev;  /* previous element */  \
}

/*
* Circular queue functions.
*/
#define CIRCLEQ_INIT(head) do {      \
 (head)->cqh_first = CIRCLEQ_END(head);    \
 (head)->cqh_last = CIRCLEQ_END(head);    \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_INSERT_AFTER(head, listelm, elm, field) do {  \
 QUEUEDEBUG_CIRCLEQ_HEAD((head), field)    \
 QUEUEDEBUG_CIRCLEQ_ELM((head), (listelm), field)  \
 (elm)->field.cqe_next = (listelm)->field.cqe_next;  \
 (elm)->field.cqe_prev = (listelm);    \
 if ((listelm)->field.cqe_next == CIRCLEQ_ENDC(head))  \
  (head)->cqh_last = (elm);    \
 else        \
  (listelm)->field.cqe_next->field.cqe_prev = (elm); \
 (listelm)->field.cqe_next = (elm);    \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_INSERT_BEFORE(head,
 listelm, elm, field) do {  \
 QUEUEDEBUG_CIRCLEQ_HEAD((head), field)    \
 QUEUEDEBUG_CIRCLEQ_ELM((head), (listelm), field)  \
 (elm)->field.cqe_next = (listelm);    \
```

```
 (elm)->field.cqe_prev = (listelm)->field.cqe_prev;  \
 if ((listelm)->field.cqe_prev == CIRCLEQ_ENDC(head))  \
  (head)->cqh_first = (elm);    \
 else       \
  (listelm)->field.cqe_prev->field.cqe_next = (elm); \
 (listelm)->field.cqe_prev = (elm);    \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_INSERT_HEAD(head, elm, field) do {   \
 QUEUEDEBUG_CIRCLEQ_HEAD((head), field)    \
 (elm)->field.cqe_next = (head)->cqh_first;   \
 (elm)->field.cqe_prev = CIRCLEQ_END(head);   \
 if ((head)->cqh_last == CIRCLEQ_ENDC(head))   \
  (head)->cqh_last = (elm);    \
 else       \
  (head)->cqh_first->field.cqe_prev = (elm);  \
 (head)->cqh_first = (elm);     \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_INSERT_TAIL(head, elm, field) do {   \
 QUEUEDEBUG_CIRCLEQ_HEAD((head), field)    \
 (elm)->field.cqe_next
 = CIRCLEQ_END(head);   \
 (elm)->field.cqe_prev = (head)->cqh_last;   \
 if ((head)->cqh_first == CIRCLEQ_ENDC(head))   \
  (head)->cqh_first = (elm);    \
 else       \
  (head)->cqh_last->field.cqe_next = (elm);  \
 (head)->cqh_last = (elm);     \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_REMOVE(head, elm, field) do {    \
 QUEUEDEBUG_CIRCLEQ_HEAD((head), field)    \
 QUEUEDEBUG_CIRCLEQ_ELM((head), (elm), field)   \
 if ((elm)->field.cqe_next == CIRCLEQ_ENDC(head))  \
  (head)->cqh_last = (elm)->field.cqe_prev;  \
 else       \
  (elm)->field.cqe_next->field.cqe_prev =   \
     (elm)->field.cqe_prev;    \
 if ((elm)->field.cqe_prev == CIRCLEQ_ENDC(head))  \
  (head)->cqh_first = (elm)->field.cqe_next;  \
 else       \
  (elm)->field.cqe_prev->field.cqe_next =   \
     (elm)->field.cqe_next;    \
 QUEUEDEBUG_CIRCLEQ_POSTREMOVE((elm), field)   \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_FOREACH(var, head, field)    \
```

```
 for ((var) = ((head)->cqh_first);    \
  (var) != CIRCLEQ_ENDC(head);    \
  (var)
 = ((var)->field.cqe_next))

#define CIRCLEQ_FOREACH_REVERSE(var, head, field)   \
 for ((var) = ((head)->cqh_last);    \
  (var) != CIRCLEQ_ENDC(head);    \
  (var) = ((var)->field.cqe_prev))

/*
* Circular queue access methods.
*/
#define CIRCLEQ_FIRST(head)  ((head)->cqh_first)
#define CIRCLEQ_LAST(head)  ((head)->cqh_last)
/* For comparisons */
#define CIRCLEQ_ENDC(head)  (__launder_type(head))
/* For assignments */
#define CIRCLEQ_END(head)  ((void *)(head))
#define CIRCLEQ_NEXT(elm, field) ((elm)->field.cqe_next)
#define CIRCLEQ_PREV(elm, field) ((elm)->field.cqe_prev)
#define CIRCLEQ_EMPTY(head)      \
   (CIRCLEQ_FIRST(head) == CIRCLEQ_ENDC(head))

#define CIRCLEQ_LOOP_NEXT(head, elm, field)    \
 (((elm)->field.cqe_next == CIRCLEQ_ENDC(head))   \
     ? ((head)->cqh_first)     \
     : (elm->field.cqe_next))
#define CIRCLEQ_LOOP_PREV(head, elm, field)    \
 (((elm)->field.cqe_prev == CIRCLEQ_ENDC(head))   \
     ? ((head)->cqh_last)     \
     :
 (elm->field.cqe_prev))
#endif /* !_KERNEL */

#endif /* !_SYS_QUEUE_H_ */
#ifndef _SYS_CDEFS_H_
#define _SYS_CDEFS_H_

#warning usage of non-standard #include <sys/cdefs.h> is deprecated

#undef __P
#undef __PMT

#define __P(args) args
#define __PMT(args) args

#define __CONCAT(x,y) x ## y
```

```
#define __STRING(x) #x

#ifdef  __cplusplus
# define __BEGIN_DECLS extern "C" {
# define __END_DECLS }
#else
# define __BEGIN_DECLS
# define __END_DECLS
#endif

#if defined(__GNUC__) && !defined(__cplusplus)
# define __THROW __attribute__ ((__nothrow__))
# define __NTH(fct) __attribute__ ((__nothrow__)) fct
#else
# define __THROW
# define __NTH(fct)     fct
#endif

#endif /* _SYS_CDEFS_H_ */
# Contributor: Fabian Affolter <fabian@affolter-engineering.ch>
# Maintainer: Fabian Affolter <fabian@affolter-engineering.ch>
pkgname=py3-flake8-copyright
_pkgname=flake8-copyright
pkgver=0.2.4
pkgrel=3
pkgdesc="Extension for flake8 which checks for copyrights"
options="!check" # No testsuite
url="https://github.com/savoirfairelinux/flake8-copyright"
arch="noarch"
license="MIT"
depends="py3-flake8 py3-setuptools"
makedepends="py3-gpep517 py3-wheel"
subpackages="$pkgname-pyc"
source="https://files.pythonhosted.org/packages/source/${_pkgname:0:1}/$_pkgname/$_pkgname-$pkgver.tar.gz"
builddir="$srcdir"/$_pkgname-$pkgver

replaces="py-flake8-copyright"                  # Backwards compatibility
provides="py-flake8-copyright=$pkgver-r$pkgrel" # Backwards compatibility

build() {
 gpep517 build-wheel \
  --wheel-dir .dist \
  --output-fd 3 3>&1 >&2
}

package() {
 gpep517 install-wheel --destdir "$pkgdir" \
  .dist/*.whl
```

```
}

sha512sums="
a6ab47e1bb715618f075c51f398e18180404871b3b0faf1c2d30701d5203db6bc23771bf22ffb5bafcd8ee856b9b64237
b316bd503ae7dceed6ca284ccd5a74d
  flake8-copyright-0.2.4.tar.gz
"
# Maintainer: fossdd <fossdd@pwned.life>
pkgname=cargo-license
pkgver=0.6.1
pkgrel=1
pkgdesc="Cargo subcommand to see license of dependencies"
url="https://github.com/onur/cargo-license"
arch="all"
license="MIT"
makedepends="cargo cargo-auditable"
source="$pkgname-$pkgver.tar.gz::https://crates.io/api/v1/crates/cargo-license/$pkgver/download"

prepare() {
 default_prepare

 cargo fetch --target="$CTARGET" --locked
}

build() {
 cargo auditable build --release --frozen
}

check() {
 cargo test --frozen
}

package() {
 install -Dm755 target/release/cargo-license -t "$pkgdir"/usr/bin
}

sha512sums="
36215145e79965be090ae2f5ce6f5eb208465eb67a94c26bed1fe70a131c46c6dc35695e30852759b7366883fbc3caf00
272d796ac634f0a5e1d49232b6b29d5  cargo-license-0.6.1.tar.gz
"
/* $NetBSD: tree.h,v 1.20 2013/09/14 13:20:45 joerg Exp $ */
/* $OpenBSD: tree.h,v 1.13 2011/07/09 00:19:45 pirofti Exp $ */
/* Modified by Void Linux. */
/*
* Copyright 2002 Niels Provos <provos@citi.umich.edu>
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
```

```
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
*
* THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
* OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
* IN NO EVENT SHALL THE
 AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
* INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
* THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
* (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
* THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

#ifndef _SYS_TREE_H_
#define _SYS_TREE_H_

#ifdef __GNUC__
#define __GNUC_PREREQ__(x, y)      \
 ((__GNUC__ == (x) && __GNUC_MINOR__ >= (y)) ||   \
  (__GNUC__ > (x)))
#else
#define __GNUC_PREREQ__(x, y) 0
#endif

#if __GNUC_PREREQ__(2, 7) || defined(__lint__)
#define _sys_tree_h_unused __attribute__((__unused__))
#else
#define _sys_tree_h_unused /* delete */
#endif

/*
* This file defines data structures for different types of trees:
* splay trees and red-black trees.
*
* A splay tree is a self-organizing
 data structure.  Every operation
* on the tree causes a splay to happen.  The splay moves the requested
* node to the root of the tree and partly rebalances it.
*
* This has the benefit that request locality causes faster lookups as
```

```
* the requested nodes move to the top of the tree.  On the other hand,
* every lookup causes memory writes.
*
* The Balance Theorem bounds the total access time for m operations
* and n inserts on an initially empty tree as O((m + n)lg n).  The
* amortized cost for a sequence of m accesses to a splay tree is O(lg n);
*
* A red-black tree is a binary search tree with the node color as an
* extra attribute.  It fulfills a set of conditions:
* - every search path from the root to a leaf consists of the
*   same number of black nodes,
* - each red node (except for the root) has a black parent,
* - each leaf node is black.
*
* Every operation on a red-black tree is bounded as O(lg n).
* The maximum height of a red-black tree is 2lg (n+1).
 */

#define SPLAY_HEAD(name, type)      \
struct name {       \
 struct type *sph_root; /* root of the tree */   \
}

#define SPLAY_INITIALIZER(root)     \
 { NULL }

#define SPLAY_INIT(root) do {      \
 (root)->sph_root = NULL;     \
} while (/*CONSTCOND*/ 0)

#define SPLAY_ENTRY(type)      \
struct {       \
 struct type *spe_left; /* left element */   \
 struct type *spe_right; /* right element */   \
}

#define SPLAY_LEFT(elm, field)  (elm)->field.spe_left
#define SPLAY_RIGHT(elm, field)  (elm)->field.spe_right
#define SPLAY_ROOT(head)  (head)->sph_root
#define SPLAY_EMPTY(head)  (SPLAY_ROOT(head) == NULL)

/* SPLAY_ROTATE_{LEFT,RIGHT} expect that tmp hold SPLAY_{RIGHT,LEFT} */
#define SPLAY_ROTATE_RIGHT(head, tmp, field) do {   \
 SPLAY_LEFT((head)->sph_root, field) = SPLAY_RIGHT(tmp, field); \
 SPLAY_RIGHT(tmp, field) = (head)->sph_root;   \
 (head)->sph_root = tmp;      \
} while (/*CONSTCOND*/ 0)
```

```
#define SPLAY_ROTATE_LEFT(head, tmp, field) do {   \
 SPLAY_RIGHT((head)->sph_root,
 field) = SPLAY_LEFT(tmp, field); \
 SPLAY_LEFT(tmp, field) = (head)->sph_root;   \
 (head)->sph_root = tmp;      \
} while (/*CONSTCOND*/ 0)

#define SPLAY_LINKLEFT(head, tmp, field) do {    \
 SPLAY_LEFT(tmp, field) = (head)->sph_root;   \
 tmp = (head)->sph_root;      \
 (head)->sph_root = SPLAY_LEFT((head)->sph_root, field);  \
} while (/*CONSTCOND*/ 0)

#define SPLAY_LINKRIGHT(head, tmp, field) do {    \
 SPLAY_RIGHT(tmp, field) = (head)->sph_root;   \
 tmp = (head)->sph_root;      \
 (head)->sph_root = SPLAY_RIGHT((head)->sph_root, field); \
} while (/*CONSTCOND*/ 0)

#define SPLAY_ASSEMBLE(head, node, left, right, field) do {  \
 SPLAY_RIGHT(left, field) = SPLAY_LEFT((head)->sph_root, field); \
 SPLAY_LEFT(right, field) = SPLAY_RIGHT((head)->sph_root, field);\
 SPLAY_LEFT((head)->sph_root, field) = SPLAY_RIGHT(node, field); \
 SPLAY_RIGHT((head)->sph_root, field) = SPLAY_LEFT(node, field); \
} while (/*CONSTCOND*/ 0)

/* Generates prototypes and inline functions */

#define
 SPLAY_PROTOTYPE(name, type, field, cmp)    \
void name##_SPLAY(struct name *, struct type *);   \
void name##_SPLAY_MINMAX(struct name *, int);    \
struct type *name##_SPLAY_INSERT(struct name *, struct type *);  \
struct type *name##_SPLAY_REMOVE(struct name *, struct type *);  \
        \
/* Finds the node with the same key as elm */    \
static __inline struct type *      \
name##_SPLAY_FIND(struct name *head, struct type *elm)   \
{        \
 if (SPLAY_EMPTY(head))      \
  return(NULL);      \
 name##_SPLAY(head, elm);     \
 if ((cmp)(elm, (head)->sph_root) == 0)    \
  return (head->sph_root);    \
 return (NULL);       \
}        \
        \
static __inline _sys_tree_h_unused struct type *   \
```

```
name##_SPLAY_NEXT(struct name *head, struct type *elm)   \
{       \
 name##_SPLAY(head, elm);     \
 if (SPLAY_RIGHT(elm, field) != NULL) {    \
  elm = SPLAY_RIGHT(elm, field);    \
  while (SPLAY_LEFT(elm, field) != NULL) {  \
   elm = SPLAY_LEFT(elm, field);   \
  }       \
 }
 else       \
  elm = NULL;      \
 return (elm);       \
}       \
        \
static _sys_tree_h_unused __inline struct type *   \
name##_SPLAY_MIN_MAX(struct name *head, int val)   \
{       \
 name##_SPLAY_MINMAX(head, val);     \
       return (SPLAY_ROOT(head));     \
}

/* Main splay operation.
* Moves node close to the key of elm to top
*/
#define SPLAY_GENERATE(name, type, field, cmp)    \
struct type *       \
name##_SPLAY_INSERT(struct name *head, struct type *elm)  \
{       \
   if (SPLAY_EMPTY(head)) {      \
     SPLAY_LEFT(elm, field) = SPLAY_RIGHT(elm, field) = NULL; \
   } else {       \
     int __comp;       \
     name##_SPLAY(head, elm);     \
     __comp = (cmp)(elm, (head)->sph_root);   \
     if(__comp < 0) {      \
      SPLAY_LEFT(elm, field) = SPLAY_LEFT((head)->sph_root, field);\
      SPLAY_RIGHT(elm, field) = (head)->sph_root;  \
      SPLAY_LEFT((head)->sph_root, field) = NULL;  \
     } else if (__comp > 0) {     \
      SPLAY_RIGHT(elm,
 field) = SPLAY_RIGHT((head)->sph_root, field);\
      SPLAY_LEFT(elm, field) = (head)->sph_root;  \
      SPLAY_RIGHT((head)->sph_root, field) = NULL; \
     } else      \
      return ((head)->sph_root);    \
   }        \
   (head)->sph_root = (elm);      \
   return (NULL);       \
```

```
}       \
        \
struct type *       \
name##_SPLAY_REMOVE(struct name *head, struct type *elm)  \
{       \
 struct type *__tmp;     \
 if (SPLAY_EMPTY(head))     \
  return (NULL);     \
 name##_SPLAY(head, elm);    \
 if ((cmp)(elm, (head)->sph_root) == 0) {   \
  if (SPLAY_LEFT((head)->sph_root, field) == NULL) { \
   (head)->sph_root = SPLAY_RIGHT((head)->sph_root, field);\
  } else {     \
   __tmp = SPLAY_RIGHT((head)->sph_root, field); \
   (head)->sph_root = SPLAY_LEFT((head)->sph_root, field);\
   name##_SPLAY(head, elm);   \
   SPLAY_RIGHT((head)->sph_root, field) = __tmp; \
  }      \
  return (elm);     \
 }       \
 return (NULL);      \
}       \
        \
void        \
name##_SPLAY(struct
 name *head, struct type *elm)   \
{       \
 struct type __node, *__left, *__right, *__tmp;   \
 int __comp;      \
\
 SPLAY_LEFT(&__node, field) = SPLAY_RIGHT(&__node, field) = NULL;\
 __left = __right = &__node;    \
\
 while ((__comp = (cmp)(elm, (head)->sph_root)) != 0) {  \
  if (__comp < 0) {    \
   __tmp = SPLAY_LEFT((head)->sph_root, field); \
   if (__tmp == NULL)    \
    break;    \
   if ((cmp)(elm, __tmp) < 0){   \
    SPLAY_ROTATE_RIGHT(head, __tmp, field); \
    if (SPLAY_LEFT((head)->sph_root, field) == NULL)\
     break;    \
   }     \
   SPLAY_LINKLEFT(head, __right, field);  \
  } else if (__comp > 0) {    \
   __tmp = SPLAY_RIGHT((head)->sph_root, field); \
   if (__tmp == NULL)    \
    break;    \
```

```
  if ((cmp)(elm, __tmp) > 0){   \
   SPLAY_ROTATE_LEFT(head, __tmp, field); \
   if (SPLAY_RIGHT((head)->sph_root, field) == NULL)\
    break;    \
   }      \
   SPLAY_LINKRIGHT(head, __left, field);  \
  }       \
 }       \
 SPLAY_ASSEMBLE(head,
 &__node, __left, __right, field);  \
}        \
       \
/* Splay with either the minimum or the maximum element   \
* Used to find minimum or maximum element in tree.   \
*/        \
void name##_SPLAY_MINMAX(struct name *head, int __comp) \
{        \
 struct type __node, *__left, *__right, *__tmp;   \
\
 SPLAY_LEFT(&__node, field) = SPLAY_RIGHT(&__node, field) = NULL;\
 __left = __right = &__node;     \
\
 while (1) {       \
  if (__comp < 0) {     \
   __tmp = SPLAY_LEFT((head)->sph_root, field); \
   if (__tmp == NULL)    \
    break;     \
   if (__comp < 0){    \
    SPLAY_ROTATE_RIGHT(head, __tmp, field); \
    if (SPLAY_LEFT((head)->sph_root, field) == NULL)\
     break;    \
   }      \
   SPLAY_LINKLEFT(head, __right, field);  \
  } else if (__comp > 0) {    \
   __tmp = SPLAY_RIGHT((head)->sph_root, field); \
   if (__tmp == NULL)    \
    break;     \
   if (__comp > 0) {    \
    SPLAY_ROTATE_LEFT(head, __tmp, field); \
    if (SPLAY_RIGHT((head)->sph_root,
  field) == NULL)\
     break;    \
   }      \
   SPLAY_LINKRIGHT(head, __left, field);  \
  }       \
 }       \
 SPLAY_ASSEMBLE(head, &__node, __left, __right, field);  \
}
```

```
#define SPLAY_NEGINF -1
#define SPLAY_INF 1

#define SPLAY_INSERT(name, x, y) name##_SPLAY_INSERT(x, y)
#define SPLAY_REMOVE(name, x, y) name##_SPLAY_REMOVE(x, y)
#define SPLAY_FIND(name, x, y)  name##_SPLAY_FIND(x, y)
#define SPLAY_NEXT(name, x, y)  name##_SPLAY_NEXT(x, y)
#define SPLAY_MIN(name, x)  (SPLAY_EMPTY(x) ? NULL \
    : name##_SPLAY_MIN_MAX(x, SPLAY_NEGINF))
#define SPLAY_MAX(name, x)  (SPLAY_EMPTY(x) ? NULL \
    : name##_SPLAY_MIN_MAX(x, SPLAY_INF))

#define SPLAY_FOREACH(x, name, head)    \
 for ((x) = SPLAY_MIN(name, head);   \
     (x) != NULL;     \
     (x) = SPLAY_NEXT(name, head, x))

/* Macros that define a red-black tree */
#define RB_HEAD(name, type)     \
struct name {       \
 struct type *rbh_root; /* root of the tree */   \
}

#define RB_INITIALIZER(root)     \
 {
 NULL }

#define RB_INIT(root) do {      \
 (root)->rbh_root = NULL;    \
} while (/*CONSTCOND*/ 0)

#define RB_BLACK 0
#define RB_RED  1
#define RB_ENTRY(type)      \
struct {       \
 struct type *rbe_left;  /* left element */  \
 struct type *rbe_right;  /* right element */  \
 struct type *rbe_parent; /* parent element */  \
 int rbe_color;   /* node color */  \
}

#define RB_LEFT(elm, field)  (elm)->field.rbe_left
#define RB_RIGHT(elm, field)  (elm)->field.rbe_right
#define RB_PARENT(elm, field)  (elm)->field.rbe_parent
#define RB_COLOR(elm, field)  (elm)->field.rbe_color
#define RB_ROOT(head)   (head)->rbh_root
#define RB_EMPTY(head)   (RB_ROOT(head) == NULL)
```

```
#define RB_SET(elm, parent, field) do {     \
 RB_PARENT(elm, field) = parent;     \
 RB_LEFT(elm, field) = RB_RIGHT(elm, field) = NULL;  \
 RB_COLOR(elm, field) = RB_RED;     \
} while (/*CONSTCOND*/ 0)

#define RB_SET_BLACKRED(black, red, field) do {    \
 RB_COLOR(black, field) = RB_BLACK;    \
 RB_COLOR(red, field)
 = RB_RED;     \
} while (/*CONSTCOND*/ 0)

#ifndef RB_AUGMENT
#define RB_AUGMENT(x) do {} while (/*CONSTCOND*/ 0)
#endif

#define RB_ROTATE_LEFT(head, elm, tmp, field) do {   \
 (tmp) = RB_RIGHT(elm, field);     \
 if ((RB_RIGHT(elm, field) = RB_LEFT(tmp, field)) != NULL) { \
  RB_PARENT(RB_LEFT(tmp, field), field) = (elm);  \
 }       \
 RB_AUGMENT(elm);      \
 if ((RB_PARENT(tmp, field) = RB_PARENT(elm, field)) != NULL) { \
  if ((elm) == RB_LEFT(RB_PARENT(elm, field), field)) \
   RB_LEFT(RB_PARENT(elm, field), field) = (tmp); \
  else      \
   RB_RIGHT(RB_PARENT(elm, field), field) = (tmp); \
 } else       \
 (head)->rbh_root = (tmp);    \
 RB_LEFT(tmp, field) = (elm);     \
 RB_PARENT(elm, field) = (tmp);     \
 RB_AUGMENT(tmp);      \
 if ((RB_PARENT(tmp, field)))     \
  RB_AUGMENT(RB_PARENT(tmp, field));   \
} while (/*CONSTCOND*/ 0)

#define RB_ROTATE_RIGHT(head, elm, tmp, field) do {   \
 (tmp) = RB_LEFT(elm, field);     \
 if ((RB_LEFT(elm, field) = RB_RIGHT(tmp, field))
 != NULL) { \
  RB_PARENT(RB_RIGHT(tmp, field), field) = (elm);  \
 }       \
 RB_AUGMENT(elm);      \
 if ((RB_PARENT(tmp, field) = RB_PARENT(elm, field)) != NULL) { \
  if ((elm) == RB_LEFT(RB_PARENT(elm, field), field)) \
   RB_LEFT(RB_PARENT(elm, field), field) = (tmp); \
  else      \
```

```
  RB_RIGHT(RB_PARENT(elm, field), field) = (tmp); \
 } else       \
 (head)->rbh_root = (tmp);    \
 RB_RIGHT(tmp, field) = (elm);     \
 RB_PARENT(elm, field) = (tmp);     \
 RB_AUGMENT(tmp);      \
 if ((RB_PARENT(tmp, field)))     \
  RB_AUGMENT(RB_PARENT(tmp, field));   \
} while (/*CONSTCOND*/ 0)

/* Generates prototypes and inline functions */
#define RB_PROTOTYPE(name, type, field, cmp)    \
 RB_PROTOTYPE_INTERNAL(name, type, field, cmp,)
#define RB_PROTOTYPE_STATIC(name, type, field, cmp)   \
 RB_PROTOTYPE_INTERNAL(name, type, field, cmp, _sys_tree_h_unused static)
#define RB_PROTOTYPE_INTERNAL(name, type, field, cmp, attr)  \
attr void name##_RB_INSERT_COLOR(struct name *, struct
 type *);  \
attr void name##_RB_REMOVE_COLOR(struct name *, struct type *, struct type *);\
attr struct type *name##_RB_REMOVE(struct name *, struct type *); \
attr struct type *name##_RB_INSERT(struct name *, struct type *); \
attr struct type *name##_RB_FIND(struct name *, struct type *);  \
attr struct type *name##_RB_NFIND(struct name *, struct type *); \
attr struct type *name##_RB_NEXT(struct type *);   \
attr struct type *name##_RB_PREV(struct type *);   \
attr struct type *name##_RB_MINMAX(struct name *, int);   \
        \

/* Main rb operation.
* Moves node close to the key of elm to top
*/
#define RB_GENERATE(name, type, field, cmp)    \
 RB_GENERATE_INTERNAL(name, type, field, cmp,)
#define RB_GENERATE_STATIC(name, type, field, cmp)   \
 RB_GENERATE_INTERNAL(name, type, field, cmp, _sys_tree_h_unused static)
#define RB_GENERATE_INTERNAL(name, type, field, cmp, attr)  \
attr void       \
name##_RB_INSERT_COLOR(struct name *head, struct type *elm)  \
{        \
 struct type
 *parent, *gparent, *tmp;    \
 while ((parent = RB_PARENT(elm, field)) != NULL &&  \
     RB_COLOR(parent, field) == RB_RED) {   \
  gparent = RB_PARENT(parent, field);   \
  if (parent == RB_LEFT(gparent, field)) {  \
   tmp = RB_RIGHT(gparent, field);   \
   if (tmp && RB_COLOR(tmp, field) == RB_RED) { \
    RB_COLOR(tmp, field) = RB_BLACK; \
```

```
   RB_SET_BLACKRED(parent, gparent, field);\
   elm = gparent;    \
   continue;    \
  }      \
  if (RB_RIGHT(parent, field) == elm) {  \
   RB_ROTATE_LEFT(head, parent, tmp, field);\
   tmp = parent;    \
   parent = elm;    \
   elm = tmp;    \
  }      \
  RB_SET_BLACKRED(parent, gparent, field); \
  RB_ROTATE_RIGHT(head, gparent, tmp, field); \
 } else {      \
  tmp = RB_LEFT(gparent, field);   \
  if (tmp && RB_COLOR(tmp, field) == RB_RED) { \
   RB_COLOR(tmp, field) = RB_BLACK; \
   RB_SET_BLACKRED(parent, gparent, field);\
   elm = gparent;    \
   continue;    \
  }      \
  if (RB_LEFT(parent, field) == elm)
 {  \
   RB_ROTATE_RIGHT(head, parent, tmp, field);\
   tmp = parent;    \
   parent = elm;    \
   elm = tmp;    \
  }      \
  RB_SET_BLACKRED(parent, gparent, field); \
  RB_ROTATE_LEFT(head, gparent, tmp, field); \
 }       \
 }       \
 RB_COLOR(head->rbh_root, field) = RB_BLACK;   \
}        \
        \
attr void        \
name##_RB_REMOVE_COLOR(struct name *head, struct type *parent, struct type *elm) \
{        \
 struct type *tmp;      \
 while ((elm == NULL || RB_COLOR(elm, field) == RB_BLACK) && \
     elm != RB_ROOT(head)) {     \
  if (RB_LEFT(parent, field) == elm) {   \
   tmp = RB_RIGHT(parent, field);   \
   if (RB_COLOR(tmp, field) == RB_RED) {  \
    RB_SET_BLACKRED(tmp, parent, field); \
    RB_ROTATE_LEFT(head, parent, tmp, field);\
    tmp = RB_RIGHT(parent, field);  \
   }      \
   if ((RB_LEFT(tmp, field) == NULL ||  \
```

```
      RB_COLOR(RB_LEFT(tmp, field), field) == RB_BLACK) &&\
      (RB_RIGHT(tmp, field) == NULL ||  \
      RB_COLOR(RB_RIGHT(tmp,
field), field) == RB_BLACK)) {\
   RB_COLOR(tmp, field) = RB_RED;  \
   elm = parent;    \
   parent = RB_PARENT(elm, field);  \
  } else {     \
   if (RB_RIGHT(tmp, field) == NULL || \
       RB_COLOR(RB_RIGHT(tmp, field), field) == RB_BLACK) {\
    struct type *oleft;  \
    if ((oleft = RB_LEFT(tmp, field)) \
        != NULL)   \
     RB_COLOR(oleft, field) = RB_BLACK;\
    RB_COLOR(tmp, field) = RB_RED; \
    RB_ROTATE_RIGHT(head, tmp, oleft, field);\
    tmp = RB_RIGHT(parent, field); \
   }     \
   RB_COLOR(tmp, field) = RB_COLOR(parent, field);\
   RB_COLOR(parent, field) = RB_BLACK; \
   if (RB_RIGHT(tmp, field))  \
    RB_COLOR(RB_RIGHT(tmp, field), field) = RB_BLACK;\
   RB_ROTATE_LEFT(head, parent, tmp, field);\
   elm = RB_ROOT(head);   \
   break;     \
  }      \
 } else {      \
  tmp = RB_LEFT(parent, field);   \
  if (RB_COLOR(tmp, field) == RB_RED) {  \
   RB_SET_BLACKRED(tmp, parent, field); \
   RB_ROTATE_RIGHT(head, parent, tmp, field);\
   tmp
= RB_LEFT(parent, field);  \
  }      \
  if ((RB_LEFT(tmp, field) == NULL ||  \
      RB_COLOR(RB_LEFT(tmp, field), field) == RB_BLACK) &&\
      (RB_RIGHT(tmp, field) == NULL ||  \
      RB_COLOR(RB_RIGHT(tmp, field), field) == RB_BLACK)) {\
   RB_COLOR(tmp, field) = RB_RED;  \
   elm = parent;    \
   parent = RB_PARENT(elm, field);  \
  } else {     \
   if (RB_LEFT(tmp, field) == NULL || \
       RB_COLOR(RB_LEFT(tmp, field), field) == RB_BLACK) {\
    struct type *oright;  \
    if ((oright = RB_RIGHT(tmp, field)) \
        != NULL)   \
     RB_COLOR(oright, field) = RB_BLACK;\
```

```
    RB_COLOR(tmp, field) = RB_RED; \
    RB_ROTATE_LEFT(head, tmp, oright, field);\
    tmp = RB_LEFT(parent, field); \
   }    \
   RB_COLOR(tmp, field) = RB_COLOR(parent, field);\
   RB_COLOR(parent, field) = RB_BLACK; \
   if (RB_LEFT(tmp, field))  \
    RB_COLOR(RB_LEFT(tmp, field), field) = RB_BLACK;\
   RB_ROTATE_RIGHT(head, parent, tmp, field);\
   elm = RB_ROOT(head);   \
   break;    \
  }     \
 }      \
}       \
if
(elm)      \
 RB_COLOR(elm, field) = RB_BLACK;   \
}       \
       \
attr struct type *      \
name##_RB_REMOVE(struct name *head, struct type *elm)   \
{       \
 struct type *child, *parent, *old = elm;   \
 int color;      \
 if (RB_LEFT(elm, field) == NULL)    \
  child = RB_RIGHT(elm, field);    \
 else if (RB_RIGHT(elm, field) == NULL)    \
  child = RB_LEFT(elm, field);    \
 else {       \
  struct type *left;     \
  elm = RB_RIGHT(elm, field);    \
  while ((left = RB_LEFT(elm, field)) != NULL)  \
   elm = left;     \
  child = RB_RIGHT(elm, field);    \
  parent = RB_PARENT(elm, field);    \
  color = RB_COLOR(elm, field);    \
  if (child)     \
   RB_PARENT(child, field) = parent;  \
  if (parent) {     \
   if (RB_LEFT(parent, field) == elm)  \
    RB_LEFT(parent, field) = child;  \
   else     \
    RB_RIGHT(parent, field) = child; \
   RB_AUGMENT(parent);    \
  } else      \
   RB_ROOT(head)
 = child;    \
  if (RB_PARENT(elm, field) == old)   \
```

```
  parent = elm;     \
 (elm)->field = (old)->field;    \
 if (RB_PARENT(old, field)) {    \
  if (RB_LEFT(RB_PARENT(old, field), field) == old)\
   RB_LEFT(RB_PARENT(old, field), field) = elm;\
  else      \
   RB_RIGHT(RB_PARENT(old, field), field) = elm;\
  RB_AUGMENT(RB_PARENT(old, field));  \
 } else       \
  RB_ROOT(head) = elm;    \
 RB_PARENT(RB_LEFT(old, field), field) = elm;  \
 if (RB_RIGHT(old, field))    \
  RB_PARENT(RB_RIGHT(old, field), field) = elm; \
 if (parent) {      \
  left = parent;     \
  do {      \
   RB_AUGMENT(left);   \
  } while ((left = RB_PARENT(left, field)) != NULL); \
 }       \
 goto color;      \
}        \
 parent = RB_PARENT(elm, field);     \
 color = RB_COLOR(elm, field);     \
 if (child)       \
  RB_PARENT(child, field) = parent;   \
 if (parent) {       \
  if (RB_LEFT(parent, field) == elm)   \
   RB_LEFT(parent, field) = child;   \
  else       \
   RB_RIGHT(parent,
 field) = child;  \
  RB_AUGMENT(parent);     \
 } else        \
  RB_ROOT(head) = child;     \
color:         \
 if (color == RB_BLACK)      \
  name##_RB_REMOVE_COLOR(head, parent, child);  \
 return (old);       \
}         \
        \
/* Inserts a node into the RB tree */     \
attr struct type *       \
name##_RB_INSERT(struct name *head, struct type *elm)   \
{         \
 struct type *tmp;      \
 struct type *parent = NULL;     \
 int comp = 0;       \
 tmp = RB_ROOT(head);      \
```

```
 while (tmp) {       \
  parent = tmp;      \
  comp = (cmp)(elm, parent);    \
  if (comp < 0)      \
   tmp = RB_LEFT(tmp, field);   \
  else if (comp > 0)     \
   tmp = RB_RIGHT(tmp, field);   \
  else       \
   return (tmp);     \
 }        \
 RB_SET(elm, parent, field);     \
 if (parent != NULL) {      \
  if (comp < 0)      \
   RB_LEFT(parent, field) = elm;   \
  else       \
   RB_RIGHT(parent, field) = elm;   \
  RB_AUGMENT(parent);     \
 } else       \
  RB_ROOT(head) = elm;     \
 name##_RB_INSERT_COLOR(head,
 elm);    \
 return (NULL);       \
}        \
        \
/* Finds the node with the same key as elm */    \
attr struct type *       \
name##_RB_FIND(struct name *head, struct type *elm)   \
{        \
 struct type *tmp = RB_ROOT(head);    \
 int comp;       \
 while (tmp) {       \
  comp = cmp(elm, tmp);     \
  if (comp < 0)      \
   tmp = RB_LEFT(tmp, field);   \
  else if (comp > 0)     \
   tmp = RB_RIGHT(tmp, field);   \
  else       \
   return (tmp);     \
 }        \
 return (NULL);       \
}        \
        \
/* Finds the first node greater than or equal to the search key */ \
attr struct type *       \
name##_RB_NFIND(struct name *head, struct type *elm)   \
{        \
 struct type *tmp = RB_ROOT(head);    \
 struct type *res = NULL;     \
```

```
 int comp;       \
 while (tmp) {       \
  comp = cmp(elm, tmp);     \
  if (comp < 0) {      \
   res = tmp;     \
   tmp = RB_LEFT(tmp, field);   \
  }       \
  else if (comp > 0)     \
   tmp =
 RB_RIGHT(tmp, field);   \
  else       \
   return (tmp);     \
 }       \
 return (res);       \
}        \
        \
/* ARGSUSED */       \
attr struct type *       \
name##_RB_NEXT(struct type *elm)     \
{        \
 if (RB_RIGHT(elm, field)) {     \
  elm = RB_RIGHT(elm, field);    \
  while (RB_LEFT(elm, field))    \
   elm = RB_LEFT(elm, field);   \
 } else {       \
  if (RB_PARENT(elm, field) &&    \
      (elm == RB_LEFT(RB_PARENT(elm, field), field))) \
   elm = RB_PARENT(elm, field);   \
  else {       \
   while (RB_PARENT(elm, field) &&   \
       (elm == RB_RIGHT(RB_PARENT(elm, field), field)))\
    elm = RB_PARENT(elm, field);  \
   elm = RB_PARENT(elm, field);   \
  }       \
 }       \
 return (elm);       \
}        \
        \
/* ARGSUSED */       \
attr struct type *       \
name##_RB_PREV(struct type *elm)     \
{        \
 if (RB_LEFT(elm, field)) {     \
  elm = RB_LEFT(elm, field);    \
  while (RB_RIGHT(elm, field))    \
   elm = RB_RIGHT(elm, field);   \
 }
```

```
 else {       \
  if (RB_PARENT(elm, field) &&    \
      (elm == RB_RIGHT(RB_PARENT(elm, field), field))) \
   elm = RB_PARENT(elm, field);   \
  else {       \
   while (RB_PARENT(elm, field) &&   \
       (elm == RB_LEFT(RB_PARENT(elm, field), field)))\
    elm = RB_PARENT(elm, field);  \
   elm = RB_PARENT(elm, field);   \
  }       \
 }       \
 return (elm);       \
}        \
        \
attr struct type *       \
name##_RB_MINMAX(struct name *head, int val)    \
{        \
 struct type *tmp = RB_ROOT(head);    \
 struct type *parent = NULL;     \
 while (tmp) {       \
  parent = tmp;      \
  if (val < 0)      \
   tmp = RB_LEFT(tmp, field);   \
  else       \
   tmp = RB_RIGHT(tmp, field);   \
 }       \
 return (parent);      \
}

#define RB_NEGINF -1
#define RB_INF 1

#define RB_INSERT(name, x, y) name##_RB_INSERT(x, y)
#define RB_REMOVE(name, x, y) name##_RB_REMOVE(x, y)
#define RB_FIND(name, x, y) name##_RB_FIND(x, y)
#define RB_NFIND(name, x, y) name##_RB_NFIND(x,
 y)
#define RB_NEXT(name, x, y) name##_RB_NEXT(y)
#define RB_PREV(name, x, y) name##_RB_PREV(y)
#define RB_MIN(name, x)  name##_RB_MINMAX(x, RB_NEGINF)
#define RB_MAX(name, x)  name##_RB_MINMAX(x, RB_INF)

#define RB_FOREACH(x, name, head)     \
 for ((x) = RB_MIN(name, head);     \
      (x) != NULL;      \
      (x) = name##_RB_NEXT(x))

#define RB_FOREACH_FROM(x, name, y)     \
```

```
 for ((x) = (y);       \
     ((x) != NULL) && ((y) = name##_RB_NEXT(x), (x) != NULL); \
      (x) = (y))

#define RB_FOREACH_SAFE(x, name, head, y)    \
 for ((x) = RB_MIN(name, head);     \
     ((x) != NULL) && ((y) = name##_RB_NEXT(x), (x) != NULL); \
      (x) = (y))

#define RB_FOREACH_REVERSE(x, name, head)    \
 for ((x) = RB_MAX(name, head);     \
      (x) != NULL;      \
      (x) = name##_RB_PREV(x))

#define RB_FOREACH_REVERSE_FROM(x, name, y)    \
 for ((x) = (y);       \
     ((x) != NULL) && ((y) = name##_RB_PREV(x), (x) != NULL); \
      (x) = (y))

#define RB_FOREACH_REVERSE_SAFE(x, name,
 head, y)   \
 for ((x) = RB_MAX(name, head);     \
     ((x) != NULL) && ((y) = name##_RB_PREV(x), (x) != NULL); \
      (x) = (y))

#endif /* _SYS_TREE_H_ */
# Contributor: Dhruvin Gandhi <contact@dhru.vin>
# Maintainer: Patrycja Rosa <alpine@ptrcnull.me>
pkgname=py3-license-expression
_pkgname=license_expression
pkgver=30.4.0
pkgrel=0
pkgdesc="Library to parse, compare, simplify and normalize license expressions"
url="https://github.com/nexB/license-expression"
arch="noarch"
license="Apache-2.0"
depends="python3 py3-boolean.py"
makedepends="py3-setuptools py3-setuptools_scm py3-gpep517 py3-wheel"
checkdepends="py3-pytest py3-pytest-xdist"
subpackages="$pkgname-pyc"
source="https://files.pythonhosted.org/packages/source/l/$_pkgname/$_pkgname-$pkgver.tar.gz"
builddir="$srcdir/$_pkgname-$pkgver"

build() {
 gpep517 build-wheel \
  --wheel-dir .dist \
  --output-fd 3 3>&1 >&2
}
```

```
check() {
 python3 -m venv --clear --without-pip --system-site-packages .testenv
 .testenv/bin/python3 -m installer .dist/*.whl
 .testenv/bin/python3 -m pytest
}

package() {
 python3 -m installer -d "$pkgdir" \
  .dist/*.whl
}

sha512sums="
cc7cd6b5bd8ea4c99b66f074871ffd7cc78b3e8b1b0d3afd9b95efdb7147c8293db2fac977d684fc34d3d60bd79066a06
dc2bff0a38b130d9d83c63538502db1
  license_expression-30.4.0.tar.gz
"
```

1.119 x-sys 0.34.0

1.119.1 Available under license :

Copyright 2009 The Go Authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE
 FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.120 aws-sdk-go-v2 1.37.2

1.120.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

```
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string
```

```
// Unique, case-sensitive identifier that you provide to ensure the idempotency of
// the request.
//
//
This member is required.
ClientToken *string

// Configuration for consumption of the license. Choose a provisional
// configuration for workloads running with continuous connectivity. Choose a
// borrow configuration for workloads with offline usage.
//
// This member is required.
ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
```

```
 Validity *types.DatetimeRange

 // Information about
 the license.
 LicenseMetadata []types.Metadata

 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }
```

```
if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
```

```
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
```

```
        with:
          path: sdkbase
          ref: ${{ github.base_ref }}
      - name: Checkout this ref
        uses: actions/checkout@v2
        with:
          path: new-ref
          fetch-depth: 0
      - name: Get Diff
        run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
      - name: Get Target Files
        run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
      - name: Checkout scancode
        uses: actions/checkout@v2
        with:
          repository: nexB/scancode-toolkit
          path: scancode-toolkit
          fetch-depth: 1
      - name: Set up Python ${{ matrix.python-version }}
         uses: actions/setup-python@v2
        with:
          python-version: ${{ matrix.python-version }}
      # ScanCode
      - name: Self-configure scancode
        working-directory: ./scancode-toolkit
        run: ./scancode --help
      - name: Run Scan code on target
        run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
      - name: Run Scan code on pr ref
        run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
      # compare
      - name: License test
        run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
```

setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger

spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
```

```
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
```

```
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
```

```
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
```

```
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata
```

```
 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
```

```
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
```

```
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
```

```
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
```

```
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
```

```
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
```

```
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options);
err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
```

```
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
```

```
 return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
```

```
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string
```

```
 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
```

```
 return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.

```
{
  "smithy": "2.0",
  "shapes": {
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
        "type": "integer"
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/DeregisterSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
            "smithy.api#required": {}
          }
```

```
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of name to filter by.</p>"
                }
            },
            "Values": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
                }
            },
            "Operator": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
                "traits": {
                    "smithy.api#documentation": "<p>An operator for filtering results.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
```

```
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

       "traits": {
            "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
          }
        },
        "SubscriptionProviderStatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
          }
        },
        "LastSuccessfulDataRetrievalTime": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
          }
        }
      },
```

```
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
```

```
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }
            },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                 "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
            "AmiId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
                }
            },
            "InstanceID": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
                }
            },
            "InstanceType": {
                "target": "smithy.api#String",
```

```
            "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
        },
        "AccountID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
        "Region": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
        },
        "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
        },
        "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
        },
        "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
        },
```

```
            "SubscriptionName": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
               }
            },
            "OsVersion": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
               }
            },
            "SubscriptionProviderCreateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
               }
            },
            "SubscriptionProviderUpdateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
               }
            },
            "DualSubscription": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
               }
            },
            "RegisteredWithSubscriptionProvider": {
               "target": "smithy.api#String",
               "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
         }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>An exception occurred with the service.</p>",
        "smithy.api#error": "server"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
      "type": "service",
      "version": "2018-05-10",
      "operations": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
         },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
          }
        ],
        "traits": {
          "aws.api#service": {
            "sdkId": "License Manager Linux Subscriptions",
             "arnNamespace": "license-manager-linux-subscriptions",
            "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
          },
          "aws.auth#sigv4": {
            "name": "license-manager-linux-subscriptions"
          },
          "aws.protocols#restJson1": {},
          "smithy.api#cors": {
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id"
            ],
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager,
    you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager Linux Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region": {
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
```

```
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                 "type": "Boolean"
            },
            "UseFIPS": {
                "builtIn": "AWS::UseFIPS",
                "required": true,
                "default": false,
                "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                "type": "Boolean"
            },
            "Endpoint": {
                "builtIn": "SDK::Endpoint",
                "required": false,
                "documentation": "Override the endpoint used to send this request",
                "type": "String"
            }
        },
        "rules": [
            {
                "conditions": [
                    {
                      "fn": "isSet",
                      "argv": [
                          {
                            "ref": "Endpoint"
                          }
                      ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                              "fn": "booleanEquals",
                              "argv": [
                                  {
                                     "ref": "UseFIPS"
                                  },
                                  true
                              ]
                            }

    ],
                        "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
```

```
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]

}
                            ],
                            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                            "type": "error"
                        },
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": {
                                    "ref": "Endpoint"
                                },
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"

                }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "isSet",
                                "argv": [
                                    {
```

```
                    "ref": "Region"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

        "fn": "aws.partition",
                    "argv": [
                      {
                        "ref": "Region"
                      }
                    ],
                    "assign": "PartitionResult"
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {

                       "ref": "UseFIPS"
                          },
                          true
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
                      }

    ],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
```

```
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [
                      {
                        "ref": "PartitionResult"

},
                    "supportsFIPS"
                    ]
                  }
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [

                     {
                        "ref": "PartitionResult"
                      },
                      "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [],

    "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],
```

```
                "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {

    "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {

            "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true

                    ]
                    }
                ],
```

```
                "rules": [
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS is enabled
 but this partition does not support FIPS",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseDualStack"
                    },
                    true

    ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
```

```
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [
                      {

                        "ref": "PartitionResult"
                      },
                      "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [],
                "rules": [

    {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],
                "type": "tree"

            }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "DualStack is enabled but this partition does not support DualStack",
              "type": "error"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [],
          "rules": [
```

```
                                    {
                                      "conditions": [],
                                      "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                      },
                                      "type": "endpoint"
                                    }
                                  ],
                                  "type": "tree"
                                }
                              ],
                              "type": "tree"
                            }
                          ],
                          "type": "tree"
                        },
                        {
                          "conditions": [],
                          "error": "Invalid Configuration: Missing Region",
                          "type": "error"
                        }
                      ],
                      "type": "tree"
                    }
                  ]
                },
                "smithy.rules#endpointTests": {
                  "testCases": [
                    {
                      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
                      "expect": {
                        "endpoint": {
                          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

                    }
                        },
                        "params": {
                          "Region": "us-east-1",
                          "UseFIPS": true,
                          "UseDualStack": true
                        }
                      },
                      {
                        "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                        "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {

      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
```

```
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {

    "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
           },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

     "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }

         },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

        "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
```

```
                "Region": "us-iso-east-1",
                "UseFIPS":
false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                 }
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {

          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                }
```

```
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {

      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
```

```
            },
            {
              "documentation": "For custom endpoint with fips disabled and dualstack enabled",
              "expect": {
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
              },
              "params": {

"Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true,
                "Endpoint": "https://example.com"
              }
            },
            {
              "documentation": "Missing region",
              "expect": {
                "error": "Invalid Configuration: Missing Region"
              }
            }
          ],
          "version": "1.0"
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "Enabled",
            "value": "Enabled",
            "documentation": "Enabled LinuxSubscriptionsDiscovery"

     },
          {
            "name": "Disabled",
            "value": "Disabled",
            "documentation": "Disabled LinuxSubscriptionsDiscovery"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "OrganizationIntegration": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
            "traits": {
              "smithy.api#documentation":
"<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },

  {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptionInstances"
          },
          "smithy.api#idempotent": {},
```

```
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n          <li>\n
  <p>\n                <code>AccountID</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
      <code>AmiID</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>DualSubscription</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>InstanceID</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>InstanceType</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>ProductCode</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>Region</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>Status</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>UsageOperation</code>\n              </p>\n          </li>\n        </ul>\n        <p>For each filter, you can use
one of the following <code>Operator</code>
 values to \n  \t\tdefine the behavior of the filter:</p>\n          <ul>\n          <li>\n              <p>\n
<code>contains</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>equals</code>\n              </p>\n          </li>\n          <li>\n              <p>\n
<code>Notequal</code>\n              </p>\n          </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
```

```
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
          "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
              "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
            }
          },
          "NextToken": {

       "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
           {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
```

```
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n  <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n  <li>\n              <p>\n                  <code>Subscription</code>\n              </p>\n          </li>\n      </ul>\n  <p>The
  valid Operators for this filter are:</p>\n          <ul>\n          <li>\n              <p>\n  <code>contains</code>\n              </p>\n          </li>\n          <li>\n              <p>\n  <code>equals</code>\n              </p>\n          </li>\n          <li>\n              <p>\n  <code>Notequal</code>\n              </p>\n          </li>\n      </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
          "type": "structure",
          "members": {
            "Subscriptions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
               "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
          },
          "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "RegisteredSubscriptionProviders"
        }
      }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSources": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
          "traits": {
            "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
          }
        },
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }

  },
        "NextToken": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
          "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
            }
          },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
         }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "EQUAL",
            "value": "Equal",
            "documentation": "Equal operator"
          },
          {
            "name": "NOT_EQUAL",
            "value": "NotEqual",
            "documentation": "Not equal operator"
          },
          {
            "name": "CONTAINS",
            "value": "Contains",
            "documentation": "Contains operator"
          }
        ],
        "smithy.api#length": {
          "min": 1,
          "max": 20
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "Enabled",
            "value": "Enabled",
            "documentation": "Enabled OrganizationIntegration"
          },
          {
            "name": "Disabled",
            "value": "Disabled",
            "documentation": "Disabled OrganizationIntegration"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
```

```
Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
                "traits": {
                    "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
                }
            },
            "SubscriptionProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
```

```
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
                "traits": {
                    "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
                }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed
third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and
license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider,
License Manager can get subscription data from the registered provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "InProgress",
                "value": "InProgress",
                "documentation": "InProgress status"
              },
              {
                "name": "Completed",
                "value": "Completed",
                "documentation": "Completed status"
              },
              {
                "name": "Successful",
```

```
                "value": "Successful",
                "documentation": "Successful status"
              },
              {
                "name": "Failed",
                "value": "Failed",
                "documentation": "Failed status"
              }
            ]
          }
        },

        "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
            }
          },
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            },
            "smithy.api#uniqueItems": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
          "type": "map",
          "key": {
            "target": "smithy.api#String"
          },
          "value": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
          "type": "structure",
          "members": {
            "Name":
{
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the subscription.</p>"
```

```
            }
          },
          "Type": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
            }
          },
          "InstanceCount": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
            "traits": {
              "smithy.api#documentation": "<p>The total amount of running instances using this
 subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [

 {
              "name": "RedHat",
              "value": "RedHat",
              "documentation": "RedHat subscription provider namespace"
            }
          ]
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "ACTIVE",
            "value": "ACTIVE",
            "documentation": "ACTIVE status"
          },
          {
            "name": "INVALID",
            "value": "INVALID",

"documentation": "INVALID status"
          },
          {
            "name": "PENDING",
            "value": "PENDING",
            "documentation": "PENDING status"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
        "type": "structure",
        "members":
{
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
```

```
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
             "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tagKeys": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
                "traits": {

              "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                    "smithy.api#httpQuery": "tagKeys",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
```

```
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

    },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
```

```
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
                }

        },
            "HomeRegions": {
```

```
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }
```

```
 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
```

```
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
```

```
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
```

```
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
```

```
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
```

```
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
```

```
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string
```

```
 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
```

```
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
```

```
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
```

spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR

A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP \n\t\t\taddresses, and the credential provider for user administration.</p>"
          }
        },
        "ActiveDirectoryType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
          "traits": {
            "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
          }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
            },
            "DomainIpv4List": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 2
                    }
                }
            },
            "DomainCredentialsProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
            },
            "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "SELF_MANAGED",
                    "value": "SELF_MANAGED",
                    "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                    "name": "AWS_MANAGED",
                    "value": "AWS_MANAGED",
                    "documentation": "AWS_MANAGED type of Active Directory"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n        <note>\n          <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
          "smithy.api#http":
{
            "code": 200,
            "method": "POST",
            "uri": "/user/AssociateUser"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current
```

```
state of the\n\t\t\tresource.</p>",
            "smithy.api#error": "server"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
```

```
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
              "smithy.api#required": {}
            }
          },
          "LicenseServerSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
          "SecretsManagerCredentialsProvider":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
```

```
resource that was deleted.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
 {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
```

```
    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/DisassociateUser"
        },
```

```
            "smithy.api#idempotent": {}

        }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
            "type": "structure",
            "members": {
                "Username": {
                    "target": "smithy.api#String",
                    "traits": {
                        "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                    }
                },
                "InstanceId": {
                    "target": "smithy.api#String",
                    "traits": {
                        "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                    }
                },
                "IdentityProvider": {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                    "traits": {
                        "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                    }
                },
                "InstanceUserArn": {
                    "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                    "traits": {
                        "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                    }
                },
                "Domain": {
                    "target": "smithy.api#String",
                    "traits": {
                        "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
                    }
                }
            },
            "traits": {
                "smithy.api#input": {}
            }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
```

```
        "type": "structure",
        "members": {
          "InstanceUserSummary":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
              "smithy.api#length": {
                "min": 1
              },

    "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Attribute": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
```

```
            }
          },
          "Value": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>Value of the filter.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
          "ActiveDirectoryIdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
             "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
              "smithy.api#required": {}
            }
          },
```

```
        "Settings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
            "smithy.api#required": {}
          }
        },
        "Product": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of the identity provider.</p>",
            "smithy.api#required": {}
          }
        },
        "IdentityProviderArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
          }
        },
        "FailureMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes an identity provider.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
      "type": "list",
      "member": {

        "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
      "type": "structure",
      "members": {
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
            "smithy.api#required": {}
          }
        },
        "Products": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
           "traits": {
            "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
            "smithy.api#required": {}
          }
        },
        "LastStatusCheckDate": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The date of the last status check.</p>"
          }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
      "type": "structure",
      "members": {
        "Username": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
            "smithy.api#required": {}
          }
        },
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },

    "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
          "traits": {
            "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
            "smithy.api#required": {}
          }
        },
        "Status": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
            "smithy.api#required": {}
          }
        },
        "InstanceUserArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
           }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
          }
        },
```

```
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
             "smithy.api#error": "server",
            "smithy.api#httpError": 500
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
```

```
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
      },
```

```
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",

       "x-api-key",
            "authorization",
            "x-amz-date",
            "x-amz-security-token",
            "Access-Control-Allow-Headers",
            "Access-Control-Allow-Methods",
            "Access-Control-Allow-Origin"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
```

```
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region":
{
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
              "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
```

```
                }
            ]
        }
    ],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseFIPS"
                        },
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [
                {

                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": {
                    "ref": "Endpoint"
                },

"properties": {},
                "headers": {}
            },
            "type": "endpoint"
        }
```

```
      ],
      "type": "tree"
    },
    {
      "conditions": [
        {
          "fn": "isSet",
          "argv": [
            {
              "ref": "Region"
            }
          ]
        }
      ],
      "rules": [
        {
          "conditions": [
            {
              "fn": "aws.partition",

              "argv": [
                {
                  "ref": "Region"
                }
              ],
              "assign": "PartitionResult"
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },

true
                  ]
                },
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseDualStack"
                    },
                    true
```

```
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

 "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      }
                    ]
                  },

                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }

            ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
```

```
                    },
                    "type": "endpoint"
                }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [

  {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [

{
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true
                        ]
                    }
```

```
                ],
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {

            "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS is enabled but this partition does not support FIPS",
                "type": "error"

}
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
                    ]
                }
            ],
            "rules": [
                {

    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                true,
                                {
                                    "fn": "getAttr",
                                    "argv": [
                                        {
```

```
                                        "ref": "PartitionResult"
                                    },
                                    "supportsDualStack"
                                ]

        }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }

                    ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "endpoint": {
                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

            "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
    }
],
"type": "tree"
```

```
            },
            {
              "conditions": [],
              "error": "Invalid Configuration: Missing Region",
              "type": "error"
            }
          ]
        },
        "smithy.rules#endpointTests": {
          "testCases": [
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
              "expect":
{
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
```

```
            "endpoint":
{
                "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
        },
        "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
        }
    },
    {
        "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
        },
        "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
        "expect": {
            "endpoint":
{
                "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
```

```
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": false

    }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
              }
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
              "Region": "us-isob-east-1",

"UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
              }
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
            "expect": {

           "endpoint": {
                "url": "https://example.com"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false,
              "Endpoint": "https://example.com"
            }
```

```
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "Missing region",
      "expect": {
        "error": "Invalid Configuration: Missing Region"
      }
    }
  ],
```

```
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
        "type": "structure",
        "members": {
          "ProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
             "traits": {
               "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
            }
          },
          "HealthStatus": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
            "traits": {
              "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
            }
          },
          "Ipv4Address": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
            }
          },
          "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of license server.</p>"
```

```
            }
          },
          "ServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network \n\t\t\taddress of the RDS license server endpoint.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
          },
          "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
              "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
          },
          "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
              "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },
```

```
            "CreationTime": {
                "target": "smithy.api#Timestamp",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "PROVISIONING",
                    "value": "PROVISIONING",
                    "documentation": ""
                },
                {
                    "name": "PROVISIONING_FAILED",
                    "value": "PROVISIONING_FAILED",
                    "documentation": ""
                },
                {
                    "name": "PROVISIONED",
                    "value": "PROVISIONED",
                    "documentation": ""
                },
                {
                    "name": "DELETING",
                    "value": "DELETING",
                    "documentation": ""
                },
                {
```

```
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
    "type": "string",
    "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
    }
},
 "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
    "type": "structure",
    "members": {
        "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>",
```

```
                "smithy.api#required": {}
              }
            },
            "ServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
```

```
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/ListIdentityProviders"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
```

```
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
         "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
    {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
```

```
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
            "InstanceSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/ListLicenseServerEndpoints"
            },

        "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
```

```
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
         "type": "structure",
         "members": {
            "LicenseServerEndpoints": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
                "traits": {
                  "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
         "type":
 "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
 {
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
```

```
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n          <p>Status</p>\n          </li>\n          <li>\n          <p>Username</p>\n
</li>\n          <li>\n          <p>Domain</p>\n          </li>\n          </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

```
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
    }
      }
    },
    "traits": {
      "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
    "type": "structure",
    "members": {
      "Tags": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
        "traits": {
          "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
        }
      }
    },
    "traits": {
      "smithy.api#output": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
```

```
      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummaries": {

             "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
         "type": "structure",
         "members": {
            "Username":
{
               "target": "smithy.api#String",
               "traits": {
```

```
                "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
                "smithy.api#required": {}
            }
        },
        "Product": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                "smithy.api#required": {}
            }
        },
        "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a product for this user.</p>",
                "smithy.api#required": {}
            }
        },
        "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {

        "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "SubscriptionStartDate": {
            "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/RegisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
 {
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
```

```
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

       "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
```

```
        "members": {
          "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
        "type": "union",
        "members": {
          "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
             "traits": {
              "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

  "target": "smithy.api#String"
            }
        },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
            "smithy.api#length": {
              "min": 1
            },
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
            "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n          </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
            }

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
```

```
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {

 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                "smithy.api#required": {}
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
              }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/StopProductSubscription"
        }
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
      "type": "structure",
      "members": {
        "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
            }
          },
          "IdentityProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
```

```
                "smithy.api#required": {}
            }

    }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
"<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
```

```
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
```

```
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

          }
            },
            "TagKeys": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
              "traits": {
                "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                "smithy.api#httpQuery": "tagKeys",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
```

```
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
            "smithy.api#http": {

      "code": 200,
                "method": "POST",
                "uri": "/identity-provider/UpdateIdentityProviderSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
```

```
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
               }
            },
            "UpdateSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
               "traits": {
                  "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n            <li>\n               <p>Subnets which you want to add to provision VPC endpoints.</p>\n            </li>\n
      <li>\n               <p>Subnets which you want to remove the VPC endpoints from.</p>\n            </li>\n
<li>\n               <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n            </li>\n         </ul>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
         "type": "structure",
         "members": {
            "IdentityProviderSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
               "traits": {
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
         "type": "structure",
         "members": {
            "AddSubnets": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
```

```
                "smithy.api#required": {}
              }
            },
            "RemoveSubnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
                "smithy.api#required": {}
              }
            },
            "SecurityGroupId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
              "traits": {
                "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
          }
        }
      }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
```

```
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
```

```
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
 nil {
  return err
```

```
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of,

the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this
License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You

meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate

comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop

Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.121 iputils-tracepath 20240905-r0

1.121.1 Available under license :

arping: GPL-2.0-or-later
clockdiff: BSD-3-Clause
ping: BSD-3-Clause
tracepath: GPL-2.0-or-later

Files containing license texts are available in Documentation directory.
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.
Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their

rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in
the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program
is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program).
Whether that is true depends on what the
Program does.

1. You may copy and distribute verbatim copies of the Program's
source code as you receive it, in any medium, provided that you
conspicuously and appropriately publish on each copy an appropriate
copyright notice and disclaimer of warranty; keep intact all the

notices that refer to this License and to the absence of any warranty;
and give any other recipients of the Program a copy of this License
along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion
of it, thus forming a work based on the Program, and copy and
distribute such modifications or work under the terms of Section 1
above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause
any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any
part thereof, to be licensed as a whole at no charge to all third
parties under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a
notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is

void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed

through that system in reliance on consistent application of that
system; it is up to the author/donor to
decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS

TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU
General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

  Gnomovision version 69, Copyright (C) year name of author
  Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute
it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
 is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.122 github.com/aws/aws-sdk-go-v2/feature/ec2/imds 1.18.2

1.122.1 Available under license :

GetLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart

```
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
```

```
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
```

```
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
```

```
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
```

```
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
```

```
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
```

RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop

InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware

```
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
```

```
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string
```

```
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
```

```
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
```

```
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
```

```
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
```

```
//   - ProductSKU
//
//   - Fingerprint
//
//   - Status
Filters
[]types.Filter

// Amazon Resource Names (ARNs) of the licenses.
LicenseArns []string

// Maximum number of results to return in a single call.
MaxResults *int32

// Token for the next set of results.
NextToken *string

noSmithyDocumentSerde
}

type ListLicensesOutput struct {

// License details.
Licenses []types.License

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack,
```

```
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
```

```
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
```

```
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
```

```
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
```

```
 ServiceID:     ServiceID,
 OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}
```

```
type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
```

```
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
```

```
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
```

```
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {
```

```
//
Checkout type.
//
// This member is required.
CheckoutType types.CheckoutType

// Unique, case-sensitive identifier that you provide to ensure the idempotency of
// the request.
//
// This member is required.
ClientToken *string

// License entitlements.
//
// This member is required.
Entitlements []types.EntitlementData

// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string
```

```
// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
```

```
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
```

```
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
```

```
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },

    {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
            }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

        "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
```

```
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
             }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
        },
        "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
      "type": "structure",
      "members": {
        "AmiId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
        },
        "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
        },
        "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
        },
        "AccountID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
```

```
            "Region": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
               }
            },
            "UsageOperation": {
               "target": "smithy.api#String",

   "traits": {
                  "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
               }
            },
            "ProductCode": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
               "traits": {
                  "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
               }
            },
            "LastUpdatedTime": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
               }
            },
            "SubscriptionName": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
               }
            },
            "OsVersion": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
               }
            },
            "SubscriptionProviderCreateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp when you registered
```

```
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
                }
            },
            "SubscriptionProviderUpdateTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
                }
            },
            "DualSubscription": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
                }
            },
            "RegisteredWithSubscriptionProvider": {
                "target": "smithy.api#String",
                "traits": {

      "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
```

```
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
       },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
      }
    ],
    "traits": {
      "aws.api#service": {
        "sdkId": "License Manager Linux Subscriptions",
         "arnNamespace": "license-manager-linux-subscriptions",
        "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
      },
      "aws.auth#sigv4": {
        "name": "license-manager-linux-subscriptions"
```

```
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
```

```
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }

],
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]
```

```
}
                        ],
                        "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                        "type": "error"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": {
                                "ref": "Endpoint"
                            },
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],
                "type": "tree"

            }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "isSet",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {

            "fn": "aws.partition",
                                    "argv": [
                                        {
                                            "ref": "Region"
                                        }
                                    ],
```

```
                "assign": "PartitionResult"
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {

                    "ref": "UseFIPS"
                            },
                            true
                        ]
                    },
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }

],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

        },
                                    "supportsFIPS"
                                ]
                            }
                        ]
                    },
                    {
                        "fn": "booleanEquals",
```

```
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [

                     {
                          "ref": "PartitionResult"
                       },
                       "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [],

    "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],

            "type": "tree"
                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
```

```
            "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
                    true
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {

          "fn": "booleanEquals",
                      "argv": [
                        {
                          "fn": "getAttr",
                          "argv": [
                            {
                              "ref": "PartitionResult"
                            },
                            "supportsFIPS"
                          ]
                        },
                        true

                    ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "rules": [
                        {
                          "conditions": [],
                          "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                            "headers": {}
                          },
                          "type": "endpoint"
                        }
                      ],
```

```
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS is enabled
but this partition does not support FIPS",
            "type": "error"
        }
    ],
    "type": "tree"
},
{
    "conditions": [
        {
            "fn": "booleanEquals",
            "argv": [
                {
                    "ref": "UseDualStack"
                },
                true

]
        }
    ],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [
                                {

                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }
                    ]
                }
            ],
            "rules": [
```

```
                                        {
                                            "conditions": [],
                                            "rules": [

        {
                                                    "conditions": [],
                                                    "endpoint": {
                                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                        "properties": {},
                                                        "headers": {}
                                                    },
                                                    "type": "endpoint"
                                                }
                                            ],
                                            "type": "tree"

                                }
                                    ],
                                    "type": "tree"
                                },
                                {
                                    "conditions": [],
                                    "error": "DualStack is enabled but this partition does not support DualStack",
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"
                        }
                    ],
                    "type": "tree"
```

```
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
            }
        ],
        "type": "tree"
    }
  ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
```

```
                "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
              }

        },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
```

```
            }

        },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

       "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
```

```
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
       }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "error": "DualStack is enabled but this partition does not support DualStack"
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {

   "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
      }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
    "expect": {
      "endpoint": {
        "url": "https://example.com"
      }
```

```
    },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://example.com"
                  }
                },
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

 "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
```

```
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

        },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

 {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n        <li>\n  <p>\n            <code>AccountID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n    <code>AmiID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>DualSubscription</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceType</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>ProductCode</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Region</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Status</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>UsageOperation</code>\n          </p>\n        </li>\n      </ul>\n      <p>For each filter, you can use one of the following <code>Operator</code>\n values to \n  \t\tdefine the behavior of the filter:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to\n start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
```

```
            "Instances": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
               "traits": {
                  "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
               }
            },
            "NextToken": {

         "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
```

```
            "outputToken": "NextToken",
            "pageSize": "MaxResults",

  "items": "Subscriptions"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n        <p>The valid names for this filter are:</p>\n        <ul>\n
<li>\n            <p>\n              <code>Subscription</code>\n            </p>\n          </li>\n        </ul>\n
<p>The
 valid Operators for this filter are:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
      "type": "structure",
      "members": {
        "Subscriptions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
```

```
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "RegisteredSubscriptionProviders"
            }
         }

      },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
         "type": "structure",
         "members": {
            "SubscriptionProviderSources": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
               "traits": {
                  "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }

    },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
       },
       "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
         "type": "structure",
         "members": {
            "RegisteredSubscriptionProviders": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
```

```
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
          }
        },
        "SubscriptionProviderArn": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
          }
        },
```

```
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
               }
            },
            "SubscriptionProviderStatusMessage": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
               }
            },
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

  }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
                    "documentation": "Failed status"
                }
            ]
        }
    },

   "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
            }
          },
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            },
            "smithy.api#uniqueItems": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
          "type": "map",
          "key": {
            "target": "smithy.api#String"
          },
          "value": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
          "type": "structure",
          "members": {
            "Name":
{
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the subscription.</p>"
              }
            },
            "Type": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
              }
            },
            "InstanceCount": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
              "traits": {
                "smithy.api#documentation": "<p>The total amount of running instances using this
```

```
subscription.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
              ]
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
            }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                  "name": "ACTIVE",
                  "value": "ACTIVE",
                  "documentation": "ACTIVE status"
```

```
            },
            {
               "name": "INVALID",
               "value": "INVALID",

"documentation": "INVALID status"
            },
            {
               "name": "PENDING",
               "value": "PENDING",
               "documentation": "PENDING status"
            }
         ]
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
         "target": "smithy.api#String"
      },
      "traits": {
         "smithy.api#length": {
            "min": 0,
            "max": 50
         },
         "smithy.api#sensitive": {}
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
         }
      ],
      "traits": {
```

```
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
{
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
         "type": "map",
         "key": {
            "target": "smithy.api#String"
         },
```

```
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n integration has been enabled, and which Regions data will be aggregated from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target": "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
                }
            }
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
           "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
          }
        },
        "StatusMessage": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
          "traits": {
            "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
          }

     },
        "HomeRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
```

```
            "traits": {
                "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
```

```
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string
```

```
// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string
```

```
// License status.
Status types.LicenseDeletionStatus

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
        "type": "structure",
        "members": {
            "DirectoryId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
                "traits": {
                    "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
                }
            },
            "ActiveDirectorySettings":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
                }
            },
            "ActiveDirectoryType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
```

```
            },
            "DomainIpv4List": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 2
                  }
               }
            },
            "DomainCredentialsProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
               }
            },
            "DomainNetworkSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
               },
               {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
               }
```

```
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
```

charges in the Amazon Web Services Billing User Guide. \n </note>",
"smithy.api#http":
{
"code": 200,
"method": "POST",
"uri": "/user/AssociateUser"
},
"smithy.api#idempotent": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
"type": "structure",
"members": {
"Username": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The user name from the identity provider. ",
"smithy.api#required": {}
}
},
"InstanceId": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The ID of the EC2 instance that provides the user-based subscription. ",
"smithy.api#required": {}
}
},
"IdentityProvider": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
"traits": {
"smithy.api#documentation": " The identity provider for the user. ",
"smithy.api#required": {}
}
},
"Domain": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The domain name of the Active Directory that contains information for the user to associate. "
}
},
"Tags": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
"traits": {
"smithy.api#documentation": " The tags that apply for the user association. "
}
}

```
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
```

```
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
```

```
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
            "smithy.api#length": {
              "min": 1
            },

  "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Attribute": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
          }
        },
        "Operation": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
          }
        },
        "Value": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>Value of the filter.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
          "ActiveDirectoryIdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
```

```
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
          },
          "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
              }
            },
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

    "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details \n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance user.</p>"
             }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
```

```
            "target": "smithy.api#String",
             "traits": {
               "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
           "smithy.api#error": "server",
          "smithy.api#httpError": 500
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
```

```
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
},
{
```

```
    "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
          ],
          "traits": {
            "aws.api#service": {
              "sdkId": "License Manager User Subscriptions",
              "arnNamespace": "license-manager-user-subscriptions",
              "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
              "name": "license-manager-user-subscriptions"
            },
            "aws.protocols#restJson1": {},
            "smithy.api#cors": {
              "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",

           "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
              ],
              "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
              ]
            },
            "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to
utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager User Subscriptions",
            "smithy.rules#endpointRuleSet": {
              "version": "1.0",
              "parameters": {
                "Region":
{
                  "builtIn": "AWS::Region",
                  "required": false,
                  "documentation": "The AWS region used to dispatch the request.",
```

```
            "type": "String"
        },
        "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
            "type": "Boolean"
        },
        "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
        },
        "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
```

```
                    ]
                }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [
                {

                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": {
                    "ref": "Endpoint"
                },

"properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "isSet",
                "argv": [
                    {
                        "ref": "Region"
                    }
                ]
            }
        ],
```

```
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "aws.partition",

                       "argv": [
                            {
                              "ref": "Region"
                            }
                          ],
                          "assign": "PartitionResult"
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseFIPS"
                              },

true
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              {
                                "ref": "UseDualStack"
                              },
                              true
                            ]
                          }
                        ],
                        "rules": [
                          {
                            "conditions": [
                              {

"fn": "booleanEquals",
                                  "argv": [
                                    true,
                                    {
                                      "fn": "getAttr",
                                      "argv": [
```

```
                                {
                                    "ref": "PartitionResult"
                                },
                                "supportsFIPS"
                            ]
                        }
                    ]
                },

            {
                "fn": "booleanEquals",
                "argv": [
                    true,
                    {
                        "fn": "getAttr",
                        "argv": [
                            {
                                "ref": "PartitionResult"
                            },
                            "supportsDualStack"
                        ]
                    }

        ]
                }
            ],
            "rules": [
                {
                    "conditions": [],
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [

{
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
```

```
                    },
                    {
                      "conditions": [],
                      "error": "FIPS is enabled but this partition does not support FIPS",
                      "type": "error"

}
                  ],
                  "type": "tree"
                },
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseDualStack"
                        },
                        true
                      ]
                    }
                  ],
                  "rules": [
                    {

    "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            true,
                            {
                              "fn": "getAttr",
                              "argv": [
                                {
                                  "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                              ]

     }
                            ]
                          }
                        ],
                        "rules": [
                          {
                            "conditions": [],
                            "endpoint": {
                              "url": "https://license-manager-user-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

                            ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
```

```
{
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",

        "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint":
{
                        "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",
```

```
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
         "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
```

```
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
```

```
      },
      "params": {
        "Region": "us-isob-east-1",

  "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

       "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
```

```
false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                    "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
    }
  }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
  "type": "structure",
  "members": {
    "ProvisioningStatus": {
      "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
       "traits": {
         "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
```

```
\n\t\t\tlicense server.</p>"
                }
            },
            "HealthStatus": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
                }
            },
            "Ipv4Address": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

  "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
        },
        "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
        },
        "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
        },
        "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
        },
        "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
        },

       "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
        }
    },
    "traits": {
      "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
    }
  },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
      "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
      "type": "structure",
      "members": {
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>",
            "smithy.api#required": {}
          }
        },
        "ServerSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
            "smithy.api#required": {}
          }
        }
      },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {

        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/identity-provider/ListIdentityProviders"
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
```

```
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
```

contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria. "
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/ListLicenseServerEndpoints"
            },

          "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
          "type": "structure",
          "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                 "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
```

```
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
             "traits": {
               "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListProductSubscriptions"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "ProductUserSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
 {
        "type": "structure",
        "members": {
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
             "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
```

```
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n          <p>Status</p>\n          </li>\n          <li>\n          <p>Username</p>\n
</li>\n          <li>\n          <p>Domain</p>\n          </li>\n          </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

         }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
```

```
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {

    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
```

```
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
         "type": "structure",
         "members": {
            "IdentityProvider": {

     "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                  "smithy.api#required": {}
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
               "traits":
```

```
{
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",
```

```
    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
            "smithy.api#length": {

             "min": 5,
                "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
            "Endpoint": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
             "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
```

```
                "smithy.api#length": {
                    "min": 1
                },
                "smithy.api#required": {}
            }
        },
        "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
            }

    }
     },
     "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n        <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
```

```
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                  "smithy.api#required": {}
               }

   }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
         "type": "list",
         "member": {
```

```
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
```

```
        "traits": {
            "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
```

```
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

           "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
```

configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the: \n \n \n Subnets which you want to add to provision VPC endpoints. \n \n \n Subnets which you want to remove the VPC endpoints from. \n \n \n Security
group ID which permits traffic to the VPC endpoints. \n \n ",
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
"type": "structure",
"members": {
"IdentityProviderSummary": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
"traits": {
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
"type": "structure",
"members": {
"AddSubnets": {

"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets in which License Manager will create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers. ",
"smithy.api#required": {}
}
},
"RemoveSubnets": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets to remove. ",
"smithy.api#required": {}
}
},
"SecurityGroupId": {
"target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

```
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if
```

```
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
```

Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.123 github.com/aws/aws-sdk-go-v2/service/internal/checksum 1.8.2

1.123.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop

```
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
```

```
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
       uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer
```

```
// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
```

```
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
```

```
 OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
```

InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody

CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

```
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
```

```
//
//   - ProductSKU
//
//   - Status
//
//
  - Fingerprint
//
//   - IssuerName
//
//   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
```

```
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
```

Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (

```
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string
```

```
 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
```

```
 return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
 return err
 }
 if err = addRetry(stack, options); err != nil {
 return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
 err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
```

```
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
```

```
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
```

```
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
```

```
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
```

```
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)
```

```
// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
```

```
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData
```

```
// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
```

```
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
```

```
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
```

```
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
        "type": "integer"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
        "type": "long"
     },
     "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
        "type": "operation",
        "input": {
           "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
        },
        "output": {
           "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
        },
        "errors": [
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
           },
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
           },

     {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
           },
           {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
           }
        ],
        "traits": {
           "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
           "smithy.api#http": {
              "code": 200,
              "method": "POST",
```

```
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
```

```
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

       "traits": {
            "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
          }
        },
        "SecretArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
          }
        },
```

```
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
```

```
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
          "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
          },
          "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
          },
          "AccountID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
          },
          "Region": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
          },
          "UsageOperation": {
            "target": "smithy.api#String",

    "traits": {
              "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
          },
```

```
        "ProductCode": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
          "traits": {
            "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a
href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-
operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
          }
        },
        "LastUpdatedTime": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The time in which the last discovery updated the instance
details.</p>"
          }
        },
        "SubscriptionName": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
          }
        },
        "OsVersion": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
          }
        },
        "SubscriptionProviderCreateTime": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
          }
        },
        "SubscriptionProviderUpdateTime": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
          }
        },
        "DualSubscription": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
          }
```

```
            },
            "RegisteredWithSubscriptionProvider": {
               "target": "smithy.api#String",
               "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
         "type": "service",
         "version": "2018-05-10",
         "operations": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
        }
    ],
    "traits": {
        "aws.api#service": {
            "sdkId": "License Manager Linux Subscriptions",
            "arnNamespace": "license-manager-linux-subscriptions",
            "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
            "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
            "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
```

```
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
                }
              ],
```

```
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            }

        ],
                        "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                        "type": "error"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "ref": "UseDualStack"
                                            },
                                            true
                                        ]

}
                                ],
                                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                                "type": "error"
                            },
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": {
                                        "ref": "Endpoint"
                                    },
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
```

```
            "type": "tree"

        }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "isSet",
                        "argv": [
                            {
                                "ref": "Region"
                            }
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {

        "fn": "aws.partition",
                                "argv": [
                                    {
                                        "ref": "Region"
                                    }
                                ],
                                "assign": "PartitionResult"
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {

                                      "ref": "UseFIPS"
                                            },
                                            true
                                        ]
                                    },
                                    {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }

  ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"

        },
                                "supportsFIPS"
                              ]
                            }
                          ]
                        },
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            true,
                            {
                              "fn": "getAttr",
                              "argv": [

                               {
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                              ]
                            }
                          ]
                        }
                      ],
                      "rules": [
                        {
```

```
                "conditions": [],

        "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],

            "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {

        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [
                    {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
```

```
                "fn": "booleanEquals",
                    "argv": [
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      },
                      true

                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }
                  ],
                  "type": "tree"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "FIPS is enabled
 but this partition does not support FIPS",
              "type": "error"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
```

```
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "ref": "UseDualStack"
                                            },
                                            true

                                ]
                                    }
                                ],
                                "rules": [
                                    {
                                        "conditions": [
                                            {
                                                "fn": "booleanEquals",
                                                "argv": [
                                                    true,
                                                    {
                                                        "fn": "getAttr",
                                                        "argv": [
                                                            {

                                                            "ref": "PartitionResult"
                                                            },
                                                            "supportsDualStack"
                                                        ]
                                                    }
                                                ]
                                            }
                                        ],
                                        "rules": [
                                            {
                                                "conditions": [],
                                                "rules": [

        {
                                                        "conditions": [],
                                                        "endpoint": {
                                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                            "properties": {},
                                                            "headers": {}
                                                        },
                                                        "type": "endpoint"
                                                    }
                                                ],
                                                "type": "tree"
```

```
                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
]
},
"smithy.rules#endpointTests": {
"testCases": [
{
```

```
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

 "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
        }
```

```
    },
        "params": {
          "Region": "us-east-1",
          "UseFIPS": false,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
          }
        },
        "params": {
          "Region": "cn-north-1",
          "UseFIPS": true,
          "UseDualStack": true
        }
      },
      {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
          }
        },
        "params": {
          "Region": "cn-north-1",
          "UseFIPS": true,
          "UseDualStack": false
        }
      },
      {
        "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
        "expect": {
          "endpoint": {
            "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
          }
         },
        "params": {
          "Region": "cn-north-1",
          "UseFIPS": false,
          "UseDualStack": true
        }
      },
```

```
                {
                  "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
                    }
                  },
                  "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
                    }

                 },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
                    }
                  },
```

```
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {

    "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
```

```
enabled",
                "expect": {
                  "error": "DualStack is enabled but this partition does not support DualStack"
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
                  }
                },
                "params": {
                  "Region": "us-iso-east-1",
                  "UseFIPS":
false,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                   }
                },
                "params": {
                  "Region": "us-isob-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false
                }
              },
```

```
                {
                  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "error": "DualStack is enabled but this partition does not support DualStack"
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {

                 "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                    }
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }

        },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }
                  },
```

```
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
```

```
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

            },
            {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "OrganizationIntegration": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
          "traits": {
            "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n              <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceType</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>ProductCode</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Region</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Status</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>UsageOperation</code>\n              </p>\n            </li>\n          </ul>\n          <p>For each filter, you can use one of the following <code>Operator</code>
```

```
values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
          "type": "structure",
          "members": {
            "Instances": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
              }
            },
            "NextToken": {

           "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListLinuxSubscriptions"
        },
        "smithy.api#idempotent": {},
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",

  "items": "Subscriptions"
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
      "type": "structure",
      "members": {
        "Filters": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
```

```
match a certain subscription's name.</p>\n        <p>The valid names for this filter are:</p>\n        <ul>\n
<li>\n            <p>\n                <code>Subscription</code>\n            </p>\n        </li>\n        </ul>\n
<p>The
 valid Operators for this filter are:</p>\n        <ul>\n        <li>\n            <p>\n
<code>contains</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>equals</code>\n            </p>\n        </li>\n        <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n        </li>\n        </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
                }
```

```
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
          },
          "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",
              "items": "RegisteredSubscriptionProviders"
            }
          }

        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSources": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
            }
        },
        "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                "smithy.api#range": {
                    "min": 1,
                    "max": 100
                }
            }

 },
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
                "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
        },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
        }
      },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
      },
      "errors": [
        {

     "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
        "smithy.api#http": {
          "method": "GET",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#readonly": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
                    "documentation": "Equal operator"
                },
                {
                    "name": "NOT_EQUAL",
                    "value": "NotEqual",
                    "documentation": "Not equal operator"
                },
                {
                    "name": "CONTAINS",
                    "value": "Contains",
                    "documentation": "Contains operator"
                }
            ],
            "smithy.api#length": {
                "min": 1,
                "max": 20
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled OrganizationIntegration"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
```

```
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
            }
          },
```

```
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
                }
            },
            "LastSuccessfulDataRetrievalTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"
```

```
}
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "InProgress",
          "value": "InProgress",
          "documentation": "InProgress status"
        },
        {
          "name": "Completed",
          "value": "Completed",
          "documentation": "Completed status"
        },
        {
          "name": "Successful",
          "value": "Successful",
          "documentation": "Successful status"
        },
        {
          "name": "Failed",
          "value": "Failed",
          "documentation": "Failed status"
        }
      ]
    }
  },

  "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
    "type": "list",
    "member": {
      "target": "smithy.api#String",
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        }
      }
    },
    "traits": {
      "smithy.api#length": {
        "min": 1,
        "max": 100
      },
      "smithy.api#uniqueItems": {}
    }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
      "type": "structure",
      "members": {
        "Name":
{
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the subscription.</p>"
          }
        },
        "Type": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS.</p>"
          }
        },
        "InstanceCount": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>The total amount of running instances using this subscription.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
```

```
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
                },
                {
                    "name": "INVALID",
                    "value": "INVALID",

   "documentation": "INVALID status"
                },
                {
                    "name": "PENDING",
                    "value": "PENDING",
                    "documentation": "PENDING status"
                }
            ]
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
      "type": "structure",
      "members":
{
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services resource to which to add the specified \n\t\t\tmetadata tags.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
```

```
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

          "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
          },
```

```
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
```

```
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
          }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
          "type": "structure",
          "members": {
              "message": {
                  "target": "smithy.api#String"
              }
          },
          "traits": {
              "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
              "smithy.api#error": "client"
          }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
```

```
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
```

```
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
```

```
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
if err != nil {
 return
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
```

```
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
```

```
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
```

```
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
```

legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",

```
            "traits": {
                "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
        },
        "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
        },
        "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
                "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
    "type": "structure",
    "members": {
        "DomainName": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
            }
        },
        "DomainIpv4List": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
            "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                "smithy.api#length": {
                    "min": 1,
                    "max": 2
                }
            }
        },
        "DomainCredentialsProvider": {
            "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
              },
              "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>Contains network access and credential details that are needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
            "type": "string",
            "traits": {
              "smithy.api#enum": [
                {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
                }
              ]
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#Arn": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
 {
            "type": "operation",
            "input": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n          </note>",
            "smithy.api#http":
 {
              "code": 200,
              "method": "POST",
              "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
          "type": "structure",
          "members": {
            "Username": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
subscription.</p>",
              "smithy.api#required": {}
            }
          },
           "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },

        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
```

```
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
      "type": "structure",
      "members": {
        "LicenseServerEndpoint": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
          "traits": {
            "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
```

```
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}

      }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Directory": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
                }
            },
```

```
        "InstanceUserArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate from the EC2 instance.</p>"
          }
        },
        "Domain": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to disassociate.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
      "type": "structure",
      "members": {
        "InstanceUserSummary":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
          "traits": {
            "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory domain.</p>",
            "smithy.api#length": {
              "min": 1
            },
```

```
    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
              }
            },
            "FailureMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
          "type": "list",
          "member": {

            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
    "type": "structure",
    "members": {
        "Username": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

"IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
```

```
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
               }
            },
            "AssociationDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
               }
            },
            "DisassociationDate": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
         "type": "list",
```

```
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
    "type": "structure",
    "members": {
        "message": {
            "target": "smithy.api#String"
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
        "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
             },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
            },
            {

        "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
          ],
          "traits": {
            "aws.api#service": {
              "sdkId": "License Manager User Subscriptions",
              "arnNamespace": "license-manager-user-subscriptions",
              "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
              "name": "license-manager-user-subscriptions"
            },
            "aws.protocols#restJson1": {},
```

```
        "smithy.api#cors": {
            "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",

            "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
                "Region":
{
                    "builtIn": "AWS::Region",
                    "required": false,
                    "documentation": "The AWS region used to dispatch the request.",
                    "type": "String"
                },
                "UseDualStack": {
                    "builtIn": "AWS::UseDualStack",
                    "required": true,
                    "default": false,
                    "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                    "type": "Boolean"
                },
                "UseFIPS": {
                    "builtIn": "AWS::UseFIPS",
                    "required": true,
```

```
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
            "type": "Boolean"
          },
          "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
          }
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
             ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [
                  {

                    "fn": "booleanEquals",
                    "argv": [
                      {
```

```
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "aws.partition",

                      "argv": [
                        {
                          "ref": "Region"
                        }
                      ],
                      "assign": "PartitionResult"
                    }
```

```
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },
```

true

```
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [
                          {
```

"fn": "booleanEquals",

```
                            "argv": [
                              true,
                              {
                                "fn": "getAttr",
                                "argv": [
                                  {
                                    "ref": "PartitionResult"
                                  },
                                  "supportsFIPS"
                                ]
                              }
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              true,
```

```
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }

                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }

    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                    "type": "error"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [

 {
                            "ref": "UseFIPS"
                        },
                        true
                    ]
```

```
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "fn": "getAttr",
                                    "argv": [

        {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

    "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS is enabled but this partition does not support FIPS",
                    "type": "error"

}
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {

        "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]

          }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

            ],
                  "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
```

```
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                            "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
{
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",

      "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint":
{
                  "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                }
              },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
```

```
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
```

```
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

    },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",

  "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
```

```
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

     "endpoint": {
            "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
 false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
```

```
                },
                {
                  "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                  "expect": {
                    "error": "Invalid Configuration:
 Dualstack and custom endpoint are not supported"
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
 "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
 \n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
 \n\t\t\tlicense server.</p>"
              }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>"
              }
            },
            "ServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
              }
            },
            "LicenseServerEndpointId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits":
```

```
{
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
              }
            },
            "LicenseServerEndpointProvisioningStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
              "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
              }
            },
            "LicenseServers": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
              }
            },

           "CreationTime": {
              "target": "smithy.api#Timestamp",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
          "type": "string"
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

      "type": "string",
          "traits": {
            "smithy.api#enum": [
```

```
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
              "name": "PROVISIONED",
              "value": "PROVISIONED",
              "documentation": ""
            },
            {
              "name": "DELETING",
              "value": "DELETING",
              "documentation": ""
            },
            {
              "name": "DELETION_FAILED",
              "value": "DELETION_FAILED",
              "documentation": ""

           },
            {
              "name": "DELETED",
              "value": "DELETED",
              "documentation": ""
            }
          ]
       }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
       "type": "string",
       "traits": {
          "smithy.api#enum": [
            {
              "name": "HEALTHY",
              "value": "HEALTHY",
              "documentation": ""
            },
            {
              "name": "UNHEALTHY",
              "value": "UNHEALTHY",
              "documentation": ""
            },
```

```
                {
                    "name": "NOT_APPLICABLE",
                    "value": "NOT_APPLICABLE",
                    "documentation": ""
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
        "type": "structure",
        "members": {
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>",
                    "smithy.api#required": {}
                }
            },
            "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
```

```
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n        <li>\n        <p>Product</p>\n        </li>\n
        <li>\n        <p>DirectoryId</p>\n        </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
                    "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
 that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                    "smithy.api#required": {}
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
 empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
 next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
```

```
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },

{
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
      }
    ],
    "traits": {
      "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
      "smithy.api#http": {
        "code": 200,
        "method": "POST",
        "uri": "/instance/ListInstances"
      },
      "smithy.api#paginated": {
        "inputToken": "NextToken",
        "outputToken": "NextToken",
        "pageSize": "MaxResults",
        "items": "InstanceSummaries"
      }
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
    "type": "structure",
    "members":
```

```
{
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n
         <li>\n               <p>InstanceId</p>\n            </li>\n         </ul>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
         "type": "structure",
         "members": {
            "InstanceSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/license-server/ListLicenseServerEndpoints"
        },

      "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "LicenseServerEndpoints"
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
      "type": "structure",
      "members": {
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n        <li>\n          <p>IdentityProviderArn</p>\n        </li>\n      </ul>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
      "type": "structure",
      "members": {
        "LicenseServerEndpoints": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
```

empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
"operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " Lists the user-based subscription products available from an identity provider. ",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"

```
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
```

```
This is the nextToken \n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "ProductUserSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
```

```
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}

           }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
          "type": "structure",
          "members": {
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
```

```
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
    "type": "structure",
    "members": {
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
```

```
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {

            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
               }
            },
            "SubscriptionStartDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The start date of a subscription.</p>"
               }
            },
            "SubscriptionEndDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The end date of a subscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
         "type":
 "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
         "type": "structure",
         "members": {
```

```
            "RdsSalCredentialsProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
```

```
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
         "type": "structure",
         "members": {
            "IdentityProvider": {

     "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                  "smithy.api#required": {}
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
               "traits":
 {
                  "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
               }
            },
            "Tags": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
```

```
                    "min": 1
                }
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
    "type": "string",
    "traits": {
        "smithy.api#length": {

     "min": 5,
            "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
    "type": "structure",
    "members": {
        "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more servers.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
    "type": "union",
    "members": {
        "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
                "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

           "traits": {
              "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688
communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
              "smithy.api#required": {}
            }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StartProductSubscription"
            }

      }
       },
       "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
          "type": "structure",
          "members": {
             "Username": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                   "smithy.api#required": {}
                }
             },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                   "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                   "smithy.api#required": {}
                }
             },
             "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                   "smithy.api#required": {}
                }
             },
             "Domain": {
                "target": "smithy.api#String",
                "traits": {
                   "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
                }
             },
             "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                   "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
                }
```

```
  }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/user/StopProductSubscription"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
              }
            },
            "IdentityProvider": {
              "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
              }
            },
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }

    }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

 "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
 {
        "type": "structure",
        "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {
```

```
      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
```

```
            "type": "structure",
            "members": {
                "message": {
                    "target": "smithy.api#String"
                }
            },
            "traits": {
                "smithy.api#documentation": "<p>A parameter is not valid.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
```

```
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
```

```
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
```

```
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
```

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation

spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.124 openssl 3.3.4-r0

1.124.1 Available under license :

This software is copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software; you can redistribute it and/or modify it under
the same terms as the Perl 5 programming language system itself.

Terms of the Perl programming language system itself

a) the GNU General Public License as published by the Free
  Software Foundation; either version 1, or (at your option) any
  later version, or
b) the "Artistic License"

--- The GNU General Public License, Version 1, February 1989 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

 The GNU General Public License, Version 1, February 1989

                GNU GENERAL PUBLIC LICENSE
                 Version 1, February 1989

Copyright (C) 1989 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

                     Preamble

 The license agreements of most software companies try to keep users
at the mercy of those companies. By contrast, our General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. The
General Public License applies to the Free Software Foundation's
software and to any other program whose authors commit to using it.
You can use it for your programs, too.

 When we speak of free software, we are referring to freedom, not
price. Specifically, the General Public License is designed to make
sure that you have the freedom to give away or sell copies of free
software, that you receive source code or can get it if you want it,

that you can change the software or use pieces of it in new free
programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender
the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of a such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must tell them their rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

The precise terms and conditions
for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any program or other work which
contains a notice placed by the copyright holder saying it may be
distributed under the terms of this General Public License. The
"Program", below, refers to any such program or work, and a "work based
on the Program" means either the Program or any work containing the
Program or a portion of it, either verbatim or with modifications. Each
licensee is addressed as "you".

1. You may copy and distribute verbatim copies of the Program's source
code as you receive it, in any medium, provided that you conspicuously and
appropriately publish on each copy an appropriate copyright notice and
disclaimer of warranty; keep intact all the notices that refer to this
General Public License and to the absence of any warranty; and give any
other recipients of the
Program a copy of this General Public License
along with the Program. You may charge a fee for the physical act of

transferring a copy.

2. You may modify your copy or copies of the Program or any portion of it, and copy and distribute such modifications under the terms of Paragraph 1 above, provided that you also do the following:

a) cause the modified files to carry prominent notices stating that you changed the files and the date of any change; and

b) cause the whole of any work that you distribute or publish, that in whole or in part contains the Program or any part thereof, either with or without modifications, to be licensed at no charge to all third parties under the terms of this General Public License (except that you may choose to grant warranty protection to some or all third parties, at your option).

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use
in the simplest and most usual way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this General Public License.

d) You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

Mere aggregation of another independent work with the Program (or its derivative) on a volume of a storage or distribution medium does not bring the other work under the scope of these terms.

3. You may copy and distribute the Program (or a portion or derivative of it, under Paragraph 2) in object code or executable form under the terms of Paragraphs 1 and 2 above provided that you also do one of the following:

a) accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Paragraphs 1 and 2 above; or,

b) accompany it with a written offer, valid for at least three years, to give any third party free (except for a nominal charge for the cost of distribution) a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Paragraphs 1 and 2 above; or,

c) accompany it with the information you received as to where the corresponding source code may be obtained. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form alone.)

Source code for a work means the preferred form of the work for making modifications to it. For an executable file, complete source code means all the source code for all modules it contains; but, as a special exception, it need not include source code for modules which are standard libraries that
accompany the operating system on which the executable file runs, or for standard header files or definitions files that accompany that operating system.

4. You may not copy, modify, sublicense, distribute or transfer the Program except as expressly provided under this General Public License. Any attempt otherwise to copy, modify, sublicense, distribute or transfer the Program is void, and will automatically terminate your rights to use the Program under this License. However, parties who have received copies, or rights to use copies, from you under this General Public License will not have their licenses terminated so long as such parties remain in full compliance.

5. By copying, distributing or modifying the Program (or any work based on the Program) you indicate your acceptance of this license to do so, and all its terms and conditions.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original
licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein.

7. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of the license which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the license, you may choose any version ever published by the Free Software Foundation.

8. If you wish to incorporate parts of the Program into other free
programs whose distribution
conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

9. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY
SERVICING,
REPAIR OR CORRECTION.

10. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to humanity, the best way to achieve this is to make it
free software which everyone can redistribute and change under these
terms.

To do so,
attach the following notices to the program. It is safest to
attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the
"copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 1, or (at your option)
any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free
Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19xx name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the
appropriate parts of the General Public License. Of course, the
commands you use may be called something other than `show w' and `show
c'; they could even be mouse-clicks or menu items--whatever suits your
program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here a sample; alter
the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
program `Gnomovision' (a program to direct compilers to make passes
at assemblers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

That's all there is to it!

--- The Artistic License 1.0 ---

This software is Copyright (c) 2013 by Mark Jason Dominus <mjd@cpan.org>.

This is free software, licensed under:

The Artistic License 1.0

The Artistic License

Preamble

The intent of this document is to state the conditions under which a Package may be copied, such that the Copyright Holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

Definitions:

- "Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection of files created through textual modification.
- "Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder.
- "Copyright Holder" is whoever is named in the copyright or copyrights for the package.
- "You" is you, if you're thinking about copying or distributing this Package.
- "Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)
- "Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as ftp.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified
Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide a separate manual page for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) accompany any non-standard executables with their corresponding Standard Version executables, giving the non-standard executables non-standard names,
and clearly documenting the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that you do not advertise this Package as a product of your own.

6. The scripts and library files supplied as input to or produced as output

from the programs of this Package do not automatically fall under the copyright
of this Package, but belong to whomever generated them, and may be sold
commercially, and may be aggregated with this Package.

7. C or perl subroutines supplied by you and linked into this Package
shall not
be considered part of this Package.

8. The name of the Copyright Holder may not be used to endorse or promote
products derived from this software without specific prior written permission.

9. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF
MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

Apache License
Version 2.0, January 2004
https://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical

transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made,

use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,

or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.125 alpine-release 3.21.4-r0

1.125.1 Available under license :

```
# Contributor: Carlo Landmeter <clandmeter@alpinelinux.org>
# Maintainer: Kevin Daudt <kdaudt@alpinelinux.org>
pkgname=spdx-licenses
pkgver=3.27.0
pkgrel=0
pkgdesc="Various data formats for the SPDX License List"
url="https://spdx.org/"
arch="noarch"
options="!check" # no test suite
license="CC-BY-3.0"
source="license-list-data-$pkgver.tar.gz::https://github.com/spdx/license-list-data/archive/v$pkgver.tar.gz"
builddir="$srcdir/license-list-data-$pkgver"
subpackages="$pkgname-list"

_types="html json rdfa rdfnt rdfturtle rdfxml template text"

for type in $_types; do
 subpackages="$subpackages $pkgname-$type:_subpkg"
done

package() {
 mkdir -p "$pkgdir"
}

_subpkg() {
 local type=${subpkgname/$pkgname-/}
 pkgdesc="$pkgdesc ($type)"
 install_if="$pkgname=$pkgver-r$pkgrel"
 mkdir -p "$subpkgdir"/usr/share/spdx
 cp -r "$builddir"/$type "$subpkgdir"/usr/share/spdx/
}

list() {
 pkgdesc="$pkgdesc (licence list)"
```

```
 mkdir -p "$subpkgdir"/usr/share/spdx
 local i; for i in "$builddir"/text/*.txt;
 do
  local license=${i##*/}
  echo ${license%.*} >> "$subpkgdir"/usr/share/spdx/license.lst
 done
}

sha512sums="
16d59c81e331b54b52639826f83408d98144cdaa70eacc3e8ce35dc3b13992e4794cf7515eb9db200efd390a0c0e35ae9
d4706fbe0ca6a8d236189e88870720c  license-list-data-3.27.0.tar.gz
"
# MIT License

Copyright  2019-2021 Caleb Porzio and contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
 OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
# Contributor: Maxim Karasev <begs@disroot.org>
# Maintainer: mio <miyopan@e.email>
pkgname=bsd-games
pkgver=3.3
pkgrel=2
pkgdesc="traditional text mode games from BSD"
url="https://bsd-games.sourceforge.io/"
arch="all"
license="BSD-3-Clause"
install="$pkgname.post-install"
makedepends="ncurses-dev coreutils" # configure causes busybox expr error
subpackages="$pkgname-doc"
source="https://sourceforge.net/projects/bsd-games/files/bsd-games-$pkgver.tar.gz
 0001-bsd-games-scores-dir.patch
```

```
 "
options="!check" # no tests

build() {
 # some GNU autoconf options are ignored, but it works
 ./configure \
  --build=$CBUILD \
  --host=$CHOST \
  --prefix=/usr \
  --sysconfdir=/etc \
  --mandir=/usr/share/man \
  --scoredir=/usr/share/$pkgname
 make
}

package() {
 make DESTDIR="$pkgdir" install
 install -Dm644 LICENSE "$pkgdir"/usr/share/licenses/bsd-games/LICENSE
}

sha512sums="
aaf36d09d4fe68514a5c279063d7e77a9a9a84c447037cba974b29faa07eb80c2aab2379d0699c196b5c27ffe1b2bb2c6
8d3390143e0e62d5e3d210ccfb61294
  bsd-games-3.3.tar.gz
e1def0d4835a877242c4173fae862e278a7858738e0bacacbb045a42bcabec2aa7c72d000bbd2421ce35fe66cdc1f52c0
577b7e278029ca5ed50f7aab22319f6  0001-bsd-games-scores-dir.patch
"
```

MIT License

Copyright (c) 2023 Leaf Corcoran

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION

```
 WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
# Maintainer: Natanael Copa <ncopa@alpinelinux.org>
pkgname=libart-lgpl
pkgver=2.3.21
pkgrel=8
pkgdesc="A library for high-performance 2D graphics"
url="https://www.levien.com/libart/"
arch="all"
options="!check"  # No test suite.
license="LGPL-2.0-or-later"
subpackages="$pkgname-dev"
source="https://download.gnome.org/sources/libart_lgpl/2.3/libart_lgpl-$pkgver.tar.bz2
 "

builddir="$srcdir"/libart_lgpl-$pkgver

prepare() {
 update_config_sub
 default_prepare
}

build() {
 ./configure \
  --build=$CBUILD \
  --host=$CHOST \
  --prefix=/usr
 make
}

package() {
 make DESTDIR="$pkgdir" install
}

sha512sums="8a632a6a4da59e5e8c02ec2f5a57e36d182b325b46513765425e5f171ff9ae326af1b133725beba28f7e7
6654309e001aee9bace727b5b4c8589405256a3c020  libart_lgpl-2.3.21.tar.bz2"
mini_sendmail - accept email on behalf of real sendmail

Copyright  1999,2015 by Jef Poskanzer <jef@mail.acme.com>.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
```

documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING,
 BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

```
# Contributor: Patrycja Rosa <alpine@ptrcnull.me>
# Maintainer: Patrycja Rosa <alpine@ptrcnull.me>
pkgname=bsd-compat-headers
pkgver=0.7.2
pkgrel=6
pkgdesc="BSD compatibility headers (cdefs, queue, tree)"
url="https://gitlab.alpinelinux.org/alpine/aports"
arch="noarch"
license="BSD-2-Clause AND BSD-3-Clause"
source="
 cdefs.h
 queue.h
 tree.h
"
builddir="$srcdir"
options="!check" # just headers

package() {
 mkdir -p "$pkgdir"
 install -Dm644 -t "$pkgdir"/usr/include/sys \
  cdefs.h queue.h tree.h
}
sha512sums="
37c8fc73c7aea7b490f7850927e2bb91d12137c9e59e22c084146d515696dbc7973b5de92f4c987ba080dd2502ba8312
7006442c3f019b6447a620c0cae73178  cdefs.h
2f0d5e6e4dc3350285cf17009265dddcbe12431c111868eea39bc8cb038ab7c1f2acacbb21735c4e9d4a1fd106a8fc0f86
11ea33987d4faba37dde5ce6da0750  queue.h
d9ac210d81feb8ad2655bc80fb065d3fe20ae4417b32b4a1711e6738a4870140005c13373b5d1846ef3ce5ae6da45f2da
cef2092881eded0a2e94f6a07752ef3  tree.h
"
```

Original Copyright (c) 1985 by Supoj Sutanthavibul
Parts Copyright (c) 1989-2012 by Brian V. Smith
Parts Copyright (c) 1991 by Paul King
Other Copyrights may be found in various files

Main Xfig copyright notice:

Any party obtaining a copy of these files is granted, free of charge, a full and unrestricted irrevocable, world-wide, paid up, royalty-free, nonexclusive right and license to deal in this software and documentation files (the "Software"), including without limitation the rights to use, copy, modify, merge, publish and/or distribute copies of the Software, and to permit persons who receive copies from any such party to do so, with the only requirement being that this copyright notice remain intact.

No representations are made about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

Parts Copyright (C) 1993 by Alan Richardson (mppa3@uk.ac.sussex.syma)
The text rotation code in w_rottext.c was written by Alan Richardson.
The above copyright notice holds for this work as well.

Parts Copyright (c) 1994 by Anthony Dekker
The Kohonen neural network code for color optimization was written by Anthony Dekker.

Parts Copyright (c) 1995 by C. Blanc and C. Schlick
The X-Spline code was written Carole Blanc (blanc@labri.u-bordeaux.fr) and Christophe Schlick (schlick@labri.u-bordeaux.fr) starting from an initial implementation done by C. Feuille, S. Grosbois, L. Maziere and L. Minihot as a student practice (Universite Bordeaux, France). For additional information about X-splines, see:
"X-Splines: A Spline Model Designed for the End User" by C. Blanc and C. Schlick, Proceedings of SIGGRAPH'95
http://dept-info.labri.u-bordeaux.fr/~schlick/DOC/sig1.html
/* $NetBSD: queue.h,v 1.70 2015/11/02 15:21:23 christos Exp $ */

/*
* Copyright (c) 1991, 1993
* The Regents of the University of California. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the University nor the names of its contributors
*   may be used to endorse or promote products derived from this software
*   without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING,
 BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE

```
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* @(#)queue.h 8.5 (Berkeley) 8/20/94
*/

#ifndef _SYS_QUEUE_H_
#define _SYS_QUEUE_H_

/*
* This file defines five types of data structures: singly-linked lists,
* lists, simple queues, tail queues, and circular queues.
*
* A singly-linked list is headed by a single forward pointer. The
* elements are singly linked for minimum space and
 pointer manipulation
* overhead at the expense of O(n) removal for arbitrary elements. New
* elements can be added to the list after an existing element or at the
* head of the list.  Elements being removed from the head of the list
* should use the explicit macro for this purpose for optimum
* efficiency. A singly-linked list may only be traversed in the forward
* direction.  Singly-linked lists are ideal for applications with large
* datasets and few or no removals or for implementing a LIFO queue.
*
* A list is headed by a single forward pointer (or an array of forward
* pointers for a hash table header). The elements are doubly linked
* so that an arbitrary element can be removed without a need to
* traverse the list. New elements can be added to the list before
* or after an existing element or at the head of the list. A list
* may only be traversed in the forward direction.
*
* A simple queue is headed by a pair of pointers, one the head of the
* list and the
 other to the tail of the list. The elements are singly
* linked to save space, so elements can only be removed from the
* head of the list. New elements can be added to the list after
* an existing element, at the head of the list, or at the end of the
* list. A simple queue may only be traversed in the forward direction.
*
* A tail queue is headed by a pair of pointers, one to the head of the
* list and the other to the tail of the list. The elements are doubly
* linked so that an arbitrary element can be removed without a need to
* traverse the list. New elements can be added to the list before or
```

```
* after an existing element, at the head of the list, or at the end of
* the list. A tail queue may be traversed in either direction.
*
* A circle queue is headed by a pair of pointers, one to the head of the
* list and the other to the tail of the list. The elements are doubly
* linked so that an arbitrary element can be removed without a need to
* traverse the list. New elements
 can be added to the list before or after
* an existing element, at the head of the list, or at the end of the list.
* A circle queue may be traversed in either direction, but has a more
* complex end of list detection.
*
* For details on the use of these macros, see the queue(3) manual page.
*/

/*
* Include the definition of NULL only on NetBSD because sys/null.h
* is not available elsewhere.  This conditional makes the header
* portable and it can simply be dropped verbatim into any system.
* The caveat is that on other systems some other header
* must provide NULL before the macros can be used.
*/
#ifdef __NetBSD__
#include <sys/null.h>
#endif

#if defined(QUEUEDEBUG)
# if defined(_KERNEL)
#  define QUEUEDEBUG_ABORT(...) panic(__VA_ARGS__)
# else
#  include <err.h>
#  define QUEUEDEBUG_ABORT(...) err(1, __VA_ARGS__)
# endif
#endif

/*
* Singly-linked List definitions.
*/
#define SLIST_HEAD(name, type)      \
struct name {       \
 struct type *slh_first; /* first
 element */   \
}

#define SLIST_HEAD_INITIALIZER(head)     \
 { NULL }

#define SLIST_ENTRY(type)      \
```

```
struct {        \
 struct type *sle_next; /* next element */   \
}

/*
* Singly-linked List access methods.
*/
#define SLIST_FIRST(head) ((head)->slh_first)
#define SLIST_END(head)  NULL
#define SLIST_EMPTY(head) ((head)->slh_first == NULL)
#define SLIST_NEXT(elm, field) ((elm)->field.sle_next)

#define SLIST_FOREACH(var, head, field)     \
 for((var) = (head)->slh_first;     \
     (var) != SLIST_END(head);     \
     (var) = (var)->field.sle_next)

#define SLIST_FOREACH_SAFE(var, head, field, tvar)   \
 for ((var) = SLIST_FIRST((head));    \
     (var) != SLIST_END(head) &&     \
     ((tvar) = SLIST_NEXT((var), field), 1);   \
     (var) = (tvar))

/*
* Singly-linked List functions.
*/
#define SLIST_INIT(head) do {      \
 (head)->slh_first = SLIST_END(head);    \
} while (/*CONSTCOND*/0)

#define SLIST_INSERT_AFTER(slistelm, elm, field) do {   \
 (elm)->field.sle_next = (slistelm)->field.sle_next;  \
 (slistelm)->field.sle_next
 = (elm);    \
} while (/*CONSTCOND*/0)

#define SLIST_INSERT_HEAD(head, elm, field) do {    \
 (elm)->field.sle_next = (head)->slh_first;   \
 (head)->slh_first = (elm);     \
} while (/*CONSTCOND*/0)

#define SLIST_REMOVE_AFTER(slistelm, field) do {    \
 (slistelm)->field.sle_next =     \
     SLIST_NEXT(SLIST_NEXT((slistelm), field), field);  \
} while (/*CONSTCOND*/0)

#define SLIST_REMOVE_HEAD(head, field) do {    \
 (head)->slh_first = (head)->slh_first->field.sle_next;  \
```

```
} while (/*CONSTCOND*/0)

#define SLIST_REMOVE(head, elm, type, field) do {   \
 if ((head)->slh_first == (elm)) {    \
  SLIST_REMOVE_HEAD((head), field);   \
 }       \
 else {       \
  struct type *curelm = (head)->slh_first;  \
  while(curelm->field.sle_next != (elm))   \
   curelm = curelm->field.sle_next;  \
  curelm->field.sle_next =    \
      curelm->field.sle_next->field.sle_next;  \
 }       \
} while (/*CONSTCOND*/0)


/*
* List definitions.
 */
#define LIST_HEAD(name, type)      \
struct name {       \
 struct type *lh_first; /* first element */   \
}

#define LIST_HEAD_INITIALIZER(head)     \
 { NULL }

#define LIST_ENTRY(type)      \
struct {       \
 struct type *le_next; /* next element */   \
 struct type **le_prev; /* address of previous next element */ \
}

/*
* List access methods.
*/
#define LIST_FIRST(head)  ((head)->lh_first)
#define LIST_END(head)   NULL
#define LIST_EMPTY(head)  ((head)->lh_first == LIST_END(head))
#define LIST_NEXT(elm, field)  ((elm)->field.le_next)

#define LIST_FOREACH(var, head, field)     \
 for ((var) = ((head)->lh_first);    \
     (var) != LIST_END(head);     \
     (var) = ((var)->field.le_next))

#define LIST_FOREACH_SAFE(var, head, field, tvar)   \
 for ((var) = LIST_FIRST((head));    \
```

```
    (var) != LIST_END(head) &&     \
    ((tvar) = LIST_NEXT((var), field), 1);   \
    (var) = (tvar))

#define LIST_MOVE(head1, head2) do {     \
 LIST_INIT((head2));      \
 if (!LIST_EMPTY((head1)))
 {     \
  (head2)->lh_first = (head1)->lh_first;   \
  LIST_INIT((head1));     \
 }       \
} while (/*CONSTCOND*/0)

/*
* List functions.
*/
#if defined(QUEUEDEBUG)
#define QUEUEDEBUG_LIST_INSERT_HEAD(head, elm, field)   \
 if ((head)->lh_first &&      \
    (head)->lh_first->field.le_prev != &(head)->lh_first) \
  QUEUEDEBUG_ABORT("LIST_INSERT_HEAD %p %s:%d", (head), \
      __FILE__, __LINE__);
#define QUEUEDEBUG_LIST_OP(elm, field)     \
 if ((elm)->field.le_next &&     \
    (elm)->field.le_next->field.le_prev !=   \
    &(elm)->field.le_next)     \
  QUEUEDEBUG_ABORT("LIST_* forw %p %s:%d", (elm),  \
      __FILE__, __LINE__);    \
 if (*(elm)->field.le_prev != (elm))    \
  QUEUEDEBUG_ABORT("LIST_* back %p %s:%d", (elm),  \
      __FILE__, __LINE__);
#define QUEUEDEBUG_LIST_POSTREMOVE(elm, field)    \
 (elm)->field.le_next = (void *)1L;    \
 (elm)->field.le_prev = (void *)1L;
#else
#define QUEUEDEBUG_LIST_INSERT_HEAD(head, elm, field)
#define QUEUEDEBUG_LIST_OP(elm,
 field)
#define QUEUEDEBUG_LIST_POSTREMOVE(elm, field)
#endif

#define LIST_INIT(head) do {      \
 (head)->lh_first = LIST_END(head);    \
} while (/*CONSTCOND*/0)

#define LIST_INSERT_AFTER(listelm, elm, field) do {   \
 QUEUEDEBUG_LIST_OP((listelm), field)    \
 if (((elm)->field.le_next = (listelm)->field.le_next) !=  \
```

```
    LIST_END(head))      \
  (listelm)->field.le_next->field.le_prev =  \
      &(elm)->field.le_next;    \
 (listelm)->field.le_next = (elm);    \
 (elm)->field.le_prev = &(listelm)->field.le_next;  \
} while (/*CONSTCOND*/0)

#define LIST_INSERT_BEFORE(listelm, elm, field) do {   \
 QUEUEDEBUG_LIST_OP((listelm), field)    \
 (elm)->field.le_prev = (listelm)->field.le_prev;  \
 (elm)->field.le_next = (listelm);    \
 *(listelm)->field.le_prev = (elm);    \
 (listelm)->field.le_prev = &(elm)->field.le_next;  \
} while (/*CONSTCOND*/0)

#define LIST_INSERT_HEAD(head, elm, field) do {    \
 QUEUEDEBUG_LIST_INSERT_HEAD((head), (elm), field)  \
 if (((elm)->field.le_next
 = (head)->lh_first) != LIST_END(head))\
  (head)->lh_first->field.le_prev = &(elm)->field.le_next;\
 (head)->lh_first = (elm);     \
 (elm)->field.le_prev = &(head)->lh_first;   \
} while (/*CONSTCOND*/0)

#define LIST_REMOVE(elm, field) do {     \
 QUEUEDEBUG_LIST_OP((elm), field)    \
 if ((elm)->field.le_next != NULL)    \
  (elm)->field.le_next->field.le_prev =    \
      (elm)->field.le_prev;    \
 *(elm)->field.le_prev = (elm)->field.le_next;   \
 QUEUEDEBUG_LIST_POSTREMOVE((elm), field)   \
} while (/*CONSTCOND*/0)

#define LIST_REPLACE(elm, elm2, field) do {    \
 if (((elm2)->field.le_next = (elm)->field.le_next) != NULL) \
  (elm2)->field.le_next->field.le_prev =   \
      &(elm2)->field.le_next;    \
 (elm2)->field.le_prev = (elm)->field.le_prev;   \
 *(elm2)->field.le_prev = (elm2);    \
 QUEUEDEBUG_LIST_POSTREMOVE((elm), field)   \
} while (/*CONSTCOND*/0)

/*
* Simple queue definitions.
*/
#define SIMPLEQ_HEAD(name, type)     \
struct name {        \
 struct
```

```
 type *sqh_first; /* first element */   \
 struct type **sqh_last; /* addr of last next element */  \
}

#define SIMPLEQ_HEAD_INITIALIZER(head)     \
 { NULL, &(head).sqh_first }

#define SIMPLEQ_ENTRY(type)      \
struct {        \
 struct type *sqe_next; /* next element */   \
}

/*
* Simple queue access methods.
*/
#define SIMPLEQ_FIRST(head)  ((head)->sqh_first)
#define SIMPLEQ_END(head)  NULL
#define SIMPLEQ_EMPTY(head)  ((head)->sqh_first == SIMPLEQ_END(head))
#define SIMPLEQ_NEXT(elm, field) ((elm)->field.sqe_next)

#define SIMPLEQ_FOREACH(var, head, field)    \
 for ((var) = ((head)->sqh_first);    \
     (var) != SIMPLEQ_END(head);     \
     (var) = ((var)->field.sqe_next))

#define SIMPLEQ_FOREACH_SAFE(var, head, field, next)   \
 for ((var) = ((head)->sqh_first);    \
     (var) != SIMPLEQ_END(head) &&    \
     ((next = ((var)->field.sqe_next)), 1);   \
     (var) = (next))

/*
* Simple queue functions.
*/
#define SIMPLEQ_INIT(head) do {      \
 (head)->sqh_first = NULL;     \
 (head)->sqh_last
 = &(head)->sqh_first;    \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_INSERT_HEAD(head, elm, field) do {   \
 if (((elm)->field.sqe_next = (head)->sqh_first) == NULL) \
  (head)->sqh_last = &(elm)->field.sqe_next;  \
 (head)->sqh_first = (elm);     \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_INSERT_TAIL(head, elm, field) do {   \
 (elm)->field.sqe_next = NULL;     \
```

```
 *(head)->sqh_last = (elm);     \
 (head)->sqh_last = &(elm)->field.sqe_next;   \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_INSERT_AFTER(head, listelm, elm, field) do {  \
 if (((elm)->field.sqe_next = (listelm)->field.sqe_next) == NULL)\
  (head)->sqh_last = &(elm)->field.sqe_next;  \
 (listelm)->field.sqe_next = (elm);    \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_REMOVE_HEAD(head, field) do {    \
 if (((head)->sqh_first = (head)->sqh_first->field.sqe_next) == NULL) \
  (head)->sqh_last = &(head)->sqh_first;   \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_REMOVE_AFTER(head, elm, field) do {   \
 if
 (((elm)->field.sqe_next = (elm)->field.sqe_next->field.sqe_next) \
    == NULL)       \
  (head)->sqh_last = &(elm)->field.sqe_next;  \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_REMOVE(head, elm, type, field) do {   \
 if ((head)->sqh_first == (elm)) {    \
  SIMPLEQ_REMOVE_HEAD((head), field);   \
 } else {       \
  struct type *curelm = (head)->sqh_first;  \
  while (curelm->field.sqe_next != (elm))   \
   curelm = curelm->field.sqe_next;  \
  if ((curelm->field.sqe_next =    \
   curelm->field.sqe_next->field.sqe_next) == NULL) \
      (head)->sqh_last = &(curelm)->field.sqe_next; \
 }       \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_CONCAT(head1, head2) do {    \
 if (!SIMPLEQ_EMPTY((head2))) {     \
  *(head1)->sqh_last = (head2)->sqh_first;  \
  (head1)->sqh_last = (head2)->sqh_last;  \
  SIMPLEQ_INIT((head2));     \
 }       \
} while (/*CONSTCOND*/0)

#define SIMPLEQ_LAST(head, type, field)     \
 (SIMPLEQ_EMPTY((head)) ?      \
  NULL :       \
        ((struct type
```

```
 *)(void *)    \
  ((char *)((head)->sqh_last) - offsetof(struct type, field))))

/*
* Tail queue definitions.
*/
#define _TAILQ_HEAD(name, type, qual)     \
struct name {        \
 qual type *tqh_first;  /* first element */  \
 qual type *qual *tqh_last; /* addr of last next element */ \
}
#define TAILQ_HEAD(name, type) _TAILQ_HEAD(name, struct type,)

#define TAILQ_HEAD_INITIALIZER(head)     \
 { TAILQ_END(head), &(head).tqh_first }

#define _TAILQ_ENTRY(type, qual)     \
struct {        \
 qual type *tqe_next;  /* next element */  \
 qual type *qual *tqe_prev; /* address of previous next element */\
}
#define TAILQ_ENTRY(type) _TAILQ_ENTRY(struct type,)

/*
* Tail queue access methods.
*/
#define TAILQ_FIRST(head)  ((head)->tqh_first)
#define TAILQ_END(head)   (NULL)
#define TAILQ_NEXT(elm, field)  ((elm)->field.tqe_next)
#define TAILQ_LAST(head, headname) \
 (*(((struct headname *)(void *)((head)->tqh_last))->tqh_last))
#define TAILQ_PREV(elm, headname, field) \
 (*(((struct headname
 *)(void *)((elm)->field.tqe_prev))->tqh_last))
#define TAILQ_EMPTY(head)  (TAILQ_FIRST(head) == TAILQ_END(head))


#define TAILQ_FOREACH(var, head, field)     \
 for ((var) = ((head)->tqh_first);    \
     (var) != TAILQ_END(head);     \
     (var) = ((var)->field.tqe_next))

#define TAILQ_FOREACH_SAFE(var, head, field, next)   \
 for ((var) = ((head)->tqh_first);    \
     (var) != TAILQ_END(head) &&     \
     ((next) = TAILQ_NEXT(var, field), 1); (var) = (next))

#define TAILQ_FOREACH_REVERSE(var, head, headname, field)  \
```

```
 for ((var) = TAILQ_LAST((head), headname);   \
    (var) != TAILQ_END(head);     \
    (var) = TAILQ_PREV((var), headname, field))

#define TAILQ_FOREACH_REVERSE_SAFE(var, head, headname, field, prev) \
 for ((var) = TAILQ_LAST((head), headname);   \
    (var) != TAILQ_END(head) &&     \
    ((prev) = TAILQ_PREV((var), headname, field), 1); (var) = (prev))

/*
* Tail queue functions.
*/
#if defined(QUEUEDEBUG)
#define QUEUEDEBUG_TAILQ_INSERT_HEAD(head,
 elm, field)   \
 if ((head)->tqh_first &&     \
    (head)->tqh_first->field.tqe_prev != &(head)->tqh_first) \
  QUEUEDEBUG_ABORT("TAILQ_INSERT_HEAD %p %s:%d", (head), \
     __FILE__, __LINE__);
#define QUEUEDEBUG_TAILQ_INSERT_TAIL(head, elm, field)   \
 if (*(head)->tqh_last != NULL)     \
  QUEUEDEBUG_ABORT("TAILQ_INSERT_TAIL %p %s:%d", (head), \
     __FILE__, __LINE__);
#define QUEUEDEBUG_TAILQ_OP(elm, field)     \
 if ((elm)->field.tqe_next &&     \
    (elm)->field.tqe_next->field.tqe_prev !=   \
    &(elm)->field.tqe_next)     \
  QUEUEDEBUG_ABORT("TAILQ_* forw %p %s:%d", (elm), \
     __FILE__, __LINE__);    \
 if (*(elm)->field.tqe_prev != (elm))    \
  QUEUEDEBUG_ABORT("TAILQ_* back %p %s:%d", (elm), \
     __FILE__, __LINE__);
#define QUEUEDEBUG_TAILQ_PREREMOVE(head, elm, field)   \
 if ((elm)->field.tqe_next == NULL &&    \
    (head)->tqh_last != &(elm)->field.tqe_next)   \
  QUEUEDEBUG_ABORT("TAILQ_PREREMOVE head %p elm %p %s:%d",\
     (head), (elm), __FILE__,
 __LINE__);
#define QUEUEDEBUG_TAILQ_POSTREMOVE(elm, field)    \
 (elm)->field.tqe_next = (void *)1L;    \
 (elm)->field.tqe_prev = (void *)1L;
#else
#define QUEUEDEBUG_TAILQ_INSERT_HEAD(head, elm, field)
#define QUEUEDEBUG_TAILQ_INSERT_TAIL(head, elm, field)
#define QUEUEDEBUG_TAILQ_OP(elm, field)
#define QUEUEDEBUG_TAILQ_PREREMOVE(head, elm, field)
#define QUEUEDEBUG_TAILQ_POSTREMOVE(elm, field)
#endif
```

```
#define TAILQ_INIT(head) do {      \
 (head)->tqh_first = TAILQ_END(head);    \
 (head)->tqh_last = &(head)->tqh_first;    \
} while (/*CONSTCOND*/0)

#define TAILQ_INSERT_HEAD(head, elm, field) do {    \
 QUEUEDEBUG_TAILQ_INSERT_HEAD((head), (elm), field)  \
 if (((elm)->field.tqe_next = (head)->tqh_first) != TAILQ_END(head))\
  (head)->tqh_first->field.tqe_prev =    \
     &(elm)->field.tqe_next;    \
 else       \
  (head)->tqh_last = &(elm)->field.tqe_next;  \
 (head)->tqh_first = (elm);     \
 (elm)->field.tqe_prev = &(head)->tqh_first;   \
} while (/*CONSTCOND*/0)

#define TAILQ_INSERT_TAIL(head,
 elm, field) do {   \
 QUEUEDEBUG_TAILQ_INSERT_TAIL((head), (elm), field)  \
 (elm)->field.tqe_next = TAILQ_END(head);   \
 (elm)->field.tqe_prev = (head)->tqh_last;   \
 *(head)->tqh_last = (elm);     \
 (head)->tqh_last = &(elm)->field.tqe_next;   \
} while (/*CONSTCOND*/0)

#define TAILQ_INSERT_AFTER(head, listelm, elm, field) do {  \
 QUEUEDEBUG_TAILQ_OP((listelm), field)    \
 if (((elm)->field.tqe_next = (listelm)->field.tqe_next) !=  \
    TAILQ_END(head))      \
  (elm)->field.tqe_next->field.tqe_prev =   \
     &(elm)->field.tqe_next;    \
 else       \
  (head)->tqh_last = &(elm)->field.tqe_next;  \
 (listelm)->field.tqe_next = (elm);    \
 (elm)->field.tqe_prev = &(listelm)->field.tqe_next;  \
} while (/*CONSTCOND*/0)

#define TAILQ_INSERT_BEFORE(listelm, elm, field) do {   \
 QUEUEDEBUG_TAILQ_OP((listelm), field)    \
 (elm)->field.tqe_prev = (listelm)->field.tqe_prev;  \
 (elm)->field.tqe_next = (listelm);    \
 *(listelm)->field.tqe_prev = (elm);    \
 (listelm)->field.tqe_prev
 = &(elm)->field.tqe_next;  \
} while (/*CONSTCOND*/0)

#define TAILQ_REMOVE(head, elm, field) do {    \
```

```
 QUEUEDEBUG_TAILQ_PREREMOVE((head), (elm), field)  \
 QUEUEDEBUG_TAILQ_OP((elm), field)    \
 if (((elm)->field.tqe_next) != TAILQ_END(head))   \
  (elm)->field.tqe_next->field.tqe_prev =   \
      (elm)->field.tqe_prev;    \
 else       \
  (head)->tqh_last = (elm)->field.tqe_prev;  \
 *(elm)->field.tqe_prev = (elm)->field.tqe_next;   \
 QUEUEDEBUG_TAILQ_POSTREMOVE((elm), field);   \
} while (/*CONSTCOND*/0)

#define TAILQ_REPLACE(head, elm, elm2, field) do {   \
       if (((elm2)->field.tqe_next = (elm)->field.tqe_next) !=  \
     TAILQ_END(head))        \
             (elm2)->field.tqe_next->field.tqe_prev =  \
                 &(elm2)->field.tqe_next;    \
       else       \
             (head)->tqh_last = &(elm2)->field.tqe_next;  \
       (elm2)->field.tqe_prev = (elm)->field.tqe_prev;   \
       *(elm2)->field.tqe_prev = (elm2);    \
 QUEUEDEBUG_TAILQ_POSTREMOVE((elm),
 field);   \
} while (/*CONSTCOND*/0)

#define TAILQ_CONCAT(head1, head2, field) do {    \
 if (!TAILQ_EMPTY(head2)) {     \
  *(head1)->tqh_last = (head2)->tqh_first;  \
  (head2)->tqh_first->field.tqe_prev = (head1)->tqh_last; \
  (head1)->tqh_last = (head2)->tqh_last;   \
  TAILQ_INIT((head2));     \
 }       \
} while (/*CONSTCOND*/0)

/*
* Singly-linked Tail queue declarations.
*/
#define STAILQ_HEAD(name, type)      \
struct name {       \
 struct type *stqh_first; /* first element */  \
 struct type **stqh_last; /* addr of last next element */ \
}

#define STAILQ_HEAD_INITIALIZER(head)     \
 { NULL, &(head).stqh_first }

#define STAILQ_ENTRY(type)      \
struct {       \
 struct type *stqe_next; /* next element */   \
```

```
}

/*
* Singly-linked Tail queue access methods.
*/
#define STAILQ_FIRST(head) ((head)->stqh_first)
#define STAILQ_END(head) NULL
#define STAILQ_NEXT(elm, field) ((elm)->field.stqe_next)
#define STAILQ_EMPTY(head) (STAILQ_FIRST(head)
 == STAILQ_END(head))

/*
* Singly-linked Tail queue functions.
*/
#define STAILQ_INIT(head) do {      \
 (head)->stqh_first = NULL;     \
 (head)->stqh_last = &(head)->stqh_first;    \
} while (/*CONSTCOND*/0)

#define STAILQ_INSERT_HEAD(head, elm, field) do {   \
 if (((elm)->field.stqe_next = (head)->stqh_first) == NULL) \
  (head)->stqh_last = &(elm)->field.stqe_next;  \
 (head)->stqh_first = (elm);     \
} while (/*CONSTCOND*/0)

#define STAILQ_INSERT_TAIL(head, elm, field) do {   \
 (elm)->field.stqe_next = NULL;     \
 *(head)->stqh_last = (elm);     \
 (head)->stqh_last = &(elm)->field.stqe_next;   \
} while (/*CONSTCOND*/0)

#define STAILQ_INSERT_AFTER(head, listelm, elm, field) do {  \
 if (((elm)->field.stqe_next = (listelm)->field.stqe_next) == NULL)\
  (head)->stqh_last = &(elm)->field.stqe_next;  \
 (listelm)->field.stqe_next = (elm);    \
} while (/*CONSTCOND*/0)

#define STAILQ_REMOVE_HEAD(head, field) do {    \
 if (((head)->stqh_first = (head)->stqh_first->field.stqe_next)
 == NULL) \
  (head)->stqh_last = &(head)->stqh_first;   \
} while (/*CONSTCOND*/0)

#define STAILQ_REMOVE(head, elm, type, field) do {   \
 if ((head)->stqh_first == (elm)) {    \
  STAILQ_REMOVE_HEAD((head), field);   \
 } else {       \
  struct type *curelm = (head)->stqh_first;  \
```

```
  while (curelm->field.stqe_next != (elm))   \
   curelm = curelm->field.stqe_next;  \
  if ((curelm->field.stqe_next =    \
   curelm->field.stqe_next->field.stqe_next) == NULL) \
      (head)->stqh_last = &(curelm)->field.stqe_next; \
 }       \
} while (/*CONSTCOND*/0)

#define STAILQ_FOREACH(var, head, field)    \
 for ((var) = ((head)->stqh_first);    \
  (var);       \
  (var) = ((var)->field.stqe_next))

#define STAILQ_FOREACH_SAFE(var, head, field, tvar)   \
 for ((var) = STAILQ_FIRST((head));    \
     (var) && ((tvar) = STAILQ_NEXT((var), field), 1);  \
     (var) = (tvar))

#define STAILQ_CONCAT(head1, head2) do {    \
 if (!STAILQ_EMPTY((head2))) {     \
  *(head1)->stqh_last
 = (head2)->stqh_first;  \
  (head1)->stqh_last = (head2)->stqh_last;  \
  STAILQ_INIT((head2));     \
 }       \
} while (/*CONSTCOND*/0)

#define STAILQ_LAST(head, type, field)     \
 (STAILQ_EMPTY((head)) ?      \
  NULL :       \
        ((struct type *)(void *)    \
  ((char *)((head)->stqh_last) - offsetof(struct type, field))))


#ifndef _KERNEL
/*
* Circular queue definitions. Do not use. We still keep the macros
* for compatibility but because of pointer aliasing issues their use
* is discouraged!
*/

/*
* __launder_type():  We use this ugly hack to work around the the compiler
* noticing that two types may not alias each other and elide tests in code.
* We hit this in the CIRCLEQ macros when comparing 'struct name *' and
* 'struct type *' (see CIRCLEQ_HEAD()).  Modern compilers (such as GCC
* 4.8) declare these comparisons as always false, causing the code to
* not run as designed.
```

```
*
* This hack is only to be used for comparisons and thus can be fully const.
 * Do not use for assignment.
*
* If we ever choose to change the ABI of the CIRCLEQ macros, we could fix
* this by changing the head/tail sentinal values, but see the note above
* this one.
*/
static __inline const void * __launder_type(const void *);
static __inline const void *
__launder_type(const void *__x)
{
 __asm __volatile("" : "+r" (__x));
 return __x;
}

#if defined(QUEUEDEBUG)
#define QUEUEDEBUG_CIRCLEQ_HEAD(head, field)    \
 if ((head)->cqh_first != CIRCLEQ_ENDC(head) &&   \
    (head)->cqh_first->field.cqe_prev != CIRCLEQ_ENDC(head)) \
  QUEUEDEBUG_ABORT("CIRCLEQ head forw %p %s:%d", (head), \
       __FILE__, __LINE__);    \
 if ((head)->cqh_last != CIRCLEQ_ENDC(head) &&   \
    (head)->cqh_last->field.cqe_next != CIRCLEQ_ENDC(head)) \
  QUEUEDEBUG_ABORT("CIRCLEQ head back %p %s:%d", (head), \
       __FILE__, __LINE__);
#define QUEUEDEBUG_CIRCLEQ_ELM(head, elm, field)   \
 if ((elm)->field.cqe_next == CIRCLEQ_ENDC(head)) {  \
  if ((head)->cqh_last != (elm))    \
   QUEUEDEBUG_ABORT("CIRCLEQ
 elm last %p %s:%d", \
      (elm), __FILE__, __LINE__);   \
 } else {       \
  if ((elm)->field.cqe_next->field.cqe_prev != (elm)) \
   QUEUEDEBUG_ABORT("CIRCLEQ elm forw %p %s:%d", \
      (elm), __FILE__, __LINE__);   \
 }       \
 if ((elm)->field.cqe_prev == CIRCLEQ_ENDC(head)) {  \
  if ((head)->cqh_first != (elm))    \
   QUEUEDEBUG_ABORT("CIRCLEQ elm first %p %s:%d", \
      (elm), __FILE__, __LINE__);   \
 } else {       \
  if ((elm)->field.cqe_prev->field.cqe_next != (elm)) \
   QUEUEDEBUG_ABORT("CIRCLEQ elm prev %p %s:%d", \
      (elm), __FILE__, __LINE__);   \
 }
#define QUEUEDEBUG_CIRCLEQ_POSTREMOVE(elm, field)   \
 (elm)->field.cqe_next = (void *)1L;    \
```

```
 (elm)->field.cqe_prev = (void *)1L;
#else
#define QUEUEDEBUG_CIRCLEQ_HEAD(head, field)
#define QUEUEDEBUG_CIRCLEQ_ELM(head, elm, field)
#define QUEUEDEBUG_CIRCLEQ_POSTREMOVE(elm, field)
#endif

#define CIRCLEQ_HEAD(name, type)     \
struct name {        \
 struct type *cqh_first;  /*
 first element */  \
 struct type *cqh_last;  /* last element */  \
}

#define CIRCLEQ_HEAD_INITIALIZER(head)     \
 { CIRCLEQ_END(&head), CIRCLEQ_END(&head) }

#define CIRCLEQ_ENTRY(type)      \
struct {        \
 struct type *cqe_next;  /* next element */  \
 struct type *cqe_prev;  /* previous element */  \
}

/*
* Circular queue functions.
*/
#define CIRCLEQ_INIT(head) do {      \
 (head)->cqh_first = CIRCLEQ_END(head);    \
 (head)->cqh_last = CIRCLEQ_END(head);    \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_INSERT_AFTER(head, listelm, elm, field) do {  \
 QUEUEDEBUG_CIRCLEQ_HEAD((head), field)    \
 QUEUEDEBUG_CIRCLEQ_ELM((head), (listelm), field)  \
 (elm)->field.cqe_next = (listelm)->field.cqe_next;  \
 (elm)->field.cqe_prev = (listelm);    \
 if ((listelm)->field.cqe_next == CIRCLEQ_ENDC(head))  \
  (head)->cqh_last = (elm);    \
 else        \
  (listelm)->field.cqe_next->field.cqe_prev = (elm); \
 (listelm)->field.cqe_next = (elm);    \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_INSERT_BEFORE(head,
 listelm, elm, field) do {  \
 QUEUEDEBUG_CIRCLEQ_HEAD((head), field)    \
 QUEUEDEBUG_CIRCLEQ_ELM((head), (listelm), field)  \
 (elm)->field.cqe_next = (listelm);    \
```

```
 (elm)->field.cqe_prev = (listelm)->field.cqe_prev;  \
 if ((listelm)->field.cqe_prev == CIRCLEQ_ENDC(head))  \
  (head)->cqh_first = (elm);    \
 else       \
  (listelm)->field.cqe_prev->field.cqe_next = (elm); \
 (listelm)->field.cqe_prev = (elm);    \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_INSERT_HEAD(head, elm, field) do {   \
 QUEUEDEBUG_CIRCLEQ_HEAD((head), field)    \
 (elm)->field.cqe_next = (head)->cqh_first;   \
 (elm)->field.cqe_prev = CIRCLEQ_END(head);   \
 if ((head)->cqh_last == CIRCLEQ_ENDC(head))   \
  (head)->cqh_last = (elm);    \
 else       \
  (head)->cqh_first->field.cqe_prev = (elm);  \
 (head)->cqh_first = (elm);     \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_INSERT_TAIL(head, elm, field) do {   \
 QUEUEDEBUG_CIRCLEQ_HEAD((head), field)    \
 (elm)->field.cqe_next
 = CIRCLEQ_END(head);   \
 (elm)->field.cqe_prev = (head)->cqh_last;   \
 if ((head)->cqh_first == CIRCLEQ_ENDC(head))   \
  (head)->cqh_first = (elm);    \
 else       \
  (head)->cqh_last->field.cqe_next = (elm);  \
 (head)->cqh_last = (elm);     \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_REMOVE(head, elm, field) do {    \
 QUEUEDEBUG_CIRCLEQ_HEAD((head), field)    \
 QUEUEDEBUG_CIRCLEQ_ELM((head), (elm), field)   \
 if ((elm)->field.cqe_next == CIRCLEQ_ENDC(head))  \
  (head)->cqh_last = (elm)->field.cqe_prev;  \
 else       \
  (elm)->field.cqe_next->field.cqe_prev =   \
     (elm)->field.cqe_prev;    \
 if ((elm)->field.cqe_prev == CIRCLEQ_ENDC(head))  \
  (head)->cqh_first = (elm)->field.cqe_next;  \
 else       \
  (elm)->field.cqe_prev->field.cqe_next =   \
     (elm)->field.cqe_next;    \
 QUEUEDEBUG_CIRCLEQ_POSTREMOVE((elm), field)   \
} while (/*CONSTCOND*/0)

#define CIRCLEQ_FOREACH(var, head, field)    \
```

```
 for ((var) = ((head)->cqh_first);    \
  (var) != CIRCLEQ_ENDC(head);    \
  (var)
 = ((var)->field.cqe_next))

#define CIRCLEQ_FOREACH_REVERSE(var, head, field)   \
 for ((var) = ((head)->cqh_last);    \
  (var) != CIRCLEQ_ENDC(head);    \
  (var) = ((var)->field.cqe_prev))

/*
* Circular queue access methods.
*/
#define CIRCLEQ_FIRST(head)  ((head)->cqh_first)
#define CIRCLEQ_LAST(head)  ((head)->cqh_last)
/* For comparisons */
#define CIRCLEQ_ENDC(head)  (__launder_type(head))
/* For assignments */
#define CIRCLEQ_END(head)  ((void *)(head))
#define CIRCLEQ_NEXT(elm, field) ((elm)->field.cqe_next)
#define CIRCLEQ_PREV(elm, field) ((elm)->field.cqe_prev)
#define CIRCLEQ_EMPTY(head)      \
   (CIRCLEQ_FIRST(head) == CIRCLEQ_ENDC(head))

#define CIRCLEQ_LOOP_NEXT(head, elm, field)    \
 (((elm)->field.cqe_next == CIRCLEQ_ENDC(head))   \
     ? ((head)->cqh_first)     \
     : (elm->field.cqe_next))
#define CIRCLEQ_LOOP_PREV(head, elm, field)    \
 (((elm)->field.cqe_prev == CIRCLEQ_ENDC(head))   \
     ? ((head)->cqh_last)     \
     :
 (elm->field.cqe_prev))
#endif /* !_KERNEL */

#endif /* !_SYS_QUEUE_H_ */
# Contributor: Fabian Affolter <fabian@affolter-engineering.ch>
# Maintainer: Fabian Affolter <fabian@affolter-engineering.ch>
pkgname=py3-flake8-copyright
_pkgname=flake8-copyright
pkgver=0.2.4
pkgrel=3
pkgdesc="Extension for flake8 which checks for copyrights"
options="!check" # No testsuite
url="https://github.com/savoirfairelinux/flake8-copyright"
arch="noarch"
license="MIT"
depends="py3-flake8 py3-setuptools"
```

```
makedepends="py3-gpep517 py3-wheel"
subpackages="$pkgname-pyc"
source="https://files.pythonhosted.org/packages/source/${_pkgname:0:1}/$_pkgname/$_pkgname-$pkgver.tar.gz"
builddir="$srcdir"/$_pkgname-$pkgver

replaces="py-flake8-copyright"                  # Backwards compatibility
provides="py-flake8-copyright=$pkgver-r$pkgrel" # Backwards compatibility

build() {
 gpep517 build-wheel \
  --wheel-dir .dist \
  --output-fd 3 3>&1 >&2
}

package() {
 gpep517 install-wheel --destdir "$pkgdir" \
  .dist/*.whl
}

sha512sums="
a6ab47e1bb715618f075c51f398e18180404871b3b0faf1c2d30701d5203db6bc23771bf22ffb5bafcd8ee856b9b64237
b316bd503ae7dceed6ca284ccd5a74d
  flake8-copyright-0.2.4.tar.gz
"
#ifndef _SYS_CDEFS_H_
#define _SYS_CDEFS_H_

#warning usage of non-standard #include <sys/cdefs.h> is deprecated

#undef __P
#undef __PMT

#define __P(args) args
#define __PMT(args) args

#define __CONCAT(x,y) x ## y
#define __STRING(x) #x

#ifdef  __cplusplus
# define __BEGIN_DECLS extern "C" {
# define __END_DECLS }
#else
# define __BEGIN_DECLS
# define __END_DECLS
#endif

#if defined(__GNUC__) && !defined(__cplusplus)
# define __THROW __attribute__ ((__nothrow__))
```

```
# define __NTH(fct) __attribute__ ((__nothrow__)) fct
#else
# define __THROW
# define __NTH(fct)     fct
#endif

#endif /* _SYS_CDEFS_H_ */
/* $NetBSD: tree.h,v 1.20 2013/09/14 13:20:45 joerg Exp $ */
/* $OpenBSD: tree.h,v 1.13 2011/07/09 00:19:45 pirofti Exp $ */
/* Modified by Void Linux. */
/*
* Copyright 2002 Niels Provos <provos@citi.umich.edu>
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
*
* THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
* OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
* IN NO EVENT SHALL THE
 AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
* INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
* THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
* (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
* THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

#ifndef _SYS_TREE_H_
#define _SYS_TREE_H_

#ifdef __GNUC__
#define __GNUC_PREREQ__(x, y)      \
 ((__GNUC__ == (x) && __GNUC_MINOR__ >= (y)) ||   \
  (__GNUC__ > (x)))
#else
#define __GNUC_PREREQ__(x, y) 0
#endif

#if __GNUC_PREREQ__(2, 7) || defined(__lint__)
```

```
#define _sys_tree_h_unused __attribute__((__unused__))
#else
#define _sys_tree_h_unused /* delete */
#endif

/*
* This file defines data structures for different types of trees:
* splay trees and red-black trees.
*
* A splay tree is a self-organizing
 data structure.  Every operation
* on the tree causes a splay to happen.  The splay moves the requested
* node to the root of the tree and partly rebalances it.
*
* This has the benefit that request locality causes faster lookups as
* the requested nodes move to the top of the tree.  On the other hand,
* every lookup causes memory writes.
*
* The Balance Theorem bounds the total access time for m operations
* and n inserts on an initially empty tree as O((m + n)lg n).  The
* amortized cost for a sequence of m accesses to a splay tree is O(lg n);
*
* A red-black tree is a binary search tree with the node color as an
* extra attribute.  It fulfills a set of conditions:
* - every search path from the root to a leaf consists of the
*   same number of black nodes,
* - each red node (except for the root) has a black parent,
* - each leaf node is black.
*
* Every operation on a red-black tree is bounded as O(lg n).
* The maximum height of a red-black tree is 2lg (n+1).
 */

#define SPLAY_HEAD(name, type)      \
struct name {       \
 struct type *sph_root; /* root of the tree */   \
}

#define SPLAY_INITIALIZER(root)     \
 { NULL }

#define SPLAY_INIT(root) do {      \
 (root)->sph_root = NULL;     \
} while (/*CONSTCOND*/ 0)

#define SPLAY_ENTRY(type)      \
struct {       \
 struct type *spe_left; /* left element */   \
```

```
 struct type *spe_right; /* right element */   \
}

#define SPLAY_LEFT(elm, field)  (elm)->field.spe_left
#define SPLAY_RIGHT(elm, field)  (elm)->field.spe_right
#define SPLAY_ROOT(head)  (head)->sph_root
#define SPLAY_EMPTY(head)  (SPLAY_ROOT(head) == NULL)

/* SPLAY_ROTATE_{LEFT,RIGHT} expect that tmp hold SPLAY_{RIGHT,LEFT} */
#define SPLAY_ROTATE_RIGHT(head, tmp, field) do {   \
 SPLAY_LEFT((head)->sph_root, field) = SPLAY_RIGHT(tmp, field); \
 SPLAY_RIGHT(tmp, field) = (head)->sph_root;   \
 (head)->sph_root = tmp;      \
} while (/*CONSTCOND*/ 0)

#define SPLAY_ROTATE_LEFT(head, tmp, field) do {   \
 SPLAY_RIGHT((head)->sph_root,
 field) = SPLAY_LEFT(tmp, field); \
 SPLAY_LEFT(tmp, field) = (head)->sph_root;   \
 (head)->sph_root = tmp;      \
} while (/*CONSTCOND*/ 0)

#define SPLAY_LINKLEFT(head, tmp, field) do {    \
 SPLAY_LEFT(tmp, field) = (head)->sph_root;   \
 tmp = (head)->sph_root;      \
 (head)->sph_root = SPLAY_LEFT((head)->sph_root, field);  \
} while (/*CONSTCOND*/ 0)

#define SPLAY_LINKRIGHT(head, tmp, field) do {    \
 SPLAY_RIGHT(tmp, field) = (head)->sph_root;   \
 tmp = (head)->sph_root;      \
 (head)->sph_root = SPLAY_RIGHT((head)->sph_root, field); \
} while (/*CONSTCOND*/ 0)

#define SPLAY_ASSEMBLE(head, node, left, right, field) do {  \
 SPLAY_RIGHT(left, field) = SPLAY_LEFT((head)->sph_root, field); \
 SPLAY_LEFT(right, field) = SPLAY_RIGHT((head)->sph_root, field);\
 SPLAY_LEFT((head)->sph_root, field) = SPLAY_RIGHT(node, field); \
 SPLAY_RIGHT((head)->sph_root, field) = SPLAY_LEFT(node, field); \
} while (/*CONSTCOND*/ 0)

/* Generates prototypes and inline functions */

#define
 SPLAY_PROTOTYPE(name, type, field, cmp)    \
void name##_SPLAY(struct name *, struct type *);   \
void name##_SPLAY_MINMAX(struct name *, int);    \
struct type *name##_SPLAY_INSERT(struct name *, struct type *);  \
```

```
struct type *name##_SPLAY_REMOVE(struct name *, struct type *);  \
        \
/* Finds the node with the same key as elm */    \
static __inline struct type *      \
name##_SPLAY_FIND(struct name *head, struct type *elm)   \
{        \
 if (SPLAY_EMPTY(head))      \
  return(NULL);      \
 name##_SPLAY(head, elm);     \
 if ((cmp)(elm, (head)->sph_root) == 0)    \
  return (head->sph_root);    \
 return (NULL);       \
}        \
        \
static __inline _sys_tree_h_unused struct type *   \
name##_SPLAY_NEXT(struct name *head, struct type *elm)   \
{        \
 name##_SPLAY(head, elm);     \
 if (SPLAY_RIGHT(elm, field) != NULL) {    \
  elm = SPLAY_RIGHT(elm, field);    \
  while (SPLAY_LEFT(elm, field) != NULL) {  \
   elm = SPLAY_LEFT(elm, field);   \
  }       \
 }
 else       \
  elm = NULL;      \
 return (elm);       \
}        \
        \
static _sys_tree_h_unused __inline struct type *   \
name##_SPLAY_MIN_MAX(struct name *head, int val)   \
{        \
 name##_SPLAY_MINMAX(head, val);     \
       return (SPLAY_ROOT(head));     \
}

/* Main splay operation.
* Moves node close to the key of elm to top
*/
#define SPLAY_GENERATE(name, type, field, cmp)    \
struct type *       \
name##_SPLAY_INSERT(struct name *head, struct type *elm)  \
{        \
   if (SPLAY_EMPTY(head)) {      \
     SPLAY_LEFT(elm, field) = SPLAY_RIGHT(elm, field) = NULL; \
   } else {       \
     int __comp;       \
     name##_SPLAY(head, elm);     \
```

```
    __comp = (cmp)(elm, (head)->sph_root);   \
    if(__comp < 0) {      \
     SPLAY_LEFT(elm, field) = SPLAY_LEFT((head)->sph_root, field);\
     SPLAY_RIGHT(elm, field) = (head)->sph_root;  \
     SPLAY_LEFT((head)->sph_root, field) = NULL;  \
    } else if (__comp > 0) {     \
     SPLAY_RIGHT(elm,
 field) = SPLAY_RIGHT((head)->sph_root, field);\
     SPLAY_LEFT(elm, field) = (head)->sph_root;  \
     SPLAY_RIGHT((head)->sph_root, field) = NULL; \
    } else       \
     return ((head)->sph_root);    \
  }        \
  (head)->sph_root = (elm);      \
  return (NULL);       \
}        \
       \
struct type *        \
name##_SPLAY_REMOVE(struct name *head, struct type *elm)  \
{        \
 struct type *__tmp;      \
 if (SPLAY_EMPTY(head))      \
  return (NULL);      \
 name##_SPLAY(head, elm);     \
 if ((cmp)(elm, (head)->sph_root) == 0) {   \
  if (SPLAY_LEFT((head)->sph_root, field) == NULL) { \
   (head)->sph_root = SPLAY_RIGHT((head)->sph_root, field);\
  } else {      \
   __tmp = SPLAY_RIGHT((head)->sph_root, field); \
   (head)->sph_root = SPLAY_LEFT((head)->sph_root, field);\
   name##_SPLAY(head, elm);   \
   SPLAY_RIGHT((head)->sph_root, field) = __tmp; \
  }       \
  return (elm);      \
 }        \
 return (NULL);       \
}        \
       \
void         \
name##_SPLAY(struct
 name *head, struct type *elm)   \
{        \
 struct type __node, *__left, *__right, *__tmp;   \
 int __comp;       \
\
 SPLAY_LEFT(&__node, field) = SPLAY_RIGHT(&__node, field) = NULL;\
 __left = __right = &__node;     \
\
```

```
 while ((__comp = (cmp)(elm, (head)->sph_root)) != 0) {  \
  if (__comp < 0) {     \
   __tmp = SPLAY_LEFT((head)->sph_root, field); \
   if (__tmp == NULL)    \
    break;     \
   if ((cmp)(elm, __tmp) < 0){   \
    SPLAY_ROTATE_RIGHT(head, __tmp, field); \
    if (SPLAY_LEFT((head)->sph_root, field) == NULL)\
     break;    \
   }      \
   SPLAY_LINKLEFT(head, __right, field);  \
  } else if (__comp > 0) {    \
   __tmp = SPLAY_RIGHT((head)->sph_root, field); \
   if (__tmp == NULL)    \
    break;     \
   if ((cmp)(elm, __tmp) > 0){   \
    SPLAY_ROTATE_LEFT(head, __tmp, field); \
    if (SPLAY_RIGHT((head)->sph_root, field) == NULL)\
     break;    \
   }      \
   SPLAY_LINKRIGHT(head, __left, field);  \
  }       \
 }       \
 SPLAY_ASSEMBLE(head,
 &__node, __left, __right, field);  \
}        \
        \
/* Splay with either the minimum or the maximum element   \
* Used to find minimum or maximum element in tree.   \
*/        \
void name##_SPLAY_MINMAX(struct name *head, int __comp) \
{        \
 struct type __node, *__left, *__right, *__tmp;   \
\
 SPLAY_LEFT(&__node, field) = SPLAY_RIGHT(&__node, field) = NULL;\
 __left = __right = &__node;     \
\
 while (1) {       \
  if (__comp < 0) {     \
   __tmp = SPLAY_LEFT((head)->sph_root, field); \
   if (__tmp == NULL)    \
    break;     \
   if (__comp < 0){    \
    SPLAY_ROTATE_RIGHT(head, __tmp, field); \
    if (SPLAY_LEFT((head)->sph_root, field) == NULL)\
     break;    \
   }      \
   SPLAY_LINKLEFT(head, __right, field);  \
```

```
  } else if (__comp > 0) {    \
   __tmp = SPLAY_RIGHT((head)->sph_root, field); \
   if (__tmp == NULL)    \
    break;     \
   if (__comp > 0) {    \
    SPLAY_ROTATE_LEFT(head, __tmp, field); \
    if (SPLAY_RIGHT((head)->sph_root,
 field) == NULL)\
     break;    \
   }      \
   SPLAY_LINKRIGHT(head, __left, field);  \
  }       \
 }       \
 SPLAY_ASSEMBLE(head, &__node, __left, __right, field);  \
}

#define SPLAY_NEGINF -1
#define SPLAY_INF 1

#define SPLAY_INSERT(name, x, y) name##_SPLAY_INSERT(x, y)
#define SPLAY_REMOVE(name, x, y) name##_SPLAY_REMOVE(x, y)
#define SPLAY_FIND(name, x, y)  name##_SPLAY_FIND(x, y)
#define SPLAY_NEXT(name, x, y)  name##_SPLAY_NEXT(x, y)
#define SPLAY_MIN(name, x)  (SPLAY_EMPTY(x) ? NULL \
    : name##_SPLAY_MIN_MAX(x, SPLAY_NEGINF))
#define SPLAY_MAX(name, x)  (SPLAY_EMPTY(x) ? NULL \
    : name##_SPLAY_MIN_MAX(x, SPLAY_INF))

#define SPLAY_FOREACH(x, name, head)     \
 for ((x) = SPLAY_MIN(name, head);    \
      (x) != NULL;      \
      (x) = SPLAY_NEXT(name, head, x))

/* Macros that define a red-black tree */
#define RB_HEAD(name, type)      \
struct name {        \
 struct type *rbh_root; /* root of the tree */   \
}

#define RB_INITIALIZER(root)      \
 {
 NULL }

#define RB_INIT(root) do {      \
 (root)->rbh_root = NULL;     \
} while (/*CONSTCOND*/ 0)

#define RB_BLACK 0
```

```
#define RB_RED  1
#define RB_ENTRY(type)      \
struct {        \
 struct type *rbe_left;  /* left element */  \
 struct type *rbe_right;  /* right element */  \
 struct type *rbe_parent; /* parent element */  \
 int rbe_color;   /* node color */  \
}

#define RB_LEFT(elm, field)  (elm)->field.rbe_left
#define RB_RIGHT(elm, field)  (elm)->field.rbe_right
#define RB_PARENT(elm, field)  (elm)->field.rbe_parent
#define RB_COLOR(elm, field)  (elm)->field.rbe_color
#define RB_ROOT(head)   (head)->rbh_root
#define RB_EMPTY(head)   (RB_ROOT(head) == NULL)

#define RB_SET(elm, parent, field) do {     \
 RB_PARENT(elm, field) = parent;     \
 RB_LEFT(elm, field) = RB_RIGHT(elm, field) = NULL;  \
 RB_COLOR(elm, field) = RB_RED;     \
} while (/*CONSTCOND*/ 0)

#define RB_SET_BLACKRED(black, red, field) do {    \
 RB_COLOR(black, field) = RB_BLACK;    \
 RB_COLOR(red, field)
 = RB_RED;     \
} while (/*CONSTCOND*/ 0)

#ifndef RB_AUGMENT
#define RB_AUGMENT(x) do {} while (/*CONSTCOND*/ 0)
#endif

#define RB_ROTATE_LEFT(head, elm, tmp, field) do {   \
 (tmp) = RB_RIGHT(elm, field);     \
 if ((RB_RIGHT(elm, field) = RB_LEFT(tmp, field)) != NULL) { \
  RB_PARENT(RB_LEFT(tmp, field), field) = (elm);  \
 }       \
 RB_AUGMENT(elm);      \
 if ((RB_PARENT(tmp, field) = RB_PARENT(elm, field)) != NULL) { \
  if ((elm) == RB_LEFT(RB_PARENT(elm, field), field)) \
   RB_LEFT(RB_PARENT(elm, field), field) = (tmp); \
  else      \
   RB_RIGHT(RB_PARENT(elm, field), field) = (tmp); \
 } else       \
  (head)->rbh_root = (tmp);    \
 RB_LEFT(tmp, field) = (elm);     \
 RB_PARENT(elm, field) = (tmp);     \
 RB_AUGMENT(tmp);      \
```

```
 if ((RB_PARENT(tmp, field)))     \
  RB_AUGMENT(RB_PARENT(tmp, field));   \
} while (/*CONSTCOND*/ 0)

#define RB_ROTATE_RIGHT(head, elm, tmp, field) do {   \
 (tmp) = RB_LEFT(elm, field);     \
 if ((RB_LEFT(elm, field) = RB_RIGHT(tmp, field))
 != NULL) { \
  RB_PARENT(RB_RIGHT(tmp, field), field) = (elm);  \
 }        \
 RB_AUGMENT(elm);      \
 if ((RB_PARENT(tmp, field) = RB_PARENT(elm, field)) != NULL) { \
  if ((elm) == RB_LEFT(RB_PARENT(elm, field), field)) \
   RB_LEFT(RB_PARENT(elm, field), field) = (tmp); \
  else       \
   RB_RIGHT(RB_PARENT(elm, field), field) = (tmp); \
 } else        \
  (head)->rbh_root = (tmp);    \
 RB_RIGHT(tmp, field) = (elm);     \
 RB_PARENT(elm, field) = (tmp);     \
 RB_AUGMENT(tmp);      \
 if ((RB_PARENT(tmp, field)))     \
  RB_AUGMENT(RB_PARENT(tmp, field));   \
} while (/*CONSTCOND*/ 0)

/* Generates prototypes and inline functions */
#define RB_PROTOTYPE(name, type, field, cmp)    \
 RB_PROTOTYPE_INTERNAL(name, type, field, cmp,)
#define RB_PROTOTYPE_STATIC(name, type, field, cmp)   \
 RB_PROTOTYPE_INTERNAL(name, type, field, cmp, _sys_tree_h_unused static)
#define RB_PROTOTYPE_INTERNAL(name, type, field, cmp, attr)  \
attr void name##_RB_INSERT_COLOR(struct name *, struct
 type *);  \
attr void name##_RB_REMOVE_COLOR(struct name *, struct type *, struct type *);\
attr struct type *name##_RB_REMOVE(struct name *, struct type *); \
attr struct type *name##_RB_INSERT(struct name *, struct type *); \
attr struct type *name##_RB_FIND(struct name *, struct type *);  \
attr struct type *name##_RB_NFIND(struct name *, struct type *); \
attr struct type *name##_RB_NEXT(struct type *);   \
attr struct type *name##_RB_PREV(struct type *);   \
attr struct type *name##_RB_MINMAX(struct name *, int);   \
        \

/* Main rb operation.
* Moves node close to the key of elm to top
*/
#define RB_GENERATE(name, type, field, cmp)    \
 RB_GENERATE_INTERNAL(name, type, field, cmp,)
```

```
#define RB_GENERATE_STATIC(name, type, field, cmp)   \
 RB_GENERATE_INTERNAL(name, type, field, cmp, _sys_tree_h_unused static)
#define RB_GENERATE_INTERNAL(name, type, field, cmp, attr)  \
attr void       \
name##_RB_INSERT_COLOR(struct name *head, struct type *elm)  \
{       \
 struct type
 *parent, *gparent, *tmp;    \
 while ((parent = RB_PARENT(elm, field)) != NULL &&  \
     RB_COLOR(parent, field) == RB_RED) {   \
  gparent = RB_PARENT(parent, field);   \
  if (parent == RB_LEFT(gparent, field)) {  \
   tmp = RB_RIGHT(gparent, field);   \
   if (tmp && RB_COLOR(tmp, field) == RB_RED) { \
    RB_COLOR(tmp, field) = RB_BLACK; \
    RB_SET_BLACKRED(parent, gparent, field);\
    elm = gparent;    \
    continue;    \
   }      \
   if (RB_RIGHT(parent, field) == elm) {  \
    RB_ROTATE_LEFT(head, parent, tmp, field);\
    tmp = parent;    \
    parent = elm;    \
    elm = tmp;    \
   }      \
   RB_SET_BLACKRED(parent, gparent, field); \
   RB_ROTATE_RIGHT(head, gparent, tmp, field); \
  } else {      \
   tmp = RB_LEFT(gparent, field);   \
   if (tmp && RB_COLOR(tmp, field) == RB_RED) { \
    RB_COLOR(tmp, field) = RB_BLACK; \
    RB_SET_BLACKRED(parent, gparent, field);\
    elm = gparent;    \
    continue;    \
   }      \
   if (RB_LEFT(parent, field) == elm)
  {  \
    RB_ROTATE_RIGHT(head, parent, tmp, field);\
    tmp = parent;    \
    parent = elm;    \
    elm = tmp;    \
   }      \
   RB_SET_BLACKRED(parent, gparent, field); \
   RB_ROTATE_LEFT(head, gparent, tmp, field); \
  }       \
 }       \
 RB_COLOR(head->rbh_root, field) = RB_BLACK;   \
}       \
```

```
        \
attr void       \
name##_RB_REMOVE_COLOR(struct name *head, struct type *parent, struct type *elm) \
{       \
 struct type *tmp;      \
 while ((elm == NULL || RB_COLOR(elm, field) == RB_BLACK) && \
     elm != RB_ROOT(head)) {     \
  if (RB_LEFT(parent, field) == elm) {   \
   tmp = RB_RIGHT(parent, field);   \
   if (RB_COLOR(tmp, field) == RB_RED) {  \
    RB_SET_BLACKRED(tmp, parent, field); \
    RB_ROTATE_LEFT(head, parent, tmp, field);\
    tmp = RB_RIGHT(parent, field);  \
   }      \
   if ((RB_LEFT(tmp, field) == NULL ||  \
       RB_COLOR(RB_LEFT(tmp, field), field) == RB_BLACK) &&\
       (RB_RIGHT(tmp, field) == NULL ||  \
       RB_COLOR(RB_RIGHT(tmp,
 field), field) == RB_BLACK)) {\
    RB_COLOR(tmp, field) = RB_RED;  \
    elm = parent;    \
    parent = RB_PARENT(elm, field);  \
   } else {     \
    if (RB_RIGHT(tmp, field) == NULL || \
        RB_COLOR(RB_RIGHT(tmp, field), field) == RB_BLACK) {\
     struct type *oleft;  \
     if ((oleft = RB_LEFT(tmp, field)) \
         != NULL)   \
      RB_COLOR(oleft, field) = RB_BLACK;\
     RB_COLOR(tmp, field) = RB_RED; \
     RB_ROTATE_RIGHT(head, tmp, oleft, field);\
     tmp = RB_RIGHT(parent, field); \
    }     \
    RB_COLOR(tmp, field) = RB_COLOR(parent, field);\
    RB_COLOR(parent, field) = RB_BLACK; \
    if (RB_RIGHT(tmp, field))  \
     RB_COLOR(RB_RIGHT(tmp, field), field) = RB_BLACK;\
    RB_ROTATE_LEFT(head, parent, tmp, field);\
    elm = RB_ROOT(head);   \
    break;     \
   }      \
  } else {      \
   tmp = RB_LEFT(parent, field);   \
   if (RB_COLOR(tmp, field) == RB_RED) {  \
    RB_SET_BLACKRED(tmp, parent, field); \
    RB_ROTATE_RIGHT(head, parent, tmp, field);\
    tmp
```

```
 = RB_LEFT(parent, field);  \
  }      \
  if ((RB_LEFT(tmp, field) == NULL ||  \
      RB_COLOR(RB_LEFT(tmp, field), field) == RB_BLACK) &&\
      (RB_RIGHT(tmp, field) == NULL ||  \
      RB_COLOR(RB_RIGHT(tmp, field), field) == RB_BLACK)) {\
    RB_COLOR(tmp, field) = RB_RED;  \
    elm = parent;    \
    parent = RB_PARENT(elm, field);  \
   } else {     \
    if (RB_LEFT(tmp, field) == NULL || \
        RB_COLOR(RB_LEFT(tmp, field), field) == RB_BLACK) {\
     struct type *oright;  \
     if ((oright = RB_RIGHT(tmp, field)) \
         != NULL)   \
      RB_COLOR(oright, field) = RB_BLACK;\
     RB_COLOR(tmp, field) = RB_RED; \
     RB_ROTATE_LEFT(head, tmp, oright, field);\
     tmp = RB_LEFT(parent, field); \
    }     \
    RB_COLOR(tmp, field) = RB_COLOR(parent, field);\
    RB_COLOR(parent, field) = RB_BLACK; \
    if (RB_LEFT(tmp, field))  \
     RB_COLOR(RB_LEFT(tmp, field), field) = RB_BLACK;\
    RB_ROTATE_RIGHT(head, parent, tmp, field);\
    elm = RB_ROOT(head);   \
    break;     \
   }      \
  }       \
 }        \
 if
 (elm)       \
  RB_COLOR(elm, field) = RB_BLACK;   \
}         \
         \
attr struct type *       \
name##_RB_REMOVE(struct name *head, struct type *elm)   \
{         \
 struct type *child, *parent, *old = elm;   \
 int color;       \
 if (RB_LEFT(elm, field) == NULL)    \
  child = RB_RIGHT(elm, field);    \
 else if (RB_RIGHT(elm, field) == NULL)    \
  child = RB_LEFT(elm, field);    \
 else {        \
  struct type *left;     \
  elm = RB_RIGHT(elm, field);    \
  while ((left = RB_LEFT(elm, field)) != NULL)  \
```

```
 elm = left;     \
child = RB_RIGHT(elm, field);    \
parent = RB_PARENT(elm, field);    \
color = RB_COLOR(elm, field);    \
if (child)      \
 RB_PARENT(child, field) = parent;  \
if (parent) {      \
 if (RB_LEFT(parent, field) == elm)  \
  RB_LEFT(parent, field) = child;  \
 else      \
  RB_RIGHT(parent, field) = child; \
 RB_AUGMENT(parent);    \
} else       \
 RB_ROOT(head)
= child;    \
if (RB_PARENT(elm, field) == old)   \
 parent = elm;     \
(elm)->field = (old)->field;    \
if (RB_PARENT(old, field)) {    \
 if (RB_LEFT(RB_PARENT(old, field), field) == old)\
  RB_LEFT(RB_PARENT(old, field), field) = elm;\
 else      \
  RB_RIGHT(RB_PARENT(old, field), field) = elm;\
 RB_AUGMENT(RB_PARENT(old, field));  \
} else       \
 RB_ROOT(head) = elm;    \
RB_PARENT(RB_LEFT(old, field), field) = elm;  \
if (RB_RIGHT(old, field))    \
 RB_PARENT(RB_RIGHT(old, field), field) = elm; \
if (parent) {      \
 left = parent;     \
 do {      \
  RB_AUGMENT(left);   \
 } while ((left = RB_PARENT(left, field)) != NULL); \
}       \
goto color;      \
}       \
parent = RB_PARENT(elm, field);     \
color = RB_COLOR(elm, field);     \
if (child)       \
 RB_PARENT(child, field) = parent;   \
if (parent) {       \
 if (RB_LEFT(parent, field) == elm)   \
  RB_LEFT(parent, field) = child;   \
 else       \
  RB_RIGHT(parent,
field) = child;  \
 RB_AUGMENT(parent);     \
```

```
 } else       \
  RB_ROOT(head) = child;    \
color:       \
 if (color == RB_BLACK)     \
  name##_RB_REMOVE_COLOR(head, parent, child);  \
 return (old);      \
}       \
       \
/* Inserts a node into the RB tree */    \
attr struct type *      \
name##_RB_INSERT(struct name *head, struct type *elm)   \
{       \
 struct type *tmp;     \
 struct type *parent = NULL;    \
 int comp = 0;      \
 tmp = RB_ROOT(head);     \
 while (tmp) {      \
  parent = tmp;     \
  comp = (cmp)(elm, parent);   \
  if (comp < 0)     \
   tmp = RB_LEFT(tmp, field);   \
  else if (comp > 0)    \
   tmp = RB_RIGHT(tmp, field);   \
  else      \
   return (tmp);    \
 }       \
 RB_SET(elm, parent, field);    \
 if (parent != NULL) {     \
  if (comp < 0)     \
   RB_LEFT(parent, field) = elm;   \
  else      \
   RB_RIGHT(parent, field) = elm;   \
  RB_AUGMENT(parent);    \
 } else       \
  RB_ROOT(head) = elm;    \
 name##_RB_INSERT_COLOR(head,
 elm);   \
 return (NULL);      \
}       \
       \
/* Finds the node with the same key as elm */   \
attr struct type *      \
name##_RB_FIND(struct name *head, struct type *elm)   \
{       \
 struct type *tmp = RB_ROOT(head);   \
 int comp;      \
 while (tmp) {      \
  comp = cmp(elm, tmp);    \
```

```
 if (comp < 0)      \
  tmp = RB_LEFT(tmp, field);   \
 else if (comp > 0)     \
  tmp = RB_RIGHT(tmp, field);   \
 else       \
  return (tmp);     \
 }       \
 return (NULL);       \
}        \
        \
/* Finds the first node greater than or equal to the search key */ \
attr struct type *       \
name##_RB_NFIND(struct name *head, struct type *elm)   \
{        \
 struct type *tmp = RB_ROOT(head);    \
 struct type *res = NULL;     \
 int comp;       \
 while (tmp) {       \
  comp = cmp(elm, tmp);     \
  if (comp < 0) {      \
   res = tmp;     \
   tmp = RB_LEFT(tmp, field);   \
  }       \
  else if (comp > 0)     \
   tmp =
 RB_RIGHT(tmp, field);   \
  else       \
   return (tmp);     \
 }       \
 return (res);       \
}        \
        \
/* ARGSUSED */       \
attr struct type *       \
name##_RB_NEXT(struct type *elm)     \
{        \
 if (RB_RIGHT(elm, field)) {     \
  elm = RB_RIGHT(elm, field);    \
  while (RB_LEFT(elm, field))    \
   elm = RB_LEFT(elm, field);   \
 } else {       \
  if (RB_PARENT(elm, field) &&    \
      (elm == RB_LEFT(RB_PARENT(elm, field), field))) \
   elm = RB_PARENT(elm, field);   \
  else {       \
   while (RB_PARENT(elm, field) &&   \
       (elm == RB_RIGHT(RB_PARENT(elm, field), field)))\
    elm = RB_PARENT(elm, field);  \
```

```
   elm = RB_PARENT(elm, field);   \
  }       \
 }       \
 return (elm);       \
}        \
        \
/* ARGSUSED */       \
attr struct type *       \
name##_RB_PREV(struct type *elm)     \
{        \
 if (RB_LEFT(elm, field)) {     \
  elm = RB_LEFT(elm, field);    \
  while (RB_RIGHT(elm, field))    \
   elm = RB_RIGHT(elm, field);   \
 }
 else {       \
  if (RB_PARENT(elm, field) &&    \
      (elm == RB_RIGHT(RB_PARENT(elm, field), field))) \
   elm = RB_PARENT(elm, field);   \
  else {       \
   while (RB_PARENT(elm, field) &&   \
       (elm == RB_LEFT(RB_PARENT(elm, field), field)))\
    elm = RB_PARENT(elm, field);  \
   elm = RB_PARENT(elm, field);   \
  }       \
 }       \
 return (elm);       \
}        \
        \
attr struct type *       \
name##_RB_MINMAX(struct name *head, int val)    \
{        \
 struct type *tmp = RB_ROOT(head);    \
 struct type *parent = NULL;     \
 while (tmp) {       \
  parent = tmp;      \
  if (val < 0)      \
   tmp = RB_LEFT(tmp, field);   \
  else       \
   tmp = RB_RIGHT(tmp, field);   \
 }       \
 return (parent);      \
}

#define RB_NEGINF -1
#define RB_INF 1

#define RB_INSERT(name, x, y) name##_RB_INSERT(x, y)
```

```
#define RB_REMOVE(name, x, y) name##_RB_REMOVE(x, y)
#define RB_FIND(name, x, y) name##_RB_FIND(x, y)
#define RB_NFIND(name, x, y) name##_RB_NFIND(x,
 y)
#define RB_NEXT(name, x, y) name##_RB_NEXT(y)
#define RB_PREV(name, x, y) name##_RB_PREV(y)
#define RB_MIN(name, x)  name##_RB_MINMAX(x, RB_NEGINF)
#define RB_MAX(name, x)  name##_RB_MINMAX(x, RB_INF)

#define RB_FOREACH(x, name, head)     \
 for ((x) = RB_MIN(name, head);     \
      (x) != NULL;      \
      (x) = name##_RB_NEXT(x))

#define RB_FOREACH_FROM(x, name, y)     \
 for ((x) = (y);       \
     ((x) != NULL) && ((y) = name##_RB_NEXT(x), (x) != NULL); \
      (x) = (y))

#define RB_FOREACH_SAFE(x, name, head, y)    \
 for ((x) = RB_MIN(name, head);     \
     ((x) != NULL) && ((y) = name##_RB_NEXT(x), (x) != NULL); \
      (x) = (y))

#define RB_FOREACH_REVERSE(x, name, head)    \
 for ((x) = RB_MAX(name, head);     \
      (x) != NULL;      \
      (x) = name##_RB_PREV(x))

#define RB_FOREACH_REVERSE_FROM(x, name, y)    \
 for ((x) = (y);       \
     ((x) != NULL) && ((y) = name##_RB_PREV(x), (x) != NULL); \
      (x) = (y))

#define RB_FOREACH_REVERSE_SAFE(x, name,
 head, y)   \
 for ((x) = RB_MAX(name, head);     \
     ((x) != NULL) && ((y) = name##_RB_PREV(x), (x) != NULL); \
      (x) = (y))

#endif /* _SYS_TREE_H_ */
MIT
# Contributor: Wen Heping <wenhepingalpine@sohu.com>
# Maintainer: Wen Heping <wenhepingalpine@sohu.com>
pkgname=perl-software-license
pkgver=0.104007
pkgrel=0
# _pkgreal is used by apkbuild-cpan to find modules at MetaCpan
```

```
_pkgreal=Software-License
pkgdesc="packages that provide templated software licenses"
url="https://metacpan.org/release/Software-License/"
arch="noarch"
license="GPL-1.0-or-later OR Artistic-1.0-Perl"
depends="perl perl-data-section perl-text-template"
checkdepends="perl-try-tiny"
subpackages="$pkgname-doc"
source="https://cpan.metacpan.org/authors/id/L/LE/LEONT/Software-License-$pkgver.tar.gz"
builddir="$srcdir/$_pkgreal-$pkgver"

build() {
 export CFLAGS=$(perl -MConfig -E 'say $Config{ccflags}')
 PERL_MM_USE_DEFAULT=1 perl -I. Makefile.PL \
  INSTALLDIRS=vendor \
  NO_PACKLIST=1 \
  NO_PERLLOCAL=1
 make
}

check() {
 export CFLAGS=$(perl -MConfig -E 'say $Config{ccflags}')
 make test
}

package() {
 make DESTDIR="$pkgdir" install
}

sha512sums="
12d75e9583b3013d9b4a282467f1ac80ab6b7f3251926d66591d01404489b528f22adc396dfd4528a0f0ca650f0eed6d
9c959e69eace2169c6ed1cfffe5277e4
  Software-License-0.104007.tar.gz
"
```

1.126 smithy-go 1.22.5

1.126.1 Available under license :

```
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
```

copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,

including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of

this
License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside

or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

1.127 alpine-baselayout 3.6.8-r1

1.127.1 Available under license :

Note that many files in here are not copyrighted/licensed, so they are
actually in the public domain.

Otherwise:
Copyright 1996-2013 Gentoo Foundation

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License
instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it

in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the
Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in

themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component

itself accompanies the executable.

If distribution of executable or object code is made by offering
access to copy from a designated place,
 then offering equivalent
access to copy the source code from the same place counts as
distribution of the source code, even though third parties are not
compelled to copy the source along with the object code.

 4. You may not copy, modify, sublicense, or distribute the Program
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense or distribute the Program is
void, and will automatically terminate your rights under this License.
However, parties who have received copies, or rights, from you under
this License will not have their licenses terminated so long as such
parties remain in full compliance.

 5. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Program or its derivative works. These actions are
prohibited by law if you do not accept this License. Therefore, by
modifying or distributing the Program (or any work based on the
Program),
 you indicate your acceptance of this License to do so, and
all its terms and conditions for copying, distributing or modifying
the Program or works based on it.

 6. Each time you redistribute the Program (or any work based on the
Program), the recipient automatically receives a license from the
original licensor to copy, distribute or modify the Program subject to
these terms and conditions. You may not impose any further
restrictions on the recipients' exercise of the rights granted herein.
You are not responsible for enforcing compliance by third parties to
this License.

 7. If, as a consequence of a court judgment or allegation of patent
infringement or for any other reason (not limited to patent issues),
conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this
License
 and any other pertinent obligations, then as a consequence you
may not distribute the Program at all. For example, if a patent
license would not permit royalty-free redistribution of the Program by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through
that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present
version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals

of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software
generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT
LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you
can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type
`show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit
linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

1.128 mime-type 1.4.9

1.128.1 Available under license :

Copyright (c) 2013-present Contentful GmbH

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.129 libncursesw 6.5_p20241006-r3

1.129.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
# ncurses 6.5 - patch 20241006 - Thomas E. Dickey
#
# -------------------------------------------------------------------------
#
# Ncurses 6.5 is at
#   https://invisible-island.net/archives/ncurses/
#   https://invisible-mirror.net/archives/ncurses/
#   https://ftp.gnu.org/gnu/ncurses/
#
# Patches for ncurses 6.5 can be found at
#   https://invisible-island.net/archives/ncurses/6.5
#   https://invisible-mirror.net/archives/ncurses/6.5
#
# -------------------------------------------------------------------------
# https://invisible-island.net/archives/ncurses/6.5/ncurses-6.5-20241006.patch.gz
# patch by Thomas E. Dickey <dickey@invisible-island.net>
# created  Sun Oct  6 23:44:01 UTC 2024
# -------------------------------------------------------------------------
# NEWS                    |   6 +++
# VERSION                 |   2 -
# c++/cursesf.cc          |   6 +--
# c++/cursesf.h
```

```
                | 6 +--
# c++/cursesm.cc              | 6 +--
# c++/cursesm.h               | 6 +--
# c++/cursesp.cc              | 6 +--
# c++/cursespad.cc            | 6 +--
# c++/cursslk.cc              | 12 +++----
# c++/cursslk.h               | 6 +--
# dist.mk                     | 4 +-
# misc/terminfo.src           | 23 ++++++++++--
# ncurses/base/lib_screen.c   | 4 +-
# ncurses/base/new_pair.c     | 4 +-
# ncurses/curses.priv.h       | 4 +-
# ncurses/new_pair.h          | 4 +-
# ncurses/tinfo/trim_sgr0.c   | 7 ++--
# ncurses/tty/lib_twait.c     | 6 +--
# package/debian-mingw/changelog   | 4 +-
# package/debian-mingw64/changelog | 4 +-
# package/debian/changelog    | 4 +-
# package/mingw-ncurses.nsi   | 4 +-
# package/mingw-ncurses.spec  | 2 -
# package/ncurses.spec        | 2 -
# package/ncursest.spec       |
  2 -
# test/blue.c                 | 10 +++---
# test/bs.c                   | 8 ++--
# test/cardfile.c             | 12 +++----
# test/chgat.c                | 6 +--
# test/clip_printw.c          | 8 ++--
# test/color_name.h           | 6 +--
# test/demo_defkey.c          | 4 +-
# test/demo_forms.c           | 22 ++++++-------
# test/demo_menus.c           | 32 ++++++++++---------
# test/demo_new_pair.c        | 4 +-
# test/demo_panels.c          | 16 ++++-----
# test/demo_termcap.c         | 18 +++++-----
# test/demo_terminfo.c        | 18 +++++-----
# test/dots.c                 | 6 +--
# test/dots_mvcur.c           | 6 +--
# test/dots_termcap.c         | 8 ++--
# test/dup_field.c            | 14 ++++----
# test/filter.c               | 6 +--
# test/form_driver_w.c        | 6 +--
# test/gdc.c                  | 10 +++---
# test/inch_wide.c
              | 6 +--
# test/inchs.c                | 6 +--
# test/ins_wide.c             | 6 +--
# test/insdelln.c             | 8 ++--
```

```
# test/inserts.c                |   6 +--
# test/knight.c                 |   7 ++--
# test/list_keys.c              |   8 ++--
# test/move_field.c             |  18 +++++-----
# test/movewindow.c             |  16 ++++-----
# test/ncurses.c                |  61 ++++++++++++++++++++----------------
# test/padview.c                |  12 +++++----
# test/parse_rgb.h              |   6 +--
# test/picsmap.c                |  14 ++++++----
# test/popup_msg.c              |   8 ++--
# test/popup_msg.h              |   6 +--
# test/railroad.c               |   6 +--
# test/rain.c                   |  20 ++++++------
# test/redraw.c                 |   6 +--
# test/savescreen.c             |  14 ++++++----
# test/tclock.c                 |   4 +-
# test/test.priv.h
                |  10 +++++---
# test/test_add_wchstr.c        |   6 +--
# test/test_addchstr.c          |   6 +--
# test/test_addstr.c            |   6 +--
# test/test_addwstr.c           |   6 +--
# test/test_endwin.c            |   6 +--
# test/test_get_wstr.c          |   8 ++--
# test/test_getstr.c            |   8 ++--
# test/test_instr.c             |   8 ++--
# test/test_inwstr.c            |   8 ++--
# test/test_mouse.c             |   4 +-
# test/test_opaque.c            |   8 ++--
# test/test_sgr.c               |  26 +++++++--------
# test/test_tparm.c             |  12 +++++----
# test/test_vidputs.c           |   6 +--
# test/testcurs.c               |   8 ++--
# test/testscanw.c              |   6 +--
# test/view.c                   |  21 +++++-------
# 83 files changed, 392 insertions(+), 369 deletions(-)
# ----------------------------------------------------------------------------
Index: NEWS
Prereq:
  1.4185
--- ncurses-6.5-20240928+/NEWS 2024-09-28 20:27:44.000000000 +0000
+++ ncurses-6.5-20241006/NEWS 2024-10-06 08:53:45.000000000 +0000
@@ -26,7 +26,7 @@
-- sale, use or other dealings in this Software without prior written        --
-- authorization.                                                           --
--------------------------------------------------------------------------------
--- $Id: NEWS,v 1.4185 2024/09/28 20:27:44 tom Exp $
+-- $Id: NEWS,v 1.4188 2024/10/06 08:53:45 tom Exp $
```

```
--------------------------------------------------------------------------------

This is a log of changes that ncurses has gone through since Zeyd started
@@ -46,6 +46,10 @@
Changes through 1.9.9e did not credit all contributions;
it is not possible to add this information.

+20241006
+ + fixes for compiler warnings/cppcheck.
+ + use xterm+alt+title in wezterm -TD
+
20240928
 + improve error-message from infocmp when a terminal entry cannot be
   opened (patch by Branden Robinson).
Index:
 VERSION
--- ncurses-6.5-20240928+/VERSION 2024-09-28 09:53:21.000000000 +0000
+++ ncurses-6.5-20241006/VERSION 2024-10-06 08:53:45.000000000 +0000
@@ -1 +1 @@
-5:0:10 6.5 20240928
+5:0:10 6.5 20241006
Index: c++/cursesf.cc
Prereq:  1.26
--- ncurses-6.5-20240928+/c++/cursesf.cc 2021-04-17 18:11:08.000000000 +0000
+++ ncurses-6.5-20241006/c++/cursesf.cc 2024-10-05 22:47:12.000000000 +0000
@@ -1,6 +1,6 @@
// * this is for making emacs happy: -*-Mode: C++;-*-
/****************************************************************************
- * Copyright 2019-2020,2021 Thomas E. Dickey                                *
+ * Copyright 2019-2021,2024 Thomas E. Dickey                                *
 * Copyright 1998-2005,2011 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -36,7 +36,7 @@
#include "cursesf.h"
#include "cursesapp.h"

-MODULE_ID("$Id: cursesf.cc,v 1.26 2021/04/17 18:11:08 tom Exp $")
+MODULE_ID("$Id: cursesf.cc,v 1.27 2024/10/05 22:47:12 tom Exp $")

NCursesFormField::~NCursesFormField () THROWS(NCursesException)
{
@@ -76,7 +76,7 @@

void NCursesForm::setDefaultAttributes()
{
-  NCursesApplication* S = NCursesApplication::getApplication();
+  const NCursesApplication* S = NCursesApplication::getApplication();
```

```
 int n = count();
 if (n > 0) {
Index: c++/cursesf.h
Prereq:  1.39
--- ncurses-6.5-20240928+/c++/cursesf.h 2022-08-20 20:52:15.000000000 +0000
+++ ncurses-6.5-20241006/c++/cursesf.h 2024-10-05 22:47:12.000000000 +0000
@@ -1,7 +1,7 @@
// * This makes emacs happy -*-Mode: C++;-*-
// vile:cppmode
/****************************************************************************
- * Copyright 2019-2021,2022 Thomas E. Dickey                                *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                                *
 * Copyright 1998-2012,2014 Free Software
 Foundation, Inc.                *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -33,7 +33,7 @@
 *   Author: Juergen Pfeifer, 1997                                          *
 ****************************************************************************/

-// $Id: cursesf.h,v 1.39 2022/08/20 20:52:15 tom Exp $
+// $Id: cursesf.h,v 1.40 2024/10/05 22:47:12 tom Exp $

#ifndef NCURSES_CURSESF_H_incl
#define NCURSES_CURSESF_H_incl 1
@@ -384,7 +384,7 @@
  }

  inline void *get_user() {
-    UserHook* uptr = reinterpret_cast<UserHook*>(::form_userptr (form));
+    const UserHook* uptr = reinterpret_cast<UserHook*>(::form_userptr (form));
    assert (uptr != 0 && uptr->m_back==this && uptr->m_owner==form);
    return uptr->m_user;
  }
Index: c++/cursesm.cc
Prereq:  1.27
--- ncurses-6.5-20240928+/c++/cursesm.cc 2021-04-17 18:11:08.000000000 +0000
+++ ncurses-6.5-20241006/c++/cursesm.cc 2024-10-05
 22:47:12.000000000 +0000
@@ -1,6 +1,6 @@
// * this is for making emacs happy: -*-Mode: C++;-*-
/****************************************************************************
- * Copyright 2019-2020,2021 Thomas E. Dickey                                *
+ * Copyright 2019-2021,2024 Thomas E. Dickey                                *
 * Copyright 1998-2011,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
```

```
@@ -36,7 +36,7 @@
#include "cursesm.h"
#include "cursesapp.h"

-MODULE_ID("$Id: cursesm.cc,v 1.27 2021/04/17 18:11:08 tom Exp $")
+MODULE_ID("$Id: cursesm.cc,v 1.28 2024/10/05 22:47:12 tom Exp $")

NCursesMenuItem::~NCursesMenuItem() THROWS(NCursesException)
{
@@ -168,7 +168,7 @@
void
NCursesMenu::setDefaultAttributes()
{
-  NCursesApplication* S = NCursesApplication::getApplication();
+
  const NCursesApplication* S = NCursesApplication::getApplication();
  if (S) {
    ::set_menu_fore(menu, S->foregrounds());
    ::set_menu_back(menu, S->backgrounds());
Index: c++/cursesm.h
Prereq:  1.35
--- ncurses-6.5-20240928+/c++/cursesm.h 2022-08-20 20:52:15.000000000 +0000
+++ ncurses-6.5-20241006/c++/cursesm.h 2024-10-05 22:47:12.000000000 +0000
@@ -1,6 +1,6 @@
// * This makes emacs happy -*-Mode: C++;-*-
/****************************************************************************
- * Copyright 2019-2020,2022 Thomas E. Dickey                                *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                                *
 * Copyright 1998-2012,2014 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -32,7 +32,7 @@
 *   Author: Juergen Pfeifer, 1997                                          *
 ****************************************************************************/

-// $Id: cursesm.h,v 1.35 2022/08/20 20:52:15 tom Exp $
+// $Id: cursesm.h,v 1.36 2024/10/05 22:47:12 tom Exp $

#ifndef NCURSES_CURSESM_H_incl
#define NCURSES_CURSESM_H_incl 1
@@ -245,7 +245,7 @@
  }

  inline void *get_user() {
-    UserHook* uptr = STATIC_CAST(UserHook*)(::menu_userptr (menu));
+    const UserHook* uptr = STATIC_CAST(UserHook*)(::menu_userptr (menu));
    assert (uptr != 0 && uptr->m_back==this && uptr->m_owner==menu);
    return uptr->m_user;
```

```
  }
Index: c++/cursesp.cc
Prereq:  1.27
--- ncurses-6.5-20240928+/c++/cursesp.cc 2020-02-02 23:34:34.000000000 +0000
+++ ncurses-6.5-20241006/c++/cursesp.cc 2024-10-05 22:47:12.000000000 +0000
@@ -1,6 +1,6 @@
// * this is for making emacs happy: -*-Mode: C++;-*-
/****************************************************************************
- * Copyright 2019,2020 Thomas E. Dickey                                     *
+ * Copyright 2019-2020,2024
 Thomas E. Dickey                                *
 * Copyright 1998-2003,2005 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -35,7 +35,7 @@
#include "internal.h"
#include "cursesp.h"

-MODULE_ID("$Id: cursesp.cc,v 1.27 2020/02/02 23:34:34 tom Exp $")
+MODULE_ID("$Id: cursesp.cc,v 1.28 2024/10/05 22:47:12 tom Exp $")

NCursesPanel* NCursesPanel::dummy = static_cast<NCursesPanel*>(0);

@@ -64,7 +64,7 @@
void
NCursesPanel::redraw()
{
-  PANEL *pan;
+  const PANEL *pan;

  pan = ::panel_above(NULL);
  while (pan) {
Index: c++/cursespad.cc
Prereq:  1.18
--- ncurses-6.5-20240928+/c++/cursespad.cc 2020-02-02 23:34:34.000000000 +0000
+++ ncurses-6.5-20241006/c++/cursespad.cc 2024-10-05 22:47:12.000000000 +0000
@@ -1,6 +1,6 @@
// * this is for making emacs happy: -*-Mode: C++;-*-
/****************************************************************************
-
 * Copyright 2020 Thomas E. Dickey                                          *
+ * Copyright 2020,2024 Thomas E. Dickey                                     *
 * Copyright 1999-2012,2013 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -36,7 +36,7 @@

#include <cursesw.h>
```

```
-MODULE_ID("$Id: cursespad.cc,v 1.18 2020/02/02 23:34:34 tom Exp $")
+MODULE_ID("$Id: cursespad.cc,v 1.19 2024/10/05 22:47:12 tom Exp $")

NCursesPad::NCursesPad(int nlines, int ncols)
  : NCursesWindow(),
@@ -221,7 +221,7 @@
void NCursesFramedPad::OnOperation(int pad_req)
{
  (void) pad_req;
-  NCursesWindow* W = Win();
+  const NCursesWindow* W = Win();
  NCursesWindow* W2 = getWindow();

  if ((static_cast<NCursesWindow*>(0) != W) && (static_cast<NCursesWindow*>(0) != W2)) {
Index: c++/cursslk.cc
Prereq:
  1.22
--- ncurses-6.5-20240928+/c++/cursslk.cc 2024-06-15 21:07:30.000000000 +0000
+++ ncurses-6.5-20241006/c++/cursslk.cc 2024-10-05 19:36:22.000000000 +0000
@@ -35,10 +35,10 @@
#include "internal.h"
#include "cursesapp.h"

-MODULE_ID("$Id: cursslk.cc,v 1.22 2024/06/15 21:07:30 tom Exp $")
+MODULE_ID("$Id: cursslk.cc,v 1.23 2024/10/05 19:36:22 tom Exp $")

Soft_Label_Key_Set::Soft_Label_Key&
-  Soft_Label_Key_Set::Soft_Label_Key::operator=(char *text)
+  Soft_Label_Key_Set::Soft_Label_Key::operator=(const char *text)
{
  delete[] label;
  size_t need = 1 + ::strlen(text);
@@ -111,11 +111,11 @@

void Soft_Label_Key_Set::activate_label(int i, bool bf) {
  if (!b_attrInit) {
-    NCursesApplication* A = NCursesApplication::getApplication();
+    const NCursesApplication* A = NCursesApplication::getApplication();
    if (A) attrset(A->labels());
    b_attrInit = TRUE;
  }
-  Soft_Label_Key& K = (*this)[i];
+  const Soft_Label_Key& K = (*this)[i];
  if (ERR==::slk_set(K.num,bf?K.label:"",K.format))
     Error("slk_set");
  noutrefresh();
@@ -124,12 +124,12 @@
```

```
void Soft_Label_Key_Set::activate_labels(bool bf)
{
  if (!b_attrInit) {
-    NCursesApplication* A = NCursesApplication::getApplication();
+    const NCursesApplication* A = NCursesApplication::getApplication();
    if (A) attrset(A->labels());
    b_attrInit = TRUE;
  }
  for(int i=1; i <= num_labels; i++) {
-    Soft_Label_Key& K = (*this)[i];
+    const Soft_Label_Key& K = (*this)[i];
    if (ERR==::slk_set(K.num,bf?K.label:"",K.format))
      Error("slk_set");
  }
Index: c++/cursslk.h
Prereq:  1.19
--- ncurses-6.5-20240928+/c++/cursslk.h 2021-04-17 18:11:08.000000000 +0000
+++ ncurses-6.5-20241006/c++/cursslk.h 2024-10-05 22:47:12.000000000 +0000
@@ -1,7 +1,7 @@
// * this is for making emacs happy: -*-Mode: C++;-*-
// vile:cppmode
/****************************************************************************
- * Copyright 2019-2020,2021 Thomas E. Dickey                                *
+ * Copyright 2019-2021,2024 Thomas E. Dickey                                *
 * Copyright 1998-2003,2005 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -33,7 +33,7 @@
 *   Author: Juergen Pfeifer, 1997                                          *
 ****************************************************************************/

-// $Id: cursslk.h,v 1.19 2021/04/17 18:11:08 tom Exp $
+// $Id: cursslk.h,v 1.20 2024/10/05 22:47:12 tom Exp $

#ifndef NCURSES_CURSSLK_H_incl
#define NCURSES_CURSSLK_H_incl
@@ -62,7 +62,7 @@

  public:
    // Set the text of the Label
-    Soft_Label_Key& operator=(char *text);
+    Soft_Label_Key& operator=(const char *text);

    // Set the Justification of the Label
    Soft_Label_Key& operator=(Justification just) {
Index: dist.mk
Prereq:  1.1634
```

```
--- ncurses-6.5-20240928+/dist.mk 2024-09-28
 09:53:21.000000000 +0000
+++ ncurses-6.5-20241006/dist.mk 2024-10-06 08:53:45.000000000 +0000
@@ -26,7 +26,7 @@
# use or other dealings in this Software without prior written               #
# authorization.                                                             #
##############################################################################
-# $Id: dist.mk,v 1.1634 2024/09/28 09:53:21 tom Exp $
+# $Id: dist.mk,v 1.1636 2024/10/06 08:53:45 tom Exp $
# Makefile for creating ncurses distributions.
#
# This only needs to be used directly as a makefile by developers, but
@@ -38,7 +38,7 @@
# These define the major/minor/patch versions of ncurses.
NCURSES_MAJOR = 6
NCURSES_MINOR = 5
-NCURSES_PATCH = 20240928
+NCURSES_PATCH = 20241006

# We don't append the patch to the version, since this only applies to releases
VERSION = $(NCURSES_MAJOR).$(NCURSES_MINOR)
Index: misc/terminfo.src
--- ncurses-6.5-20240928+/misc/terminfo.src 2024-09-07 16:23:31.000000000
 +0000
+++ ncurses-6.5-20241006/misc/terminfo.src 2024-10-05 16:04:17.000000000 +0000
@@ -6,8 +6,8 @@
# Report bugs and new terminal descriptions to
# bug-ncurses@gnu.org
#
-# $Revision: 1.1150 $
-# $Date: 2024/09/07 16:23:31 $
+# $Revision: 1.1153 $
+# $Date: 2024/10/05 16:04:17 $
#
# The original header is preserved below for reference.  It is noted that there
# is a "newer" version which differs in some cosmetic details (but actually
@@ -8060,6 +8060,17 @@
# "wezterm is a terminal emulator with support for modern features
#  such as fonts with ligatures, hyperlinks, tabs and multiple windows."
#
+# The documentation bears mention.  It refers to the "ANSI" standard and
+#  https://wezfurlong.org/wezterm/what-is-a-terminal.html#ansi-and-ecma-48
+# X3.64 (withdrawn long ago).  A related website
+# https://github.com/wez/ecma48
+# states that ECMA-48 was issued in 1979 and not revised since.  Actually that
+# was the second revision; the fifth revision in 1991 is current.  The source
+#
```

```
 code refers to the second revision in a half-dozen places.  Further, there
+# are three times as many references to Wikipedia as to xterm's documentation.
+# The git commit comments in several instances hint at an incomplete reading
+# of the relevant standards.
+#
# wezterm-20240203-110809-5046fc22 tested with MacOS
# General:
# + initial screensize is now 80x24
@@ -8094,7 +8105,7 @@
# + poor (doesn't copy anyone, most of the results are wrong)
# vttest:
# + DA is VT5xx with sixel, selective erase, user windows, color
-# + DA2 is VT220 version 277
+# + DA2 is VT220 version 277, perhaps a reference to xterm #277
# + only the VT100 character set works, contrary to DA/DA2.
# + no NRCS, either
# + double-sized character work, with some debris
@@ -8136,7 +8147,7 @@
 use=ansi+rep, use=ansi+sgrdim, use=bracketed+paste,
 use=ecma+index, use=ecma+italics, use=ecma+strikeout,
 use=report+version, use=vt220+cvis,
- use=xterm+256color2, use=xterm+alt1049,
+ use=xterm+256color2,
 use=xterm+alt+title,
 use=xterm+focus, use=xterm+pcc2, use=xterm+pce2,
 use=xterm+pcf2, use=xterm+sl-alt, use=xterm+sm+1006,
 use=xterm+tmux,
@@ -27644,4 +27655,8 @@
# 2024-09-07
# + update comments -TD
#
+# 2024-10-05
+# + use xterm+alt+title in wezterm -TD
+# + update comments -TD
+#
######## SHANTIH!  SHANTIH!  SHANTIH!
Index: ncurses/base/lib_screen.c
Prereq:  1.108
--- ncurses-6.5-20240928+/ncurses/base/lib_screen.c 2024-09-22 20:20:36.000000000 +0000
+++ ncurses-6.5-20241006/ncurses/base/lib_screen.c 2024-10-05 20:47:44.000000000 +0000
@@ -42,7 +42,7 @@
#define CUR SP_TERMTYPE
#endif

-MODULE_ID("$Id: lib_screen.c,v 1.108 2024/09/22 20:20:36 tom Exp $")
+MODULE_ID("$Id: lib_screen.c,v 1.109 2024/10/05 20:47:44 tom Exp $")

#define MAX_SIZE 0x3fff  /* 16k is big enough for a window or pad */
```

```
@@ -943,7 +943,7 @@
 * Replace a window covering the whole screen, i.e., newscr or curscr.
 */
static WINDOW *
-replace_window(WINDOW *target, FILE *source)
+replace_window(const
 WINDOW *target, FILE *source)
{
   WINDOW *result = getwin(source);
#if NCURSES_EXT_FUNCS
Index: ncurses/base/new_pair.c
Prereq:  1.24
--- ncurses-6.5-20240928+/ncurses/base/new_pair.c 2024-07-27 19:22:23.000000000 +0000
+++ ncurses-6.5-20241006/ncurses/base/new_pair.c 2024-10-05 20:51:29.000000000 +0000
@@ -61,7 +61,7 @@

#endif

-MODULE_ID("$Id: new_pair.c,v 1.24 2024/07/27 19:22:23 tom Exp $")
+MODULE_ID("$Id: new_pair.c,v 1.25 2024/10/05 20:51:29 tom Exp $")

#if NCURSES_EXT_COLORS

@@ -193,7 +193,7 @@
 * pair table.
 */
NCURSES_EXPORT(void)
-_nc_reset_color_pair(SCREEN *sp, int pair, colorpair_t * next)
+_nc_reset_color_pair(SCREEN *sp, int pair, const colorpair_t * next)
{
   colorpair_t *last;

Index: ncurses/curses.priv.h
Prereq:  1.691
--- ncurses-6.5-20240928+/ncurses/curses.priv.h 2024-09-28 15:35:01.000000000 +0000
+++ ncurses-6.5-20241006/ncurses/curses.priv.h 2024-10-05 21:01:50.000000000 +0000
@@ -35,7 +35,7 @@
 ********************************************************************************/

/*
- * $Id: curses.priv.h,v 1.691 2024/09/28 15:35:01 tom Exp $
+ * $Id: curses.priv.h,v 1.692 2024/10/05 21:01:50 tom Exp $
 *
 * curses.priv.h
 *
@@ -2170,7 +2170,7 @@
extern NCURSES_EXPORT(int) _nc_read_termcap_entry (const char *const, TERMTYPE2 *const);
```

```
extern NCURSES_EXPORT(int) _nc_setup_tinfo(const char *, TERMTYPE2 *);
extern NCURSES_EXPORT(int) _nc_setupscreen (int, int, FILE *, int, int);
-extern NCURSES_EXPORT(int) _nc_timed_wait (SCREEN *, int, int, int * EVENTLIST_2nd(_nc_eventlist *));
+extern NCURSES_EXPORT(int) _nc_timed_wait (const SCREEN *, int, int, int *
EVENTLIST_2nd(_nc_eventlist *));
extern NCURSES_EXPORT(int) _nc_trans_string (char *, const char *);
extern NCURSES_EXPORT(void) _nc_init_termtype (TERMTYPE2 *const);
extern NCURSES_EXPORT(void) _nc_do_color (int, int, int, NCURSES_OUTC);
Index: ncurses/new_pair.h
Prereq:  1.14
--- ncurses-6.5-20240928+/ncurses/new_pair.h 2024-05-25 23:10:33.000000000 +0000
+++
 ncurses-6.5-20241006/ncurses/new_pair.h 2024-10-05 20:57:47.000000000 +0000
@@ -34,7 +34,7 @@
/*
 * Common type definitions and macros for new_pair.c, lib_color.c
 *
- * $Id: new_pair.h,v 1.14 2024/05/25 23:10:33 tom Exp $
+ * $Id: new_pair.h,v 1.15 2024/10/05 20:57:47 tom Exp $
 */

#ifndef NEW_PAIR_H
@@ -116,7 +116,7 @@
#if NCURSES_EXT_FUNCS && NCURSES_EXT_COLORS
extern NCURSES_EXPORT(void)     _nc_copy_pairs(SCREEN*, colorpair_t*, colorpair_t*, int);
extern NCURSES_EXPORT(void)     _nc_free_ordered_pairs(SCREEN*);
-extern NCURSES_EXPORT(void)     _nc_reset_color_pair(SCREEN*, int, colorpair_t*);
+extern NCURSES_EXPORT(void)     _nc_reset_color_pair(SCREEN*, int, const colorpair_t*);
extern NCURSES_EXPORT(void)     _nc_set_color_pair(SCREEN*, int, int);
#else
#define _nc_free_ordered_pairs(sp) /* nothing */
Index: ncurses/tinfo/trim_sgr0.c
Prereq:  1.23
--- ncurses-6.5-20240928+/ncurses/tinfo/trim_sgr0.c 2024-07-27 19:22:23.000000000 +0000
+++ ncurses-6.5-20241006/ncurses/tinfo/trim_sgr0.c 2024-10-05
 20:53:48.000000000 +0000
@@ -37,7 +37,7 @@

#include <tic.h>

-MODULE_ID("$Id: trim_sgr0.c,v 1.23 2024/07/27 19:22:23 tom Exp $")
+MODULE_ID("$Id: trim_sgr0.c,v 1.24 2024/10/05 20:53:48 tom Exp $")

#undef CUR
#define CUR tp->
@@ -237,12 +237,10 @@

   if (PRESENT(exit_attribute_mode)
```

```
 && PRESENT(set_attributes)) {
- bool found = FALSE;
 char *on = set_attribute_9(tp, 1);
 char *off = set_attribute_9(tp, 0);
 char *end = strdup(exit_attribute_mode);
 char *tmp;
- size_t i, j, k;

 TR(TRACE_DATABASE, ("checking if we can trim sgr0 based on sgr"));
 TR(TRACE_DATABASE, ("sgr0       %s", _nc_visbuf(end)));
@@ -255,6 +253,9 @@
    FreeIfNeeded(off);
 } else if (similar_sgr(off, end)
    && !similar_sgr(off, on)) {
+    bool found = FALSE;
+    size_t i, j, k;
+
    TR(TRACE_DATABASE, ("adjusting sgr(9:off) : %s", _nc_visbuf(off)));
    result = off;
    /*
Index: ncurses/tty/lib_twait.c
Prereq:  1.81
--- ncurses-6.5-20240928+/ncurses/tty/lib_twait.c 2023-09-16
 16:30:40.000000000 +0000
+++ ncurses-6.5-20241006/ncurses/tty/lib_twait.c 2024-10-05 22:47:12.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2018-2020,2023 Thomas E. Dickey                                *
+ * Copyright 2018-2023,2024 Thomas E. Dickey                                *
 * Copyright 1998-2015,2016 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -76,7 +76,7 @@
#endif
#undef CUR

-MODULE_ID("$Id: lib_twait.c,v 1.81 2023/09/16 16:30:40 tom Exp $")
+MODULE_ID("$Id: lib_twait.c,v 1.82 2024/10/05 22:47:12 tom Exp $")

/*
 * Returns an elapsed time, in milliseconds (if possible).
@@ -168,7 +168,7 @@
 * descriptors.
 */
NCURSES_EXPORT(int)
-_nc_timed_wait(SCREEN *sp MAYBE_UNUSED,
+_nc_timed_wait(const
```

```
 SCREEN *sp MAYBE_UNUSED,
        int mode MAYBE_UNUSED,
        int milliseconds,
        int *timeleft
Index: package/debian-mingw/changelog
--- ncurses-6.5-20240928+/package/debian-mingw/changelog 2024-09-28 09:53:21.000000000 +0000
+++ ncurses-6.5-20241006/package/debian-mingw/changelog 2024-10-06 08:53:45.000000000 +0000
@@ -1,8 +1,8 @@
-ncurses6td (6.5+20240928) unstable; urgency=low
+ncurses6td (6.5+20241006) unstable; urgency=low

  * latest weekly patch

- -- Thomas E. Dickey <dickey@invisible-island.net>  Sat, 28 Sep 2024 05:53:21 -0400
+ -- Thomas E. Dickey <dickey@invisible-island.net>  Sun, 06 Oct 2024 04:53:45 -0400

ncurses6 (5.9+20131005) unstable; urgency=low

Index: package/debian-mingw64/changelog
--- ncurses-6.5-20240928+/package/debian-mingw64/changelog 2024-09-28 09:53:21.000000000 +0000
+++ ncurses-6.5-20241006/package/debian-mingw64/changelog 2024-10-06 08:53:45.000000000 +0000
@@ -1,8 +1,8 @@
-ncurses6td (6.5+20240928) unstable; urgency=low
+ncurses6td
 (6.5+20241006) unstable; urgency=low

  * latest weekly patch

- -- Thomas E. Dickey <dickey@invisible-island.net>  Sat, 28 Sep 2024 05:53:21 -0400
+ -- Thomas E. Dickey <dickey@invisible-island.net>  Sun, 06 Oct 2024 04:53:45 -0400

ncurses6 (5.9+20131005) unstable; urgency=low

Index: package/debian/changelog
--- ncurses-6.5-20240928+/package/debian/changelog 2024-09-28 09:53:21.000000000 +0000
+++ ncurses-6.5-20241006/package/debian/changelog 2024-10-06 08:53:45.000000000 +0000
@@ -1,8 +1,8 @@
-ncurses6td (6.5+20240928) unstable; urgency=low
+ncurses6td (6.5+20241006) unstable; urgency=low

  * latest weekly patch

- -- Thomas E. Dickey <dickey@invisible-island.net>  Sat, 28 Sep 2024 05:53:21 -0400
+ -- Thomas E. Dickey <dickey@invisible-island.net>  Sun, 06 Oct 2024 04:53:45 -0400

ncurses6 (5.9+20120608) unstable; urgency=low

Index: package/mingw-ncurses.nsi
```

```
Prereq:  1.669
--- ncurses-6.5-20240928+/package/mingw-ncurses.nsi 2024-09-28 09:53:21.000000000 +0000
+++
 ncurses-6.5-20241006/package/mingw-ncurses.nsi 2024-10-06 08:53:45.000000000 +0000
@@ -1,4 +1,4 @@
-; $Id: mingw-ncurses.nsi,v 1.669 2024/09/28 09:53:21 tom Exp $
+; $Id: mingw-ncurses.nsi,v 1.671 2024/10/06 08:53:45 tom Exp $

; TODO add examples
; TODO bump ABI to 6
@@ -10,7 +10,7 @@
!define VERSION_MAJOR "6"
!define VERSION_MINOR "5"
!define VERSION_YYYY  "2024"
-!define VERSION_MMDD  "0928"
+!define VERSION_MMDD  "1006"
!define VERSION_PATCH ${VERSION_YYYY}${VERSION_MMDD}

!define MY_ABI   "5"
Index: package/mingw-ncurses.spec
--- ncurses-6.5-20240928+/package/mingw-ncurses.spec 2024-09-28 09:53:21.000000000 +0000
+++ ncurses-6.5-20241006/package/mingw-ncurses.spec 2024-10-06 08:53:45.000000000 +0000
@@ -3,7 +3,7 @@
Summary: shared libraries for terminal handling
Name: mingw32-ncurses6
Version: 6.5
-Release: 20240928
+Release: 20241006
License: X11
Group: Development/Libraries
URL: https://invisible-island.net/ncurses/
Index: package/ncurses.spec
--- ncurses-6.5-20240928+/package/ncurses.spec 2024-09-28
 09:53:21.000000000 +0000
+++ ncurses-6.5-20241006/package/ncurses.spec 2024-10-06 08:53:45.000000000 +0000
@@ -1,7 +1,7 @@
Summary: shared libraries for terminal handling
Name: ncurses6
Version: 6.5
-Release: 20240928
+Release: 20241006
License: X11
Group: Development/Libraries
URL: https://invisible-island.net/ncurses/
Index: package/ncursest.spec
--- ncurses-6.5-20240928+/package/ncursest.spec 2024-09-28 09:53:21.000000000 +0000
+++ ncurses-6.5-20241006/package/ncursest.spec 2024-10-06 08:53:45.000000000 +0000
@@ -1,7 +1,7 @@
```

```
Summary: Curses library with POSIX thread support.
Name: ncursest6
Version: 6.5
-Release: 20240928
+Release: 20241006
License: X11
Group: Development/Libraries
Source: ncurses-%{version}-%{release}.tgz
Index: test/blue.c
Prereq:  1.55
--- ncurses-6.5-20240928+/test/blue.c 2022-12-10 23:31:31.000000000 +0000
+++ ncurses-6.5-20241006/test/blue.c 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
-
 * Copyright 2019-2021,2022 Thomas E. Dickey                                *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                                *
 * Copyright 1998-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -37,7 +37,7 @@
 ****************************************************************************/

/*
- * $Id: blue.c,v 1.55 2022/12/10 23:31:31 tom Exp $
+ * $Id: blue.c,v 1.56 2024/10/05 19:26:24 tom Exp $
 */

#include <test.priv.h>
@@ -437,7 +437,7 @@
static void
use_pc_display(void)
{
-    char *check = nl_langinfo(CODESET);
+    const char *check = nl_langinfo(CODESET);
    if (!strcmp(check, "UTF-8")) {
#if USE_WIDEC_SUPPORT
 suits = uglyphs;
@@ -448,8 +448,8 @@
     !strcmp(check, "CP437") ||
     !strcmp(check,
 "IBM850") ||
     !strcmp(check, "CP850")) {
-     char *smacs = tigetstr("smacs");
-     char *smpch = tigetstr("smpch");
+     const char *smacs = tigetstr("smacs");
+     const char *smpch = tigetstr("smpch");
     /*
```

```
     * The ncurses library makes this check to decide whether to allow
     * the alternate character set for the (normally) nonprinting codes.
Index: test/bs.c
Prereq:  1.79
--- ncurses-6.5-20240928+/test/bs.c 2023-05-27 20:13:10.000000000 +0000
+++ ncurses-6.5-20241006/test/bs.c 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2018-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2018-2023,2024 Thomas E. Dickey                                *
 * Copyright 1998-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge,
 to any person obtaining a  *
@@ -35,7 +35,7 @@
 * v2.0 featuring strict ANSI/POSIX conformance, November 1993.
 * v2.1 with ncurses mouse support, September 1995
 *
- * $Id: bs.c,v 1.79 2023/05/27 20:13:10 tom Exp $
+ * $Id: bs.c,v 1.80 2024/10/05 19:26:24 tom Exp $
 */

#include <test.priv.h>
@@ -147,7 +147,7 @@
   bool placed;  /* has it been placed on the board? */
} ship_t;

-static bool checkplace(int b, ship_t * ss, int vis);
+static bool checkplace(int b, const ship_t * ss, int vis);

#define SHIPIT(name, symbol, length) { name, 0, symbol, length, 0,0, 0, FALSE }

@@ -686,7 +686,7 @@
}

static bool
-checkplace(int b, ship_t * ss, int vis)
+checkplace(int b, const ship_t * ss, int vis)
{
   int l, xend, yend;

Index: test/cardfile.c
Prereq:  1.51
--- ncurses-6.5-20240928+/test/cardfile.c 2022-12-04 00:40:11.000000000 +0000
+++ ncurses-6.5-20241006/test/cardfile.c 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
-
```

```
 * Copyright 2019-2021,2022 Thomas E. Dickey                          *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                          *
 * Copyright 1999-2016,2017 Free Software Foundation, Inc.              *
 *                                                                      *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -30,7 +30,7 @@
/*
 * Author: Thomas E. Dickey
 *
- * $Id: cardfile.c,v 1.51 2022/12/04 00:40:11 tom Exp $
+ * $Id: cardfile.c,v 1.52 2024/10/05 19:26:24 tom Exp $
 *
 * File format: text beginning in column 1 is a title; other text is content.
 */
@@ -161,7 +161,7 @@
}

static CARD *
-find_card(char *title)
+find_card(const char *title)
{
   CARD *card;

@@ -173,7 +173,7 @@
}

static void
-read_data(char *fname)
+read_data(const char *fname)
{
   FILE *fp;

@@ -341,7 +341,7 @@
}

static FIELD **
-make_fields(CARD * p, int form_high,
- int form_wide)
+make_fields(const CARD * p, int form_high, int form_wide)
{
   FIELD **f = typeCalloc(FIELD *, (size_t) 3);

@@ -385,7 +385,7 @@
/*******************************************************************************/

static void
-cardfile(char *fname)
+cardfile(const char *fname)
```

```
{
   WINDOW *win;
   CARD *p;
Index: test/chgat.c
Prereq:  1.21
--- ncurses-6.5-20240928+/test/chgat.c 2024-06-29 17:45:32.000000000 +0000
+++ ncurses-6.5-20241006/test/chgat.c 2024-10-06 22:35:55.000000000 +0000
@@ -27,7 +27,7 @@
 * authorization.                                        *
 ****************************************************************************/
/*
- * $Id: chgat.c,v 1.21 2024/06/29 17:45:32 tom Exp $
+ * $Id: chgat.c,v 1.23 2024/10/06 22:35:55 tom Exp $
 *
 * test-driver for chgat/wchgat/mvchgat/mvwchgat
 */
@@ -160,7 +160,7 @@
}

static void
-do_subwindow(WINDOW *win, STATUS * sp, void func(WINDOW *))
+do_subwindow(WINDOW *win, const STATUS
 * sp, void func(WINDOW *))
{
   WINDOW *win1 = newwin(sp->y_max - 2, sp->x_max - 2,
    sp->y_beg + 1, sp->x_beg + 1);
@@ -204,7 +204,7 @@
static void
show_help(WINDOW *win)
{
-    static const char *msgs[] =
+    static NCURSES_CONST char *msgs[] =
   {
 "Basic commands:"
 ,"Use h/j/k/l or arrow keys to move the cursor."
Index: test/clip_printw.c
Prereq:  1.23
--- ncurses-6.5-20240928+/test/clip_printw.c 2023-09-30 19:57:44.000000000 +0000
+++ ncurses-6.5-20241006/test/clip_printw.c 2024-10-06 22:36:25.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2019-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2019-2023,2024 Thomas E. Dickey                                *
 * Copyright 2008-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge,
 to any person obtaining a  *
@@ -27,7 +27,7 @@
```

```
 * authorization.                                          *
 ****************************************************************************/
/*
- * $Id: clip_printw.c,v 1.23 2023/09/30 19:57:44 tom Exp $
+ * $Id: clip_printw.c,v 1.25 2024/10/06 22:36:25 tom Exp $
 *
 * demonstrate how to use printw with/without wrapping.
 */
@@ -212,7 +212,7 @@
}

static void
-do_subwindow(WINDOW *win, STATUS * sp, void func(WINDOW *))
+do_subwindow(WINDOW *win, const STATUS * sp, void func(WINDOW *))
{
   WINDOW *win1 = newwin(sp->y_max - (2 * MARGIN),
    sp->x_max - (2 * MARGIN),
@@ -268,7 +268,7 @@
static void
show_help(WINDOW *win)
{
-    static const char *msgs[] =
+    static NCURSES_CONST char *msgs[] =
    {
 "Basic commands:"
 ,"Use h/j/k/l or arrow keys to move the cursor."
Index: test/color_name.h
Prereq:  1.9
--- ncurses-6.5-20240928+/test/color_name.h 2021-04-24 23:25:29.000000000 +0000
+++ ncurses-6.5-20241006/test/color_name.h 2024-10-05
 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2018-2020,2021 Thomas E. Dickey                                *
+ * Copyright 2018-2021,2024 Thomas E. Dickey                                *
 * Copyright 2011-2012,2016 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                          *
 ****************************************************************************/
/*
- * $Id: color_name.h,v 1.9 2021/04/24 23:25:29 tom Exp $
+ * $Id: color_name.h,v 1.10 2024/10/05 19:26:24 tom Exp $
 */

#ifndef __COLORNAME_H
@@ -63,7 +63,6 @@
```

```
{
   int result = 0;
   char *endp = 0;
-    size_t n;

   if ((result = (int) strtol(color,
 &endp, 0)) >= 0
 && (endp == 0 || *endp == 0)) {
@@ -71,6 +70,7 @@
   } else if (!strcmp(color, "default")) {
 result = -1;
   } else {
+ size_t n;
 for (n = 0; n < SIZEOF(the_color_names); ++n) {
     if (!strcmp(the_color_names[n], color)) {
  result = (int) n;
Index: test/demo_defkey.c
Prereq:  1.35
--- ncurses-6.5-20240928+/test/demo_defkey.c 2024-01-20 20:46:12.000000000 +0000
+++ ncurses-6.5-20241006/test/demo_defkey.c 2024-10-05 18:20:04.000000000 +0000
@@ -27,7 +27,7 @@
 * authorization.                                           *
 ****************************************************************************/
/*
- * $Id: demo_defkey.c,v 1.35 2024/01/20 20:46:12 tom Exp $
+ * $Id: demo_defkey.c,v 1.36 2024/10/05 18:20:04 tom Exp $
 *
 * Demonstrate the define_key() function.
 * Thomas Dickey - 2002/11/23
@@ -199,7 +199,7 @@
}

static void
-redefine(WINDOW *win, char *string, int code)
+redefine(WINDOW *win, const char *string, int code)
{

   really_define_key(win, string, code);
}
Index: test/demo_forms.c
Prereq:  1.63
--- ncurses-6.5-20240928+/test/demo_forms.c 2023-11-11 00:29:53.000000000 +0000
+++ ncurses-6.5-20241006/test/demo_forms.c 2024-10-06 21:15:12.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2018-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2018-2023,2024 Thomas E. Dickey                                *
 * Copyright 2003-2016,2017 Free Software Foundation, Inc.                  *
```

```
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: demo_forms.c,v 1.63 2023/11/11 00:29:53 tom Exp $
+ * $Id: demo_forms.c,v 1.67
 2024/10/06 21:15:12 tom Exp $
 *
 * Demonstrate a variety of functions from the form library.
 * Thomas Dickey - 2003/4/26
@@ -148,7 +148,7 @@
}

static FIELD *
-make_label(const char *label, int frow, int fcol)
+make_label(NCURSES_CONST char *label, int frow, int fcol)
{
   FIELD *f = new_field(1, (int) strlen(label), frow, fcol, 0, 0);

@@ -242,7 +242,7 @@
#define O_SELECTABLE (O_ACTIVE | O_VISIBLE)

static FIELD *
-another_field(FORM *form, const FIELD *const field)
+another_field(NCURSES_CONST FORM *form, NCURSES_CONST FIELD *const field)
{
   FIELD **f = form_fields(form);
   FIELD *result = 0;
@@ -306,9 +306,9 @@
}

static void
-show_current_field(WINDOW *win, FORM *form)
+show_current_field(WINDOW *win, NCURSES_CONST FORM *form)
{
-   FIELD *field;
+   NCURSES_CONST FIELD *field;
   int field_rows, field_cols, field_max;
   int currow, curcol;

@@ -325,7 +325,7 @@
   waddch(win, '\n');

   if ((field = current_field(form)) != 0) {
- FIELDTYPE *type;
+ NCURSES_CONST
```

```
 FIELDTYPE *type;
 int nbuf;

 wprintw(win, "Page %d%s, Field %d/%d%s:",
@@ -383,7 +383,7 @@

 waddstr(win, "\n");
 for (nbuf = 0; nbuf <= 2; ++nbuf) {
-    char *buffer;
+    NCURSES_CONST char *buffer;
     if ((buffer = field_buffer(field, nbuf)) != 0) {
  wprintw(win, "buffer %d:", nbuf);
  (void) wattrset(win, A_REVERSE);
@@ -408,8 +408,8 @@
    int c;
    unsigned n = 0;
    int pg;
-   const char *fname;
-   static const char *my_enum[] =
+   NCURSES_CONST char *fname;
+   static NCURSES_CONST char *my_enum[] =
    {"first", "second", "third", 0};

#ifdef NCURSES_MOUSE_VERSION
@@ -515,7 +515,7 @@
    f[n] = (FIELD *) 0;

    if ((form = new_form(f)) != 0) {
- WINDOW *w;
+ NCURSES_CONST WINDOW *w;
 WINDOW *also;
 int finished = 0;

Index: test/demo_menus.c
Prereq:  1.80
--- ncurses-6.5-20240928+/test/demo_menus.c 2023-05-27 20:13:10.000000000 +0000
+++ ncurses-6.5-20241006/test/demo_menus.c 2024-10-06 19:58:28.000000000 +0000
@@ -1,5
 +1,5 @@
/****************************************************************************
- * Copyright 2019-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2019-2023,2024 Thomas E. Dickey                                *
 * Copyright 2003-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
```

```
/*
- * $Id: demo_menus.c,v 1.80 2023/05/27 20:13:10 tom Exp $
+ * $Id: demo_menus.c,v 1.82 2024/10/06 19:58:28 tom Exp $
 *
 * Demonstrate a variety of functions from the menu library.
 * Thomas Dickey - 2005/4/9
@@ -185,7 +185,7 @@
}

static int
-menu_getc(MENU * m)
+menu_getc(NCURSES_CONST MENU * m)
{
   return wGetchar(menu_win(m));
 }
@@ -214,7 +214,7 @@
my_menu_init(MENU * menu)
{
   Trace(("called MenuHook my_menu_init"));
-   mvwprintw(status, 2, 0, "menu_init %p", (void *) menu);
+    mvwprintw(status, 2, 0, "menu_init %p", (const void *) menu);
   wclrtoeol(status);
   wrefresh(status);
}
@@ -223,7 +223,7 @@
my_menu_term(MENU * menu)
{
   Trace(("called MenuHook my_menu_term"));
-   mvwprintw(status, 2, 0, "menu_term %p", (void *) menu);
+    mvwprintw(status, 2, 0, "menu_term %p", (const void *) menu);
   wclrtoeol(status);
   wrefresh(status);
}
@@ -231,7 +231,7 @@
static void
my_item_init(MENU * menu)
{
-   ITEM *item = current_item(menu);
+    NCURSES_CONST ITEM *item = current_item(menu);
   const char *name = item_name(item);

   Trace(("called MenuHook my_item_init (%s)", name));
@@ -243,7 +243,7 @@
static void
my_item_term(MENU * menu)
{
-   ITEM *item = current_item(menu);
+    NCURSES_CONST ITEM *item = current_item(menu);
```

```
   const char *name = item_name(item);

   Trace(("called MenuHook my_item_term (%s)", name));
@@ -348,7 +348,7 @@

/* force the given menu to appear */
static void
-menu_display(MENU * m)
+menu_display(NCURSES_CONST MENU * m)
{
   touchwin(menu_win(m));
   wrefresh(menu_win(m));
@@ -584,10 +584,10 @@
 * the others
 */
static bool
-update_trace_menu(MENU * m)
+update_trace_menu(NCURSES_CONST MENU * m)
{
   ITEM **items;
-   ITEM *i;
+    NCURSES_CONST ITEM *i;
   bool changed = FALSE;

   items = menu_items(m);
@@ -613,7 +613,7 @@
   int result;

   for (ip = menu_items(mpTrace); *ip; ip++) {
- MENU_DATA *td = (MENU_DATA *) item_userptr(*ip);
+ NCURSES_CONST MENU_DATA *td = (MENU_DATA *) item_userptr(*ip);
 unsigned mask = td->mask;
 if (mask == 0)
    set_item_value(*ip, _nc_tracing == 0);
@@ -628,7 +628,7 @@
    unsigned newtrace = 0;
    for (ip = menu_items(mpTrace); *ip; ip++) {
  if (item_value(*ip)) {
-      MENU_DATA *td = (MENU_DATA *) item_userptr(*ip);
+      NCURSES_CONST
 MENU_DATA *td = (MENU_DATA *) item_userptr(*ip);
     newtrace |= td->mask;
  }
@@ -718,7 +718,9 @@
}

static int
```

```
-move_menu(MENU * menu, MENU * current, int by_y, int by_x)
+move_menu(NCURSES_CONST MENU * menu,
+   NCURSES_CONST MENU * current,
+   int by_y, int by_x)
{
   WINDOW *top_win = menu_win(menu);
   WINDOW *sub_win = menu_sub(menu);
@@ -798,7 +800,7 @@
#endif /* defined(KEY_RESIZE) && NCURSES_EXT_FUNCS */

static void
-show_status(int ch, MENU * menu)
+show_status(int ch, NCURSES_CONST MENU * menu)
{
   wmove(status, 0, 0);
   wprintw(status, "key %s, menu %d, mark %s, match %s",
@@ -919,7 +921,7 @@
 wrefresh(menu_win(last_menu));
 if (code == E_UNKNOWN_COMMAND
     || code == E_NOT_POSTED) {
-    ITEM *item = current_item(last_menu);
+    NCURSES_CONST ITEM *item = current_item(last_menu);
     MENU_DATA *td = (MENU_DATA *) item_userptr(item);
     td->func((int) td->mask);
 }
Index: test/demo_new_pair.c
Prereq:  1.28
--- ncurses-6.5-20240928+/test/demo_new_pair.c 2024-06-29
 19:30:26.000000000 +0000
+++ ncurses-6.5-20241006/test/demo_new_pair.c 2024-10-05 18:21:44.000000000 +0000
@@ -27,7 +27,7 @@
 * authorization.                                          *
 ****************************************************************************/
/*
- * $Id: demo_new_pair.c,v 1.28 2024/06/29 19:30:26 tom Exp $
+ * $Id: demo_new_pair.c,v 1.29 2024/10/05 18:21:44 tom Exp $
 *
 * Demonstrate the alloc_pair() function.
 */
@@ -49,7 +49,7 @@
static bool
valid_cap(NCURSES_CONST char *name)
{
-   char *value = tigetstr(name);
+   const char *value = tigetstr(name);
   return (value != 0 && value != (char *) -1) ? TRUE : FALSE;
}
```

```
Index: test/demo_panels.c
Prereq:  1.48
--- ncurses-6.5-20240928+/test/demo_panels.c 2022-12-04 00:40:11.000000000 +0000
+++ ncurses-6.5-20241006/test/demo_panels.c 2024-10-06 20:01:21.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
-
 * Copyright 2018-2020,2022 Thomas E. Dickey                                *
+ * Copyright 2018-2022,2024 Thomas E. Dickey                                *
 * Copyright 2003-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: demo_panels.c,v 1.48 2022/12/04 00:40:11 tom Exp $
+ * $Id: demo_panels.c,v 1.50 2024/10/06 20:01:21 tom Exp $
 *
 * Demonstrate a variety of functions from the panel library.
 */
@@ -42,7 +42,7 @@
#define TEMP_POS '>'

typedef void (*InitPanel) (void);
-typedef void (*FillPanel) (PANEL *);
+typedef void (*FillPanel) (NCURSES_CONST PANEL *);

static bool use_colors = FALSE;
static bool
 unboxed = FALSE;
@@ -301,7 +301,7 @@
 int code;
 int y0, x0;
 int y1, x1;
- WINDOW *win = panel_window(pans[which]);
+ NCURSES_CONST WINDOW *win = panel_window(pans[which]);
 char also[80];

 getbegyx(win, y0, x0);
@@ -368,7 +368,7 @@
}

static void
-fill_panel(PANEL *pan)
+fill_panel(NCURSES_CONST PANEL *pan)
{
   WINDOW *win = panel_window(pan);
```

```
   const char *userptr = (const char *) panel_userptr(pan);
@@ -388,7 +388,7 @@
}

static void
-fill_unboxed(PANEL *pan)
+fill_unboxed(NCURSES_CONST PANEL *pan)
{
   WINDOW *win = panel_window(pan);
   const char *userptr = (const char *) panel_userptr(pan);
@@ -431,7 +431,7 @@
}

static void
-fill_wide_panel(PANEL *pan)
+fill_wide_panel(NCURSES_CONST PANEL *pan)
{
   WINDOW *win = panel_window(pan);
   int num = ((const char *) panel_userptr(pan))[1];
@@ -453,7 +453,7 @@
#define MAX_PANELS 5

static int
-which_panel(PANEL *px[MAX_PANELS + 1], PANEL *pan)
+which_panel(PANEL *px[MAX_PANELS + 1], NCURSES_CONST
 PANEL *pan)
{
   int result = 0;
   int j;
Index: test/demo_termcap.c
Prereq:  1.65
--- ncurses-6.5-20240928+/test/demo_termcap.c 2023-05-27 20:13:10.000000000 +0000
+++ ncurses-6.5-20241006/test/demo_termcap.c 2024-10-06 20:05:09.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2019-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2019-2023,2024 Thomas E. Dickey                                *
 * Copyright 2005-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -30,7 +30,7 @@
/*
 * Author: Thomas E. Dickey
 *
- * $Id: demo_termcap.c,v 1.65 2023/05/27 20:13:10 tom Exp $
+ * $Id: demo_termcap.c,v 1.70 2024/10/06 20:05:09 tom Exp $
 *
 * A simple demo of the termcap interface.
```

```
 */
@@ -256,7 +256,7 @@

   * to hold all of the strings extracted from the terminal entry.
    */
   char area[1024], *ap = area;
-    char *str;
+    NCURSES_CONST char *str;
   int num;

   if ((str = tgetstr(cap, &ap)) != 0) {
@@ -289,7 +289,7 @@
}

static void
-brute_force(const char *name)
+brute_force(NCURSES_CONST char *name)
{
   char buffer[1024];

@@ -369,7 +369,7 @@
#ifdef NCURSES_VERSION
 if (x_opt && (my_blob == 0) && y_opt) {
#if NCURSES_XNAMES
-     TERMTYPE *term = (TERMTYPE *) cur_term;
+     NCURSES_CONST TERMTYPE *term = (TERMTYPE *) cur_term;
     if (term != 0
  && ((NUM_BOOLEANS(term) != BOOLCOUNT)
     || (NUM_NUMBERS(term) != NUMCOUNT)
@@ -781,12 +781,12 @@
{
   int ch;
   int n;
-    char *name;
+    NCURSES_CONST char *name;
   bool a_opt = FALSE;
#if defined(NCURSES_VERSION) || defined(HAVE_CURSES_DATA_OSPEED)
   bool v_opt = FALSE;
#endif
-    char *input_name = 0;
+    NCURSES_CONST char *input_name = 0;

   int repeat;
   int r_opt = 1;
@@ -867,7
 +867,7 @@
    } else if ((name = getenv("TERM")) != 0) {
  brute_force(name);
```

```
    } else {
-  static char dumb[] = "dumb";
+  static NCURSES_CONST char dumb[] = "dumb";
  brute_force(dumb);
    }
 }
@@ -894,7 +894,7 @@
    } else if ((name = getenv("TERM")) != 0) {
  demo_termcap(name);
    } else {
-  static char dumb[] = "dumb";
+  static NCURSES_CONST char dumb[] = "dumb";
  demo_termcap(dumb);
    }
 }
Index: test/demo_terminfo.c
Prereq:  1.57
--- ncurses-6.5-20240928+/test/demo_terminfo.c 2023-05-27 20:13:10.000000000 +0000
+++ ncurses-6.5-20241006/test/demo_terminfo.c 2024-10-06 21:16:43.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2019-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2019-2023,2024 Thomas E. Dickey                                *
 * Copyright 2009-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
                                    *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -30,7 +30,7 @@
/*
 * Author: Thomas E. Dickey
 *
- * $Id: demo_terminfo.c,v 1.57 2023/05/27 20:13:10 tom Exp $
+ * $Id: demo_terminfo.c,v 1.59 2024/10/06 21:16:43 tom Exp $
 *
 * A simple demo of the terminfo interface.
 */
@@ -253,7 +253,7 @@
#define LegalItem(c,n) (n)

static void
-brute_force(const char *name)
+brute_force(NCURSES_CONST char *name)
{
#define MAX_FORCE 5  /* omit "colors", since CPU-time is a problem */
    static const char legal[] = "\
@@ -324,7 +324,7 @@
#endif
```

```
static void
-demo_terminfo(char *name)
+demo_terminfo(NCURSES_CONST char *name)
{
   unsigned n;
   NCURSES_CONST char *cap;
@@ -366,7 +366,7 @@
   if (x_opt && (my_blob == 0)) {
 if (y_opt) {
#if NCURSES_XNAMES
-    TERMTYPE *term = (TERMTYPE *) cur_term;
+    const TERMTYPE *term = (TERMTYPE *) cur_term;
     if (term != 0
  && ((NUM_BOOLEANS(term)
 != BOOLCOUNT)
     || (NUM_NUMBERS(term) != NUMCOUNT)
@@ -813,9 +813,9 @@
   int ch;
   int n;
   int repeat;
-   char *name;
+   NCURSES_CONST char *name;
   int r_opt = 1;
-   char *input_name = 0;
+   const char *input_name = 0;

   while ((ch = getopt(argc, argv, OPTS_COMMON "abd:e:fi:nqr:sxy")) != -1) {
 switch (ch) {
@@ -891,7 +891,7 @@
    } else if ((name = getenv("TERM")) != 0) {
  brute_force(name);
    } else {
-  static char dumb[] = "dumb";
+  static NCURSES_CONST char dumb[] = "dumb";
  brute_force(dumb);
    }
 }
@@ -918,7 +918,7 @@
    } else if ((name = getenv("TERM")) != 0) {
  demo_terminfo(name);
    } else {
-  static char dumb[] = "dumb";
+  static NCURSES_CONST char dumb[] = "dumb";
  demo_terminfo(dumb);
    }
 }
Index: test/dots.c
Prereq:  1.45
```

```
--- ncurses-6.5-20240928+/test/dots.c 2023-01-07 17:21:48.000000000 +0000
+++ ncurses-6.5-20241006/test/dots.c 2024-10-06 21:17:54.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
-
 * Copyright 2019-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2019-2023,2024 Thomas E. Dickey                                *
 * Copyright 1999-2013,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -30,7 +30,7 @@
/*
 * Author: Thomas E. Dickey <dickey@clark.net> 1999
 *
- * $Id: dots.c,v 1.45 2023/01/07 17:21:48 tom Exp $
+ * $Id: dots.c,v 1.46 2024/10/06 21:17:54 tom Exp $
 *
 * A simple demo of the terminfo interface.
 */
@@ -61,7 +61,7 @@
}

static bool
-outs(const char *s)
+outs(NCURSES_CONST char *s)
{
   if (VALID_STRING(s)) {
 tputs(s, 1, outc);
Index: test/dots_mvcur.c
Prereq:  1.31
--- ncurses-6.5-20240928+/test/dots_mvcur.c 2023-01-07 17:21:48.000000000 +0000
+++ ncurses-6.5-20241006/test/dots_mvcur.c 2024-10-06
 21:17:54.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2019-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2019-2023,2024 Thomas E. Dickey                                *
 * Copyright 2007-2013,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -30,7 +30,7 @@
/*
 * Author: Thomas E. Dickey - 2007
 *
- * $Id: dots_mvcur.c,v 1.31 2023/01/07 17:21:48 tom Exp $
+ * $Id: dots_mvcur.c,v 1.32 2024/10/06 21:17:54 tom Exp $
 *
 * A simple demo of the terminfo interface, and mvcur.
```

```
 */
@@ -62,7 +62,7 @@
}

static bool
-outs(const char *s)
+outs(NCURSES_CONST char *s)
{
   if (VALID_STRING(s)) {
 tputs(s, 1, outc);
Index: test/dots_termcap.c
Prereq:  1.33
--- ncurses-6.5-20240928+/test/dots_termcap.c 2024-08-31
 15:55:46.000000000 +0000
+++ ncurses-6.5-20241006/test/dots_termcap.c 2024-10-06 21:18:35.000000000 +0000
@@ -30,7 +30,7 @@
/*
 * Author: Thomas E. Dickey
 *
- * $Id: dots_termcap.c,v 1.33 2024/08/31 15:55:46 tom Exp $
+ * $Id: dots_termcap.c,v 1.35 2024/10/06 21:18:35 tom Exp $
 *
 * A simple demo of the termcap interface.
 */
@@ -113,7 +113,7 @@
}

static bool
-outs(char *s)
+outs(NCURSES_CONST char *s)
{
   if (VALID_STRING(s)) {
 tputs(s, 1, outc);
@@ -178,7 +178,7 @@
get_number(NCURSES_CONST char *cap, const char *env)
{
   int result = tgetnum(cap);
-   char *value = env ? getenv(env) : 0;
+   const char *value = env ? getenv(env) : 0;
   if (value != 0 && *value != 0) {
 char *next = 0;
 long check = strtol(value, &next, 10);
@@ -229,7 +229,7 @@
   double c;
   char buffer[1024];
   char area[1024];
-   char *name;
+   NCURSES_CONST char *name;
```

```
   size_t need;
   char *my_env;

Index: test/dup_field.c
Prereq:  1.9
--- ncurses-6.5-20240928+/test/dup_field.c 2024-06-29
 17:45:32.000000000 +0000
+++ ncurses-6.5-20241006/test/dup_field.c 2024-10-06 20:07:19.000000000 +0000
@@ -26,7 +26,7 @@
 * authorization.                                        *
 ****************************************************************************/
/*
- * $Id: dup_field.c,v 1.9 2024/06/29 17:45:32 tom Exp $
+ * $Id: dup_field.c,v 1.11 2024/10/06 20:07:19 tom Exp $
 *
 * Demonstrate dup_field().
 */
@@ -146,27 +146,27 @@
}

static FieldAttrs *
-my_field_attrs(FIELD *f)
+my_field_attrs(NCURSES_CONST FIELD *f)
{
   return (FieldAttrs *) field_userptr(f);
}

static int
-buffer_length(FIELD *f)
+buffer_length(NCURSES_CONST FIELD *f)
{
   return my_field_attrs(f)->row_lengths[0];
}

static void
-set_buffer_length(FIELD *f, int length)
+set_buffer_length(NCURSES_CONST FIELD *f, int length)
{
   my_field_attrs(f)->row_lengths[0] = length;
}

static int
-offset_in_field(FORM *form)
+offset_in_field(NCURSES_CONST
 FORM *form)
{
-    FIELD *field = current_field(form);
+    NCURSES_CONST FIELD *field = current_field(form);
```

```
   int currow, curcol;

   form_getyx(form, currow, curcol);
@@ -245,7 +245,7 @@

 default:
    modified = (ch < MIN_FORM_COMMAND
-   && isprint(ch));
+   && isprint(UChar(ch)));
    break;
 }

Index: test/filter.c
Prereq:  1.38
--- ncurses-6.5-20240928+/test/filter.c 2022-12-04 00:40:11.000000000 +0000
+++ ncurses-6.5-20241006/test/filter.c 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2019-2020,2022 Thomas E. Dickey                                *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                                *
 * Copyright 1998-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@
 -30,7 +30,7 @@
/*
 * Author:  Thomas E. Dickey 1998
 *
- * $Id: filter.c,v 1.38 2022/12/04 00:40:11 tom Exp $
+ * $Id: filter.c,v 1.39 2024/10/05 19:26:24 tom Exp $
 *
 * An example of the 'filter()' function in ncurses, this program prompts
 * for commands and executes them (like a command shell).  It illustrates
@@ -65,7 +65,7 @@
   if (clocked) {
 if (limit >= 3) {
    time_t now = time((time_t *) 0);
-    struct tm *my = localtime(&now);
+     const struct tm *my = localtime(&now);
    char buffer[80];
    int skip, y, x;
    int margin;
Index: test/form_driver_w.c
Prereq:  1.17
--- ncurses-6.5-20240928+/test/form_driver_w.c 2022-12-10 23:31:31.000000000 +0000
+++ ncurses-6.5-20241006/test/form_driver_w.c 2024-10-06 23:13:40.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
```

```
- * Copyright 2020,2022 Thomas E. Dickey                                *
+ * Copyright 2020-2022,2024 Thomas E. Dickey
                      *
 * Copyright 2013-2014,2017 Free Software Foundation, Inc.              *
 *                                                                      *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -32,7 +32,7 @@
 ****************************************************************************/

 /*
- * $Id: form_driver_w.c,v 1.17 2022/12/10 23:31:31 tom Exp $
+ * $Id: form_driver_w.c,v 1.18 2024/10/06 23:13:40 tom Exp $
  *
  * Test form_driver_w (int, int, wchar_t), a wide char aware
  * replacement of form_driver.
@@ -68,7 +68,7 @@
 int
 main(int argc, char *argv[])
 {
-    static const char *help[] =
+    static NCURSES_CONST char *help[] =
     {
  "Commands:",
  "  ^D,^Q,ESC           - quit program",
Index: test/gdc.c
Prereq:  1.60
--- ncurses-6.5-20240928+/test/gdc.c 2024-06-29 19:59:06.000000000 +0000
+++ ncurses-6.5-20241006/test/gdc.c 2024-10-06 20:08:59.000000000 +0000
@@ -34,7 +34,7 @@
  * modified 10-18-89
  for curses (jrl)
  * 10-18-89 added signal handling
  *
- * $Id: gdc.c,v 1.60 2024/06/29 19:59:06 tom Exp $
+ * $Id: gdc.c,v 1.62 2024/10/06 20:08:59 tom Exp $
  */

 #include <test.priv.h>
@@ -181,7 +181,7 @@
    int check;
    time_t result;
    char c = 0;
-    struct tm *tm;
+    NCURSES_CONST struct tm *tm;

    switch (sscanf(value, "%d:%d:%d%c", &hh, &mm, &ss, &c)) {
    default:
@@ -243,7 +243,7 @@
```

```
main(int argc, char *argv[])
{
   time_t now;
-   struct tm *tm;
+    NCURSES_CONST struct tm *tm;
   long t, a;
   int i, j, s, k, ch;
   int count = 0;
@@ -293,7 +293,7 @@

   InitAndCatch({
 if (redirected) {
-     char *name = getenv("TERM");
+     NCURSES_CONST char *name = getenv("TERM");
     if (name == 0
  || newterm(name, ofp, ifp) == 0) {
  fprintf(stderr, "cannot open terminal\n");
@@ -431,7 +431,7 @@
     _nc_STRNCPY(buf, ctime(&now), (size_t) 30);
     {
  char *d2 = buf + 10;
-  char *s2 = buf + 19;
+  NCURSES_CONST char *s2 = buf + 19;
   while ((*d2++ = *s2++) != '\0') ;
     }
     MvAddStr(16, 30, buf);
Index: test/inch_wide.c
Prereq:  1.13
--- ncurses-6.5-20240928+/test/inch_wide.c 2022-12-10 23:55:34.000000000 +0000
+++ ncurses-6.5-20241006/test/inch_wide.c 2024-10-06 23:14:31.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2019-2020,2022 Thomas E. Dickey                                *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                                *
 * Copyright 2007-2010,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: inch_wide.c,v 1.13 2022/12/10 23:55:34 tom Exp $
+
 * $Id: inch_wide.c,v 1.14 2024/10/06 23:14:31 tom Exp $
 */
/*
      int in_wch(cchar_t *wcval);
@@ -61,7 +61,7 @@
```

```
static int
test_inchs(int level, char **argv, WINDOW *chrwin, WINDOW *strwin)
{
-    static const char *help[] =
+    static NCURSES_CONST char *help[] =
     {
 "Test input from screen using inch(), etc., in a moveable viewport.",
 "",
Index: test/inchs.c
Prereq:  1.19
--- ncurses-6.5-20240928+/test/inchs.c 2022-12-11 00:01:39.000000000 +0000
+++ ncurses-6.5-20241006/test/inchs.c 2024-10-06 21:17:54.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2019-2020,2022 Thomas E. Dickey                                *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                                *
 * Copyright 2007-2012,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of
 charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: inchs.c,v 1.19 2022/12/11 00:01:39 tom Exp $
+ * $Id: inchs.c,v 1.20 2024/10/06 21:17:54 tom Exp $
 *
 * Author: Thomas E Dickey
 */
@@ -71,7 +71,7 @@
static int
test_inchs(int level, char **argv, WINDOW *chrwin, WINDOW *strwin)
{
-    static const char *help[] =
+    static NCURSES_CONST char *help[] =
     {
 "Test input from screen using inch(), etc., in a moveable viewport.",
 "",
Index: test/ins_wide.c
Prereq:  1.30
--- ncurses-6.5-20240928+/test/ins_wide.c 2022-12-10 22:28:50.000000000 +0000
+++ ncurses-6.5-20241006/test/ins_wide.c 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2020,2022 Thomas E. Dickey                                     *
+ * Copyright
 2020-2022,2024 Thomas E. Dickey                                *
 * Copyright 2002-2016,2017 Free Software Foundation, Inc.                  *
```

```
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: ins_wide.c,v 1.30 2022/12/10 22:28:50 tom Exp $
+ * $Id: ins_wide.c,v 1.31 2024/10/05 19:26:24 tom Exp $
 *
 * Demonstrate the wins_wstr() and wins_wch functions.
 * Thomas Dickey - 2002/11/23
@@ -73,7 +73,7 @@
static int n_opt = -1;

static void
-legend(WINDOW *win, int level, Options state, wchar_t *buffer, int length)
+legend(WINDOW *win, int level, Options state, const wchar_t *buffer, int length)
{
   const char *showstate;

Index: test/insdelln.c
Prereq:  1.15
--- ncurses-6.5-20240928+/test/insdelln.c 2022-12-10
 23:31:31.000000000 +0000
+++ ncurses-6.5-20241006/test/insdelln.c 2024-10-06 21:08:52.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2019-2020,2022 Thomas E. Dickey                                *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                                *
 * Copyright 2008-2014,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: insdelln.c,v 1.15 2022/12/10 23:31:31 tom Exp $
+ * $Id: insdelln.c,v 1.17 2024/10/06 21:08:52 tom Exp $
 *
 * test-driver for deleteln, wdeleteln, insdelln, winsdelln, insertln, winsertln
  */
@@ -160,7 +160,7 @@
}

static void
-do_subwindow(WINDOW *win, STATUS * sp, void func(WINDOW *))
+do_subwindow(WINDOW *win, const STATUS * sp, void func(WINDOW *))
{
```

```
   WINDOW *win1 = newwin(sp->y_max - 2, sp->x_max - 2,
    sp->y_beg + 1, sp->x_beg + 1);
@@ -204,7 +204,7 @@
static void
show_help(WINDOW *win)
{
-    static const char *table[] =
+    static NCURSES_CONST char *table[] =
   {
 "Basic commands:"
 ,"Use h/j/k/l or arrow keys to move the cursor."
Index: test/inserts.c
Prereq:  1.34
--- ncurses-6.5-20240928+/test/inserts.c 2022-12-10 22:28:50.000000000 +0000
+++ ncurses-6.5-20241006/test/inserts.c 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2020,2022 Thomas E. Dickey                                     *
+ * Copyright 2020-2022,2024 Thomas E. Dickey                                *
 * Copyright 2002-2016,2017 Free Software Foundation, Inc.                  *
     *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: inserts.c,v 1.34 2022/12/10 22:28:50 tom Exp $
+ * $Id: inserts.c,v 1.35 2024/10/05 19:26:24 tom Exp $
 *
 * Demonstrate the winsstr() and winsch functions.
 * Thomas Dickey - 2002/10/19
@@ -98,7 +98,7 @@
}

static int
-ColOf(char *buffer, int length, int margin)
+ColOf(const char *buffer, int length, int margin)
{
   int n;
   int result;
Index: test/knight.c
Prereq:  1.52
--- ncurses-6.5-20240928+/test/knight.c 2022-12-04 00:40:11.000000000 +0000
+++ ncurses-6.5-20241006/test/knight.c 2024-10-05 19:38:58.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright
```

```
 2018-2021,2022 Thomas E. Dickey                                *
+ * Copyright 2018-2022,2024 Thomas E. Dickey                    *
 * Copyright 1998-2013,2017 Free Software Foundation, Inc.       *
 *                                                               *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -34,7 +34,7 @@
 * Eric S. Raymond <esr@snark.thyrsus.com> July 22 1995.  Mouse support
 * added September 20th 1995.
 *
- * $Id: knight.c,v 1.52 2022/12/04 00:40:11 tom Exp $
+ * $Id: knight.c,v 1.53 2024/10/05 19:38:58 tom Exp $
 */

#include <test.priv.h>
@@ -450,7 +450,8 @@
}

static bool
-evaluate_move(SQUARES squares, HISTORY * doneData, int doneSize, int row, int column)
+evaluate_move(SQUARES squares, const HISTORY * doneData, int doneSize,
+       int row, int column)
{
   if (doneSize <= 1)
 return (TRUE);
Index: test/list_keys.c
Prereq:  1.33
--- ncurses-6.5-20240928+/test/list_keys.c 2023-11-11
 00:35:05.000000000 +0000
+++ ncurses-6.5-20241006/test/list_keys.c 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2018-2022,2023 Thomas E. Dickey                    *
+ * Copyright 2018-2023,2024 Thomas E. Dickey                    *
 * Copyright 2016,2017 Free Software Foundation, Inc.            *
 *                                                               *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                               *
 ****************************************************************************/
/*
- * $Id: list_keys.c,v 1.33 2023/11/11 00:35:05 tom Exp $
+ * $Id: list_keys.c,v 1.34 2024/10/05 19:26:24 tom Exp $
 *
 * Author: Thomas E Dickey
 *
@@ -297,7 +297,7 @@
#if NCURSES_XNAMES
   if (x_opt) {
```

```
  for (k = 0; k < count; ++k) {
-     TERMTYPE *term;
+     const TERMTYPE *term;
      set_curterm(terms[k]);
      term = (TERMTYPE *) cur_term;
      total += (size_t) (NUM_STRINGS(term) - STRCOUNT);
@@ -348,7 +348,7 @@
  widths1 = (int) strlen(modifier);

    for (k = 0; k < count; ++k) {
- char *value;
+ const char *value;
  set_curterm(terms[k]);
  if ((value = termname()) == NULL)
      failed("termname");
Index: test/move_field.c
Prereq:  1.16
--- ncurses-6.5-20240928+/test/move_field.c 2024-06-29 17:45:02.000000000 +0000
+++ ncurses-6.5-20241006/test/move_field.c 2024-10-06 21:12:35.000000000 +0000
@@ -26,7 +26,7 @@
  * authorization.                                           *
  ****************************************************************************/
 /*
- * $Id: move_field.c,v 1.16 2024/06/29 17:45:02 tom Exp $
+ * $Id: move_field.c,v 1.19 2024/10/06 21:12:35 tom Exp $
  *
  * Demonstrate move_field().
  */
@@ -146,27 +146,27 @@
 }

 static FieldAttrs
  *
-my_field_attrs(FIELD *f)
+my_field_attrs(NCURSES_CONST FIELD *f)
 {
    return (FieldAttrs *) field_userptr(f);
 }

 static int
-buffer_length(FIELD *f)
+buffer_length(NCURSES_CONST FIELD *f)
 {
    return my_field_attrs(f)->row_lengths[0];
 }

 static void
-set_buffer_length(FIELD *f, int length)
```

```
+set_buffer_length(NCURSES_CONST FIELD *f, int length)
{
   my_field_attrs(f)->row_lengths[0] = length;
}

static int
-offset_in_field(FORM *form)
+offset_in_field(NCURSES_CONST FORM *form)
{
-    FIELD *field = current_field(form);
+    NCURSES_CONST FIELD *field = current_field(form);
   int currow, curcol;

   form_getyx(form, currow, curcol);
@@ -245,7 +245,7 @@

 default:
     modified = (ch < MIN_FORM_COMMAND
-   && isprint(ch));
+   && isprint(UChar(ch)));
     break;
 }

@@ -275,9 +275,9 @@

/* display a status message to show what's happening */
static void
-show_status(FORM *form, FIELD *field)
+show_status(NCURSES_CONST FORM *form, NCURSES_CONST FIELD
 *field)
{
-    WINDOW *sub = form_sub(form);
+    NCURSES_CONST WINDOW *sub = form_sub(form);
   int currow, curcol;

   getyx(stdscr, currow, curcol);
Index: test/movewindow.c
Prereq:  1.54
--- ncurses-6.5-20240928+/test/movewindow.c 2023-05-27 20:13:10.000000000 +0000
+++ ncurses-6.5-20241006/test/movewindow.c 2024-10-06 18:44:26.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2018-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2018-2023,2024 Thomas E. Dickey                                *
 * Copyright 2006-2013,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
```

```
 * authorization.                                          *
 ****************************************************************************/
 /*
- * $Id: movewindow.c,v 1.54 2023/05/27 20:13:10 tom Exp $
+ * $Id: movewindow.c,v 1.56 2024/10/06 18:44:26 tom Exp $
 *
 * Demonstrate move functions for windows and derived windows from the curses
 * library.
@@ -135,7 +135,7 @@
 */
static PAIR *
selectcell(WINDOW *parent,
-    WINDOW *child,
+    NCURSES_CONST WINDOW *child,
    int uli, int ulj,
    int lri, int lrj,
    bool relative,
@@ -252,7 +252,7 @@
    int max_col = (parent == stdscr) ? COL_MAX : getmaxx(parent);
    int min_line = (parent == stdscr) ? LINE_MIN : 0;
    int max_line = (parent == stdscr) ? LINE_MAX : getmaxy(parent);
-    PAIR *tmp;
+    NCURSES_CONST PAIR *tmp;
    bool result = FALSE;

    head_line("Use arrows to move cursor, anything else to mark corner 1");
@@ -346,7 +346,7 @@
}

static WINDOW *
-parent_of(WINDOW *win)
+parent_of(NCURSES_CONST WINDOW *win)
{
    WINDOW *result = 0;
    int n = window2num(win);
@@ -435,7 +435,7 @@
 int max_col = top ? COL_MAX
 : getmaxx(parent);
 int min_line = top ? LINE_MIN : 0;
 int max_line = top ? LINE_MAX : getmaxy(parent);
- PAIR *tmp;
+ NCURSES_CONST PAIR *tmp;
 bool more;

 head_line("Select new position for %swindow", top ? "" : "sub");
@@ -474,7 +474,7 @@
}
```

```
static void
-show_derwin(WINDOW *win)
+show_derwin(NCURSES_CONST WINDOW *win)
{
   int pary, parx, maxy, maxx;

@@ -500,7 +500,7 @@
 int max_col = top ? COL_MAX : getmaxx(parent);
 int min_line = top ? LINE_MIN : 0;
 int max_line = top ? LINE_MAX : getmaxy(parent);
- PAIR *tmp;
+ NCURSES_CONST PAIR *tmp;
 bool more;

 show_derwin(win);
Index: test/ncurses.c
Prereq:  1.538
--- ncurses-6.5-20240928+/test/ncurses.c 2023-11-11 01:23:59.000000000 +0000
+++ ncurses-6.5-20241006/test/ncurses.c 2024-10-06 20:18:59.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2018-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2018-2023,2024
 Thomas E. Dickey                                *
 * Copyright 1998-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -41,7 +41,7 @@
   Author: Eric S. Raymond <esr@snark.thyrsus.com> 1993
         Thomas E. Dickey (beginning revision 1.27 in 1996).

-$Id: ncurses.c,v 1.538 2023/11/11 01:23:59 tom Exp $
+$Id: ncurses.c,v 1.541 2024/10/06 20:18:59 tom Exp $

****************************************************************************/

@@ -273,7 +273,7 @@
    ++x;
    break;
 default:
-    if (!isprint(ch) || ch >= KEY_MIN) {
+    if (!isprint(UChar(ch)) || ch >= KEY_MIN) {
  beep();
    } else if ((int) strlen(buffer) < limit) {
  int j;
@@ -928,7 +928,7 @@
  /* at least Solaris SVR4 curses breaks unctrl(128), etc. */
  c2 &= 0x7f;
```

```
#endif
-  if (isprint(c))
+  if (isprint(UChar(c)))
      (void)
 wprintw(win, "%c", UChar(c));
  else if (c2 != UChar(c))
      (void) wprintw(win, "M-%s", unctrl(c2));
@@ -1693,7 +1693,7 @@
     chtype extras = (chtype) ac;

     if (UseColors) {
-  NCURSES_PAIRS_T pair = 0;
+  NCURSES_PAIRS_T pair;
   if ((fg != COLOR_BLACK) || (bg != COLOR_BLACK)) {
       pair = 1;
       if (init_pair(pair, fg, bg) == ERR) {
@@ -2345,7 +2345,6 @@
 for (i = (NCURSES_PAIRS_T) (base_row * per_row); i < pairs_max; i++) {
     int row = grid_top + (i / per_row) - base_row;
     int col = (i % per_row + 1) * width;
-     NCURSES_PAIRS_T pair = i;

     if ((i / per_row) > row_limit)
   break;
@@ -2355,6 +2354,7 @@
     if (row >= 0 && move(row, col) != ERR) {
   NCURSES_COLOR_T fg = (NCURSES_COLOR_T) InxToFG(i);
   NCURSES_COLOR_T bg = (NCURSES_COLOR_T) InxToBG(i);
+  NCURSES_PAIRS_T pair = i;

   init_pair(pair, fg, bg);
   attron(COLOR_PAIR(pair));
@@ -2517,7 +2517,7 @@
 static int
 x_color_test(bool recur GCC_UNUSED)
 {
-    long i;
+    int i;

 int top = 0, width;
    int base_row = 0;
    int grid_top = top + 3;
@@ -2613,17 +2613,17 @@
 /* show color names/numbers across the top */
 for (i = 0; i < per_row; i++) {
     show_color_name(top + 2,
-       ((int) i + 1) * width,
-       (int) i * zoom_size + MinColors,
```

```
+       (i + 1) * width,
+       i * zoom_size + MinColors,
        opt_wide,
        opt_zoom);
 }

 /* show a grid of colors, with color names/ numbers on the left */
 for (i = (base_row * per_row); i < pairs_max; i++) {
-    int row = grid_top + ((int) i / per_row) - base_row;
-    int col = ((int) i % per_row + 1) * width;
-    int pair = (int) i;
+     int row = grid_top + (i / per_row) - base_row;
+     int col = (i % per_row + 1) * width;
+     int pair = i;

     if ((i / per_row) > row_limit)
  break;
@@ -2828,7 +2828,7 @@
#define DecodeRGB(n) (NCURSES_COLOR_T) ((n * 1000) / 0xffff)

static void
-init_all_colors(bool xterm_colors, char *palette_file)
+init_all_colors(bool xterm_colors, NCURSES_CONST
 char *palette_file)
{
   NCURSES_PAIRS_T cp;
   all_colors = typeMalloc(RGB_DATA, (unsigned) MaxColors);
@@ -3317,7 +3317,7 @@
{
   int c, fmt = 1;
   char buf[9];
-   char *s;
+    NCURSES_CONST char *s;
   attr_t attr = A_NORMAL;
   unsigned at_code = 0;
#if HAVE_SLK_COLOR
@@ -3938,8 +3938,7 @@

   *dst = *src;
   do {
- int count;
- TEST_CCHAR(src, count, {
+ TEST_CCHAR(src, {
     attr |= (test_attrs & A_ALTCHARSET);
     setcchar(dst, test_wch, attr, pair, NULL);
  }, {
@@ -4810,7 +4809,8 @@
/* Ask user for a window definition */
```

```
{
   WINDOW *rwindow;
-    pair ul, lr, *tmp;
+    pair ul, lr;
+    NCURSES_CONST pair *tmp;

   move(0, 0);
   clrtoeol();
@@ -5014,7 +5014,8 @@
#if HAVE_WRESIZE
 case CTRL('X'): /* resize window */
    if (current) {
-  pair *tmp, ul, lr;
+  NCURSES_CONST pair *tmp;
+  pair ul, lr;
  int mx, my;

  move(0, 0);
@@ -5249,7 +5250,7 @@
}

static void
-fill_panel(PANEL *pan)
+fill_panel(NCURSES_CONST PANEL
 *pan)
{
   WINDOW *win = panel_window(pan);
   const char *userptr = (const char *) panel_userptr(pan);
@@ -5286,7 +5287,7 @@
}

static void
-fill_wide_panel(PANEL *pan)
+fill_wide_panel(NCURSES_CONST PANEL *pan)
{
   WINDOW *win = panel_window(pan);
   const char *userptr = (const char *) panel_userptr(pan);
@@ -5336,7 +5337,7 @@
}

static int
-demo_panels(void (*InitPanel) (WINDOW *), void (*FillPanel) (PANEL *))
+demo_panels(void (*InitPanel) (WINDOW *), void (*FillPanel) (NCURSES_CONST PANEL *))
{
   int count;
   int itmp;
@@ -6246,7 +6247,8 @@
run_trace_menu(MENU * m)
```

```
{
   ITEM **items;
-    ITEM *i, **p;
+    NCURSES_CONST ITEM *i;
+    ITEM **p;

   for (;;) {
 bool changed = FALSE;
@@ -6424,7 +6426,7 @@

   if (field_info(me, &rows, &cols, &frow, &fcol, &nrow, &nbuf) == E_OK
 && nbuf > 0) {
- char *source = field_buffer(me, 1);
+ NCURSES_CONST char *source = field_buffer(me, 1);
 size_t have = (source ? strlen(source) : 0) + 1;
 size_t need
 = 80 + have;
 char *temp = malloc(need);
@@ -6434,7 +6436,7 @@
     _nc_STRNCPY(temp, source ? source : "", have + 1);
     len = (size_t) (char *) field_userptr(me);
     if (c <= KEY_MAX) {
-  if (isgraph(c) && (len + 1) < sizeof(temp)) {
+  if (isgraph(UChar(c)) && (len + 1) < sizeof(temp)) {
      temp[len++] = (char) c;
      temp[len] = 0;
      set_field_buffer(me, 1, temp);
@@ -6484,7 +6486,7 @@
 }

 static int
-form_virtualize(FORM *f, WINDOW *w)
+form_virtualize(NCURSES_CONST FORM *f, WINDOW *w)
 {
   /* *INDENT-OFF* */
   static const struct {
@@ -6658,7 +6660,7 @@
 static
 FIELDCHECK_CB(pw_field_check)
 {
-    char *s = field_buffer(fld, 0);
+    NCURSES_CONST char *s = field_buffer(fld, 0);
   int n;

   for (n = 0; s[n] != '\0'; ++n) {
@@ -6680,7 +6682,8 @@
 form_test(bool recur GCC_UNUSED)
 {
```

```
   FORM *form;
-    FIELD *f[12], *secure;
+    FIELD *f[12];
+    NCURSES_CONST FIELD *secure;
   FIELDTYPE *fty_middle = new_fieldtype(mi_field_check, mi_char_check);
    FIELDTYPE *fty_passwd = new_fieldtype(pw_field_check, pw_char_check);
   int c;
@@ -7176,7 +7179,7 @@
}

static void
-overlap_test_4(int flavor, WINDOW *a, WINDOW *b)
+overlap_test_4(int flavor, NCURSES_CONST WINDOW *a, WINDOW *b)
{
   switch ((otCOPY) flavor) {
   case otCOPY_overwrite:
@@ -7899,7 +7902,7 @@
   bool monochrome = FALSE;
#if HAVE_COLOR_CONTENT
   bool xterm_colors = FALSE;
-    char *palette_file = 0;
+    NCURSES_CONST char *palette_file = 0;
#endif

   setlocale(LC_ALL, "");
Index: test/padview.c
Prereq:  1.22
--- ncurses-6.5-20240928+/test/padview.c 2022-12-04 00:40:11.000000000 +0000
+++ ncurses-6.5-20241006/test/padview.c 2024-10-06 21:08:25.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2019-2021,2022 Thomas E. Dickey                                *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                                *
 * Copyright 2017 Free
 Software Foundation, Inc.                         *
 *                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -29,7 +29,7 @@
/*
 * clone of view.c, using pads
 *
- * $Id: padview.c,v 1.22 2022/12/04 00:40:11 tom Exp $
+ * $Id: padview.c,v 1.24 2024/10/06 21:08:25 tom Exp $
 */

#include <test.priv.h>
@@ -182,7 +182,7 @@
```

```
#if USE_WIDEC_SUPPORT
   if (!memcmp("\357\273\277", my_blob, 3)) {
- char *s = my_blob + 3;
+ const char *s = my_blob + 3;
 char *d = my_blob;
 Trace(("trim BOM"));
 do {
@@ -213,7 +213,7 @@
   for (k = 0; my_vec[k]; ++k) {
 char *s;
#if USE_WIDEC_SUPPORT
- char *last = my_vec[k] + (int) strlen(my_vec[k]);
+ const char *last = my_vec[k] + (int) strlen(my_vec[k]);
 wchar_t wch[2];
 size_t rc;
#ifndef state_unused
@@ -279,7 +279,7 @@
int
main(int argc, char *argv[])
{
-   static const char *help[] =
+   static NCURSES_CONST char *help[] =

   {
 "Commands:",
 "  q,^Q,ESC       - quit this program",
@@ -532,7 +532,7 @@
    beep();
    break;
 }
- if (c >= KEY_MIN || (c > 0 && !isdigit(c))) {
+ if (c >= KEY_MIN || (c > 0 && !isdigit(UChar(c)))) {
    got_number = FALSE;
    value = 0;
 }
Index: test/parse_rgb.h
Prereq:  1.5
--- ncurses-6.5-20240928+/test/parse_rgb.h 2020-02-02 23:34:34.000000000 +0000
+++ ncurses-6.5-20241006/test/parse_rgb.h 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2018,2020 Thomas E. Dickey                                     *
+ * Copyright 2018-2020,2024 Thomas E. Dickey                                *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
 * copy of this software and associated documentation files (the            *
@@ -26,7 +26,7 @@
 * authorization.
```

```
                                *
 ****************************************************************************/
/*
- * $Id: parse_rgb.h,v 1.5 2020/02/02 23:34:34 tom Exp $
+ * $Id: parse_rgb.h,v 1.6 2024/10/05 19:26:24 tom Exp $
 *
 * Sample implementation of ncurses RGB extension from user_caps(5).
 */
@@ -49,7 +49,7 @@
 int bits;
 int pwr2;
 int r = 0, g = 0, b = 0;
- char *data;
+ const char *data;
 char ch;

 for (max_bits = 0, pwr2 = 1;
Index: test/picsmap.c
Prereq:  1.149
--- ncurses-6.5-20240928+/test/picsmap.c 2023-04-23 23:20:37.000000000 +0000
+++ ncurses-6.5-20241006/test/picsmap.c 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2018-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2018-2023,2024 Thomas E. Dickey                                *
 * Copyright 2017,2018 Free Software Foundation, Inc.                       *
 *                                                                          *
                                        *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: picsmap.c,v 1.149 2023/04/23 23:20:37 tom Exp $
+ * $Id: picsmap.c,v 1.150 2024/10/05 19:26:24 tom Exp $
 *
 * Author: Thomas E. Dickey
 *
@@ -574,7 +574,7 @@
    _nc_STRCAT(full_name, filename, need);
    if (tries & 4) {
  char *t = s;
-  char *tc;
+  const char *tc;
  int num;
  char chr;
  int found = 0;
@@ -1374,8 +1374,8 @@
```

```
  int r, g, b, nocolor;
  float rf, gf, bf;
  unsigned check;
-  char *t;
-  char *s = t = strchr(buffer, '#');
+  char *s = strchr(buffer, '#');
+  const char *t = s;
  bool matched = FALSE;

  if (s != 0) {
@@ -1492,7 +1492,7 @@
#define fg_color(pics,n) (pics->fgcol[n].fgcol)

static void
-dump_picture(PICS_HEAD
- * pics)
+dump_picture(const PICS_HEAD * pics)
{
    int y, x;

@@ -1767,7 +1767,7 @@
#if USE_EXTENDED_COLORS
 case 'x':
     {
-  char *s = optarg;
+  const char *s = optarg;
  while (*s) {
      switch (*s++) {
      case 'p':
Index: test/popup_msg.c
Prereq:  1.12
--- ncurses-6.5-20240928+/test/popup_msg.c 2024-06-29 18:34:58.000000000 +0000
+++ ncurses-6.5-20241006/test/popup_msg.c 2024-10-06 21:07:01.000000000 +0000
@@ -27,7 +27,7 @@
 * authorization.                                       *
 ****************************************************************************/
/*
- * $Id: popup_msg.c,v 1.12 2024/06/29 18:34:58 tom Exp $
+ * $Id: popup_msg.c,v 1.13 2024/10/06 21:07:01 tom Exp $
 *
 * Show a multi-line message in a window which may extend beyond the screen.
 *
@@ -62,7 +62,7 @@
 * Display a temporary window, e.g., to display a help-message.
 */
void
-popup_msg(WINDOW *parent, const char *const *msg)
+popup_msg(WINDOW *parent, NCURSES_CONST
```

```
 char *const *msg)
{
   int x0 = 4;
   int y0 = 2;
@@ -171,12 +171,12 @@
void
popup_msg2(WINDOW *parent, char **msg)
{
-    popup_msg(parent, (const char *const *) msg);
+    popup_msg(parent, (NCURSES_CONST char *const *) msg);
}

#else
void
-popup_msg(WINDOW *parent, const char *const *msg)
+popup_msg(WINDOW *parent, NCURSES_CONST char *const *msg)
{
   (void) parent;
   (void) msg;
Index: test/popup_msg.h
Prereq:  1.5
--- ncurses-6.5-20240928+/test/popup_msg.h 2020-02-02 23:34:34.000000000 +0000
+++ ncurses-6.5-20241006/test/popup_msg.h 2024-10-06 21:17:54.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2018,2020 Thomas E. Dickey                                     *
+ * Copyright 2018-2020,2024 Thomas E. Dickey                                *
 * Copyright 2017 Free Software Foundation, Inc.                            *
 *                                                                          *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: popup_msg.h,v 1.5 2020/02/02 23:34:34 tom Exp $
+ * $Id: popup_msg.h,v 1.6 2024/10/06 21:17:54 tom Exp $
 *
 * Utility functions for a popup-message or help-screen.
 */
@@ -37,7 +37,7 @@

#include <test.priv.h>

-extern void popup_msg(WINDOW *parent, const char *const *msg);
+extern void popup_msg(WINDOW *parent, NCURSES_CONST char *const *msg);
extern void popup_msg2(WINDOW *parent, char **msg);
```

```
#endif /* POPUP_MSG_H_incl */
Index: test/railroad.c
Prereq:  1.26
--- ncurses-6.5-20240928+/test/railroad.c 2022-12-11 00:12:13.000000000 +0000
+++ ncurses-6.5-20241006/test/railroad.c 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
-
 * Copyright 2019-2020,2022 Thomas E. Dickey                                *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                                *
 * Copyright 2000-2013,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -30,7 +30,7 @@
/*
 * Author: Thomas E. Dickey - 2000
 *
- * $Id: railroad.c,v 1.26 2022/12/11 00:12:13 tom Exp $
+ * $Id: railroad.c,v 1.27 2024/10/05 19:26:24 tom Exp $
 *
 * A simple demo of the termcap interface.
 */
@@ -113,7 +113,7 @@
static void
ShowSign(char *string)
{
-    char *base = string;
+    const char *base = string;
    int first, last;

    if (moveit != 0) {
Index: test/rain.c
Prereq:  1.58
--- ncurses-6.5-20240928+/test/rain.c 2024-08-31 15:56:10.000000000 +0000
+++ ncurses-6.5-20241006/test/rain.c 2024-10-06 21:09:00.000000000 +0000
@@ -27,7 +27,7
 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: rain.c,v 1.58 2024/08/31 15:56:10 tom Exp $
+ * $Id: rain.c,v 1.62 2024/10/06 21:09:00 tom Exp $
 */
#include <test.priv.h>
#include <popup_msg.h>
@@ -45,7 +45,7 @@

struct DATA;
```

```
-typedef void (*DrawPart) (struct DATA *);
+typedef void (*DrawPart) (const struct DATA *);

typedef struct DATA {
   int y, x;
@@ -118,25 +118,25 @@
}

static void
-part1(DATA * drop)
+part1(const DATA * drop)
{
   MvAddCh(drop->y, drop->x, '.');
}

static void
-part2(DATA * drop)
+part2(const DATA * drop)
{
   MvAddCh(drop->y, drop->x, 'o');
}

static void
-part3(DATA * drop)
+part3(const DATA * drop)
{
   MvAddCh(drop->y, drop->x, 'O');
}

static void
-part4(DATA * drop)
+part4(const DATA * drop)
{
   MvAddCh(drop->y - 1, drop->x, '-');
   MvAddStr(drop->y, drop->x - 1, "|.|");
@@ -144,7 +144,7 @@
 }

static void
-part5(DATA * drop)
+part5(const DATA * drop)
{
   MvAddCh(drop->y - 2, drop->x, '-');
   MvAddStr(drop->y - 1, drop->x - 1, "/ \\");
@@ -154,7 +154,7 @@
}
```

```
static void
-part6(DATA * drop)
+part6(const DATA * drop)
{
   MvAddCh(drop->y - 2, drop->x, ' ');
   MvAddStr(drop->y - 1, drop->x - 1, "   ");
@@ -186,7 +186,7 @@
}

static void
-draw_part(void (*func) (DATA *), int state, DATA * data)
+draw_part(void (*func) (const DATA *), int state, DATA * data)
{
   data->func = func;
   data->state = state;
@@ -328,7 +328,7 @@
int
main(int argc, char *argv[])
{
-   static const char *help[] =
+   static NCURSES_CONST char *help[] =
   {
 "Commands:",
 " q/Q        exit the program",
Index: test/redraw.c
Prereq:  1.17
--- ncurses-6.5-20240928+/test/redraw.c 2022-12-10 22:28:50.000000000 +0000
+++ ncurses-6.5-20241006/test/redraw.c 2024-10-06 21:17:54.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
-
 * Copyright 2020-2021,2022 Thomas E. Dickey                                *
+ * Copyright 2020-2022,2024 Thomas E. Dickey                                *
 * Copyright 2006-2012,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: redraw.c,v 1.17 2022/12/10 22:28:50 tom Exp $
+ * $Id: redraw.c,v 1.18 2024/10/06 21:17:54 tom Exp $
 *
 * Demonstrate the redrawwin() and wredrawln() functions.
 * Thomas Dickey - 2006/11/4
@@ -61,7 +61,7 @@
static void
test_redraw(WINDOW *win)
```

```
{
-    static const char *help[] =
+    static NCURSES_CONST char *help[] =
     {
  "Commands:",
  "  ^Q/ESC/q   - quit",
Index: test/savescreen.c
Prereq:
  1.62
--- ncurses-6.5-20240928+/test/savescreen.c 2022-12-10 23:23:27.000000000 +0000
+++ ncurses-6.5-20241006/test/savescreen.c 2024-10-06 21:10:09.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2018-2021,2022 Thomas E. Dickey                                *
+ * Copyright 2018-2022,2024 Thomas E. Dickey                                *
  * Copyright 2006-2017,2018 Free Software Foundation, Inc.                  *
  *                                                                          *
  * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
  * authorization.                                                           *
  ****************************************************************************/
/*
- * $Id: savescreen.c,v 1.62 2022/12/10 23:23:27 tom Exp $
+ * $Id: savescreen.c,v 1.65 2024/10/06 21:10:09 tom Exp $
  *
  * Demonstrate save/restore functions
  from the curses library.
  * Thomas Dickey - 2007/7/14
@@ -96,7 +96,7 @@
}

static int
-load_screen(char *filename)
+load_screen(NCURSES_CONST char *filename)
{
    int result;

@@ -170,7 +170,7 @@
#if USE_WIDEC_SUPPORT
    cchar_t mycc;
#endif
-    char *filename = files[which];
+    NCURSES_CONST char *filename = files[which];
    bool dumped = FALSE;

    if (filename != 0) {
@@ -216,7 +216,7 @@
static void
```

```
editor_help(void)
{
-    static const char *msgs[] =
+    static NCURSES_CONST char *msgs[] =
     {
  "You are now in the screen-editor, which allows you to make some",
  "lines on the screen, as well as save copies of the screen to a",
@@ -238,7 +238,7 @@
static void
replay_help(void)
{
-    static const char *msgs[] =
+    static NCURSES_CONST char *msgs[] =
     {
  "You are now in the screen-loader, which allows you to view",
  "the dumped/restored screens.",
@@ -286,7 +286,7 @@
    bool replaying = FALSE;
    bool done = FALSE;
    char **files;
-
    char *fill_by = 0;
+    NCURSES_CONST char *fill_by = 0;
#if USE_WIDEC_SUPPORT
    cchar_t mycc;
    static const wchar_t mywc[2] =
Index: test/tclock.c
Prereq:  1.48
--- ncurses-6.5-20240928+/test/tclock.c 2023-02-25 16:42:22.000000000 +0000
+++ ncurses-6.5-20241006/test/tclock.c 2024-10-05 18:47:56.000000000 +0000
@@ -1,4 +1,4 @@
-/* $Id: tclock.c,v 1.48 2023/02/25 16:42:22 tom Exp $ */
+/* $Id: tclock.c,v 1.49 2024/10/05 18:47:56 tom Exp $ */

#define NEED_TIME_H
#include <test.priv.h>
@@ -145,7 +145,7 @@
    int lastbeep = -1;
    bool odd = FALSE;
    time_t tim;
-    struct tm *t;
+    const struct tm *t;
    char szChar[20];
    char *text;
    short my_bg = COLOR_BLACK;
Index: test/test.priv.h
Prereq:  1.219
--- ncurses-6.5-20240928+/test/test.priv.h 2024-08-31 10:46:01.000000000 +0000
```

```
+++ ncurses-6.5-20241006/test/test.priv.h 2024-10-05 19:01:00.000000000 +0000
@@ -30,7 +30,7 @@
/****************************************************************************
 *  Author: Thomas E. Dickey                    1996-on                     *
 ****************************************************************************/
-/* $Id: test.priv.h,v 1.219 2024/08/31 10:46:01 Rafael.Kitover Exp $ */
+/* $Id: test.priv.h,v 1.220 2024/10/05 19:01:00 tom Exp $ */

#ifndef __TEST_PRIV_H
#define __TEST_PRIV_H 1
@@ -765,8 +765,8 @@

#define VERSION_COMMON() \
static char *version_common(char **argv) { \
- char *base = argv[0]; \
- char *part = strrchr(base, '/'); \
+ const char *base = argv[0]; \
+ const char *part = strrchr(base, '/'); \
 size_t need = strlen(base) + 80; \
 char *result = malloc(need); \
 if (result != NULL) { \
@@ -916,8 +916,8 @@
 * Workaround in case getcchar() returns a positive value when the source
 * string produces only a L'\0'.
 */
-#define TEST_CCHAR(s, count, then_stmt, else_stmt) \
- if ((count = getcchar(s, NULL, NULL, NULL, NULL)) > 0) { \
+#define TEST_CCHAR(s, then_stmt, else_stmt) \
+ if (getcchar(s, NULL, NULL,
+  NULL, NULL) > 0) { \
     wchar_t test_wch[CCHARW_MAX + 2]; \
     attr_t test_attrs; \
     NCURSES_PAIRS_T test_pair; \
Index: test/test_add_wchstr.c
Prereq:  1.34
--- ncurses-6.5-20240928+/test/test_add_wchstr.c 2022-12-10 22:28:50.000000000 +0000
+++ ncurses-6.5-20241006/test/test_add_wchstr.c 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2020-2021,2022 Thomas E. Dickey                                *
+ * Copyright 2020-2022,2024 Thomas E. Dickey                                *
 * Copyright 2009-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
```

```
 /*
- * $Id: test_add_wchstr.c,v 1.34 2022/12/10 22:28:50 tom Exp $
+ * $Id: test_add_wchstr.c,v 1.35 2024/10/05 19:26:24 tom Exp $
 *
 * Demonstrate the waddwchstr() and wadd_wch functions.
 * Thomas Dickey - 2009/9/12
@@ -158,7 +158,7 @@
}

static void
-legend(WINDOW *win, int level, Options state, wchar_t *buffer, int length)
+legend(WINDOW *win, int level, Options state, const wchar_t *buffer, int length)
{
   const char *showstate;

Index: test/test_addchstr.c
Prereq:  1.29
--- ncurses-6.5-20240928+/test/test_addchstr.c 2022-12-10 22:28:50.000000000 +0000
+++ ncurses-6.5-20241006/test/test_addchstr.c 2024-10-05 19:26:24.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2020,2022 Thomas E. Dickey                                     *
+ * Copyright 2020-2022,2024 Thomas E. Dickey                                *
 * Copyright 2009-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: test_addchstr.c,v 1.29 2022/12/10 22:28:50 tom Exp $
+ * $Id: test_addchstr.c,v 1.30 2024/10/05 19:26:24 tom Exp $
 *
 * Demonstrate the waddchstr() and waddch functions.
 * Thomas Dickey - 2009/9/12
@@ -169,7 +169,7 @@
}

static int
-ColOf(char *buffer, int length, int margin)
+ColOf(const char *buffer, int length, int margin)
{
   int n;
   int result;
Index: test/test_addstr.c
Prereq:  1.20
--- ncurses-6.5-20240928+/test/test_addstr.c 2022-12-10 22:28:50.000000000 +0000
+++ ncurses-6.5-20241006/test/test_addstr.c 2024-10-05 19:27:33.000000000 +0000
```

```
@@ -1,5 +1,5 @@
/****************************************************************************
-
 * Copyright 2020,2022 Thomas E. Dickey                                     *
+ * Copyright 2020-2022,2024 Thomas E. Dickey                                *
 * Copyright 2009-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: test_addstr.c,v 1.20 2022/12/10 22:28:50 tom Exp $
+ * $Id: test_addstr.c,v 1.21 2024/10/05 19:27:33 tom Exp $
 *
 * Demonstrate the waddstr() and waddch functions.
 * Thomas Dickey - 2009/9/12
@@ -91,7 +91,7 @@
}

static int
-ColOf(char *buffer, int length, int margin)
+ColOf(const char *buffer, int length, int margin)
{
   int n;
   int result;
Index: test/test_addwstr.c
Prereq:  1.22
---
 ncurses-6.5-20240928+/test/test_addwstr.c 2023-05-27 20:13:10.000000000 +0000
+++ ncurses-6.5-20241006/test/test_addwstr.c 2024-10-05 19:27:33.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2020-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2020-2023,2024 Thomas E. Dickey                                *
 * Copyright 2009-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: test_addwstr.c,v 1.22 2023/05/27 20:13:10 tom Exp $
+ * $Id: test_addwstr.c,v 1.23 2024/10/05 19:27:33 tom Exp $
 *
 * Demonstrate the waddwstr() and wadd_wch
 functions.
 * Thomas Dickey - 2009/9/12
```

```
@@ -82,7 +82,7 @@
static int n_opt = -1;

static void
-legend(WINDOW *win, int level, Options state, wchar_t *buffer, int length)
+legend(WINDOW *win, int level, Options state, const wchar_t *buffer, int length)
{
   const char *showstate;

Index: test/test_endwin.c
Prereq:  1.2
--- ncurses-6.5-20240928+/test/test_endwin.c 2023-11-10 15:17:19.000000000 +0000
+++ ncurses-6.5-20241006/test/test_endwin.c 2024-10-05 19:27:33.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2023 Thomas E. Dickey                                          *
+ * Copyright 2023,2024 Thomas E. Dickey                                     *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
 * copy of this software and associated documentation files (the            *
@@ -26,7 +26,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: test_endwin.c,v 1.2 2023/11/10 15:17:19 tom Exp $
+ * $Id: test_endwin.c,v 1.3 2024/10/05 19:27:33 tom Exp $
 */
#include <test.priv.h>

@@ -67,7 +67,7 @@
   int rc_e1 = OK;
   int rc_e2 = OK;
   int rc_e3 = OK;
-   SCREEN *sp = NULL;
+    const SCREEN *sp = NULL;
   bool opt_e = FALSE;
   bool opt_i = FALSE;
   bool opt_n = FALSE;
Index: test/test_get_wstr.c
Prereq:  1.14
--- ncurses-6.5-20240928+/test/test_get_wstr.c 2022-12-10 23:59:13.000000000 +0000
+++ ncurses-6.5-20241006/test/test_get_wstr.c 2024-10-06 23:15:10.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2020,2022 Thomas E. Dickey                                     *
+ * Copyright 2020-2022,2024 Thomas E. Dickey                                *
 * Copyright 2007-2011,2017
```

```
 Free Software Foundation, Inc.                *
 *                                                                            *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                            *
 ****************************************************************************/
/*
- * $Id: test_get_wstr.c,v 1.14 2022/12/10 23:59:13 tom Exp $
+ * $Id: test_get_wstr.c,v 1.16 2024/10/06 23:15:10 tom Exp $
 *
 * Author: Thomas E Dickey
 *
@@ -69,7 +69,7 @@
}

static int
-Remainder(WINDOW *txtwin)
+Remainder(const WINDOW *txtwin)
{
   int result = getmaxx(txtwin) - getcurx(txtwin);
   return (result > 0) ? result : 0;
@@ -138,7 +138,7 @@
static int
recursive_test(int level, char **argv, WINDOW *strwin)
{
-   static const char *help[] =
+   static NCURSES_CONST char *help[] =
   {
 "Commands:",
 "  q,^Q,ESC       - quit this program",
Index: test/test_getstr.c
Prereq:
  1.16
--- ncurses-6.5-20240928+/test/test_getstr.c 2022-12-10 23:58:37.000000000 +0000
+++ ncurses-6.5-20241006/test/test_getstr.c 2024-10-06 22:36:46.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2020,2022 Thomas E. Dickey                                     *
+ * Copyright 2020-2022,2024 Thomas E. Dickey                                *
 * Copyright 2007-2012,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: test_getstr.c,v 1.16 2022/12/10 23:58:37 tom Exp $
+ * $Id: test_getstr.c,v 1.19 2024/10/06 22:36:46 tom Exp $
```

```
 *
 * Author: Thomas E Dickey
  *
@@ -76,7 +76,7 @@
}

static int
-Remainder(WINDOW *txtwin)
+Remainder(NCURSES_CONST WINDOW *txtwin)
{
   int result = getmaxx(txtwin) - getcurx(txtwin);
   return (result > 0) ? result : 0;
@@ -145,7 +145,7 @@
static int
recursive_test(int level, char **argv, WINDOW *strwin)
{
-    static const char *help[] =
+    static NCURSES_CONST char *help[] =
    {
 "Commands:",
 "  q,^Q,ESC       - quit this program",
Index: test/test_instr.c
Prereq:  1.13
--- ncurses-6.5-20240928+/test/test_instr.c 2024-06-29 18:42:53.000000000 +0000
+++ ncurses-6.5-20241006/test/test_instr.c 2024-10-06 21:11:54.000000000 +0000
@@ -27,7 +27,7 @@
 * authorization.                                               *
 ******************************************************************************/
/*
- * $Id: test_instr.c,v 1.13 2024/06/29 18:42:53 tom Exp $
+ * $Id: test_instr.c,v 1.15 2024/10/06 21:11:54 tom Exp $
 *
 * Author: Thomas E Dickey
 *
@@ -56,13 +56,13 @@
}

static
 void
-show_1st(WINDOW *win, int line, char *buffer)
+show_1st(WINDOW *win, int line, NCURSES_CONST char *buffer)
{
   MvWAddStr(win, line, 5, buffer);
}

static void
-showmore(WINDOW *win, int line, char *buffer)
+showmore(WINDOW *win, int line, NCURSES_CONST char *buffer)
```

```
{
   wmove(win, line, 0);
   wclrtoeol(win);
@@ -72,7 +72,7 @@
static void
show_help(WINDOW *win)
{
-    static const char *msgs[] =
+    static NCURSES_CONST char *msgs[] =
    {
 "Show file contents and a viewport from the variants of winstr."
 ,"Use h/j/k/l or arrow keys to move the viewport."
Index: test/test_inwstr.c
Prereq:  1.9
--- ncurses-6.5-20240928+/test/test_inwstr.c 2024-06-29 18:40:02.000000000 +0000
+++ ncurses-6.5-20241006/test/test_inwstr.c 2024-10-06 23:15:38.000000000 +0000
@@ -27,7 +27,7 @@
 * authorization.                                        *
 ****************************************************************************/
/*
- * $Id: test_inwstr.c,v
 1.9 2024/06/29 18:40:02 tom Exp $
+ * $Id: test_inwstr.c,v 1.11 2024/10/06 23:15:38 tom Exp $
 *
 * Author: Thomas E Dickey
 *
@@ -59,13 +59,13 @@
}

static void
-show_1st(WINDOW *win, int line, wchar_t *buffer)
+show_1st(WINDOW *win, int line, const wchar_t *buffer)
{
   (void) mvwaddwstr(win, line, 5, buffer);
}

static void
-showmore(WINDOW *win, int line, wchar_t *buffer)
+showmore(WINDOW *win, int line, const wchar_t *buffer)
{
   wmove(win, line, 0);
   wclrtoeol(win);
@@ -75,7 +75,7 @@
static void
show_help(WINDOW *win)
{
-    static const char *msgs[] =
+    static NCURSES_CONST char *msgs[] =
```

```
   {
 "Show file contents and a viewport from the variants of winwstr."
 ,"Use h/j/k/l or arrow keys to move the viewport."
Index: test/test_mouse.c
Prereq:  1.32
--- ncurses-6.5-20240928+/test/test_mouse.c 2024-08-31 10:46:01.000000000 +0000
+++ ncurses-6.5-20241006/test/test_mouse.c 2024-10-05 18:47:56.000000000 +0000
@@ -22,7 +22,7 @@
 * THE USE OR OTHER DEALINGS
 IN THE SOFTWARE.                        *
 ******************************************************************************/
/*
- * $Id: test_mouse.c,v 1.32 2024/08/31 10:46:01 Rafael.Kitover Exp $
+ * $Id: test_mouse.c,v 1.33 2024/10/05 18:47:56 tom Exp $
 *
 * Author: Leonid S Usov
 *
@@ -38,7 +38,7 @@
static void
raw_loop(void)
{
-    char *xtermcap;
+    const char *xtermcap;

    printf("Entering raw mode. Ctrl-c to quit.\n");

Index: test/test_opaque.c
Prereq:  1.15
--- ncurses-6.5-20240928+/test/test_opaque.c 2022-12-11 00:03:10.000000000 +0000
+++ ncurses-6.5-20241006/test/test_opaque.c 2024-10-05 19:27:33.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2020-2021,2022 Thomas E. Dickey                                *
+ * Copyright 2020-2022,2024 Thomas E. Dickey                                *
 * Copyright 2007-2008,2009 Free Software Foundation, Inc.                  *
 *                                                                          *
                                                                            *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: test_opaque.c,v 1.15 2022/12/11 00:03:10 tom Exp $
+ * $Id: test_opaque.c,v 1.16 2024/10/05 19:27:33 tom Exp $
 *
 * Author: Thomas E Dickey
 *
@@ -157,13 +157,13 @@
```

```
}

static int
-status_y(WINDOW *stswin, int cell)
+status_y(const WINDOW *stswin, int cell)
{
   return (cell % getmaxy(stswin));
}

static int
-status_x(WINDOW *stswin, int cell)
+status_x(const WINDOW *stswin, int cell)
{
   return (15 * (cell / getmaxy(stswin)));
}
Index: test/test_sgr.c
Prereq:  1.22
--- ncurses-6.5-20240928+/test/test_sgr.c 2023-05-27 20:13:10.000000000 +0000
+++ ncurses-6.5-20241006/test/test_sgr.c 2024-10-06 21:05:50.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
-
 * Copyright 2019-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2019-2023,2024 Thomas E. Dickey                                *
 * Copyright 2015-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -30,7 +30,7 @@
/*
 * Author: Thomas E. Dickey
 *
- * $Id: test_sgr.c,v 1.22 2023/05/27 20:13:10 tom Exp $
+ * $Id: test_sgr.c,v 1.25 2024/10/06 21:05:50 tom Exp $
 *
 * A simple demo of the sgr/sgr0 terminal capabilities.
 */
@@ -142,10 +142,10 @@
#define MASK_REV  (1 << 2)

static void
-dumpit(unsigned bits, unsigned ignore, const char *sgr, const char *sgr0)
+dumpit(unsigned bits, unsigned ignore, NCURSES_CONST char *sgr, NCURSES_CONST char *sgr0)
{
-    static const char sample[] = "abcdefghijklm";
-    static
 char params[] = "SURBDBIPA";
+    static NCURSES_CONST char sample[] = "abcdefghijklm";
+    static NCURSES_CONST char params[] = "SURBDBIPA";
```

```
   unsigned n;

   printf("%4u ", bits);
@@ -177,12 +177,11 @@
static void
brute_force(const char *name)
{
-   unsigned count;
-   char *my_sgr;
-   char *my_sgr0;
-   char *my_bold;
-   char *my_revs;
-   char *my_smso;
+    NCURSES_CONST char *my_sgr;
+    NCURSES_CONST char *my_sgr0;
+    NCURSES_CONST char *my_bold;
+    NCURSES_CONST char *my_revs;
+    NCURSES_CONST char *my_smso;
    char *my_name = strdup(name);

    if (db_list) {
@@ -219,6 +218,7 @@
 unsigned ignore = 0;
 unsigned reason = 0;
 unsigned repeat = 0;
+ unsigned count;
 for (count = 0; count < MAXSGR; ++count) {
     values[count] = tparm(my_sgr,
      BITS2P(1),
@@ -334,7 +334,7 @@
main(int argc, char *argv[])
{
    int ch;
-   char *name;
+    const char *name;

    while ((ch = getopt(argc, argv, OPTS_COMMON "d:e:nq")) != -1) {
 switch (ch)
 {
@@ -369,7 +369,7 @@
    } else if ((name = getenv("TERM")) != 0) {
 brute_force(name);
    } else {
- static char dumb[] = "dumb";
+ static const char dumb[] = "dumb";
 brute_force(dumb);
    }
```

```
Index: test/test_tparm.c
Prereq:  1.39
--- ncurses-6.5-20240928+/test/test_tparm.c 2023-11-11 01:00:03.000000000 +0000
+++ ncurses-6.5-20241006/test/test_tparm.c 2024-10-06 20:50:27.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2020-2022,2023 Thomas E. Dickey                                *
+ * Copyright 2020-2023,2024 Thomas E. Dickey                                *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
 * copy of this software and associated documentation files (the            *
@@ -29,7 +29,7 @@
/*
 * Author: Thomas E. Dickey
 *
- * $Id: test_tparm.c,v 1.39 2023/11/11 01:00:03
 tom Exp $
+ * $Id: test_tparm.c,v 1.42 2024/10/06 20:50:27 tom Exp $
 *
 * Exercise tparm/tiparm, either for all possible capabilities with fixed
 * parameters, or one capability with specific combinations of parameters.
@@ -107,7 +107,7 @@
}

static int
-isNumeric(char *source)
+isNumeric(NCURSES_CONST char *source)
{
   char *next = 0;
   long value = strtol(source, &next, 0);
@@ -245,7 +245,7 @@
#define NS_9(fmt) NS_8(fmt), NumStr(8)

static void
-test_tparm(const char *name, const char *format, long *number, char **string)
+test_tparm(const char *name, NCURSES_CONST char *format, long *number, char **string)
{
   char *use_strings[MAX_PARM];
   char *result = NULL;
@@ -527,7 +527,7 @@
    }
 } else {
    char *s = t_opt;
-    char *t;
+    NCURSES_CONST char *t;
    while ((t = strtok(s, ",")) != 0) {
  s = 0;
  if (len_terms + 2 >= max_terms) {
```

```
@@ -603,7 +603,7 @@
#if NCURSES_XNAMES
    len_caps = std_caps;
    if (cur_term) {
-  TERMTYPE *term =
 (TERMTYPE *) cur_term;
+  NCURSES_CONST TERMTYPE *term = (TERMTYPE *) cur_term;
   for (n = STRCOUNT; n < NUM_STRINGS(term); ++n) {
      GrowArray(all_caps, max_caps, len_caps);
      GrowArray(cap_name, max_name, len_caps);
Index: test/test_vidputs.c
Prereq:  1.15
--- ncurses-6.5-20240928+/test/test_vidputs.c 2022-12-10 23:23:27.000000000 +0000
+++ ncurses-6.5-20241006/test/test_vidputs.c 2024-10-06 21:17:54.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2020-2021,2022 Thomas E. Dickey                                *
+ * Copyright 2020-2022,2024 Thomas E. Dickey                                *
 * Copyright 2013-2014,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -27,7 +27,7 @@
 * authorization.                                                           *
 ****************************************************************************/
/*
- * $Id: test_vidputs.c,v 1.15 2022/12/10 23:23:27 tom Exp $
+ * $Id: test_vidputs.c,v 1.16 2024/10/06 21:17:54 tom Exp $
 *
 * Demonstrate the vidputs and vidattr functions.
 * Thomas Dickey - 2013/01/12
@@ -51,7 +51,7 @@
}

static bool
-outs(const char *s)
+outs(NCURSES_CONST char *s)
{
   if (VALID_STRING(s)) {
 tputs(s, 1, outc);
Index: test/testcurs.c
Prereq:  1.58
--- ncurses-6.5-20240928+/test/testcurs.c 2023-05-28 14:23:34.000000000 +0000
+++ ncurses-6.5-20241006/test/testcurs.c 2024-10-05 19:17:19.000000000 +0000
@@ -6,7 +6,7 @@
 *  wrs(5/28/93) -- modified to be consistent (perform identically) with either
 *                  PDCurses or under Unix System V, R4
 *
```

```
- * $Id: testcurs.c,v 1.58 2023/05/28 14:23:34 tom Exp $
+ * $Id: testcurs.c,v 1.59 2024/10/05 19:17:19 tom Exp $
 */

#include <test.priv.h>
@@ -245,7 +245,7 @@
 wclrtobot(win);
 if (c >= KEY_MIN)
     wprintw(win, "Key Pressed: %s", keyname(c));
- else if (isprint(c))
+ else if (isprint(UChar(c)))
    wprintw(win, "Key Pressed: %c", c);
 else
    wprintw(win, "Key Pressed: %s", unctrl(UChar(c)));
@@ -748,8 +748,8 @@
 keypad(stdscr, TRUE);
 raw();
 key = getch();
- if (key < KEY_MIN && key > 0 && isalpha(key)) {
-     if (islower(key))
+ if (key < KEY_MIN && key > 0 && isalpha(UChar(key))) {
+     if (islower(UChar(key)))
  key = toupper(key);
    for (n = 0; n < MAX_OPTIONS; ++n) {
  if (key == command[n].text[0]) {
Index: test/testscanw.c
Prereq:  1.15
--- ncurses-6.5-20240928+/test/testscanw.c 2022-12-11 00:10:29.000000000 +0000
+++ ncurses-6.5-20241006/test/testscanw.c 2024-10-05 19:27:33.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
- * Copyright 2019-2020,2022 Thomas E. Dickey                                *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                                *
 *
 Copyright 1998-2002,2006 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -30,7 +30,7 @@
 * Date:  1997/03/17
 * From:  bayern@morpheus.cis.yale.edu
 *
- * $Id: testscanw.c,v 1.15 2022/12/11 00:10:29 tom Exp $
+ * $Id: testscanw.c,v 1.16 2024/10/05 19:27:33 tom Exp $
 */
#include <test.priv.h>

@@ -85,7 +85,7 @@
   curses_trace(TRACE_UPDATE | TRACE_CALLS);
```

```
#endif
    while (optind < argc) {
- char *token = argv[optind++];
+ const char *token = argv[optind++];
 if (isdigit(UChar(*token)))
     move(atoi(token), 0);
 else if (!strcmp(token, "k+"))
Index: test/view.c
Prereq:  1.145
--- ncurses-6.5-20240928+/test/view.c 2022-12-04 00:40:11.000000000 +0000
+++ ncurses-6.5-20241006/test/view.c 2024-10-06 21:08:05.000000000 +0000
@@ -1,5 +1,5 @@
/****************************************************************************
-
 * Copyright 2019-2021,2022 Thomas E. Dickey                                *
+ * Copyright 2019-2022,2024 Thomas E. Dickey                                *
 * Copyright 1998-2016,2017 Free Software Foundation, Inc.                  *
 *                                                                          *
 * Permission is hereby granted, free of charge, to any person obtaining a  *
@@ -52,7 +52,7 @@
 * scroll operation worked, and the refresh() code only had to do a
 * partial repaint.
 *
- * $Id: view.c,v 1.145 2022/12/04 00:40:11 tom Exp $
+ * $Id: view.c,v 1.147 2024/10/06 21:08:05 tom Exp $
 */

#include <test.priv.h>
@@ -93,8 +93,7 @@

#if USE_WIDEC_SUPPORT
    for (;;) {
- int count;
- TEST_CCHAR(src, count, {
+ TEST_CCHAR(src, {
     int len = wcwidth(test_wch[0]);
     result += (len > 0) ? len : 1;
     ++src;
@@ -186,12 +185,10 @@
      */
     {
  int j;
-  int width = 1;
+  int width;

  for (j = actual = 0; j < shift; ++j) {
-      int count;
-
```

```
-
    TEST_CCHAR(s + j, count, {
+       TEST_CCHAR(s + j, {
   width = wcwidth(test_wch[0]);
      }
      , {
@@ -294,7 +291,7 @@

#if USE_WIDEC_SUPPORT
    if (!memcmp("\357\273\277", my_blob, 3)) {
- char *s = my_blob + 3;
+ const char *s = my_blob + 3;
 char *d = my_blob;
 Trace(("trim BOM"));
 do {
@@ -329,7 +326,7 @@
 char *s;
 int y, x;
#if USE_WIDEC_SUPPORT
- char *last = my_vec[k] + (int) strlen(my_vec[k]);
+ const char *last = my_vec[k] + (int) strlen(my_vec[k]);
 wchar_t wch[2];
 size_t rc;
#ifndef state_unused
@@ -408,7 +405,7 @@
int
main(int argc, char *argv[])
{
-    static const char *help[] =
+    static NCURSES_CONST char *help[] =
    {
 "Commands:",
 "  q,^Q,ESC       - quit this program",
@@ -659,7 +656,7 @@
     beep();
     break;
 }
- if (c >= KEY_MIN || (c > 0 && !isdigit(c))) {
+ if (c >= KEY_MIN || (c > 0 && !isdigit(UChar(c)))) {
     got_number = FALSE;
     value = 0;
 }
```

Found in path(s):
* /ncurses-6-5-20241006-patch-gz/ncurses-6.5-20241006.patch

1.130 clientmodel 0.6.2

1.130.1 Available under license :

Data model artifacts for Prometheus.
Copyright 2012-2015 The Prometheus Authors

This product includes software developed at
SoundCloud Ltd. (http://soundcloud.com/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct

or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.131 musl-utils 1.2.5-r9

1.131.1 Available under license :

musl as a whole is licensed under the following standard MIT license:

Copyright © 2005-2020 Rich Felker, et al.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Authors/contributors include:

A. Wilcox
Ada Worcester
Alex Dowad
Alex Suykov
Alexander Monakov
Andre McCurdy
Andrew Kelley
Anthony G. Basile
Aric Belsito
Arvid Picciani
Bartosz Brachaczek
Benjamin Peterson
Bobby Bingham
Boris Brezillon
Brent Cook
Chris Spiegel
Clment Vasseur
Daniel Micay
Daniel Sabogal
Daurnimator
David Carlier
David Edelsohn
Denys Vlasenko
Dmitry Ivanov
Dmitry V. Levin
Drew DeVault
Emil Renner Berthing
Fangrui Song
Felix Fietkau
Felix Janda
Gianluca Anzolin
Hauke Mehrtens
He X
Hiltjo Posthuma
Isaac Dunham
Jaydeep Patil
Jens Gustedt

Jeremy Huntwork
Jo-Philipp Wich
Joakim Sindholt
John Spencer
Julien Ramseier
Justin Cormack
Kaarle Ritvanen
Khem Raj
Kylie McClain
Leah Neukirchen
Luca Barbato
Luka
Perkov
M Farkas-Dyck (Strake)
Mahesh Bodapati
Markus Wichmann
Masanori Ogino
Michael Clark
Michael Forney
Mikhail Kremnyov
Natanael Copa
Nicholas J. Kain
orc
Pascal Cuoq
Patrick Oppenlander
Petr Hosek
Petr Skocik
Pierre Carrier
Reini Urban
Rich Felker
Richard Pennington
Ryan Fairfax
Samuel Holland
Segev Finer
Shiz
sin
Solar Designer
Stefan Kristiansson
Stefan O'Rear
Szabolcs Nagy
Timo Ters
Trutz Behn
Valentin Ochs
Will Dietz
William Haddon
William Pitcock

Portions of this software are derived from third-party works licensed

under terms compatible with the above MIT license:

The TRE regular expression implementation (src/regex/reg* and
src/regex/tre*) is Copyright 2001-2008 Ville Laurikari and licensed
under a 2-clause BSD license (license text in the source files). The
included version has been heavily modified by Rich Felker in 2012, in
the interests of size, simplicity, and namespace cleanliness.

Much of the math library code (src/math/* and src/complex/*) is
Copyright 1993,2004
 Sun Microsystems or
Copyright 2003-2011 David Schultz or
Copyright 2003-2009 Steven G. Kargl or
Copyright 2003-2009 Bruce D. Evans or
Copyright 2008 Stephen L. Moshier or
Copyright 2017-2018 Arm Limited
and labelled as such in comments in the individual source files. All
have been licensed under extremely permissive terms.

The ARM memcpy code (src/string/arm/memcpy.S) is Copyright 2008
The Android Open Source Project and is licensed under a two-clause BSD
license. It was taken from Bionic libc, used on Android.

The AArch64 memcpy and memset code (src/string/aarch64/*) are
Copyright 1999-2019, Arm Limited.

The implementation of DES for crypt (src/crypt/crypt_des.c) is
Copyright 1994 David Burren. It is licensed under a BSD license.

The implementation of blowfish crypt (src/crypt/crypt_blowfish.c) was
originally written by Solar Designer and placed into the public
domain. The code also comes with a fallback permissive license for use
in jurisdictions that may not recognize the
 public domain.

The smoothsort implementation (src/stdlib/qsort.c) is Copyright 2011
Valentin Ochs and is licensed under an MIT-style license.

The x86_64 port was written by Nicholas J. Kain and is licensed under
the standard MIT terms.

The mips and microblaze ports were originally written by Richard
Pennington for use in the ellcc project. The original code was adapted
by Rich Felker for build system and code conventions during upstream
integration. It is licensed under the standard MIT terms.

The mips64 port was contributed by Imagination Technologies and is
licensed under the standard MIT terms.

The powerpc port was also originally written by Richard Pennington,
and later supplemented and integrated by John Spencer. It is licensed
under the standard MIT terms.

All other files which have no copyright comments are original works
produced specifically for use as part of this library, written either
by Rich Felker, the main author of the library, or by one or more
contibutors listed
 above. Details on authorship of individual files
can be found in the git version control history of the project. The
omission of copyright and license comments in each file is in the
interest of source tree size.

In addition, permission is hereby granted for all public header files
(include/* and arch/*/bits/*) and crt files intended to be linked into
applications (crt/*, ldso/dlstart.c, and arch/*/crt_arch.h) to omit
the copyright notice and permission notice otherwise required by the
license, and to use these files without any requirement of
attribution. These files include substantial contributions from:

Bobby Bingham
John Spencer
Nicholas J. Kain
Rich Felker
Richard Pennington
Stefan Kristiansson
Szabolcs Nagy

all of whom have explicitly granted such permission.

This file previously contained text expressing a belief that most of
the files covered by the above exception were sufficiently trivial not
to be subject to copyright, resulting in confusion over whether it
negated
 the permissions granted in the license. In the spirit of
permissive licensing, and of not having licensing issues being an
obstacle to adoption, that text has been removed.

1.132 ca-certificates 20250619-r0

1.132.1 Available under license :

No license file was found, but licenses were detected in source scan.

#!/usr/bin/env perl
***
*   _   _ ____ _

```
# *  Project                     ___| | | |  _ \| |
# *                             / __| | | | |_) | |
# *                            | (__| |_| |  _ <| |___
# *                             \___|\___/|_| \_\_____|
# *
# * Copyright (C) Daniel Stenberg, <daniel@haxx.se>, et al.
# *
# * This software is licensed as described in the file COPYING, which
# * you should have received as part of this distribution. The terms
# * are also available at https://curl.se/docs/copyright.html.
# *
# * You may opt to use, copy, modify, merge, publish, distribute and/or sell
# * copies of the Software, and permit persons to whom the Software is
# * furnished to do so, under the terms of the COPYING file.
# *
# * This software is distributed on an "AS IS" basis, WITHOUT WARRANTY OF ANY
#
 * KIND, either express or implied.
# *
# * SPDX-License-Identifier: curl
# *
# ***************************************************************************
# This Perl script creates a fresh ca-bundle.crt file for use with libcurl.
# It downloads certdata.txt from Mozilla's source tree (see URL below),
# then parses certdata.txt and extracts CA Root Certificates into PEM format.
# These are then processed with the OpenSSL commandline tool to produce the
# final ca-bundle.crt file.
# The script is based on the parse-certs script written by Roland Krikava.
# This Perl script works on almost any platform since its only external
# dependency is the OpenSSL commandline tool for optional text listing.
# Hacked by Guenter Knauf.
#
```

Found in path(s):
* /ca-certificates-20250619-tar-bz2/ca-certificates-20250619/mk-ca-bundle.pl
No license file was found, but licenses were detected in source scan.

```
/* c_rehash.c - Create hash symlinks for certificates
* C implementation based on the original Perl and shell versions
*
* Copyright (c) 2013-2014 Timo Teräs <timo.teras@iki.fi>
* All rights reserved.
*
* This software is licensed under the MIT License.
* Full license available at: http://opensource.org/licenses/MIT
*/
```

Found in path(s):

* /ca-certificates-20250619-tar-bz2/ca-certificates-20250619/c_rehash.c
Mozilla Public License
Version 2.0
1. Definitions
1.1. “Contributor”
means each individual or legal entity that creates, contributes to the creation of, or owns Covered Software.

1.2. “Contributor Version”
means the combination of the Contributions of others (if any) used by a Contributor and that particular Contributor’s Contribution.

1.3. “Contribution”
means Covered Software of a particular Contributor.

1.4. “Covered Software”
means Source Code Form to which the initial Contributor has attached the notice in Exhibit A, the Executable Form of such Source Code Form, and Modifications of such Source Code Form, in each case including portions thereof.

1.5. “Incompatible With Secondary Licenses”
means

that the initial Contributor has attached the notice described in Exhibit B to the Covered Software; or

that the Covered Software was made available under the terms of version 1.1 or earlier of the License, but not also under the terms of a Secondary License.

1.6. “Executable Form”
means
any form of the work other than Source Code Form.

1.7. “Larger Work”
means a work that combines Covered Software with other material, in a separate file or files, that is not Covered Software.

1.8. “License”
means this document.

1.9. “Licensable”
means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently, any and all of the rights conveyed by this License.

1.10. “Modifications”
means any of the following:

any file in Source Code Form that results from an addition to, deletion from, or modification of the contents of Covered Software; or

any new file in Source Code Form that contains any Covered Software.

1.11. “Patent Claims” of a Contributor
means any patent claim(s), including without limitation, method, process, and apparatus claims, in any patent Licensable by such Contributor that would be infringed, but for the grant of the License, by the making, using, selling, offering for sale, having made, import, or transfer
of either its Contributions or its Contributor Version.

1.12. “Secondary License”
means either the GNU General Public License, Version 2.0, the GNU Lesser General Public License, Version 2.1, the GNU Affero General Public License, Version 3.0, or any later versions of those licenses.

1.13. “Source Code Form”
means the form of the work preferred for making modifications.

1.14. “You” (or “Your”)
means an individual or a legal entity exercising rights under this License. For legal entities, “You” includes any entity that controls, is controlled by, or is under common control with You. For purposes of this definition, “control” means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants and Conditions
2.1. Grants
Each Contributor hereby grants You a world-wide, royalty-free, non-exclusive
license:

under intellectual property rights (other than patent or trademark) Licensable by such Contributor to use, reproduce, make available, modify, display, perform, distribute, and otherwise exploit its Contributions, either on an unmodified basis, with Modifications, or as part of a Larger Work; and

under Patent Claims of such Contributor to make, use, sell, offer for sale, have made, import, and otherwise transfer either its Contributions or its Contributor Version.

2.2. Effective Date
The licenses granted in Section 2.1 with respect to any Contribution become effective for each Contribution on the date the Contributor first distributes such Contribution.

2.3. Limitations on Grant Scope
The licenses granted in this Section 2 are the only rights granted under this License. No additional rights or licenses will be implied from the distribution or licensing of Covered Software under this License. Notwithstanding Section 2.1(b) above, no patent license is granted by a Contributor:

for
any code that a Contributor has removed from Covered Software; or

for infringements caused by: (i) Your and any other third party’s modifications of Covered Software, or (ii) the combination of its Contributions with other software (except as part of its Contributor Version); or

under Patent Claims infringed by Covered Software in the absence of its Contributions.

This License does not grant any rights in the trademarks, service marks, or logos of any Contributor (except as may be necessary to comply with the notice requirements in Section 3.4).

2.4. Subsequent Licenses
No Contributor makes additional grants as a result of Your choice to distribute the Covered Software under a subsequent version of this License (see Section 10.2) or under the terms of a Secondary License (if permitted under the terms of Section 3.3).

2.5. Representation
Each Contributor represents that the Contributor believes its Contributions are its original creation(s) or it has sufficient rights
to grant the rights to its Contributions conveyed by this License.

2.6. Fair Use
This License is not intended to limit any rights You have under applicable copyright doctrines of fair use, fair dealing, or other equivalents.

2.7. Conditions
Sections 3.1, 3.2, 3.3, and 3.4 are conditions of the licenses granted in Section 2.1.

3. Responsibilities
3.1. Distribution of Source Form
All distribution of Covered Software in Source Code Form, including any Modifications that You create or to which You contribute, must be under the terms of this License. You must inform recipients that the Source Code Form of the Covered Software is governed by the terms of this License, and how they can obtain a copy of this License. You may not attempt to alter or restrict the recipients' rights in the Source Code Form.

3.2. Distribution of Executable Form
If You distribute Covered Software in Executable Form then:

such Covered Software must also be made available in Source Code Form, as described in
Section 3.1, and You must inform recipients of the Executable Form how they can obtain a copy of such Source Code Form by reasonable means in a timely manner, at a charge no more than the cost of distribution to the recipient; and

You may distribute such Executable Form under the terms of this License, or sublicense it under different terms, provided that the license for the Executable Form does not attempt to limit or alter the recipients' rights in the Source Code Form under this License.

3.3. Distribution of a Larger Work
You may create and distribute a Larger Work under terms of Your choice, provided that You also comply with the requirements of this License for the Covered Software. If the Larger Work is a combination of Covered Software with a work governed by one or more Secondary Licenses, and the Covered Software is not Incompatible With Secondary Licenses, this License permits You to additionally distribute such Covered Software under the terms of such Secondary License(s),

so that the recipient of the Larger Work may, at their option, further distribute the Covered Software under the terms of either this License or such Secondary License(s).

3.4. Notices
You may not remove or alter the substance of any license notices (including copyright notices, patent notices, disclaimers of warranty, or limitations of liability) contained within the Source Code Form of the Covered Software, except that You may alter any license notices to the extent required to remedy known factual inaccuracies.

3.5. Application of Additional Terms
You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, You may do so only on Your own behalf, and not on behalf of any Contributor. You must make it absolutely clear that any such warranty, support, indemnity, or liability obligation is offered by You alone, and You hereby agree to indemnify every Contributor for any liability incurred by such Contributor as a result of warranty, support, indemnity or liability terms You offer. You may include additional disclaimers of warranty and limitations of liability specific to any jurisdiction.

4. Inability to Comply Due to Statute or Regulation
If it is impossible for You to comply with any of the terms of this License with respect to some or all of the Covered Software due to statute, judicial order, or regulation then You must: (a) comply with the terms of this License to the maximum extent possible; and (b) describe the limitations and the code they affect. Such description must be placed in a text file included with all distributions of the Covered Software under this License. Except to the extent prohibited by statute or regulation, such description must be sufficiently detailed for a recipient of ordinary skill to be able to understand it.

5. Termination
5.1. The rights granted under this License will terminate automatically if You fail to comply with any of its terms. However, if You become compliant, then the rights granted under this License from a particular Contributor are reinstated (a) provisionally, unless and until such Contributor explicitly and finally terminates Your grants, and (b) on an ongoing basis, if such Contributor fails to notify You of the non-compliance by some reasonable means prior to 60 days after You have come back into compliance. Moreover, Your grants from a particular Contributor are reinstated on an ongoing basis if such Contributor notifies You of the non-compliance by some reasonable means, this is the first time You have received notice of non-compliance with this License from such Contributor, and You become compliant prior to 30 days after Your receipt of the notice.

5.2. If You initiate litigation against any entity by asserting a patent infringement claim (excluding declaratory judgment actions, counter-claims, and cross-claims) alleging that a Contributor Version directly or indirectly infringes any patent,
then the rights granted to You by any and all Contributors for the Covered Software under Section 2.1 of this License shall terminate.

5.3. In the event of termination under Sections 5.1 or 5.2 above, all end user license agreements (excluding distributors and resellers) which have been validly granted by You or Your distributors under this License prior to termination shall survive termination.

6. Disclaimer of Warranty
Covered Software is provided under this License on an “as is” basis, without warranty of any kind, either expressed, implied, or statutory, including, without limitation, warranties that the Covered Software is free of defects, merchantable, fit for a particular purpose or non-infringing. The entire risk as to the quality and performance of the

Covered Software is with You. Should any Covered Software prove defective in any respect, You (not any Contributor) assume the cost of any necessary servicing, repair, or correction. This disclaimer of warranty constitutes
an essential part of this License. No use of any Covered Software is authorized under this License except under this disclaimer.

7. Limitation of Liability
Under no circumstances and under no legal theory, whether tort (including negligence), contract, or otherwise, shall any Contributor, or anyone who distributes Covered Software as permitted above, be liable to You for any direct, indirect, special, incidental, or consequential damages of any character including, without limitation, damages for lost profits, loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses, even if such party shall have been informed of the possibility of such damages. This limitation of liability shall not apply to liability for death or personal injury resulting from such party's negligence to the extent applicable law prohibits such limitation. Some jurisdictions do not allow the exclusion or limitation of incidental or consequential damages, so
this exclusion and limitation may not apply to You.

8. Litigation
Any litigation relating to this License may be brought only in the courts of a jurisdiction where the defendant maintains its principal place of business and such litigation shall be governed by laws of that jurisdiction, without reference to its conflict-of-law provisions. Nothing in this Section shall prevent a party's ability to bring cross-claims or counter-claims.

9. Miscellaneous
This License represents the complete agreement concerning the subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. Any law or regulation which provides that the language of a contract shall be construed against the drafter shall not be used to construe this License against a Contributor.

10. Versions of the License
10.1. New Versions
Mozilla Foundation is the license steward. Except as provided in Section 10.3, no one other
than the license steward has the right to modify or publish new versions of this License. Each version will be given a distinguishing version number.

10.2. Effect of New Versions
You may distribute the Covered Software under the terms of the version of the License under which You originally received the Covered Software, or under the terms of any subsequent version published by the license steward.

10.3. Modified Versions
If you create software not governed by this License, and you want to create a new license for such software, you may create and use a modified version of this License if you rename the license and remove any references to the name of the license steward (except to note that such modified license differs from this License).

10.4. Distributing Source Code Form that is Incompatible With Secondary Licenses
If You choose to distribute Source Code Form that is Incompatible With Secondary Licenses under the terms of this version of the License, the notice described in

Exhibit B of this License must be attached.

Exhibit A - Source Code Form License Notice
This Source Code Form is subject to the terms of the Mozilla Public License, v. 2.0. If a copy of the MPL was not distributed with this file, You can obtain one at https://mozilla.org/MPL/2.0/.

If it is not possible or desirable to put the notice in a particular file, then You may include the notice in a location (such as a LICENSE file in a relevant directory) where a recipient would be likely to look for such a notice.

You may add additional accurate notices of copyright ownership.

Exhibit B - “Incompatible With Secondary Licenses” Notice
This Source Code Form is “Incompatible With Secondary Licenses”, as defined by the Mozilla Public License, v. 2.0.
No license file was found, but licenses were detected in source scan.

#
This Source Code Form is subject to the terms of the Mozilla Public
License, v. 2.0. If a copy of the MPL was not distributed with this
file, You can obtain one at http://mozilla.org/MPL/2.0/.

Found in path(s):
* /ca-certificates-20250619-tar-bz2/ca-certificates-20250619/certdata.txt

1.133 libcrypto3 3.3.4-r0

1.133.1 Notifications :

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/)
This product includes cryptographic software written by Eric Young (eay@cryptsoft.com).
This product includes software written by Tim Hudson (tjh@cryptsoft.com).

1.133.2 Available under license :

LibreSSL files are retained under the copyright of the authors. New
additions are ISC licensed as per OpenBSD's normal licensing policy,
or are placed in the public domain.

The OpenSSL code is distributed under the terms of the original OpenSSL
licenses which follow:

LICENSE ISSUES
==========

The OpenSSL toolkit stays under a dual license, i.e. both the conditions of
the OpenSSL License and the original SSLeay license apply to the toolkit.
See below for the actual license texts. In case of any license issues
related to OpenSSL please contact openssl-core@openssl.org.

OpenSSL License

```
/* ====================================================================
* Copyright (c) 1998-2011 The OpenSSL Project.  All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above
 copyright
*    notice, this list of conditions and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in
*    the documentation and/or other materials provided with the
*    distribution.
*
* 3. All advertising materials mentioning features or use of this
*    software must display the following acknowledgment:
*    "This product includes software developed by the OpenSSL Project
*    for use in the OpenSSL Toolkit. (http://www.openssl.org/)"
*
* 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to
*    endorse or promote products derived from this software without
*    prior written permission. For written permission, please contact
*    openssl-core@openssl.org.
*
* 5. Products derived from this software may not be called "OpenSSL"
*    nor may "OpenSSL" appear in their names without prior written
*    permission of the OpenSSL Project.
 *
* 6. Redistributions of any form whatsoever must retain the following
*    acknowledgment:
*    "This product includes software developed by the OpenSSL Project
*    for use in the OpenSSL Toolkit (http://www.openssl.org/)"
*
* THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS" AND ANY
* EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED.  IN NO EVENT SHALL THE OpenSSL PROJECT OR
* ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
* LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
```

* STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
* OF THE POSSIBILITY
OF SUCH DAMAGE.
* ==
*
* This product includes cryptographic software written by Eric Young
* (eay@cryptsoft.com). This product includes software written by Tim
* Hudson (tjh@cryptsoft.com).
*
*/

Original SSLeay License

/* Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)
* All rights reserved.
*
* This package is an SSL implementation written
* by Eric Young (eay@cryptsoft.com).
* The implementation was written so as to conform with Netscapes SSL.
*
* This library is free for commercial and non-commercial use as long as
* the following conditions are aheared to. The following conditions
* apply to all code found in this distribution, be it the RC4, RSA,
* lhash, DES, etc., code; not just the SSL code. The SSL documentation
* included with this distribution is covered by the same copyright terms
* except that the holder is Tim Hudson (tjh@cryptsoft.com).
*
* Copyright
remains Eric Young's, and as such any Copyright notices in
* the code are not to be removed.
* If this package is used in a product, Eric Young should be given attribution
* as the author of the parts of the library used.
* This can be in the form of a textual message at program startup or
* in documentation (online or textual) provided with the package.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software
* must display the following acknowledgement:

 *   "This product includes cryptographic software written by
*   Eric Young (eay@cryptsoft.com)"
*   The word 'cryptographic' can be left out if the rouines from the library
*   being used are not cryptographic related :-).
* 4. If you include any Windows specific code (or a derivative thereof) from
*   the apps directory (application code) you must include an acknowledgement:
*   "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"
*
* THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER
 CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* The licence and distribution terms for any publically available version or
* derivative of this code cannot be changed. i.e. this code cannot simply be
* copied and put under another distribution licence
* [including the GNU Public Licence.]
*/

1.134 github.com/aws/aws-sdk-go-v2/service/sso 1.27.0

1.134.1 Available under license :

GetLicense

 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer

```
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]
```

```
  steps:
    - name: Checkout target
      uses: actions/checkout@v2
      with:
        path: sdkbase
        ref: ${{ github.base_ref }}
    - name: Checkout this ref
      uses: actions/checkout@v2
      with:
        path: new-ref
        fetch-depth: 0
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
       uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
```

```
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
```

```
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
```

```
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
```

```
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
 spanInitializeStart
 InterceptExecution
 RegisterServiceMetadata
 legacyEndpointContextSetter
 SetLogger
 OperationInputValidation
 spanInitializeEnd
 Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
 Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
 Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
```

disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader

ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop

```
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
```

```
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata
```

```
 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
```

```
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
```

```
 OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
```

```
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
```

```
//   - Status
Filters
[]types.Filter

// Amazon Resource Names (ARNs) of the licenses.
LicenseArns []string

// Maximum number of results to return in a single call.
MaxResults *int32

// Token for the next set of results.
NextToken *string

noSmithyDocumentSerde
}

type ListLicensesOutput struct {

// License details.
Licenses []types.License

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack,
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
```

```
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
```

```
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
```

```
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
```

```
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
```

```
}
err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
```

```
 return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
```

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
```

```
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
```

```
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
```

```
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}
```

```
func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
```

```
    // This member is required.
    CheckoutType types.CheckoutType

    // Unique, case-sensitive identifier that you provide to ensure the idempotency of
    // the request.
    //
    // This member is required.
    ClientToken *string

    // License entitlements.
    //
    // This member is required.
    Entitlements []types.EntitlementData

    // Key fingerprint identifying the license.
    //
    // This member is required.
    KeyFingerprint *string

    // Product SKU.
    //
    // This member is required.
    ProductSKU *string

    // License beneficiary.
    Beneficiary *string

    // Node ID.
    NodeId *string

    noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

    // Checkout type.
    CheckoutType types.CheckoutType

    // Allowed license entitlements.
    EntitlementsAllowed []types.EntitlementData

    // Date and time at which the license checkout expires.
    Expiration *string

    // Date and time at which the license checkout is issued.
    IssuedAt *string

    // Amazon Resource Name (ARN) of the checkout license.
```

```
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
```

```
 return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
 return err
 }
 if err = addRetry(stack, options); err != nil {
 return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
```

```
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
```

```
    {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
```

```
            }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
```

```
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
              }
            },
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

           "traits": {
                "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
              }
            },
            "SecretArn": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
```

```
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
               "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
          "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
          },
          "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
          },
          "AccountID": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
          },
          "Region": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
        },
        "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
        },
        "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
        },
        "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
        },
        "SubscriptionName": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
            }
        },
        "OsVersion": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
            }
        },
        "SubscriptionProviderCreateTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
        },
```

```
            "SubscriptionProviderUpdateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the registered \n\t\t\tthird-party Linux subscription provider.</p>"
               }
            },
            "DualSubscription": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for \n\t\t\tthe same software on your instance.</p>"
               }
            },
            "RegisteredWithSubscriptionProvider": {
               "target": "smithy.api#String",
               "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta third-party Linux subscription provider that you've registered with License Manager.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
```

```
"type": "service",
"version": "2018-05-10",
"operations": [
    {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
    },
    {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
    },
    {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
    },
    {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
    },
    {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
     },
    {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
    },
    {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
    },
    {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
    },
    {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
    },
    {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
    },
    {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
    }
],
"traits": {
    "aws.api#service": {
        "sdkId": "License Manager Linux Subscriptions",
         "arnNamespace": "license-manager-linux-subscriptions",
        "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
    },
    "aws.auth#sigv4": {
        "name": "license-manager-linux-subscriptions"
    },
    "aws.protocols#restJson1": {},
    "smithy.api#cors": {
```

```
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id"
            ],
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager Linux Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region": {
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
support dual-stack, dispatching the request MAY return an error.",
                 "type": "Boolean"
              },
              "UseFIPS": {
                "builtIn": "AWS::UseFIPS",
                "required": true,
                "default": false,
                "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                "type": "Boolean"
              },
              "Endpoint": {
                "builtIn": "SDK::Endpoint",
                "required": false,
                "documentation": "Override the endpoint used to send this request",
                "type": "String"
              }
```

```
        },
        "rules": [
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Endpoint"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }

    ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]

}
                    ],
                    "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                    "type": "error"
```

```
            },
            {
              "conditions": [],
              "endpoint": {
                "url": {
                  "ref": "Endpoint"
                },
                "properties": {},
                "headers": {}
              },
              "type": "endpoint"
            }
          ],
          "type": "tree"

    }
    ],
    "type": "tree"
  },
  {
    "conditions": [],
    "rules": [
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Region"
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {

    "fn": "aws.partition",
                "argv": [
                  {
                    "ref": "Region"
                  }
                ],
                "assign": "PartitionResult"
              }
            ],
            "rules": [
```

```
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {

                    "ref": "UseFIPS"
                        },
                        true
                      ]
                    },
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseDualStack"
                        },
                        true
                      ]
                    }

],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            true,
                            {
                              "fn": "getAttr",
                              "argv": [
                                {
                                  "ref": "PartitionResult"

},
                                    "supportsFIPS"
                                ]
                              }
                            ]
                          },
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              true,
                              {
                                "fn": "getAttr",
```

```
                "argv": [

                  {
                    "ref": "PartitionResult"
                  },
                  "supportsDualStack"
                ]
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [],

    "rules": [
                {
                  "conditions": [],
                  "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                    "properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],

            "type": "tree"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",

              "type": "error"
            }
          ],
          "type": "tree"
        },
        {

      "conditions": [
            {
              "fn": "booleanEquals",
              "argv": [
```

```
                {
                  "ref": "UseFIPS"
                },
                true
              ]
            }
          ],
          "rules": [
            {
              "conditions": [
                {

        "fn": "booleanEquals",
                  "argv": [
                    {
                      "fn": "getAttr",
                      "argv": [
                        {
                          "ref": "PartitionResult"
                        },
                        "supportsFIPS"
                      ]
                    },
                    true

                ]
                }
              ],
              "rules": [
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }
                  ],
                  "type": "tree"
                }
              ],
              "type": "tree"
```

```
                },
                {
                  "conditions": [],
                  "error": "FIPS is enabled
but this partition does not support FIPS",
                  "type": "error"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseDualStack"
                    },
                    true

          ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        true,
                        {
                          "fn": "getAttr",
                          "argv": [
                            {

                              "ref": "PartitionResult"
                            },
                            "supportsDualStack"
                          ]
                        }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "rules": [
```

```
        {
                                                "conditions": [],
                                                "endpoint": {
                                                   "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                   "properties": {},
                                                   "headers": {}
                                                },
                                                "type": "endpoint"
                                             }
                                          ],
                                          "type": "tree"

                                    }
                                       ],
                                       "type": "tree"
                                    },
                                    {
                                       "conditions": [],
                                       "error": "DualStack is enabled but this partition does not support DualStack",
                                       "type": "error"
                                    }
                                 ],
                                 "type": "tree"
                              },
                              {
                                 "conditions": [],
                                 "rules": [
                                    {
                                       "conditions": [],
                                       "endpoint": {
                                          "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                          "properties": {},
                                          "headers": {}
                                       },
                                       "type": "endpoint"
                                    }
                                 ],
                                 "type": "tree"
                              }
                           ],
                           "type": "tree"
                        }
                     ],
                     "type": "tree"
                  },
                  {
```

```
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
              }
            ],
            "type": "tree"
          }
        ]
      },
      "smithy.rules#endpointTests": {
        "testCases": [
          {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

        }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {

         "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
              }
            },
            "params": {
              "Region": "us-east-1",
```

```
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
                }

    },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {

  "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": true,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }

     },
      "params": {
        "Region": "us-gov-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

        "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
```

```
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
```

```
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {

      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
      },
      "params": {

 "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "Missing region",
      "expect": {
        "error": "Invalid Configuration: Missing Region"
      }
    }
```

```
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled LinuxSubscriptionsDiscovery"

     },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
        "type": "structure",
        "members": {
          "SourceRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "OrganizationIntegration": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
            "traits": {
              "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
```

```
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },

  {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptionInstances"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "Instances"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
 {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n
```

\n <code>AccountID</code>\n \n \n \n \n <code>AmiID</code>\n \n \n \n \n <code>DualSubscription</code>\n \n \n \n \n <code>InstanceID</code>\n \n \n \n \n <code>InstanceType</code>\n \n \n \n \n <code>ProductCode</code>\n \n \n \n \n <code>Region</code>\n \n \n \n \n <code>Status</code>\n \n \n \n \n <code>UsageOperation</code>\n \n \n \n For each filter, you can use one of the following <code>Operator</code>
values to \n \t\tdefine the behavior of the filter: \n \n \n \n <code>contains</code>\n \n \n \n \n <code>equals</code>\n \n \n \n \n <code>Notequal</code>\n \n \n "
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": " The maximum items to return in a request. "
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " A token to specify where to
start paginating. This \n\tis the nextToken from a previously truncated response. ",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
          "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
              "smithy.api#documentation": " An array that contains instance objects. "
            }
          },

```
            "NextToken": {

        "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
                }
              }
            }
          },
          "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
            "type": "operation",
            "input": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
            },
            "output": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
            },
            "errors": [
              {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
              },
               {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
              },
              {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
              }
            ],
            "traits": {
              "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
              "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptions"
              },
              "smithy.api#idempotent": {},
              "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

   "items": "Subscriptions"
              }
            }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
      "type": "structure",
      "members": {
        "Filters": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n        <p>The valid names for this filter are:</p>\n        <ul>\n
<li>\n            <p>\n              <code>Subscription</code>\n            </p>\n          </li>\n        </ul>\n
<p>The
 valid Operators for this filter are:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
          }
        },
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
            "smithy.api#length": {
              "min": 1,
              "max": 16384
            }
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
      "type": "structure",
      "members": {
        "Subscriptions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
          "traits": {
```

```
                "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
               "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",
```

```
                "items": "RegisteredSubscriptionProviders"
            }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSources": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
                "traits": {
                    "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }

 },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
            "RegisteredSubscriptionProviders": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
                "traits": {
                    "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
                }
            },
```

```
        "NextToken": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
              "name": "CONTAINS",
              "value": "Contains",
              "documentation": "Contains operator"
            }
          ],
          "smithy.api#length": {
```

```
            "min": 1,
            "max": 20
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled OrganizationIntegration"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring Your Own License (BYOL) subscription.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/RegisterSubscriptionProvider"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
                "traits": {
                    "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
                    "smithy.api#required": {}
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
```

```
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
 {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
```

```
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
```

```
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "InProgress",
                "value": "InProgress",
                "documentation": "InProgress status"
              },
              {
                "name": "Completed",
                "value": "Completed",
                "documentation": "Completed status"
              },
              {
                "name": "Successful",
                "value": "Successful",
                "documentation": "Successful status"
              },
              {
                "name": "Failed",
                "value": "Failed",
                "documentation": "Failed status"
              }
            ]
          }
        },

       "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
```

```
            }
        },
        "traits": {
            "smithy.api#length": {
                "min": 1,
                "max": 100
            },
            "smithy.api#uniqueItems": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
            "Name":
{
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the subscription.</p>"
                }
            },
            "Type": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [

 {
                "name": "RedHat",
                "value": "RedHat",
                "documentation": "RedHat subscription provider namespace"
              }
            ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "ACTIVE",
              "value": "ACTIVE",
              "documentation": "ACTIVE status"
            },
            {
              "name": "INVALID",
              "value": "INVALID",
```

```
    "documentation": "INVALID status"
                },
                {
                    "name": "PENDING",
                    "value": "PENDING",
                    "documentation": "PENDING status"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{resourceArn}"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
        "type": "structure",
        "members":
{
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
```

```
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
          "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
```

```
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tagKeys": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
               "traits": {

              "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                  "smithy.api#httpQuery": "tagKeys",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                    "smithy.api#required": {}
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target":
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
        },
        "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
             "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
            }
        },
        "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
                "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
            }
        },
        "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
            }

    },
        "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated data for Linux\n      subscriptions.</p>"
            }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
        "smithy.api#error": "client"
      }
    }
```

```
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
```

```
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string
```

```
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
```

```
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {
```

```
 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
```

```
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
```

```
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata
```

```
 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
```

```
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
```

```
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
 spanInitializeStart
 InterceptExecution
 RegisterServiceMetadata
 legacyEndpointContextSetter
 SetLogger
 OperationInputValidation
 spanInitializeEnd
 Serialize stack step
 spanBuildRequestStart
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
 Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
 Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
 Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
```

ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {

```
            "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
        "type": "structure",
        "members": {
            "DirectoryId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
                "traits": {
                    "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
                }
            },
            "ActiveDirectorySettings":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
                }
            },
            "ActiveDirectoryType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
            },
            "DomainIpv4List": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
```

```
Directory.</p>",
                    "smithy.api#length": {
                      "min": 1,
                      "max": 2
                    }
                  }
                },
                "DomainCredentialsProvider": {
                  "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                  "traits": {
                    "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                  }
                },
                "DomainNetworkSettings": {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                  "traits": {
                    "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                  }
                }
              },
              "traits": {
                "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
              }
            },
            "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
              "type": "string",
              "traits": {
                "smithy.api#enum": [
                  {
                    "name": "SELF_MANAGED",
                    "value": "SELF_MANAGED",
                    "documentation": "SELF_MANAGED type of Active Directory"
                  },
                  {
                    "name": "AWS_MANAGED",
                    "value": "AWS_MANAGED",
                    "documentation": "AWS_MANAGED type of Active Directory"
                  }
                ]
              }
            },
            "com.amazonaws.licensemanagerusersubscriptions#Arn": {
              "type": "string",
```

```
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
```

```
            "uri": "/user/AssociateUser"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
              "smithy.api#required": {}
            }
          },
           "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
      "type": "structure",
      "members": {
        "InstanceUserSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
          "traits": {
            "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
         }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
        "smithy.api#error": "server"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
```

```
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/CreateLicenseServerEndpoint"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
              "smithy.api#required": {}
            }
          },
          "LicenseServerSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
              "smithy.api#required": {}
            }
```

```
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
           },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
          ],
          "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
          "type": "structure",
```

```
        "members": {
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
              "smithy.api#required": {}
            }
          },
           "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
            "traits": {
              "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
            }
          }
        },
         "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
```

```
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

      }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
               }
```

```
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary":
{
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
         "type": "structure",
         "members": {
            "Subnets": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory domain.</p>",
                "smithy.api#length": {
                  "min": 1
                },

    "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Attribute": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
            }
          },
          "Value": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>Value of the filter.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific \n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
          "ActiveDirectoryIdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
             "traits": {
               "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
               "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
               "smithy.api#required": {}
            }
          },
           "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits": {
               "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
               "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
               "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The status of the
```

```
identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
                }
            },
            "FailureMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                    "smithy.api#required": {}
                }
            },
            "Products": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
            }
        },
        "LastStatusCheckDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
    "type": "structure",
    "members": {
        "Username": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
            }
        },
```

```
    "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
             }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
            }
          },
          "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
          },
          "DisassociationDate": {
            "target": "smithy.api#String",
             "traits": {
              "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
          }
        },
```

```
      "traits": {
        "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
        "smithy.api#error": "server",
        "smithy.api#httpError": 500
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
      "type": "service",
      "version": "2018-05-10",
      "operations": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
         },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
```

```
            "arnNamespace": "license-manager-user-subscriptions",
            "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
          },
          "aws.auth#sigv4": {
            "name": "license-manager-user-subscriptions"
          },
          "aws.protocols#restJson1": {},
          "smithy.api#cors": {
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id",
              "content-length",

        "x-api-key",
              "authorization",
              "x-amz-date",
              "x-amz-security-token",
              "Access-Control-Allow-Headers",
              "Access-Control-Allow-Methods",
              "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to
utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager User Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region":
{
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
```

```
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                "type": "Boolean"
            },
            "UseFIPS": {
                "builtIn": "AWS::UseFIPS",
                "required": true,
                "default": false,
                "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                "type": "Boolean"
            },
            "Endpoint": {
                "builtIn": "SDK::Endpoint",
                "required": false,
                "documentation": "Override the endpoint used to send this request",
                "type": "String"
            }
        },
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "isSet",
                        "argv": [
                            {
                                "ref": "Endpoint"
                            }
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            }
                        ],
                        "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                        "type": "error"
                    },
```

```
            {
              "conditions": [
                {

                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseDualStack"
                    },
                    true
                  ]
                }
              ],
              "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
              "type": "error"
            },
            {
              "conditions": [],
              "endpoint": {
                "url": {
                  "ref": "Endpoint"
                },

"properties": {},
                  "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Region"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "aws.partition",
```

```
                "argv": [
                    {
                        "ref": "Region"
                    }
                ],
                "assign": "PartitionResult"
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseFIPS"
                            },
```

```
true
```

```
                        ]
                    },
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
```

```
"fn": "booleanEquals",
```

```
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsFIPS"
                                        ]
                                    }
```

```
                ]
              },

              {
                "fn": "booleanEquals",
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [
                      {
                        "ref": "PartitionResult"
                      },
                      "supportsDualStack"
                    ]
                  }

            ]
              }
            ],
            "rules": [
              {
                "conditions": [],
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                  "properties": {},
                  "headers": {}
                },
                "type": "endpoint"
              }

    ],
            "type": "tree"
          },
          {
            "conditions": [],
            "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
            "type": "error"
          }
        ],
        "type": "tree"
      },
      {
        "conditions": [
          {
            "fn": "booleanEquals",
```

```
                "argv": [

{
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [

    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {

    "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS is enabled but this partition does not support FIPS",
                "type": "error"
```

```
}
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]

        }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
```

```
                ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "DualStack is enabled but this partition does not support DualStack",
                    "type": "error"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "endpoint": {
                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          }
        ],
        "type": "tree"
      },
      {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
      }
    ]
  },
  "smithy.rules#endpointTests": {
    "testCases": [
      {
        "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
        "expect":
{
          "endpoint": {
            "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
          }
        },
        "params": {
          "Region": "us-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",

      "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
```

```
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
             "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
              }
            },
            "params": {
              "Region": "us-gov-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
              }
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": false

    }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
```

```
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
              }

          },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
              }
            },
            "params": {
              "Region": "us-isob-east-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
              "Region": "us-isob-east-1",

  "UseFIPS": false,
              "UseDualStack": true
            }
```

```
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

     "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
 false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
```

```
                    },
                    "params": {
                      "Region": "us-east-1",
                      "UseFIPS": true,
                      "UseDualStack": false,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {
                    "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                    "expect": {
                      "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                    },
                    "params": {
                      "Region": "us-east-1",
                      "UseFIPS": false,
                      "UseDualStack": true,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {
                    "documentation": "Missing region",
                    "expect": {
                      "error": "Invalid Configuration: Missing Region"
                    }
                  }
                ],
                "version": "1.0"
              }
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
            "type": "structure",
            "members": {
              "ProvisioningStatus": {
                "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
                 "traits": {
                   "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
                }
              },
              "HealthStatus": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
                "traits": {
                  "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
                }
```

```
            },
            "Ipv4Address": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
               }
            },
            "ServerType": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
               "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>"
               }
            },
            "ServerEndpoint": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
               }
            },
            "LicenseServerEndpointId": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
               "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits":
{
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the
RDS \n\t\t\tlicense server.</p>"
              }
            },
            "LicenseServerEndpointProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
              "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
              }
            },
            "LicenseServers": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent
the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
              }
            },

           "CreationTime": {
              "target": "smithy.api#Timestamp",
              "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server
endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop
Services (RDS) \n\t\t\tlicense server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
          "type": "string"
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
          }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
```

```
                },
                {
                  "name": "UNHEALTHY",
                  "value": "UNHEALTHY",
                  "documentation": ""
                },
                {
                  "name": "NOT_APPLICABLE",
                  "value": "NOT_APPLICABLE",
                  "documentation": ""
                }
              ]
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
            "type": "structure",
            "members": {
              "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>",
                  "smithy.api#required": {}
                }
              },
              "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                  "smithy.api#required": {}
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
            "type": "operation",
            "input": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
```

```
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
```

```
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
      "type": "operation",
       "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

    {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/instance/ListInstances"
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "InstanceSummaries"
        }
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next
```

token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
"type": "operation",
"input": {
"target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
},
"output": {
"target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
},
"errors": [
{
"target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
}
],
"traits": {
"smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",
"smithy.api#http": {
"code": 200,
"method": "POST",
"uri": "/license-server/ListLicenseServerEndpoints"
},
"smithy.api#paginated": {
"inputToken": "NextToken",

```
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                    "smithy.api#range": {
                        "min": 1,
                        "max": 100
                    }
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                 "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoints": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
                 "traits": {
                    "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
                }
```

```
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
         "type":
 "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
```

```
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
```

```
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

            }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
```

```
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
```

```
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                 "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
          "type": "structure",
          "members": {
            "Username":
 {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
                 "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                 "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                 "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                 "smithy.api#required": {}
              }
            },
             "Status": {
              "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
{
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {

   "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits":
{
                    "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
"<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

    "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

           "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
          "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
        "type": "union",
        "members": {
          "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

"target": "smithy.api#String"
            }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
```

```
          "traits": {
              "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

        },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity
```

provider. \n <note>\n Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as Pending billing status) in Amazon Web Services Billing. For more information, see Viewing your\n\t\t\t\tmonthly charges in the Amazon Web Services Billing User Guide. \n </note>",
"smithy.api#http": {
"code": 200,
"method": "POST",
"uri": "/user/StartProductSubscription"
}

}
},
"com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
"type": "structure",
"members": {
"Username": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The user name from the identity provider of the user. ",
"smithy.api#required": {}
}
},
"IdentityProvider": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
"traits": {
"smithy.api#documentation": " An object that specifies details for the identity provider. ",
"smithy.api#required": {}
}
},
"Product": {
"target": "smithy.api#String",
"traits": {

"smithy.api#documentation": " The name of the user-based subscription product. \n Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n ",
"smithy.api#required": {}
}
},
"Domain": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The domain name of the Active Directory that contains the user for whom to start the product \n\t\t\tsubscription. "
}
},

```
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
              }

  }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
```

```
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
                  "smithy.api#required": {}
               }

   }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
         "type": "list",
         "member": {
            "target": "smithy.api#String"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
         }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

"min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        },
        "Tags": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
          "traits": {
            "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {

         "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
        "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
```

```
to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

            }
               },
               "TagKeys": {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
                  "traits": {
                     "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                     "smithy.api#httpQuery": "tagKeys",
                     "smithy.api#required": {}
                  }
               }
            },
            "traits": {
               "smithy.api#input": {}
            }
         },
         "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
            "type": "structure",
            "members": {},
            "traits": {
               "smithy.api#output": {}
            }
         },
         "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
            "type": "operation",
            "input": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
             },
            "output": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
            },
            "errors": [
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
               }
            ],
```

```
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

       "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n <ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n <li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
```

```
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
```

```
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A parameter is not valid.</p>",
          "smithy.api#error": "client"
        }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {
```

```
 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
```

```
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
```

```
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
```

InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership

of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or

documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.135 skalibs-libs 2.14.3.0-r0

1.135.1 Available under license :

Copyright (c) 2011-2024 Laurent Bercot <ska-skaware@skarnet.org>

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.136 busybox 1.37.0-r14

1.136.1 Available under license :

bzip2 applet in busybox is based on lightly-modified source
of bzip2 version 1.0.4. bzip2 source is distributed
under the following conditions (copied verbatim from LICENSE file)
==

This program, "bzip2", the associated library "libbzip2", and all
documentation, are copyright (C) 1996-2006 Julian R Seward. All
rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

2. The origin of this software must not be misrepresented; you must
  not claim that you wrote the original software. If you use this
  software in a product, an acknowledgment in the product
  documentation would be appreciated but is not required.

3. Altered source versions must be plainly marked as such, and must
  not be misrepresented
 as being the original software.

4. The name of the author may not be used to endorse or promote
  products derived from this software without specific prior written
  permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS
OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, Cambridge, UK.
jseward@bzip.org
bzip2/libbzip2 version 1.0.4 of 20 December 2006
--- A note on GPL versions

BusyBox is distributed under version 2 of the General Public License (included
in its entirety, below). Version 2 is the only version of this license which
this version of BusyBox (or modified versions derived from this one) may be
distributed under.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's

software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for
a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent
this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this
License; they are outside its scope. The act of
running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and
copy and
distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide

a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or

otherwise) that contradict
the conditions of this License, they do not
excuse you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you
may not distribute the Program at all. For example, if a patent
license would not permit royalty-free redistribution of the Program by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under
any particular circumstance, the balance of the section is intended to
apply and the section as a whole is intended to apply in other
circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity
of the free software distribution system, which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free

Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make
exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED
ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where

the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice
 like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of
Vice

This General Public License does not permit incorporating your program into

proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

1.137 github.com/go-asn1-ber/asn1-ber 1.5.8-0.20250403174932-29230038a667

1.137.1 Available under license :

The MIT License (MIT)

Copyright (c) 2011-2015 Michael Mitton (mmitton@gmail.com)
Portions copyright (c) 2015-2016 go-asn1-ber Authors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY,
 WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.138 bash 5.2.37-r0

1.138.1 Available under license :

Shellfloat is copyright (c) 2020 by Michael Wood.
==========

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work
released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code.
And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of

protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed
this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables

other
parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces
specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts
to
control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those

subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met.
This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or

modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions

of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms
of sections 4 and 5, provided that you also convey the
machine-readable Corresponding Source under the terms of this License,
in one of these ways:

a) Convey the object code in, or embodied in, a physical product
(including a physical distribution medium), accompanied by the
Corresponding Source fixed on a durable physical medium
customarily used for software interchange.

b) Convey the object code in, or embodied in,
a physical product
(including a physical distribution medium), accompanied by a
written offer, valid for at least three years and valid for as
long as you offer spare parts or customer support for that product
model, to give anyone who possesses the object code either (1) a
copy of the Corresponding Source for all the software in the
product that is covered by this License, on a durable physical
medium customarily used for software interchange, for a price no
more than your reasonable cost of physically performing this
conveying of source, or (2) access to copy the
Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the
written offer to provide the Corresponding Source. This
alternative is allowed only occasionally and noncommercially, and
only if you received the object code with such an offer, in accord
with subsection 6b.

d) Convey the object code by
offering access from a designated
place (gratis or for a charge), and offer equivalent access to the
Corresponding Source in the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)

that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no

charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the
only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor
any third party retains the ability to install
modified object code on the User Product (for example, the work has

been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement
the terms of this
License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if
authorized by the copyright holders of
that material) supplement the terms of this License with terms:

a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or

requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual
assumptions of liability to the recipient, for
any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional
terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright

holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation
by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept
this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor
has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the

rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling
its contributor version,
but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent
license,
and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work

in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have

permission to link or combine any covered work with a work licensed
under version 3 of the GNU Affero General Public License into a single
combined work, and to convey the resulting work. The terms of this
License will continue to apply to the part which is the covered work,
but the special requirements of the GNU Affero General Public License,
section 13, concerning interaction through a network will apply to the
combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of
the GNU General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing version number.
If the
Program specifies that a certain numbered version of the GNU General
Public License "or any later version" applies to it, you have the
option of following the terms and conditions either of that numbered
version or of any later version published by the Free Software
Foundation. If the Program does not specify a version number of the
GNU General Public License, you may choose any version ever published
by the Free Software Foundation.

If the Program specifies that a proxy can decide which future
versions of the GNU General Public License can be used, that proxy's
public statement of acceptance of a version permanently authorizes you
to choose that version for the Program.

Later license versions may give you additional or different
permissions. However, no additional obligations are imposed on any
author or copyright holder as a result of your choosing to follow a
later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED
BY
APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS
THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY
GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE
USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF
DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD
PARTIES OR A FAILURE OF THE PROGRAM
TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF
SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided
above cannot be given local legal effect according to their terms,
reviewing courts shall apply local law that most closely approximates
an absolute waiver of all civil liability in connection with the
Program, unless a warranty or assumption of liability accompanies a
copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file
to most effectively
state the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper
mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine
library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<https://www.gnu.org/licenses/why-not-lgpl.html>.

GNU Free Documentation License
Version 1.3, 3 November 2008

Copyright (C) 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
<http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other
functional and useful document "free" in the sense of freedom: to
assure everyone the effective freedom to copy and redistribute it,
with or without modifying it, either commercially or noncommercially.
Secondarily, this License preserves for the author and publisher a way
to get credit for their work, while not being considered responsible

for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We
have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy,
modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections,

in the notice
that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters
or
for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some
word
processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

The "publisher" means any person or entity that distributes copies of the Document to the public.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The
Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section
3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
C. State on the Title page the name of the publisher of the Modified Version, as the publisher.

D. Preserve all the copyright notices of the Document.
E. Add an appropriate copyright notice for your modifications
adjacent to the other copyright notices.
F. Include, immediately after the copyright notices, a license notice
giving the public permission to use the Modified Version under the
terms of this License, in the form shown in the Addendum below.
G. Preserve in that license notice the full lists of Invariant Sections
and required Cover Texts given in the Document's license notice.
H. Include an unaltered copy of this License.
I. Preserve the section Entitled "History", Preserve its Title, and add
to it an item stating at least the title, year,
new authors, and
publisher of the Modified Version as given on the Title Page. If
there is no section Entitled "History" in the Document, create one
stating the title, year, authors, and publisher of the Document as
given on its Title Page, then add an item describing the Modified
Version as stated in the previous sentence.
J. Preserve the network location, if any, given in the Document for
public access to a Transparent copy of the Document, and likewise
the network locations given in the Document for previous versions
it was based on. These may be placed in the "History" section.
You may omit a network location for a work that was published at
least four years before the Document itself, or if the original
publisher of the version it refers to gives permission.
K. For any section Entitled "Acknowledgements" or "Dedications",
Preserve the Title of the section, and preserve in the section all
the substance and tone of each of the contributor
acknowledgements
and/or dedications given therein.
L. Preserve all the Invariant Sections of the Document,
unaltered in their text and in their titles. Section numbers
or the equivalent are not considered part of the section titles.
M. Delete any section Entitled "Endorsements". Such a section
may not be included in the Modified Version.
N. Do not retitle any existing section to be Entitled "Endorsements"
or to conflict in title with any Invariant Section.
O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or
appendices that qualify as Secondary Sections and contain no material
copied from the Document, you may at your option designate some or all
of these sections as invariant. To do this, add their titles to the
list of Invariant Sections in the Modified Version's license notice.
These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains
nothing but

endorsements of your Modified Version by various
parties--for example, statements of peer review or that the text has
been approved by an organization as the authoritative definition of a
standard.

You may add a passage of up to five words as a Front-Cover Text, and a
passage of up to 25 words as a Back-Cover Text, to the end of the list
of Cover Texts in the Modified Version. Only one passage of
Front-Cover Text and one of Back-Cover Text may be added by (or
through arrangements made by) any one entity. If the Document already
includes a cover text for the same cover, previously added by you or
by arrangement made by the same entity you are acting on behalf of,
you may not add another; but you may replace the old one, on explicit
permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License
give permission to use their names for publicity for or to assert or
imply endorsement of any Modified Version.

5. COMBINING
DOCUMENTS

You may combine the Document with other documents released under this
License, under the terms defined in section 4 above for modified
versions, provided that you include in the combination all of the
Invariant Sections of all of the original documents, unmodified, and
list them all as Invariant Sections of your combined work in its
license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and
multiple identical Invariant Sections may be replaced with a single
copy. If there are multiple Invariant Sections with the same name but
different contents, make the title of each such section unique by
adding at the end of it, in parentheses, the name of the original
author or publisher of that section if known, or else a unique number.
Make the same adjustment to the section titles in the list of
Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections
Entitled "History"
in the various original documents, forming one section Entitled
"History"; likewise combine any sections Entitled "Acknowledgements",
and any sections Entitled "Dedications". You must delete all sections
Entitled "Endorsements".

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives
with other separate
and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under
the terms of section 4.
Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions

of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See http://www.gnu.org/copyleft/.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

11. RELICENSING

"Massive Multiauthor Collaboration Site" (or "MMC Site") means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A "Massive Multiauthor Collaboration" (or "MMC") contained in the site means any set of copyrightable works thus published on the MMC site.

"CC-BY-SA" means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

"Incorporate" means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is "eligible for relicensing" if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and

license notices just after the title page:

> Copyright (c) YEAR YOUR NAME.
> Permission is granted to copy, distribute and/or modify this document
> under the terms of the GNU Free Documentation License, Version 1.3
> or any later version published by the Free Software Foundation;
> with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts.
> A copy of the license is included in the section entitled "GNU
> Free Documentation License".

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the "with...Texts." line with this:

> with the Invariant Sections being LIST THEIR TITLES, with the
> Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.

If you have Invariant Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of
free software license, such as the GNU General Public License,
to permit their use in free software.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for

this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which gives you legal permission to copy,
distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which
contains
a notice placed by the copyright holder saying it may be distributed
under the terms of this General Public License. The "Program", below,
refers to any such program or work, and a "work based on the Program"
means either the Program or any derivative work under copyright law:
that is to say, a work containing the Program or a portion of it,
either verbatim or with modifications and/or translated into another
language. (Hereinafter, translation is included without limitation in

the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program,

and can be reasonably considered
independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based
on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution and only if you
received the program in object code or
executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include

anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the
source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each
time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution

of the Program by
all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through
any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number
of this License which applies to it and "any
later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free

programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN
IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify

it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License,
or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w'
and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License.
@c The GNU Free Documentation License.
@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{} 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.
@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other
functional and useful document @dfn{free} in the sense of freedom: to
assure everyone the effective freedom to copy and redistribute it,
with or without modifying it, either commercially or noncommercially.
Secondarily, this License preserves for the author and publisher a way
to get credit for their work, while not being considered responsible
for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative
works of the document
 must themselves be free in the same sense. It
complements the GNU General Public License, which is a copyleft
license designed for free software.

We have designed this License in order to use it for manuals for free
software, because free software needs free documentation: a free
program should come with manuals providing the same freedoms that the
software does. But this License is not limited to software manuals;
it can be used for any textual work, regardless of subject matter or
whether it is published as a printed book. We recommend this License
principally for works whose purpose is instruction or reference.

@item
APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that
contains a notice placed by the copyright holder saying it can be
distributed under the terms of this License. Such a notice grants a
world-wide, royalty-free license, unlimited in duration, to use that
work under the conditions stated herein. The ``Document'', below,
refers
 to any such manual or work. Any member of the public is a
licensee, and is addressed as ``you''. You accept the license if you

copy, modify or distribute the work in a way requiring permission
under copyright law.

A ``Modified Version'' of the Document means any work containing the
Document or a portion of it, either copied verbatim, or with
modifications and/or translated into another language.

A ``Secondary Section'' is a named appendix or a front-matter section
of the Document that deals exclusively with the relationship of the
publishers or authors of the Document to the Document's overall
subject (or to related matters) and contains nothing that could fall
directly within that overall subject. (Thus, if the Document is in
part a textbook of mathematics, a Secondary Section may not explain
any mathematics.) The relationship could be a matter of historical
connection with the subject or with related matters, or of legal,
commercial, philosophical, ethical or political
 position regarding
them.

The ``Invariant Sections'' are certain Secondary Sections whose titles
are designated, as being those of Invariant Sections, in the notice
that says that the Document is released under this License. If a
section does not fit the above definition of Secondary then it is not
allowed to be designated as Invariant. The Document may contain zero
Invariant Sections. If the Document does not identify any Invariant
Sections then there are none.

The ``Cover Texts'' are certain short passages of text that are listed,
as Front-Cover Texts or Back-Cover Texts, in the notice that says that
the Document is released under this License. A Front-Cover Text may
be at most 5 words, and a Back-Cover Text may be at most 25 words.

A ``Transparent'' copy of the Document means a machine-readable copy,
represented in a format whose specification is available to the
general public, that is suitable for revising the document
straightforwardly with generic text editors or (for
 images composed of
pixels) generic paint programs or (for drawings) some widely available
drawing editor, and that is suitable for input to text formatters or
for automatic translation to a variety of formats suitable for input
to text formatters. A copy made in an otherwise Transparent file
format whose markup, or absence of markup, has been arranged to thwart
or discourage subsequent modification by readers is not Transparent.
An image format is not Transparent if used for any substantial amount
of text. A copy that is not ``Transparent'' is called ``Opaque''.

Examples of suitable formats for Transparent copies include plain
@sc{ascii} without markup, Texinfo input format, La@TeX{} input

format, @acronym{SGML} or @acronym{XML} using a publicly available
@acronym{DTD}, and standard-conforming simple @acronym{HTML},
PostScript or @acronym{PDF} designed for human modification. Examples
of transparent image formats include @acronym{PNG}, @acronym{XCF} and
@acronym{JPG}. Opaque formats
 include proprietary formats that can be
read and edited only by proprietary word processors, @acronym{SGML} or
@acronym{XML} for which the @acronym{DTD} and/or processing tools are
not generally available, and the machine-generated @acronym{HTML},
PostScript or @acronym{PDF} produced by some word processors for
output purposes only.

The ``Title Page'' means, for a printed book, the title page itself,
plus such following pages as are needed to hold, legibly, the material
this License requires to appear in the title page. For works in
formats which do not have any title page as such, ``Title Page'' means
the text near the most prominent appearance of the work's title,
preceding the beginning of the body of the text.

The ``publisher'' means any person or entity that distributes copies
of the Document to the public.

A section ``Entitled XYZ'' means a named subunit of the Document whose
title either is precisely XYZ or contains XYZ in parentheses following
text that translates XYZ in
 another language. (Here XYZ stands for a
specific section name mentioned below, such as ``Acknowledgements'',
``Dedications'', ``Endorsements'', or ``History''.)  To ``Preserve the Title''
of such a section when you modify the Document means that it remains a
section ``Entitled XYZ'' according to this definition.

The Document may include Warranty Disclaimers next to the notice which
states that this License applies to the Document. These Warranty
Disclaimers are considered to be included by reference in this
License, but only as regards disclaiming warranties: any other
implication that these Warranty Disclaimers may have is void and has
no effect on the meaning of this License.

@item
VERBATIM COPYING

You may copy and distribute the Document in any medium, either
commercially or noncommercially, provided that this License, the
copyright notices, and the license notice saying this License applies
to the Document are reproduced in all copies, and that you add no other
conditions whatsoever
 to those of this License. You may not use
technical measures to obstruct or control the reading or further

copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

@item
COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible.
You may add other material on the covers in addition.
Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that
this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

@item

MODIFICATIONS

You may copy and distribute a Modified Version of the Document under
the conditions of sections 2 and 3 above, provided that you release
the Modified Version under precisely this License, with the Modified
Version filling the role of the Document, thus licensing distribution
and modification of the Modified Version to whoever possesses a copy
of it. In addition, you must do these things in the Modified Version:

@enumerate A
@item
Use in the Title Page (and on the covers, if any) a title distinct
from that of the Document, and from
 those of previous versions
(which should, if there were any, be listed in the History section
of the Document). You may use the same title as a previous version
if the original publisher of that version gives permission.

@item
List on the Title Page, as authors, one or more persons or entities
responsible for authorship of the modifications in the Modified
Version, together with at least five of the principal authors of the
Document (all of its principal authors, if it has fewer than five),
unless they release you from this requirement.

@item
State on the Title page the name of the publisher of the
Modified Version, as the publisher.

@item
Preserve all the copyright notices of the Document.

@item
Add an appropriate copyright notice for your modifications
adjacent to the other copyright notices.

@item
Include, immediately after the copyright notices, a license notice
giving the public permission to use the Modified Version under the
terms of this License, in the form shown in
 the Addendum below.

@item
Preserve in that license notice the full lists of Invariant Sections
and required Cover Texts given in the Document's license notice.

@item
Include an unaltered copy of this License.

@item
Preserve the section Entitled ``History'', Preserve its Title, and add
to it an item stating at least the title, year, new authors, and
publisher of the Modified Version as given on the Title Page. If
there is no section Entitled ``History'' in the Document, create one
stating the title, year, authors, and publisher of the Document as
given on its Title Page, then add an item describing the Modified
Version as stated in the previous sentence.

@item
Preserve the network location, if any, given in the Document for
public access to a Transparent copy of the Document, and likewise
the network locations given in the Document for previous versions
it was based on. These may be placed in the ``History'' section.
You may omit a network location for a work that was published at
least
four years before the Document itself, or if the original
publisher of the version it refers to gives permission.

@item
For any section Entitled ``Acknowledgements'' or ``Dedications'', Preserve
the Title of the section, and preserve in the section all the
substance and tone of each of the contributor acknowledgements and/or
dedications given therein.

@item
Preserve all the Invariant Sections of the Document,
unaltered in their text and in their titles. Section numbers
or the equivalent are not considered part of the section titles.

@item
Delete any section Entitled ``Endorsements''. Such a section
may not be included in the Modified Version.

@item
Do not retitle any existing section to be Entitled ``Endorsements'' or
to conflict in title with any Invariant Section.

@item
Preserve any Warranty Disclaimers.
@end enumerate

If the Modified Version includes new front-matter sections or
appendices that qualify as Secondary Sections and contain no material
copied from the Document,
you may at your option designate some or all
of these sections as invariant. To do this, add their titles to the

list of Invariant Sections in the Modified Version's license notice.
These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements", provided it contains
nothing but endorsements of your Modified Version by various
parties---for example, statements of peer review or that the text has
been approved by an organization as the authoritative definition of a
standard.

You may add a passage of up to five words as a Front-Cover Text, and a
passage of up to 25 words as a Back-Cover Text, to the end of the list
of Cover Texts in the Modified Version. Only one passage of
Front-Cover Text and one of Back-Cover Text may be added by (or
through arrangements made by) any one entity. If the Document already
includes a cover text for the same cover, previously added by you or
by arrangement made by the same entity you are acting on behalf
 of,
you may not add another; but you may replace the old one, on explicit
permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License
give permission to use their names for publicity for or to assert or
imply endorsement of any Modified Version.

@item
COMBINING DOCUMENTS

You may combine the Document with other documents released under this
License, under the terms defined in section 4 above for modified
versions, provided that you include in the combination all of the
Invariant Sections of all of the original documents, unmodified, and
list them all as Invariant Sections of your combined work in its
license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and
multiple identical Invariant Sections may be replaced with a single
copy. If there are multiple Invariant Sections with the same name but
different contents, make the title of
 each such section unique by
adding at the end of it, in parentheses, the name of the original
author or publisher of that section if known, or else a unique number.
Make the same adjustment to the section titles in the list of
Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History"
in the various original documents, forming one section Entitled
``History"; likewise combine any sections Entitled ``Acknowledgements",
and any sections Entitled ``Dedications". You must delete all

sections Entitled ``Endorsements."

@item
COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract
a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

@item
AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an ``aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may
be placed on
covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

@item
TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the

Document, and any Warranty Disclaimers, provided that you also include
the original English version of this License and the original versions
of those notices and disclaimers. In case of a disagreement between
the translation and the original version of this License or a notice
or disclaimer, the original
 version will prevail.

If a section in the Document is Entitled ``Acknowledgements'',
``Dedications'', or ``History'', the requirement (section 4) to Preserve
its Title (section 1) will typically require changing the actual
title.

@item
TERMINATION

You may not copy, modify, sublicense, or distribute the Document
except as expressly provided under this License. Any attempt
otherwise to copy, modify, sublicense, or distribute it is void, and
will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license
from a particular copyright holder is reinstated (a) provisionally,
unless and until the copyright holder explicitly and finally
terminates your license, and (b) permanently, if the copyright holder
fails to notify you of the violation by some reasonable means prior to
60 days after the cessation.

Moreover, your license from a particular copyright holder is
reinstated permanently if the copyright holder notifies
 you of the
violation by some reasonable means, this is the first time you have
received notice of violation of this License (for any work) from that
copyright holder, and you cure the violation prior to 30 days after
your receipt of the notice.

Termination of your rights under this section does not terminate the
licenses of parties who have received copies or rights from you under
this License. If your rights have been terminated and not permanently
reinstated, receipt of a copy of some or all of the same material does
not give you any rights to use it.

@item
FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions
of the GNU Free Documentation License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns. See

@uref{http://www.gnu.org/copyleft/}.

Each version of the License is given a distinguishing version number.
If the Document specifies that
 a particular numbered version of this
License ``or any later version'' applies to it, you have the option of
following the terms and conditions either of that specified version or
of any later version that has been published (not as a draft) by the
Free Software Foundation. If the Document does not specify a version
number of this License, you may choose any version ever published (not
as a draft) by the Free Software Foundation. If the Document
specifies that a proxy can decide which future versions of this
License can be used, that proxy's public statement of acceptance of a
version permanently authorizes you to choose that version for the
Document.

@item
RELICENSING

``Massive Multiauthor Collaboration Site'' (or ``MMC Site'') means any
World Wide Web server that publishes copyrightable works and also
provides prominent facilities for anybody to edit those works. A
public wiki that anybody can edit is an example of such a server. A
``Massive Multiauthor Collaboration'' (or ``MMC'')
 contained in the
site means any set of copyrightable works thus published on the MMC
site.

``CC-BY-SA'' means the Creative Commons Attribution-Share Alike 3.0
license published by Creative Commons Corporation, a not-for-profit
corporation with a principal place of business in San Francisco,
California, as well as future copyleft versions of that license
published by that same organization.

``Incorporate'' means to publish or republish a Document, in whole or
in part, as part of another Document.

An MMC is ``eligible for relicensing'' if it is licensed under this
License, and if all works that were first published under this License
somewhere other than this MMC, and subsequently incorporated in whole
or in part into the MMC, (1) had no cover texts or invariant sections,
and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site
under CC-BY-SA on the same site at any time before August 1, 2009,
provided the
 MMC is eligible for relicensing.

@end enumerate

@page
@heading ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

@smallexample
@group
 Copyright (C) @var{year} @var{your name}.
 Permission is granted to copy, distribute and/or modify this document
 under the terms of the GNU Free Documentation License, Version 1.3
 or any later version published by the Free Software Foundation;
 with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
 Texts. A copy of the license is included in the section entitled ``GNU
 Free Documentation License".
@end group
@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the ``with@dots{}Texts." line with this:

@smallexample
@group
   with the Invariant Sections being @var{list their titles}, with
   the Front-Cover
 Texts being @var{list}, and with the Back-Cover Texts
   being @var{list}.
@end group
@end smallexample

If you have Invariant Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of
free software license, such as the GNU General Public License,
to permit their use in free software.

@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:
                GNU GENERAL PUBLIC LICENSE
                 Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
them if you wish), that you receive source code or can get it if you
want it, that you can change the software or use pieces of it in new
free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you
these rights or asking you to surrender the rights. Therefore, you have
certain responsibilities if you distribute copies of the software, or if
you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must pass on to the recipients the same
freedoms that you received. You must make sure that they, too, receive
or can get the source code. And you must show them these terms so they
know their rights.

Developers that use the GNU GPL protect your rights with two steps:
(1)
assert copyright on the software, and (2) offer you this License
giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains
that there is no warranty for this free software. For both users' and
authors' sake, the GPL requires that modified versions be marked as
changed, so that their problems will not be attributed erroneously to
authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand
ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"
and
"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying,

distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source

includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered
by this License only if the output, given its
content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;
section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to
"keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your

work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in

the same way through the same place at no
further charge. You need not require recipients to copy the
Corresponding Source along with the object code. If the place to
copy the object code is a network server, the Corresponding Source
may be on a different server (operated by you or a third party)
that supports equivalent copying facilities, provided you maintain
clear directions next to the object code saying where to find the
Corresponding Source. Regardless of what server hosts the
Corresponding Source, you remain obligated to ensure that it is
available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided
you inform other peers where the object code and Corresponding
Source of the work are being offered to the general public at no
charge under subsection 6d.

A separable portion of the object code, whose source code is excluded
from the Corresponding Source
as a System Library, need not be
included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any
tangible personal property which is normally used for personal, family,
or household purposes, or (2) anything designed or sold for incorporation
into a dwelling. In determining whether a product is a consumer product,
doubtful cases shall be resolved in favor of coverage. For a particular
product received by a particular user, "normally used" refers to a
typical or common use of that class of product, regardless of the status
of the particular user or of the way in which the particular user
actually uses, or expects or is expected to use, the product. A product
is a consumer product regardless of whether the product has substantial
commercial, industrial or non-consumer uses, unless such uses represent
the only significant mode of use of the product.

"Installation Information" for a User Product means any methods,
procedures, authorization
keys, or other information required to install
and execute modified versions of a covered work in that User Product from
a modified version of its Corresponding Source. The information must
suffice to ensure that the continued functioning of the modified object
code is in no case prevented or interfered with solely because
modification has been made.

If you convey an object code work under this section in, or with, or
specifically for use in, a User Product, and the conveying occurs as
part of a transaction in which the right of possession and use of the
User Product is transferred to the recipient in perpetuity or for a
fixed term (regardless of how the transaction is characterized), the

Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in
ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the
entire Program shall
be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a) Disclaiming warranty or
limiting liability differently from the
terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions;
the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright
holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the

Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the

patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM

IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.
Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<http://www.gnu.org/philosophy/why-not-lgpl.html>.
Unless otherwise stated, all files in this directory are Copyright (C)
1991,1992,1993,1994,1995,1996,1997,1998,1999,2000,2001,2002,2003,
2004,2005,2006,2007,2008,2009,2010,2011
Free Software Foundation, Inc.

See the file COPYING in the bash distribution root directory for copying
and usage restrictions.

The file ifs-posix.tests is Copyright (C) 2005 Glen Fowler.

1.139 common 0.65.0

1.139.1 Available under license :

ISC

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain

separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without

modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include

the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.140 github.com/confluentinc/confluent-kafka-go/v2 2.11.0

1.140.1 Available under license :

LICENSE
---
librdkafka - Apache Kafka C driver library

Copyright (c) 2012-2022, Magnus Edenhill
2023, Confluent Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE

FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LICENSE.cjson

For cJSON.c and cJSON.h:

Copyright (c) 2009-2017 Dave Gamble and cJSON contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished
to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

LICENSE.crc32c

For src/crc32c.c copied (with modifications) from
http://stackoverflow.com/a/17646775/1821055

/* crc32c.c -- compute CRC-32C using the Intel crc32 instruction
* Copyright (C) 2013 Mark Adler
* Version 1.1 1 Aug 2013 Mark Adler
*/

/*
This software is provided 'as-is',

without any express or implied
warranty. In no event will the author be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
   claim that you wrote the original software. If you use this software
   in a product, an acknowledgment in the product documentation would be
   appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be
   misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Mark Adler
madler@alumni.caltech.edu
*/

LICENSE.fnv1a
---
parts of src/rdfnv1a.c: http://www.isthe.com/chongo/src/fnv/hash_32a.c

Please
do not copyright this code. This code is in the public domain.

LANDON CURT NOLL DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE,
INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO
EVENT SHALL LANDON CURT NOLL BE LIABLE FOR ANY SPECIAL, INDIRECT OR
CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF
USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR
OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

By:
  chongo <Landon Curt Noll> /\oo/\
  http://www.isthe.com/chongo/

Share and Enjoy! :-)

LICENSE.hdrhistogram

This license covers src/rdhdrhistogram.c which is a C port of
Coda Hale's Golang HdrHistogram https://github.com/codahale/hdrhistogram

at revision 3a0bb77429bd3a61596f5e8a3172445844342120

The MIT License
(MIT)

Copyright (c) 2014 Coda Hale

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE

LICENSE.lz4
---
src/rdxxhash.[ch] src/lz4*.[ch]: git@github.com:lz4/lz4.git 5ff839680134437dbf4678f3d0c7b371d84f4964

LZ4 Library
Copyright (c) 2011-2020, Yann Collet
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this
list of conditions and the following disclaimer in the documentation and/or
other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND

ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LICENSE.murmur2

---

parts of src/rdmurmur2.c: git@github.com:abrandoned/murmur2.git

MurMurHash2 Library

//--

// MurmurHash2 was written by Austin Appleby, and is placed in the public
// domain. The author hereby disclaims copyright to this source code.

Permission is hereby granted, free of charge, to any person
obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

LICENSE.nanopb

For
files in src/nanopb :
https://github.com/nanopb/nanopb/blob/8ef41e0ebd45daaf19459a011f67e66224b247cd/LICENSE.txt

Copyright (c) 2011 Petteri Aimonen <jpa at nanopb.mail.kapsi.fi>

This software is provided 'as-is', without any express or
implied warranty. In no event will the authors be held liable
for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any
purpose, including commercial applications, and to alter it and
redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you
must not claim that you wrote the original software. If you use
this software in a product, an acknowledgment in the product
documentation would be appreciated but is not required.

2. Altered source versions must be plainly marked as such, and
must not be misrepresented as being the original software.

3. This notice may
not be removed or altered from any source
distribution.

LICENSE.opentelemetry

For files in src/opentelemetry: https://github.com/open-telemetry/opentelemetry-proto/blob/81a296f9dba23e32d77f46d58c8ea4244a2157a6/LICENSE

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes
of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or

otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated
by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of

the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution
incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or

documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE
text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding
such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event
and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,

incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

LICENSE.pycrc

The following license applies to the files rdcrc32.c and rdcrc32.h which
have been generated by the pycrc tool.
==========

Copyright (c) 2006-2012, Thomas Pircher <tehpeh@gmx.net>

Permission is hereby granted,
free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

LICENSE.queue

For
sys/queue.h:

* Copyright (c) 1991, 1993
* The Regents of the University of California. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 4. Neither the name of the University nor the names of its contributors
*   may be used to endorse or promote products derived from this software
*   without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND

* ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* @(#)queue.h 8.5 (Berkeley) 8/20/94
* $FreeBSD$

LICENSE.regexp
---
regexp.c and regexp.h from https://github.com/ccxvii/minilibs sha 875c33568b5a4aa4fb3dd0c52ea98f7f0e5ca684

"
These libraries are in the public domain (or the equivalent where that is not
possible). You can do anything you want with them. You have no legal obligation to do anything else, although I appreciate attribution.
"

LICENSE.snappy

##
LICENSE.snappy covers files: snappy.c, snappy.h, snappy_compat.h
originally retrieved from http://github.com/andikleen/snappy-c
git revision 8015f2d28739b9a6076ebaa6c53fe27bc238d219
##

The snappy-c code is under the same license as the original snappy source

Copyright 2011 Intel Corporation All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

   * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
   * Redistributions
in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the

distribution.
  * Neither the name of Intel Corporation nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING
 NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LICENSE.tinycthread

From https://github.com/tinycthread/tinycthread/README.txt c57166cd510ffb5022dd5f127489b131b61441b9

License

Copyright (c) 2012 Marcus Geelnard
          2013-2014 Evan Nemerson

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

  1. The origin of this software must not be misrepresented; you must not
  claim that you wrote the original software. If you use this software
  in a product, an acknowledgment in the product documentation would be
   appreciated but is not required.

  2. Altered source versions must be plainly marked as such, and must not be
  misrepresented as being the original software.

  3. This notice may not be removed or altered from any source
  distribution.

LICENSE.wingetopt

For the files wingetopt.c wingetopt.h downloaded from https://github.com/alex85k/wingetopt

/*
* Copyright (c) 2002 Todd C. Miller <Todd.Miller@courtesan.com>
*
* Permission to use, copy, modify, and distribute this software for any
* purpose with or without fee is hereby granted, provided that the above
* copyright notice and this permission notice appear in all copies.
*
* THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
* WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
* MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
* ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR
 ANY DAMAGES
* WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
* ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
* OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
*
* Sponsored in part by the Defense Advanced Research Projects
* Agency (DARPA) and Air Force Research Laboratory, Air Force
* Materiel Command, USAF, under agreement number F39502-99-1-0512.
*/
/*-
* Copyright (c) 2000 The NetBSD Foundation, Inc.
* All rights reserved.
*
* This code is derived from software contributed to The NetBSD Foundation
* by Dieter Baron and Thomas Klausner.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice,
 this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
* THIS SOFTWARE IS PROVIDED BY THE NETBSD FOUNDATION, INC. AND CONTRIBUTORS
* ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE FOUNDATION OR CONTRIBUTORS
* BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR

* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
* POSSIBILITY OF SUCH DAMAGE.
*/

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object

form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations,
or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems
that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants
to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses

granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work
or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not

pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution
of Your modifications, or
for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,

any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental,
or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted
against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "{}" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright {yyyy} {name of copyright owner}

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.141 aws-sdk-go-v2-credentials 1.18.3

1.141.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step

```
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)
```

```
// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string
```

```
 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer

 // License name.
 //
 // This member is required.
 LicenseName *string

 // Product name.
 //
 // This member is required.
 ProductName *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // Date and time range during which the license is valid, in ISO8601-UTC format.
 //
 // This member is required.
 Validity *types.DatetimeRange

 // Information about
 the license.
 LicenseMetadata []types.Metadata

 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
```

```
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
```

```
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
```

```
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
```

setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity

ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry

```
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
```

```
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
```

```
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
```

```
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
```

```
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
```

```
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
```

```
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
```

```
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
```

```
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options);
err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
```

```
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
```

```
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
```

```
 Region:
      region,
 ServiceID:     ServiceID,
 OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType
```

```
// Unique, case-sensitive identifier that you provide to ensure the idempotency of
// the request.
//
// This member is required.
ClientToken *string

// License entitlements.
//
// This member is required.
Entitlements []types.EntitlementData

// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string
```

```
// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
```

```
 return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
```

```
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
            }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
```

```
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
           },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
```

registered to your account. ",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation":
 " The Amazon Resource Name (ARN) of the BYOL registration resource to get details for. ",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
          "type": "structure",
          "members": {
            "SubscriptionProviderArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation": " The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request. "
              }
            },
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

           "traits": {
                "smithy.api#documentation": " The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request. "
              }
            },
            "SecretArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
              "traits": {
                "smithy.api#documentation": " The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request. "

```
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
```

```
      "traits": {
        "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/GetServiceSettings"

        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
      "type": "structure",
      "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
          "traits": {
            "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
          }
        },
        "StatusMessage": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
          "traits": {
            "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
          }
        },
        "HomeRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
            "AmiId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
                }
            },
            "InstanceID": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
                }
            },
            "InstanceType": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>The instance type of the resource.</p>"
                }
            },
            "AccountID": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the instance.</p>"
                }
            },
            "Region": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
                }
            },
            "UsageOperation": {
```

```
            "target": "smithy.api#String",

    "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
          },
          "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
              "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
          },
          "LastUpdatedTime": {
            "target": "smithy.api#String",
             "traits": {
              "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
            }
          },
          "SubscriptionName": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
            }
          },
          "OsVersion": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
            }
          },
          "SubscriptionProviderCreateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
          },
          "SubscriptionProviderUpdateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
```

```
registered \n\t\t\tthird-party Linux subscription provider.</p>"
                }
            },
            "DualSubscription": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
                }
            },
            "RegisteredWithSubscriptionProvider": {
                "target": "smithy.api#String",
                "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
```

```
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
       },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
      }
    ],
    "traits": {
      "aws.api#service": {
        "sdkId": "License Manager Linux Subscriptions",
         "arnNamespace": "license-manager-linux-subscriptions",
        "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
      },
      "aws.auth#sigv4": {
        "name": "license-manager-linux-subscriptions"
      },
      "aws.protocols#restJson1": {},
      "smithy.api#cors": {
        "additionalAllowedHeaders": [
          "*",
          "content-type",
          "x-amz-content-sha256",
```

```
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
```

```
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseFIPS"
                        },
                        true
                      ]
                    }

        ],
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                  "type": "error"
                },
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            {
                              "ref": "UseDualStack"
                            },
                            true
                          ]

}
                      ],
                      "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                      "type": "error"
                    },
                    {
                      "conditions": [],
                      "endpoint": {
```

```
                    "url": {
                        "ref": "Endpoint"
                    },
                    "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"

    }
    ],
    "type": "tree"
},
{
    "conditions": [],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Region"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {

    "fn": "aws.partition",
                            "argv": [
                                {
                                    "ref": "Region"
                                }
                            ],
                            "assign": "PartitionResult"
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
```

```
                "argv": [
                  {

                "ref": "UseFIPS"
                  },
                  true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }

    ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"

        },
                              "supportsFIPS"
                          ]
                        }
                      ]
                  },
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [

                         {
                              "ref": "PartitionResult"
```

```
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],

    "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],

                "type": "tree"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {

        "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseFIPS"
                            },
                            true
```

```
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

          "fn": "booleanEquals",
                      "argv": [
                        {
                          "fn": "getAttr",
                          "argv": [
                            {
                              "ref": "PartitionResult"
                            },
                            "supportsFIPS"
                          ]
                        },
                        true

                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "rules": [
                      {
                        "conditions": [],
                        "endpoint": {
                          "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                          "headers": {}
                        },
                        "type": "endpoint"
                      }
                    ],
                    "type": "tree"
                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS is enabled
```

```
but this partition does not support FIPS",
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true

                    ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [
                                        {
                                            "fn": "booleanEquals",
                                            "argv": [
                                                true,
                                                {
                                                    "fn": "getAttr",
                                                    "argv": [
                                                        {

                                                            "ref": "PartitionResult"
                                                        },
                                                        "supportsDualStack"
                                                    ]
                                                }
                                            ]
                                        }
                                    ],
                                    "rules": [
                                        {
                                            "conditions": [],
                                            "rules": [

        {
                                                    "conditions": [],
                                                    "endpoint": {
                                                        "url": "https://license-manager-linux-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],
                                    "type": "tree"

                            }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
```

```
            ],
            "type": "tree"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

    }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": false
            }
        },
        {

     "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
```

```
            {
              "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
                }

        },
              "params": {
                "Region": "us-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {

 "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                }
              },
              "params": {
                "Region": "cn-north-1",
                "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                }
```

```
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }

     },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
```

```
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                  },
                  "params": {

               "Region": "us-iso-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                    }
                  },
                  "params": {
                    "Region": "us-iso-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
             }
          },
```

```
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

     "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

},
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
```

```
disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://example.com"
                      }
                    },
                    "params": {
                      "UseFIPS": false,
                      "UseDualStack": false,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {

                    "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                    "expect": {
                      "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                    },
                    "params": {
                      "Region": "us-east-1",
                      "UseFIPS": true,
                      "UseDualStack": false,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {
                    "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                    "expect": {
                      "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                    },
                    "params": {

 "Region": "us-east-1",
                      "UseFIPS": false,
                      "UseDualStack": true,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {
                    "documentation": "Missing region",
                    "expect": {
                      "error": "Invalid Configuration: Missing Region"
                    }
                  }
                ],
                "version": "1.0"
              }
            }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "Enabled",
            "value": "Enabled",
            "documentation": "Enabled LinuxSubscriptionsDiscovery"

    },
          {
            "name": "Disabled",
            "value": "Disabled",
            "documentation": "Disabled LinuxSubscriptionsDiscovery"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "OrganizationIntegration": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
          "traits": {
            "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

  {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n
  <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
      <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
```

<code>InstanceType</code>\n \n \n \n \n
<code>ProductCode</code>\n \n \n \n \n
<code>Region</code>\n \n \n \n \n
<code>Status</code>\n \n \n \n \n
<code>UsageOperation</code>\n \n \n \n For each filter, you can use one of the following <code>Operator</code>
values to \n \t\tdefine the behavior of the filter: \n \n \n \n
<code>contains</code>\n \n \n \n \n
<code>equals</code>\n \n \n \n \n
<code>Notequal</code>\n \n \n "
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": " The maximum items to return in a request. "
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " A token to specify where to
start paginating. This \n\tis the nextToken from a previously truncated response. ",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
          "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
              "smithy.api#documentation": " An array that contains instance objects. "
            }
          },
          "NextToken": {

       "target": "smithy.api#String",
            "traits": {

```
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

  "items": "Subscriptions"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
```

```
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n partially match, or don't match a certain subscription's name.</p>\n <p>The valid names for this filter are:</p>\n <ul>\n <li>\n <p>\n <code>Subscription</code>\n </p>\n </li>\n </ul>\n <p>The valid Operators for this filter are:</p>\n <ul>\n <li>\n <p>\n <code>contains</code>\n </p>\n </li>\n <li>\n <p>\n <code>equals</code>\n </p>\n </li>\n <li>\n <p>\n <code>Notequal</code>\n </p>\n </li>\n </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 16384
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
            "Subscriptions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
                }
            },
            "NextToken": {
```

```
            "target": "smithy.api#String",
             "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListRegisteredSubscriptionProviders"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "RegisteredSubscriptionProviders"
          }
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSources": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
          "traits": {
            "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
          }
        },
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }

  },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
          "traits": {
            "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
          }
        },

       "NextToken": {
          "target": "smithy.api#String",
          "traits": {
```

```
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
          },
          "errors": [
            {

         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
            "smithy.api#http": {
              "method": "GET",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
          "type": "structure",
          "members": {
            "resourceArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                 "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
```

```
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
      "type": "structure",
      "members": {
        "tags": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
          "traits": {
            "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "EQUAL",
            "value": "Equal",
            "documentation": "Equal operator"
          },
          {
            "name": "NOT_EQUAL",
            "value": "NotEqual",
            "documentation": "Not equal operator"
          },
          {
            "name": "CONTAINS",
            "value": "Contains",
            "documentation": "Contains operator"
          }
        ],
        "smithy.api#length": {
          "min": 1,
          "max": 20
        }
      }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "Enabled",
            "value": "Enabled",
            "documentation": "Enabled OrganizationIntegration"
          },
          {
            "name": "Disabled",
            "value": "Disabled",
            "documentation": "Disabled OrganizationIntegration"
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
        "smithy.api#http": {
```

```
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
            }
```

```
            },
            "SubscriptionProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
         "type": "structure",
         "members": {
            "SubscriptionProviderArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
               }
            },
            "SubscriptionProviderSource": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
               "traits": {
                  "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
               }
            },
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
```

```
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "InProgress",
              "value": "InProgress",
              "documentation": "InProgress status"
            },
            {
              "name": "Completed",
              "value": "Completed",
              "documentation": "Completed status"
            },
            {
              "name": "Successful",
              "value": "Successful",
              "documentation": "Successful status"
            },
            {
              "name": "Failed",
              "value": "Failed",
              "documentation": "Failed status"
            }
          ]
        }
      },

      "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            }
          }
        },
        "traits": {
          "smithy.api#length": {
```

```
                "min": 1,
                "max": 100
            },
            "smithy.api#uniqueItems": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
            "Name":
{
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the subscription.</p>"
                }
            },
            "Type": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
```

```
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
                },
                {
                    "name": "INVALID",
                    "value": "INVALID",

   "documentation": "INVALID status"
                },
                {
                    "name": "PENDING",
                    "value": "PENDING",
```

```
                "documentation": "PENDING status"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
           },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
              "method": "PUT",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
```

```
        "type": "structure",
        "members":
{
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
        "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
```

```
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}
              }
            },
            "tagKeys": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
              "traits": {

            "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                "smithy.api#httpQuery": "tagKeys",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
          "type": "structure",
          "members": {},
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

         },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
```

```
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                "smithy.api#required": {}
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                "smithy.api#required": {}
              }
            },
            "AllowUpdate": {
              "target":
 "smithy.api#Boolean",
              "traits": {
                "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
```

```
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                   "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
               }
            },
            "StatusMessage": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
               "traits": {
                  "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
               }

       },
            "HomeRegions": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                  "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated data for Linux\n      subscriptions.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
         }
      }
   }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
```

```
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
```

```
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
```

```
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
```

```
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
```

```
//
// This member is required.
LicenseType types.LicenseType

// The ID of the workspace to associate the license with.
//
// This member is required.
WorkspaceId *string

// A token from Grafana Labs that ties your Amazon Web Services account with a
// Grafana Labs account. For more information, see [Link your account with Grafana Labs].
//
// [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
GrafanaToken *string

noSmithyDocumentSerde
}

type AssociateLicenseOutput
struct {

// A structure containing data about the workspace.
//
// This member is required.
Workspace *types.WorkspaceDescription

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}
```

```
if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
```

```
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
```

```
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
  return err
```

```
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
```

CheckInLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": " You don't have sufficient access to perform this action. ",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {

```
        "type": "structure",
        "members": {
          "DirectoryId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
            "traits": {
              "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
            }
          },
          "ActiveDirectorySettings":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
          },
          "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
              "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
          "DomainName": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
            }
          },
          "DomainIpv4List": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
            "traits": {
              "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 2
              }
```

```
            }
          },
          "DomainCredentialsProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
            }
          },
          "DomainNetworkSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "SELF_MANAGED",
              "value": "SELF_MANAGED",
              "documentation": "SELF_MANAGED type of Active Directory"
            },
            {
              "name": "AWS_MANAGED",
              "value": "AWS_MANAGED",
              "documentation": "AWS_MANAGED type of Active Directory"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based
subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related
costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing
status) in Amazon Web Services Billing. For more information, see <a
href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
{
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
```

```
"com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
    "type": "structure",
    "members": {
      "Username": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
          "smithy.api#required": {}
        }
      },
      "InstanceId": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
          "smithy.api#required": {}
        }
      },
      "IdentityProvider": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
        "traits": {
          "smithy.api#documentation": "<p>The identity provider for the user.</p>",
          "smithy.api#required": {}
        }
      },
      "Domain": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
        }
      },
      "Tags": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
        "traits": {
          "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
        }
      }
    },
    "traits": {

  "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
    "type": "structure",
    "members": {
      "InstanceUserSummary": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },

        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                  "smithy.api#required": {}
               }
            },
            "Tags": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
          "SecretsManagerCredentialsProvider":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
```

```
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
```

<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete. ",
                "smithy.api#required": {}
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": " The type of License Server that the delete request refers to. ",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoint": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
              "traits": {
                "smithy.api#documentation": " Shows details from the <code>LicenseServerEndpoint</code> resource that was deleted. "
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
         "type": "structure",
         "members": {
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity provider to deregister.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
```

```
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

      }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
```

```
                "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
              }
            },
            "InstanceUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
          "type": "structure",
          "members": {
            "InstanceUserSummary":
{
              "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
          "type": "structure",
          "members": {
            "Subnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                "smithy.api#length": {
```

```
                    "min": 1
                },

    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
                }
            },
            "Operation": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
                }
            },
            "Value": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>Value of the filter.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
```

```
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
```

```
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
               }
            },
            "FailureMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
         "type": "list",
         "member": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
         "type": "structure",
         "members": {
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                  "smithy.api#required": {}
               }
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                  "smithy.api#required": {}
               }
            },
            "Products": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
                "traits": {
                  "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                  "smithy.api#required": {}
               }
```

```
            },
            "LastStatusCheckDate": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The date of the last status check.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                  "smithy.api#required": {}
               }
            },
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                  "smithy.api#required": {}
               }
            },

      "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
```

```
\n\t\t\tabout the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
                 }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
                }
            },
            "AssociationDate": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
                }
            },
            "DisassociationDate": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
```

```
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
   "type": "list",
   "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
   }
},
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
   "type": "structure",
   "members": {
      "message": {
         "target": "smithy.api#String"
      }
   },
   "traits": {
      "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
       "smithy.api#error": "server",
      "smithy.api#httpError": 500
   }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
   "type": "string",
   "traits": {
      "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
   }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
   "type": "list",
   "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
   }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
   "type": "service",
   "version": "2018-05-10",
   "operations": [
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
       },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
      },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
            },
            {
"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
        ],
        "traits": {
            "aws.api#service": {
              "sdkId": "License Manager User Subscriptions",
              "arnNamespace": "license-manager-user-subscriptions",
              "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
```

```
            "name": "license-manager-user-subscriptions"
          },
          "aws.protocols#restJson1": {},
          "smithy.api#cors": {
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id",
              "content-length",

        "x-api-key",
              "authorization",
              "x-amz-date",
              "x-amz-security-token",
              "Access-Control-Allow-Headers",
              "Access-Control-Allow-Methods",
              "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager User Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region":
{
                "builtIn": "AWS::Region",
                "required": false,
                "documentation": "The AWS region used to dispatch the request.",
                "type": "String"
              },
              "UseDualStack": {
                "builtIn": "AWS::UseDualStack",
                "required": true,
                "default": false,
                "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                "type": "Boolean"
              },
```

```
      "UseFIPS": {
        "builtIn": "AWS::UseFIPS",
        "required": true,
        "default": false,
        "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will
return an error.",
        "type": "Boolean"
      },
      "Endpoint": {
        "builtIn": "SDK::Endpoint",
        "required": false,
        "documentation": "Override the endpoint used to send this request",
        "type": "String"
      }
    },
    "rules": [
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Endpoint"
              }
            ]
          }
         ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [
              {
```

```
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "endpoint": {
              "url": {
                "ref": "Endpoint"
              },

"properties": {},
              "headers": {}
            },
            "type": "endpoint"
          }
        ],
        "type": "tree"
      },
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Region"
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "aws.partition",

                "argv": [
                  {
                    "ref": "Region"
                  }
```

```
                ],
                "assign": "PartitionResult"
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseFIPS"
                      },
```

true

```
                    ]
                  },
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
```

"fn": "booleanEquals",

```
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"
                              },
                              "supportsFIPS"
                            ]
                          }
                        ]
                      },
```

```
                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }

                ]
                  }
                ],
                "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }

    ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
```

```
{
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "fn": "getAttr",
                                            "argv": [

                                {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsFIPS"
                                        ]
                                    },
                                    true
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {

                        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

    }
                    ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]

         }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
```

```
                ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "DualStack is enabled but this partition does not support DualStack",
                    "type": "error"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

            "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
      }
    ],
    "type": "tree"
  },
  {
    "conditions": [],
    "error": "Invalid Configuration: Missing Region",
    "type": "error"
  }
 ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect":
{
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",

    "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS":
true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint":
{
                "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
```

```
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false

    }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
```

```
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

            },
              "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
              },
              "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
                }
              },
              "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
              },
              "params": {
                "Region": "us-isob-east-1",

  "UseFIPS": false,
                "UseDualStack": true
              }
            },
```

```
                {
                  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
                    }
                  },
                  "params": {
                    "Region": "us-isob-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
                  "expect": {

                 "endpoint": {
                      "url": "https://example.com"
                    }
                  },
                  "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://example.com"
                    }
                  },
                  "params": {
                    "UseFIPS": false,
                    "UseDualStack":
 false,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                  "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                  },
```

```
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
        "type": "structure",
        "members": {
          "ProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
             "traits": {
               "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
            }
          },
          "HealthStatus": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
            "traits": {
              "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
            }
          },
```

```
            "Ipv4Address": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
               }
            },
            "ServerType": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
               "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>"
               }
            },
            "ServerEndpoint": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
               }
            },
            "LicenseServerEndpointId": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
```

```
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
{
              "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the
RDS \n\t\t\tlicense server.</p>"
            }
          },
          "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
              "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent
the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },

         "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when License Manager created the license server
endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop
Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
```

```
                {
                  "name": "UNHEALTHY",
                  "value": "UNHEALTHY",
                  "documentation": ""
                },
                {
                  "name": "NOT_APPLICABLE",
                  "value": "NOT_APPLICABLE",
                  "documentation": ""
                }
              ]
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
            "type": "structure",
            "members": {
              "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>",
                  "smithy.api#required": {}
                }
              },
              "ServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                  "smithy.api#required": {}
                }
              }
            },
            "traits": {
              "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
            "type": "operation",
            "input": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
            },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
             },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n <ul>\n <li>\n <p>Product</p>\n </li>\n <li>\n <p>DirectoryId</p>\n </li>\n </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

            "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
```

```
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
    "type": "operation",
     "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
    },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },

{
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/instance/ListInstances"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
        }
    }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
      "type": "structure",
      "members":
{
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
          }
        },
        "Filters": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
          "traits": {
            "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
      "type": "structure",
      "members": {
        "InstanceSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next
```

token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
"type": "operation",
"input": {
"target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
},
"output": {
"target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
},
"errors": [
{
"target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
},
{
"target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
}
],
"traits": {
"smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",
"smithy.api#http": {
"code": 200,
"method": "POST",
"uri": "/license-server/ListLicenseServerEndpoints"
},
"smithy.api#paginated": {
"inputToken": "NextToken",

```
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "LicenseServerEndpoints"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>IdentityProviderArn</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
```

```
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
         "type":
 "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
```

```
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "ProductUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
         "type": "structure",
         "members": {
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n               <p>Status</p>\n            </li>\n            <li>\n               <p>Username</p>\n
</li>\n            <li>\n               <p>Domain</p>\n            </li>\n         </ul>"
               }
```

```
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

             }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
```

```
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceUserSummaries"
        }
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
```

```
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
 \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
```

```
            "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
              "traits": {
                 "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
          "type": "structure",
          "members": {
            "Username":
 {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
                 "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                 "smithy.api#required": {}
              }
            },
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                 "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                 "smithy.api#required": {}
              }
            },
             "Status": {
              "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
{
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {

   "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits":
{
                    "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
"<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

    "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

           "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
          "Endpoint": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
        "type": "union",
        "members": {
          "RdsSalSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {

"target": "smithy.api#String"
            }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity
```

provider. \n <note>\n Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as Pending billing status) in Amazon Web Services Billing. For more information, see Viewing your\n\t\t\t\tmonthly charges in the Amazon Web Services Billing User Guide. \n </note>",
"smithy.api#http": {
"code": 200,
"method": "POST",
"uri": "/user/StartProductSubscription"
}

}
},
"com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
"type": "structure",
"members": {
"Username": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The user name from the identity provider of the user. ",
"smithy.api#required": {}
}
},
"IdentityProvider": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
"traits": {
"smithy.api#documentation": " An object that specifies details for the identity provider. ",
"smithy.api#required": {}
}
},
"Product": {
"target": "smithy.api#String",
"traits": {

"smithy.api#documentation": " The name of the user-based subscription product. \n Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n ",
"smithy.api#required": {}
}
},
"Domain": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The domain name of the Active Directory that contains the user for whom to start the product \n\t\t\tsubscription. "
}
},

```
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
              }

  }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
```

```
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
                  "smithy.api#required": {}
               }

   }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
         "type": "list",
         "member": {
            "target": "smithy.api#String"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
         }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {

"min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        },
        "Tags": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
          "traits": {
            "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

             "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
```

```
to remove tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}

            }
               },
               "TagKeys": {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
                  "traits": {
                     "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                     "smithy.api#httpQuery": "tagKeys",
                     "smithy.api#required": {}
                  }
               }
            },
            "traits": {
               "smithy.api#input": {}
            }
         },
         "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
            "type": "structure",
            "members": {},
            "traits": {
               "smithy.api#output": {}
            }
         },
         "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
            "type": "operation",
            "input": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
             },
            "output": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
            },
            "errors": [
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
               },
               {
                  "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
               }
            ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
            "smithy.api#http": {

       "code": 200,
                "method": "POST",
                "uri": "/identity-provider/UpdateIdentityProviderSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },

            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
                }
            },
            "UpdateSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
                "traits": {
                    "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n <ul>\n            <li>\n                <p>Subnets which you want to add to provision VPC endpoints.</p>\n            </li>\n        <li>\n                <p>Subnets which you want to remove the VPC endpoints from.</p>\n            </li>\n <li>\n                <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n            </li>\n        </ul>",
                    "smithy.api#required": {}
                }
            }
        },
```

```
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
      "type": "structure",
      "members": {
        "IdentityProviderSummary": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
          "traits": {
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
```

```
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A parameter is not valid.</p>",
          "smithy.api#error": "client"
        }
      }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {
```

```
 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
```

```
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
```

```
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
```

InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership

of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or

documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization

AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.142 github.com/go-ldap/ldap/v3 3.4.11

1.142.1 Available under license :

The MIT License (MIT)

Copyright (c) 2011-2015 Michael Mitton (mmitton@gmail.com)
Portions copyright (c) 2015-2024 go-ldap Authors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.143 aws-sdk-go-v2-service-sts 1.36.0

1.143.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart

```
 setOperationInput
 ResolveEndpoint
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
```

```
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
```

```
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer

 // License name.
 //
 // This member is required.
 LicenseName *string

 // Product name.
 //
 // This member is required.
 ProductName *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // Date and time range during which the license is valid, in ISO8601-UTC format.
 //
 // This member is required.
 Validity *types.DatetimeRange

 // Information about
 the license.
 LicenseMetadata []types.Metadata

 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
```

```
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
```

```
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err
 = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addResponseErrorMiddleware(stack); err != nil {
 return
err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return
err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
```

```
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
      uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
```

RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop

InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware

```
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  InterceptAfterDeserialization
  OperationDeserializer
  InterceptBeforeDeserialization
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
  InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
```

```
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string
```

```
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
```

```
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
```

```
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
 Deserialize stack step
  AddRawResponseToMetadata
```

```
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
```

```
//   - ProductSKU
//
//   - Fingerprint
//
//   - Status
Filters
[]types.Filter

// Amazon Resource Names (ARNs) of the licenses.
LicenseArns []string

// Maximum number of results to return in a single call.
MaxResults *int32

// Token for the next set of results.
NextToken *string

noSmithyDocumentSerde
}

type ListLicensesOutput struct {

// License details.
Licenses []types.License

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack,
```

```
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
```

```
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
 return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
 return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
```

```
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
```

```
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
```

```
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
```

```
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
```

```
 ServiceID:     ServiceID,
 OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}
```

```
type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
```

```
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
```

```
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
```

```
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {
```

```
//
Checkout type.
//
// This member is required.
CheckoutType types.CheckoutType

// Unique, case-sensitive identifier that you provide to ensure the idempotency of
// the request.
//
// This member is required.
ClientToken *string

// License entitlements.
//
// This member is required.
Entitlements []types.EntitlementData

// Key fingerprint identifying the license.
//
// This member is required.
KeyFingerprint *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// License beneficiary.
Beneficiary *string

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

// Checkout type.
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string
```

```
// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
```

```
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
```

```
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
```

```
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },

    {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/DeregisterSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
            }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation":
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

        "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
```

```
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
             }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
```

```
            "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
        },
        "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
      "type": "structure",
      "members": {
        "AmiId": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
        },
        "InstanceID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
        },
        "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
        },
        "AccountID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
```

```
            "Region": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
               }
            },
            "UsageOperation": {
               "target": "smithy.api#String",

   "traits": {
                  "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
               }
            },
            "ProductCode": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
               "traits": {
                  "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
               }
            },
            "LastUpdatedTime": {
               "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
               }
            },
            "SubscriptionName": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
               }
            },
            "OsVersion": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
               }
            },
            "SubscriptionProviderCreateTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp when you registered
```

```
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
                }
            },
            "SubscriptionProviderUpdateTime": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
                }
            },
            "DualSubscription": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
                }
            },
            "RegisteredWithSubscriptionProvider": {
                "target": "smithy.api#String",
                "traits": {

      "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
```

```
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
       },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
      },
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
      }
    ],
    "traits": {
      "aws.api#service": {
        "sdkId": "License Manager Linux Subscriptions",
         "arnNamespace": "license-manager-linux-subscriptions",
        "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
      },
      "aws.auth#sigv4": {
        "name": "license-manager-linux-subscriptions"
```

```
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the
 configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
```

```
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
                            ]
                        }

],
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                    "type": "error"
                },
                {
                    "conditions": [],
                    "rules": [
                        {
                            "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseDualStack"
                                        },
                                        true
                                    ]
```

```
}
                ],
                "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                "type": "error"
              },
              {
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },
                  "properties": {},
                  "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"

          }
          ],
          "type": "tree"
        },
        {
          "conditions": [],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Region"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {

          "fn": "aws.partition",
                        "argv": [
                          {
                            "ref": "Region"
                          }
                        ],
```

```
                "assign": "PartitionResult"
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {

                    "ref": "UseFIPS"
                            },
                            true
                        ]
                    },
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }

],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

        },
                                        "supportsFIPS"
                                    ]
                                }
                            ]
                        },
                        {
                            "fn": "booleanEquals",
```

```
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [

                     {
                          "ref": "PartitionResult"
                       },
                       "supportsDualStack"
                    ]
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [],

    "rules": [
                  {
                    "conditions": [],
                    "endpoint": {
                      "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                      "properties": {},
                      "headers": {}
                    },
                    "type": "endpoint"
                  }
                ],

            "type": "tree"
                  }
                ],
                "type": "tree"
              },
              {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                "type": "error"
              }
            ],
            "type": "tree"
          },
          {
```

```
            "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
                    true
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {

          "fn": "booleanEquals",
                      "argv": [
                        {
                          "fn": "getAttr",
                          "argv": [
                            {
                              "ref": "PartitionResult"
                            },
                            "supportsFIPS"
                          ]
                        },
                        true

                    ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "rules": [
                        {
                          "conditions": [],
                          "endpoint": {
                            "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                            "headers": {}
                          },
                          "type": "endpoint"
                        }
                      ],
```

```
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS is enabled
but this partition does not support FIPS",
            "type": "error"
        }
    ],
    "type": "tree"
},
{
    "conditions": [
        {
            "fn": "booleanEquals",
            "argv": [
                {
                    "ref": "UseDualStack"
                },
                true

            ]
        }
    ],
    "rules": [
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [
                                {

                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }
                    ]
                }
            ],
            "rules": [
```

```
                                        {
                                            "conditions": [],
                                            "rules": [

        {
                                                    "conditions": [],
                                                    "endpoint": {
                                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                        "properties": {},
                                                        "headers": {}
                                                    },
                                                    "type": "endpoint"
                                                }
                                            ],
                                            "type": "tree"

                                }
                                    ],
                                    "type": "tree"
                                },
                                {
                                    "conditions": [],
                                    "error": "DualStack is enabled but this partition does not support DualStack",
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"
                        }
                    ],
                    "type": "tree"
```

```
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
            }
        ],
        "type": "tree"
    }
  ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

  }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {

   "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
```

```
                "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
              }
            },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
              }

      },
            "params": {
              "Region": "us-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

 "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
```

```
            }

        },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

      "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
```

```
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
       }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": true,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
    "expect": {
      "error": "DualStack is enabled but this partition does not support DualStack"
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": true
    }
  },
  {

   "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
    "expect": {
      "endpoint": {
        "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
      }
    },
    "params": {
      "Region": "us-isob-east-1",
      "UseFIPS": false,
      "UseDualStack": false
    }
  },
  {
    "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
    "expect": {
      "endpoint": {
        "url": "https://example.com"
      }
```

```
    },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://example.com"
                  }
                },
                "params": {
                  "UseFIPS": false,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {

                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

 "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
```

```
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled LinuxSubscriptionsDiscovery"

        },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

 {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
```

```
            "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n \t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n        <li>\n  <p>\n            <code>AccountID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n    <code>AmiID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>DualSubscription</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceID</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>InstanceType</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>ProductCode</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Region</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Status</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>UsageOperation</code>\n          </p>\n        </li>\n      </ul>\n      <p>For each filter, you can use one of the following <code>Operator</code>\n values to \n  \t\tdefine the behavior of the filter:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
```

```
            "Instances": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
               "traits": {
                  "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
               }
            },
            "NextToken": {

         "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
```

```
                "outputToken": "NextToken",
                "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n
<li>\n              <p>\n                <code>Subscription</code>\n              </p>\n            </li>\n          </ul>\n
<p>The
 valid Operators for this filter are:</p>\n          <ul>\n            <li>\n              <p>\n
<code>contains</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>equals</code>\n              </p>\n            </li>\n            <li>\n              <p>\n
<code>Notequal</code>\n              </p>\n            </li>\n          </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
      "type": "structure",
      "members": {
        "Subscriptions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
          "traits": {
            "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
           "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/ListRegisteredSubscriptionProviders"
```

```
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "RegisteredSubscriptionProviders"
            }
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
         "type": "structure",
         "members": {
            "SubscriptionProviderSources": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
               "traits": {
                  "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                  "smithy.api#range": {
                     "min": 1,
                     "max": 100
                  }
               }

   },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
         "type": "structure",
         "members": {
            "RegisteredSubscriptionProviders": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria \n\t\t\tyou specified in the request.</p>"
            }
          },

         "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
```

```
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation":
"<p>The Linux subscription provider that you registered.</p>"
          }
        },
        "SubscriptionProviderArn": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderStatus": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
          }
        },
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
          }
        },
```

```
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is the offline token.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions, \n\t\t\tthis is the status of the offline token.</p>"
               }
            },
            "SubscriptionProviderStatusMessage": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription \n\t\t\tprovider token status.</p>"
               }
            },
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
```

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

  }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
                    "documentation": "Failed status"
                }
            ]
        }
    },

   "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#length": {
                "min": 1,
                "max": 100
              }
            }
          },
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            },
            "smithy.api#uniqueItems": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
          "type": "map",
          "key": {
            "target": "smithy.api#String"
          },
          "value": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
          "type": "structure",
          "members": {
            "Name":
{
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the subscription.</p>"
              }
            },
            "Type": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
              }
            },
            "InstanceCount": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
              "traits": {
                "smithy.api#documentation": "<p>The total amount of running instances using this
```

```
subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
```

```
            },
            {
               "name": "INVALID",
               "value": "INVALID",

"documentation": "INVALID status"
            },
            {
               "name": "PENDING",
               "value": "PENDING",
               "documentation": "PENDING status"
            }
         ]
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
      "type": "list",
      "member": {
         "target": "smithy.api#String"
      },
      "traits": {
         "smithy.api#length": {
            "min": 0,
            "max": 50
         },
         "smithy.api#sensitive": {}
      }
   },
   "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
       },
      "errors": [
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
         },
         {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
         }
      ],
      "traits": {
```

```
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
{
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
         "type": "map",
         "key": {
            "target": "smithy.api#String"
         },
```

```
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

       },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
         "type": "structure",
         "members": {
            "LinuxSubscriptionsDiscovery": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
               "traits": {
                  "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                  "smithy.api#required": {}
               }
            },
            "LinuxSubscriptionsDiscoverySettings": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
               "traits": {
                  "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                  "smithy.api#required": {}
               }
            },
            "AllowUpdate": {
               "target":
 "smithy.api#Boolean",
               "traits": {
                  "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux
subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home
Region.</p>"
               }
            }
         }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
          "traits": {
            "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
          }
        },
        "LinuxSubscriptionsDiscoverySettings": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
           "traits": {
            "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>"
          }
        },
        "Status": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
          "traits": {
            "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
          }
        },
        "StatusMessage": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
          "traits": {
            "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
          }

     },
        "HomeRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
          }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
```

```
            "traits": {
                "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
                "smithy.api#error": "client"
            }
        }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
```

```
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string
```

```
 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
```

```
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
```

```
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return
err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
```

```
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager
```

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string
```

```
// License status.
Status types.LicenseDeletionStatus

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addCredentialSource(stack, options); err != nil {
 return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
```

```
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {

```
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
        "type": "structure",
        "members": {
            "DirectoryId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
                "traits": {
                    "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
                }
            },
            "ActiveDirectorySettings":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
                }
            },
            "ActiveDirectoryType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Details about an Active Directory identity
 provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
```

```
            },
            "DomainIpv4List": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
               "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 2
                  }
               }
            },
            "DomainCredentialsProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
               }
            },
            "DomainNetworkSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
               },
               {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
               }
```

```
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n          <note>\n             <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly
```

charges in the Amazon Web Services Billing User Guide. \n </note>",
"smithy.api#http":
{
"code": 200,
"method": "POST",
"uri": "/user/AssociateUser"
},
"smithy.api#idempotent": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
"type": "structure",
"members": {
"Username": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The user name from the identity provider. ",
"smithy.api#required": {}
}
},
"InstanceId": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The ID of the EC2 instance that provides the user-based subscription. ",
"smithy.api#required": {}
}
},
"IdentityProvider": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
"traits": {
"smithy.api#documentation": " The identity provider for the user. ",
"smithy.api#required": {}
}
},
"Domain": {
"target": "smithy.api#String",
"traits": {
"smithy.api#documentation": " The domain name of the Active Directory that contains information for the user to associate. "
}
},
"Tags": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
"traits": {
"smithy.api#documentation": " The tags that apply for the user association. "
}
}

```
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },

          {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS)
license server.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/license-server/CreateLicenseServerEndpoint"
             },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
         "type": "structure",
         "members": {
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                  "smithy.api#required": {}
               }
            },
            "LicenseServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
```

```
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
```

```
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
            "LicenseServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
                "traits": {
                    "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
                }
            }
        },
         "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
```

```
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
```

```
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
               }
            },
            "InstanceUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary":
{
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
            "smithy.api#length": {
              "min": 1
            },

  "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Attribute": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
          }
        },
        "Operation": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
          }
        },
        "Value": {
          "target": "smithy.api#String",
          "traits":
{
            "smithy.api#documentation": "<p>Value of the filter.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
```

```
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
            "ActiveDirectoryIdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of the
identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
          },
          "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
```

```
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
          "type": "structure",
          "members": {
            "Username": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                "smithy.api#required": {}
              }
            },
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based subscriptions.</p>",
                "smithy.api#required": {}
            }
        },

    "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details \n\t\t\tabout the identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                "smithy.api#required": {}
            }
        },
        "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance user.</p>"
             }
        },
        "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
        },
        "Domain": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
```

```
            "target": "smithy.api#String",
             "traits": {
               "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
           "smithy.api#error": "server",
          "smithy.api#httpError": 500
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
```

```
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
 },
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
},
{
   "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
},
{
```

```
    "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
            }
          ],
          "traits": {
            "aws.api#service": {
              "sdkId": "License Manager User Subscriptions",
              "arnNamespace": "license-manager-user-subscriptions",
              "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
            },
            "aws.auth#sigv4": {
              "name": "license-manager-user-subscriptions"
            },
            "aws.protocols#restJson1": {},
            "smithy.api#cors": {
              "additionalAllowedHeaders": [
                "*",
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",

           "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
              ],
              "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
              ]
            },
            "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to
utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager User Subscriptions",
            "smithy.rules#endpointRuleSet": {
              "version": "1.0",
              "parameters": {
                "Region":
{
                  "builtIn": "AWS::Region",
                  "required": false,
                  "documentation": "The AWS region used to dispatch the request.",
```

```
            "type": "String"
        },
        "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
            "type": "Boolean"
        },
        "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
        },
        "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
                                true
```

```
                ]
              }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [
              {

                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [],
            "endpoint": {
              "url": {
                "ref": "Endpoint"
              },

"properties": {},
                "headers": {}
              },
              "type": "endpoint"
            }
          ],
          "type": "tree"
        },
        {
          "conditions": [
            {
              "fn": "isSet",
              "argv": [
                {
                  "ref": "Region"
                }
              ]
            }
          ],
```

```
"rules": [
  {
    "conditions": [
      {
        "fn": "aws.partition",

        "argv": [
          {
            "ref": "Region"
          }
        ],
        "assign": "PartitionResult"
      }
    ],
    "rules": [
      {
        "conditions": [
          {
            "fn": "booleanEquals",
            "argv": [
              {
                "ref": "UseFIPS"
              },

true
            ]
          },
          {
            "fn": "booleanEquals",
            "argv": [
              {
                "ref": "UseDualStack"
              },
              true
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {

"fn": "booleanEquals",
                "argv": [
                  true,
                  {
                    "fn": "getAttr",
                    "argv": [
```

```
                                    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            }
                        ]
                    },

                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [
                                {
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }

            ]
                }
            ],
            "rules": [
                {
                    "conditions": [],
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }

    ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
            "type": "error"
        }
    ],
```

```
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [

{
                                "ref": "UseFIPS"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "fn": "getAttr",
                                        "argv": [

                {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsFIPS"
                                    ]
                                },
                                true
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {

        "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
```

```
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"

}
                ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "ref": "UseDualStack"
                            },
                            true
                        ]
                    }
                ],
                "rules": [
                    {

    "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]

    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
```

```
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }

                            ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "DualStack is enabled but this partition does not support DualStack",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect":
```

```
{
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",

      "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                    }
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint":
{
                        "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                    }
                },
                "params": {
                    "Region": "us-east-1",
```

```
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS":
true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": false,
         "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
```

```
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": false,
                "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                }
            },
            "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

    }
        },
        {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
            "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
```

```
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
```

```
      },
      "params": {
        "Region": "us-isob-east-1",

  "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {

       "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
```

```
false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                    "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                    "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
                },
                "params": {
                    "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
            },
            {
                "documentation": "Missing region",
                "expect": {
                    "error": "Invalid Configuration: Missing Region"
                }
            }
        ],
        "version": "1.0"
    }
  }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
  "type": "structure",
  "members": {
    "ProvisioningStatus": {
      "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
       "traits": {
         "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
```

```
\n\t\t\tlicense server.</p>"
                }
            },
            "HealthStatus": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
                }
            },
            "Ipv4Address": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

  "traits": {
                    "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
            }
        },
        "LicenseServerEndpointId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
            "traits": {
                "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
            }
        },
        "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits":
 {
                "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
            }
        },
        "LicenseServerEndpointProvisioningStatus": {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
            "traits": {
                "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
            }
        },
        "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
        },

       "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
        }
    },
    "traits": {
      "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
    }
  },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
      "type": "string"
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

"type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "PROVISIONING",
            "value": "PROVISIONING",
            "documentation": ""
          },
          {
            "name": "PROVISIONING_FAILED",
            "value": "PROVISIONING_FAILED",
            "documentation": ""
          },
          {
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
      "type": "structure",
      "members": {
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>",
            "smithy.api#required": {}
          }
        },
        "ServerSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
            "smithy.api#required": {}
          }
        }
      },
```

```
      "traits": {
        "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {

        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/identity-provider/ListIdentityProviders"
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
```

```
            "items": "IdentityProviderSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n          <li>\n            <p>Product</p>\n          </li>\n
        <li>\n            <p>DirectoryId</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

          "traits": {
              "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources
that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },

      {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
```

```
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
```

contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest criteria. "
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": " The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects. "
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": " List the Remote Desktop Services (RDS) License Server endpoints
",

```
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/license-server/ListLicenseServerEndpoints"
            },

          "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",
              "items": "LicenseServerEndpoints"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
          "type": "structure",
          "members": {
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
                "smithy.api#range": {
                  "min": 1,
                  "max": 100
                }
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
```

```
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
             "traits": {
               "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                 "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
```

```
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n          <p>Status</p>\n          </li>\n          <li>\n          <p>Username</p>\n
</li>\n          <li>\n          <p>Domain</p>\n          </li>\n          </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
         "type": "structure",
         "members": {
            "ProductUserSummaries": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#readonly": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

           }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
     },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
         }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListUserAssociations"
        },
        "smithy.api#paginated": {
```

```
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {

    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
  <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
```

```
user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
         "type": "structure",
         "members": {
            "IdentityProvider": {

     "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                  "smithy.api#required": {}
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
               "traits":
```

```
{
                "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
              "traits": {
                "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
          "type": "string",
          "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",
```

```
    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
            "smithy.api#length": {

             "min": 5,
                "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
            "Endpoint": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
             "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
      "type": "structure",
      "members": {
        "message": {

  "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
      "type": "structure",
      "members": {
        "Subnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
```

```
                "smithy.api#length": {
                    "min": 1
                },
                "smithy.api#required": {}
            }
        },
        "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

         "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StartProductSubscription"
            }

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {

  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n        <p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n</p>",
                    "smithy.api#required": {}
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/StopProductSubscription"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
                }
            },
            "IdentityProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
                }
            },
```

```
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
              }
            },
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
          "type": "structure",
          "members": {
            "ProductUserSummary": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
              "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                "smithy.api#required": {}
              }

    }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#StringList": {
          "type": "list",
          "member": {
```

```
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
```

```
        "traits": {
            "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation":
 "<p>The tags to apply to the specified resource.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
            "target": "smithy.api#String"
        },
        "value": {
```

```
            "target": "smithy.api#String"
          },
          "traits": {
            "smithy.api#length": {
              "min": 0,
              "max": 50
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
          "type": "structure",
          "members": {
            "message": {
              "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {

           "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered identity\n\t\t\tprovider.</p>",
            "smithy.api#http": {

      "code": 200,
                "method": "POST",
                "uri": "/identity-provider/UpdateIdentityProviderSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },

            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to update.</p>"
                }
            },
            "UpdateSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
                "traits": {
                    "smithy.api#documentation": "<p>Updates the registered identity providers product related
```

configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the: \n \n \n Subnets which you want to add to provision VPC endpoints. \n \n \n Subnets which you want to remove the VPC endpoints from. \n \n \n Security
group ID which permits traffic to the VPC endpoints. \n \n ",
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#input": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
"type": "structure",
"members": {
"IdentityProviderSummary": {
"target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
"traits": {
"smithy.api#required": {}
}
}
},
"traits": {
"smithy.api#output": {}
}
},
"com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
"type": "structure",
"members": {
"AddSubnets": {

"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets in which License Manager will create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers. ",
"smithy.api#required": {}
}
},
"RemoveSubnets": {
"target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
"traits": {
"smithy.api#documentation": " The ID of one or more subnets to remove. ",
"smithy.api#required": {}
}
},
"SecurityGroupId": {
"target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

```
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
```

```
 return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
```

```
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if
```

```
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
```

Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata

ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing

InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.144 github.com/google/uuid 1.6.0

1.144.1 Available under license :

Paul Borman <borman@google.com>
bmatsuo
shawnps
theory
jboverfelt
dsymonds
cd1
wallclockbuilder
dansouza
Copyright (c) 2009,2014 Google Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT

OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.145 ca-certificates-bundle 20250619-r0

1.145.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
#!/usr/bin/env perl
# ***************************************************************************
# *                                  _   _ ____  _
# *  Project                     ___| | | |  _ \| |
# *                             / __| | | | |_) | |
# *                            | (__| |_| |  _ <| |___
# *                             \___|\___/|_| \_\_____|
# *
# * Copyright (C) Daniel Stenberg, <daniel@haxx.se>, et al.
# *
# * This software is licensed as described in the file COPYING, which
# * you should have received as part of this distribution. The terms
# * are also available at https://curl.se/docs/copyright.html.
# *
# * You may opt to use, copy, modify, merge, publish, distribute and/or sell
# * copies of the Software, and permit persons to whom the Software is
# * furnished to do so, under the terms of the COPYING file.
# *
# * This software is distributed on an "AS IS" basis, WITHOUT WARRANTY OF ANY
#
 * KIND, either express or implied.
# *
# * SPDX-License-Identifier: curl
# *
# ***************************************************************************
# This Perl script creates a fresh ca-bundle.crt file for use with libcurl.
# It downloads certdata.txt from Mozilla's source tree (see URL below),
# then parses certdata.txt and extracts CA Root Certificates into PEM format.
# These are then processed with the OpenSSL commandline tool to produce the
# final ca-bundle.crt file.
# The script is based on the parse-certs script written by Roland Krikava.
# This Perl script works on almost any platform since its only external
# dependency is the OpenSSL commandline tool for optional text listing.
```

Hacked by Guenter Knauf.
#

Found in path(s):
* /ca-certificates-20250619-tar-bz2/ca-certificates-20250619/mk-ca-bundle.pl
No license file was found, but licenses were detected in source scan.

/* c_rehash.c - Create hash symlinks for certificates
* C implementation based on the original Perl and shell versions
*
* Copyright (c) 2013-2014 Timo Teräs <timo.teras@iki.fi>
* All rights reserved.
*
* This software is licensed under the MIT License.
* Full license available at: http://opensource.org/licenses/MIT
*/

Found in path(s):
* /ca-certificates-20250619-tar-bz2/ca-certificates-20250619/c_rehash.c
No license file was found, but licenses were detected in source scan.

#
This Source Code Form is subject to the terms of the Mozilla Public
License, v. 2.0. If a copy of the MPL was not distributed with this
file, You can obtain one at http://mozilla.org/MPL/2.0/.

Found in path(s):
* /ca-certificates-20250619-tar-bz2/ca-certificates-20250619/certdata.txt

1.146 alpine-base 3.21.4-r0

1.146.1 Available under license :

Contributor: Natanael Copa <ncopa@alpinelinux.org>
Maintainer: Natanael Copa <ncopa@alpinelinux.org>
pkgname=alpine-base
pkgver=3.21.4
pkgrel=0
pkgdesc="Meta package for minimal alpine base"
url="https://alpinelinux.org"
arch="noarch"
license="MIT"
The MIT License

Copyright <YEAR> <COPYRIGHT HOLDER>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the

rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.147 githubcomgoopenapijsonpointer 0.21.1

1.147.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable

(except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,

and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.148 zlib 1.3.1-r2

1.148.1 Available under license :

Copyright notice:

(C) 1995-2022 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
   claim that you wrote the original software. If you use this software
   in a product, an acknowledgment in the product documentation would be
   appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be
   misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu
Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization
obtaining a copy of the software and accompanying documentation covered by
this license (the "Software") to use, reproduce, display, distribute,
execute, and transmit the Software, and to prepare derivative works of the
Software, and to permit third-parties to whom the Software is furnished to
do so, all subject to the following:

The copyright notices in the Software and this entire statement, including
the above license grant, this restriction and the following disclaimer,
must be included in all copies of the Software, in whole or in part, and
all derivative works of the Software, unless such copies or derivative
works are solely in the form of machine-executable object code generated by
a source language processor.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT
SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.149 aws-sdk-go-v2-service-dynamodb 1.46.0

1.149.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart

InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger

```
  InterceptTransmit
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
     - name: Run Scan code on pr ref
       run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
```

```
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
```

This member is required.
ClientToken *string

// Configuration for consumption of the license. Choose a provisional
// configuration for workloads running with continuous connectivity. Choose a
// borrow configuration for workloads with offline usage.
//
// This member is required.
ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

```
 // Tags to add to the license. For more information about tagging support in
 // License Manager, see the [TagResource]operation.
 //
 // [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
 Tags []types.Tag

 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
```

```
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
```

UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step

ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint

```
 InterceptBeforeSerialization
 OperationSerializer
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
```

```
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
```

```
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
```

```
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
```

```
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return
err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if
err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
```

```
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
```

```
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
```

```
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack,
options, "ListLicenses"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
```

OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

```
import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
```

```
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
```

```
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
```

```
 return err
}
if err = addDisableHTTPSMiddleware(stack, options);
err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if
err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
```

```
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
```

```
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
```

```
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options);
err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
 return err
}
```

```
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack,
options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
```

```
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
```

```
CheckoutType types.CheckoutType

// Allowed license entitlements.
EntitlementsAllowed []types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string

// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the checkout license.
LicenseArn
*string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
```

```
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack,
c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
```

```
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack,
options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go

Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.

Copyright 2014-2015 Stripe, Inc.

```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
```

```
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own
License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/DeregisterSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider
resource to deregister.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
      "type": "structure",
      "members": {},
```

```
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of name to filter by.</p>"
                 }
            },
            "Values": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
                }
            },
            "Operator": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
                "traits": {
                    "smithy.api#documentation": "<p>An operator for filtering results.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe
operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
 "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
```

```
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's registered to your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetRegisteredSubscriptionProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration resource specified in the request.</p>"
```

```
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

        "traits": {
              "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource specified \n\t\t\tin the request.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the last \n\t\t\tsuccessful subscription data request.</p>"
             }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target":
```

```
"com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/GetServiceSettings"

            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
```

```
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
                }
            },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                 "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
            "AmiId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
                }
            },
            "InstanceID": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
                }
            },
            "InstanceType": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>The instance type of the resource.</p>"
                }
            },
            "AccountID": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
              }
            },
            "Region": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
              }
            },
            "UsageOperation": {
              "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
              }
            },
            "ProductCode": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
              "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
              }
            },
            "LastUpdatedTime": {
              "target": "smithy.api#String",
               "traits": {
                "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
              }
            },
            "SubscriptionName": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
              }
            },
            "OsVersion": {
              "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
            }
          },
          "SubscriptionProviderCreateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
          },
          "SubscriptionProviderUpdateTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the registered \n\t\t\tthird-party Linux subscription provider.</p>"
            }
          },
          "DualSubscription": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for \n\t\t\tthe same software on your instance.</p>"
            }
          },
          "RegisteredWithSubscriptionProvider": {
            "target": "smithy.api#String",
            "traits": {

    "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta third-party Linux subscription provider that you've registered with License Manager.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
```

```
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
"<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
            }
```

```
    ],
    "traits": {
      "aws.api#service": {
        "sdkId": "License Manager Linux Subscriptions",
         "arnNamespace": "license-manager-linux-subscriptions",
        "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
      },
      "aws.auth#sigv4": {
        "name": "license-manager-linux-subscriptions"
      },
      "aws.protocols#restJson1": {},
      "smithy.api#cors": {
        "additionalAllowedHeaders": [
          "*",
          "content-type",
          "x-amz-content-sha256",
          "x-amz-user-agent",
          "x-amzn-platform-id",
          "x-amzn-trace-id"
        ],
        "additionalExposedHeaders": [
          "x-amzn-errortype",
          "x-amzn-requestid",
          "x-amzn-trace-id"
        ]
      },
      "smithy.api#documentation": "<p>With License Manager,
 you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
      "smithy.api#title": "AWS License Manager Linux Subscriptions",
      "smithy.rules#endpointRuleSet": {
        "version": "1.0",
        "parameters": {
          "Region": {
            "builtIn": "AWS::Region",
            "required": false,
            "documentation": "The AWS region used to dispatch the request.",
            "type": "String"
          },
          "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not
 support dual-stack, dispatching the request MAY return an error.",
             "type": "Boolean"
          },
          "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
```

```
                "required": true,
                "default": false,
                "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                "type": "Boolean"
            },
            "Endpoint": {
                "builtIn": "SDK::Endpoint",
                "required": false,
                "documentation": "Override the endpoint used to send this request",
                "type": "String"
            }
        },
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "isSet",
                        "argv": [
                            {
                                "ref": "Endpoint"
                            }
                        ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseFIPS"
                                    },
                                    true
                                ]
                            }

    ],
                        "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                        "type": "error"
                    },
                    {
                        "conditions": [],
                        "rules": [
                            {
                                "conditions": [
                                    {
```

```
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseDualStack"
                                    },
                                    true
                                ]

    }
                            ],
                            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                            "type": "error"
                        },
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": {
                                    "ref": "Endpoint"
                                },
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],
                    "type": "tree"

                }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "isSet",
                                "argv": [
                                    {
                                        "ref": "Region"
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
```

```
                {

            "fn": "aws.partition",
                    "argv": [
                      {
                        "ref": "Region"
                      }
                    ],
                    "assign": "PartitionResult"
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {

                       "ref": "UseFIPS"
                          },
                          true
                        ]
                      },
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseDualStack"
                          },
                          true
                        ]
                      }

],
                    "rules": [
                      {
                        "conditions": [
                          {
                            "fn": "booleanEquals",
                            "argv": [
                              true,
                              {
                                "fn": "getAttr",
                                "argv": [
                                  {
                                    "ref": "PartitionResult"
```

```
                },
                                "supportsFIPS"
                            ]
                        }
                    ]
                },
                {
                    "fn": "booleanEquals",
                    "argv": [
                        true,
                        {
                            "fn": "getAttr",
                            "argv": [

                             {
                                    "ref": "PartitionResult"
                                },
                                "supportsDualStack"
                            ]
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [],

        "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],

             "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support
```

```
one or both",
                                        "type": "error"
                                    }
                                ],
                                "type": "tree"
                            },
                            {

                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            {
                                                "ref": "UseFIPS"
                                            },
                                            true
                                        ]
                                    }
                                ],
                                "rules": [
                                    {
                                        "conditions": [
                                            {

                                "fn": "booleanEquals",
                                                "argv": [
                                                    {
                                                        "fn": "getAttr",
                                                        "argv": [
                                                            {
                                                                "ref": "PartitionResult"
                                                            },
                                                            "supportsFIPS"
                                                        ]
                                                    },
                                                    true

                                                ]
                                            }
                                        ],
                                        "rules": [
                                            {
                                                "conditions": [],
                                                "rules": [
                                                    {
                                                        "conditions": [],
                                                        "endpoint": {
                                                            "url": "https://license-manager-linux-subscriptions-
```

```
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                                    "headers": {}
                                                },
                                                "type": "endpoint"
                                            }
                                        ],
                                        "type": "tree"
                                    }
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "error": "FIPS is enabled
but this partition does not support FIPS",
                                "type": "error"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseDualStack"
                                    },
                                    true


                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [
                                    {
                                        "fn": "booleanEquals",
                                        "argv": [
                                            true,
                                            {
                                                "fn": "getAttr",
                                                "argv": [
                                                    {
```

```
                                        "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "rules": [

        {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"

                }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                            "properties": {},
                            "headers": {}
```

```
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
],
"type": "tree"
}
]
},
"smithy.rules#endpointTests": {
"testCases": [
{
"documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
"expect": {
"endpoint": {
"url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
},
"params": {
"Region": "us-east-1",
"UseFIPS": true,
"UseDualStack": true
}
},
{
"documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
"expect": {
"endpoint": {
"url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
}
},
"params": {
"Region": "us-east-1",
"UseFIPS": true,
```

```
            "UseDualStack": false
          }
        },
        {

      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
```

```
"documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                      }
                    },
                    "params": {
                      "Region": "cn-north-1",
                      "UseFIPS": true,
                      "UseDualStack": false
                    }
                  },
                  {
                    "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                      }
                     },
                    "params": {
                      "Region": "cn-north-1",
                      "UseFIPS": false,
                      "UseDualStack": true
                    }
                  },
                  {
                    "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
                      }
                    },
                    "params": {
                      "Region": "cn-north-1",
                      "UseFIPS": false,
                      "UseDualStack": false
                    }
                  },
                  {

 "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
                      }
                    },
                    "params": {
                      "Region": "us-gov-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }

        },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
```

```
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {

        "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS":
false,
            "UseDualStack": false
          }
        },
```

```
{
  "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
  "expect": {
    "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": true,
    "UseDualStack": true
  }
},
{
  "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
  "expect": {
    "endpoint": {
      "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
     }
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": true,
    "UseDualStack": false
  }
},
{
  "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
  "expect": {
    "error": "DualStack is enabled but this partition does not support DualStack"
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": false,
    "UseDualStack": true
  }
},
{

 "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
  "expect": {
    "endpoint": {
      "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
    }
  },
  "params": {
    "Region": "us-isob-east-1",
    "UseFIPS": false,
    "UseDualStack": false
  }
```

```
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {

      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
      },
```

```
                "params": {

 "Region": "us-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled LinuxSubscriptionsDiscovery"

       },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
        "type": "structure",
        "members": {
          "SourceRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
```

```
            "OrganizationIntegration": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
                "traits": {
                    "smithy.api#documentation":
"<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

 {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n        <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n        <ul>\n          <li>\n
  <p>\n              <code>AccountID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
    <code>AmiID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>DualSubscription</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceID</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>InstanceType</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>ProductCode</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Region</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Status</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>UsageOperation</code>\n            </p>\n          </li>\n        </ul>\n        <p>For each filter, you can use
one of the following <code>Operator</code>
 values to \n  \t\tdefine the behavior of the filter:</p>\n        <ul>\n          <li>\n            <p>\n
<code>contains</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>equals</code>\n            </p>\n          </li>\n          <li>\n            <p>\n
<code>Notequal</code>\n            </p>\n          </li>\n        </ul>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
```

```
        "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
            "Instances": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
                "traits": {
                    "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
                }
            },
            "NextToken": {

         "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
             {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",

   "items": "Subscriptions"
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
         "type": "structure",
         "members": {
            "Filters": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those
that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n
 <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't
match a certain subscription's name.</p>\n         <p>The valid names for this filter are:</p>\n         <ul>\n
<li>\n               <p>\n                  <code>Subscription</code>\n               </p>\n            </li>\n         </ul>\n
<p>The
 valid Operators for this filter are:</p>\n         <ul>\n            <li>\n               <p>\n
<code>contains</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>equals</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>Notequal</code>\n               </p>\n            </li>\n         </ul>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 16384
                  }
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "Subscriptions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
            "traits": {
              "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
             "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
```

```
        ],
        "traits": {
          "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration resources for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListRegisteredSubscriptionProviders"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "RegisteredSubscriptionProviders"
          }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSources": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
          "traits": {
            "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to return \n\t\t\tin the list.</p>"
          }
        },
        "MaxResults": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
            "smithy.api#range": {
              "min": 1,
              "max": 100
            }
          }

  },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the nextToken from a previously truncated response.</p>"
          }
        }
      },
```

```
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
          "traits": {
            "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
          }
        },

        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
      },
      "errors": [
        {

      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
            "tags": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
         }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
```

```
                "documentation": "Equal operator"
              },
              {
                "name": "NOT_EQUAL",
                "value": "NotEqual",
                "documentation": "Not equal operator"
              },
              {
                "name": "CONTAINS",
                "value": "Contains",
                "documentation": "Contains operator"
              }
            ],
            "smithy.api#length": {
              "min": 1,
              "max": 20
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
          "type": "string",
          "traits": {
            "smithy.api#enum": [
              {
                "name": "Enabled",
                "value": "Enabled",
                "documentation": "Enabled OrganizationIntegration"
              },
              {
                "name": "Disabled",
                "value": "Disabled",
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
```

```
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/RegisterSubscriptionProvider"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
              "smithy.api#required": {}
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription provider \n\t\t\tresource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>The Linux subscription provider that you registered.</p>"
            }
          },
          "SubscriptionProviderArn": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux subscription provider \n\t\t\tthat you requested.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription provider resource that you registered.</p>"
```

```
            }
        },
        "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
                "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
        },
        "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
            }
        },
        "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
                "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
            }
        },
        "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
            }
        },
        "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed
third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and
license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider,
License Manager can get subscription data from the registered provider.</p>"
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
```

```
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

    }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
                    "value": "Completed",
                    "documentation": "Completed status"
                },
                {
                    "name": "Successful",
                    "value": "Successful",
                    "documentation": "Successful status"
                },
                {
                    "name": "Failed",
                    "value": "Failed",
```

```
                "documentation": "Failed status"
              }
            ]
          }
        },

      "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#length": {
              "min": 1,
              "max": 100
            }
          }
        },
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
          },
          "smithy.api#uniqueItems": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
        "type": "structure",
        "members": {
          "Name":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the subscription.</p>"
            }
          },
          "Type": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
```

with Amazon EC2, Bring Your Own\n Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS. "
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": " The total amount of running instances using this subscription. "
                }
            }
        },
        "traits": {
            "smithy.api#documentation": " An object which details a discovered Linux subscription. "
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }

```
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
    "type": "string",
    "traits": {
      "smithy.api#enum": [
        {
          "name": "ACTIVE",
          "value": "ACTIVE",
          "documentation": "ACTIVE status"
        },
        {
          "name": "INVALID",
          "value": "INVALID",

"documentation": "INVALID status"
        },
        {
          "name": "PENDING",
          "value": "PENDING",
          "documentation": "PENDING status"
        }
      ]
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
    "type": "list",
    "member": {
      "target": "smithy.api#String"
    },
    "traits": {
      "smithy.api#length": {
        "min": 0,
        "max": 50
      },
      "smithy.api#sensitive": {}
    }
  },
  "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
     },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
               "method": "PUT",
               "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
         "type": "structure",
         "members":
 {
            "resourceArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                  "smithy.api#httpLabel": {},
                  "smithy.api#required": {}
               }
            },
            "tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        }
```

```
        ],
        "traits": {
          "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
           "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "tagKeys": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
            "traits": {

           "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
        "type": "operation",
        "input": {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

        },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/UpdateServiceSettings"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
          "type": "structure",
          "members": {
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                "smithy.api#required": {}
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The
settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated
from.</p>",
                "smithy.api#required": {}
              }
            },
            "AllowUpdate": {
              "target":
```

```
 "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                 "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings current status.</p>"
                }

    },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated data for Linux\n      subscriptions.</p>"
                }
            }
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
          "smithy.api#error": "client"
        }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {
```

```
// Unique, case-sensitive identifier that you provide to ensure the idempotency of
//
the request.
//
// This member is required.
ClientToken *string

// Digital signature method. The possible value is JSON Web Signature (JWS)
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string
```

```
// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
```

```
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
```

```
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options);
err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
```

```
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
```

```
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata
```

```
 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
```

```
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
string) *awsmiddleware.RegisterServiceMetadata {
return &awsmiddleware.RegisterServiceMetadata{
```

```
 Region:       region,
 ServiceID:    ServiceID,
 OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
```

```
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err !=
 nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
```

```
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
```

```
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err !=
nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
```

```
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
```

InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,

DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.


```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
\n\t\t\taddresses, and the credential provider for user administration.</p>"
          }
        },
        "ActiveDirectoryType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
          "traits": {
            "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active
Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity
```

```
provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
            "DomainName": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
                }
            },
            "DomainIpv4List": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
                "traits": {
                    "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active
Directory.</p>",
                    "smithy.api#length": {
                        "min": 1,
                        "max": 2
                    }
                }
            },
            "DomainCredentialsProvider": {
                "target":
 "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that
contains \n\t\t\tinformation about the credential provider for user administration.</p>"
                }
            },
            "DomainNetworkSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
        "type": "string",
        "traits": {
```

```
            "smithy.api#enum": [
               {
                  "name": "SELF_MANAGED",
                  "value": "SELF_MANAGED",
                  "documentation": "SELF_MANAGED type of Active Directory"
               },
               {
                  "name": "AWS_MANAGED",
                  "value": "AWS_MANAGED",
                  "documentation": "AWS_MANAGED type of Active Directory"
               }
            ]
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Arn": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n         <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n         </note>",
            "smithy.api#http":
 {
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
      },
      "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
           }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
          "smithy.api#error": "server"
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },

      {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/license-server/CreateLicenseServerEndpoint"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
      "type": "structure",
      "members": {
        "IdentityProviderArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
              "smithy.api#required": {}
            }
          },
          "LicenseServerSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
            }
          },
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
            }
          }
        },
        "traits": {
```

```
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
        "type": "union",
        "members": {
            "SecretsManagerCredentialsProvider":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
                "traits": {
                    "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
         },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

 }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/DeleteLicenseServerEndpoint"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
              "smithy.api#required": {}
            }
          },
           "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
            "traits": {
              "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
            }
          }
        },
```

```
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/DeregisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
```

```
{
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}

    }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
         },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/DisassociateUser"
        },
        "smithy.api#idempotent": {}
```

```
    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
      "type": "structure",
      "members": {
        "Username": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
          }
        },
        "InstanceId": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
          }
        },
        "IdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
          "traits": {
            "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
          }
        },
        "InstanceUserArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
          }
        },
        "Domain": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to disassociate.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
      "type": "structure",
      "members": {
```

```
        "InstanceUserSummary":
{
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
              "smithy.api#length": {
                "min": 1
              },

    "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Attribute": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
            }
          },
```

```
            "Value": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>Value of the filter.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
         "type": "union",
         "members": {
            "ActiveDirectoryIdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
         "type": "structure",
         "members": {
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                  "smithy.api#required": {}
               }
            },
            "Settings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC endpoints.</p>",
                "smithy.api#required": {}
            }
        },
        "Product": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                "smithy.api#required": {}
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                "smithy.api#required": {}
            }
        },
        "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
            }
        },
        "FailureMessage": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Describes an identity provider.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
    "type": "list",
    "member": {

      "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
    "type": "structure",
```

```
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                    "smithy.api#required": {}
                }
            },
            "Products": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
                 "traits": {
                    "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                    "smithy.api#required": {}
                }
            },
            "LastStatusCheckDate": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The date of the last status check.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
```

```
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },

     "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
user.</p>"
             }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
        },
        "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
        },
        "DisassociationDate": {
            "target": "smithy.api#String",
             "traits": {
                "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
         "smithy.api#error": "server",
        "smithy.api#httpError": 500
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IpV4": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
      }
    },
```

```
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",

       "x-api-key",
            "authorization",
            "x-amz-date",
            "x-amz-security-token",
            "Access-Control-Allow-Headers",
            "Access-Control-Allow-Methods",
            "Access-Control-Allow-Origin"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
```

```
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
            "Region":
{
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
              "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
```

```
        }
      ],
      "rules": [
        {
          "conditions": [
            {
              "fn": "booleanEquals",
              "argv": [
                {
                  "ref": "UseFIPS"
                },
                true
              ]
            }
          ],
          "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
          "type": "error"
        },
        {
          "conditions": [
            {

              "fn": "booleanEquals",
              "argv": [
                {
                  "ref": "UseDualStack"
                },
                true
              ]
            }
          ],
          "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
          "type": "error"
        },
        {
          "conditions": [],
          "endpoint": {
            "url": {
              "ref": "Endpoint"
            },

"properties": {},
            "headers": {}
          },
          "type": "endpoint"
        }
      ],
      "type": "tree"
```

```
    },
    {
      "conditions": [
        {
          "fn": "isSet",
          "argv": [
            {
              "ref": "Region"
            }
          ]
        }
      ],
      "rules": [
        {
          "conditions": [
            {
              "fn": "aws.partition",

              "argv": [
                {
                  "ref": "Region"
                }
              ],
              "assign": "PartitionResult"
            }
          ],
          "rules": [
            {
              "conditions": [
                {
                  "fn": "booleanEquals",
                  "argv": [
                    {
                      "ref": "UseFIPS"
                    },
```

true

```
                    ]
                  },
                  {
                    "fn": "booleanEquals",
                    "argv": [
                      {
                        "ref": "UseDualStack"
                      },
                      true
                    ]
                  }
```

```
                ],
                "rules": [
                  {
                    "conditions": [
                      {

 "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"
                              },
                              "supportsFIPS"
                            ]
                          }
                        ]
                      },

                    {
                        "fn": "booleanEquals",
                        "argv": [
                          true,
                          {
                            "fn": "getAttr",
                            "argv": [
                              {
                                "ref": "PartitionResult"
                              },
                              "supportsDualStack"
                            ]
                          }

                ]
                      }
                    ],
                    "rules": [
                      {
                        "conditions": [],
                        "endpoint": {
                          "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                          "properties": {},
                          "headers": {}
                        },
                        "type": "endpoint"
```

```
                }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [

 {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
                                "argv": [

    {
                                        "ref": "PartitionResult"
                                    },
                                    "supportsFIPS"
                                ]
                            },
                            true
                        ]
                    }
                ],
                "rules": [
```

```
                                    {
                                      "conditions": [],
                                      "endpoint": {

                "url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                      },
                                      "type": "endpoint"
                                    }
                                  ],
                                  "type": "tree"
                                },
                                {
                                  "conditions": [],
                                  "error": "FIPS is enabled but this partition does not support FIPS",
                                  "type": "error"

}
                              ],
                              "type": "tree"
                            },
                            {
                              "conditions": [
                                {
                                  "fn": "booleanEquals",
                                  "argv": [
                                    {
                                      "ref": "UseDualStack"
                                    },
                                    true
                                  ]
                                }
                              ],
                              "rules": [
                                {

        "conditions": [
                                    {
                                      "fn": "booleanEquals",
                                      "argv": [
                                        true,
                                        {
                                          "fn": "getAttr",
                                          "argv": [
                                            {
                                              "ref": "PartitionResult"
                                            },
```

```
                                    "supportsDualStack"
                                ]

        }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                    "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }

                    ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
                        "type": "error"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "endpoint": {
                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",

                "properties": {},
                    "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
    },
    {
```

```
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
              }
            ]
          },
          "smithy.rules#endpointTests": {
            "testCases": [
              {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
                "expect":
{
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                  }
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                  }
                },
                "params": {
                  "Region": "us-east-1",

      "UseFIPS": true,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                  }
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
```

```
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS":
true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint":
```

```
{
                    "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": false,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
                }
            },
            "params": {
                "Region": "cn-north-1",
                "UseFIPS": false,
                 "UseDualStack": false
            }
        },
        {
            "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint":
{
                    "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
                }
            },
            "params": {
                "Region": "us-gov-east-1",
                "UseFIPS": true,
                "UseDualStack": false
```

```
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
         "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
```

```
                "Region": "us-iso-east-1",
                "UseFIPS": true,
                "UseDualStack": false

        }
            },
            {
              "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
              "expect": {
                "error": "DualStack is enabled but this partition does not support DualStack"
              },
              "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                }

          },
              "params": {
                "Region": "us-iso-east-1",
                "UseFIPS": false,
                "UseDualStack": false
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
              "expect": {
                "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
              },
              "params": {
                "Region": "us-isob-east-1",
                "UseFIPS": true,
                "UseDualStack": true
              }
            },
            {
              "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
              "expect": {
                "endpoint": {
                  "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
```

```
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",

"UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
          "expect": {

           "endpoint": {
                "url": "https://example.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
```

```
        {
          "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }
          },
          "params": {
            "UseFIPS": false,
            "UseDualStack":
false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with fips enabled and dualstack disabled",
          "expect": {
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with fips disabled and dualstack enabled",
          "expect": {
            "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "Missing region",
          "expect": {
            "error": "Invalid Configuration: Missing Region"
          }
        }
      ],
      "version": "1.0"
```

```
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
          "members": {
            "IdentityProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
              }
            },
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>"
              }
```

```
        },
        "ServerEndpoint": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
              "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network \n\t\t\taddress of the RDS license server endpoint.</p>"
          }
        },
        "StatusMessage": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is one.</p>"
          }
        },
        "LicenseServerEndpointId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
          "traits": {
            "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
          }
        },
        "LicenseServerEndpointArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
          "traits":
 {
            "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
          }
        },
        "LicenseServerEndpointProvisioningStatus": {
          "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
          "traits": {
            "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license \n\t\t\tserver endpoint</p>"
          }
        },
        "LicenseServers": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
          "traits": {
            "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
          }
        },

       "CreationTime": {
          "target": "smithy.api#Timestamp",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
              "name": "PROVISIONED",
              "value": "PROVISIONED",
              "documentation": ""
            },
            {
              "name": "DELETING",
              "value": "DELETING",
              "documentation": ""
            },
            {
              "name": "DELETION_FAILED",
              "value": "DELETION_FAILED",
```

```
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
     "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
      "type": "structure",
      "members": {
        "ServerType": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
          "traits": {
            "smithy.api#documentation": "<p>The type of license server.</p>",
            "smithy.api#required": {}
          }
```

```
            },
            "ServerSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
               "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
```

```
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/ListIdentityProviders"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "IdentityProviderSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
         "type": "structure",
         "members": {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n        <li>\n        <p>Product</p>\n        </li>\n
        <li>\n        <p>DirectoryId</p>\n        </li>\n        </ul>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
         "type": "structure",
         "members": {
```

```
        "IdentityProviderSummaries": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

        "traits": {
            "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
            "smithy.api#required": {}
          }
        },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
      "type": "operation",
       "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
```

```
    {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/instance/ListInstances"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "InstanceSummaries"
          }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
        "type": "structure",
        "members":
{
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n              <p>Status</p>\n          </li>\n
        <li>\n              <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/ListLicenseServerEndpoints"
          },

        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "LicenseServerEndpoints"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
             "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n              <p>IdentityProviderArn</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that \n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListProductSubscriptions"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "ProductUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
{
        "type": "structure",
        "members": {
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
             "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n<ul>\n<li>\n<p>Status</p>\n</li>\n<li>\n<p>Username</p>\n</li>\n<li>\n<p>Domain</p>\n</li>\n</ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
```

```
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
"com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
            "smithy.api#http": {
                "method": "GET",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#readonly": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
```

```
    }
      }
    },
    "traits": {
      "smithy.api#input": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
    "type": "structure",
    "members": {
      "Tags": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
        "traits": {
          "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
        }
      }
    },
    "traits": {
      "smithy.api#output": {}
    }
  },
  "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
    "type": "operation",
    "input": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
    },
    "output": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
    },
    "errors": [
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
      },
      {
        "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
      },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance, which
 provides user-based subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
```

```
      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
```

```
user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a product for this user.</p>",
                    "smithy.api#required": {}
                }
            },
            "ProductUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {

            "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
                }
            },
            "SubscriptionStartDate": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The start date of a subscription.</p>"
              }
            },
            "SubscriptionEndDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The end date of a subscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
user.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
          "type":
 "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
          "type": "structure",
          "members": {
            "RdsSalCredentialsProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
              "traits": {
                "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
 {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
          },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/RegisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
 {
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
 "<p>Metadata that describes the results of an identity provider operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

     "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
        "type": "string",
        "traits": {
          "smithy.api#length": {

       "min": 5,
            "max": 200
          },
          "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
        "type": "structure",
        "members": {
```

```
            "Endpoint": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
         "type": "union",
         "members": {
            "RdsSalSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
                "traits": {
                  "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "RDS_SAL",
                  "value": "RDS_SAL",
                  "documentation": ""
               }
            ]
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
         "type": "structure",
         "members": {
            "message": {

   "target": "smithy.api#String"
            }
         },
         "traits": {
```

```
            "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
            "Subnets": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
                "traits": {
                    "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
                    "smithy.api#length": {
                        "min": 1
                    },
                    "smithy.api#required": {}
                }
            },
            "SecurityGroupId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

             "traits": {
                    "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

          },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n        <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/user/StartProductSubscription"
            }

    }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
```

```
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {

 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
                "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/StopProductSubscription"
        }
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
      "type": "structure",
      "members": {
        "Username": {
          "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
            }
          },
          "IdentityProvider": {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
```

```
            }

    }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {

"min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation":
"<p>Adds tags to a resource.</p>",
          "smithy.api#http": {
            "method": "PUT",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
"<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
```

```
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
          "smithy.api#http": {
            "method": "DELETE",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

        }
          },
          "TagKeys": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
            "traits": {
              "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
              "smithy.api#httpQuery": "tagKeys",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
```

```
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {

      "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },
```

```
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
               }
            },
            "UpdateSettings": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
               "traits": {
                  "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n            <li>\n               <p>Subnets which you want to add to provision VPC endpoints.</p>\n            </li>\n
      <li>\n               <p>Subnets which you want to remove the VPC endpoints from.</p>\n            </li>\n
<li>\n               <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n            </li>\n         </ul>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
         "type": "structure",
         "members": {
            "IdentityProviderSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
               "traits": {
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
         "type": "structure",
         "members": {
            "AddSubnets": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
                  "smithy.api#required": {}
```

```
                }
            },
            "RemoveSubnets": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
                    "smithy.api#required": {}
                }
            },
            "SecurityGroupId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
                "traits": {
                    "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)
```

```
// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
```

```
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err !=
 nil {
  return err
 }
```

```
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
```

SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License

Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this
License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,

except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the

same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity

ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt

RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

1.150 aws-sdk-go-v2-service-internal-s3shared 1.19.2

1.150.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition,

"control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and

subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding

those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise,

unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.151 iputils 20240905-r0

1.151.1 Available under license :

arping: GPL-2.0-or-later
clockdiff: BSD-3-Clause
ping: BSD-3-Clause
tracepath: GPL-2.0-or-later

Files containing license texts are available in Documentation directory.
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This

General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price.
Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and
(2) offer you this license which
gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software
patents. We wish to avoid the danger that redistributors of a free
program will individually obtain patent licenses, in effect making the
program proprietary. To prevent this, we have made it clear that any
patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a

notice that there is no warranty (or else, saying that you provide
a warranty) and that users may redistribute the program under
these conditions, and telling the user how to view a copy of this
License. (Exception: if the Program itself is interactive but
does not normally print such an announcement, your work based on
the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If
identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such

an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source
code, even though third parties are not
compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues),

conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any

later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively

convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

  <one line to give the program's name and a brief idea of what it does.>
  Copyright (C) <year> <name of author>

  This program is free software; you can redistribute it and/or modify
  it under the terms of the GNU
General Public License as published by
  the Free Software Foundation; either version 2 of the License, or
  (at your option) any later version.

  This program is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
  GNU General Public License for more details.

  You should have received a copy of the GNU General Public License along
  with this program; if not, write to the Free Software Foundation, Inc.,
  51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

  Gnomovision version 69, Copyright (C) year name of author
  Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
  This is free software, and you are welcome to redistribute
it
  under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

 Yoyodyne, Inc., hereby disclaims all copyright interest in the program
 `Gnomovision' (which makes passes at compilers) written by James Hacker.

 <signature of Ty Coon>, 1 April 1989
 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into

proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
 is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.152 sirupsen-logrus 1.9.3

1.152.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Simon Eskildsen

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF
 OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.153 cjson 1.7.19-r0

1.153.1 Notifications :

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit
(http://www.openssl.org/)
This product includes cryptographic software written by Eric Young (eay@cryptsoft.com).
This product includes software written by Tim Hudson (tjh@cryptsoft.com).

1.153.2 Available under license :

Apache License 2.0
Contributors
==========

Original Author:
- [Dave Gamble](https://github.com/DaveGamble)

Current Maintainer:
- [Max Bruckner](https://github.com/FSMaxB)
- [Alan Wang](https://github.com/Alanscut)

Contributors:
* [Ajay Bhargav](https://github.com/ajaybhargav)
* [AlexanderVasiljev](https://github.com/AlexanderVasiljev)
* [Alper Akcan](https://github.com/alperakcan)
* [Andrew Tang](https://github.com/singku)
* [Andy](https://github.com/mlh0101)
* [Anton Sergeev](https://github.com/anton-sergeev)
* [Benbuck Nason](https://github.com/bnason-nf)
* [Bernt Johan Damslora](https://github.com/bjda)
* [Bob Kocisko](https://github.com/bobkocisko)
* [Christian Schulze](https://github.com/ChristianSch)
* [Casperinous](https://github.com/Casperinous)
* [ChenYuan](https://github.com/zjuchenyuan)
* [Debora Grosse](https://github.com/DeboraG)
* [dieyushi](https://github.com/dieyushi)
* [Dngwn Hung ()](https://github.com/DongwenHuang)
* [Dominik](https://github.com/DL6ER)
* [Donough Liu](https://github.com/ldm0)
*
[Erez Oxman](https://github.com/erez-o)
* Eswar Yaganti
* [Evan Todd](https://github.com/etodd)
* [Fabrice Fontaine](https://github.com/ffontaine)
* Ian Mobley
* Irwan Djadjadi
* [hopper-vul](https://github.com/hopper-vul)
* [HuKeping](https://github.com/HuKeping)
* [IvanVoid](https://github.com/npi3pak)
* [Jakub Wilk](https://github.com/jwilk)
* [Jiri Zouhar](https://github.com/loigu)
* [Jonathan Fether](https://github.com/jfether)
* [Joshua Arulsamy](https://github.com/jarulsamy)
* [Julian Ste](https://github.com/julian-st)
* [Julin Vsquez](https://github.com/juvasquezg)
* [Junbo Zheng](https://github.com/Junbo-Zheng)
* [Kevin Branigan](https://github.com/kbranigan)
* [Kevin Sapper](https://github.com/sappo)
* [Kyle Chisholm](https://github.com/ChisholmKyle)
* [Linus Wallgren](https://github.com/ecksun)
* [Luo Jin](https://github.com/Up-wind)
* [Max](https://github.com/maebex)
* [MaxBrandtner](https://github.com/MaxBrandtner)
* [Mateusz Szafoni](https://github.com/raiden00pl)

*
Mike Pontillo
* [miaoerduo](https://github.com/miaoerduo)
* [mohawk2](https://github.com/mohawk2)
* [Mike Jerris](https://github.com/mjerris)
* [Mike Robinson](https://github.com/mhrobinson)
* [Moorthy](https://github.com/moorthy-bs)
* [myd7349](https://github.com/myd7349)
* [NancyLi1013](https://github.com/NancyLi1013)
* [Orri](https://github.com/sbvoxel)
* Paulo Antonio Alvarez
* [Pawe Malowany](https://github.com/PawelMalowany)
* [Pawel Winogrodzki](https://github.com/PawelWMS)
* [prefetchnta](https://github.com/prefetchnta)
* [Rafael Leal Dias](https://github.com/rafaeldias)
* [Randy](https://github.com/randy408)
* [raiden00pl](https://github.com/raiden00pl)
* [Robin Mallinson](https://github.com/rmallins)
* [Rod Vagg](https://github.com/rvagg)
* [Roland Meertens](https://github.com/rmeertens)
* [Romain Porte](https://github.com/MicroJoe)
* [SANJEEV BA](https://github.com/basanjeev)
* [Sang-Heon Jeon](https://github.com/lntuition)
* [Sayan Bandyopadhyay](https://github.com/saynb)
*
[Simon Sobisch](https://github.com/GitMensch)
* [Simon Ricaldone](https://github.com/simon-p-r)
* [Stoian Ivanov](https://github.com/sdrsdr)
* [SuperH-0630](https://github.com/SuperH-0630)
* [Square789](https://github.com/Square789)
* [Stephan Gatzka](https://github.com/gatzka)
* [Tony Langhammer](https://github.com/BigBrainAFK)
* [Vemake](https://github.com/vemakereporter)
* [vwvw](https://github.com/vwvw)
* [warmsocks](https://github.com/warmsocks)
* [Wei Tan](https://github.com/tan-wei)
* [Weston Schmidt](https://github.com/schmidtw)
* [xiaomianhehe](https://github.com/xiaomianhehe)
* [yangfl](https://github.com/yangfl)
* [yuta-oxo](https://github.com/yuta-oxo)
* [Zach Hindes](https://github.com/zhindes)
* [Zhao Zhixu](https://github.com/zhaozhixu)
* [10km](https://github.com/10km)

And probably more people on [SourceForge](https://sourceforge.net/p/cjson/bugs/search/?q=status%3Aclosed-rejected+or+status%3Aclosed-out-of-date+or+status%3Awont-fix+or+status%3Aclosed-fixed+or+status%3Aclosed&page=0)

Also
thanks to all the people who reported bugs and suggested new features.
Copyright (c) 2009-2017 Dave Gamble and cJSON contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
The MIT License (MIT)

Copyright (c) <year> 2007-14 Mike Karlesky, Mark VanderVoord, Greg Williams

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.154 prometheus-client-model 0.6.2

1.154.1 Available under license :

Data model artifacts for Prometheus.
Copyright 2012-2015 The Prometheus Authors

This product includes software developed at
SoundCloud Ltd. (http://soundcloud.com/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct

or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.155 aws-sdk-go-v2-internal-ini 1.8.3

1.155.1 Available under license :

```
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
```

```
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string

 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string
```

```
 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
 if err != nil {
  return err
 }
```

```
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err !=
 nil {
  return err
 }
 return nil
}
```

```
func newServiceMetadataMiddleware_opCheckoutLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  Signing
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  OperationDeserializer
  AddTimeOffsetMiddleware
  RecordResponseTiming
```

```
  RequestResponseLogger
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
   strategy:
     matrix:
       python-version: [3.9]

   steps:
     - name: Checkout target
       uses: actions/checkout@v2
       with:
         path: sdkbase
         ref: ${{ github.base_ref }}
     - name: Checkout this ref
       uses: actions/checkout@v2
       with:
         path: new-ref
         fetch-depth: 0
     - name: Get Diff
       run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
     - name: Get Target Files
       run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
     - name: Checkout scancode
       uses: actions/checkout@v2
       with:
         repository: nexB/scancode-toolkit
         path: scancode-toolkit
         fetch-depth: 1
     - name: Set up Python ${{ matrix.python-version }}
        uses: actions/setup-python@v2
       with:
         python-version: ${{ matrix.python-version }}
     # ScanCode
     - name: Self-configure scancode
       working-directory: ./scancode-toolkit
       run: ./scancode --help
     - name: Run Scan code on target
       run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
     - name: Run Scan code on pr ref
       run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
```

```
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string
```

```
 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
```

```
 return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
 return err
 }
 if err = addRetry(stack, options); err != nil {
 return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if
 err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err
 != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists the licenses for your account.
```

```
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {

 // License details.
 Licenses []types.License
```

```
 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
```

```
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
 err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil
 {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListLicenses",
 }
}
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP \n\t\t\taddresses, and the credential provider for user administration.</p>"
            }
        },
        "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
                "smithy.api#documentation": "<p>The type of Active Directory  either a self-managed Active Directory or an \n\t\t\tAmazon Web Services Managed Active Directory.</p>"
            }
        }
    },
    "traits": {
        "smithy.api#documentation": "<p>Details about an Active Directory identity provider.</p>"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
    "type": "structure",
    "members": {
        "DomainName": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The domain name for the Active Directory.</p>"
            }
        },
        "DomainIpv4List": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
            "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the Active Directory.</p>",
                "smithy.api#length": {
                    "min": 1,
                    "max": 2
                }
            }
        },
        "DomainCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
                "smithy.api#documentation": "<p>Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration.</p>"
            }
        },
        "DomainNetworkSettings": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
            "traits": {
              "smithy.api#documentation": "<p>The <code>DomainNetworkSettings</code> resource contains an array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains network access and credential details that are needed for \n\t\t\tuser administration in the Active Directory.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
 {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "SELF_MANAGED",
              "value": "SELF_MANAGED",
              "documentation": "SELF_MANAGED type of Active Directory"
            },
            {
              "name": "AWS_MANAGED",
              "value": "AWS_MANAGED",
              "documentation": "AWS_MANAGED type of Active Directory"
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
 {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
          {
```

```
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n          <note>\n            <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n          </note>",
            "smithy.api#http":
{
                "code": 200,
                "method": "POST",
                "uri": "/user/AssociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based subscription.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to associate.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
            }
          }
        },
        "traits": {

      "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
         }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
        "smithy.api#error": "server"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },

       {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
       ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the <code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
```

```
            "IdentityProviderArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider
specified in the request.</p>"
               }
            },
            "LicenseServerEndpointArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code>
resource.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
         "type": "union",
         "members": {
            "SecretsManagerCredentialsProvider":
{
               "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
               "traits": {
                  "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials
needed for \n\t\t\tuser administration in the Active Directory.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user
\n\t\t\tadministration.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
          },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
```

```
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
            "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/DeleteLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
                    "smithy.api#required": {}
                }
            },
             "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
                    "smithy.api#required": {}
                }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
            "traits": {
              "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/DeregisterIdentityProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>"
            }
          },
          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",

            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
```

```
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Directory":
{
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
           {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/DisassociateUser"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest":
{
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
                }
            },
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"

                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
                }
```

```
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains information for the user to disassociate.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
         "type": "structure",
         "members": {
            "InstanceUserSummary": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
               "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
         "type": "structure",
         "members": {
            "Subnets": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
               "traits": {
                  "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory domain.</p>",
                  "smithy.api#length": {
                     "min": 1
                  },
                  "smithy.api#required": {}

         }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
         }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
      "type": "structure",
      "members": {
        "Attribute": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
          }
        },
        "Operation": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
          }
        },
        "Value": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation":
 "<p>Value of the filter.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
      "type": "union",
      "members": {
        "ActiveDirectoryIdentityProvider": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
          "traits": {

            "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
          }
        }
      },
      "traits": {
```

```
            "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
          "type": "structure",
          "members": {
            "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                "smithy.api#required": {}
              }
            },
            "Settings": {

             "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                "smithy.api#required": {}
              }
            },
            "Product": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of the identity provider.</p>",

           "smithy.api#required": {}
              }
            },
            "IdentityProviderArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
              }
            },
            "FailureMessage": {
              "target": "smithy.api#String",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
           }
        },
        "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
          "type": "structure",
          "members": {
            "InstanceId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "Status": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
                "smithy.api#required": {}
              }
            },
            "Products": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
              "traits":
{
                "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
                "smithy.api#required": {}
              }
            },
            "LastStatusCheckDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The date of the last status check.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList": {

 "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
              "smithy.api#required": {}
```

```
            }
          },
          "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance user.</p>"
            }

  },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "AssociationDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
            }
          },
          "DisassociationDate": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
      },
```

```
"com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
   "type": "structure",
   "members": {
      "message": {
         "target": "smithy.api#String"
      }
   },
   "traits": {
      "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
      "smithy.api#error": "server",
       "smithy.api#httpError": 500
   }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
   "type": "string",
   "traits": {
      "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
   }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
   "type": "list",
   "member": {
      "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
   }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
   "type": "service",
   "version": "2018-05-10",
   "operations": [
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"

   },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
      },
      {
         "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
      },
```

```
    {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
    },
    {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
    },
    {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
    },
    {

     "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
    },
    {
      "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
    },
    {
      "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
    },
    {
      "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
    },
    {
      "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
    },
    {
      "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
    },
    {
      "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
    }
  ],
  "traits": {
    "aws.api#service": {
      "sdkId": "License Manager User Subscriptions",
      "arnNamespace": "license-manager-user-subscriptions",
      "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
    },
    "aws.auth#sigv4": {
      "name": "license-manager-user-subscriptions"
    },
    "aws.protocols#restJson1": {},
    "smithy.api#cors": {
      "additionalAllowedHeaders": [
        "*",
```

```
                "content-type",
                "x-amz-content-sha256",
                "x-amz-user-agent",
                "x-amzn-platform-id",
                "x-amzn-trace-id",
                "content-length",
                "x-api-key",

        "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
              ],
              "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
              ]
            },
            "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
            "smithy.api#title": "AWS License Manager User Subscriptions",
            "smithy.rules#endpointRuleSet": {
              "version": "1.0",
              "parameters": {
                "Region": {
                  "builtIn":
 "AWS::Region",
                  "required": false,
                  "documentation": "The AWS region used to dispatch the request.",
                  "type": "String"
                },
                "UseDualStack": {
                  "builtIn": "AWS::UseDualStack",
                  "required": true,
                  "default": false,
                  "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                  "type": "Boolean"
                },
                "UseFIPS": {
                  "builtIn": "AWS::UseFIPS",
                  "required": true,
                  "default": false,
                  "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured
```

endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
"type": "Boolean"
},
"Endpoint": {
"builtIn": "SDK::Endpoint",
"required": false,
"documentation": "Override the endpoint used to send this request",
"type": "String"
}
},
"rules": [
{
"conditions": [
{
"fn": "isSet",
"argv": [
{
"ref": "Endpoint"
}
]
}
],

"rules": [
{
"conditions": [
{
"fn": "booleanEquals",
"argv": [
{
"ref": "UseFIPS"
},
true
]
}
],
"error": "Invalid Configuration: FIPS and custom endpoint are not supported",
"type": "error"
},
{
"conditions": [
{

"fn": "booleanEquals",
"argv": [
{
"ref": "UseDualStack"
},

```
                        true
                    ]
                }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
        },
        {
            "conditions": [],
            "endpoint": {
                "url": {
                    "ref": "Endpoint"
                },
                "properties": {},

            "headers": {}
                },
                "type": "endpoint"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "isSet",
                "argv": [
                    {
                        "ref": "Region"
                    }
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "aws.partition",
                        "argv":
[
                            {
                                "ref": "Region"
                            }
                        ],
                        "assign": "PartitionResult"
                    }
                ],
                "rules": [
```

```
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseFIPS"
                        },
                        true

            ]
                    },
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
                          "ref": "UseDualStack"
                        },
                        true
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",

                    "argv": [
                              true,
                              {
                                "fn": "getAttr",
                                "argv": [
                                  {
                                    "ref": "PartitionResult"
                                  },
                                  "supportsFIPS"
                                ]
                              }
                            ]
                          },

{
                          "fn": "booleanEquals",
                          "argv": [
                            true,
                            {
                              "fn": "getAttr",
```

```
                                    "argv": [
                                        {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]

                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "endpoint": {
                                "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                "properties": {},
                                "headers": {}
                            },
                            "type": "endpoint"
                        }
                    ],

            "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                    "type": "error"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {

        "ref": "UseFIPS"
                        },
                        true
                    ]
                }
            ],
```

```
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {

                                                "ref": "PartitionResult"
                                            },
                                            "supportsFIPS"
                                        ]
                                    },
                                    true
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "endpoint": {
                                    "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",
                                     "properties": {},
                                    "headers": {}
                                },
                                "type": "endpoint"
                            }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "FIPS is enabled but this partition does not support FIPS",
                        "type": "error"
                    }

        ],
                "type": "tree"
            },
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
```

```
                {
                  "ref": "UseDualStack"
                },
                true
              ]
            }
          ],
          "rules": [
            {
              "conditions": [

           {
                  "fn": "booleanEquals",
                  "argv": [
                    true,
                    {
                      "fn": "getAttr",
                      "argv": [
                        {
                          "ref": "PartitionResult"
                        },
                        "supportsDualStack"
                      ]
                    }

        ]
                }
              ],
              "rules": [
                {
                  "conditions": [],
                  "endpoint": {
                    "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                    "properties": {},
                    "headers": {}
                  },
                  "type": "endpoint"
                }
              ],
               "type": "tree"
            },
            {
              "conditions": [],
              "error": "DualStack is enabled but this partition does not support DualStack",
              "type": "error"
            }
          ],
```

```
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],
                "type": "tree"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [],
        "error": "Invalid Configuration: Missing Region",
        "type": "error"
    }
]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint":
{
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
                }
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
                "UseDualStack": true
            }
        },
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
                }
            },
```

```
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,

            "UseDualStack": false
                }
              },
              {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
                  }
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true
                }
              },
              {
                "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
                "expect": {
                  "endpoint": {

  "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
                  }
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": false
                }
              },
              {
                "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
                "expect": {
                  "endpoint": {
                    "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                  }
                },
                "params": {
                  "Region": "cn-north-1",
                  "UseFIPS": true,
                  "UseDualStack":
 true
                }
```

```
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url":
"https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack":
false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
```

```
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url":
"https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack":
true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
```

```
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "error": "FIPS and DualStack are enabled, but this partition
does not support one or both"
                  },
                  "params": {
                    "Region": "us-iso-east-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                    }
                  },
                  "params": {
                    "Region": "us-iso-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },

               {
                  "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "error": "DualStack is enabled but this partition does not support DualStack"
                  },
                  "params": {
                    "Region": "us-iso-east-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
                    }
                  },

        "params": {
                    "Region": "us-iso-east-1",
                    "UseFIPS": false,
```

```
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",

"expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-isob-east-1",
            "UseFIPS": false,

    "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
            }
          },
          "params": {
```

```
            "Region": "us-isob-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
          "expect": {
            "endpoint": {

              "url": "https://example.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
          "expect": {
            "endpoint": {
              "url": "https://example.com"
            }
          },
          "params": {
            "UseFIPS": false,
            "UseDualStack": false,
            "Endpoint":
 "https://example.com"
          }
        },
        {
          "documentation": "For custom endpoint with fips enabled and dualstack disabled",
          "expect": {
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false,
            "Endpoint": "https://example.com"
          }
        },
        {
```

```
                    "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                    "expect": {
                      "error": "Invalid Configuration: Dualstack and custom endpoint are
not supported"
                    },
                    "params": {
                      "Region": "us-east-1",
                      "UseFIPS": false,
                      "UseDualStack": true,
                      "Endpoint": "https://example.com"
                    }
                  },
                  {
                    "documentation": "Missing region",
                    "expect": {
                      "error": "Invalid Configuration: Missing Region"
                    }
                  }
                ],
                "version": "1.0"
              }
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
            "type": "structure",
            "members": {
              "ProvisioningStatus": {
                "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
                 "traits": {
                   "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
                 }
              },
              "HealthStatus": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
                "traits": {
                  "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
                }
              },
              "Ipv4Address": {
                "target": "smithy.api#String",
                "traits": {
                  "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
                }
              }
            },
```

```
        "traits": {
            "smithy.api#documentation": "<p>Information about a Remote Desktop Services (RDS) license
 server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
                }
            },
            "ServerType": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
                "traits": {
                    "smithy.api#documentation": "<p>The type of license server.</p>"
                }
            },
            "ServerEndpoint": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",
                "traits": {
                    "smithy.api#documentation":
 "<p>The <code>ServerEndpoint</code> resource contains the network \n\t\t\taddress of the RDS license server
endpoint.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
                }
            },
            "LicenseServerEndpointId": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
                }
            },
            "LicenseServerEndpointArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation":
 "<p>The ARN of the <code>ServerEndpoint</code> resource for the RDS \n\t\t\tlicense server.</p>"
                }
```

```
            },
            "LicenseServerEndpointProvisioningStatus": {
               "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                  "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
               }
            },
            "LicenseServers": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
               "traits": {
                  "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent
the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
               }
            },
            "CreationTime": {

         "target": "smithy.api#Timestamp",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp when License Manager created the license server
endpoint.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop
Services (RDS) \n\t\t\tlicense server.</p>"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
         "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {
         "type": "string",
         "traits":
 {
            "smithy.api#enum": [
               {
                  "name": "PROVISIONING",
                  "value": "PROVISIONING",
                  "documentation": ""
```

```
            },
            {
               "name": "PROVISIONING_FAILED",
               "value": "PROVISIONING_FAILED",
               "documentation": ""
            },
            {
               "name": "PROVISIONED",
               "value": "PROVISIONED",
               "documentation": ""
            },
            {
               "name": "DELETING",
               "value": "DELETING",
               "documentation": ""
            },
            {
               "name": "DELETION_FAILED",
               "value": "DELETION_FAILED",
               "documentation": ""
            },
            {
                "name": "DELETED",
               "value": "DELETED",
               "documentation": ""
            }
         ]
      }
   },
   "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
         "smithy.api#enum": [
            {
               "name": "HEALTHY",
               "value": "HEALTHY",
               "documentation": ""
            },
            {
               "name": "UNHEALTHY",
               "value": "UNHEALTHY",
               "documentation": ""
            },
            {
               "name": "NOT_APPLICABLE",
               "value": "NOT_APPLICABLE",
               "documentation": ""
            }
```

```
            ]
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList":
{
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
          "type": "structure",
          "members": {
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>",
                "smithy.api#required": {}
              }
            },
            "ServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for your \n\t\t\tserver.</p>",

                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/identity-provider/ListIdentityProviders"
            },

            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "IdentityProviderSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
         "type": "structure",
         "members": {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "Filters": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
```

```
<ul>\n <li>\n <p>Product</p>\n </li>\n <li>\n <p>DirectoryId</p>\n
</li>\n </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",
            "traits": {

          "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that
contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
              "smithy.api#required": {}
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
        "type": "operation",
        "input": {

  "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
        },
        "output": {
```

```
        "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
         },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/instance/ListInstances"
        },
        "smithy.api#paginated": {
          "inputToken": "NextToken",
          "outputToken": "NextToken",
          "pageSize": "MaxResults",
          "items": "InstanceSummaries"
        }
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
      "type": "structure",
      "members": {
        "MaxResults": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
          "traits": {
            "smithy.api#documentation": "<p>The maximum number of results to return from a single
```

```
request.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>Status</p>\n            </li>\n            <li>\n                <p>InstanceId</p>\n
        </li>\n        </ul>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
            "InstanceSummaries": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The next token used for paginated responses. When
 this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token
\n\t\twith the next request to retrieve additional objects.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
```

```
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
             },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/ListLicenseServerEndpoints"
            },
            "smithy.api#paginated": {

            "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "LicenseServerEndpoints"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
              }
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits":
 {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>IdentityProviderArn</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoints": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
             "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
```

```
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
        "type": "operation",
        "input": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
             "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/ListProductSubscriptions"
          },
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
```

```
            "pageSize": "MaxResults",
            "items": "ProductUserSummaries"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest": {
        "type":
 "structure",
        "members": {
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>"
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {

              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n
</li>\n          <li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
```

```
        }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to
 retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
```

```
        }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#readonly": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}
            }
          }
        },
        "traits": {

    "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
```

```
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits":
{
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "InstanceUserSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
        "type": "structure",
        "members": {
            "InstanceId": {
                "target": "smithy.api#String",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required":
 {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline
 results:</p>\n        <ul>\n        <li>\n        <p>Status</p>\n        </li>\n        <li>\n
<p>Username</p>\n        </li>\n        <li>\n        <p>Domain</p>\n        </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
             "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
```

```
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",

            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
```

```
            },
            "ProductUserArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
              }
            },
            "StatusMessage": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
              }
            },
            "Domain": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The domain name of the  Active Directory
 that contains the user information for the product subscription.</p>"
              }
            },
            "SubscriptionStartDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The start date of a subscription.</p>"
              }
            },
            "SubscriptionEndDate": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The end date of a subscription.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific
 user.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
          "type": "list",
          "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
          "type": "structure",
          "members": {
            "RdsSalCredentialsProvider": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a
reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider": {
        "type":
 "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
          "smithy.api#http": {
```

```
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                 "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>",
                    "smithy.api#required": {}
                }
            },
            "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The registered identity providers product related configuration
 \n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
```

```
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider
operation.</p>",

       "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The resource couldn't be found.</p>",
          "smithy.api#error": "client",
          "smithy.api#httpError": 404
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider":
 {
        "type": "structure",
        "members": {
          "SecretId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
              "smithy.api#length": {
                "min": 1
              }
            }
```

```
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
          "type": "string",
          "traits": {
            "smithy.api#length": {
              "min": 5,
              "max": 200
            },
            "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
          "type": "structure",
          "members": {
            "Endpoint": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
          "type": "union",
          "members": {
            "RdsSalSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource
 contains settings to configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
          "type": "string",
```

```
        "traits": {
          "smithy.api#enum": [
            {
              "name": "RDS_SAL",
              "value": "RDS_SAL",
              "documentation": ""
            }
          ]
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request failed because a service quota is exceeded.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Settings": {
        "type": "structure",
        "members": {
          "Subnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
              "smithy.api#length": {
                "min": 1
              },
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
            "traits": {
              "smithy.api#documentation": "<p>A security group ID that allows inbound
 TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation
servers.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The registered identity providers product related configuration settings
```

such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC. "
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": " Starts a product subscription for a user with the specified identity provider. \n <note>\n Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as Pending billing status) in Amazon Web Services Billing. For more information, see Viewing your\n\t\t\t\tmonthly charges in the Amazon Web Services Billing User Guide. \n </note>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/StartProductSubscription"
          }

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
        "type":
 "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code>
 | <code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse":
{
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },

 "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
```

```
        ],

    "traits": {
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StopProductSubscription"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An
 object that specifies details for the identity provider.</p>"
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>"
               }
            },
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"
               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The
```

```
domain name of the  Active Directory that contains the user for whom to stop the product \n\t\t\tsubscription.</p>"
                }
              }
            },
            "traits": {
              "smithy.api#input": {}
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
            "type": "structure",
            "members": {
              "ProductUserSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
                "traits": {
                  "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
                  "smithy.api#required": {}
                }
              }
            },
            "traits": {
              "smithy.api#output": {}
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#StringList": {
            "type": "list",
             "member": {
              "target": "smithy.api#String"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
            "type": "string",
            "traits": {
              "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
            "type": "list",
            "member": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
            }
          },
          "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
            "type": "list",
            "member": {
              "target": "smithy.api#String"
            },
            "traits": {
```

```
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {

    "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Adds tags to a resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{ResourceArn}"
            },

    "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
```

```
            },
            "Tags": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The tags to apply to the specified resource.</p>",
                  "smithy.api#required": {}
               }
            }
         },
         "traits":
{
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
         "type": "structure",
         "members": {},
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
         "type": "map",
         "key": {
            "target": "smithy.api#String"
         },
         "value": {
            "target": "smithy.api#String"
         },
         "traits": {
            "smithy.api#length": {
               "min": 0,
               "max": 50
            },
            "smithy.api#sensitive": {}
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }

       },
         "traits": {
            "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
```

```
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Removes
 tags from a resource.</p>",
            "smithy.api#http": {
              "method": "DELETE",
              "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
          "type": "structure",
          "members": {
            "ResourceArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
 to remove tags from.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}
              }
            },
            "TagKeys": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
              "traits": {

   "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
                "smithy.api#httpQuery": "tagKeys",
                "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },

 "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/identity-provider/UpdateIdentityProviderSettings"
          },
          "smithy.api#idempotent": {}
```

```
    }
   },
   "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
     "type": "structure",
     "members": {
       "IdentityProvider": {
         "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
       },
       "Product": {
         "target": "smithy.api#String",
         "traits": {
           "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code>\n
</p>"
         }
       },
       "IdentityProviderArn": {
         "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
         "traits": {
           "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the
 identity provider to update.</p>"
         }
       },
       "UpdateSettings": {
         "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
         "traits": {
           "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
     <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
           "smithy.api#required": {}
         }
       }
     },
     "traits": {

  "smithy.api#input": {}
     }
   },
   "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
     "type": "structure",
     "members": {
       "IdentityProviderSummary": {
         "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
         "traits": {
           "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
        "type": "structure",
        "members": {
          "AddSubnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint
 for products that\n\t\t\trequire connectivity to activation servers.</p>",
              "smithy.api#required": {}
            }
          },
          "RemoveSubnets": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
            "traits": {
              "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
              "smithy.api#required": {}
            }
          },
          "SecurityGroupId": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
            "traits": {
              "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688
communication between resources in\n\t\t\tyour VPC and the VPC endpoints for activation servers.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>Updates the registered identity providers product related configuration settings such as\n\t\t\tthe subnets to
provision VPC endpoints.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>A parameter is not valid.</p>",
            "smithy.api#error": "client"
          }
        }
      }
    }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
```

This member is required.
ClientToken *string

// Configuration for consumption of the license. Choose a provisional
// configuration for workloads running with continuous connectivity. Choose a
// borrow configuration for workloads with offline usage.
//
// This member is required.
ConsumptionConfiguration *types.ConsumptionConfiguration

// License entitlements.
//
// This member is required.
Entitlements []types.Entitlement

// Home Region for the license.
//
// This member is required.
HomeRegion *string

// License issuer.
//
// This member is required.
Issuer *types.Issuer

// License name.
//
// This member is required.
LicenseName *string

// Product name.
//
// This member is required.
ProductName *string

// Product SKU.
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

```
 noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License status.
 Status types.LicenseStatus

 // License version.
 Version *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if
 err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
```

```
 return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
 return err
 }
 if err = addRetry(stack, options); err != nil {
 return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err
 = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
```

```
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack);
 err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
```

```
 OperationSerializer
Build stack step
 ClientRequestID
 ComputeContentLength
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 Retry
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 Signing
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 OperationDeserializer
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }
```

```
if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if
err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
```

```
 }
 if
 err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
 {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckInLicense",
 }
}
```

```
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  Signing
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  OperationDeserializer
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
```

```
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}
```

```
func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err
 != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
```

```
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
```

```
 return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata
 {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
  params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {
```

```
// Unique, case-sensitive identifier that you provide to ensure the idempotency of
//
the request.
//
// This member is required.
ClientToken *string

// Digital signature method. The possible value is JSON Web Signature (JWS)
// algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
//
// [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
//
// This member is required.
DigitalSignatureMethod types.DigitalSignatureMethod

// License entitlements. Partial checkouts are not supported.
//
// This member is required.
Entitlements []types.EntitlementData

// Amazon Resource Name (ARN) of the license. The license must use the borrow
// consumption configuration.
//
// This member is required.
LicenseArn *string

// Information about constraints.
CheckoutMetadata []types.Metadata

// Node ID.
NodeId *string

noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

// Information about constraints.
CheckoutMetadata []types.Metadata

// Allowed license entitlements.
EntitlementsAllowed
[]types.EntitlementData

// Date and time at which the license checkout expires.
Expiration *string
```

```
// Date and time at which the license checkout is issued.
IssuedAt *string

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License consumption token.
LicenseConsumptionToken *string

// Node ID.
NodeId *string

// Signed token.
SignedToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
 err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
```

```
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
 err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
```

```
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
GetLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
```

setOperationInput
ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
ListReceivedLicenses
Initialize stack step
spanInitializeStart
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
UserAgent
AddTimeOffsetMiddleware

```
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 Retry
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 Signing
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 OperationDeserializer
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
AWS SDK for Go
Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
```

```
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
```

```
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
```

```
 != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region string) *awsmiddleware.RegisterServiceMetadata {
```

```
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
  }
 }
AssociateLicense
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  Retry
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  Signing
 Deserialize stack step
  AddRawResponseToMetadata
  ErrorCloseResponseBody
  CloseResponseBody
  ResponseErrorWrapper
  RequestIDRetriever
  OperationDeserializer
  AddTimeOffsetMiddleware
  RecordResponseTiming
  RequestResponseLogger
```

```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/DeregisterSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
```

```
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Name": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of name to filter by.</p>"
                }
            },
            "Values": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
                }
            },
            "Operator": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
                "traits": {
                    "smithy.api#documentation": "<p>An operator for filtering results.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
        "type":
```

```
"list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
        },
        "output": {
          "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
           },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/GetRegisteredSubscriptionProvider"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation":
 "<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
              "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

         "traits": {
              "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
             }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/GetServiceSettings"

          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
        "type": "structure",
        "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
        "type": "structure",
        "members": {
```

```
            "LinuxSubscriptionsDiscovery": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
              "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
              }
            },
            "LinuxSubscriptionsDiscoverySettings": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
              "traits": {
                "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
              }
            },
            "Status": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
              "traits": {
                "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
              }
            },
            "StatusMessage": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
              "traits": {
                "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
              }
            },
            "HomeRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
          "type": "structure",
          "members": {
            "AmiId": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
              }
            },
            "InstanceID": {
              "target": "smithy.api#String",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
            }
        },
        "InstanceType": {
            "target": "smithy.api#String",
            "traits":
{
                "smithy.api#documentation": "<p>The instance type of the resource.</p>"
            }
        },
        "AccountID": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
            }
        },
        "Status": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The status of the instance.</p>"
            }
        },
        "Region": {
            "target": "smithy.api#String",
            "traits": {
                "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
            }
        },
        "UsageOperation": {
            "target": "smithy.api#String",

   "traits": {
                "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
            }
        },
        "ProductCode": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
            "traits": {
                "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
            }
        },
        "LastUpdatedTime": {
```

```
            "target": "smithy.api#String",
             "traits": {
               "smithy.api#documentation": "<p>The time in which the last discovery updated the instance
details.</p>"
            }
          },
          "SubscriptionName": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
            }
          },
          "OsVersion": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The operating system software version that runs on your
instance.</p>"
            }
          },
          "SubscriptionProviderCreateTime": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
            }
          },
          "SubscriptionProviderUpdateTime": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the
registered \n\t\t\tthird-party Linux subscription provider.</p>"
            }
          },
          "DualSubscription": {
            "target": "smithy.api#String",
            "traits": {
               "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for
\n\t\t\tthe same software on your instance.</p>"
            }
          },
          "RegisteredWithSubscriptionProvider": {
            "target": "smithy.api#String",
            "traits": {

     "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta
third-party Linux subscription provider that you've registered with License Manager.</p>"
            }
          }
```

```
        },
        "traits": {
            "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
            "smithy.api#error": "server"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
             },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
          }
        ],
        "traits": {
          "aws.api#service": {
            "sdkId": "License Manager Linux Subscriptions",
             "arnNamespace": "license-manager-linux-subscriptions",
            "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
          },
          "aws.auth#sigv4": {
            "name": "license-manager-linux-subscriptions"
          },
          "aws.protocols#restJson1": {},
          "smithy.api#cors": {
            "additionalAllowedHeaders": [
              "*",
              "content-type",
              "x-amz-content-sha256",
              "x-amz-user-agent",
              "x-amzn-platform-id",
              "x-amzn-trace-id"
            ],
            "additionalExposedHeaders": [
              "x-amzn-errortype",
              "x-amzn-requestid",
              "x-amzn-trace-id"
            ]
          },
          "smithy.api#documentation": "<p>With License Manager,
you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
          "smithy.api#title": "AWS License Manager Linux Subscriptions",
          "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
              "Region": {
                "builtIn": "AWS::Region",
```

```
            "required": false,
            "documentation": "The AWS region used to dispatch the request.",
            "type": "String"
        },
        "UseDualStack": {
            "builtIn": "AWS::UseDualStack",
            "required": true,
            "default": false,
            "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
            "type": "Boolean"
        },
        "UseFIPS": {
            "builtIn": "AWS::UseFIPS",
            "required": true,
            "default": false,
            "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
            "type": "Boolean"
        },
        "Endpoint": {
            "builtIn": "SDK::Endpoint",
            "required": false,
            "documentation": "Override the endpoint used to send this request",
            "type": "String"
        }
    },
    "rules": [
        {
            "conditions": [
                {
                    "fn": "isSet",
                    "argv": [
                        {
                            "ref": "Endpoint"
                        }
                    ]
                }
            ],
            "rules": [
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseFIPS"
                                },
```

```
                        true
                    ]
                }

        ],
                "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                "type": "error"
            },
            {
                "conditions": [],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    {
                                        "ref": "UseDualStack"
                                    },
                                    true
                                ]

}
                        ],
                        "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                        "type": "error"
                    },
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": {
                                "ref": "Endpoint"
                            },
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }
                ],
                "type": "tree"

            }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "rules": [
```

```
  {
    "conditions": [
      {
        "fn": "isSet",
        "argv": [
          {
            "ref": "Region"
          }
        ]
      }
    ],
    "rules": [
      {
        "conditions": [
          {

"fn": "aws.partition",
            "argv": [
              {
                "ref": "Region"
              }
            ],
            "assign": "PartitionResult"
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {

                "ref": "UseFIPS"
                  },
                  true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
```

```
],
                                    "rules": [
                                      {
                                        "conditions": [
                                          {
                                            "fn": "booleanEquals",
                                            "argv": [
                                              true,
                                              {
                                                "fn": "getAttr",
                                                "argv": [
                                                  {
                                                    "ref": "PartitionResult"

                                },
                                                    "supportsFIPS"
                                                  ]
                                                }
                                              ]
                                            },
                                            {
                                              "fn": "booleanEquals",
                                              "argv": [
                                                true,
                                                {
                                                  "fn": "getAttr",
                                                  "argv": [

                                                   {
                                                      "ref": "PartitionResult"
                                                    },
                                                    "supportsDualStack"
                                                  ]
                                                }
                                              ]
                                            }
                                          ],
                                          "rules": [
                                            {
                                              "conditions": [],

        "rules": [
                                                {
                                                  "conditions": [],
                                                  "endpoint": {
                                                    "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                    "properties": {},
```

```
                "headers": {}
              },
              "type": "endpoint"
            }
          ],

      "type": "tree"
        }
      ],
      "type": "tree"
    },
    {
      "conditions": [],
      "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
      "type": "error"
    }
  ],
  "type": "tree"
},
{

  "conditions": [
    {
      "fn": "booleanEquals",
      "argv": [
        {
          "ref": "UseFIPS"
        },
        true
      ]
    }
  ],
  "rules": [
    {
      "conditions": [
        {

    "fn": "booleanEquals",
          "argv": [
            {
              "fn": "getAttr",
              "argv": [
                {
                  "ref": "PartitionResult"
                },
                "supportsFIPS"
              ]
```

```
                                        },
                                        true

                                    ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [],
                                    "rules": [
                                        {
                                            "conditions": [],
                                            "endpoint": {
                                                "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],
                                    "type": "tree"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "error": "FIPS is enabled
but this partition does not support FIPS",
                            "type": "error"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                {
                                    "ref": "UseDualStack"
                                },
                                true

                ]
                            }
```

```
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {

                                            "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "rules": [

        {
                                        "conditions": [],
                                        "endpoint": {
                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"

                    }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
                        "type": "error"
                    }
```

```
                                ],
                                "type": "tree"
                            },
                            {
                                "conditions": [],
                                "rules": [
                                    {
                                        "conditions": [],
                                        "endpoint": {
                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"
                            }
                        ],
                        "type": "tree"
                    }
                ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "Invalid Configuration: Missing Region",
                "type": "error"
            }
        ],
        "type": "tree"
    }
]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
            },
            "params": {
                "Region": "us-east-1",
                "UseFIPS": true,
```

```
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {

      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
```

```
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {

 "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
              }
             },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
              }
            },
            "params": {
              "Region": "cn-north-1",
              "UseFIPS": false,
              "UseDualStack": false
```

```
      }
    },
    {

  "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
        }

     },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-gov-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
```

```
                "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
              }
            },
            "params": {
              "Region": "us-gov-east-1",
              "UseFIPS": false,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
              "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
            },
            "params": {

        "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
            "expect": {
              "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
              }
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": true,
              "UseDualStack": false
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
            "expect": {
              "error": "DualStack is enabled but this partition does not support DualStack"
            },
            "params": {
              "Region": "us-iso-east-1",
              "UseFIPS": false,
              "UseDualStack": true
            }
          },
          {
            "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
```

```
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
         }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
```

```
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {

      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
```

```
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled LinuxSubscriptionsDiscovery"

       },
            {
              "name": "Disabled",
              "value": "Disabled",
              "documentation": "Disabled LinuxSubscriptionsDiscovery"
            }
          ]
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
      "type": "structure",
      "members": {
        "SourceRegions": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
          "traits": {
            "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
            "smithy.api#required": {}
          }
        },
        "OrganizationIntegration": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
          "traits": {
            "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },

  {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with
commercial Linux\n      subscriptions.</p>",
```

```
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "Instances"
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest":
{
         "type": "structure",
         "members": {
            "Filters": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
               "traits": {
                  "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your
specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the
\n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n
\t<code>Value</code>, such as <code>us-west</code>.</p>\n         <p>For each filter, you can specify one of the
following values for the <code>Name</code> key \n    \tto streamline results:</p>\n         <ul>\n            <li>\n
   <p>\n                  <code>AccountID</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
      <code>AmiID</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>DualSubscription</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>InstanceID</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>InstanceType</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>ProductCode</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>Region</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>Status</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>UsageOperation</code>\n               </p>\n            </li>\n         </ul>\n         <p>For each filter, you can use
one of the following <code>Operator</code>
 values to \n  \t\tdefine the behavior of the filter:</p>\n         <ul>\n            <li>\n               <p>\n
<code>contains</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>equals</code>\n               </p>\n            </li>\n            <li>\n               <p>\n
<code>Notequal</code>\n               </p>\n            </li>\n         </ul>"
               }
            },
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
               }
            },
```

```
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
                  "smithy.api#length": {
                     "min": 1,
                     "max": 16384
                  }
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
         "type": "structure",
         "members": {
            "Instances": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
               "traits": {
                  "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
               }
            },
            "NextToken": {

          "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
         "type": "operation",
         "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
```

```
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/ListLinuxSubscriptions"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",

    "items": "Subscriptions"
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
          "type": "structure",
          "members": {
            "Filters": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n       <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n          <p>The valid names for this filter are:</p>\n          <ul>\n <li>\n              <p>\n                  <code>Subscription</code>\n              </p>\n          </li>\n          </ul>\n <p>The
       valid Operators for this filter are:</p>\n          <ul>\n          <li>\n              <p>\n <code>contains</code>\n              </p>\n          </li>\n          <li>\n              <p>\n <code>equals</code>\n              </p>\n          </li>\n          <li>\n              <p>\n <code>Notequal</code>\n              </p>\n          </li>\n          </ul>"
              }
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
          "type": "structure",
          "members": {
            "Subscriptions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
               "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
          },
          "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListRegisteredSubscriptionProviders"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "RegisteredSubscriptionProviders"
          }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
          "SubscriptionProviderSources": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
            "traits": {
              "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
```

```
                }
            }

  },
        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
      "type": "structure",
      "members": {
        "RegisteredSubscriptionProviders": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
          "traits": {
            "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
          }
        },

        "NextToken": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
      },
```

```
      "errors": [
        {

    "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon Web Services resource.</p>",
        "smithy.api#http": {
          "method": "GET",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#readonly": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
           "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to list metadata tags.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
      "type": "structure",
      "members": {
        "tags": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
          "traits": {
            "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
          }
        }
```

```
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "EQUAL",
                    "value": "Equal",
                    "documentation": "Equal operator"
                },
                {
                    "name": "NOT_EQUAL",
                    "value": "NotEqual",
                    "documentation": "Not equal operator"
                },
                {
                    "name": "CONTAINS",
                    "value": "Contains",
                    "documentation": "Contains operator"
                }
            ],
            "smithy.api#length": {
                "min": 1,
                "max": 20
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "Enabled",
                    "value": "Enabled",
                    "documentation": "Enabled OrganizationIntegration"
                },
                {
                    "name": "Disabled",
                    "value": "Disabled",
                    "documentation": "Disabled OrganizationIntegration"
                }
            ]
        }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
       },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/RegisterSubscriptionProvider"

         },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderSource": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
          "traits": {
            "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
            "smithy.api#required": {}
          }
        },
```

```
            "SecretArn": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
                  "smithy.api#required": {}
               }
            },
            "Tags": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
               "traits": {
                  "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#input": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
         "type": "structure",
         "members": {
            "SubscriptionProviderSource": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
               "traits": {
                  "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
               }
            },
            "SubscriptionProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
               }
            },
            "SubscriptionProviderStatus": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
               "traits": {
                  "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
            }
          },
          "SubscriptionProviderSource": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
            "traits": {
              "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
            }
          },
          "SecretArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
             "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
            }
          },
          "SubscriptionProviderStatus": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
            }
          },
          "SubscriptionProviderStatusMessage": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
            }
          },
          "LastSuccessfulDataRetrievalTime": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed
```

```
third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and
license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider,
License Manager can get subscription data from the registered provider.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-
\\.]{0,63}:secret:[^/]{1,1023}$"

  }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "InProgress",
                    "value": "InProgress",
                    "documentation": "InProgress status"
                },
                {
                    "name": "Completed",
```

```
                "value": "Completed",
                "documentation": "Completed status"
            },
            {
                "name": "Successful",
                "value": "Successful",
                "documentation": "Successful status"
            },
            {
                "name": "Failed",
                "value": "Failed",
                "documentation": "Failed status"
            }
        ]
    }
},

"com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
    "type": "list",
    "member": {
        "target": "smithy.api#String",
        "traits": {
            "smithy.api#length": {
                "min": 1,
                "max": 100
            }
        }
    },
    "traits": {
        "smithy.api#length": {
            "min": 1,
            "max": 100
        },
        "smithy.api#uniqueItems": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
    "type": "map",
    "key": {
        "target": "smithy.api#String"
    },
    "value": {
        "target": "smithy.api#String"
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
    "type": "structure",
    "members": {
```

```
            "Name":
{
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the subscription.</p>"
                }
            },
            "Type": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included
with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services
Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as
OS licensing from Amazon EC2 or BYOS.</p>"
                }
            },
            "InstanceCount": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
                "traits": {
                    "smithy.api#documentation": "<p>The total amount of running instances using this
subscription.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-
9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [

 {
                    "name": "RedHat",
```

```
                "value": "RedHat",
                "documentation": "RedHat subscription provider namespace"
            }
          ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
                },
                {
                    "name": "INVALID",
                    "value": "INVALID",

"documentation": "INVALID status"
                },
                {
                    "name": "PENDING",
                    "value": "PENDING",
                    "documentation": "PENDING status"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
        "smithy.api#http": {
          "method": "PUT",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
      "type": "structure",
      "members":
{
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        },
        "tags": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
          "traits": {
            "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource.
Tags are \n\t\t\tformatted as key value pairs.</p>",
            "smithy.api#required": {}
```

```
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }

      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
"<p>The request was denied due to request throttling.</p>",
          "smithy.api#error": "client"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
```

```
        },
        "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
             "smithy.api#http": {
                "method": "DELETE",
                "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
        "type": "structure",
        "members": {
            "resourceArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "tagKeys": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
                "traits": {

              "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
                    "smithy.api#httpQuery": "tagKeys",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
```

```
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
   "type": "structure",
   "members": {},
   "traits": {
      "smithy.api#output": {}
   }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
   "type": "operation",
   "input": {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
   },
   "output": {
      "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

 },
   "errors": [
      {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
      },
      {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
      },
      {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
      }
   ],
   "traits": {
      "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
      "smithy.api#http": {
         "code": 200,
         "method": "POST",
         "uri": "/subscription/UpdateServiceSettings"
      },
      "smithy.api#idempotent": {}
   }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
   "type": "structure",
   "members": {
       "LinuxSubscriptionsDiscovery": {
         "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
         "traits": {
            "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
            "smithy.api#required": {}
         }
      },
```

```
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>",
                    "smithy.api#required": {}
                }
            },
            "AllowUpdate": {
                "target": "smithy.api#Boolean",
                "traits": {
                    "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
        "type": "structure",
        "members": {
            "LinuxSubscriptionsDiscovery": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
                "traits": {
                    "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
                }
            },
            "LinuxSubscriptionsDiscoverySettings": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
                "traits": {
                    "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
                }
            },
            "Status": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
                }
            },
            "StatusMessage": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
                "traits": {
                    "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
```

```
current status.</p>"
                }

        },
            "HomeRegions": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
                "traits": {
                    "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
                }
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
        }
    }
  }
}
ListLicenses
 Initialize stack step
  spanInitializeStart
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  OperationSerializer
 Build stack step
  ClientRequestID
  ComputeContentLength
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
```

Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
CheckoutLicense
Initialize stack step
spanInitializeStart
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash

setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
DeleteLicense
Initialize stack step
spanInitializeStart
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper

RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
CreateLicense
Initialize stack step
spanInitializeStart
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
OperationSerializer
Build stack step
ClientRequestID
ComputeContentLength
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
Retry
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
Signing
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
OperationDeserializer
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {

```
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-
Grafana-Enterprise.html#AMG-workspace-register-enterprise
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription
```

```
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
```

```
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
 return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
 return err
```

```
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err !=
 nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
```

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
"context"
"fmt"
awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"

```
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
   - Fingerprint
 //
 //   - IssuerName
 //
 //   - Beneficiary
 Filters []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string
```

```
 noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

 // Received license details.
 Licenses []types.GrantedLicense

 // Token for the next set of results.
 NextToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
 middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
```

```
 return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
 return err
 }
 if err = addRetry(stack, options); err != nil {
 return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
 return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
 return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
 return err
 }
 if err =
 addClientUserAgent(stack, options); err != nil {
 return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
 return err
 }
 if err = addRecursionDetection(stack); err != nil {
 return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err !=
 nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
```

1.156 xxhash 2.3.0

1.156.1 Available under license :

Copyright (c) 2016 Caleb Spare

MIT License

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.157 golang-jwt 5.3.0

1.157.1 Available under license :

Copyright (c) 2012 Dave Grijalva
Copyright (c) 2021 golang-jwt maintainers

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.158 prometheus-client 1.23.0

1.158.1 Available under license :

Copyright (c) 2013 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above

copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Prometheus instrumentation library for Go applications
Copyright 2012-2015 The Prometheus Authors

This product includes software developed at
SoundCloud Ltd. (http://soundcloud.com/).

The following components are included in this product:

perks - a fork of https://github.com/bmizerany/perks
https://github.com/beorn7/perks
Copyright 2013-2015 Blake Mizerany, Bjrn Rabenstein
See https://github.com/beorn7/perks/blob/master/README.md for license details.

Go support for Protocol Buffers - Google's data interchange format
http://github.com/golang/protobuf/
Copyright 2010 The Go Authors
See source code for license details.
                    Apache License
                Version 2.0, January 2004
             http://www.apache.org/licenses/

 TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

 1. Definitions.

    "License" shall mean the terms and conditions for use, reproduction,
    and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.159 aws-sdk-go-v2-service-internal-accept-encoding 1.13.0

1.159.1 Available under license :

GetLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS

```
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Creates a license.
func (c *Client) CreateLicense(ctx context.Context, params *CreateLicenseInput, optFns ...func(*Options))
(*CreateLicenseOutput, error) {
 if params == nil {
  params = &CreateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CreateLicense", params, optFns,
c.addOperationCreateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CreateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}
```

```
type CreateLicenseInput struct {

 // License beneficiary.
 //
 // This member is required.
 Beneficiary *string

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 //
 This member is required.
 ClientToken *string

 // Configuration for consumption of the license. Choose a provisional
 // configuration for workloads running with continuous connectivity. Choose a
 // borrow configuration for workloads with offline usage.
 //
 // This member is required.
 ConsumptionConfiguration *types.ConsumptionConfiguration

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.Entitlement

 // Home Region for the license.
 //
 // This member is required.
 HomeRegion *string

 // License issuer.
 //
 // This member is required.
 Issuer *types.Issuer

 // License name.
 //
 // This member is required.
 LicenseName *string

 // Product name.
 //
 // This member is required.
 ProductName *string

 // Product SKU.
```

```
//
// This member is required.
ProductSKU *string

// Date and time range during which the license is valid, in ISO8601-UTC format.
//
// This member is required.
Validity *types.DatetimeRange

// Information about
the license.
LicenseMetadata []types.Metadata

// Tags to add to the license. For more information about tagging support in
// License Manager, see the [TagResource]operation.
//
// [TagResource]: https://docs.aws.amazon.com/license-manager/latest/APIReference/API_TagResource.html
Tags []types.Tag

noSmithyDocumentSerde
}

type CreateLicenseOutput struct {

// Amazon Resource Name (ARN) of the license.
LicenseArn *string

// License status.
Status types.LicenseStatus

// License version.
Version *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationCreateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCreateLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCreateLicense{},
```

```
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CreateLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err
= addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCreateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCreateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return
 err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return
 err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCreateLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CreateLicense",
 }
}
name: License Scan

on: [pull_request]

jobs:
 licensescan:
   name: License Scan
   runs-on: ubuntu-latest
```

```
  strategy:
    matrix:
      python-version: [3.9]

  steps:
    - name: Checkout target
      uses: actions/checkout@v2
      with:
        path: sdkbase
        ref: ${{ github.base_ref }}
    - name: Checkout this ref
      uses: actions/checkout@v2
      with:
        path: new-ref
        fetch-depth: 0
    - name: Get Diff
      run: git --git-dir ./new-ref/.git diff --name-only --diff-filter=ACMRT ${{ github.event.pull_request.base.sha }}
${{ github.sha }} > refDiffFiles.txt
    - name: Get Target Files
      run: git --git-dir ./sdkbase/.git ls-files | grep -xf refDiffFiles.txt - > targetFiles.txt
    - name: Checkout scancode
      uses: actions/checkout@v2
      with:
        repository: nexB/scancode-toolkit
        path: scancode-toolkit
        fetch-depth: 1
    - name: Set up Python ${{ matrix.python-version }}
       uses: actions/setup-python@v2
      with:
        python-version: ${{ matrix.python-version }}
    # ScanCode
    - name: Self-configure scancode
      working-directory: ./scancode-toolkit
      run: ./scancode --help
    - name: Run Scan code on target
      run: cat targetFiles.txt | while read filename; do echo ./sdkbase/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> old-licenses.txt
    - name: Run Scan code on pr ref
      run: cat refDiffFiles.txt | while read filename; do echo ./new-ref/$filename; done | xargs ./scancode-
toolkit/scancode -l -n 30 --json-pp - | grep short_name | sort | uniq >> new-licenses.txt
    # compare
    - name: License test
      run: if ! cmp old-licenses.txt new-licenses.txt; then echo "Licenses differ! Failing."; exit -1; else echo "Licenses
are the same. Success."; exit 0; fi
CheckoutBorrowLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
```

RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

ListReceivedLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware

RecordResponseTiming
RequestResponseLogger
InterceptTransmit
CheckoutLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever

```
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Lists received licenses.
func (c *Client) ListReceivedLicenses(ctx context.Context, params *ListReceivedLicensesInput, optFns
...func(*Options)) (*ListReceivedLicensesOutput, error) {
 if params == nil {
  params = &ListReceivedLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListReceivedLicenses", params, optFns,
c.addOperationListReceivedLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListReceivedLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListReceivedLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - ProductSKU
 //
 //   - Status
 //
 //
```

```
  - Fingerprint
//
//   - IssuerName
//
//   - Beneficiary
Filters []types.Filter

// Amazon Resource Names (ARNs) of the licenses.
LicenseArns []string

// Maximum number of results to return in a single call.
MaxResults *int32

// Token for the next set of results.
NextToken *string

noSmithyDocumentSerde
}

type ListReceivedLicensesOutput struct {

// Received license details.
Licenses []types.GrantedLicense

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListReceivedLicensesMiddlewares(stack *middleware.Stack, options Options) (err
error) {
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpListReceivedLicenses{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListReceivedLicenses{},
middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "ListReceivedLicenses"); err != nil {
```

```
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err =
addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
```

```
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListReceivedLicenses(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return
 err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if
 err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opListReceivedLicenses(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListReceivedLicenses",
 }
}
DeleteLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
```

```
 InterceptAfterSerialization
Build stack step
 ClientRequestID
 ComputeContentLength
 SetCredentialSourceMiddleware
 UserAgent
 AddTimeOffsetMiddleware
 RecursionDetection
 spanBuildRequestEnd
Finalize stack step
 spanRetryLoop
 InterceptBeforeRetryLoop
 Retry
 InterceptAttempt
 RetryMetricsHeader
 ResolveAuthScheme
 GetIdentity
 ResolveEndpointV2
 disableHTTPS
 ComputePayloadHash
 setLegacyContextSigningOptions
 InterceptBeforeSigning
 Signing
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
```

```
)

// Lists the licenses for your account.
func (c *Client) ListLicenses(ctx context.Context, params *ListLicensesInput, optFns ...func(*Options))
(*ListLicensesOutput, error) {
 if params == nil {
  params = &ListLicensesInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "ListLicenses", params, optFns,
c.addOperationListLicensesMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*ListLicensesOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type ListLicensesInput struct {

 // Filters to scope the results. The following filters are supported:
 //
 //   - Beneficiary
 //
 //   - ProductSKU
 //
 //   - Fingerprint
 //
 //   - Status
 Filters
 []types.Filter

 // Amazon Resource Names (ARNs) of the licenses.
 LicenseArns []string

 // Maximum number of results to return in a single call.
 MaxResults *int32

 // Token for the next set of results.
 NextToken *string

 noSmithyDocumentSerde
}

type ListLicensesOutput struct {
```

```
// License details.
Licenses []types.License

// Token for the next set of results.
NextToken *string

// Metadata pertaining to the operation's result.
ResultMetadata middleware.Metadata

noSmithyDocumentSerde
}

func (c *Client) addOperationListLicensesMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpListLicenses{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack,
 options, "ListLicenses"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
```

```
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
if err = stack.Initialize.Add(newServiceMetadataMiddleware_opListLicenses(options.Region), middleware.Before);
err != nil {
 return err
}
if err = addRecursionDetection(stack); err != nil {
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
```

```
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack,
options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if
err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
```

```
 return nil
}

func newServiceMetadataMiddleware_opListLicenses(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:    ServiceID,
  OperationName: "ListLicenses",
 }
}
DisassociateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
```

```
 InterceptAfterSigning
Deserialize stack step
 AddRawResponseToMetadata
 ErrorCloseResponseBody
 CloseResponseBody
 ResponseErrorWrapper
 RequestIDRetriever
 InterceptAfterDeserialization
 OperationDeserializer
 InterceptBeforeDeserialization
 AddTimeOffsetMiddleware
 RecordResponseTiming
 RequestResponseLogger
 InterceptTransmit
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Removes the Grafana Enterprise license from a workspace.
func (c *Client) DisassociateLicense(ctx context.Context, params *DisassociateLicenseInput, optFns
...func(*Options)) (*DisassociateLicenseOutput, error) {
 if params == nil {
  params = &DisassociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DisassociateLicense", params, optFns,
c.addOperationDisassociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DisassociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type DisassociateLicenseInput struct {

 // The type of license to remove from the workspace.
```

```
 //
 // This member is required.
 LicenseType types.LicenseType

 //
 The ID of the workspace to remove the Grafana Enterprise license from.
 //
 // This member is required.
 WorkspaceId *string

 noSmithyDocumentSerde
}

type DisassociateLicenseOutput struct {

 // A structure containing information about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDisassociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpDisassociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DisassociateLicense");
 err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if
err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
if err = addUserAgentRetryMode(stack, options); err != nil {
 return err
}
if err = addCredentialSource(stack, options); err != nil {
 return err
}
```

```
 if err = addOpDisassociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDisassociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options);
 err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if
 err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDisassociateLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DisassociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Gets detailed information about the specified license.
func (c *Client) GetLicense(ctx context.Context, params *GetLicenseInput, optFns ...func(*Options))
(*GetLicenseOutput, error) {
 if params == nil {
  params = &GetLicenseInput{}
 }
```

```
 result, metadata, err := c.invokeOperation(ctx, "GetLicense", params, optFns,
c.addOperationGetLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*GetLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type GetLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // License version.
 Version *string

 noSmithyDocumentSerde
}

type
 GetLicenseOutput struct {

 // License details.
 License *types.License

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationGetLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpGetLicense{}, middleware.After)
 if err != nil {
  return err
```

```
}
if err := addProtocolFinalizerMiddlewares(stack, options, "GetLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err
!= nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
}
```

```
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options);
 err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpGetLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opGetLicense(options.Region), middleware.Before);
err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opGetLicense(region string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:
       region,
  ServiceID:     ServiceID,
  OperationName: "GetLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
```

```
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license.
//
// If the account that created the license is the same that is performing the
// check out, you must specify the account as the beneficiary.
func (c *Client) CheckoutLicense(ctx context.Context, params *CheckoutLicenseInput, optFns ...func(*Options))
(*CheckoutLicenseOutput, error) {
 if params == nil {
  params = &CheckoutLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutLicense", params, optFns,
c.addOperationCheckoutLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutLicenseInput struct {

 //
 Checkout type.
 //
 // This member is required.
 CheckoutType types.CheckoutType

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 // the request.
 //
 // This member is required.
 ClientToken *string

 // License entitlements.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Key fingerprint identifying the license.
 //
 // This member is required.
 KeyFingerprint *string
```

```
 // Product SKU.
 //
 // This member is required.
 ProductSKU *string

 // License beneficiary.
 Beneficiary *string

 // Node ID.
 NodeId *string

 noSmithyDocumentSerde
}

type CheckoutLicenseOutput struct {

 // Checkout type.
 CheckoutType types.CheckoutType

 // Allowed license entitlements.
 EntitlementsAllowed []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the checkout license.
 LicenseArn
 *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
```

```
if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
 return err
}
err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutLicense{}, middleware.After)
if err != nil {
 return err
}
err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutLicense{}, middleware.After)
if err != nil {
 return err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack,
options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
```

```
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptExecution(stack,
 options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutLicense",
 }
}
```

AWS SDK for Go
Copyright 2015 Amazon.com, Inc. or its affiliates. All Rights Reserved.
Copyright 2014-2015 Stripe, Inc.
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger": {
      "type": "integer"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong": {
      "type": "long"
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },

    {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": " Remove a third-party subscription provider from the Bring Your Own License (BYOL) subscriptions \n\t\t\tregistered to your account. ",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/DeregisterSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderRequest": {
      "type": "structure",

```
        "members": {
          "SubscriptionProviderArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the subscription provider resource to deregister.</p>",
               "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProviderResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Filter": {
        "type": "structure",
        "members": {
          "Name": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of name to filter by.</p>"
             }
          },
          "Values": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
            "traits": {
              "smithy.api#documentation": "<p>One or more values for the name to filter by.</p>"
            }
          },
          "Operator": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Operator",
            "traits": {
              "smithy.api#documentation": "<p>An operator for filtering results.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter object that is used to return more specific results from a describe operation.\n      Filters can be used to match a set of resources by specific criteria.</p>"
        }
      },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList": {
      "type":
 "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Filter"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest"
      },
      "output": {
        "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
         },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Get details for a Bring Your Own License (BYOL) subscription that's
registered to your account.</p>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/subscription/GetRegisteredSubscriptionProvider"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderRequest": {
      "type": "structure",
      "members": {
        "SubscriptionProviderArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation":
```

```
"<p>The Amazon Resource Name (ARN) of the BYOL registration resource to get details for.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProviderResponse": {
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for the BYOL registration
resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",

          "traits": {
                    "smithy.api#documentation": "<p>The subscription provider for the BYOL registration resource
specified \n\t\t\tin the request.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the third-party access
secret stored in Secrets Manager for the BYOL \n\t\t\tregistration resource specified in the request.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the Linux subscription provider access token from the
last \n\t\t\tsuccessful subscription data request.</p>"
                 }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The detailed message from your subscription provider token
status.</p>"
                }
            },
```

```
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time License Manager retrieved
subscription details \n\t\t\tfrom your registered third-party Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#output": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings": {
         "type": "operation",
         "input": {
            "target":
 "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest"
         },
         "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse"
         },
         "errors": [
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the Linux subscriptions service settings for your account.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/subscription/GetServiceSettings"

          },
            "smithy.api#idempotent": {}
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsRequest": {
         "type": "structure",
         "members": {}
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettingsResponse": {
```

```
        "type": "structure",
        "members": {
          "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
              "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
          },
          "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
              "smithy.api#documentation": "<p>Lists
 the settings defined for Linux subscriptions discovery. The settings include if\n      Organizations integration has
been enabled, and which Regions data will be aggregated from.</p>"
            }
          },
          "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
              "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being
applied.</p>"
            }
          },
          "StatusMessage": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
            "traits": {
              "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
            }
          },
          "HomeRegions": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Instance": {
        "type": "structure",
        "members": {
          "AmiId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The AMI ID used to launch the instance.</p>"
            }
          },
```

```
            "InstanceID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The instance ID of the resource.</p>"
               }
            },
            "InstanceType": {
               "target": "smithy.api#String",
               "traits":
{
                  "smithy.api#documentation": "<p>The instance type of the resource.</p>"
               }
            },
            "AccountID": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The account ID which owns the instance.</p>"
               }
            },
            "Status": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The status of the instance.</p>"
               }
            },
            "Region": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Region the instance is running in.</p>"
               }
            },
            "UsageOperation": {
               "target": "smithy.api#String",

   "traits": {
                  "smithy.api#documentation": "<p>The usage operation of the instance. For more information, see For more information, see\n        <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i>.</p>"
               }
            },
            "ProductCode": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList",
               "traits": {
                  "smithy.api#documentation": "<p>The product code for the instance. For more information, see <a href=\"https://docs.aws.amazon.com/license-manager/latest/userguide/linux-subscriptions-usage-operation.html\">Usage\n        operation values</a> in the <i>License Manager User Guide</i> .</p>"
               }
```

```
        },
        "LastUpdatedTime": {
          "target": "smithy.api#String",
           "traits": {
             "smithy.api#documentation": "<p>The time in which the last discovery updated the instance details.</p>"
          }
        },
        "SubscriptionName": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The name of the license subscription that the instance uses.</p>"
          }
        },
        "OsVersion": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The operating system software version that runs on your instance.</p>"
          }
        },
        "SubscriptionProviderCreateTime": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The timestamp when you registered
 the third-party Linux subscription \n\t\t\tprovider for the subscription that the instance uses.</p>"
          }
        },
        "SubscriptionProviderUpdateTime": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>The timestamp from the last time that the instance synced with the registered \n\t\t\tthird-party Linux subscription provider.</p>"
          }
        },
        "DualSubscription": {
          "target": "smithy.api#String",
          "traits": {
             "smithy.api#documentation": "<p>Indicates that you have two different license subscriptions for \n\t\t\tthe same software on your instance.</p>"
          }
        },
        "RegisteredWithSubscriptionProvider": {
          "target": "smithy.api#String",
          "traits": {

     "smithy.api#documentation": "<p>Indicates that your instance uses a BYOL license subscription from \n\t\t\ta third-party Linux subscription provider that you've registered with License Manager.</p>"
```

```
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Details discovered information about a running instance using Linux
subscriptions.</p>"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Instance"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation":
 "<p>An exception occurred with the service.</p>",
          "smithy.api#error": "server"
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LicenseManagerLinuxSubscriptions": {
        "type": "service",
        "version": "2018-05-10",
        "operations": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#DeregisterSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetRegisteredSubscriptionProvider"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#GetServiceSettings"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager Linux Subscriptions",
           "arnNamespace": "license-manager-linux-subscriptions",
          "cloudTrailEventSource": "license-manager-linux-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-linux-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id"
          ],
          "additionalExposedHeaders": [
            "x-amzn-errortype",
            "x-amzn-requestid",
            "x-amzn-trace-id"
          ]
        },
        "smithy.api#documentation": "<p>With License Manager,
you can discover and track your commercial Linux subscriptions on running\n      Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager Linux Subscriptions",
        "smithy.rules#endpointRuleSet": {
          "version": "1.0",
          "parameters": {
```

```
            "Region": {
              "builtIn": "AWS::Region",
              "required": false,
              "documentation": "The AWS region used to dispatch the request.",
              "type": "String"
            },
            "UseDualStack": {
              "builtIn": "AWS::UseDualStack",
              "required": true,
              "default": false,
              "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
               "type": "Boolean"
            },
            "UseFIPS": {
              "builtIn": "AWS::UseFIPS",
              "required": true,
              "default": false,
              "documentation": "When true, send this request to the FIPS-compliant regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
              "type": "Boolean"
            },
            "Endpoint": {
              "builtIn": "SDK::Endpoint",
              "required": false,
              "documentation": "Override the endpoint used to send this request",
              "type": "String"
            }
          },
          "rules": [
            {
              "conditions": [
                {
                  "fn": "isSet",
                  "argv": [
                    {
                      "ref": "Endpoint"
                    }
                  ]
                }
              ],
              "rules": [
                {
                  "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        {
```

```
                        "ref": "UseFIPS"
                      },
                      true
                    ]
                  }

        ],
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
                  "type": "error"
                },
                {
                  "conditions": [],
                  "rules": [
                    {
                      "conditions": [
                        {
                          "fn": "booleanEquals",
                          "argv": [
                            {
                              "ref": "UseDualStack"
                            },
                            true
                          ]

}
                      ],
                      "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
                      "type": "error"
                    },
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": {
                          "ref": "Endpoint"
                        },
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }
                  ],
                  "type": "tree"

              }
              ],
             "type": "tree"
            },
            {
```

```
"conditions": [],
"rules": [
  {
    "conditions": [
      {
        "fn": "isSet",
        "argv": [
          {
            "ref": "Region"
          }
        ]
      }
    ],
    "rules": [
      {
        "conditions": [
          {

"fn": "aws.partition",
            "argv": [
              {
                "ref": "Region"
              }
            ],
            "assign": "PartitionResult"
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {

                "ref": "UseFIPS"
                  },
                  true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
```

```
                }

    ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {
                                                "ref": "PartitionResult"

                    },
                                        "supportsFIPS"
                                    ]
                                }
                            ]
                        },
                        {
                            "fn": "booleanEquals",
                            "argv": [
                                true,
                                {
                                    "fn": "getAttr",
                                    "argv": [

                                     {
                                            "ref": "PartitionResult"
                                        },
                                        "supportsDualStack"
                                    ]
                                }
                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],

        "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-subscriptions-
```

```
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                                "properties": {},
                                                "headers": {}
                                            },
                                            "type": "endpoint"
                                        }
                                    ],

                                "type": "tree"
                                        }
                                    ],
                                    "type": "tree"
                                },
                                {
                                    "conditions": [],
                                    "error": "FIPS and DualStack are enabled, but this partition does not support
one or both",
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {

                "conditions": [
                                {
                                    "fn": "booleanEquals",
                                    "argv": [
                                        {
                                            "ref": "UseFIPS"
                                        },
                                        true
                                    ]
                                }
                            ],
                            "rules": [
                                {
                                    "conditions": [
                                        {

                            "fn": "booleanEquals",
                                            "argv": [
                                                {
                                                    "fn": "getAttr",
                                                    "argv": [
                                                        {
                                                            "ref": "PartitionResult"
                                                        },
```

```
                                        "supportsFIPS"
                                    ]
                                },
                                true

                            ]
                        }
                    ],
                    "rules": [
                        {
                            "conditions": [],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-subscriptions-
fips.{Region}.{PartitionResult#dnsSuffix}",

    "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"
                        }
                    ],
                    "type": "tree"
                },
                {
                    "conditions": [],
                    "error": "FIPS is enabled
but this partition does not support FIPS",
                    "type": "error"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
```

```
                ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [
                            {
                                "fn": "booleanEquals",
                                "argv": [
                                    true,
                                    {
                                        "fn": "getAttr",
                                        "argv": [
                                            {

                                                "ref": "PartitionResult"
                                            },
                                            "supportsDualStack"
                                        ]
                                    }
                                ]
                            }
                        ],
                        "rules": [
                            {
                                "conditions": [],
                                "rules": [

    {
                                        "conditions": [],
                                        "endpoint": {
                                            "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                                            "properties": {},
                                            "headers": {}
                                        },
                                        "type": "endpoint"
                                    }
                                ],
                                "type": "tree"

                    }
                        ],
                        "type": "tree"
                    },
                    {
                        "conditions": [],
                        "error": "DualStack is enabled but this partition does not support DualStack",
```

```
                                    "type": "error"
                                }
                            ],
                            "type": "tree"
                        },
                        {
                            "conditions": [],
                            "rules": [
                                {
                                    "conditions": [],
                                    "endpoint": {
                                        "url": "https://license-manager-linux-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
                                        "properties": {},
                                        "headers": {}
                                    },
                                    "type": "endpoint"
                                }
                            ],
                            "type": "tree"
                        }
                    ],
                    "type": "tree"
                }
            ],
            "type": "tree"
        },
        {
            "conditions": [],
            "error": "Invalid Configuration: Missing Region",
            "type": "error"
        }
    ],
    "type": "tree"
}
]
},
"smithy.rules#endpointTests": {
    "testCases": [
        {
            "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
            "expect": {
                "endpoint": {
                    "url": "https://license-manager-linux-subscriptions-fips.us-east-1.api.aws"

}
            },
            "params": {
```

```
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions-fips.us-east-1.amazonaws.com"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {

      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-linux-subscriptions.us-east-1.amazonaws.com"
            }

    },
          "params": {
            "Region": "us-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
```

```
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
                    }
                },
                "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": true,
                    "UseDualStack": true
                }
            },
            {

 "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.cn-north-1.amazonaws.com.cn"
                    }
                },
                "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                }
            },
            {
                "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
                    }
                 },
                "params": {
                    "Region": "cn-north-1",
                    "UseFIPS": false,
                    "UseDualStack": true
                }
            },
            {
                "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
                "expect": {
                    "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.cn-north-1.amazonaws.com.cn"
                    }
                },
                "params": {
                    "Region": "cn-north-1",
```

```
            "UseFIPS": false,
            "UseDualStack": false
        }
    },
    {

"documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.api.aws"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions-fips.us-gov-east-1.amazonaws.com"
            }

     },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": false
        }
    },
    {
        "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
        "expect": {
            "endpoint": {
                "url": "https://license-manager-linux-subscriptions.us-gov-east-1.api.aws"
            }
        },
        "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": false,
            "UseDualStack": true
        }
    },
    {
```

```
"documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions.us-gov-east-1.amazonaws.com"
                      }
                    },
                    "params": {
                      "Region": "us-gov-east-1",
                      "UseFIPS": false,
                      "UseDualStack": false
                    }
                  },
                  {
                    "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                    "expect": {
                      "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
                    },
                    "params": {

                 "Region": "us-iso-east-1",
                      "UseFIPS": true,
                      "UseDualStack": true
                    }
                  },
                  {
                    "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
                    "expect": {
                      "endpoint": {
                        "url": "https://license-manager-linux-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
                      }
                    },
                    "params": {
                      "Region": "us-iso-east-1",
                      "UseFIPS": true,
                      "UseDualStack": false
                    }
                  },
                  {
                    "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack
enabled",
                    "expect": {
                      "error": "DualStack is enabled but this partition does not support DualStack"
                    },
                    "params": {
                      "Region": "us-iso-east-1",
                      "UseFIPS": false,
                      "UseDualStack": true
                    }
```

```
    },
    {
      "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-iso-east-1.c2s.ic.gov"
        }
      },
      "params": {
        "Region": "us-iso-east-1",
        "UseFIPS":
false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": true
```

```
      }
    },
    {

      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-linux-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }

  },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
```

```
                "documentation": "For custom endpoint with fips enabled and dualstack disabled",
                "expect": {
                  "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
                },
                "params": {
                  "Region": "us-east-1",
                  "UseFIPS": true,
                  "UseDualStack": false,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "For custom endpoint with fips disabled and dualstack enabled",
                "expect": {
                  "error": "Invalid Configuration: Dualstack and custom endpoint are not supported"
                },
                "params": {

"Region": "us-east-1",
                  "UseFIPS": false,
                  "UseDualStack": true,
                  "Endpoint": "https://example.com"
                }
              },
              {
                "documentation": "Missing region",
                "expect": {
                  "error": "Invalid Configuration: Missing Region"
                }
              }
            ],
            "version": "1.0"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled LinuxSubscriptionsDiscovery"

      },
            {
              "name": "Disabled",
              "value": "Disabled",
```

```
                "documentation": "Disabled LinuxSubscriptionsDiscovery"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings": {
          "type": "structure",
          "members": {
            "SourceRegions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
              "traits": {
                "smithy.api#documentation": "<p>The Regions in which to discover data for Linux
subscriptions.</p>",
                "smithy.api#required": {}
              }
            },
            "OrganizationIntegration": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration",
              "traits": {
                "smithy.api#documentation":
 "<p>Details if you have enabled resource discovery across your accounts in Organizations.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Lists the settings defined for discovering Linux subscriptions.</p>"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstances": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },

    {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
```

```
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the running Amazon EC2 instances that were discovered with commercial Linux\n      subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListLinuxSubscriptionInstances"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "Instances"
            }
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesRequest": {
        "type": "structure",
        "members": {
            "Filters": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>An array of structures that you can use to filter the results by your specified criteria. \n    \tFor example, you can specify <code>Region</code> in the <code>Name</code>, with the \n    \t<code>contains</code> operator to list all subscriptions that match a partial string in the \n    \t<code>Value</code>, such as <code>us-west</code>.</p>\n          <p>For each filter, you can specify one of the following values for the <code>Name</code> key \n    \tto streamline results:</p>\n          <ul>\n            <li>\n              <p>\n                <code>AccountID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>AmiID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>DualSubscription</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceID</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>InstanceType</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>ProductCode</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Region</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Status</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>UsageOperation</code>\n              </p>\n            </li>\n          </ul>\n          <p>For each filter, you can use one of the following <code>Operator</code>\n           values to \n    \t\tdefine the behavior of the filter:</p>\n          <ul>\n            <li>\n              <p>\n                <code>contains</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>equals</code>\n              </p>\n            </li>\n            <li>\n              <p>\n                <code>Notequal</code>\n              </p>\n            </li>\n          </ul>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to
 start paginating. This \n\tis the nextToken from a previously truncated response.</p>",
              "smithy.api#length": {
                "min": 1,
                "max": 16384
              }
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
 parameters in request increases."
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionInstancesResponse": {
        "type": "structure",
        "members": {
          "Instances": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InstanceList",
            "traits": {
              "smithy.api#documentation": "<p>An array that contains instance objects.</p>"
            }
          },
          "NextToken": {

         "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
 isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
 next request to retrieve \n\tadditional objects.</p>"
            }
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptions": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse"
```

```
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Lists the Linux subscriptions that have been discovered. If you have linked your\n      organization, the returned results will include data aggregated across your accounts in\n Organizations.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/ListLinuxSubscriptions"
          },
          "smithy.api#idempotent": {},
          "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",

   "items": "Subscriptions"
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsRequest": {
        "type": "structure",
        "members": {
          "Filters": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>An array of structures that you can use to filter the results to those that match one or\n      more sets of key-value pairs that you specify. For example, you can filter by the name of\n <code>Subscription</code> with an optional operator to see subscriptions that match,\n      partially match, or don't match a certain subscription's name.</p>\n      <p>The valid names for this filter are:</p>\n      <ul>\n <li>\n          <p>\n            <code>Subscription</code>\n          </p>\n        </li>\n      </ul>\n <p>The
 valid Operators for this filter are:</p>\n      <ul>\n        <li>\n          <p>\n <code>contains</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>equals</code>\n          </p>\n        </li>\n        <li>\n          <p>\n <code>Notequal</code>\n          </p>\n        </li>\n      </ul>"
            }
```

```
            },
            "MaxResults": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
              "traits": {
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis
 the nextToken from a previously truncated response.</p>",
                "smithy.api#length": {
                  "min": 1,
                  "max": 16384
                }
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "NextToken length limit is half of ddb accepted limit.\nIncrease this limit if
parameters in request increases."
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListLinuxSubscriptionsResponse": {
          "type": "structure",
          "members": {
            "Subscriptions": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList",
              "traits": {
                "smithy.api#documentation": "<p>An array that contains subscription objects.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
               "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
              }
            }
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProviders": {
          "type": "operation",
          "input": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest"
```

```
        },
        "output": {
            "target":
"com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"

            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>List Bring Your Own License (BYOL) subscription registration
resources for your account.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/subscription/ListRegisteredSubscriptionProviders"
            },
            "smithy.api#idempotent": {},
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "RegisteredSubscriptionProviders"
            }
        }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersRequest": {
        "type": "structure",
        "members": {
            "SubscriptionProviderSources": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList",
                "traits": {
                    "smithy.api#documentation": "<p>To filter your results, specify which subscription providers to
return \n\t\t\tin the list.</p>"
                }
            },
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxInteger",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The maximum items to return in a request.</p>",
                "smithy.api#range": {
                  "min": 1,
                  "max": 100
                }
              }

  },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This \n\tis the
nextToken from a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListRegisteredSubscriptionProvidersResponse": {
        "type": "structure",
        "members": {
          "RegisteredSubscriptionProviders": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList",
            "traits": {
              "smithy.api#documentation": "<p>The list of BYOL registration resources that fit the criteria
\n\t\t\tyou specified in the request.</p>"
            }
          },

           "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this \n\tfield
isn't empty, there are additional elements that the service hasn't \n\tincluded in this request. Use this token with the
next request to retrieve \n\tadditional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest"
```

```
        },
        "output": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {

       "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the metadata tags that are assigned to the \n\t\t\tspecified Amazon
Web Services resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{resourceArn}"
          },
          "smithy.api#readonly": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "resourceArn": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
             "traits": {
               "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource for which to
list metadata tags.</p>",
               "smithy.api#httpLabel": {},
               "smithy.api#required": {}
             }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "tags": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
```

```
            "traits": {
              "smithy.api#documentation": "<p>The metadata tags for the requested resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Operator": {
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "EQUAL",
              "value": "Equal",
              "documentation": "Equal operator"
            },
            {
              "name": "NOT_EQUAL",
              "value": "NotEqual",
              "documentation": "Not equal operator"
            },
            {
              "name": "CONTAINS",
              "value": "Contains",
              "documentation": "Contains operator"
            }
          ],
          "smithy.api#length": {
            "min": 1,
            "max": 20
          }
        }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#OrganizationIntegration":
{
        "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "Enabled",
              "value": "Enabled",
              "documentation": "Enabled OrganizationIntegration"
            },
            {
              "name": "Disabled",
              "value": "Disabled",
```

```
                "documentation": "Disabled OrganizationIntegration"
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#ProductCodeList": {
          "type": "list",
          "member": {
            "target": "smithy.api#String"
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProvider": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest"
           },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Register the supported third-party subscription provider for your Bring
Your Own License (BYOL) subscription.</p>",
            "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/subscription/RegisterSubscriptionProvider"

            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderRequest": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
              "traits": {
```

```
                "smithy.api#documentation": "<p>The supported Linux subscription provider to register.</p>",
                "smithy.api#required": {}
              }
            },
            "SecretArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the secret where you've
stored your subscription provider's access token. For \n\t\t\tRHEL subscriptions managed through the
 Red Hat Subscription Manager (RHSM), the secret contains \n\t\t\tyour Red Hat Offline token.</p>",
                "smithy.api#required": {}
              }
            },
            "Tags": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
              "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to your registered Linux subscription
provider \n\t\t\tresource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#RegisterSubscriptionProviderResponse": {
          "type": "structure",
          "members": {
            "SubscriptionProviderSource": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
              "traits": {
                "smithy.api#documentation":
 "<p>The Linux subscription provider that you registered.</p>"
              }
            },
            "SubscriptionProviderArn": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
              }
            },
            "SubscriptionProviderStatus": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
              "traits": {
                "smithy.api#documentation": "<p>Indicates the status of the registration action for the Linux
subscription provider \n\t\t\tthat you requested.</p>"
              }
```

```
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider":
{
        "type": "structure",
        "members": {
            "SubscriptionProviderArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Linux subscription
provider resource that you registered.</p>"
                }
            },
            "SubscriptionProviderSource": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource",
                "traits": {
                    "smithy.api#documentation": "<p>A supported third-party Linux subscription provider. License
Manager currently supports \n\t\t\tRed Hat subscriptions.</p>"
                }
            },
            "SecretArn": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Secrets Manager secret
that stores your registered Linux subscription provider \n\t\t\taccess token. For RHEL account subscriptions, this is
the offline token.</p>"
                }
            },
            "SubscriptionProviderStatus": {
                "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus",
                "traits": {
                    "smithy.api#documentation": "<p>Indicates the status of your registered Linux subscription provider
access token \n\t\t\tfrom the last time License Manager retrieved subscription data. For RHEL account subscriptions,
\n\t\t\tthis is the status of the offline token.</p>"
                }
            },
            "SubscriptionProviderStatusMessage": {
                "target": "smithy.api#String",
                "traits":
{
                    "smithy.api#documentation": "<p>A detailed message that's associated with your BYOL subscription
\n\t\t\tprovider token status.</p>"
                }
            },
```

```
            "LastSuccessfulDataRetrievalTime": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The timestamp from the last time that License Manager accessed third-party subscription data \n\t\t\tfor your account from your registered Linux subscription provider.</p>"
               }
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>A third-party provider for operating system (OS) platform software and license \n\t\t\tsubscriptions, such as Red Hat. When you register a third-party Linux subscription \n\t\t\tprovider, License Manager can get subscription data from the registered provider.</p>"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProviderList": {
         "type": "list",
         "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#RegisteredSubscriptionProvider"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>Unable to find the requested Amazon Web Services resource.</p>",
            "smithy.api#error": "client"
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#SecretArn": {
         "type": "string",
         "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:secretsmanager:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:secret:[^/]{1,1023}$"

   }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#Status": {
         "type": "string",
         "traits": {
            "smithy.api#enum": [
               {
                  "name": "InProgress",
                  "value": "InProgress",
```

```
            "documentation": "InProgress status"
          },
          {
            "name": "Completed",
            "value": "Completed",
            "documentation": "Completed status"
          },
          {
            "name": "Successful",
            "value": "Successful",
            "documentation": "Successful status"
          },
          {
            "name": "Failed",
            "value": "Failed",
            "documentation": "Failed status"
          }
        ]
      }
    },

    "com.amazonaws.licensemanagerlinuxsubscriptions#StringList": {
      "type": "list",
      "member": {
        "target": "smithy.api#String",
        "traits": {
          "smithy.api#length": {
            "min": 1,
            "max": 100
          }
        }
      },
      "traits": {
        "smithy.api#length": {
          "min": 1,
          "max": 100
        },
        "smithy.api#uniqueItems": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      }
```

```
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription": {
      "type": "structure",
      "members": {
        "Name":
{
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The name of the subscription.</p>"
          }
        },
        "Type": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The type of subscription. The type can be subscription-included with Amazon EC2, Bring Your Own\n      Subscription model (BYOS), or from the Amazon Web Services Marketplace. Certain subscriptions may use licensing from the\n      Amazon Web Services Marketplace as well as OS licensing from Amazon EC2 or BYOS.</p>"
          }
        },
        "InstanceCount": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#BoxLong",
          "traits": {
            "smithy.api#documentation": "<p>The total amount of running instances using this subscription.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>An object which details a discovered Linux subscription.</p>"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionList": {
      "type": "list",
      "member": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Subscription"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,510}/[a-z0-9-\\.]{1,510}$"
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource": {
      "type": "string",
      "traits": {
```

```
            "smithy.api#enum": [

{
                    "name": "RedHat",
                    "value": "RedHat",
                    "documentation": "RedHat subscription provider namespace"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSourceList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderSource"
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderStatus": {
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "ACTIVE",
                    "value": "ACTIVE",
                    "documentation": "ACTIVE status"
                },
                {
                    "name": "INVALID",
                    "value": "INVALID",

 "documentation": "INVALID status"
                },
                {
                    "name": "PENDING",
                    "value": "PENDING",
                    "documentation": "PENDING status"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList": {
        "type": "list",
        "member": {
            "target": "smithy.api#String"
        },
        "traits": {
            "smithy.api#length": {
                "min": 0,
                "max": 50
```

```
            },
            "smithy.api#sensitive": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagResource": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse"
           },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
            }
          ],
          "traits": {
            "smithy.api#documentation": "<p>Add metadata tags to the specified Amazon Web Services
resource.</p>",
            "smithy.api#http": {
              "method": "PUT",
              "uri": "/tags/{resourceArn}"
            },
            "smithy.api#idempotent": {}
          }
        },
        "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceRequest": {
          "type": "structure",
          "members":
 {
            "resourceArn": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
              "traits": {
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to which to add the specified \n\t\t\tmetadata tags.</p>",
                "smithy.api#httpLabel": {},
                "smithy.api#required": {}
              }
            },
            "tags": {
              "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Tags",
```

```
            "traits": {
                "smithy.api#documentation": "<p>The metadata tags to assign to the Amazon Web Services resource. Tags are \n\t\t\tformatted as key value pairs.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#input": {}
      }

    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#TagResourceResponse": {
      "type": "structure",
      "members": {},
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#Tags": {
      "type": "map",
      "key": {
        "target": "smithy.api#String"
      },
      "value": {
        "target": "smithy.api#String"
      },
      "traits": {
        "smithy.api#length": {
          "min": 0,
          "max": 50
        },
        "smithy.api#sensitive": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request was denied due to request throttling.</p>",
        "smithy.api#error": "client"
      }
    },
```

```
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Remove one or more metadata tag from the specified Amazon Web
Services resource.</p>",
         "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{resourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "resourceArn": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#SubscriptionProviderArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the Amazon Web Services
resource to remove the metadata tags from.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}
          }
        },
        "tagKeys": {
          "target": "com.amazonaws.licensemanagerlinuxsubscriptions#TagKeyList",
          "traits": {

         "smithy.api#documentation": "<p>A list of metadata tag keys to remove from the requested
\n\t\t\tresource.</p>",
            "smithy.api#httpQuery": "tagKeys",
            "smithy.api#required": {}
          }
        }
```

```
    },
    "traits": {
        "smithy.api#input": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UntagResourceResponse": {
    "type": "structure",
    "members": {},
    "traits": {
        "smithy.api#output": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettings": {
    "type": "operation",
    "input": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest"
    },
    "output": {
        "target": "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse"

 },
    "errors": [
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#InternalServerException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ThrottlingException"
        },
        {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException"
        }
    ],
    "traits": {
        "smithy.api#documentation": "<p>Updates the service settings for Linux subscriptions.</p>",
        "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/subscription/UpdateServiceSettings"
        },
        "smithy.api#idempotent": {}
    }
},
"com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsRequest": {
    "type": "structure",
    "members": {
        "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
```

```
                "smithy.api#documentation": "<p>Describes if the discovery of Linux subscriptions is enabled.</p>",
                "smithy.api#required": {}
            }
        },
        "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>",
                "smithy.api#required": {}
            }
        },
        "AllowUpdate": {
            "target": "smithy.api#Boolean",
            "traits": {
                "smithy.api#documentation": "<p>Describes if updates are allowed to the service settings for Linux subscriptions. If you\n      allow updates, you can aggregate Linux subscription data in more than one home Region.</p>"
            }
        }
      }
    },
    "com.amazonaws.licensemanagerlinuxsubscriptions#UpdateServiceSettingsResponse": {
      "type": "structure",
      "members": {
        "LinuxSubscriptionsDiscovery": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscovery",
            "traits": {
                "smithy.api#documentation": "<p>Lists if discovery has been enabled for Linux subscriptions.</p>"
            }
        },
        "LinuxSubscriptionsDiscoverySettings": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#LinuxSubscriptionsDiscoverySettings",
            "traits": {
                "smithy.api#documentation": "<p>The settings defined for Linux subscriptions discovery. The settings include if Organizations\n      integration has been enabled, and which Regions data will be aggregated from.</p>"
            }
        },
        "Status": {
            "target": "com.amazonaws.licensemanagerlinuxsubscriptions#Status",
            "traits": {
                "smithy.api#documentation": "<p>Indicates the status of Linux subscriptions settings being applied.</p>"
            }
        },
```

```
            "StatusMessage": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringMap",
               "traits": {
                  "smithy.api#documentation": "<p>A message which details the Linux subscriptions service settings
current status.</p>"
               }

        },
            "HomeRegions": {
               "target": "com.amazonaws.licensemanagerlinuxsubscriptions#StringList",
               "traits": {
                  "smithy.api#documentation": "<p>The Region in which License Manager displays the aggregated
data for Linux\n      subscriptions.</p>"
               }
            }
         }
      },
      "com.amazonaws.licensemanagerlinuxsubscriptions#ValidationException": {
         "type": "structure",
         "members": {
            "message": {
               "target": "smithy.api#String"
            }
         },
         "traits": {
            "smithy.api#documentation": "<p>The provided input is not valid. Try your request again.</p>",
            "smithy.api#error": "client"
         }
      }
   }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks out the specified license for offline use.
func (c *Client) CheckoutBorrowLicense(ctx context.Context, params *CheckoutBorrowLicenseInput, optFns
...func(*Options)) (*CheckoutBorrowLicenseOutput, error) {
 if params == nil {
```

```
 params = &CheckoutBorrowLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckoutBorrowLicense", params, optFns,
c.addOperationCheckoutBorrowLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckoutBorrowLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckoutBorrowLicenseInput struct {

 // Unique, case-sensitive identifier that you provide to ensure the idempotency of
 //
 the request.
 //
 // This member is required.
 ClientToken *string

 // Digital signature method. The possible value is JSON Web Signature (JWS)
 // algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS].
 //
 // [RFC 7518 Digital Signature with RSASSA-PSS]: https://tools.ietf.org/html/rfc7518#section-3.5
 //
 // This member is required.
 DigitalSignatureMethod types.DigitalSignatureMethod

 // License entitlements. Partial checkouts are not supported.
 //
 // This member is required.
 Entitlements []types.EntitlementData

 // Amazon Resource Name (ARN) of the license. The license must use the borrow
 // consumption configuration.
 //
 // This member is required.
 LicenseArn *string

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Node ID.
 NodeId *string
```

```
 noSmithyDocumentSerde
}

type CheckoutBorrowLicenseOutput struct {

 // Information about constraints.
 CheckoutMetadata []types.Metadata

 // Allowed license entitlements.
 EntitlementsAllowed
 []types.EntitlementData

 // Date and time at which the license checkout expires.
 Expiration *string

 // Date and time at which the license checkout is issued.
 IssuedAt *string

 // Amazon Resource Name (ARN) of the license.
 LicenseArn *string

 // License consumption token.
 LicenseConsumptionToken *string

 // Node ID.
 NodeId *string

 // Signed token.
 SignedToken *string

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckoutBorrowLicenseMiddlewares(stack *middleware.Stack, options Options) (err
error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckoutBorrowLicense{}, middleware.After)
 if err != nil {
  return
```

```
err
}
if err := addProtocolFinalizerMiddlewares(stack, options, "CheckoutBorrowLicense"); err != nil {
 return fmt.Errorf("add protocol finalizers: %v", err)
}

if err = addlegacyEndpointContextSetter(stack, options); err != nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack);
err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
 return err
```

```
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckoutBorrowLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckoutBorrowLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options);
 err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err != nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
```

```
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return
 err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opCheckoutBorrowLicense(region string)
*awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "CheckoutBorrowLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package grafana

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/grafana/types"
```

```
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Assigns a Grafana Enterprise license to a workspace. To upgrade, you must use
// ENTERPRISE for the licenseType , and pass in a valid Grafana Labs token for the
// grafanaToken . Upgrading to Grafana Enterprise incurs additional fees. For more
// information, see [Upgrade a workspace to Grafana Enterprise].
//
// [Upgrade a workspace to Grafana Enterprise]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html
func (c *Client) AssociateLicense(ctx context.Context, params *AssociateLicenseInput, optFns ...func(*Options))
(*AssociateLicenseOutput, error) {
 if params == nil {
  params = &AssociateLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx,
 "AssociateLicense", params, optFns, c.addOperationAssociateLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*AssociateLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type AssociateLicenseInput struct {

 // The type of license to associate with the workspace.
 //
 // Amazon Managed Grafana workspaces no longer support Grafana Enterprise free
 // trials.
 //
 // This member is required.
 LicenseType types.LicenseType

 // The ID of the workspace to associate the license with.
 //
 // This member is required.
 WorkspaceId *string

 // A token from Grafana Labs that ties your Amazon Web Services account with a
 // Grafana Labs account. For more information, see [Link your account with Grafana Labs].
 //
 // [Link your account with Grafana Labs]: https://docs.aws.amazon.com/grafana/latest/userguide/upgrade-to-Grafana-Enterprise.html#AMG-workspace-register-enterprise
```

```
 GrafanaToken *string

 noSmithyDocumentSerde
}

type AssociateLicenseOutput
 struct {

 // A structure containing data about the workspace.
 //
 // This member is required.
 Workspace *types.WorkspaceDescription

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationAssociateLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsRestjson1_serializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsRestjson1_deserializeOpAssociateLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "AssociateLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack,
 options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if err = addComputeContentLength(stack); err != nil {
  return err
 }
```

```
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack,
 c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpAssociateLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opAssociateLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
```

```
 return err
}
if err = addRequestIDRetrieverMiddleware(stack); err != nil {
 return err
}
if err = addResponseErrorMiddleware(stack); err != nil {
 return err
}
if err = addRequestResponseLogging(stack, options); err != nil {
 return err
}
if err = addDisableHTTPSMiddleware(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack,
options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
```

```
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opAssociateLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "AssociateLicense",
 }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/aws-sdk-go-v2/service/licensemanager/types"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Deletes the specified license.
func (c *Client) DeleteLicense(ctx context.Context, params *DeleteLicenseInput, optFns ...func(*Options))
(*DeleteLicenseOutput, error) {
 if params == nil {
  params = &DeleteLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "DeleteLicense", params, optFns,
c.addOperationDeleteLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*DeleteLicenseOutput)
 out.ResultMetadata = metadata
```

```
 return out, nil
}

type DeleteLicenseInput struct {

 // Amazon Resource Name (ARN) of the license.
 //
 // This member is required.
 LicenseArn *string

 // Current version of the license.
 //
 // This member is required.
 SourceVersion
 *string

 noSmithyDocumentSerde
}

type DeleteLicenseOutput struct {

 // Date when the license is deleted.
 DeletionDate *string

 // License status.
 Status types.LicenseDeletionStatus

 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationDeleteLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpDeleteLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "DeleteLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }
```

```
if err = addlegacyEndpointContextSetter(stack, options); err !=
nil {
 return err
}
if err = addSetLoggerMiddleware(stack, options); err != nil {
 return err
}
if err = addClientRequestID(stack); err != nil {
 return err
}
if err = addComputeContentLength(stack); err != nil {
 return err
}
if err = addResolveEndpointMiddleware(stack, options); err != nil {
 return err
}
if err = addComputePayloadSHA256(stack); err != nil {
 return err
}
if err = addRetry(stack, options); err != nil {
 return err
}
if err = addRawResponseToMetadata(stack); err != nil {
 return err
}
if err = addRecordResponseTiming(stack); err != nil {
 return err
}
if err = addSpanRetryLoop(stack, options); err != nil {
 return err
}
if err = addClientUserAgent(stack, options); err != nil {
 return err
}
if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
 return err
}
if err = addSetLegacyContextSigningOptionsMiddleware(stack); err
!= nil {
 return err
}
if err = addTimeOffsetBuild(stack, c); err != nil {
 return err
}
```

```
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpDeleteLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opDeleteLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addInterceptAttempt(stack, options); err !=
 nil {
  return err
 }
 if err = addInterceptExecution(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSerialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeSigning(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterSigning(stack, options); err != nil {
```

```
 return err
 }
 if err = addInterceptTransmit(stack, options); err != nil {
  return err
 }
 if err = addInterceptBeforeDeserialization(stack, options); err != nil {
  return err
 }
 if err = addInterceptAfterDeserialization(stack, options); err != nil {
  return err
 }
 if err = addSpanInitializeStart(stack); err != nil {
  return err
 }
 if err = addSpanInitializeEnd(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestStart(stack); err != nil {
  return err
 }
 if err = addSpanBuildRequestEnd(stack); err != nil {
  return err
 }
 return nil
}

func newServiceMetadataMiddleware_opDeleteLicense(region
 string) *awsmiddleware.RegisterServiceMetadata {
 return &awsmiddleware.RegisterServiceMetadata{
  Region:        region,
  ServiceID:     ServiceID,
  OperationName: "DeleteLicense",
 }
}
CheckInLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
```

OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer

in the documentation and/or other materials provided with the
distribution.
  * Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER
 OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

```
{
  "smithy": "2.0",
  "shapes": {
    "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>You don't have sufficient access to perform this action.</p>",
        "smithy.api#error": "client"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider": {
      "type": "structure",
      "members": {
        "DirectoryId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Directory",
          "traits": {
            "smithy.api#documentation": "<p>The directory ID for an Active Directory identity provider.</p>"
          }
        },
        "ActiveDirectorySettings":
{
          "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings",
          "traits": {
            "smithy.api#documentation": "<p>The <code>ActiveDirectorySettings</code> resource contains
details about \n\t\t\tthe Active Directory, including network access details such as domain name and IP
```

\n\t\t\taddresses, and the credential provider for user administration. "
            }
          },
          "ActiveDirectoryType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType",
            "traits": {
              "smithy.api#documentation": " The type of Active Directory either a self-managed Active Directory or an \n\t\t\tAmazon Web Services Managed Active Directory. "
            }
          }
        },
        "traits": {
          "smithy.api#documentation": " Details about an Active Directory identity provider. "
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectorySettings": {
        "type": "structure",
        "members": {
          "DomainName": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": " The domain name for the Active Directory. "
            }
          },
          "DomainIpv4List": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4List",
            "traits": {
              "smithy.api#documentation": " A list of domain IPv4 addresses that are used for the Active Directory. ",
              "smithy.api#length": {
                "min": 1,
                "max": 2
              }
            }
          },
          "DomainCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": " Points to the <code>CredentialsProvider</code> resource that contains \n\t\t\tinformation about the credential provider for user administration. "
            }
          },
          "DomainNetworkSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings",
            "traits": {
              "smithy.api#documentation": " The <code>DomainNetworkSettings</code> resource contains an

```
array of \n\t\t\tsubnets that apply for the Active Directory.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network access and credential details that are needed for
\n\t\t\tuser administration in the Active Directory.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryType":
{
        "type": "string",
        "traits": {
            "smithy.api#enum": [
                {
                    "name": "SELF_MANAGED",
                    "value": "SELF_MANAGED",
                    "documentation": "SELF_MANAGED type of Active Directory"
                },
                {
                    "name": "AWS_MANAGED",
                    "value": "AWS_MANAGED",
                    "documentation": "AWS_MANAGED type of Active Directory"
                }
            ]
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Arn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-z0-9-\\.]{1,63}:[a-
zA-Z0-9-\\.]{1,510}/[a-zA-Z0-9-\\.]{1,510}$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUser":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Associates the user to an EC2 instance to utilize user-based subscriptions.</p>\n        <note>\n          <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n        </note>",
          "smithy.api#http":
{
            "code": 200,
            "method": "POST",
            "uri": "/user/AssociateUser"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#AssociateUserRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance that provides the user-based
```

```
subscription.</p>",
                    "smithy.api#required": {}
                }
            },
             "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
information for the user to associate.</p>"
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the user association.</p>"
                }
            }
        },
        "traits": {

    "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#AssociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#BoxInteger": {
        "type": "integer"
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#ConflictException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>The request couldn't be completed because it conflicted with the current state of the\n\t\t\tresource.</p>",
        "smithy.api#error": "server"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },

      {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Creates a network endpoint for the Remote Desktop Services (RDS) license server.</p>",
```

```
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/license-server/CreateLicenseServerEndpoint"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>IdentityProvider</code> resource that contains details \n\t\t\tabout a registered identity provider. In the case
of Active Directory, that can be \n\t\t\ta self-managed Active Directory or an Amazon Web Services Managed
Active Directory that contains user identity details.</p>",
                    "smithy.api#required": {}
                }
            },
            "LicenseServerSettings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>LicenseServerSettings</code> resource to create for
the endpoint. The \n\t\t\tsettings include the type of license server and the Secrets Manager secret that \n\t\t\tenables
administrators to add or remove users associated with the \n\t\t\tlicense server.</p>",
                    "smithy.api#required": {}
                }
            },
            "Tags": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
                "traits": {
                    "smithy.api#documentation": "<p>The tags that apply for the license server endpoint.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpointResponse":
{
        "type": "structure",
        "members": {
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
```

```
                "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider specified in the request.</p>"
              }
            },
            "LicenseServerEndpointArn": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
              "traits": {
                "smithy.api#documentation": "<p>The ARN of the <code>LicenseServerEndpoint</code> resource.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider": {
          "type": "union",
          "members": {
            "SecretsManagerCredentialsProvider":
{
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider",
              "traits": {
                "smithy.api#documentation": "<p>Identifies the Secrets Manager secret that contains credentials needed for \n\t\t\tuser administration in the Active Directory.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Contains information about the credential provider for user \n\t\t\tadministration.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse"
           },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
```

```
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"

}
        ],
        "traits": {
          "smithy.api#documentation": "<p>Deletes a <code>LicenseServerEndpoint</code> resource.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/DeleteLicenseServerEndpoint"
          },
          "smithy.api#idempotent": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointRequest": {
        "type": "structure",
        "members": {
          "LicenseServerEndpointArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the
<code>LicenseServerEndpoint</code> \n\t\t\tresource to delete.</p>",
              "smithy.api#required": {}
            }
          },
           "ServerType": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
            "traits": {
              "smithy.api#documentation": "<p>The type of License Server that the delete request refers to.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpointResponse": {
        "type": "structure",
        "members": {
          "LicenseServerEndpoint": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint",
            "traits": {
              "smithy.api#documentation": "<p>Shows details from the <code>LicenseServerEndpoint</code>
resource that was deleted.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
```

```
        "traits": {
            "smithy.api#documentation": "<p>Deregisters the Active Directory identity provider from License
Manager user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/DeregisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderRequest":
{
        "type": "structure",
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>An object that specifies details for the Active Directory identity
provider.</p>"
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                 "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the identity
provider to deregister.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
            "IdentityProviderSummary": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
```

```
            "traits": {
                "smithy.api#documentation": "<p>Metadata that describes the results of an identity provider operation.</p>",
                "smithy.api#required": {}
            }
        }
      },
      "traits": {
        "smithy.api#output": {}

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Directory": {
      "type": "string",
      "traits": {
        "smithy.api#pattern": "^(d|sd)-[0-9a-f]{10}$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
         },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
```

```
        ],
        "traits": {
          "smithy.api#documentation": "<p>Disassociates the user from an EC2 instance providing user-based
subscriptions.</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/user/DisassociateUser"
          },
          "smithy.api#idempotent": {}

      }
      },
      "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserRequest": {
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the Active Directory identity provider for the
user.</p>"
            }
          },
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance which provides user-based
subscriptions.</p>"
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the Active
 Directory identity provider.</p>"
            }
          },
          "InstanceUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the user to disassociate
from the EC2 instance.</p>"
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains
```

```
information for the user to disassociate.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DisassociateUserResponse": {
        "type": "structure",
        "members": {
            "InstanceUserSummary":
{
                "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary",
                "traits": {
                    "smithy.api#documentation": "<p>Metadata that describes the associate user operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#DomainNetworkSettings": {
        "type": "structure",
        "members": {
            "Subnets": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
                "traits": {
                    "smithy.api#documentation": "<p>Contains a list of subnets that apply for the Active Directory
domain.</p>",
                    "smithy.api#length": {
                        "min": 1
                    },

   "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains network settings for the Active Directory domain.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#Filter": {
        "type": "structure",
        "members": {
            "Attribute": {
```

```
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of an attribute to use as a filter.</p>"
            }
          },
          "Operation": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The type of search (For example, eq, geq, leq)</p>"
            }
          },
          "Value": {
            "target": "smithy.api#String",
            "traits":
{
              "smithy.api#documentation": "<p>Value of the filter.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A filter name and value pair that is used to return more specific results
from a describe\n\t\t\tor list operation. You can use filters can be used to match a set of resources by specific
\n\t\t\tcriteria, such as tags, attributes, or IDs.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#FilterList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Filter"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider": {
        "type": "union",
        "members": {
          "ActiveDirectoryIdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ActiveDirectoryIdentityProvider",
             "traits": {
              "smithy.api#documentation": "<p>The <code>ActiveDirectoryIdentityProvider</code> resource
contains settings \n\t\t\tand other details about a specific Active Directory identity provider.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Refers to an identity provider.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary": {
        "type": "structure",
```

```
        "members": {
            "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource contains information
about \n\t\t\tan identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
             "Settings": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>Settings</code> resource contains details about the
registered \n\t\t\tidentity providers product related configuration settings, such as the \n\t\t\tsubnets to provision VPC
endpoints.</p>",
                    "smithy.api#required": {}
                }
            },
            "Product": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of the
 identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "IdentityProviderArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider.</p>"
                }
            },
            "FailureMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The failure message associated with an identity provider.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes an identity provider.</p>"
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList": {
        "type": "list",
        "member": {

          "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary": {
        "type": "structure",
        "members": {
          "InstanceId": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The ID of the EC2 instance, which provides user-based
subscriptions.</p>",
              "smithy.api#required": {}
            }
          },
          "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of an EC2 instance resource.</p>",
              "smithy.api#required": {}
            }
          },
          "Products": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#StringList",
             "traits": {
              "smithy.api#documentation": "<p>A list of provided user-based subscription products.</p>",
              "smithy.api#required": {}
            }
          },
          "LastStatusCheckDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The date of the last status check.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for an EC2 instance.</p>"
            }
          }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>Describes an EC2 instance providing user-based subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList":
{
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary": {
        "type": "structure",
        "members": {
            "Username": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the EC2 instance that provides user-based
subscriptions.</p>",
                    "smithy.api#required": {}
                }
            },

    "IdentityProvider": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
                "traits": {
                    "smithy.api#documentation": "<p>The <code>IdentityProvider</code> resource specifies details
\n\t\t\tabout the identity provider.</p>",
                    "smithy.api#required": {}
                }
            },
            "Status": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status of a user associated with an EC2 instance.</p>",
                    "smithy.api#required": {}
                }
            },
            "InstanceUserArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) that identifies the instance
```

```
user.</p>"
                }
            },
            "StatusMessage": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The status message for users of an EC2 instance.</p>"
                }
            },
            "Domain": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
information for the product subscription.</p>"
                }
            },
            "AssociationDate": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The date a user was associated with an EC2 instance.</p>"
                }
            },
            "DisassociationDate": {
                "target": "smithy.api#String",
                 "traits": {
                    "smithy.api#documentation": "<p>The date a user was disassociated from an EC2 instance.</p>"
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Describes users of an EC2 instance providing user-based
subscriptions.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList": {
        "type": "list",
        "member": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummary"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#InternalServerException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
```

```
        "smithy.api#documentation": "<p>An exception occurred with the service.</p>",
        "smithy.api#error": "server",
        "smithy.api#httpError": 500
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4": {
    "type": "string",
    "traits": {
        "smithy.api#pattern": "^(?:(25[0-5]|2[0-4][0-9]|1[0-9][0-9]|[1-9][0-9]|[0-9])(\\.(?!$)|$)){4}$"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#IpV4List": {
    "type": "list",
    "member": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#IpV4"
    }
},
"com.amazonaws.licensemanagerusersubscriptions#LicenseManagerUserSubscriptions": {
    "type": "service",
    "version": "2018-05-10",
    "operations": [
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AssociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CreateLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeleteLicenseServerEndpoint"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DeregisterIdentityProvider"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#DisassociateUser"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstances"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints"
        },
        {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions"
```

```
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagResource"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResource"
        },
        {

"target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings"
        }
      ],
      "traits": {
        "aws.api#service": {
          "sdkId": "License Manager User Subscriptions",
          "arnNamespace": "license-manager-user-subscriptions",
          "cloudTrailEventSource": "license-manager-user-subscriptions.amazonaws.com"
        },
        "aws.auth#sigv4": {
          "name": "license-manager-user-subscriptions"
        },
        "aws.protocols#restJson1": {},
        "smithy.api#cors": {
          "additionalAllowedHeaders": [
            "*",
            "content-type",
            "x-amz-content-sha256",
            "x-amz-user-agent",
            "x-amzn-platform-id",
            "x-amzn-trace-id",
            "content-length",
```

```
            "x-api-key",
                "authorization",
                "x-amz-date",
                "x-amz-security-token",
                "Access-Control-Allow-Headers",
                "Access-Control-Allow-Methods",
                "Access-Control-Allow-Origin"
            ],
            "additionalExposedHeaders": [
                "x-amzn-errortype",
                "x-amzn-requestid",
                "x-amzn-trace-id"
            ]
        },
        "smithy.api#documentation": "<p>With License Manager, you can create user-based subscriptions to utilize licensed software with\n\t\ta per user subscription fee on Amazon EC2 instances.</p>",
        "smithy.api#title": "AWS License Manager User Subscriptions",
        "smithy.rules#endpointRuleSet": {
            "version": "1.0",
            "parameters": {
                "Region":
{
                    "builtIn": "AWS::Region",
                    "required": false,
                    "documentation": "The AWS region used to dispatch the request.",
                    "type": "String"
                },
                "UseDualStack": {
                    "builtIn": "AWS::UseDualStack",
                    "required": true,
                    "default": false,
                    "documentation": "When true, use the dual-stack endpoint. If the configured endpoint does not support dual-stack, dispatching the request MAY return an error.",
                    "type": "Boolean"
                },
                "UseFIPS": {
                    "builtIn": "AWS::UseFIPS",
                    "required": true,
                    "default": false,
                    "documentation": "When true, send this request to the FIPS-compliant
 regional endpoint. If the configured endpoint does not have a FIPS compliant endpoint, dispatching the request will return an error.",
                    "type": "Boolean"
                },
                "Endpoint": {
                    "builtIn": "SDK::Endpoint",
                    "required": false,
                    "documentation": "Override the endpoint used to send this request",
```

```
        "type": "String"
      }
    },
    "rules": [
      {
        "conditions": [
          {
            "fn": "isSet",
            "argv": [
              {
                "ref": "Endpoint"
              }
            ]
          }
        ],
        "rules": [
          {
            "conditions": [
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseFIPS"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: FIPS and custom endpoint are not supported",
            "type": "error"
          },
          {
            "conditions": [
              {

                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "error": "Invalid Configuration: Dualstack and custom endpoint are not supported",
            "type": "error"
          },
          {
```

```
                "conditions": [],
                "endpoint": {
                  "url": {
                    "ref": "Endpoint"
                  },

"properties": {},
                    "headers": {}
                },
                "type": "endpoint"
              }
            ],
            "type": "tree"
          },
          {
            "conditions": [
              {
                "fn": "isSet",
                "argv": [
                  {
                    "ref": "Region"
                  }
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {
                    "fn": "aws.partition",

                   "argv": [
                      {
                        "ref": "Region"
                      }
                    ],
                    "assign": "PartitionResult"
                  }
                ],
                "rules": [
                  {
                    "conditions": [
                      {
                        "fn": "booleanEquals",
                        "argv": [
                          {
                            "ref": "UseFIPS"
                          },
```

```
true
                ]
              },
              {
                "fn": "booleanEquals",
                "argv": [
                  {
                    "ref": "UseDualStack"
                  },
                  true
                ]
              }
            ],
            "rules": [
              {
                "conditions": [
                  {

"fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsFIPS"
                        ]
                      }
                    ]
                  },

                {
                    "fn": "booleanEquals",
                    "argv": [
                      true,
                      {
                        "fn": "getAttr",
                        "argv": [
                          {
                            "ref": "PartitionResult"
                          },
                          "supportsDualStack"
                        ]
                      }
```

```
                ]
                    }
                ],
                "rules": [
                    {
                        "conditions": [],
                        "endpoint": {
                            "url": "https://license-manager-user-subscriptions-
fips.{Region}.{PartitionResult#dualStackDnsSuffix}",
                            "properties": {},
                            "headers": {}
                        },
                        "type": "endpoint"
                    }

    ],
                "type": "tree"
            },
            {
                "conditions": [],
                "error": "FIPS and DualStack are enabled, but this partition does not support one or
both",
                "type": "error"
            }
        ],
        "type": "tree"
    },
    {
        "conditions": [
            {
                "fn": "booleanEquals",
                "argv": [

 {
                        "ref": "UseFIPS"
                    },
                    true
                ]
            }
        ],
        "rules": [
            {
                "conditions": [
                    {
                        "fn": "booleanEquals",
                        "argv": [
                            {
                                "fn": "getAttr",
```

```
                "argv": [

            {
                        "ref": "PartitionResult"
                    },
                    "supportsFIPS"
                ]
            },
            true
        ]
    }
],
"rules": [
    {
        "conditions": [],
        "endpoint": {

"url": "https://license-manager-user-subscriptions-fips.{Region}.{PartitionResult#dnsSuffix}",
                "properties": {},
                "headers": {}
            },
            "type": "endpoint"
        }
    ],
    "type": "tree"
},
{
    "conditions": [],
    "error": "FIPS is enabled but this partition does not support FIPS",
    "type": "error"

}
            ],
            "type": "tree"
        },
        {
            "conditions": [
                {
                    "fn": "booleanEquals",
                    "argv": [
                        {
                            "ref": "UseDualStack"
                        },
                        true
                    ]
                }
            ],
            "rules": [
```

```
                {

        "conditions": [
                    {
                      "fn": "booleanEquals",
                      "argv": [
                        true,
                        {
                          "fn": "getAttr",
                          "argv": [
                            {
                              "ref": "PartitionResult"
                            },
                            "supportsDualStack"
                          ]

        }
                      ]
                    }
                  ],
                  "rules": [
                    {
                      "conditions": [],
                      "endpoint": {
                        "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dualStackDnsSuffix}",
                        "properties": {},
                        "headers": {}
                      },
                      "type": "endpoint"
                    }

                ],
                    "type": "tree"
                },
                {
                  "conditions": [],
                  "error": "DualStack is enabled but this partition does not support DualStack",
                  "type": "error"
                }
              ],
              "type": "tree"
            },
            {
              "conditions": [],
              "endpoint": {
                "url": "https://license-manager-user-
subscriptions.{Region}.{PartitionResult#dnsSuffix}",
```

```
                "properties": {},
                        "headers": {}
                    },
                    "type": "endpoint"
                }
            ],
            "type": "tree"
        }
      ],
      "type": "tree"
    },
    {
      "conditions": [],
      "error": "Invalid Configuration: Missing Region",
      "type": "error"
    }
  ]
},
"smithy.rules#endpointTests": {
  "testCases": [
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack enabled",
      "expect":
{
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",

    "UseFIPS": true,
        "UseDualStack": false
      }
```

```
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-east-1.api.aws"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint":
{
          "url": "https://license-manager-user-subscriptions.us-east-1.amazonaws.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack enabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-
1.api.amazonwebservices.com.cn"
        }
      },
      "params": {
        "Region": "cn-north-1",
        "UseFIPS":
true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region cn-north-1 with FIPS enabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.cn-north-1.amazonaws.com.cn"
```

```
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": true,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "endpoint":
{
              "url": "https://license-manager-user-subscriptions.cn-north-1.api.amazonwebservices.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region cn-north-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.cn-north-1.amazonaws.com.cn"
            }
          },
          "params": {
            "Region": "cn-north-1",
            "UseFIPS": false,
             "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.api.aws"
            }
          },
          "params": {
            "Region": "us-gov-east-1",
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
```

```
                {
                  "documentation": "For region us-gov-east-1 with FIPS enabled and DualStack disabled",
                  "expect": {
                    "endpoint":
{
                      "url": "https://license-manager-user-subscriptions-fips.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": true,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack enabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-gov-east-1.api.aws"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                     "UseDualStack": true
                  }
                },
                {
                  "documentation": "For region us-gov-east-1 with FIPS disabled and DualStack disabled",
                  "expect": {
                    "endpoint": {
                      "url": "https://license-manager-user-subscriptions.us-gov-east-1.amazonaws.com"
                    }
                  },
                  "params": {
                    "Region": "us-gov-east-1",
                    "UseFIPS": false,
                    "UseDualStack": false
                  }
                },
                {
                  "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack enabled",
                  "expect": {
                    "error": "FIPS
and DualStack are enabled, but this partition does not support one or both"
                  },
                  "params": {
                    "Region": "us-iso-east-1",
```

```
            "UseFIPS": true,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS enabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions-fips.us-iso-east-1.c2s.ic.gov"
            }
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": true,
            "UseDualStack": false

}
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack enabled",
          "expect": {
            "error": "DualStack is enabled but this partition does not support DualStack"
          },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": true
          }
        },
        {
          "documentation": "For region us-iso-east-1 with FIPS disabled and DualStack disabled",
          "expect": {
            "endpoint": {
              "url": "https://license-manager-user-subscriptions.us-iso-east-1.c2s.ic.gov"
            }

      },
          "params": {
            "Region": "us-iso-east-1",
            "UseFIPS": false,
            "UseDualStack": false
          }
        },
        {
          "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack enabled",
          "expect": {
            "error": "FIPS and DualStack are enabled, but this partition does not support one or both"
          },
```

```
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS enabled and DualStack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions-fips.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": true,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack enabled",
      "expect": {
        "error": "DualStack is enabled but this partition does not support DualStack"
      },
      "params": {
        "Region": "us-isob-east-1",

 "UseFIPS": false,
        "UseDualStack": true
      }
    },
    {
      "documentation": "For region us-isob-east-1 with FIPS disabled and DualStack disabled",
      "expect": {
        "endpoint": {
          "url": "https://license-manager-user-subscriptions.us-isob-east-1.sc2s.sgov.gov"
        }
      },
      "params": {
        "Region": "us-isob-east-1",
        "UseFIPS": false,
        "UseDualStack": false
      }
    },
    {
      "documentation": "For custom endpoint with region set and fips disabled and dualstack disabled",
      "expect": {
```

```
      "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with region not set and fips disabled and dualstack
disabled",
      "expect": {
        "endpoint": {
          "url": "https://example.com"
        }
      },
      "params": {
        "UseFIPS": false,
        "UseDualStack":
false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips enabled and dualstack disabled",
      "expect": {
        "error": "Invalid Configuration: FIPS and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": true,
        "UseDualStack": false,
        "Endpoint": "https://example.com"
      }
    },
    {
      "documentation": "For custom endpoint with fips disabled and dualstack enabled",
      "expect": {
        "error": "Invalid Configuration:
Dualstack and custom endpoint are not supported"
      },
      "params": {
        "Region": "us-east-1",
        "UseFIPS": false,
```

```
                    "UseDualStack": true,
                    "Endpoint": "https://example.com"
                  }
                },
                {
                  "documentation": "Missing region",
                  "expect": {
                    "error": "Invalid Configuration: Missing Region"
                  }
                }
              ],
              "version": "1.0"
            }
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServer": {
          "type": "structure",
          "members": {
            "ProvisioningStatus": {
              "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                 "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS
\n\t\t\tlicense server.</p>"
              }
            },
            "HealthStatus": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus",
              "traits": {
                "smithy.api#documentation": "<p>The health status of the RDS license server.</p>"
              }
            },
            "Ipv4Address": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A list of domain IPv4 addresses that are used for the RDS
\n\t\t\tlicense server.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>Information
 about a Remote Desktop Services (RDS) license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint": {
          "type": "structure",
          "members": {
```

```
            "IdentityProviderArn": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider that's
associated with \n\t\t\tthe RDS license server endpoint.</p>"
               }
            },
            "ServerType": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
               "traits": {
                  "smithy.api#documentation": "<p>The type of license server.</p>"
               }
            },
            "ServerEndpoint": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint",

   "traits": {
                  "smithy.api#documentation": "<p>The <code>ServerEndpoint</code> resource contains the network
\n\t\t\taddress of the RDS license server endpoint.</p>"
               }
            },
            "StatusMessage": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The message associated with the provisioning status, if there is
one.</p>"
               }
            },
            "LicenseServerEndpointId": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the license server endpoint.</p>"
               }
            },
            "LicenseServerEndpointArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits":
{
                  "smithy.api#documentation": "<p>The ARN of the <code>ServerEndpoint</code> resource for the
RDS \n\t\t\tlicense server.</p>"
               }
            },
            "LicenseServerEndpointProvisioningStatus": {
               "target":
"com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus",
               "traits": {
                  "smithy.api#documentation": "<p>The current state of the provisioning process for the RDS license
\n\t\t\tserver endpoint</p>"
```

```
            }
          },
          "LicenseServers": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>LicenseServer</code> resources that represent the \n\t\t\tlicense servers that are accessed through this endpoint.</p>"
            }
          },

         "CreationTime": {
            "target": "smithy.api#Timestamp",
            "traits": {
              "smithy.api#documentation": "<p>The timestamp when License Manager created the license server endpoint.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>Contains details about a network endpoint for a Remote Desktop Services (RDS) \n\t\t\tlicense server.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointId": {
        "type": "string"
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpoint"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointProvisioningStatus": {

  "type": "string",
        "traits": {
          "smithy.api#enum": [
            {
              "name": "PROVISIONING",
              "value": "PROVISIONING",
              "documentation": ""
            },
            {
              "name": "PROVISIONING_FAILED",
              "value": "PROVISIONING_FAILED",
              "documentation": ""
            },
            {
```

```
            "name": "PROVISIONED",
            "value": "PROVISIONED",
            "documentation": ""
          },
          {
            "name": "DELETING",
            "value": "DELETING",
            "documentation": ""
          },
          {
            "name": "DELETION_FAILED",
            "value": "DELETION_FAILED",
            "documentation": ""

          },
          {
            "name": "DELETED",
            "value": "DELETED",
            "documentation": ""
          }
        ]
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#LicenseServerHealthStatus": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "HEALTHY",
            "value": "HEALTHY",
            "documentation": ""
          },
          {
            "name": "UNHEALTHY",
            "value": "UNHEALTHY",
            "documentation": ""
          },
          {
            "name": "NOT_APPLICABLE",
            "value": "NOT_APPLICABLE",
            "documentation": ""
          }
        ]
      }
    },
     "com.amazonaws.licensemanagerusersubscriptions#LicenseServerList": {
      "type": "list",
      "member": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServer"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#LicenseServerSettings": {
          "type": "structure",
          "members": {
            "ServerType": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerType",
              "traits": {
                "smithy.api#documentation": "<p>The type of license server.</p>",
                "smithy.api#required": {}
              }
            },
            "ServerSettings": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServerSettings",
              "traits": {
                "smithy.api#documentation": "<p>The <code>ServerSettings</code> resource contains the settings
for
 your \n\t\t\tserver.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The settings to configure your license server.</p>"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProviders": {
          "type": "operation",
          "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {

            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
```

```
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Lists the Active Directory identity providers for user-based
subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/ListIdentityProviders"
            },
            "smithy.api#paginated": {
                "inputToken": "NextToken",
                "outputToken": "NextToken",
                "pageSize": "MaxResults",
                "items": "IdentityProviderSummaries"
            }
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersRequest": {
        "type": "structure",
        "members": {
            "MaxResults": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
                "traits": {
                    "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
                }
            },
            "Filters": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
                "traits": {
                    "smithy.api#documentation": "<p>You can use
 the following filters to streamline results:</p>\n        <ul>\n            <li>\n                <p>Product</p>\n            </li>\n
        <li>\n                <p>DirectoryId</p>\n            </li>\n        </ul>"
                }
            },
            "NextToken": {
                "target": "smithy.api#String",
                "traits": {
```

```
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken \n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListIdentityProvidersResponse": {
          "type": "structure",
          "members": {
            "IdentityProviderSummaries": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummaryList",

              "traits": {
                "smithy.api#documentation": "<p>An array of <code>IdentityProviderSummary</code> resources that contain \n\t\t\tdetails about the Active Directory identity providers that meet the request criteria.</p>",
                "smithy.api#required": {}
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListInstances": {
          "type": "operation",
           "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest"
          },
          "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse"
          },
          "errors": [
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },

      {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists the EC2 instances providing user-based subscriptions.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/instance/ListInstances"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "InstanceSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesRequest": {
         "type": "structure",
         "members":
 {
            "MaxResults": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                  "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
               }
            },
            "NextToken": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
```

```
\n\tfrom a previously truncated response.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {
              "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n          <li>\n            <p>Status</p>\n          </li>\n
        <li>\n            <p>InstanceId</p>\n          </li>\n        </ul>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListInstancesResponse": {
        "type": "structure",
        "members": {
          "InstanceSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>An array of <code>InstanceSummary</code> resources that
contain details \n\t\t\tabout the instances that provide user-based subscriptions and also meet the \n\t\t\trequest
criteria.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next
 token used for paginated responses. When this field isn't empty, \n\tthere are additional elements that the service
hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpoints": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse"
        },
```

```
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>List the Remote Desktop Services (RDS) License Server endpoints
</p>",
          "smithy.api#http": {
            "code": 200,
            "method": "POST",
            "uri": "/license-server/ListLicenseServerEndpoints"
          },

        "smithy.api#paginated": {
            "inputToken": "NextToken",
            "outputToken": "NextToken",
            "pageSize": "MaxResults",
            "items": "LicenseServerEndpoints"
          }
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsRequest": {
        "type": "structure",
        "members": {
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>",
              "smithy.api#range": {
                "min": 1,
                "max": 100
```

```
                }
              }
            },
            "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {
                "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n            <li>\n                <p>IdentityProviderArn</p>\n            </li>\n        </ul>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#input": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListLicenseServerEndpointsResponse": {
          "type": "structure",
          "members": {
            "LicenseServerEndpoints": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#LicenseServerEndpointList",
              "traits": {
                "smithy.api#documentation": "<p>An array of <code>LicenseServerEndpoint</code> resources that
\n\t\t\tcontain detailed information about the RDS License Servers that meet \n\t\t\tthe request criteria.</p>"
              }
            },
            "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
              }
            }
          },
          "traits": {
            "smithy.api#output": {}
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptions": {
          "type":
```

```
 "operation",
        "input": {
           "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest"
        },
        "output": {
           "target": "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse"
        },
        "errors": [
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
           },
           {
              "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
           }
        ],
        "traits": {
           "smithy.api#documentation": "<p>Lists the user-based subscription products available from an identity
provider.</p>",
           "smithy.api#http": {
              "code": 200,
              "method": "POST",
              "uri": "/user/ListProductSubscriptions"
           },
           "smithy.api#paginated": {
              "inputToken": "NextToken",
              "outputToken": "NextToken",
              "pageSize": "MaxResults",
              "items": "ProductUserSummaries"
           }
        }
     },
     "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsRequest":
```

```
{
        "type": "structure",
        "members": {
           "Product": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
              }
           },
           "IdentityProvider": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
              "traits": {
                 "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                 "smithy.api#required": {}
              }
           },
           "MaxResults": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
               "traits": {
                 "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
              }
           },
           "Filters": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
              "traits": {
                 "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n
<ul>\n           <li>\n              <p>Status</p>\n           </li>\n           <li>\n              <p>Username</p>\n
</li>\n           <li>\n              <p>Domain</p>\n           </li>\n        </ul>"
              }
           },
           "NextToken": {
              "target": "smithy.api#String",
              "traits": {
                 "smithy.api#documentation": "<p>A token to specify where to start paginating.
 This is the nextToken \n\tfrom a previously truncated response.</p>"
              }
           }
        },
        "traits": {
           "smithy.api#input": {}
        }
     },
     "com.amazonaws.licensemanagerusersubscriptions#ListProductSubscriptionsResponse": {
        "type": "structure",
```

```
        "members": {
          "ProductUserSummaries": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list product subscriptions
operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service
 hasn't included in this request. Use this token \n\t\twith the next request to retrieve additional objects.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResource": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target":
 "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
          "smithy.api#documentation": "<p>Returns the list of tags for the specified resource.</p>",
          "smithy.api#http": {
            "method": "GET",
            "uri": "/tags/{ResourceArn}"
          },
          "smithy.api#readonly": {}
```

```
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceRequest": {
        "type": "structure",
        "members": {
          "ResourceArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource whose tags
you want to retrieve.</p>",
              "smithy.api#httpLabel": {},
              "smithy.api#required": {}

          }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListTagsForResourceResponse": {
        "type": "structure",
        "members": {
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags for the specified resource.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociations": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest"
        },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
```

```
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
               "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
             }
         ],
         "traits": {
            "smithy.api#documentation": "<p>Lists user associations for an identity provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/ListUserAssociations"
            },
            "smithy.api#paginated": {
               "inputToken": "NextToken",
               "outputToken": "NextToken",
               "pageSize": "MaxResults",
               "items": "InstanceUserSummaries"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsRequest": {
         "type": "structure",
         "members": {
            "InstanceId": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The ID of the EC2 instance, which
provides user-based subscriptions.</p>",
                  "smithy.api#required": {}
               }
            },
            "IdentityProvider": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
                  "smithy.api#required": {}
```

```
            }
          },
          "MaxResults": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#BoxInteger",
            "traits": {
              "smithy.api#documentation": "<p>The maximum number of results to return from a single
request.</p>"
            }
          },
          "Filters": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#FilterList",
            "traits": {

      "smithy.api#documentation": "<p>You can use the following filters to streamline results:</p>\n        <ul>\n
   <li>\n            <p>Status</p>\n          </li>\n          <li>\n            <p>Username</p>\n          </li>\n
<li>\n            <p>Domain</p>\n          </li>\n        </ul>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>A token to specify where to start paginating. This is the nextToken
\n\tfrom a previously truncated response.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ListUserAssociationsResponse": {
        "type": "structure",
        "members": {
          "InstanceUserSummaries": {

           "target": "com.amazonaws.licensemanagerusersubscriptions#InstanceUserSummaryList",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the list user association operation.</p>"
            }
          },
          "NextToken": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The next token used for paginated responses. When this field isn't
empty, \n\tthere are additional elements that the service hasn't included in this request. Use this token \n\t\twith the
next request to retrieve additional objects.</p>"
            }
          }
```

```
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary": {
        "type": "structure",
        "members": {
          "Username":
{
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider for this product
user.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
           "Status": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status of a product for this user.</p>",
              "smithy.api#required": {}
            }
          },
          "ProductUserArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) for this product user.</p>"
            }
          },
          "StatusMessage": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The status message for a product for this user.</p>"
```

```
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {

          "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user information for the product subscription.</p>"
            }
          },
          "SubscriptionStartDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The start date of a subscription.</p>"
            }
          },
          "SubscriptionEndDate": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The end date of a subscription.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>A summary of the user-based subscription products for a specific user.</p>"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummaryList": {
        "type":
 "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings": {
        "type": "structure",
        "members": {
          "RdsSalCredentialsProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#CredentialsProvider",
            "traits": {
              "smithy.api#documentation": "<p>The <code>CredentialsProvider</code> resource contains a reference to \n\t\t\tthe credentials provider that's used for RDS license server user administration.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
```

```
            "smithy.api#documentation": "<p>Server settings that are specific to a Remote Desktop Services (RDS)
license server.</p>"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProvider":
{
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target":
"com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Registers an identity provider for user-based subscriptions.</p>",
            "smithy.api#http": {
                "code": 200,
                "method": "POST",
                "uri": "/identity-provider/RegisterIdentityProvider"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderRequest": {
```

```
        "type": "structure",
        "members": {
          "IdentityProvider": {

    "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider to
register.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>",
              "smithy.api#required": {}
            }
          },
          "Settings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Settings",
            "traits":
 {
              "smithy.api#documentation": "<p>The registered identity providers product related configuration
\n\t\t\tsettings such as the subnets to provision VPC endpoints.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the identity provider's registration.</p>"
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#RegisterIdentityProviderResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#documentation":
```

```
"<p>Metadata that describes the results of an identity provider operation.</p>",
                    "smithy.api#required": {}
                }
            }
        },
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ResourceArn": {
        "type": "string",
        "traits": {
            "smithy.api#pattern": "^arn:([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-\\.]{1,63}):([a-z0-9-
\\.]{1,63}):([a-z0-9-\\.]{1,510})/([a-z0-9-\\.]{1,510})$"
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException": {
        "type": "structure",
        "members": {
            "message": {
                "target": "smithy.api#String"
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>The resource couldn't be found.</p>",

    "smithy.api#error": "client",
            "smithy.api#httpError": 404
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#SecretsManagerCredentialsProvider": {
        "type": "structure",
        "members": {
            "SecretId": {
                "target": "smithy.api#String",
                "traits": {
                    "smithy.api#documentation": "<p>The ID of the Secrets Manager secret that contains
credentials.</p>",
                    "smithy.api#length": {
                        "min": 1
                    }
                }
            }
        },
        "traits": {
            "smithy.api#documentation": "<p>Contains a credentials secret that's stored in Secrets Manager.</p>"
        }
    },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup": {
      "type": "string",
      "traits": {
        "smithy.api#length": {

         "min": 5,
          "max": 200
        },
        "smithy.api#pattern": "^sg-(([0-9a-z]{8})|([0-9a-z]{17}))$"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerEndpoint": {
      "type": "structure",
      "members": {
        "Endpoint": {
          "target": "smithy.api#String",
          "traits": {
            "smithy.api#documentation": "<p>The network address of the endpoint.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A network endpoint through which you can access one or more
servers.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerSettings": {
      "type": "union",
      "members": {
        "RdsSalSettings": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#RdsSalSettings",
           "traits": {
            "smithy.api#documentation": "<p>The <code>RdsSalSettings</code> resource contains settings to
configure \n\t\t\ta specific Remote Desktop Services (RDS) license server.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Contains settings for a specific server.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ServerType": {
      "type": "string",
      "traits": {
        "smithy.api#enum": [
          {
            "name": "RDS_SAL",
            "value": "RDS_SAL",
```

```
                "documentation": ""
              }
            ]
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException": {
          "type": "structure",
          "members": {
            "message": {

  "target": "smithy.api#String"
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The request failed because a service quota is exceeded.</p>",
            "smithy.api#error": "client"
          }
        },
        "com.amazonaws.licensemanagerusersubscriptions#Settings": {
          "type": "structure",
          "members": {
            "Subnets": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
              "traits": {
                "smithy.api#documentation": "<p>The subnets defined for the registered identity provider.</p>",
                "smithy.api#length": {
                  "min": 1
                },
                "smithy.api#required": {}
              }
            },
            "SecurityGroupId": {
              "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",

             "traits": {
                "smithy.api#documentation": "<p>A security group ID that allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoint for activation servers.</p>",
                "smithy.api#required": {}
              }
            }
          },
          "traits": {
            "smithy.api#documentation": "<p>The registered identity providers product related configuration settings such as the\n\t\t\tsubnets to provision VPC endpoints, and the security group ID that is associated with the VPC\n\t\t\tendpoints. The security group should permit inbound TCP port 1688 communication from resources\n\t\t\tin the VPC.</p>"
          }
        },
```

```
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscription": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
        },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

      },
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Starts a product subscription for a user with the specified identity provider.</p>\n      <note>\n        <p>Your estimated bill for charges on the number of users and related costs will take 48\n\t\t\thours to appear for billing periods that haven't closed (marked as <b>Pending</b> billing status) in Amazon Web Services Billing. For more information, see <a href=\"https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/invoice.html\">Viewing your\n\t\t\t\tmonthly charges</a> in the <i>Amazon Web Services Billing User Guide</i>.</p>\n      </note>",
        "smithy.api#http": {
          "code": 200,
          "method": "POST",
          "uri": "/user/StartProductSubscription"
        }

    }
    },
    "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionRequest": {
```

```
        "type": "structure",
        "members": {
          "Username": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The user name from the identity provider of the user.</p>",
              "smithy.api#required": {}
            }
          },
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
            "traits": {
              "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>",
              "smithy.api#required": {}
            }
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {

 "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n         <p>Valid values:
<code>VISUAL_STUDIO_ENTERPRISE</code> | <code>VISUAL_STUDIO_PROFESSIONAL</code> |
<code>OFFICE_PROFESSIONAL_PLUS</code> | \n<code>REMOTE_DESKTOP_SERVICES</code>\n
</p>",
              "smithy.api#required": {}
            }
          },
          "Domain": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to start the product \n\t\t\tsubscription.</p>"
            }
          },
          "Tags": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation": "<p>The tags that apply to the product subscription.</p>"
            }

 }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StartProductSubscriptionResponse": {
        "type": "structure",
```

```
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscription": {
        "type": "operation",
        "input": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest"

    },
        "output": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse"
        },
        "errors": [
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ConflictException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ServiceQuotaExceededException"
          },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"

    },
          {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
          }
        ],
        "traits": {
```

```
            "smithy.api#documentation": "<p>Stops a product subscription for a user with the specified identity
provider.</p>",
            "smithy.api#http": {
               "code": 200,
               "method": "POST",
               "uri": "/user/StopProductSubscription"
            }
         }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionRequest": {
         "type": "structure",
         "members": {
            "Username": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The user name from the identity provider for the user.</p>"
               }
            },
            "IdentityProvider": {
               "target":
 "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider",
               "traits": {
                  "smithy.api#documentation": "<p>An object that specifies details for the identity provider.</p>"
               }
            },
            "Product": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n         </p>"
               }
            },
            "ProductUserArn": {
               "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
               "traits": {
                  "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the product user.</p>"

               }
            },
            "Domain": {
               "target": "smithy.api#String",
               "traits": {
                  "smithy.api#documentation": "<p>The domain name of the  Active Directory that contains the user
for whom to stop the product \n\t\t\tsubscription.</p>"
               }
            }
```

```
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StopProductSubscriptionResponse": {
        "type": "structure",
        "members": {
          "ProductUserSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#ProductUserSummary",
            "traits": {
              "smithy.api#documentation": "<p>Metadata that describes the start product subscription
operation.</p>",
              "smithy.api#required": {}
            }

  }
        },
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#StringList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnet": {
        "type": "string",
        "traits": {
          "smithy.api#pattern": "^subnet-[a-z0-9]{8,17}"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Subnets": {
        "type": "list",
        "member": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnet"
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagKeyList": {
        "type": "list",
        "member": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
```

```
 "min": 0,
                "max": 50
            },
            "smithy.api#sensitive": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResource": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest"
        },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation":
 "<p>Adds tags to a resource.</p>",
            "smithy.api#http": {
                "method": "PUT",
                "uri": "/tags/{ResourceArn}"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#TagResourceRequest": {
        "type": "structure",
        "members": {
            "ResourceArn": {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
                "traits": {
                    "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to tag.</p>",
                    "smithy.api#httpLabel": {},
                    "smithy.api#required": {}
                }
            },
            "Tags": {
```

```
            "target": "com.amazonaws.licensemanagerusersubscriptions#Tags",
            "traits": {
              "smithy.api#documentation":
"<p>The tags to apply to the specified resource.</p>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#TagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
          "smithy.api#output": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#Tags": {
        "type": "map",
        "key": {
          "target": "smithy.api#String"
        },
        "value": {
          "target": "smithy.api#String"
        },
        "traits": {
          "smithy.api#length": {
            "min": 0,
            "max": 50
          },
          "smithy.api#sensitive": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException":
{
        "type": "structure",
        "members": {
          "message": {
            "target": "smithy.api#String"
          }
        },
        "traits": {
          "smithy.api#documentation": "<p>The request was denied because of request throttling. Retry the
request.</p>",
          "smithy.api#error": "client"
        }
```

```
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResource": {
      "type": "operation",
      "input": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest"
      },
      "output": {
        "target": "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse"
      },
      "errors": [
        {
          "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
        },
        {

       "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceNotFoundException"
        }
      ],
      "traits": {
        "smithy.api#documentation": "<p>Removes tags from a resource.</p>",
        "smithy.api#http": {
          "method": "DELETE",
          "uri": "/tags/{ResourceArn}"
        },
        "smithy.api#idempotent": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceRequest": {
      "type": "structure",
      "members": {
        "ResourceArn": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#ResourceArn",
          "traits": {
            "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the resource that you want
to remove tags from.</p>",
            "smithy.api#httpLabel": {},
            "smithy.api#required": {}

      }
        },
        "TagKeys": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#TagKeyList",
          "traits": {
            "smithy.api#documentation": "<p>The tag keys to remove from the resource.</p>",
            "smithy.api#httpQuery": "tagKeys",
            "smithy.api#required": {}
          }
        }
```

```
        },
        "traits": {
            "smithy.api#input": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UntagResourceResponse": {
        "type": "structure",
        "members": {},
        "traits": {
            "smithy.api#output": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettings": {
        "type": "operation",
        "input": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest"
         },
        "output": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse"
        },
        "errors": [
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#AccessDeniedException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#InternalServerException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ThrottlingException"
            },
            {
                "target": "com.amazonaws.licensemanagerusersubscriptions#ValidationException"
            }
        ],
        "traits": {
            "smithy.api#documentation": "<p>Updates additional product configuration settings for the registered
identity\n\t\t\tprovider.</p>",
            "smithy.api#http": {

     "code": 200,
                "method": "POST",
                "uri": "/identity-provider/UpdateIdentityProviderSettings"
            },
            "smithy.api#idempotent": {}
        }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsRequest": {
        "type": "structure",
```

```
        "members": {
          "IdentityProvider": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProvider"
          },
          "Product": {
            "target": "smithy.api#String",
            "traits": {
              "smithy.api#documentation": "<p>The name of the user-based subscription product.</p>\n
<p>Valid values: <code>VISUAL_STUDIO_ENTERPRISE</code> |
<code>VISUAL_STUDIO_PROFESSIONAL</code> | <code>OFFICE_PROFESSIONAL_PLUS</code> |
\n<code>REMOTE_DESKTOP_SERVICES</code>\n        </p>"
            }
          },

          "IdentityProviderArn": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#Arn",
            "traits": {
              "smithy.api#documentation": "<p>The Amazon Resource Name (ARN) of the identity provider to
update.</p>"
            }
          },
          "UpdateSettings": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings",
            "traits": {
              "smithy.api#documentation": "<p>Updates the registered identity providers product related
configuration settings. You can\n\t\t\tupdate any combination of settings in a single operation such as the:</p>\n
<ul>\n          <li>\n            <p>Subnets which you want to add to provision VPC endpoints.</p>\n          </li>\n
      <li>\n            <p>Subnets which you want to remove the VPC endpoints from.</p>\n          </li>\n
<li>\n            <p>Security
 group ID which permits traffic to the VPC endpoints.</p>\n          </li>\n        </ul>",
              "smithy.api#required": {}
            }
          }
        },
        "traits": {
          "smithy.api#input": {}
        }
      },
      "com.amazonaws.licensemanagerusersubscriptions#UpdateIdentityProviderSettingsResponse": {
        "type": "structure",
        "members": {
          "IdentityProviderSummary": {
            "target": "com.amazonaws.licensemanagerusersubscriptions#IdentityProviderSummary",
            "traits": {
              "smithy.api#required": {}
            }
          }
        },
```

```
      "traits": {
        "smithy.api#output": {}
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#UpdateSettings": {
      "type": "structure",
      "members": {
        "AddSubnets": {

       "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets in which License Manager will
create a VPC endpoint for products that\n\t\t\trequire connectivity to activation servers.</p>",
            "smithy.api#required": {}
          }
        },
        "RemoveSubnets": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#Subnets",
          "traits": {
            "smithy.api#documentation": "<p>The ID of one or more subnets to remove.</p>",
            "smithy.api#required": {}
          }
        },
        "SecurityGroupId": {
          "target": "com.amazonaws.licensemanagerusersubscriptions#SecurityGroup",
          "traits": {
            "smithy.api#documentation": "<p>A security group ID that
 allows inbound TCP port 1688 communication between resources in\n\t\t\tyour VPC and the VPC endpoints for
activation servers.</p>"
          }
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>Updates the registered identity providers product related configuration
settings such as\n\t\t\tthe subnets to provision VPC endpoints.</p>"
      }
    },
    "com.amazonaws.licensemanagerusersubscriptions#ValidationException": {
      "type": "structure",
      "members": {
        "message": {
          "target": "smithy.api#String"
        }
      },
      "traits": {
        "smithy.api#documentation": "<p>A parameter is not valid.</p>",
        "smithy.api#error": "client"
      }
```

```
      }
   }
}
// Code generated by smithy-go-codegen DO NOT EDIT.

package licensemanager

import (
 "context"
 "fmt"
 awsmiddleware "github.com/aws/aws-sdk-go-v2/aws/middleware"
 "github.com/aws/smithy-go/middleware"
 smithyhttp "github.com/aws/smithy-go/transport/http"
)

// Checks in the specified license. Check in a license when it is no longer in use.
func (c *Client) CheckInLicense(ctx context.Context, params *CheckInLicenseInput, optFns ...func(*Options))
(*CheckInLicenseOutput, error) {
 if params == nil {
  params = &CheckInLicenseInput{}
 }

 result, metadata, err := c.invokeOperation(ctx, "CheckInLicense", params, optFns,
c.addOperationCheckInLicenseMiddlewares)
 if err != nil {
  return nil, err
 }

 out := result.(*CheckInLicenseOutput)
 out.ResultMetadata = metadata
 return out, nil
}

type CheckInLicenseInput struct {

 // License consumption token.
 //
 // This member is required.
 LicenseConsumptionToken *string

 // License beneficiary.
 Beneficiary *string

 noSmithyDocumentSerde
}

type
```

```
 CheckInLicenseOutput struct {
 // Metadata pertaining to the operation's result.
 ResultMetadata middleware.Metadata

 noSmithyDocumentSerde
}

func (c *Client) addOperationCheckInLicenseMiddlewares(stack *middleware.Stack, options Options) (err error) {
 if err := stack.Serialize.Add(&setOperationInputMiddleware{}, middleware.After); err != nil {
  return err
 }
 err = stack.Serialize.Add(&awsAwsjson11_serializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 err = stack.Deserialize.Add(&awsAwsjson11_deserializeOpCheckInLicense{}, middleware.After)
 if err != nil {
  return err
 }
 if err := addProtocolFinalizerMiddlewares(stack, options, "CheckInLicense"); err != nil {
  return fmt.Errorf("add protocol finalizers: %v", err)
 }

 if err = addlegacyEndpointContextSetter(stack, options); err != nil {
  return err
 }
 if err = addSetLoggerMiddleware(stack, options); err != nil {
  return err
 }
 if err = addClientRequestID(stack); err != nil {
  return err
 }
 if
 err = addComputeContentLength(stack); err != nil {
  return err
 }
 if err = addResolveEndpointMiddleware(stack, options); err != nil {
  return err
 }
 if err = addComputePayloadSHA256(stack); err != nil {
  return err
 }
 if err = addRetry(stack, options); err != nil {
  return err
 }
 if err = addRawResponseToMetadata(stack); err != nil {
  return err
 }
```

```
 if err = addRecordResponseTiming(stack); err != nil {
  return err
 }
 if err = addSpanRetryLoop(stack, options); err != nil {
  return err
 }
 if err = addClientUserAgent(stack, options); err != nil {
  return err
 }
 if err = smithyhttp.AddErrorCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = smithyhttp.AddCloseResponseBodyMiddleware(stack); err != nil {
  return err
 }
 if err = addSetLegacyContextSigningOptionsMiddleware(stack); err != nil {
  return err
 }
 if err = addTimeOffsetBuild(stack, c); err != nil {
  return err
 }
 if err = addUserAgentRetryMode(stack, options); err != nil {
  return err
 }
 if
 err = addCredentialSource(stack, options); err != nil {
  return err
 }
 if err = addOpCheckInLicenseValidationMiddleware(stack); err != nil {
  return err
 }
 if err = stack.Initialize.Add(newServiceMetadataMiddleware_opCheckInLicense(options.Region),
middleware.Before); err != nil {
  return err
 }
 if err = addRecursionDetection(stack); err != nil {
  return err
 }
 if err = addRequestIDRetrieverMiddleware(stack); err != nil {
  return err
 }
 if err = addResponseErrorMiddleware(stack); err != nil {
  return err
 }
 if err = addRequestResponseLogging(stack, options); err != nil {
  return err
 }
 if err = addDisableHTTPSMiddleware(stack, options); err != nil {
```

```
 return err
}
if err = addInterceptBeforeRetryLoop(stack, options); err != nil {
 return err
}
if err = addInterceptAttempt(stack, options); err != nil {
 return err
}
if err = addInterceptExecution(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSerialization(stack, options); err !=
nil {
 return err
}
if err = addInterceptAfterSerialization(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeSigning(stack, options); err != nil {
 return err
}
if err = addInterceptAfterSigning(stack, options); err != nil {
 return err
}
if err = addInterceptTransmit(stack, options); err != nil {
 return err
}
if err = addInterceptBeforeDeserialization(stack, options); err != nil {
 return err
}
if err = addInterceptAfterDeserialization(stack, options); err != nil {
 return err
}
if err = addSpanInitializeStart(stack); err != nil {
 return err
}
if err = addSpanInitializeEnd(stack); err != nil {
 return err
}
if err = addSpanBuildRequestStart(stack); err != nil {
 return err
}
if err = addSpanBuildRequestEnd(stack); err != nil {
 return err
}
return nil
}
```

```
func newServiceMetadataMiddleware_opCheckInLicense(region string) *awsmiddleware.RegisterServiceMetadata
{
 return &awsmiddleware.RegisterServiceMetadata{
  Region:       region,
  ServiceID:
     ServiceID,
  OperationName: "CheckInLicense",
 }
}
CreateLicense
 Initialize stack step
  spanInitializeStart
  InterceptExecution
  RegisterServiceMetadata
  legacyEndpointContextSetter
  SetLogger
  OperationInputValidation
  spanInitializeEnd
 Serialize stack step
  spanBuildRequestStart
  setOperationInput
  ResolveEndpoint
  InterceptBeforeSerialization
  OperationSerializer
  InterceptAfterSerialization
 Build stack step
  ClientRequestID
  ComputeContentLength
  SetCredentialSourceMiddleware
  UserAgent
  AddTimeOffsetMiddleware
  RecursionDetection
  spanBuildRequestEnd
 Finalize stack step
  spanRetryLoop
  InterceptBeforeRetryLoop
  Retry
  InterceptAttempt
  RetryMetricsHeader
  ResolveAuthScheme
  GetIdentity
  ResolveEndpointV2
  disableHTTPS
  ComputePayloadHash
  setLegacyContextSigningOptions
  InterceptBeforeSigning
  Signing
  InterceptAfterSigning
```

Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their

Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf

of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
AssociateLicense
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
OperationInputValidation
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization
OperationSerializer
InterceptAfterSerialization
Build stack step

ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit
ListLicenses
Initialize stack step
spanInitializeStart
InterceptExecution
RegisterServiceMetadata
legacyEndpointContextSetter
SetLogger
spanInitializeEnd
Serialize stack step
spanBuildRequestStart
setOperationInput
ResolveEndpoint
InterceptBeforeSerialization

OperationSerializer
InterceptAfterSerialization
Build stack step
ClientRequestID
ComputeContentLength
SetCredentialSourceMiddleware
UserAgent
AddTimeOffsetMiddleware
RecursionDetection
spanBuildRequestEnd
Finalize stack step
spanRetryLoop
InterceptBeforeRetryLoop
Retry
InterceptAttempt
RetryMetricsHeader
ResolveAuthScheme
GetIdentity
ResolveEndpointV2
disableHTTPS
ComputePayloadHash
setLegacyContextSigningOptions
InterceptBeforeSigning
Signing
InterceptAfterSigning
Deserialize stack step
AddRawResponseToMetadata
ErrorCloseResponseBody
CloseResponseBody
ResponseErrorWrapper
RequestIDRetriever
InterceptAfterDeserialization
OperationDeserializer
InterceptBeforeDeserialization
AddTimeOffsetMiddleware
RecordResponseTiming
RequestResponseLogger
InterceptTransmit

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries.To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

©2025 Cisco Systems, Inc. All rights reserved.